

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250284188

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

SATO; Kiyomi et al.

PROJECTOR

Abstract

A projector according to an embodiment of the present disclosure includes a first light source including a first light emitting device configured to emit first light having a first wavelength band, a first electrically conducting line configured to supply the first light emitting device with electric power, and a base configured to support the first light emitting device and the first electrically conducting line; a first light guide having a first light incident end on which the first light output from the first light source is incident and a first light exiting end via which the first light exits, the first light guide configured to homogenize in-plane illuminance of the first light; a first parallelizing element configured to parallelize the first light output from the first light guide; a first light modulator configured to modulate the first light output from the first parallelizing element based on image information; and a projection system configured to project the light modulated by the first light modulator. The first light guide is disposed away from the first electrically conducting line, and a first distance between the first light incident end of the first light guide and the first light source is smaller than or equal to 0.7 mm.

Inventors: SATO; Kiyomi (MATSUMOTO-SHI, JP), SOWA; Takeshi (MATSUMOTO-SHI, JP)

Applicant: SEIKO EPSON CORPORATION (Tokyo, JP)

Family ID: 96948869

Appl. No.: 19/076067

Filed: March 11, 2025

Foreign Application Priority Data

JP	2024-037568	Mar. 11, 2024
----	-------------	---------------

Publication Classification

Int. Cl.: G03B21/20 (20060101); G03B21/28 (20060101)

U.S. Cl.:

CPC G03B21/208 (20130101); G03B21/2013 (20130101); G03B21/28 (20130101);

Background/Summary

[0001] The present application is based on, and claims priority from JP Application Serial Number 2024-037568, filed Mar. 11, 2024, the disclosure of which is hereby incorporated by reference herein in its entirety.

BACKGROUND

1. Technical Field

[0002] The present disclosure relates to a projector.

2. Related Art

[0003] There is a known projector including a light source that outputs color light, a light modulation apparatus that modulates the color light output from the light source in accordance with image information to generate image light, and a projection system that enlarges the image light output from the light modulation apparatus and projects the enlarged image light onto a projection receiving surface such as a screen. The projector includes a light source apparatus including, for example, a blue light source that outputs blue light, an excitation light source that is provided separately from the blue light source and outputs blue light, and a phosphor that is excited by the blue light output from the excitation light source to emit yellow light. In the thus configured projector, white light containing the blue light and the yellow light is output from the light source apparatus, and the multiple types of color light contained in the white light are converted into multiple types of image light by a common light modulation apparatus or light modulation apparatuses disposed on a color light basis.

[0004] For example, JP-A-10-361256 discloses a projector using multiple light emitting diodes (LEDs) as light emitting devices in light sources. In a projector disclosed in JP-A-10-361256, multiple types of color light emitted from the LEDs pass through blocks, are then superimposed on a path extending in one direction, modulated by a light modulator, and enlarged and projected by a projection lens. The blocks each have a parabolic side surface, and cause the angular distribution of the color light that exits via the light exiting end surface of the block to fall within a range from 0° to 90°. The multiple types of color light output from the multiple blocks enter a dichroic prism disposed to superimpose the multiple types of light from the multiple LEDs on one another.

[0005] JP-A-10-361256 is an example of the related art.

[0006] In general, a light emitting device such as an LED is mounted on a support member such as a substrate, and is coupled by wire bonding to an electrode such as a lead frame or a pad formed at the support member separately from the light emitting device. In the technology disclosed in JP-A-10-361256, in which the light sources and the blocks are in intimate contact with each other, so that the wires that couple the light emitting device to the electrode in any of the light sources as described above are in direct contact with the block, conceivably resulting in a short circuit or disconnection of the wires. It is conceivable in this case to address the problem by employing a configuration in which the light sources and the blocks are arranged separately from each other. However, depending on the distance between the light sources and the blocks, the efficiency at which the multiple types of light output from the light sources are introduced into the blocks decreases, possibly resulting in insufficient efficiency at which the light is used in the projector. That is, it is required to provide a projector capable of preventing disconnection of wires that

couple a light emitting device in a light source to an electrode or a short circuit in the light source while suppressing a decrease in light use efficiency.

SUMMARY

[0007] A projector according to an aspect of the present disclosure includes a first light source including a first light emitting device configured to emit first light having a first wavelength band, a first electrically conducting line configured to supply the first light emitting device with electric power, and a base configured to support the first light emitting device and the first electrically conducting line; a first light guide having a first light incident end on which the first light output from the first light source is incident and a first light exiting end via which the first light exits, the first light guide configured to homogenize in-plane illuminance of the first light; a first parallelizing element configured to parallelize the first light output from the first light guide; a first light modulator configured to modulate the first light output from the first parallelizing element based on image information; and a projection system configured to project the light modulated by the first light modulator. The first light guide is disposed away from the first electrically conducting line, and a first distance between the first light incident end of the first light guide and the first light source is smaller than or equal to 0.7 mm.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. 1 is a schematic diagram showing the configuration of a projector according to an embodiment.

[0009] FIG. 2 is a side view of a blue light outputting section of the projector shown in FIG. 1.

[0010] FIG. 3 is a plan view of the blue light outputting section of the projector shown in FIG. 1.

[0011] FIG. 4 is a side view of a green light outputting section of the projector shown in FIG. 1.

[0012] FIG. 5 is a side view of a red light outputting section of the projector shown in FIG. 1.

[0013] FIG. 6 is a side view of a blue light outputting section in a first variation of the projector shown in FIG. 1.

[0014] FIG. 7 is another side view of the blue light outputting section in the first variation of the projector shown in FIG. 1.

[0015] FIG. 8 is a side view of a green light outputting section in a second variation of the projector shown in FIG. 1.

[0016] FIG. 9 is a plan view of the green light outputting section in the second variation of the projector shown in FIG. 1.

[0017] FIG. 10 is a side view of a blue light outputting section in a third variation of the projector shown in FIG. 1.

[0018] FIG. 11 is a side view of a blue light outputting section in a fourth variation of the projector shown in FIG. 1.

[0019] FIG. 12 is a plan view of the blue light outputting section in the fourth variation of the projector shown in FIG. 1.

[0020] FIG. 13 is a side view of a blue light outputting section in a fifth variation of the projector shown in FIG. 1.

DESCRIPTION OF EMBODIMENTS

[0021] An embodiment of the present disclosure will be described below with reference to the drawings. In the drawings, elements are drawn at different dimensional scales in some cases for clarity of each of the elements.

[0022] The embodiment of the present disclosure will first be described with reference to FIGS. 1 to 5. FIG. 1 is a schematic view showing the configuration of a projector 301 according to the embodiment of the present disclosure. The projector 301 is an image display apparatus including

three liquid crystal panels as a light modulating apparatus, and is what is called a three-plate projector. The projector **301** includes a blue light outputting section **101**, a green light outputting section **102**, a red light outputting section **103**, light-incident-side polarizers **171**, **172**, and **173**, light modulators **181**, **182**, and **183**, light-exiting-side polarizers **175**, **176**, and **177**, a light combiner **200**, and a projection system **250**, as shown in FIG. 1.

[0023] The blue light outputting section **101** outputs blue light LB. In the following description, an axis parallel to the optical axis of the blue light LB output from the blue light outputting section **101** is referred to as a D1 direction. One side in the D1 direction is referred to as a -D1 side, and the side opposite from the -D1 side in the D1 direction is referred to as a +D1 side. The direction perpendicular to the D1 direction in a plane containing the optical axis of the blue light LB is referred to as a D2 direction. One side in the D2 direction is referred to as a -D2 side, and the side opposite from the -D2 side in the D2 direction is referred to as a +D2 side. The direction perpendicular to the D1 and D2 directions is referred to as a D3 direction. The blue light LB output from the blue light outputting section **101** travels toward the +D1 side along the D1 direction.

[0024] The blue light outputting section **101** includes a light source **401**, a light guide **141**, and a parallelizing element **161**. The light source **401** corresponds to a first light source. A light emitting device **121** of the light source **401** is supported by a substrate **111**. The light emitting device **121** is provided at the +D1-side plate surface of the substrate **111** out of the plate surfaces of the substrate **111** that are parallel to a plane containing the D2 and D3 directions. The substrate **111** corresponds to a base. The light emission surface of the light emitting device **121** is located substantially in parallel to the plane containing the D2 and D3 directions, and is a surface opposite in the D1 direction from the surface of the light emitting device **121** that faces the +D1-side plate surface of the substrate **111**. The light emitting device **121** corresponds to a first light emitting device, and outputs the blue light LB having a blue wavelength band in a visible wavelength band. The blue wavelength band corresponds to a first wavelength band. The blue light LB corresponds to first light. The blue light LB exits via the light emission surface of the light emitting device **121** toward the +D1 side while diverging in accordance with a predetermined radiation angle around the axis passing through the center of the light emission surface of the light emitting device **121** and parallel to the D1 direction. The blue wavelength band is, for example, a wavelength band ranging from 420 nm to 500 nm.

[0025] The light emitting device **121** is configured, for example, with an LED that emits the blue light LB. Note that the light emitting device **121** may be configured with one LED or multiple LEDs in their entirety. When the light emitting device **121** is configured with multiple LEDs, the multiple LEDs are arranged in the region occupied by the light emitting device **121** in a plane containing the D2 and D3 directions.

[0026] The substrate **111** is made, for example, of metal, and also acts as a heat dissipating member that receives heat, for example, from the light emitting device **121** emitting the blue light LB and dissipates the heat to an external space.

[0027] The light guide **141** is provided in the optical path of the blue light LB output from the light source **401**, and is disposed at a position which is shifted toward the +D1 side from the light emitting device **121** of the light source **401** and where the light guide **141** overlaps with the light emitting device **121** in the D2 and D3 directions. The light guide **141** corresponds to a first light guide, and has a light incident end **141a** facing the -D1 side in the D1 direction, a light exiting end **141b** facing the +D1 side in the D1 direction, and side surfaces **141s** and reflection surfaces **141r** extending between the light incident end **141a** and the light exiting end **141b** in the D1 direction.

[0028] The light incident end **141a** corresponds to a first light incident end and spreads in parallel to the plane containing the D2 and D3 directions. The light incident end **141a** viewed in the D1 direction has the same shape as the light emission surface of the light emitting device **121** viewed in the same direction, and has, for example, a quadrangular shape. The size of the light incident end **141a** in a plane containing the D2 and D3 directions may be equal to the size of the light emission

surface of the light emitting device **121** in a plane containing the D2 and D3 directions, but is preferably appropriately greater than the size of the light emission surface of the light emitting device **121** in the plane containing the D2 and D3 directions.

[0029] The light exiting end **141b** corresponds to a first light exiting end, spreads in parallel to the plane containing the D2 and D3 directions, and is larger than the light incident end **141a**. The light exiting end **141b** viewed in the D1 direction has the same shape as the light modulation surface of the light modulator **181** viewed in the same direction, is similar to the modulation surface of the light modulator **181**, and has, for example, a quadrangular shape. The size of the light exiting end **141b** in a plane containing the D2 and D3 directions is equal to the size of the light modulation surface of the light modulator **181** in a plane containing the D2 and D3 directions. The side surfaces **141s** and the reflection surfaces **141r** couple the circumferential edge of the light incident end **141a** to the circumferential edge of the light exiting end **141b** in the D1 direction.

[0030] The blue light LB output from the light source **401** enters the light guide **141** via the light incident end **141a**. In the light guide **141**, the region surrounded by the light incident end **141a**, the light exiting end **141b**, and the reflection surfaces **141r** is a region through which the blue light LB propagates. The size, in planes containing the D2 and D3 directions, of the region surrounded by the light incident end **141a**, the light exiting end **141b**, and the reflection surfaces **141r** increases as the region extends from the $-D1$ side toward the $+D1$ side in the D1 direction. Furthermore, the shape, in the planes containing the D2 and D3 directions, of the region surrounded by the light incident end **141a**, the light exiting end **141b**, and the reflection surfaces **141r** changes from the shape of the light emission surface of the light emitting device **121** to the shape of the light modulation surface of the light modulator **181** when viewed in the D1 direction as the region extends from the $-D1$ side toward the $+D1$ side.

[0031] The side surfaces **141s** of the light guide **141** and the reflection surfaces **141r** provided at the side surfaces **141s** as will be described later incline by a predetermined angle with respect to an imaginary line and the optical axis perpendicular to the light incident end **141a**, and are separate away from the imaginary line in the planes containing the D2 and D3 directions as the light guide **141** extends from the $-D1$ side toward the $+D1$ side. The blue light LB having entered the light guide **141** propagates from the $-D1$ side toward the $+D1$ side in the region surrounded by the light incident end **141a**, the light exiting end **141b**, and the reflection surfaces **141r**.

[0032] When the light modulation surface of the light modulator **181** has a rectangular shape when viewed along the D1 direction, the light emission surface of the light emitting device **121** viewed along the D1 direction is substantially similar to the modulation surface of the light modulator **181**, and has a rectangular shape. In this case, it is preferable that a predetermined angle α of the side surfaces **141s** and the reflection surfaces **141r** containing the short sides of the rectangular shape with respect to the imaginary line and the optical axis described above, that is, the taper angle falls within a range from 7° to 22° . It is preferable that a predetermined angle β of the side surfaces **141s** and the reflection surfaces **141r** containing the long sides of the rectangular shape with respect to the imaginary line and the optical axis described above, that is, the taper angle falls within a range from 14° to 36° . The preferable ranges of the angles α and β have been ascertained by a numerical simulation based on the configuration of the blue light outputting section **101** and ray tracing.

[0033] Part of the blue light LB having entered the light guide **141** propagates directly from the light incident end **141a** to the light exiting end **141b** without being incident on the reflection surfaces **141r** even once along directions that incline by angles smaller than one of the two predetermined angles with respect to the imaginary line and the optical axis described above. The remaining part of the blue light LB having entered the light guide **141** inclines by angles greater than or equal to one of the two predetermined angles with respect to the imaginary line and the optical axis described above, is incident on the reflection surfaces **141r** via the light incident end **141a** once or a greater number of times, is reflected off the reflection surfaces **141r**, and then reaches the light exiting end **141b**. The paths of beams constituting the blue light LB in the region

surrounded by the light incident end **141a**, the light exiting end **141b**, and the reflection surfaces **141r** vary in accordance with the angles of incidence of the beams incident on the light incident end **141a**, and there are multiple paths along which the beams are reflected off the reflection surfaces **141r** by different numbers of times. The illuminance distribution of the blue light LB that propagates through the region surrounded by the light incident end **141a**, the light exiting end **141b**, and the reflection surfaces **141r** is therefore homogenized in the planes containing the D2 and D3 directions. That is, the light guide **141** homogenizes the illuminance distribution of the incident blue light LB in the planes containing the D2 and D3 directions. The blue light LB having the homogenized illuminance distribution exits via the light exiting end **141b** toward the +D1 side. [0034] The light guide **141** is, for example, a reflector made of a transparent material such as optical glass. The reflector is formed as a hollow member having a frame body. When viewed along the D1 direction, the -D1-side end of the frame body of the reflector has the same shape as the light incident end **141a** and the light emission surface of the light emitting device **121**, is larger than the light emission surface of the light emitting device **121**, and is formed, for example, in the shape of a quadrangular frame. The +D1-side end of the frame body of the reflector has the same shape and size as the light exiting end **141b** and the light modulation surface of the light modulator **181**, and is formed, for example, in the shape of a quadrangular frame different in size from the -D1-side end.

[0035] The reflector is configured, for example, with a plate-shaped member made of a transparent material. When the light incident end **141a** and the light exiting end **141b** have quadrangular shapes when viewed in the D1 direction, as described above, the reflector is configured with four plate-shaped members each having a trapezoidal shape. The length of the sides facing the -D1 side that are parallel to the D2 or D3 direction and correspond to the upper bases of the four plate-shaped members is set in accordance with the size of the light incident end **141a** and the light emission surface of the light emitting device **121** in the D2 or D3 direction. The length of the sides facing the +D1 side that are parallel to the D2 or D3 direction and correspond to the lower bases of the four plate-shaped members is set in accordance with the size of the light exiting end **141b** and the light modulation surface of the light modulator **181** in the D2 or D3 direction. Out of the four plate-shaped members, a side corresponding to one leg of one of two adjacent plate-shaped members is coupled to a side corresponding to the other leg of the other plate-shaped member.

[0036] When the reflector constituting the light guide **141** is configured with the plate-shaped transparent members as described above, the side surfaces **141s**, that is, the plate surfaces of the plate-shaped members that face the space outside the reflector act as the reflection surfaces. To increase the reflectance of the side surfaces **141s** and portions in the vicinity thereof for the blue light LB having entered the light guide **141** via the light incident end **141a**, the reflector constituting the light guide **141** is provided with a reflection film **251** configured, for example, with a dielectric multilayer film at the plate surface of each of the plate-shaped members constituting the reflector that is opposite from the side surface **141s**, that is, the plate surface facing an internal space SP**141**. In this case, the plate surface of each of the plate-shaped members that faces the internal space SP**141** inside the reflector acts as the reflection surface **141r**. Part of the blue light LB having entered the internal space SP**141** inside the reflector constituting the light guide **141** via the light incident end **141a** is reflected off the reflection films **251** and travels toward the +D1 side.

[0037] The intensity of the blue light LB reflected off the reflection films **251** and output from the reflection films **251** depends in some cases on the angle of incidence of the blue light LB incident on the reflection films **251**. When the reflection films **251** are each configured with a dielectric multilayer film, the dependence of the intensity of the blue light LB output from the reflection films **251** on the angle of incidence changes in accordance, for example, with the refractive index of multiple films contained in the dielectric multilayer film, the thickness of each of the films, the number of films, and other parameters. For example, when the angle α falls within the range from 7° to 22° and the angle β falls within the range from 14° to 36° as described above, the reflection

films **251** are designed and the parameters of the dielectric multilayer film are appropriately determined in such a way that the angle of incidence of the blue light LB output from the reflection surfaces **141r** and the reflection films **251** at which the intensity of the blue light LB is maximized falls within a range, for example, from 60° to 90°. The relationship between the angle of incidence of the blue light LB incident on the reflection surfaces **141r** and the reflection films **251** and the intensity of the blue light LB output from the reflection surfaces **141r** and the reflection films **251** is derived by a numerical simulation based on the configuration of the blue light outputting section **101** and ray tracing.

[0038] Note that when the reflector is configured with plate-shaped transparent members, and the plate surface of each of the plate-shaped members that faces the space outside the reflector act as the reflection surface, part of the blue light LB having entered the internal space SP**141** inside the reflector constituting the light guide **141** via the light incident end **141a** enters the plate-shaped members via the plate surfaces of the plate-shaped members that face the internal space SP**141** inside the reflector, is refracted at the plate surfaces facing the internal space SP**141**, is reflected off the plate surfaces of the plate-shaped members that face the space outside the reflector, propagates through the plate-shaped members again, is refracted at the plate surfaces facing the internal space SP**141** inside the reflector, and exits into the internal space SP**141** inside the reflector, and travels toward the +D1 side.

[0039] The parallelizing element **161** is provided in the optical path of the blue light LB output from the light guide **141**, and is disposed at a position which is shifted toward the +D1 side from the light guide **141** and where the parallelizing element **161** overlaps with the light guide **141** in the D2 and D3 directions. The parallelizing element **161** corresponds to a first parallelizing element, and parallelizes the blue light LB output from the light guide **141** along the D1 direction.

[0040] The parallelizing element **161** is, for example, a plano-convex lens, and has a light incident surface configured with a planar surface perpendicular to the D1 direction, and a light exiting surface configured with a convex curved surface protruding toward the side via which the blue light LB exits. The light incident surface of the plano-convex lens constituting the parallelizing element **161** is in contact with the light exiting end **141b** of the light guide **141**. Since the parallelizing element **161** is in contact with the light exiting end **141b**, the blue light LB output via the light exiting end **141b** of the light guide **141** is introduced as much as possible into the parallelizing element **161**, so that loss of the blue light LB can be suppressed. The parallelizing element **161** may instead be an optical lens that can parallelize the incident blue light LB other than a plano-convex lens. The parallelizing element **161** may be disposed at an appropriate distance from the light guide **141** in the D1 direction.

[0041] The light-incident-side polarizer **171** is provided in the optical path of the blue light LB output from the parallelizing element **161**, and is disposed at a position which is shifted toward the +D1 side from the parallelizing element **161** and where the light-incident-side polarizer **171** overlaps with the parallelizing element **161** in the D2 and D3 directions. The light-incident-side polarizer **171** is in contact, for example, with the -D1 side of the light modulator **181**, and may instead be disposed at an appropriate distance from the light modulator **181** in the D1 direction. The light-incident-side polarizer **171** corresponds to a first polarizer, and outputs predetermined polarized light out of the blue light LB output from the parallelizing element **161** toward the +D1 side along the D1 direction. The predetermined polarized light corresponds to a first polarized component, and is, for example, S-polarized light.

[0042] The light-incident-side polarizer **171** is, for example, a reflective or absorptive polarizing plate having plate surfaces parallel to the plane containing the D2 and D3 directions. When it is desired to suppress return light and stray light directed to upstream optical elements including the parallelizing element **161**, it is desirable to employ an absorptive polarizing plate as the light-incident-side polarizer **171**. The light-incident-side polarizer **171** transmits part of the incident blue light LB that contains the predetermined polarized light toward the +D1 side, and absorbs or

reflects the other part of the blue light LB toward the -D1 side.

[0043] The light modulator **181** is provided in the optical path of the blue light LB output from the light-incident-side polarizer **171**, and is disposed at a position which is shifted toward the +D1 side from the light-incident-side polarizer **171** and where the light modulator **181** overlaps with the light-incident-side polarizer **171** in the D2 and D3 directions. The light modulator **181** corresponds to a first light modulator, and modulates the blue light LB output from the light-incident-side polarizer **171** based on image information input from an image formation apparatus that is not shown but is externally coupled to the light modulator **181**, such as a computer.

[0044] The light modulator **181** is, for example, a transmissive liquid crystal panel. The liquid crystal panel constituting the light modulator **181** has multiple pixels that are not shown. The pixels each include a switching element. The switching element is, for example, a polysilicon thin film transistor (TFT). An electric signal according to the brightness of the red light at the relative position of each of the pixels at the light modulation surface of the light modulator **181** in an image projected by the projector **301** is supplied to the switching element of the pixel. The pixels each modulate the vibration direction of the blue light LB incident from the light-incident-side polarizer **171** with the aid of the operation of the switching element according to the electric signal described above to generate blue image light IB. The image light IB corresponds to the first light. The light modulator **181** outputs the image light IB generated by the liquid crystal panel toward the +D1 side along the D1 direction.

[0045] The light-exiting-side polarizer **175** is provided in the optical path of the image light IB output from the light modulator **181**, and is disposed at a position which is shifted toward the +D1 side from the light modulator **181** where the light-exiting-side polarizer **175** overlaps with the light modulator **181** in the D2 and D3 directions. The light-exiting-side polarizer **175** is in contact, for example, with the +D1 side of the light modulator **181**, and may instead be disposed at an appropriate distance from the light modulator **181** in the D1 direction. The light-exiting-side polarizer **175** corresponds to a fourth polarizer, and outputs predetermined polarized light out of the image light IB output from the light modulator **181** toward the +D1 side along the D1 direction. The predetermined polarized light corresponds to a fourth polarized component, and is, for example, P-polarized light.

[0046] The light-exiting-side polarizer **175** is, for example, a reflective or absorptive polarizing plate having plate surfaces parallel to the plane containing the D2 and D3 directions. When it is desired to suppress return light and stray light directed to the light modulator **181**, it is desirable to employ an absorptive polarizing plate as the light-exiting-side polarizer **175**. The light-exiting-side polarizer **175** transmits part of the incident image light IB that contains the predetermined polarized light toward the +D1 side, and absorbs or reflects the other part of the image light IB toward the -D1 side.

[0047] The green light outputting section **102** is disposed at a position shifted toward the +D1 side and the -D2 side from the blue light outputting section **101** in a region where the green light outputting section **102** overlaps with the blue light outputting section **101** in the D3 direction. The green light outputting section **102** outputs green light LG. The green light LG output from the green light outputting section **102** travels toward the +D2 side along the D2 direction.

[0048] The green light outputting section **102** includes a light source **402**, a light guide **142**, and a parallelizing element **162**. The light source **402** corresponds to a second light source. A light emitting device **122** of the light source **402** is supported by a substrate **112**. The light emitting device **122** is provided at the +D2-side plate surface of the substrate **112** out of the plate surfaces of the substrate **112** that are parallel to a plane containing the D1 and D3 directions. The light emission surface of the light emitting device **122** is located substantially in parallel to the plane containing the D1 and D3 directions, and is a surface opposite in the D2 direction from the surface of the light emitting device **122** that is in contact with the +D2-side plate surface of the substrate **112**. The light emitting device **122** corresponds to a second light emitting device, and outputs the

green light LG having a green wavelength band in the visible wavelength band. The green wavelength band corresponds to a second wavelength band. The green light LG corresponds to second light. The green light LG exits via the light emission surface of the light emitting device **122** toward the +D2 side while diverging in accordance with a predetermined radiation angle around the axis passing through the center of the light emission surface of the light emitting device **122** and parallel to the D2 direction. The green wavelength band is, for example, a wavelength band ranging from 500 nm to 600 nm.

[0049] The light emitting device **122** includes, for example, a light emitter that emits excitation light and a phosphor that is excited by the excitation light emitted from the light emitter and emits the green light LG, as will be described later. Note that the light emitter of the light emitting device **122** may be configured with one LED or multiple LEDs in their entirety, as the light emitter of the light emitting device **121**. When the light emitter of the light emitting device **122** is configured with multiple LEDs, the multiple LEDs are arranged in the region occupied by the light emitting device **122** in the plane containing the D1 and D3 directions.

[0050] The substrate **112** is made, for example, of metal, and also acts as a heat dissipation member that receives heat, for example, from the light emitting device **122** emitting the green light LG and dissipates the heat to an external space.

[0051] The light guide **142** is provided in the optical path of the green light LG output from the light source **402**, and is disposed at a position which is shifted toward the +D2 side from the light emitting device **122** of the light source **402** and where the light guide **142** overlaps with the light emitting device **122** in the D1 and D3 directions. The light guide **142** corresponds to a second light guide, and has a light incident end **142a** facing the -D2 side in the D2 direction, a light exiting end **142b** facing the +D2 side in the D2 direction, and side surfaces **142s** and reflection surfaces **142r** extending between the light incident end **142a** and the light exiting end **142b** in the D2 direction.

[0052] The light incident end **142a** corresponds to a second light incident end and spreads in parallel to the plane containing the D1 and D3 directions. The light incident end **142a** viewed in the D2 direction has the same shape as the light emission surface of the light emitting device **122** viewed in the same direction, and has, for example, a quadrangular shape. The size of the light incident end **142a** in a plane containing the D1 and D3 directions may be equal to the size of the light emission surface of the light emitting device **122** in a plane containing the D1 and D3 directions, and is preferably appropriately greater than the size of the light emission surface of the light emitting device **122** in the plane containing the D1 and D3 directions.

[0053] The light exiting end **142b** corresponds to a second light exiting end, spreads in parallel to the plane containing the D1 and D3 directions, and is larger than the light incident end **142a**. The light exiting end **142b** viewed in the D2 direction has the same shape as the light modulation surface of the light modulator **182** viewed in the same direction, is similar to the modulation surface of the light modulator **182**, and has, for example, a quadrangular shape. The size of the light exiting end **142b** in a plane containing the D1 and D3 directions is equal to the size of the light modulation surface of the light modulator **182** in a plane containing the D1 and D3 directions. The side surfaces **142s** and the reflection surfaces **142r** couple the circumferential edge of the light incident end **142a** to the circumferential edge of the light exiting end **142b** in the D2 direction.

[0054] The green light LG output from the light source **402** enters the light guide **142** via the light incident end **142a**. In the light guide **142**, the region surrounded by the light incident end **142a**, the light exiting end **142b**, and the reflection surfaces **142r** is a region through which the green light LG propagates. The size, in planes containing the D1 and D3 directions, of the region surrounded by the light incident end **142a**, the light exiting end **142b**, and the reflection surfaces **142r** increases as the region extends from the -D2 side toward the +D2 side in the D2 direction. Furthermore, the shape, in the planes containing the D1 and D3 directions, of the region surrounded by the light incident end **142a**, the light exiting end **142b**, and the reflection surfaces **142r** changes from the shape of the light emission surface of the light emitting device **122** to the shape of the light

modulation surface of the light modulator **182** when viewed in the D2 direction as the region extends from the -D2 side toward the +D2 side.

[0055] The side surfaces **142s** of the light guide **142** and the reflection surfaces **142r** provided at the side surfaces **142s** as will be described later incline by a predetermined angle with respect to an imaginary line and the optical axis perpendicular to the light incident end **142a**, and are separate away from the imaginary line in the planes containing the D1 and D3 directions as the light guide **142** extends from the -D2 side toward the +D2 side. The green light LG having entered the light guide **142** propagates from the -D2 side toward the +D2 side in the region surrounded by the light incident end **142a**, the light exiting end **142b**, and the reflection surfaces **142r**.

[0056] When the light modulation surface of the light modulator **182** has a rectangular shape when viewed along the D2 direction, a light emission surface **122e** of the light emitting device **122** viewed along the D2 direction is substantially similar to the modulation surface of the light modulator **182**, and has a rectangular shape. In this case, it is preferable that the predetermined angle α of the side surfaces **142s** and the reflection surfaces **142r** containing the short sides of the rectangular shape with respect to the imaginary line and the optical axis described above falls within the range from 7° to 22° . It is preferable that the predetermined angle β of the side surfaces **142s** and the reflection surfaces **142r** containing the long sides of the rectangular shape with respect to the imaginary line and the optical axis described above falls within the range from 14° to 36° . The preferable ranges of the angles α and β have been ascertained by a numerical simulation based on the configuration of the green light outputting section **102** and ray tracing.

[0057] Part of the green light LG having entered the light guide **142** propagates directly from the light incident end **142a** to the light exiting end **142b** without being incident on the reflection surfaces **142r** even once along directions that incline by angles smaller than the angle α or β with respect to the imaginary line and the optical axis described above. The remaining part of the green light LG having entered the light guide **142** inclines by angles greater than or equal to the angle α or β with respect to the imaginary line and the optical axis described above, is incident on the reflection surfaces **142r** via the light incident end **142a** once or a greater number of times, is reflected off the reflection surfaces **142r**, and then reaches the light exiting end **142b**.

[0058] The paths of the beams constituting the green light LG in the region surrounded by the light incident end **142a**, the light exiting end **142b**, and the reflection surfaces **142r** vary in accordance with the angles of incidence of the beams incident on the light incident end **142a**, and there are multiple paths along which the beams are reflected off the reflection surfaces **142r** by different numbers of times. The illuminance distribution of the green light LG that propagates through the region surrounded by the light incident end **142a**, the light exiting end **142b**, and the reflection surfaces **142r** is therefore homogenized in the planes containing the D1 and D3 directions. That is, the light guide **142** homogenizes the illuminance distribution of the incident green light LG in the planes containing the D1 and D3 directions. The green light LG having the homogenized illuminance distribution exits via the light exiting end **142b** toward the +D2 side.

[0059] The light guide **142** is a hollow reflector configured with plate-shaped members made of a transparent material such as optical glass, as the light guide **141**. When viewed along the D2 direction, the -D2-side end of the frame body of the reflector has the same shape as the light incident end **142a** and the light emission surface of the light emitting device **122**, is larger by an appropriate degree than the light emission surface of the light emitting device **122**, and is formed, for example, in the shape of a quadrangular frame. The +D2-side end of the frame body of the reflector has the same shape and size as the light exiting end **142b** and the light modulation surface of the light modulator **182**, and is formed, for example, in the shape of a quadrangular frame different in size from the -D2-side end.

[0060] The reflector constituting the light guide **142** is configured with four plate-shaped members each having a trapezoidal shape with the sides corresponding to the legs of the trapezoidal shape coupled to each other. The length of the sides facing the -D2 side that are parallel to the D1 or D3

direction and correspond to the upper bases of the four plate-shaped members is set in accordance with the size of the light incident end **142a** and the light emission surface of the light emitting device **122** in the D1 or D3 direction. The length of the sides facing the +D2 side that are parallel to the D1 or D3 direction and correspond to the lower bases of the four plate-shaped members is set in accordance with the size of the light exiting end **142b** and the light modulation surface of the light modulator **182** in the D1 or D3 direction.

[0061] When the reflector constituting the light guide **142** is configured with the plate-shaped transparent members as described above, the side surfaces **142s**, that is, the plate surfaces of the plate-shaped members that face the space outside the reflector act as the reflection surfaces. To increase the reflectance of the side surface **142s** and portions in the vicinity thereof for the green light LG having entered the light guide **142** via the light incident end **142a**, the reflector constituting the light guide **142** is also provided with a reflection film **252** configured, for example, with a dielectric multilayer film at the plate surface of each of the plate-shaped members constituting the reflector that is opposite from the side surface **142s**, that is, the plate surface facing an internal space SP**142** inside the plate-shaped member. In this case, the plate surface of each of the plate-shaped members that faces the internal space SP**142** inside the reflector acts as the reflection surface **142r**. Part of the green light LG having entered the internal space SP**142** inside the reflector constituting the light guide **142** via the light incident end **142a** is reflected off the reflection films **252** and travels toward the +D2 side.

[0062] The intensity of the green light LG reflected off the reflection films **252** and output from the reflection films **252** depends in some cases on the angle of incidence of the green light LG incident on the reflection films **252**. When the reflection films **252** are each configured with a dielectric multilayer film, the dependence of the intensity of the green light LG output from the reflection films **252** on the angle of incidence changes in accordance, for example, with the refractive index of multiple films contained in the dielectric multilayer film, the thickness of each of the films, the number of films, and other parameters. For example, when the angle α falls within the range from 7° to 22° and the angle β falls within the range from 14° to 36° as described above, the reflection films **252** are designed and the parameters of the dielectric multilayer film are appropriately determined in such a way that the angle of incidence of the green light LG output from the reflection surfaces **142r** and the reflection films **252** at which the intensity of the green light LG is maximized falls within the range, for example, from 60° to 90° . The relationship between the angle of incidence of the green light LG incident on the reflection surfaces **142r** and the reflection films **252** and the intensity of the green light LG output from the reflection surface **142r** and the reflection films **252** is derived by a numerical simulation based on the configuration of the green light outputting section **102** and ray tracing.

[0063] Note that when the reflector constituting the light guide **142** is configured with plate-shaped transparent members, and the plate surface of each of the plate-shaped members that faces the space outside the reflector act as the reflection surface, part of the green light LG having entered the internal space SP**142** inside the reflector constituting the light guide **142** via the light incident end **142a** enters the plate-shaped members via the plate surfaces of the plate-shaped members that face the internal space SP**142** inside the reflector, is refracted at the plate surfaces facing the internal space SP**142**, is reflected off the plate surfaces of the plate-shaped members that face the space outside the reflector, propagates through the plate-shaped members again, is refracted at the plate surfaces facing the internal space SP**142** inside the reflector, and exits into the internal space SP**142** inside the reflector, and travels toward the +D2 side.

[0064] The parallelizing element **162** is provided in the optical path of the green light LG output from the light guide **142**, and is disposed at a position which is shifted toward the +D2 side from the light guide **142** and where the parallelizing element **162** overlaps with the light guide **142** in the D1 and D3 directions. The parallelizing element **162** corresponds to a second parallelizing element, and parallelizes the green light LG output from the light guide **142** along the D2 direction.

[0065] The parallelizing element **162** is, for example, a plano-convex lens, and has a light incident surface configured with a planar surface perpendicular to the D2 direction, and a light exiting surface configured with a convex curved surface protruding toward the side via which the green light LG exits. The light incident surface of the parallelizing element **162** is in contact with the light exiting end **142b** of the light guide **142**. Since the parallelizing element **162** is in contact with the light exiting end **142b**, the green light LG output via the light exiting end **142b** of the light guide **142** is introduced as much as possible into the parallelizing element **162**, so that loss of the green light LG can be suppressed. The parallelizing element **162** may instead be an optical lens that can parallelize the incident green light LG other than a plano-convex lens. The parallelizing element **162** may be disposed at an appropriate distance from the light guide **142** in the D2 direction.

[0066] The light-incident-side polarizer **172** is provided in the optical path of the green light LG output from the parallelizing element **162**, and is disposed at a position shifted toward the +D2 side from the parallelizing element **162** and where the light-incident-side polarizer **172** overlaps with the parallelizing element **162** in the D1 and D3 directions. The light-incident-side polarizer **172** is in contact, for example, with the +D2 side of the light modulator **182**, and may instead be disposed at an appropriate distance from the light modulator **182** in the D2 direction. The light-incident-side polarizer **172** corresponds to a second polarizer, and outputs predetermined polarized light out of the green light LG output from the parallelizing element **162** toward the +D2 side along the D2 direction. The predetermined polarized light corresponds to a second polarized component, and is, for example, S-polarized light.

[0067] The light-incident-side polarizer **172** is, for example, a reflective or absorptive polarizing plate having plate surfaces parallel to the plane containing the D1 and D3 directions. When it is desired to suppress return light and stray light directed to optical elements including the parallelizing element **162** upstream from the light-incident-side polarizer **172**, it is desirable to employ an absorptive polarizer as the light-incident-side polarizer **172**. The light-incident-side polarizer **172** transmits part of the incident green light LG that contains the predetermined polarized light toward the +D2 side, and absorbs or reflects the other part of the green light LG toward the -D2 side.

[0068] The light modulator **182** is provided in the optical path of the green light LG output from the light-incident-side polarizer **172**, and is disposed at a position shifted toward the +D2 side from the light-incident-side polarizer **172** and where the light modulator **182** overlaps with the light-incident-side polarizer **172** in the D1 and D3 directions. The light modulator **182** corresponds to a second light modulator, and modulates the green light LG output from the light-incident-side polarizer **172** based on image information input from the image formation apparatus that is not shown but is externally coupled to the light modulator **182**, such as a computer.

[0069] The light modulator **182** is, for example, a transmissive liquid crystal panel. The liquid crystal panel constituting the light modulator **182** has multiple pixels that are not shown. The pixels each include a switching element. The switching element is, for example, a TFT. An electric signal according to the brightness of the green light at the relative position of each of the pixels at the light modulation surface of the light modulator **182** in an image projected by the projector **301** is supplied to the switching element in the pixel. The pixels each modulate the vibration direction of the green light LG incident from the light-incident-side polarizer **172** with the aid of the operation of the switching element according to the electric signal described above to generate green image light IG. The image light IG corresponds to the second light. The light modulator **182** outputs the image light IG generated by the liquid crystal panel toward the +D2 side along the D2 direction.

[0070] The light-exiting-side polarizer **176** is provided in the optical path of the image light IG output from the light modulator **182**, and is disposed at a position shifted toward the +D2 side from the light modulator **182** and where the light-exiting-side polarizer **176** overlaps with the light modulator **182** in the D1 and D3 directions. The light-exiting-side polarizer **176** is in contact, for example, with the +D2 side of the light modulator **182**, and may instead be disposed at an

appropriate distance from the light modulator **182** in the D2 direction. The light-exiting-side polarizer **176** corresponds to a fifth polarizer, and outputs predetermined polarized light out of the image light IG output from the light modulator **182** toward the +D2 side along the D2 direction. The predetermined polarized light corresponds to a fifth polarized component, and is, for example, P-polarized light.

[0071] The light-exiting-side polarizer **176** is, for example, a reflective or absorptive polarizing plate having plate surfaces parallel to the plane containing the D1 and D3 directions. When it is desired to suppress return light and stray light directed to the light modulator **182**, it is desirable to employ an absorptive polarizing plate as the light-exiting-side polarizer **176**. The light-exiting-side polarizer **176** transmits part of the incident image light IG that contains the predetermined polarized light toward the +D2 side, and absorbs or reflects the other part of the image light IG toward the -D2 side.

[0072] The red light outputting section **103** is disposed at a position shifted toward the +D1 side from the green light outputting section **102** in a region where the red light outputting section **103** overlaps with the blue light emitter **101** in the D2 and D3 directions. The red light outputting section **103** outputs red light LR. The red light LR output from the red light outputting section **103** travels toward the -D1 side along the D1 direction.

[0073] The red light outputting section **103** includes a light source **403**, a light guide **143**, and a parallelizing element **163**. The light source **403** corresponds to a third light source. A light emitting device **123** of the light source **403** is supported by a substrate **113**. The light emitting device **123** is provided at the -D1-side plate surface of the substrate **113** out of the plate surfaces of the substrate **113** that are parallel to the plane containing the D2 and D3 directions. The light emission surface of the light emitting device **123** is located substantially in parallel to the plane containing the D2 and D3 directions, and is a surface opposite in the D1 direction from the surface of the light emitting device **123** that is in contact with the -D1-side plate surface of the substrate **113**. The light emitting device **123** corresponds to a third light emitting device, and outputs the red light LR having a red wavelength band in the visible wavelength band. The red wavelength band corresponds to a third wavelength band. The red light LR corresponds to third light. The red light LR exits via the light emission surface of the light emitting device **123** toward the -D1 side while diverging in accordance with a predetermined radiation angle around the axis passing through the center of the light emission surface of the light emitting device **123** and parallel to the D1 direction. The red wavelength band is, for example, a wavelength band ranging from 610 nm to 700 nm.

[0074] The light emitting device **123** is configured, for example, with an LED that emits the red light LR. Note that the light emitting device **123** may be configured with one LED or multiple LEDs in their entirety, as the light emitting devices **121** and **122**. When the light emitting device **123** is configured with multiple LEDs, the multiple LEDs are arranged in the region occupied by the light emitting device **123** in the plane containing the D2 and D3 directions.

[0075] The substrate **113** is made, for example, of metal, and also acts as a heat dissipation member that receives heat, for example, from the light emitting device **123** outputting the red light LR and dissipates the heat to an external space.

[0076] The light guide **143** is provided in the optical path of the red light LR output from the light source **403**, and is disposed at a position shifted toward the -D1 side from the light emitting device **123** of the light source **403** and where the light guide **143** overlaps with the light emitting device **123** in the D2 and D3 directions. The light guide **143** corresponds to a third light guiding element, and has a light incident end **143a** facing the +D1 side in the D1 direction, a light exiting end **143b** facing the -D1 side in the D1 direction, and side surfaces **143s** and reflection surfaces **143r** extending between the light incident end **143a** and the light exiting end **143b** in the D1 direction.

[0077] The light incident end **143a** corresponds to a third light incident end and spreads in parallel to the plane containing the D2 and D3 directions. The light incident end **143a** viewed in the D1 direction has the same shape as the light emission surface of the light emitting device **123** viewed

in the same direction, and has, for example, a quadrangular shape. The size of the light incident end **143a** in a plane containing the D2 and D3 directions may be equal to the size of the light emission surface of the light emitting device **123** in a plane containing the D2 and D3 directions, and is preferably appropriately greater than the size of the light emission surface of the light emitting device **123** in the plane containing the D2 and D3 directions.

[0078] The light exiting end **143b** corresponds to a third light exiting end, spreads in parallel to the plane containing the D2 and D3 directions, and is larger than the light incident end **143a**. The light exiting end **143b** viewed in the D1 direction has the same shape as the light modulation surface of the light modulator **183** viewed in the same direction, is similar to the modulation surface of the light modulator **183**, and has, for example, a quadrangular shape. The size of the light exiting end **143b** in a plane containing the D2 and D3 directions is equal to the size of the light modulation surface of the light modulator **183** in a plane containing the D2 and D3 directions. The side surfaces **143s** and the reflection surfaces **143r** couple the circumferential edge of the light incident end **143a** to the circumferential edge of the light exiting end **143b** in the D1 direction.

[0079] The red light LR output from the light source **403** enters the light guide **143** via the light incident end **143a**. In the light guide **143**, the region surrounded by the light incident end **143a**, the light exiting end **143b**, and the reflection surfaces **143r** is a region through which the red light LR propagates. The size, in planes containing the D2 and D3 directions, of the region surrounded by the light incident end **143a**, the light exiting end **143b**, and the reflection surfaces **143r** increases as the region extends from the +D1 side toward the -D1 side in the D1 direction. Furthermore, the shape, in the planes containing the D2 and D3 directions, of the region surrounded by the light incident end **143a**, the light exiting end **143b**, and the reflection surfaces **143r** changes from the shape of the light emission surface of the light emitting device **123** to the shape of the light modulation surface of the light modulator **183** when viewed in the D1 direction as the region extends from the +D1 side toward the -D1 side.

[0080] The side surfaces **143s** of the light guide **143** and the reflection surfaces **143r** provided at the side surfaces **143s** as will be described later incline by a predetermined angle with respect to an imaginary line and the optical axis perpendicular to the light incident end **143a**, and are separate away from the imaginary line in the planes containing the D2 and D3 directions as the light guide **143** extends from the +D1 side toward the -D1 side. The red light LR having entered the light guide **142** propagates from the +D1 side toward the -D1 side in the region surrounded by the light incident end **143a**, the light exiting end **143b**, and the reflection surfaces **143r**.

[0081] When the light modulation surface of the light modulator **183** has a rectangular shape when viewed along the D1 direction, the light emission surface of the light emitting device **123** viewed along the D1 direction is substantially similar to the modulation surface of the light modulator **183**, and has, for example, a rectangular shape. In this case, it is preferable that the predetermined angle α of the side surfaces **143s** and the reflection surfaces **143r** containing the short sides of the rectangular shape with respect to the imaginary line and the optical axis described above falls within the range from 7° to 22° . It is preferable that the predetermined angle β of the side surfaces **143s** and the reflection surfaces **143r** containing the long sides of the rectangular shape with respect to the imaginary line and the optical axis described above falls within the range from 14° to 36° . The preferable ranges of the angles α and β have been ascertained by a numerical simulation based on the configuration of the red light outputting section **103** and ray tracing.

[0082] Part of the red light LR having entered the light guide **143** propagates directly from the light incident end **143a** to the light exiting end **143b** without being incident on the reflection surfaces **143r** even once along directions that incline by angles smaller than the angle α or β with respect to the imaginary line and the optical axis described above. The remaining part of the red light LR having entered the light guide **143** inclines by angles greater than or equal to the angle α or β with respect to the imaginary line and the optical axis described above, is incident on the reflection surfaces **143r** via the light incident end **143a** once or a greater number of times, is reflected off the

reflection surfaces **143r**, and then reaches the light exiting end **143b**. The paths of the beams constituting the red light LR in the region surrounded by the light incident end **143a**, the light exiting end **143b**, and the reflection surfaces **143r** vary in accordance with the angles of incidence of the beams incident on the light incident end **143a**, and there are multiple paths along which the beams are reflected off the reflection surfaces **143r** by different numbers of times. The illuminance distribution of the red light LR that propagates through the region surrounded by the light incident end **143a**, the light exiting end **143b**, and the reflection surfaces **143r** is therefore homogenized in the planes containing the D2 and D3 directions. That is, the light guide **143** homogenizes the illuminance distribution of the incident red light LR in the planes containing the D2 and D3 directions. The red light LR having the homogenized illuminance distribution exits via the light exiting end **143b** toward the $-D1$ side.

[0083] The light guide **143** is a hollow reflector configured with plate-shaped members made of a transparent material such as optical glass, as the light guides **141** and **142**. When viewed along the D1 direction, the $+D1$ -side end of the frame body of the reflector has the same shape as the light incident end **143a** and the light emission surface of the light emitting device **123**, is larger by an appropriate degree than the light emission surface of the light emitting device **123**, and is formed, for example, in the shape of a quadrangular frame. The $-D1$ -side end of the frame body of the reflector has the same shape as the light exiting end **143b** and the light modulation surface of the light modulator **183**, and is formed, for example, in the shape of a quadrangular frame different in size from the $+D1$ -side end.

[0084] The reflector constituting the light guide **143** is configured with four plate-shaped members each having a trapezoidal shape with the sides corresponding to the legs of the trapezoidal shape coupled to each other. The length of the sides facing the $+D1$ side that are parallel to the D2 or D3 direction and correspond to the upper bases of the four plate-shaped members is set in accordance with the size of the light incident end **143a** and the light emission surface of the light emitting device **123** in the D2 or D3 direction. The length of the sides facing the $-D1$ side that are parallel to the D2 or D3 direction and correspond to the lower bases of the four plate-shaped members is set in accordance with the size of the light exiting end **143b** and the light modulation surface of the light modulator **183** in the D2 or D3 direction.

[0085] When the reflector constituting the light guide **143** is configured with the plate-shaped transparent members as described above, the side surfaces **143s**, that is, the plate surfaces of the plate-shaped members that face the space outside the reflector act as the reflection surfaces. To increase the reflectance of the side surface **143s** and portions in the vicinity thereof for the red light LR having entered the light guide **143** via the light incident end **143a**, the reflector constituting the light guide **143** is also provided with a reflection film **253** configured, for example, with a dielectric multilayer film at the plate surface of each of the plate-shaped members constituting the reflector that is opposite from the side surface **143s**, that is, the plate surface facing an internal space SP**143** inside the plate-shaped member. In this case, the plate surface of each of the plate-shaped members that faces the internal space SP**143** inside the reflector acts as the reflection surface **143r**. Part of the red light LR having entered the internal space SP**143** inside the reflector constituting the light guide **143** via the light incident end **143a** is reflected off the reflection films **253** and travels toward the $-D1$ side.

[0086] The intensity of the red light LR reflected off the reflection films **253** and output from the reflection films **253** depends in some cases on the angle of incidence of the red light LR incident on the reflection films **253**. When the reflection films **253** are each configured with a dielectric multilayer film, the dependence of the intensity of the red light LR output from the reflection films **253** on the angle of incidence changes in accordance, for example, with the refractive index of multiple films contained in the dielectric multilayer film, the thickness of each of the films, the number of films, and other parameters. For example, when the angle α falls within the range from 7° to 22° and the angle β falls within the range from 14° to 36° as described above, the reflection

films **253** are designed and the parameters of the dielectric multilayer film are appropriately determined in such a way that the angle of incidence of the red light LR output from the reflection surfaces **143r** and the reflection films **253** at which the intensity of the red light LR is maximized falls within the range, for example, from 60° to 90°. The relationship between the angle of incidence of the red light LR incident on the reflection surfaces **143r** and the reflection films **253** and the intensity of the red light LR output from the reflection surface **143r** and the reflection films **253** is derived by a numerical simulation based on the configuration of the red light outputting section **103** and ray tracing.

[0087] Note that when the reflector constituting the light guide **143** is configured with plate-shaped transparent members, and the plate surface of each of the plate-shaped members that faces the space outside the reflector act as the reflection surface, part of the red light LR having entered the internal space SP**143** inside the reflector constituting the light guide **143** via the light incident end **143a** enters the plate-shaped members via the plate surfaces of the plate-shaped members that face the internal space SP**143** inside the reflector, is refracted at the plate surfaces facing the internal space SP**143**, is reflected off the plate surfaces of the plate-shaped members that face the space outside the reflector, propagates through the plate-shaped members again, is refracted at the plate surfaces facing the internal space SP**143** inside the reflector, and exits into the internal space SP**143** inside the reflector, and travels toward the -D1 side.

[0088] The parallelizing element **163** is provided in the optical path of the red light LR output from the light guide **143**, and is disposed at a position shifted toward the -D1 side from the light guide **143** and where the parallelizing element **163** overlaps with the light guide **143** in the D2 and D3 directions. The parallelizing element **163** corresponds to a third parallelizing element, and parallelizes the red light LR output from the light guide **143** along the D1 direction.

[0089] The parallelizing element **163** is, for example, a plano-convex lens, and has a light incident surface configured with a planar surface perpendicular to the D1 direction, and a light exiting surface configured with a convex curved surface protruding toward the side via which the red light LR exits. The light incident surface of the parallelizing element **163** is in contact with the light exiting end **143b** of the light guide **143**. Since the parallelizing element **163** is in contact with the light exiting end **143b**, the red light LR output via the light exiting end **143b** of the light guide **143** is introduced as much as possible into the parallelizing element **163**, so that loss of the red light LR can be suppressed. The parallelizing element **163** may instead be an optical lens that can parallelize the incident red light LR other than a plano-convex lens. The parallelizing element **163** may be disposed at an appropriate distance from the light guide **143** in the D1 direction.

[0090] The light-incident-side polarizer **173** is provided in the optical path of the red light LR output from the parallelizing element **163**, and is disposed at a position shifted toward the -D1 side from the parallelizing element **163** and where the light-incident-side polarizer **173** overlaps with the parallelizing element **163** in the D2 and D3 directions. The light-incident-side polarizer **173** is in contact, for example, with the +D1 side of the light modulator **183**, and may instead be disposed at an appropriate distance from the light modulator **183** in the D1 direction.

[0091] The light-incident-side polarizer **173** corresponds to a third polarizer, and outputs predetermined polarized light out of the red light LR output from the parallelizing element **163** toward the -D1 side along the D1 direction. The predetermined polarized light corresponds to a third polarized component, and is, for example, S-polarized light. The light-incident-side polarizer **173** is, for example, a reflective or absorptive polarizing plate having plate surfaces parallel to the plane containing the D2 and D3 directions. When it is desired to suppress return light and stray light directed to optical elements including the parallelizing element **163** upstream from the light-incident-side polarizer **173**, it is desirable to employ an absorptive polarizer as the light-incident-side polarizer **173**. The light-incident-side polarizer **173** transmits part of the incident red light LR that contains the predetermined polarized light toward the -D1 side, and absorbs or reflects the other part of the red light LR toward the +D1 side.

[0092] The light modulator **183** is provided in the optical path of the red light LR output from the light-incident-side polarizer **173**, and is disposed at a position shifted toward the $-D1$ side from the light-incident-side polarizer **173** and where the light modulator **183** overlaps with the light-incident-side polarizer **173** in the D2 and D3 directions. The light modulator **183** corresponds to a third light modulator, and modulates the red light LR output from the light-incident-side polarizer **173** based on image information input from the image formation apparatus that is not shown but is externally coupled to the light modulator **183**, such as a computer.

[0093] The light modulator **183** is, for example, a transmissive liquid crystal panel. The liquid crystal panel constituting the light modulator **183** includes multiple pixels that are not shown. The pixels each include a switching element. The switching element is, for example, a TFT. An electric signal according to the brightness of the red light at the relative position of each of the pixels at the light modulation surface of the light modulator **183** in an image projected by the projector **301** is supplied to the switching element in the pixel. The pixels each modulate the vibration direction of the red light LR incident from the light-incident-side polarizer **173** with the aid of the operation of the switching element according to the electric signal described above to generate red image light IR. The image light IR corresponds to the third light. The light modulator **183** outputs the image light IR generated by the liquid crystal panel toward the $-D1$ side along the D1 direction.

[0094] The light-exiting-side polarizer **177** is provided in the optical path of the image light IR output from the light modulator **183**, and is disposed at a position shifted toward the $-D1$ side from the light modulator **183** and where the light-exiting-side polarizer **177** overlaps with the light modulator **183** in the D2 and D3 directions. The light-exiting-side polarizer **177** is in contact, for example, with the $-D1$ side of the light modulator **183**, and may instead be disposed at an appropriate distance from the light modulator **183** in the D1 direction. The light-exiting-side polarizer **177** corresponds to a sixth polarizer, and outputs predetermined polarized light out of the image light IR output from the light modulator **183** toward the $-D1$ side along the D1 direction. The predetermined polarized light corresponds to a sixth polarized component, and is, for example, P-polarized light.

[0095] The light-exiting-side polarizer **177** is, for example, a reflective or absorptive polarizing plate having plate surfaces parallel to the plane containing the D2 and D3 directions. When it is desired to suppress return light and stray light directed to the light modulator **183**, it is desirable to employ an absorptive polarizing plate as the light-exiting-side polarizer **177**. The light-exiting-side polarizer **177** transmits part of the incident image light IR that contains the predetermined polarized light toward the $-D1$ side, and absorbs or reflects the other part of the image light IR toward the $+D1$ side.

[0096] The light combiner **200** is disposed in a region where the optical path of the blue image light IB output from the light-exiting-side polarizer **175**, the optical path of the green image light IG output from the light-exiting-side polarizer **176**, and the optical path of the red image light IR output from the light-exiting-side polarizer **177** intersect with one another. The light combiner **200** combines the image light IB, the image light IG, and the image light IR output from the light-exiting-side polarizers **175**, **176**, and **177** with one another, and outputs thus generated image light IM toward the $+D2$ side along the D2 direction.

[0097] The light combiner **200** is, for example, a cross dichroic prism **210**. The cross dichroic prism **210** has a light incident surface **210c** facing the light exiting surface of the light-exiting-side polarizer **175**, a light incident surface **210d** facing the light exiting surface of the light-exiting-side polarizer **176**, a light incident surface **210e** facing the light exiting surface of the light-exiting-side polarizer **177**, a light exiting surface **210b**, and two reflection films **211** and **212**. The light incident surfaces **210c** and **210e** are parallel to the plane containing the D2 and D3 directions, and coincide with each other in the D2 and D3 directions. The light incident surface **210d** and the light exiting surface **210b** are parallel to the plane containing the D1 and D3 directions, and coincide with each other in the D1 and D3 directions.

[0098] The reflection film **211** is disposed so as to extend from the +D2 side toward the -D2 side as extending from the -D1 side toward the +D1 side when viewed along the D3 direction. The reflection film **212** is disposed so as to extend from the -D2 side toward the +D2 side as extending from the -D1 side toward the +D1 side when viewed along the D3 direction. The reflection films **211** and **212** overlap with the light incident surfaces **210c** and **210e** in the D2 direction, overlap with the light incident surface **210d** and the light exiting surface **210b** in the D1 direction, and overlap with the light incident surfaces **210c**, **210d**, and **210e** and the light exiting surface **210b** in the D3 direction. The reflection film **211** reflects light having the red wavelength band and transmits light having the blue wavelength band and the green wavelength band. The reflection film **212** reflects light having the blue wavelength band and transmits light having the green wavelength band and the red wavelength band.

[0099] The cross dichroic prism **210** is so configured that, when viewed in the D3 direction, four rectangular prisms are glued to each other along the right angle forming surfaces with the right-angle vertices positioned at the center of the light combiner **200**. The four rectangular prisms of the cross dichroic prism **210** are made of a transparent material that transmits light having the visible wavelength band. The reflection film **211** is disposed at the right angle forming surface that extends from the +D2 side toward the -D2 side as extending from the -D1 side toward the +D1 side as described above out of the right angle forming surfaces of the four rectangular prisms, and is configured, for example, with a dielectric multilayer film. The reflection film **212** is disposed at the right angle forming surface that extends from the -D2 side toward the +D2 side as extending from the -D1 side toward the +D1 side as described above out of the right angle forming surfaces of the four rectangular prisms, and is configured, for example, with a dielectric multilayer film.

[0100] The P-polarized blue image light IB output from the light-exiting-side polarizer **175** enters the interior of the cross dichroic prism **210** via the light incident surface **210c** toward the +D1 side along the D1 direction, passes through the reflection film **211**, is reflected off the reflection film **212**, and travels toward the +D2 side. The P-polarized green image light IG output from the light-exiting-side polarizer **176** enters the interior of the cross dichroic prism **210** via the light incident surface **210d** toward the +D2 side along the D2 direction, passes through the reflection films **211** and **212**, and travels straight toward the +D2 side. The P-polarized red image light IR output from the light-exiting-side polarizer **177** enters the interior of the cross dichroic prism **210** via the light incident surface **210e** toward the -D1 side along the D1 direction, passes through the reflection film **212**, is reflected off the reflection film **211**, and travels toward the +D2 side. The image light IB, the image light IG, and the image light IR output from the reflection films **211** and **212** of the cross dichroic prism **210** toward the +D2 side are combined with one another to generate the full-color image light IM. The cross dichroic prism **210** outputs the full-color image light IM via the light exiting surface **210b** toward the +D2 side along the D2 direction.

[0101] The projection system **250** is disposed in the optical path of the image light IM output from the light combiner **200**. The projection system **250** projects the image light IM onto a screen SCR disposed at a position shifted toward the +D2 side from the projection system **250**, enlarges images input from the image formation apparatus to the light modulators **181**, **182**, and **183**, and displays the enlarged images on the screen SCR.

[0102] The projection system **250** is configured, for example, with one or more optical lenses arranged along the D2 direction. Examples of the optical lenses may include a plano-convex lens, a plano-concave lens, a biconvex lens, a biconcave lens, a meniscus lens, an aspherical lens, and a freeform lens.

[0103] The configurations of the blue light outputting section **101**, the green light outputting section **102**, and the red light outputting section **103** will next be partly described in detail.

[0104] FIG. 2 is a side view of the light source **401** and the light guide **141** of the blue light outputting section **101** in the projector **301** according to the present embodiment. FIG. 3 is a plan view of the light source **401** and the light guide **141** of the blue light outputting section **101** in the

projector **301** according to the present embodiment the plan view viewed along the D2 direction from the +D2 side toward the -D2 side.

[0105] In the light source **401**, a +D1-side plate surface **111a** of the substrate **111** is parallel to the plane containing the directions D2 and D3 as described above, as shown in FIGS. 2 and 3.

Electrodes **411** and **412** are provided at the plate surface **111a** of the substrate **111**. The electrodes **411** and **412** are disposed in different regions of the plate surface **111a**. The number and the shapes of the electrodes provided at the plate surface **111a** of the substrate **111** are not limited to a specific number and specific shapes, and are appropriately set in accordance with the specifications, the shape, and other factors of the light emitting device **121**. FIGS. 2 and 3 show two electrodes **411** and **412** by way of example. The electrodes including the electrodes **411** and **412** and provided at the plate surface **111a** are part of the base of the light source **401**. The electrodes **411** and **412** are formed at the plate surface **111a**, for example, by a printing-based fine electrode patterning technology.

[0106] For example, the light emitting device **121** is disposed at a +D1-side surface **411a** of the electrode **411** and electrically coupled to the electrode **411**. The light emitting device **121** and the electrode **412** are electrically coupled to each other by electrically conducting lines **451** and are coupled to each other, for example, by wire bonding. The electrically conducting lines **451** correspond to a first electrically conducting line, and are, for example, wires formed by wire bonding. The electrically conducting lines **451** supply the light emitting device **121** with electric power based on a desired voltage or current supplied from a power supply that is not shown but is electrically coupled to the electrodes **411** and **412**.

[0107] The electrically conducting lines **451** couple a +D1-side light emission surface **121e** of the light emitting device **121** and a +D1-side surface **412a** of the electrode **412** to each other, and protrude and curve toward the +D1 side beyond the light emission surface **121e** and the surface **412a**. The number and arrangement of the electrically conducting lines **451** in the light source **401** are appropriately set in accordance with the specifications and shape of the light emitting device **121**, the relative positional relationship between the light emitting device **121** and the electrodes, the number and shapes of the electrodes, and other factors. FIGS. 2 and 3 show three electrically conducting lines **451** by way of example.

[0108] The light emission surface **121e** of the light emitting device **121** is shifted toward the +D1 side from the surface **412a** of the electrode **412**. The +D1 side end of each of the electrically conducting lines **451** is shifted toward the +D1 side from the light emission surface **121e** of the light emitting device **121**. A distance DT between the +D1-side end of the electrically conducting lines **451** and the light emission surface **121e** in the D1 direction, that is, the direction parallel to the optical axis of the blue light LB emitted from the light emitting device **121** is greater than or equal to 0.0 mm but smaller than 0.7 mm.

[0109] In the blue light outputting section **101**, a distance DS between the +D1-side end of one or more of the electrically conducting lines **451** and the -D1-side light incident end **141a** of the light guide **141** in the D1 direction is at least smaller than the distance DT and is greater than or equal to 0.0 mm but smaller than or equal to 0.7 mm. The distance DS in the blue light outputting section **101** corresponds to a first distance. In detail, the distances DT and DS are positive when the light incident end **141a** of the light guide **141** is shifted toward the +D1 side with respect to the light emission surface **121e** of the light emitting device **121**, while being negative when the light incident end **141a** is shifted toward the -D1 side with respect to the light emission surface **121e**. That is, the distance DS is greater than or equal to -0.7 mm but smaller than or equal to +0.7 mm, and the absolute value of the distance DS is greater than or equal to 0.0 mm but smaller than or equal to 0.7 mm. In the configuration of the blue light outputting section **101** shown in FIGS. 1 and 2 by way of example, the distance DS is greater than 0.0 mm but smaller than or equal to +0.7 mm.

[0110] In the blue light outputting section **101**, the distance DS is greater than 0.0 mm but smaller than or equal to +0.7 mm in the portion facing the light incident end **141a** of the light guide **141**

that faces the electrically conducting lines **451** in the D1 direction. The portion facing the light incident end **141a** that faces the electrically conducting lines **451** in the D1 direction is a portion that is shifted toward the +D1 side from the electrically conducting lines **451** and overlaps with the electrically conducting lines **451** in the directions D2 and D3. When the distance DS is greater than +0.7 mm, contact between the light guide **141** and the electrically conducting lines **451** is avoided, but there is a possibility of insufficient efficiency of use of the blue light LB emitted from the light emitting device **121** and introduced into the light guide **141**. When the distance DS is smaller than -0.7 mm, there is a possibility of insufficiently homogenized illuminance distribution of the blue light LB at the light exiting end **141b** of the light guide **141**.

[0111] FIG. 4 is a side view of the light source **402** and the light guide **142** of the green light outputting section **102** in the projector **301** according to the present embodiment. The green light outputting section **102** is configured in the same manner as the blue light outputting section **101** except for the configuration of the light emitting device.

[0112] Electrodes **421** and **422** are provided at a +D2-side plate surface **112a** of the substrate **112** in the light source **402**, as shown in FIG. 4. The electrodes **421** and **422** are disposed in different regions of the plate surface **112a**. The number and the shapes of the electrodes provided at the plate surface **112a** of the substrate **112** are not limited to a specific number and specific shapes, and are appropriately set in accordance with the specifications, the shape, and other factors of the light emitting device **122**. FIG. 4 shows two electrodes **421** and **422** by way of example. The electrodes including the electrodes **421** and **422** and provided at the plate surface **112a** are part of the base of the light source **402**. The electrodes **421** and **422** are formed at the plate surface **112a**, for example, by a printing-based fine electrode patterning technology.

[0113] The light emitting device **122** is disposed, for example, at a +D2-side surface **421a** of the electrode **421**. The light emitting device **122** includes a light emitter **125** and a phosphor **126**. The light emitter **125** has a light emission surface **125e**, via which excitation light exits toward the +D2 side. The light emission surface **125e** is a +D2-side surface of the light emitter **125** that is parallel to the plane containing the D1 and D3 directions. The excitation light output from the light emitter **125** is, for example, blue light having the blue wavelength band.

[0114] The light emitter **125** is electrically coupled to the electrode **421**. The light emitter **125** of the light emitting device **122** and the electrode **422** are electrically coupled to each other via electrically conducting lines **452** and are coupled to each other, for example, by wire bonding. The electrically conducting lines **452** correspond to a second electrically conducting line, and are, for example, wires formed by wire bonding. The electrically conducting lines **452** supply the light emitter **125** of the light emitting device **122** with electric power based on a desired voltage or current supplied from a power supply that is not shown but is electrically coupled to the electrodes **421** and **422**.

[0115] The electrically conducting lines **452** couple the +D2-side light emission surface **125e** of the light emitter **125** and a +D2-side surface **422a** of the electrode **422** to each other, and protrude and curve toward the +D2 side beyond the light emission surface **125e** and the surface **422a**. The number and arrangement of the electrically conducting lines **452** in the light source **402** are appropriately set in accordance with the specifications and shape of the light emitter **125** of the light emitting device **122**, the relative positional relationship between the light emitter **125** and the electrodes, the number and shapes of the electrodes, and other factors.

[0116] The phosphor **126** is disposed on the +D2 side of the light emitter **125**, and overlaps with the light emitter **125** in the D1 and D3 directions. For example, the phosphor **126** is layered on the +D2 side of the light emitter **125**. The phosphor **126** is excited by the excitation light emitted from the light emitter **125**, and emits the green light LG as fluorescence via a light emission surface **126e**. The type and material of the phosphor **126** are appropriately so selected that the phosphor **126** excited by the excitation light emitted from the light emitter **125** emits the green light LG having the green wavelength band. The phosphor **126**, which is excited by the excitation light

having the blue wavelength band to emit the green light LG, is, for example, a ceramic phosphor into which phosphor particles are sintered, and is a YAG (yttrium aluminum garnet) phosphor containing cerium (Ce) ions.

[0117] The phosphor **126** emits the green light LG via the +D2-side surface parallel to the D1 and D3 directions, the side surfaces parallel to the D1 and D2 directions, and the side surfaces parallel to the D2 and D3 directions. In the green light outputting section **102**, since the size of the phosphor **126** in the D1 and D3 directions is greater than the thickness of the phosphor **126** in the D2 direction, the +D2-side surface of the phosphor **126** that is parallel to the D1 and D3 directions is regarded as the light emission surface **126e** of the phosphor **126**. The light emission surface **126e** of the phosphor **126** constitutes the light emission surface **122e** of the light emitting device **122**.

[0118] The light emission surface **125e** of the light emitter **125** of the light emitting device **122** is located at a position shifted toward the +D2 side from the surface **422a** of the electrode **422**. The light emission surface **122e** of the light emitting device **122** is further shifted toward the +D2 side from the light emission surface **125e** of the light emitter **125**. The +D2-side end of the electrically conducting lines **452** is shifted toward the +D2 side from the light emission surface **125e** of the light emitter **125**, and is shifted, for example, toward the +D2 side from the light emission surface **121e** of the light emitting device **121**. The distance DT between the +D2-side end of the electrically conducting lines **452** and the light emission surface **122e** in the D2 direction, that is, the direction parallel to the optical axis of the green light LG emitted from the light emitting device **122** is greater than or equal to 0.0 mm but smaller than 0.7 mm, and may be smaller than the distance DT in the blue light outputting section **101**.

[0119] In the green light outputting section **102**, the distance DS between the +D2-side end of one or more of the electrically conducting lines **452** and the -D2-side light incident end **142a** of the light guide **142** in the D2 direction is at least smaller than the distance DT and is greater than or equal to 0.0 mm but smaller than or equal to 0.7 mm. The distance DS in the green light outputting section **102** corresponds to a second distance. In detail, the distances DT and DS are positive when the light incident end **142a** of the light guide **142** is shifted toward the +D2 side with respect to the light emission surface **122e** of the light emitting device **122**, while being negative when the light incident end **142a** is shifted toward the -D2 side with respect to the light emission surface **122e**. In the configuration of the green light outputting section **102** shown in FIGS. **1** and **4** by way of example, the distance DS is greater than 0.0 mm but smaller than or equal to +0.7 mm. When the distance DS is greater than +0.7 mm, there is a possibility of insufficient efficiency of use of the green light LG emitted from the light emitting device **122** and introduced into the light guide **142**. When the distance DS is smaller than -0.7 mm, there is a possibility of insufficiently homogenized illuminance distribution of the green light LG at the light exiting end **142b** of the light guide **142**.

[0120] In the green light outputting section **102**, the distance DS is greater than 0.0 mm but smaller than or equal to +0.7 mm in the portion facing the light incident end **142a** of the light guide **142** that faces the electrically conducting lines **452** in the D2 direction. The portion facing the light incident end **142a** that faces the electrically conducting lines **452** in the D2 direction is a portion that is shifted toward the +D2 side from the electrically conducting lines **452** and overlaps with the electrically conducting lines **452** in the directions D1 and D3.

[0121] FIG. **5** is a side view of the light source **403** and the light guide **143** of the red light outputting section **103** in the projector **301** according to the present embodiment. The red light outputting section **103** is configured in the same manner as the blue light outputting section **101**.

[0122] Electrodes **431** and **432** are provided at a -D1-side plate surface **113a** of the substrate **113** in the light source **403**, as shown in FIG. **5**. The electrodes **431** and **432** are disposed in different regions of the plate surface **113a**. The number and the shapes of the electrodes provided at the plate surface **113a** of the substrate **113** are not limited to a specific number and specific shapes, and are appropriately set in accordance with the specifications, the shape, and other factors of the light emitting device **123**. FIG. **5** shows two electrodes **431** and **432** by way of example. The electrodes

including the electrodes **431** and **432** and provided at the plate surface **113a** are part of the base of the light source **403**. The electrodes **431** and **432** are formed at the plate surface **113a**, for example, by a printing-based fine electrode patterning technology.

[0123] The light emitting device **123** is disposed, for example, at a $-D1$ -side surface **431a** of the electrode **431**, and is electrically coupled to the electrode **431**. The light emitting device **123** and the electrode **432** are electrically coupled to each other by electrically conducting lines **453** and are coupled to each other, for example, by wire bonding. The electrically conducting lines **453** correspond to a third electrically conducting line, and are, for example, wires formed by wire bonding. The electrically conducting lines **453** supply the light emitting device **123** with electric power based on a desired voltage or current supplied from a power supply that is not shown but is electrically coupled to the electrodes **431** and **432**.

[0124] The electrically conducting lines **453** couple a $-D1$ -side light emission surface **123e** of the light emitting device **123** and a $-D1$ -side surface **432a** of the electrode **432** to each other, and protrude and curve toward the $+D1$ side beyond the light emission surface **123e** and the surface **432a**. The number and arrangement of the electrically conducting lines **453** in the light source **403** are appropriately set in accordance with the specifications and shape of the light emitting device **123**, the relative positional relationship between the light emitting device **123** and the electrodes, the number and shapes of the electrodes, and other factors.

[0125] The light emission surface **123e** of the light emitting device **123** is shifted toward the $-D1$ side from the surface **432a** of the electrode **432**. The $-D1$ side end of the electrically conducting lines **453** is shifted toward the $-D1$ side from the light emission surface **123e** of the light emitting device **123**. The distance **DT** between the $-D1$ -side end of the electrically conducting lines **453** and the light emission surface **123e** in the $D1$ direction, that is, the direction parallel to the optical axis of the red light **LR** emitted from the light emitting device **123** is greater than or equal to 0.0 mm but smaller than 0.7 mm.

[0126] In the red light outputting section **103**, the distance **DS** between the $-D1$ -side end of one or more of the electrically conducting lines **453** and the $+D1$ -side light incident end **143a** of the light guide **143** in the $D1$ direction is at least smaller than the distance **DT** and is greater than or equal to 0.0 mm but smaller than or equal to 0.7 mm. The distance **DS** in the red light outputting section **103** corresponds to a third distance. In detail, the distances **DT** and **DS** are positive when the light incident end **143a** of the light guide **143** is shifted toward the $-D1$ side with respect to the light emission surface **123e** of the light emitting device **123**, and while being negative when the light incident end **143a** is shifted toward the $+D1$ side with respect to the light emission surface **123e**. In the configuration of the red light outputting section **103** shown in FIG. 5 by way of example, the distance **DS** is greater than 0.0 mm but smaller than or equal to +0.7 mm. When the distance **DS** is greater than +0.7 mm, there is a possibility of insufficient efficiency of use of the red light **LR** emitted from the light emitting device **123** and introduced into the light guide **143**. When the distance **DS** is smaller than -0.7 mm, there is a possibility of insufficiently homogenized illuminance distribution of the red light **LR** at the light exiting end **143b** of the light guide **143**.

[0127] In the red light outputting section **103**, the distance **DS** is greater than 0.0 mm but smaller than or equal to +0.7 mm in the portion facing the light incident end **143a** of the light guide **143** that faces the electrically conducting lines **453** in the $D1$ direction. The portion facing the light incident end **143a** that faces the electrically conducting lines **453** in the $D1$ direction is a portion that is shifted toward the $-D1$ side from the electrically conducting lines **453** and overlaps with the electrically conducting lines **453** in the directions $D2$ and $D3$.

[0128] In the projector **301** according to the present embodiment, the light emitting device **122** of the green light outputting section **102** includes the light emitter **125** and the phosphor **126**, and at least one of the light emitting device **121** of the blue light outputting section **101** and the light emitting device **123** of the red light outputting section **103** may include a light emitter that radiates excitation light and a phosphor excited by the excitation light to emit color light. Instead, the light

emitting device **122** of the green light outputting section **102** may not include a phosphor but include only a light emitter such as an LED.

[0129] Setting the absolute value of the distance DS at 0.7 mm or smaller in the present embodiment can preferably suppress a decrease in light use efficiency, and prevent disconnection of the wires that couple the light emitting device to the electrode in each of the light sources and a short circuit in the light source. Note that setting the absolute value of the distance DS at 0.5 mm or smaller can provide light use efficiency of 80% or higher. It is therefore more preferable that the absolute value of the distance DS is set at 0.5 mm or smaller. The dimension of 0.7 mm or 0.5 mm presented as the preferable upper limit of the absolute value of the distance DS by way of example is calculated by numerical calculation in consideration of the dimensions and relative arrangement of the light source and the light guide in each of the color light outputting sections.

[0130] The projector **301** according to the present embodiment described above includes the light source (first light source) **401**, the light guide (first light guide) **141**, the parallelizing element (first parallelizing element) **161**, the light modulator (first light modulator) **181**, and the projection system **250**. The light source **401** includes the light emitting device (first light emitting device) **121**, the electrically conducting lines (first electrically conducting line) **451**, and the substrate (base) **111**. The light emitting device **121** outputs the blue light (first light) LB having the blue wavelength band (first wavelength band). The electrically conducting lines **451** supply the light emitting device **121** with electric power. The substrate **111** and the electrodes (base) **411** and **412** support the light emitting device **121** and the electrically conducting lines **451** from the $-D1$ side. The light guide **141** has the light incident end (first light incident end) **141a** and the light exiting end (first light exiting end) **141b**, and homogenizes the illuminance of the incident blue light LB in the plane containing the D2 and D3 directions (in-plane illuminance). The blue light LB output from the light source **401** is incident on the light incident end **141a** and enters the light guide **141** via the light incident end **141a**. The blue light LB guided in the light guide **141** toward the $+D1$ side in the D1 direction exits via the light exiting end **141b**. That is, the light exiting end **141b** causes the blue light LB to exit. The parallelizing element **161** parallelizes the blue light LB output from the light guide **141**. The light modulator **181** modulates the blue light LB output from the parallelizing element **161** based on image information. The projection system **250** projects the image light (light) IB output from the light modulator **181**. In the projector **301** according to the present embodiment, the light guide **141** is disposed away from the electrically conducting lines **451** in the light source **401** in the D1 direction. In the projector **301** according to the present embodiment, the distance (first distance) DS between the light incident end **141a** of the light guide **141** and the light emission surface **121e** of the light emitting device **121** of the light source **401** is greater than or equal to -0.7 mm but smaller than or equal to 0.7 mm, specifically, greater than 0.0 mm but smaller than or equal to $+0.7$ mm.

[0131] In the projector **301** according to the present embodiment, the light incident end **141a** of the light guide **141** and the light emission surface **121e** of the light emitting device **121** of the light source **401** are separate from each other by an appropriate distance in the D1 direction, so that contact between the light guide **141** and the electrically conducting lines **451** is avoided, and a short circuit or disconnection in the light source **401** is avoided. In addition, the configuration in which the light incident end **141a** of the light guide **141** and the light emission surface **121e** of the light emitting device **121** of the light source **401** are separate from each other by an appropriate distance in the D1 direction suppresses the amount of the blue light LB that is output from the light source **401** but leaks via a portion outside the light incident end **141a** of the light guide **141** in the plane containing the D2 and D3 directions, and therefore ensures a certain amount of the blue light LB introduced into the light guide **141** via the light incident end **141a**. The projector **301** according to the present embodiment can therefore prevent disconnection of the electrically conducting lines **451**, which couple the light emitting device **121** to the electrode **412** in the light source **401**, and a short circuit in the light source **401** while suppressing a decrease in the light use efficiency.

[0132] In the projector **301** according to the present embodiment, the cross-sectional shape of the light guide **141** that intersects with the D1 direction, that is, the shape of the light guide **141** in the plane containing the D2 and D3 directions is a quadrangular shape.

[0133] The projector **301** according to the present embodiment, in which the blue light LB having a quadrangular shape and a homogenized illuminance distribution in the plane containing the D2 and D3 directions exits via the light exiting end **141b** of the light guide **141**, can readily generate illumination light having a quadrangular shape and a homogenized illuminance distribution.

[0134] In the projector **301** according to the present embodiment, the green light outputting section **102** and the red light outputting section **103** are configured in the same manner as the blue light outputting section **101**. The projector **301** according to the present embodiment further includes the light source (second light source) **402**, the light source (third light source) **403**, the light guide (second light guide) **142**, the light guide (third light guide) **143**, the parallelizing element (second parallelizing element) **162**, the parallelizing element (third parallelizing element) **163**, the light modulator (second light modulator) **182**, and the light modulator (third light modulator) **183**.

[0135] The light source **402** includes the light emitting device (second light emitting device) **122**, the electrically conducting lines (second electrically conducting lines) **452**, and the substrate (base) **112**. The light emitting device **122** outputs the green light (second light) LG having the green wavelength band (second wavelength band). The electrically conducting lines **452** supply the light emitting device **122** with electric power. The substrate **112** and the electrodes (base) **421** and **422** support the light emitting device **122** and the electrically conducting lines **452** from the -D2 side. The light guide **142** has the light incident end (second light incident end) **142a** and the light exiting end (second light exiting end) **142b**, and homogenizes the illuminance of the incident green light LG in planes containing the D1 and D3 directions (in-plane illuminance). The green light LG output from the light source **402** is incident on the light incident end **142a** and enters the light guide **142** via the light incident end **142a**. The green light LG guided in the light guide **142** toward the +D2 side in the D2 direction exits via the light exiting end **142b**. That is, the light exiting end **142b** causes the green light LG to exit. The parallelizing element **162** parallelizes the green light LG output from the light guide **142**. The light modulator **182** modulates the green light LG output from the parallelizing element **162** based on image information.

[0136] The light source **403** includes the light emitting device (third light emitting device) **123**, the electrically conducting lines (third electrically conducting lines) **453**, and the substrate (base) **113**. The light emitting device **123** outputs the red light (third light) LR having the red wavelength band (third wavelength band). The electrically conducting lines **453** supply the light emitting device **123** with electric power. The substrate **113** and the electrodes (base) **431** and **432** support the light emitting device **123** and the electrically conducting lines **453** from the +D1 side. The light guide **143** has the light incident end (third light incident end) **143a** and the light exiting end (third light exiting end) **143b**, and homogenizes the illuminance of the incident red light LR in the plane containing the D2 and D3 directions (in-plane illuminance). The red light LR output from the light source **403** is incident on the light incident end **143a** and enters the light guide **143** via the light incident end **143a**. The red light LR guided in the light guide **143** toward the -D1 side in the D1 direction exits via the light exiting end **143b**. That is, the light exiting end **143b** causes the red light LR to exit. The parallelizing element **163** parallelizes the red light LR output from the light guide **143**. The light modulator **183** modulates the red light LR output from the parallelizing element **163** based on image information. The projection system **250** projects the image light (light) IB, IG, and IR output from the light modulators **181**, **182**, and **183**, respectively.

[0137] The three-plate projector **301** according to the present embodiment can prevent the disconnection of the electrically conducting lines **451**, **452**, and **453** and short circuits in the light sources **401**, **402**, and **403** while suppressing a decrease in light use efficiency in each of the color light outputting sections, which output the multiple types of light having the three primary colors.

[0138] A first variation of the present embodiment will next be described. In the following

variations, elements common to those of the blue light outputting section **101**, the green light outputting section **102**, and the red light outputting section **103** of the projector **301** according to the embodiment described above have the same reference characters, and only the contents different from the configurations of the color light outputting sections will be described. In each of the variations, one of the blue light outputting section **101**, the green light outputting section **102**, and the red light outputting section **103** is shown by way of example, and configurations common to those of the color light outputting sections will be described.

First Variation

[0139] FIG. **6** is a side view of the light source **401** and the light guide **141** of a blue light outputting section **501** according to a first variation of the present embodiment, the side view viewed along the D3 direction. FIG. **7** is a side view of the light source **401** and the light guide **141** of the blue light outputting section **501**, the side view viewed along the D2 direction.

[0140] In the blue light outputting section **501**, when viewed along the D1 direction, the electrode **411** overlaps the light emitting device **121** in a plane containing the D2 and D3 directions, and has a shape and a size that are substantially the same as those of the light emitting device **121**, as shown in FIGS. **6** and **7**. The total height of the electrode **411** and the light emitting device **121** in the D1 direction is smaller than or equal to 0.7 mm. The electrode **412** is disposed at a position shifted toward the -D2 side from the electrode **411**.

[0141] In the blue light outputting section **501**, a cutout **A141** is formed in a sidewall having the side surface **141s** that overlaps with the region occupied by the electrically conducting lines **451** in the D1 direction out of the four side surfaces **141s** of the light guide **141**. The cutout **A141** is an opening starting from the light incident end **141a** of the light guide **141**, is recessed in the D1 direction from the position of the light incident end **141a**, which is the -D1-side end position thereof, toward the +D1 side to the depth equal to the distance DS. That is, in the blue light outputting section **501**, the cutout **A141** is formed at a location where the cutout **A141** faces the electrically conducting lines **451** at the light incident end **141a** of the light guide **141**.

[0142] Since the depth of the cutout **A141** in the D1 direction is equal to the distance DS, the portion of the light incident end **141a** that does not face the electrically conducting lines **451** is in contact with the +D1-side plate surface **111a** of the substrate **111**. The portion of the light incident end **141a** that does not face the electrically conducting lines **451** is disposed below the plate surface **111a** at a depth deeper than 0 mm but shallower than -0.7 mm. When viewed along the D1 direction, the electrode **411** overlaps with the light incident end **141a** of the light guide **141**, is contained in the light incident end **141a**, and is surrounded by the sidewalls of the light guide **141**. When viewed along the D1 direction, the cutout **A141** intersects with the electrically conducting lines **451**. The electrically conducting lines **451** pass through the cutout **A141** along the D2 direction.

[0143] The depth of the cutout **A141** in the D1 direction is equal to the distance DS, is greater than or equal to 0.1 mm but smaller than or equal to 0.7 mm, preferably, greater than or equal to 0.3 mm but smaller than or equal to 0.7 mm. The size or width of the cutout **A141** in the D3 direction is greater than the region occupied by one or more electrically conducting lines **451** in the D3 direction by a value greater than 0 mm but smaller than or equal to 0.7 mm toward the -D3 and +D3 sides. The plate-shaped member that forms a sidewall of the light guide **141** and faces the electrically conducting lines **451** is thus separate from the electrically conducting lines **451**.

[0144] The projector according to the first variation of the present embodiment described above can provide the same advantages and effects provided by the configurations common to those of the projector according to the present embodiment.

[0145] In the projector according to the first variation of the present embodiment, the light guide **141** is in contact with the light source **401** while being separate from the electrically conducting lines **451**. That is, a portion of the light incident end **141a** of the light guide **141** of the blue light outputting section **501** is separate from the electrically conducting lines **451**, and the substrate **111**

and the base other than the substrate **111** of the light source **401**, and the remainder of the light incident end **141a** is in contact with the substrate **111**.

[0146] In the projector according to the first variation of the present embodiment, the distance DS in the D1 direction between the light incident end **141a** other than the portion where the cutout **A141** is formed at the light incident end **141a** of the light guide **141** and the light emission surface **121e** of the light emitting device **121** of the light source **401** is greater than or equal to -0.7 mm but smaller than 0 mm. In the projector according to the first variation of the present embodiment, the shortest distance DS between the light incident end **141a** of the light guide **141** and the light emission surface **121e** of the light emitting device **121** is shorter than that in the projector **301** according to the present embodiment, so that the blue light LB emitted from the light emitting device **121** of the light source **401** can be introduced into the light guide **141** at increased efficiency.

[0147] In the projector according to the first variation of the present embodiment, the cutout **A141** is formed at a portion of (position at) the light guide **141** where the cutout **A141** faces the electrically conducting lines **451**. The electrically conducting lines **451** are inserted into the region inside (interior of) the light incident end **141a** through the cutout **A141** from the region above the substrate **111** outside the light incident end **141a** (exterior thereof) in the D2 and D3 directions.

[0148] In the projector according to the first variation of the present embodiment, the cutout **A141** prevents contact between the light guide **141** and the electrically conducting lines **451**, and minimizes a decrease in the light guide **141** around the light emitting device in the light source **401** and the amount of the blue light LB that leaks via a portion outside the light incident end **141a** of the light guide **141**. The projector according to the first variation of the first embodiment allows the blue light LB output from the light emitting device **121** to be introduced into the light guide **141** at increased efficiency.

[0149] In the projector according to the first variation of the present embodiment, the dimension of the cutout **A141** in the direction in which the blue light LB from the light source **401** exits, that is, the D1 direction is greater than or equal to 0.1 mm but smaller than or equal to 0.7 mm.

[0150] In the projector according to the first variation of the present embodiment, to avoid contact with the electrically conducting lines **451**, the dimension of the cutout **A141** can be minimized, and the loss of the blue light LB can be minimized.

[0151] Although not shown, as long as the portion of the light incident end **141a** of the plate-shaped members of the light guide **141** that extends in parallel to the D3 direction and corresponds to the cutout **A141** is separate from the electrically conducting lines **451** as described above, the portion of the light incident end **141a** of the plate-shaped members of the light guide **141** where the cutout **A141** is not formed may be separate from the plate surface **111a** of the substrate **111** and may be shifted toward the +D1 side from the plate surface **111a**. In this case, the depth of the cutout **A141** in the D1 direction may be the distance DS from which the distance in the D1 direction between the plate surface **111a** and the portion of the light incident end **141a** where the cutout **A141** is not formed is subtracted.

[0152] Furthermore, a through hole that is not open toward the $-D1$ side, unlike the cutout **A141**, may be formed in the portion of the plate-shaped members of the light guide **141** that faces the electrically conducting lines **451** in place of the cutout **A141**. Also in this case, the electrically conducting lines **451** pass through the through hole along the D3 direction, and couples the light emitting device **121** and the electrode **412** to each other.

[0153] In the projector according to the first variation of the present embodiment, when a cutout is formed in each of the green and red light outputting sections, as the cutout **A141** formed in the light guide **141** of the blue light outputting section **501**, the same advantages and effects provided by the blue light outputting section **501** can be provided by the green and red light outputting sections.

[0154] Note that all of the light emitting device **121**, the electrodes **411** and **412**, and the one or more electrically conducting lines **451** may be surrounded by the light incident end **141a** of the

light guide **141** and may not be in contact with the light incident end **141a** in the blue light outputting section **501** when viewed along the D1 direction. In this case, the cutout **A141** may not be formed in the light guide **141**. In this case as well, the light guide **141** is in contact with the substrate **111** of the light source **401** while being separate from the electrically conducting lines **451**. That is, the entire light incident end **141a** of the light guide **141** of the blue light outputting section **501** is in contact with the plate surface **111a** of the substrate **111**.

[0155] According to the projector having the configuration described above, the distance DS between the light incident end **141a** of the light guide **141** and the light emission surface **121e** of the light emitting device **121** is greater than or equal to -0.7 mm but smaller than 0 mm, and is therefore appropriately ensured, as in the projector **301** according to the present embodiment, so that the blue light LB emitted from the light emitting device **121** of the light source **401** can be introduced into the light guide **141** at increased efficiency.

Second Variation

[0156] FIG. **8** is a side view of the light source **402** and the light guide **142** of a green light outputting section **502** according to a second variation of the present embodiment, the side view viewed along the D3 direction. FIG. **9** is a plan view of the light source **402** and the light guide **142** of the green light outputting section **502**, the plan view viewed along the D2 direction. In the second variation of the present embodiment, the light source **402** of the green light outputting section **502** corresponds to the first light source, the light emitting device **122** corresponds to the first light emitting device, the green light LG corresponds to the first light, the electrically conducting lines **452** correspond to the first electrically conducting line, and the light guide **142** corresponds to the first light guide.

[0157] In the green light outputting section **502**, a sidewall **456** is provided at an outer circumferential portion of the plate surface **112a** of the substrate **112**, as shown in FIGS. **8** and **9**. The sidewall **456** extends from the plate surface **112a** toward the +D2 side, and is formed outside the light emitting device **122**, the electrodes **421** and **422** and the electrically conducting lines **452** when viewed along the D2 direction. The +D2-side end surface of the sidewall **456** is shifted toward the +D2 side from the light emission surface **122e** of the light emitting device **122**. A sealing member **460** is filled in the region inside the sidewall **456** and the region outside the light emitting device **122** in planes containing the D1 and D3 directions. The sealing member **460** is contained in the base of the light source **402**.

[0158] The +D2-side surface of the sealing member **460** is flush with the light emission surface **122e** of the light emitting device **122** in the D2 direction. The +D2-side surface and the side surfaces of each of the electrodes **421** and **422**, the side surfaces of the light emitter **125**, and the electrically conducting lines **452** are covered with the sealing member **460**. The electrodes **421** and **422** and the electrically conducting lines **452** are embedded in the sealing member **460**. The light emission surface **122e** of the light emitting device **122** is exposed out of the sealing member **460**. The sealing member **460** is an insulating member or an insulator and is made, for example, of resin that transmits visible light containing the blue light LB, the green light LG, and the red light LR.

[0159] In the green light outputting section **502**, the light incident end **142a** of the light guide **142** is in contact with the sealing member **460**. The distance DS in the D2 direction between the light incident end **142a** of the light guide **142** and the light emission surface **122e** of the light emitting device **122** is greater than or equal to 0 mm but smaller than or equal to 0.7 mm, specifically, about 0 mm. Since the light incident end **142a** is in contact with the +D2-side surface of the sealing member **460**, the light guide **142** is supported by the sealing member **460** from the -D2 side.

[0160] The projector according to the second variation of the present embodiment described above can provide the same advantages and effects provided by the configurations common to those of the projector according to the present embodiment.

[0161] In the projector according to the second variation of the present embodiment, the base of the light source (first light source) **402** of the green light outputting section **102** includes the sealing

member **460**, which covers the electrically conducting lines (first electrically conducting line) **452**. The sealing member **460** is an insulating member. The light incident end **142a** of the light guide **142** is in contact with the sealing member **460** in the D2 direction.

[0162] In the projector according to the second variation of the present embodiment, the insulating sealing member **460** is interposed between the light emitting device (first light emitting device) **122** and the light guide (first light guide) **142**. The projector according to the second variation of the present embodiment can more reliably prevent disconnection of the electrically conducting lines **452** and use the green light LG at increased efficiency.

[0163] In the projector according to the second variation of the present embodiment, the light source **402** includes light divergence sections **482**, which cause the green light LG to diverge. The light divergence sections **482** are disposed on the +D2 side of the light emitting device **122**, that is, on the side thereof via which the green light (first light) LG exits. Specifically, the light divergence sections **482** have a +D2-side end surface of the phosphor **126** of the light emitting device **122** that is parallel to the plane containing the D1 and D3 directions, that is, the light emission surface **122e**, the side surfaces of the phosphor **126** that are parallel to a plane containing the D1 and D2 directions, and the side surfaces of the phosphor **126** that are parallel to the plane containing the D2 and D3 directions. The sealing member **460** supports the circumference of the light divergence sections **482** when viewed in the D2 direction. Specifically, in the planes containing the D1 and D3 directions, the sealing member **460** surrounds the side surfaces of the light emitter **125** and the phosphor **126** of the light emitting device **122**, and is in contact with the side surfaces of the light emitter **125** and the phosphor **126** from the side facing the outer circumference thereof.

[0164] In the projector according to the second variation of the present embodiment, the configuration of the light divergence sections **482** can be simplified, and the light emitting device **122** and the light divergence sections **482** are supported by the sealing member **460**, so that the durability of the light emitting device **122** can be enhanced. Furthermore, in the projector according to the second variation of the present embodiment, since the light emission surface **122e** of the light emitting device **122** is located near the light incident end **142a** of the light guide **142** in the D2 direction, the green light LG can be used at increased efficiency.

[0165] In the projector according to the second variation of the present embodiment, when the blue and red light outputting sections are configured in the same manner as the green light outputting section **502**, the same advantages and effects provided by the green light outputting section **502** can be provided by the blue and red light outputting sections.

Third Variation

[0166] FIG. **10** is a side view of the light source **401** and the light guide **141** of a blue light outputting section **503** according to a third variation of the present embodiment, the side view viewed along the D3 direction.

[0167] In the blue light outputting section **503**, the entire light incident end **141a** of the light guide **141** is parallel to the plate surface **111a** of the substrate **111** of the light source **401** and the light emission surface **121e** of the light emitting device **121**, and is parallel to the plane containing the D2 and D3 directions, as shown in FIG. **10**. When viewed along the D1 direction, all the electrodes including the electrodes **411** and **412**, the light emitting device **121**, and the electrically conducting lines **451** are surrounded by the light incident end **141a** of the light guide **141**.

[0168] In the blue light outputting section **503**, the angles of the four side surfaces **141s** of the light guide **141** with respect to an axis parallel to the D1 direction may differ from each other in accordance with the relative arrangement of the electrodes **411** and **412** at the plate surface **111a** of the substrate **111**. For example, the light guide **141** tapers from the light exiting end **141b** toward the light incident end **141a**, and when viewed along the D1 direction, the four side surfaces **141s** of the light guide **141** approach the center of the plate surface **111a** of the substrate **111** as the four side surfaces **141s** extend from the light exiting end **141b** toward the light incident end **141a**. Out of the four side surfaces **141s** of the light guide **141**, the angles of the two side surfaces **141s** facing

each other in the D3 direction with respect to the axis parallel to the D1 direction are equal to each other, and the angles of the remaining two side surfaces **141s** facing each other in the D2 direction with respect to the axis parallel to the D1 direction differ from each other. Out of the two side surfaces **141s** facing each other in the D2 direction, the angle of the -D2-side side surface **141s** with respect to the axis parallel to the D1 direction is smaller than the angle of the +D2-side side surface **141s** with respect to the axis parallel to the D1 direction.

[0169] The projector according to the third variation of the present embodiment described above can provide the same advantages and effects provided by the configurations common to those of the projector according to the present embodiment.

[0170] In the projector according to the third variation of the present embodiment, in a plan view viewed along the direction in which the blue light LB from the light source **401** exits, that is, the D1 direction, the light incident end **141a** of the light guide **141** includes the light emitting device **121** and the electrically conducting lines **451** in the light source **401**, and surrounds the light emitting device **121** and the electrically conducting lines **451** in the light source **401**.

[0171] In the projector according to the third variation of the present embodiment, the light incident end **141a** of the light guide **141** has a size large enough to surround the light emitting device **121** and the electrically conducting lines **451**, so that contact between the electrically conducting lines **451** and the light guide **141** can be avoided even when external impact acts on the projector and the light guide **141** therefore vibrates. The projector according to the third variation of the present embodiment can more reliably prevent disconnection of the electrically conducting lines **451** and a short circuit in the light source **401**.

[0172] In the projector according to the third variation of the present embodiment, when the green and red light outputting sections are configured in the same manner as the blue light outputting section **503**, the same advantages and effects provided by the blue light outputting section **503** can be provided by the green and red light outputting sections.

[0173] In the projector according to the present embodiment and the first to third variations thereof, the light guides **141**, **142**, and **143** are each a hollow member. The internal space SP**141**, which tapers from the light exiting end **141b** toward the light incident end **141a**, is formed in the light guide **141**. The internal space SP**142**, which tapers from the light exiting end **142b** toward the light incident end **142a**, is formed in the light guide **142**. The internal space SP**143**, which tapers from the light exiting end **143b** toward the light incident end **143a**, is formed in the light guide **143**.

[0174] In the projector according to the present embodiment and the first to third variations thereof, a decrease in the efficiency of use of the blue light LB introduced into the light guide **141** can be suppressed, a decrease in the efficiency of use of the green light LG introduced into the light guide **142** can be suppressed, and a decrease in the efficiency of use of the red light LR introduced into the light guide **143** can be suppressed.

[0175] In the projector according to the third variation of the present embodiment, when the green and red light outputting sections are configured in the same manner as the blue light outputting section **503**, the same advantages and effects provided by the blue light outputting section **503** can be provided by the green and red light outputting sections.

Fourth Variation

[0176] FIG. **11** is a side view of the light source **401** and the light guide **141** of a blue light outputting section **504** according to a fourth variation of the present embodiment, the side view viewed along the D3 direction. FIG. **12** is a plan view of the light source **401** and the light guide **141** of the blue light outputting section **504**, the plan view viewed along the D1 direction.

[0177] In the blue light outputting section **504**, the entire light incident end **141a** of the light guide **141** is parallel to the plate surface **111a** of the substrate **111** and the light emission surface **121e** of the light emitting device **121** in the light source **401**, and is parallel to the plane containing the D2 and D3 directions, as shown in FIGS. **11** and **12**, as in the blue light outputting section **503**. When viewed along the D1 direction, all the electrodes including the electrodes **411** and **412**, the light

emitting device **121**, and the electrically conducting lines **451** are surrounded by the light incident end **141a** of the light guide **141**.

[0178] In the blue light outputting section **504**, the light guide **141** tapers from the light exiting end **141b** toward the light incident end **141a**, and when viewed along the D1 direction, the four side surfaces **141s** of the light guide **141** approach the center of the plate surface **111a** of the substrate **111** as the light guide **141** extends from the light exiting end **141b** toward a predetermined position shifted toward the +D1 side from the light incident end **141a**. Irrespective of the relative arrangement of the electrodes **411** and **412** at the plate surface **111a** of the substrate **111**, out of the four side surfaces **141s** of the light guide **141**, the angles of the two side surfaces **141s** facing each other in the D3 direction with respect to the axis parallel to the D1 direction from the light exiting end **141b** to the light incident end **141a** are equal to each other.

[0179] Out of the two side surfaces **141s** facing each other in the D2 direction out of the four side surfaces **141s** of the light guide **141**, the angle of the +D2-side side surface **141s** with respect to the axis parallel to the D1 direction from the light exiting end **141b** to the light incident end **141a** is equal to the angle of the -D2-side side surface **141s** with respect to the axis parallel to the D1 direction from the light exiting end **141b** to the predetermined position shifted toward the +D1 side from the light incident end **141a**. The aforementioned predetermined position shifted from the light incident end **141a** in the D1 direction falls within the range of the distance DS from the position of the light emission surface **121e** of the light emitting device **121**. Out of the two side surfaces **141s** facing each other in the D2 direction, the plate-shaped member having the -D2-side side surface **141s** has a protrusion **247**, which protrudes from the predetermined position toward the -D2 side along the -D2-side portions of the electrically conducting lines **451** and the electrode **412**. The reflection surface **141r** of the protrusion **247** is shifted toward the +D1 side in the D1 direction by the distance DS away from the light emission surface **121e** of the light emitting device **121**, and is located at the distance DS from the region occupied by the one or more electrically conducting lines **451** and the electrode **412** in a plane containing the D2 and D3 directions.

[0180] The reflection surface **141r** of the protrusion **247** of the light guide **141**, which faces the electrically conducting lines **451** in the D1 direction, is parallel to the plane containing the D2 and D3 directions. The reflection surface **141r** of the protrusion **247**, which faces the electrically conducting lines **451** and is shifted toward the -D2 side from the electrically conducting lines **451** in the D2 direction, is parallel to the plane containing the D1 and D3 directions. The reflection surfaces **141r** of the protrusion **247**, which face the electrically conducting lines **451** and are shifted toward the -D3 and +D3 sides from the electrically conducting lines **451** in the D3 direction, are parallel to the plane containing the D1 and D2 directions. In the blue light outputting section **504**, since the light guide **141** includes the protrusion **247** facing the electrically conducting lines **451**, disconnection of the electrically conducting lines **451** and a short circuit in the light source **401** are avoided.

[0181] The light guide **141** is a hollow member and has a first side surface **141S1**, a second side surface **141S2**, a third side surface **141S3**, and a fourth side surface **141S4**, which face the internal space SP**141** into which the blue light LB is guided, as shown in FIG. **12**. The first side surface **141S1** is configured with a main body and the -D3-side reflection surface **141r** out of the reflection surfaces **141r** of the protrusion **247**, the main body and the protrusion **247** facing each other in the D3 direction, extends along the D2 direction, and reflects the incident blue light LB. The second side surface **141S2** is configured with a -D2-side side surface **247s** out of the reflection surfaces **141r** that face with each other in the D2 direction, extends along the D3 direction, and reflects the incident blue light LB. The third side surface **141S3** is configured with the +D3-side reflection surface **141r** out of the reflection surfaces **141r** that face with each other in the D3 direction, extends along the D2 direction, and reflects the incident blue light LB. The fourth side surface **141S4** is configured with the +D2-side reflection surface **141r** out of the reflection surfaces **141r** that face with each other in the D2 direction, extends along the D3 direction, and reflects the

incident blue light LB.

[0182] A distance DP3 between the region occupied by the one or more electrically conducting lines **451** and the first side surface **141S1** in the D3 direction is greater than or equal to 0.1 mm but smaller than or equal to 1.0 mm. A distance DP2 between the region occupied by the electrically conducting lines **451** and the second side surface **141S2** in the D2 direction is greater than or equal to 0.1 mm but smaller than or equal to 1.0 mm. Another distance DP3 between the region occupied by the electrically conducting lines **451** and the third side surface **141S3** in the D3 direction is greater than or equal to 0.1 mm but smaller than or equal to 1.0 mm.

[0183] The projector according to the fourth variation of the present embodiment described above can provide the same advantages and effects provided by the configurations common to those of the projector according to the present embodiment.

[0184] In the projector according to the fourth variation of the present embodiment, in the plan view viewed along the direction in which the blue light LB from the light source **401** exits, that is, the D1 direction, the light incident end **141a** of the light guide **141** includes the light emitting device **121** and the electrically conducting lines **451** in the light source **401** and surrounds the light emitting device **121** and the electrically conducting lines **451** in the light source **401**.

[0185] In the projector according to the fourth variation of the present embodiment, the light incident end **141a** of the light guide **141** has a size large enough to surround the light emitting device **121** and the electrically conducting lines **451**, so that contact between the electrically conducting lines **451** and the light guide **141** can be avoided even when external impact acts on the projector and the light guide **141** therefore vibrates. The projector according to the fourth variation of the present embodiment can more reliably prevent disconnection of the electrically conducting lines **451** and a short circuit in the light source **401**.

[0186] In the projector according to the fourth variation of the present embodiment, the internal space SP**141** of the light guide **141** tapers from the light exiting end **141b** to the predetermined position between the light exiting end **141b** and the light incident end **141a** in D1 the direction.

[0187] In the projector according to the fourth variation of the present embodiment, a decrease in the efficiency of use of the blue light LB introduced into the light guide **141** can be reduced as compared with the decrease in the projector according to the third variation.

[0188] In the projector according to the fourth variation of the present embodiment, the light guide **141** has the first side surface **141S1**, the second side surface **141S2**, the third side surface **141S3**, and the fourth side surface **141S4**. The first side surface **141S1** extends in parallel to the D2 direction and reflects the incident blue light LB. The second side surface **141S2** is coupled to the first side surface **141S1** at right angles, extends in parallel to the D3 direction, and reflects the incident blue light LB. The third side surface **141S3** is coupled to the second side surface **141S2** at right angles, extends in parallel to the D2 direction, and reflects the incident blue light LB. The fourth side surface **141S4** is coupled to the third side surface **141S3** at right angles, extends in parallel to the D3 direction, and reflects the incident blue light LB. The electrically conducting lines **451** face the first side surface **141S1**, the second side surface **141S2**, and the third side surface **141S3**. The distance DP3 between the electrically conducting lines **451** and the first side surface **141S1** in the D3 direction is greater than or equal to 0.1 mm but smaller than or equal to 1.0 mm. The distance DP2 between the electrically conducting lines **451** and the second side surface **141S2** in the D2 direction is greater than or equal to 0.1 mm but smaller than or equal to 1.0 mm. Another distance DP3 between the region occupied by the electrically conducting lines **451** and the third side surface **141S3** in the D3 direction is greater than or equal to 0.1 mm but smaller than or equal to 1.0 mm.

[0189] In the projector according to the fourth variation of the present embodiment, the efficiency of use of the blue light LB output from the light source **401** and introduced into the light guide **141** can be increased, and the reliability of the light source **401** can be improved.

[0190] In the projector according to the fourth variation of the present embodiment, when the green

and red light outputting sections are configured in the same manner as the blue light outputting section **504**, the same advantages and effects provided by the blue light outputting section can be provided by the green and red light outputting sections.

Fifth Variation

[0191] FIG. **13** is a side view of the light guide **141** of a blue light outputting section according to a fifth variation of the present embodiment, the side view viewed along the D3 direction. An insulating layer **480** is provided on the -D1 side of the light incident end **141a** of the light guide **141**, as shown in FIG. **13**. The insulating layer **480** suppresses electrical conduction between the light guide **141** and the electrically conducting lines **451** in the light source **401**. The insulating layer **480** may be formed by using a known method to directly perform an insulating treatment on the light incident end **141a**, or by attaching a layer or a thin film made of an insulating material such as rubber to the light incident end **141a**.

[0192] The insulating layer **480** may be provided at the light incident end **141a** of the light guide **141**, the light incident end **142a** of the light guide **142**, and the light incident end **143a** of the light guide **143** of the projector **301** according to the present embodiment and the projector according to each of the first to fourth variations of the present embodiment.

[0193] In the projector according to the fifth variation of the present embodiment, the insulating layer **480** is interposed between the electrically conducting lines **451** and the light guide **141**, disconnection of the electrically conducting lines **451** and a short circuit in the light source **401** are more reliably avoided even when external impact acts on the projector.

Sixth Variation

[0194] Although not shown, in a projector according to a sixth variation of the present embodiment, the light guides **141**, **142**, and **143** are each a solid member, and may be made of a transparent insulating material such as an optical glass. In this case, plate surfaces of the reflectors constituting the light guides **141**, **142**, and **143** that face the space outside the reflectors, that is, the side surfaces **141s**, **142s**, and **143s** act as the reflection surfaces **141r**, **142r**, and **143r**.

[0195] The blue light LB output from the light source **401** enters the reflector constituting the light guide **141** via the light incident end **141a**. Part of the blue light LB having entered the light guide **141** is totally reflected off the reflection surfaces **141r** facing the space outside the reflector, and travels along the D1 direction and the optical axis. The green light LG output from the light source **402** enters the reflector constituting the light guide **142** via the light incident end **142a**. Part of the green light LG having entered the light guide **142** is totally reflected off the reflection surfaces **142r** facing the space outside the reflector, and travels along the D2 direction and the optical axis. The red light LR output from the light source **403** enters the reflector constituting the light guide **143** via the light incident end **143a**. Part of the red light LR having entered the light guide **143** is totally reflected off the reflection surfaces **143r** facing the space outside the reflector, and travels along the D1 direction and the optical axis.

[0196] The light guides **141**, **142**, and **143** may each be a solid element, and may be made of a transparent material such as optical glass, and the reflection films **251**, **252**, and **253** may be provided at the side surfaces **141s**, **142s**, and **143s**, respectively.

[0197] In the projector according to the sixth variation of the present embodiment, the light guides **141**, **142**, and **143** are made of an insulating material.

[0198] The projector according to the sixth variation of the present embodiment allows reduction in losses of the blue light LB, the green light LG, and the red light LR inside the light guides **141**, **142**, and **143**.

[0199] A preferable embodiment of the present disclosure has been described above in detail. The present disclosure is, however, not limited to a specific embodiment, and various modifications and changes can be made to the embodiment within the scope of the gist of the present disclosure described in the claims. The configurations of the embodiment and the configurations of the variations may be combined with each other as appropriate.

[0200] For example, the projector according to the present embodiment may be what is called a single-plate projector. In this case, the light emitting device (first light emitting device) of the light source (first light source) may emit visible-wavelength-band white light containing the blue light LB, the green light LG, and the red light LR, and may be configured, for example, with a white LED.

SUMMARY OF PRESENT DISCLOSURE

[0201] The present disclosure will be summarized below as additional remarks.

[0202] (Additional Remark 1) A projector including: a first light source including a first light emitting device configured to emit first light having a first wavelength band, a first electrically conducting line configured to supply the first light emitting device with electric power, and a base configured to support the first light emitting device and the first electrically conducting line; a first light guide having a first light incident end on which the first light output from the first light source is incident and a first light exiting end via which the first light exits, the first light guide configured to homogenize in-plane illuminance of the first light; a first parallelizing element configured to parallelize the first light output from the first light guide; a first light modulator configured to modulate the first light output from the first parallelizing element based on image information; and a projection system configured to project the light modulated by the first light modulator, wherein the first light guide is disposed away from the first electrically conducting line, and a first distance between the first light incident end of the first light guide and the first light source is smaller than or equal to 0.7 mm.

[0203] According to the configuration described in Additional Remark 1, disconnection of the first electrically conducting line and a short circuit in the first light source can be avoided with a decrease in efficiency of use of the color light suppressed.

[0204] (Additional remark 2) The projector according to Additional remark 1, wherein the first light guide has a quadrangular cross-sectional shape.

[0205] According to the configuration described in Additional Remark 2, quadrangular illumination light having a homogenized illuminance distribution can be readily generated.

[0206] (Additional Remark 3) The projector according to Additional remark 1 or 2, wherein the first light guide is in contact with the first light source.

[0207] According to the configuration described in Additional Remark 3, the efficiency at which the first light is introduced into the first light guide can be increased.

[0208] (Additional Remark 4) The projector according to any one of Additional Remarks 1 to 3, wherein a cutout is formed in the first light guide at a position where the cutout faces the first electrically conducting line, and the first electrically conducting line is inserted into the first light incident end through the cutout from a side outside the first light incident end.

[0209] According to the configuration described in Additional Remark 4, the cutout can avoid contact between the first light guide and the first electrically conducting line, minimize a decrease in the area of the first light emitting device, and increase the efficiency of use of the first light.

[0210] (Additional Remark 5) The projector according to Additional Remark 4, wherein a dimension of the cutout in a direction in which the first light from the first light source exits is greater than or equal to 0.1 mm but smaller than or equal to 0.7 mm.

[0211] According to the configuration described in Additional Remark 5, to avoid contact between the first light guide and the first electrically conducting line, the size of the cutout is minimized and the loss of the first light can be minimized.

[0212] (Additional Remark 6) The projector according to any one of Additional Remarks 1 to 5, wherein the base includes a sealing member configured to cover the first electrically conducting line, the sealing member is an insulating member, and the first light incident end is in contact with the sealing member.

[0213] According to the configuration described in Additional Remark 6, since the sealing member, which is an insulating member, is interposed between the first light guide and the first light source,

the efficiency of use of the first light can be increased with disconnection of the first electrically conducting line avoided.

[0214] (Additional Remark 7) The projector according to any one of Additional Remarks 1 to 6, wherein the first light source includes a light divergence section disposed on a light exiting side of the first light emitting device via which the first light exits and configured to cause the first light to diverge, and the sealing member is configured to support a circumference of the first light emitting device and the light divergence section.

[0215] According to the configuration described in Additional Remark 7, the configuration of the light divergence section can be simplified, and the durability of the first light emitting device can be enhanced. Furthermore, according to the configuration described in Additional Remark 7, since the light emission surface of the first light emitting device approaches the first light incident end of the first light guide, the efficiency at which the first light is introduced and used can be increased.

[0216] (Additional Remark 8) The projector according to any one of Additional Remarks 1 to 7, wherein in a plan view viewed along a direction in which the first light from the first light source exits, the first light incident end surrounds the first light emitting device and the first electrically conducting line.

[0217] According to the configuration described in Additional Remark 8, the first light incident end is large enough to surround the first light emitting device and the first electrically conducting line, so that contact between the first light guide and the first electrically conducting line can be avoided even when external impact acts on the projector and the first light guide therefore vibrates.

[0218] (Additional Remark 9) The projector according to Additional Remark 8, wherein the first light guide is a hollow member, and an internal space of the first light guide tapers from the first light exiting end to a position between the first light exiting end and the first light incident end.

[0219] According to the configuration described in Additional Remark 9, loss of the first light output from the first light guide can be reduced.

[0220] (Additional Remark 10) The projector according to Additional Remark 8 or 9, wherein the first light guide has a first side surface configured to reflect the first light, a second side surface coupled to the first side surface at right angles and configured to reflect the first light, a third side surface coupled to the second side surface at right angles and configured to reflect the first light, and a fourth side surface coupled to the third side surface at right angles and configured to reflect the first light, the first electrically conducting line faces the first, second, and the third side surfaces, a distance between the first electrically conducting line and the first side surface is greater than or equal to 0.1 mm but smaller than or equal to 1.0 mm, a distance between the first electrically conducting line and the second side surface is greater than or equal to 0.1 mm but smaller than or equal to 1.0 mm, and a distance between the first electrically conducting line and the third side surface is greater than or equal to 0.1 mm but smaller than or equal to 1.0 mm.

[0221] According to the configuration described in Additional Remark 10, the efficiency of use of the first light and the reliability of the first light source can be increased.

[0222] (Additional Remark 11) The projector according to any one of Additional Remarks 1 to 10, wherein the first light guide includes an insulating layer configured to suppress electrical conduction between the first light guide and the first electrically conducting line, the insulating layer provides at the first light incident end.

[0223] According to the configuration described in Additional Remark 11, the insulating layer is interposed between the first light guide and the first electrically conducting line, disconnection of the first electrically conducting line and a short circuit in the first light source are reliably avoided even when external impact acts on the projector.

[0224] (Additional Remark 12) The projector according to any one of Additional Remarks 1 to 11, wherein the first light guide is made of an insulating material.

[0225] According to the configuration described in Additional Remark 12, even when external impact acts on the projector so that the first light guide and the first electrically conducting line

come into contact with each other, a short circuit in the first light source can be reliably avoided.

[0226] (Additional Remark 13) The projector according to any one of Additional Remarks 1 to 12, further including: a second light source including a second light emitting device configured to emit second light having a second wavelength band, a second electrically conducting line configured to supply the second light emitting device with electric power, and a base configured to support the second light emitting device and the second electrically conducting line; a third light source including a third light emitting device configured to emit third light having a third wavelength band, a third electrically conducting line configured to supply the third light emitting device with electric power, and a base configured to support the third light emitting device and the third electrically conducting line; a second light guide having a second light incident end on which the second light output from the second light source is incident and a second light exiting end via which the second light exits, the second light guide configured to homogenize in-plane illuminance of the second light; a third light guide having a third light incident end on which the third light output from the third light source is incident and a third light exiting end via which the third light exits, the third light guide configured to homogenize in-plane illuminance of the third light; a second parallelizing element configured to parallelize the second light output from the second light guide; a third parallelizing element configured to parallelizes the third light output from the third light guide; a second light modulator configured to modulate the second light output from the second parallelizing element based on image information; and a third light modulator configured to modulate the third light output from the third parallelizing element based on image information, wherein the second light guide is disposed away from the second electrically conducting line, the third light guide is disposed away from the third electrically conducting line, a second distance between the second light incident end of the second light guide and the second light source is smaller than or equal to 0.7 mm, and a third distance between the third light incident end of the third light guide and the third light source is smaller than or equal to 0.7 mm.

[0227] According to the configuration described in Additional Remark 13, disconnection of the first electrically conducting line and a short circuit in the first light source can be avoided with a decrease in efficiency of use of the color light suppressed.

Claims

1. A projector comprising: a first light source including a first light emitting device configured to emit first light having a first wavelength band, a first electrically conducting line configured to supply the first light emitting device with electric power, and a base configured to support the first light emitting device and the first electrically conducting line; a first light guide having a first light incident end on which the first light output from the first light source is incident and a first light exiting end via which the first light exits, the first light guide configured to homogenize in-plane illuminance of the first light; a first parallelizing element configured to parallelize the first light output from the first light guide; a first light modulator configured to modulate the first light output from the first parallelizing element based on image information; and a projection system configured to project the light modulated by the first light modulator, wherein the first light guide is disposed away from the first electrically conducting line, and a first distance between the first light incident end of the first light guide and the first light source is smaller than or equal to 0.7 mm.
2. The projector according to claim 1, wherein the first light guide has a quadrangular cross-sectional shape.
3. The projector according to claim 1, wherein the first light guide is in contact with the first light source.
4. The projector according to claim 1, wherein a cutout is formed in the first light guide at a position where the cutout faces the first electrically conducting line, and the first electrically conducting line is inserted into the first light incident end through the cutout from a side outside the

first light incident end.

5. The projector according to claim 4, wherein a dimension of the cutout in a direction in which the first light from the first light source exits is greater than or equal to 0.1 mm but smaller than or equal to 0.7 mm.

6. The projector according to claim 1, wherein the base includes a sealing member configured to cover the first electrically conducting line, the sealing member is an insulating member, and the first light incident end is in contact with the sealing member.

7. The projector according to claim 6, wherein the first light source includes a light divergence section disposed on a light exiting side of the first light emitting device via which the first light exits and configured to cause the first light to diverge, and the sealing member is configured to support a circumference of the first light emitting device and the light divergence section.

8. The projector according to claim 1, wherein in a plan view viewed along a direction in which the first light from the first light source exits, the first light incident end surrounds the first light emitting device and the first electrically conducting line.

9. The projector according to claim 8, wherein the first light guide is a hollow member, and an internal space of the first light guide tapers from the first light exiting end to a position between the first light exiting end and the first light incident end.

10. The projector according to claim 8, wherein the first light guide has a first side surface configured to reflect the first light, a second side surface coupled to the first side surface at right angles and configured to reflect the first light, a third side surface coupled to the second side surface at right angles and configured to reflect the first light, and a fourth side surface coupled to the third side surface at right angles and configured to reflect the first light, the first electrically conducting line faces the first, second, and the third side surfaces, a distance between the first electrically conducting line and the first side surface is greater than or equal to 0.1 mm but smaller than or equal to 1.0 mm, a distance between the first electrically conducting line and the second side surface is greater than or equal to 0.1 mm but smaller than or equal to 1.0 mm, and a distance between the first electrically conducting line and the third side surface is greater than or equal to 0.1 mm but smaller than or equal to 1.0 mm.

11. The projector according to claim 1, wherein the first light guide includes an insulating layer configured to suppress electrical conduction between the first light guide and the first electrically conducting line, the insulating layer provides at the first light incident end.

12. The projector according to claim 1, wherein the first light guide is made of an insulating material.

13. The projector according to claim 1, further comprising: a second light source including a second light emitting device configured to emit second light having a second wavelength band, a second electrically conducting line configured to supply the second light emitting device with electric power, and a base configured to support the second light emitting device and the second electrically conducting line; a third light source including a third light emitting device configured to emit third light having a third wavelength band, a third electrically conducting line configured to supply the third light emitting device with electric power, and a base configured to support the third light emitting device and the third electrically conducting line; a second light guide having a second light incident end on which the second light output from the second light source is incident and a second light exiting end via which the second light exits, the second light guide configured to homogenize in-plane illuminance of the second light; a third light guide having a third light incident end on which the third light output from the third light source is incident and a third light exiting end via which the third light exits, the third light guide configured to homogenize in-plane illuminance of the third light; a second parallelizing element configured to parallelize the second light output from the second light guide; a third parallelizing element configured to parallelize the third light output from the third light guide; a second light modulator configured to modulate the second light output from the second parallelizing element based on image information; and a third

light modulator configured to modulate the third light output from the third parallelizing element based on image information, wherein the second light guide is disposed away from the second electrically conducting line, the third light guide is disposed away from the third electrically conducting line, a second distance between the second light incident end of the second light guide and the second light source is smaller than or equal to 0.7 mm, and a third distance between the third light incident end of the third light guide and the third light source is smaller than or equal to 0.7 mm.
