

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250282239

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Lee; Yu-Chin et al.

SWING-ARM CABLE-MANAGEMENT DEVICE

Abstract

A swing-arm cable-management device is provided and includes a mounting base, a first arm, a second arm, a guiding module, a sliding component and a clamp component. The mounting base is mounted on a charging machine. The first arm is pivotally connected to the mounting base through a first pivot shaft perpendicular to the ground, and allowed to rotate relative to the mounting base. The second arm is pivotally connected to the first arm through a second pivot shaft perpendicular to the ground, and allowed to rotate relative to the first arm. The guiding module is disposed on the second arm and slopped to increase height along a horizontal direction from rear end to the front end. The sliding component is slidably disposed on the guiding module. The clamp component is connected to the sliding component and fastens a charging cable, so as to manage the charging cable effectively.

Inventors: Lee; Yu-Chin (Taoyuan City, TW), Hsieh; Hung-Sheng (Taoyuan City, TW)

Applicant: Delta Electronics, Inc. (Taoyuan City, TW)

Family ID: 94227691

Appl. No.: 19/012300

Filed: January 07, 2025

Foreign Application Priority Data

TW

113143093

Nov. 11, 2024

Related U.S. Application Data

us-provisional-application US 63563510 20240311

Publication Classification

Int. Cl.: B60L53/18 (20190101); H02G11/00 (20060101)

U.S. Cl.:

CPC B60L53/18 (20190201); H02G11/006 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application claims the benefit of U.S. Provisional Application No. 63/563,510 filed on Mar. 11, 2024, and entitled “SWING-ARM CABLE-MANAGEMENT DEVICE”. This application claims priority to Taiwan Patent Application No. 113143093, filed on Nov. 11, 2024. The entireties of the above-mentioned patent applications are incorporated herein by reference for all purposes.

FIELD OF THE INVENTION

[0002] The present disclosure relates to a cable-management device, and more particularly to a swing-arm cable-management device holding an electric vehicle charging cable by connecting a clamp component to a sliding component on a sloped guiding module and combining a swing arm, for managing the electric vehicle charging cable when in use and idle, and avoiding damage to the charging cable and the charging gun head.

BACKGROUND OF THE INVENTION

[0003] With the continuous development and progress of science and technology, the vehicles on the current market have changed from the traditional gasoline vehicles to the electric vehicles. As time goes by, the number of electric vehicles is increasing. Since the electric vehicles only need to charge the batteries disposed thereon to start on the road, and the conversion of electrical energy is produced without the pollution, so it has a good environmental protection effect.

[0004] On the other hand, the charging machines are used for producing the charging process of electric vehicles, and the number of charging machines, such as the upright charging machines or the wall-mounted charging machines on the current market is increasing. Those types of charging machines often have a very long charging cable, so that the charging gun can be expanded to the charging port of the electric vehicle through the charging cable for charging.

[0005] However, most of the current charging machines are not equipped with a cable management device, so it is laborious to hold the charging gun. Even if there are charging machines equipped with the cable management devices, counterweights and pulleys are used to manage the cables merely. Therefore, the overall system is heavier, larger in size, and has a complex internal structure. Moreover, when retracting the charging cable, the charging gun may accidentally fall to the ground, causing the damage to the charging gun.

[0006] Therefore, there is a need of providing a swing-arm cable-management device holding an electric vehicle charging cable by connecting a clamp component to a sliding component on a sloped guiding module and combining a swing arm, so as to manage the electric vehicle charging cable when in use and idle, avoid damage to the charging cable and the charging gun head, and obviate the drawbacks encountered from the prior arts.

SUMMARY OF THE INVENTION

[0007] It is an object of the present disclosure to provide a swing-arm cable-management device holding an electric vehicle charging cable by connecting a clamp component to a sliding component on a sloped guiding module and combining a swing arm, so as to manage the electric vehicle charging cable when in use and idle, avoid damage to the charging cable and the charging gun head.

[0008] It is another object of the present disclosure to provide a swing-arm cable-management

device. By connecting a clamp component to a sliding component disposed on a sloped guiding module and disposing the sloped guiding module on a multi-section swing arms with torsion springs, a basic function of expanded support for the charging gun and the charging cable is achieved. It also provides the function of automatically returning the charging gun and charging cable to avoid damage to the charging gun and charging cable. When the charging gun is not in use, the multi-section swing arms of the swing-arm cable-management device is folded to a minimum length through the action of the torsion springs. At the same time, the sliding component connected to the clamp component of the charging cable and slidably disposed on the sloped guiding module is automatically returned by the gravity action of the charging cable, and moved to the lowest point of the sloped guiding module, thereby driving the charging cable to an initial status with the smallest footprint. On the other hand, when the user uses the charging gun to pull the charging cable, the clamp component of the charging cable drives the sliding component to move to the highest point of the sloped guiding module, and at the same time the multi-section swing arms are fully expanded, so that the charging gun can be used to charge the electric vehicle in the charging operation easily. When the user has finished the operation of the charging gun, he only needs to release the charging gun. The gravity of the charging cable drives the sliding component to automatically return to the lowest point of the sloped guiding module through the clamp component. The multi-section swing arm is folded and merged as the minimum length through the action of the torsion spring, so that the charging cable and the charging gun are moved back to the initial status. With the swing-arm cable-management device of the present disclosure, no matter whether the multi-section swing arms are unfolded or folded, the charging gun and the charging cable will not touch the ground. It reduces the risk of damage to the charging gun and the charging cable. In addition, it allows to add a limiting mechanism for limiting a rotation angle of the first arm and the second arm, or add buffering elements for providing a buffering function between the first arm and the second arm. Compared with the conventional cable management device that uses counterweights and pulleys merely, the multi-section arm-folding structure constructed by the multi-section swing arms is significantly reduced in both volume and weight. It not only simplifies the structure, but also reduces the cost. The present disclosure includes the industrial applicability and the inventive steps.

[0009] In accordance with another aspect of the present disclosure, a swing-arm cable-management device is provided and includes a mounting base, a first arm, a second arm, a guiding module, a sliding component and a clamp component. The mounting base is configured to be mounted on a lateral wall of a charging machine. The first arm includes a first end and a second end opposite to each other, wherein the first end is pivotally connected to the mounting base through a first pivot shaft perpendicular to the ground, so that the first arm is allowed to rotate relative to the mounting base around the first pivot shaft. The second arm includes a third end and a fourth end opposite to each other, wherein the third end is pivotally connected to the second end of the first arm through a second pivot shaft perpendicular to the ground, so that the second arm is allowed to rotate relative to the first arm through the second pivot shaft. The guiding module is disposed on the second arm and slopped to increase height along a horizontal direction from third end to the fourth end, wherein the guiding module comprises a rear end and a front end opposite to each other, and the rear end is disposed adjacent to the third end and lower than the front end disposed adjacent to the fourth end. The sliding component is slidably disposed on the guiding module. The clamp component is connected to the sliding component and configured to fasten a charging cable of the charging machine, wherein when the charging cable is idle, the clamp component is pulled downwardly to drive the sliding component to move to the rear end of the guiding module due to a gravity action of the charging cable, wherein when the charging cable is in use and expanded by a charging gun, the clamp component is pulled away from the mounting base to drive the sliding component to move to the front end of the guiding module due to a pull action on the charging gun.

[0010] In an embodiment, the charging machine is disposed on a ground and the lateral wall of the

charging machine is perpendicular to the ground, the mounting base is mounted on the lateral wall of the charging machine and located adjacent to a top of the charging machine, and the charging cable is connected between the lateral wall of the charging machine and the charging gun.

[0011] In an embodiment, the swing-arm cable-management device further includes at least one torsion spring, wherein the at least one torsion spring is disposed around the first pivot shaft or/and the second pivot shaft and configured to provide an elastic restoring force to keep the first arm and the second arm fold in an initial statue.

[0012] In an embodiment, when the clamp component on the first arm is pulled downwardly to drive the sliding component to move to the rear end of the guiding module due to the gravity action of the charging cable, the first arm and the second arm are folded and attached to the lateral wall of the charging machine, wherein when the clamp component is pulled away from the mounting base to drive the sliding component to move to the front end of the guiding module due to the pull action on the charging gun, the first arm and the second arm are unfolded in a front of the charging machine.

[0013] In an embodiment, the first arm and the second arm are an elongated hollow frame, respectively.

[0014] In an embodiment, the guiding module includes two guiding grooves, the two guiding grooves pass through two opposite walls of the second arm, the sliding component is located between the two guiding grooves and includes a horizontal shaft and two fastening nuts, and the horizontal shaft and the two fastening nuts are configured to install the sliding component on the guiding module.

[0015] In an embodiment, the elongated hollow frame of the second arm includes a bottom opening, wherein the sliding component is placed between two guiding grooves of the guiding module and comprises a horizontal shaft, and the horizontal shaft passes through the two guiding grooves of the guiding module and a central axis of the sliding component, wherein two ends of the horizontal shaft are limited by two fastening nuts, and the two fastening nuts are located outside two opposite walls of the elongated hollow frame, respectively, so that the sliding component is slidably disposed on the guiding module.

[0016] In an embodiment, the sliding component and the clamp component are connected through a rope, and the rope passes through the bottom opening.

[0017] In an embodiment, the rope is wound on the sliding component and includes an end fixed to the clamp component and another end fixed to the third end of the second arm.

[0018] In an embodiment, the rope is wound on the sliding component and includes two ends fixed to the clamp component.

[0019] In an embodiment, the elongated hollow frame of the second arm includes a bottom opening, wherein the guiding module includes a tubular guiding rail obliquely embedded in the second arm, and the sliding component comprises a pulley set slidably disposed in the tubular guiding rail.

[0020] In an embodiment, the sliding component and the clamp component are connected through a rope, and the rope passes through the bottom opening.

[0021] In an embodiment, the elongated hollow frame of the second arm includes a bottom opening, wherein the guiding module includes a guiding rod obliquely embedded in the second arm, and the sliding component is slidably sleeved on the guiding rod and connected to the clamp component through the bottom opening.

[0022] In an embodiment, the sliding component and the clamp component are connected through a rope, and the rope passes through the bottom opening.

[0023] In an embodiment, the swing-arm cable-management device further includes a limiting mechanism, wherein the limiting mechanism is disposed between the second end of the first arm and the third end of the second arm, and configured to limit rotation angle of the first arm and the second arm.

[0024] In an embodiment, the swing-arm cable-management device further includes a buffering element, wherein the buffering element is disposed between the mounting base and the first end and between the fourth end and the first end, and configured to provide a buffering function for collisions when the first arm is folded relative to the mounting base and the second arm is folded relative to the first arm.

[0025] In an embodiment, the swing-arm cable-management device further includes a buffering element, wherein the buffering element is disposed between the second end and the third end, and configured to provide a buffering function for collisions when the second arm is unfolded relative to the first arm.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0026] The above contents of the present disclosure will become more readily apparent to those ordinarily skilled in the art after reviewing the following detailed description and accompanying drawings, in which:

[0027] FIG. 1 is a schematic exterior view illustrating a swing-arm cable-management device applied to a charging machine when the charging cable is idle according to a first embodiment of the present disclosure;

[0028] FIG. 2 is a lateral view illustrating the swing-arm cable-management device applied to the charging machine when the charging cable is idle according to the first embodiment of the present disclosure;

[0029] FIG. 3 is a schematic exterior view illustrating the swing-arm cable-management device applied to the charging machine when the charging cable is expanded in use according to the first embodiment of the present disclosure;

[0030] FIG. 4 is a lateral view illustrating the swing-arm cable-management device applied to the charging machine when the charging cable is expanded in use according to the first embodiment of the present disclosure;

[0031] FIG. 5 is a structural perspective view illustrating the sliding component and the clamp component connected through the rope according to the first embodiment of the present disclosure;

[0032] FIG. 6 is a schematic exploded view illustrating the sliding component installed on the guiding module according to the first embodiment of the present disclosure;

[0033] FIG. 7 schematically shows the swing-arm cable-management device operated at the initial status according to the first embodiment of the present disclosure;

[0034] FIG. 8 schematically shows the swing-arm cable-management device operated at the transitional status according to the first embodiment of the present disclosure;

[0035] FIG. 9 schematically shows the swing-arm cable-management device operated at the fully expanded status according to the first embodiment of the present disclosure;

[0036] FIG. 10 schematically shows the swing-arm cable-management device having torsion springs disposed around the first pivot shaft according to the first embodiment of the present disclosure;

[0037] FIG. 11 is a structural perspective view illustrating a sliding component and a clamp component connected through a rope according to a second embodiment of the present disclosure;

[0038] FIG. 12 is a schematic exploded view illustrating the sliding component installed on the guiding module according to the second embodiment of the present disclosure;

[0039] FIG. 13 schematically shows the swing-arm cable-management device operated at the initial status according to the second embodiment of the present disclosure;

[0040] FIG. 14 schematically shows the swing-arm cable-management device operated at the transitional status according to the second embodiment of the present disclosure;

[0041] FIG. **15** schematically shows the swing-arm cable-management device operated at the fully expanded status according to the second embodiment of the present disclosure;

[0042] FIG. **16** is an internal structural perspective view illustrating a sliding component connected to a clamp component through a rope and installed in a guiding module according to a third embodiment of the present disclosure;

[0043] FIG. **17** is a lateral view illustrating the swing-arm cable-management device operated at the initial status according to the third embodiment of the present disclosure;

[0044] FIG. **18** schematically shows the swing-arm cable-management device having the limiting mechanism disposed around the second pivot shaft;

[0045] FIG. **19** schematically shows the swing-arm cable-management device having the buffering element and operated at the initial status;

[0046] FIG. **20** schematically shows the swing-arm cable-management device having the buffering element and operated at the fully expanded status;

[0047] FIG. **21** schematically shows a swing-arm cable-management device operated at the initial status according to a fourth embodiment of the present disclosure;

[0048] FIG. **22** is an internal structural perspective view illustrating the sliding component connected to the clamp component through a rope and installed in a guiding module according to the fourth embodiment of the present disclosure;

[0049] FIG. **23** is a lateral view illustrating the swing-arm cable-management device operated at the initial status according to the fourth embodiment of the present disclosure;

[0050] FIG. **24** schematically shows the swing-arm cable-management device operated at the transitional status according to the fourth embodiment of the present disclosure;

[0051] FIG. **25** schematically shows the swing-arm cable-management device operated at the transitional status from another perspective according to the fourth embodiment of the present disclosure;

[0052] FIG. **26** schematically shows the swing-arm cable-management device operated at the fully expanded status according to the fourth embodiment of the present disclosure;

[0053] FIG. **27** schematically shows a swing-arm cable-management device operated at the initial status according to a fifth embodiment of the present disclosure;

[0054] FIG. **28** is an internal structural perspective view illustrating the sliding component connected to the clamp component and installed in the guiding module according to the fifth embodiment of the present disclosure;

[0055] FIG. **29** is a lateral view illustrating the swing-arm cable-management device operated at the initial status according to the fifth embodiment of the present disclosure;

[0056] FIG. **30** schematically shows the swing-arm cable-management device operated at the transitional status according to the fifth embodiment of the present disclosure; and

[0057] FIG. **31** schematically shows the swing-arm cable-management device operated at the fully expanded status according to the fifth embodiment of the present disclosure.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0058] The present disclosure will now be described more specifically with reference to the following embodiments. It is to be noted that the following descriptions of preferred embodiments of this disclosure are presented herein for purpose of illustration and description only. It is not intended to be exhaustive or to be limited to the precise form disclosed. For example, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also include embodiments in which additional features may be formed between the first and second features, such that the first and second features may not be in direct contact. In addition, the present disclosure may repeat reference numerals and/or letters in the various examples. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed. Further, spatially relative terms, such as

“upper,” “lower,” “front,” “rear” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. The spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. The apparatus may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein may likewise be interpreted accordingly. When an element is referred to as being “connected,” or “coupled,” to another element, it can be directly connected or coupled to the other element or intervening elements may be present. Although the wide numerical ranges and parameters of the present disclosure are approximations, numerical values are set forth in the specific examples as precisely as possible. In addition, although the “first,” “second,” “third,” and the like terms in the claims be used to describe the various elements can be appreciated, these elements should not be limited by these terms, and these elements are described in the respective embodiments are used to express the different reference numerals, these terms are only used to distinguish one element from another element. For example, a first element could be termed a second element, and, similarly, a second element could be termed a first element, without departing from the scope of example embodiments.

[0059] Referring to FIG. 1 to FIG. 9. The present disclosure provides a swing-arm cable-management device **1** is provided and applied to a charging machine **9**. In the embodiment, the swing-arm cable-management device **1** includes a mounting base **10**, a first arm **20**, a second arm **30**, a guiding module **33**, a sliding component **40** and a clamp component **60**. The mounting base **10** is configured to be mounted on a lateral wall **90** of a charging machine **9**. The first arm **20** has a first end **21** and a second end **22** opposite to each other. The first end **21** is pivotally connected to the mounting base **10** through a first pivot shaft **C1** perpendicular to the ground, so that the first arm **20** is allowed to rotate relative to the mounting base **10** around the first pivot shaft **C1**. The second arm **30** has a third end **31** and a fourth end **32** opposite to each other. The third end **31** is pivotally connected to the second end **22** of the first arm **20** through a second pivot shaft **C2** perpendicular to the ground, so that the second arm **30** is allowed to rotate relative to the first arm **20** through the second pivot shaft **C2**. The guiding module **33** is disposed on the second arm **30** and slopped to increase height along a horizontal direction, such as the X axial direction, from third end **31** to the fourth end **32**. The guiding module **33** includes a rear end and a front end opposite to each other, and the rear end is disposed adjacent to the third end **31** and lower than the front end disposed adjacent to the fourth end **32**. The sliding component **40** is slidably disposed on the guiding module **33**. The clamp component **60** is connected to the sliding component **40** through a rope **50**, and configured to fasten a charging cable **91** of the charging machine **9**. When the charging cable **91** is idle, the clamp component **60** is pulled downwardly to drive the sliding component **40** to move to the rear end of the guiding module **33** due to the gravity action of the charging cable **91**, and the first arm **20** and the second arm **30** are folded in the rear of the mounting base **10**. When the charging cable **91** is in use and expanded by a charging gun **92**, the clamp component **60** is pulled away from the mounting base **10** to drive the sliding component **40** to move to the front end of the guiding module **33** due to the pull action on the charging gun **92**, and the first arm **20** and the second arm **30** are unfolded in front of the mounting base **10**.

[0060] In the embodiment, the charging machine **9** is disposed on the ground and the lateral wall **90** of the charging machine **9** is perpendicular to the ground. Preferably but not exclusively, the mounting base **10** is mounted on the lateral wall **90** of the charging machine **9** and located adjacent to the top of the charging machine **9**. The charging cable **91** is connected between the lateral wall **90** of the charging machine **9** and the charging gun **92**. Preferably but not exclusively, the rear end of the charging cable **91** is disposed adjacent to the mounting base **10**, and the front end of the charging cable **91** is connected to the charging gun **92**. Moreover, the middle section of the charging cable **91** is fastened and sleeved by the clamp component **60**. The charging gun **92** is received on a seat under the mounting base **10** and the rear end of the charging cable **91** when idle.

In this way, the charging cable **91** and the charging gun **92** are managed efficiently by the swing-arm cable-management device **1** of the present disclosure. Certainly, the arrangements of the charging cable **91** and the charging gun **92**, the length of the charging cable **91** are adjustable according to the practical requirements, and the present disclosure is not limited thereto. Notably, the method of the clamp component **60** fastening the charging cable **91** is adjustable according to the practical requirements. The present disclosure is not limited thereto and not redundantly described herein.

[0061] Preferably but not exclusively, the first arm **20** and the second arm **30** includes an elongated hollow frame, respectively to form the housing thereof. In the embodiment, the first arm **20** and the second arm **30** are pivotally connected to each other through the second pivot shaft **C2** to form a swing-arm structure. In other embodiments, a plurality of arms are pivotally connected to form a multi-section swing-arm structure. Certainly, the number of the pivoted arms is adjustable according to the practical requirements, and the present disclosure is not limited thereto. By connecting the clamp component **60** to the sliding component **40** disposed on the sloped guiding module **33** and disposing the sloped guiding module **33** on the front of the multi-section swing arms, a basic function of expanded support for the charging gun **92** and the charging cable **91** is achieved, and it also provides the function of automatically returning the charging gun **92** and charging cable **91** to avoid damage to the charging gun **92** and charging cable **91**.

[0062] As shown in FIG. 1, FIG. 2 and FIG. 7, when the charging gun **92** is not in use, the first arm **20** and the second arm **30** of the swing-arm cable-management device **1** are folded to a minimum length due to the gravity action of the charging cable **91**. Moreover, the sliding component **40** connected to the clamp component **60** fastening the charging cable **91** and slidably disposed on the guiding module **33** is automatically returned by the gravity action of the charging cable **91**. At this time, the sliding component **40** is moved to the lowest point of the sloped guiding module **33**, and the charging cable **91** is hold in an initial status with the smallest footprint. Preferably but not exclusively, when the first arm **20** and the second arm **30** of the swing-arm cable-management device **1** are folded due to the gravity action of the charging cable **91**, the first arm **20** and the second arm **30** are overlapped with each other and attached to the lateral wall **90** of the charging machine **9**, so that the swing-arm cable-management device **1** has the minimum length about 80 cm, with the smallest footprint.

[0063] As shown in FIG. 3, FIG. 4, FIG. 8 and FIG. 9, when the user uses the charging gun **92** to pull the charging cable **91**, the clamp component **60** fastening the charging cable **91** drives the sliding component **40** to move to the highest point of the sloped guiding module **33**, and at the same time the first arm **20** and the second arm **30** are fully expanded. Preferably but not exclusively, the first arm **20** and the second arm **30** are unfolded in the front of the charging machine **9**, so that the charging gun **92** can be used to charge the electric vehicle (not shown) in the charging operation easily.

[0064] In the embodiment, when the user has finished the operation of the charging gun **92**, he only needs to release the charging gun **92**. The gravity of the charging cable **91** drives the sliding component **40** to automatically return to the lowest point of the sloped guiding module **33** through the clamp component **60**. The first arm **20** and the second arm **30** are folded and merged as the minimum length through the gravity action of the charging cable **91**, so that the charging cable **91** and the charging gun **92** are moved back to the initial status, as shown in FIG. 1, FIG. 2 and FIG. 7. With the swing-arm cable-management device **1** of the present disclosure, no matter whether the multi-section swing arms are unfolded or folded, the charging gun **92** and the charging cable **91** will not touch the ground.

[0065] Referring to FIG. 1 to FIG. 9 again, in the embodiment, the guiding module **33** includes two guiding groove passing through the two opposite walls of the elongated hollow frame of the second arm **30**. The main body **41** of the sliding component **40** is located between the two guiding grooves. Moreover, the sliding component **40** includes a horizontal shaft **42** and two fastening nuts **43**,

which are configured to install the main body **41** of the sliding component **40** on the guiding module **33**. Preferably but not exclusively, in the embodiment, the elongated hollow frame of the second arm **30** further includes a bottom opening **34**. For installing the sliding component **40** on the guiding module **33**, the main body **41** of the sliding component **40** is placed between the two guiding grooves of the guiding module **33**, the horizontal shaft **42** passes through the two guiding grooves of the guiding module **33** and the main body **41** along the central axis of the sliding component **40** in the horizontal direction, and then two ends of the horizontal shaft **42** are limited by the two fastening nuts **43** outside the opposite walls of the elongated hollow frame, so that the sliding component **40** is slidably disposed on the guiding module **33**. Certainly, in other embodiments, the types of the guiding module **33** and the installation of the sliding component **40** are adjustable according to the practical requirements, and the present disclosure is not limited thereto.

[0066] Notably, in the embodiment, the clamp component **60** is connected to the sliding component **40** through a rope **50**. The rope **50** is wound on the sliding component **40** and includes one end **52** fixed to the clamp component **60** and another end **51** fixed to the third end **31** of the second arm **30**. From the initial statue (referring to FIG. 7) to the fully expanded statue (referring to FIG. 9) through the transitional status (referring to FIG. 8), the distance between the sliding component **40** and the clamp component **60** is decreased. That is, when the user uses the charging gun **92** to pull the charging cable **91**, the clamp component **60** fastening the charging cable **91** drives the sliding component **40** to move to the highest point of the sloped guiding module **33**, the first arm **20** and the second arm **30** are fully expanded in front of the mounting base **10** along the X axial direction, and the middle section of the charging cable **91** is lifted to the highest point, as shown in FIG. 3 and FIG. 4. In that, the charging gun **92** can be stretched to the farthest point, and the charging cable **91** is hold by the swing-arm cable-management device **1** stably for charging the electric vehicle.

[0067] On the contrary, from the fully expanded statue (referring to FIG. 9) to the initial statue (referring to FIG. 7) through the transitional status (referring to FIG. 8), the distance between the sliding component **40** and the clamp component **60** is increased to the original length. That is, when the user releases the charging gun **92**. The gravity of the charging cable **91** drives the sliding component **40** to automatically return to the lowest point of the sloped guiding module **33** through the clamp component **60**. The first arm **20** and the second arm **30** are folded in the rear of the mounting base **10** along the inverse X axial direction and merged as the minimum length through the gravity action of the charging cable **91**, and the middle section of the charging cable **91** is hold at a fixed height, so that the charging cable **91** and the charging gun **92** are moved back to the initial status, as shown in FIG. 1 and FIG. 2.

[0068] In the embodiment, the swing-arm cable-management device **1** further includes torsion springs **70** disposed around the first pivot shaft C1, as shown in FIG. 10. Similarly, the swing-arm cable-management device **1** further includes torsion springs **70** disposed around the second pivot shaft C2. The torsion springs **70** are configured to provide an elastic restoring force to keep the first arm **20** and the second arm **30** fold in the initial statue, as shown in FIG. 7. When the user uses the charging gun **92** to pull the charging cable **91**, the elastic restoring force is overcome by the pulling force from the user, and then the first arm **20** and the second arm **30** are fully expanded to have a maximum length about 157 cm, so that the charging cable **91** is stretched and hold stably, and the charging gun **92** can be used to charge the electric vehicle. On the other hand, when the user has finished the operation of the charging gun **92** and releases the charging gun **92**, the first arm **20** and the second arm **30** are fold to the initial statue due to the elastic restoring force of the torsion springs **70**. At the same time, the sliding component **40** connected to the clamp component **60** is acted by the gravity of the charging cable **91** and automatically returns to the lowest point of the sloped guiding module **33**. Thus, the charging cable **91** and the charging gun **92** are moved back to the initial status, as shown in FIG. 1 and FIG. 2. Certainly, the type and the installation of the torsion springs **70** are adjustable according to the practical requirements. The present disclosure is

not limited thereto, and not redundantly described hereafter.

[0069] FIG. 11 to FIG. 15 show a swing-arm cable-management device according to a second embodiment of the present disclosure. In the embodiment, the structures, elements and functions of the swing-arm cable-management device **1a** are similar to those of the swing-arm cable-management device **1** in FIG. 1 to FIG. 10, and are not redundantly described herein. In the embodiment, the clamp component **60** is connected to the sliding component **40** through a rope **50a**. The rope **50a** is wound on the sliding component **40** and includes two ends fixed to the clamp component **60**. For installing the sliding component **40** on the guiding module **33**, the main body **41** of the sliding component **40** is placed between the two guiding grooves of the guiding module **33**, the horizontal shaft **42** passes through the two guiding grooves of the guiding module **33** and the main body **41** along the central axis of the sliding component **40**, and then two ends of the horizontal shaft **42** are limited by the two fastening nuts **43** outside the opposite walls of the elongated hollow frame (i.e., the second arm **30**), so that the sliding component **40** is slidably disposed on the guiding module **33**. Afterward, the rope **50a** is wound on the main body **41** through the bottom opening **34**, and then the two ends of the rope **50a** are fixed to the clamp component **60**. [0070] From the initial statue (referring to FIG. 13) to the fully expanded statue (referring to FIG. 15) through the transitional status (referring to FIG. 14), the distance between the sliding component **40** and the clamp component **60** is constant. That is, when the user uses the charging gun **92** to pull the charging cable **91**, the clamp component **60** fastening the charging cable **91** drives the sliding component **40** to move to the highest point of the sloped guiding module **33**, the first arm **20** and the second arm **30** are fully expanded in front of the mounting base **10** along the X axial direction, and the middle section of the charging cable **91** is slightly lifted to the highest point. The altitude changes are maintained within the height difference about 10 cm between the rear and the front end of the sloped guiding module **33**. In that, the charging gun **92** can be stretched to the farthest point, and the charging cable **91** is hold by the swing-arm cable-management device **1a** stably for charging the electric vehicle.

[0071] On the contrary, from the fully expanded statue (referring to FIG. 15) to the initial statue (referring to FIG. 13) through the transitional status (referring to FIG. 14), the distance between the sliding component **40** and the clamp component **60** is constant. That is, when the user releases the charging gun **92**. The gravity of the charging cable **91** drives the sliding component **40** to automatically return to the lowest point of the sloped guiding module **33** through the clamp component **60**. The first arm **20** and the second arm **30** are folded in the rear of the mounting base **10** along the inverse X axial direction and merged as the minimum length through the gravity action of the charging cable **91**, and the middle section of the charging cable **91** is hold at a fixed height, so that the charging cable **91** and the charging gun **92** are moved back to the initial status (referring to FIG. 1 and FIG. 2). Certainly, the connection of the sliding component **40** and the clamp component **60** is adjustable according to the practical requirements. The present disclosure is not limited thereto. Certainly, the slope of the sloped guiding module **33**, the sizes of the first arm **20** and the second arm **30** are adjustable according to the practical requirements. The present disclosure is not limited thereto, and not redundantly described herein.

[0072] FIG. 16 and FIG. 17 show a swing-arm cable-management device according to a third embodiment of the present disclosure. In the embodiment, the structures, elements and functions of the swing-arm cable-management device **1b** are similar to those of the swing-arm cable-management device **1** in FIG. 1 to FIG. 10, and are not redundantly described herein. In the embodiment, the guiding module **33** of the swing-arm cable-management device **1b** further includes a tubular guiding rail **35** embedded obliquely in the second arm **30**. The sliding component **40** includes a pulley set **44**, and the pulley set **44** is slidably disposed in the tubular guiding rail **35**. The tubular guiding rail **35** includes a rear end and a front end opposite to each other, and the rear end is disposed adjacent to the third end **31** and lower than the front end disposed adjacent to the fourth end **32**. Preferably but not exclusively, the lowest point of the tubular guiding rail **35** is

disposed adjacent to the third end **31** of the second arm **30**; and the highest point of the tubular guiding rail **35** is disposed adjacent to the fourth end **32**. In the embodiment, the clamp component **60** is connected to the pulley set **44** through a rope **50a**. The rope **50a** is wound on the holding pin **45** of the pulley set **44** and includes two ends fixed to the clamp component **60**. Certainly, the slope of the tubular guiding rail **35**, the types of the tubular guiding rail **35** and the pulley set **44** are adjustable according to the practical requirements, and the present disclosure is not limited thereto. In addition, the functions of the tubular guiding rail **35** and the pulley set **44** are similar to those of the guiding module **33** and the sliding component **40** in the above embodiments, and are not redundantly described herein.

[0073] Notably, in the embodiment, the swing-arm cable-management device **1**, **1a** or **1b** further has a limiting mechanism for limiting the rotation angle of the first arm **20** and the second arm **30**. Preferably but not exclusively, the limiting mechanism includes a limiting pin **71** and a limiting groove **72** spatially corresponding to each other and arranged adjacent to the second pivot shaft **C2**, as shown in FIG. **18**. In the embodiment, the limiting groove **72** is disposed on third end **31** of the second arm **30** and arranged around the second pivot shaft **C2** of 180° . One end of the limiting pin **71** is disposed on the second end **22** of the first arm **20** and another end of the limiting pin **71** is slidably received in the limiting groove **72**. When the limiting pin **71** is limited by the one end of the limiting groove **72**, and the first arm **20** and the second arm **30** are operated in the initial state (referring to FIG. **7**), the second arm **30** is attached to each other in parallel. Namely, the rotation angle of the second arm **30** relative to the first arm **20** in the initial status is 0° . On the contrary, when the limiting pin **71** is limited by another end of the limiting groove **72**, and the first arm **20** and the second arm **30** are operated in the fully expanded state (referring to FIG. **9**), the first arm **20** and the second arm **30** are unfolded and parallel to each other. Namely, the rotation angle of the second arm **30** relative to the first arm **20** in the fully expanded status is 180° . With the limiting mechanism, the rotation angle of the second arm **30** relative to the first arm **20** is ranged from 0° to 180° . In other embodiments, the limiting mechanism is provided to limit the rotation angle of the first arm **20** relative to the mounting base **10**. Certainly, the arrangement, the rotation angle of the limiting mechanism are adjustable according to the practical requirement, but not redundantly described herein.

[0074] Furthermore, in an embodiment, the above limiting mechanism is omitted, but the swing-arm cable-management device **1**, **1a** or **1b** further includes buffering elements **73**, **74**, which are configured to provide a buffering function for collisions during rotation and swing between the first arm **20** and the second arm **30**. Please refer to FIG. **19** and FIG. **20**. Preferably but not exclusively, the buffering element **73** is a long elastic gasket, disposed on the first end **21** of the first arm **20**, arranged adjacent to the first pivot shaft **C1**, and spatially corresponding to the fourth end **32** of the second arm **30**. Preferably but not exclusively, the buffering element **74** is a long elastic gasket, disposed on the second end **22** of the first arm **20**, arranged adjacent to the second pivot shaft **C2**, and spatially corresponding to the third end **31** of the second arm **30**. As shown in FIG. **19**, in the initial state, the fourth end **32** of the second arm **30** is rotated to attach to the first end **21** of the first arm **20**, and the buffering element **73** located between the first end **21** and the fourth end **32** helps cushion impact. Similarly, as shown in FIG. **20**, in the fully expanded state, the third end **31** of the second arm **30** is rotated to attach to the second end **22** of the first arm **20**, and the buffering element **74** located between the second end **22** and the third end **31** helps cushion impact. Certainly, in other embodiment, the arrangements of the buffering elements **73**, **74** are adjustable according to the practical requirements. The present is not limited thereto.

[0075] FIG. **21** and FIG. **26** show a swing-arm cable-management device according to a fourth embodiment of the present disclosure. In the embodiment, the structures, elements and functions of the swing-arm cable-management device **1c** are similar to those of the swing-arm cable-management device **1** in FIG. **1** to FIG. **10**, and are not redundantly described herein. In the embodiment, the guiding module **33** of the swing-arm cable-management device **1c** further

includes a guiding rod **36** embedded obliquely in the second arm **30**. The sliding component **40a** is slidably sleeved on the guiding rod **36**. The guiding rod **36** includes a rear end and a front end opposite to each other, and the rear end is disposed adjacent to the third end **31** and lower than the front end disposed adjacent to the fourth end **32**. Preferably but not exclusively, the lowest point of the guiding rod **36** is disposed adjacent to the third end **31** of the second arm **30**; and the highest point of the guiding rod **36** is disposed adjacent to the fourth end **32** of the second arm **30**. In the embodiment, the clamp component **60** is connected to the sliding component **40a** through a rope **50b**. One end of the rope **50b** is connected to the sliding component **40a** and another end of the rope **50b** is fixed to the clamp component **60**. Certainly, the slop of the guiding rod **36**, the types of the guiding rod **36** and the sliding component **40a** are adjustable according to the practical requirements, and the present disclosure is not limited thereto. In addition, the functions of the guiding rod **36** and the sliding component **40a** are similar to those of the guiding module **33** and the sliding component **40** in the above embodiments, and are not redundantly described herein.

[0076] In the embodiment, the swing-arm cable-management device **1c** further includes torsion springs **70a** disposed around the first pivot shaft **C1** and the second pivot shaft **C2**, respectively. Preferably but not exclusively, the type of torsion springs **70a** is different from the torsion spring **70** in the above embodiment, but it can also be configured to provide the elastic restoring force to keep the first arm **20** and the mounting base **10** or/and the second arm **30** and the first arm **20** folded in the initial statue. In other embodiments, the type and the arrangement of the torsion springs **70a** are adjustable according to the practical requirements. In addition, the functions of the torsion springs **70a** are similar to those of the torsion springs **70** in the above embodiments, and are not redundantly described herein.

[0077] FIG. **27** and FIG. **31** show a swing-arm cable-management device according to a fifth embodiment of the present disclosure. In the embodiment, the structures, elements and functions of the swing-arm cable-management device **1d** are similar to those of the swing-arm cable-management device **1c** in FIG. **21** to FIG. **26**, and are not redundantly described herein. In the embodiment, the guiding module **33** of the swing-arm cable-management device **1d** includes a guiding rod **36** embedded obliquely in the second arm **30**. The sliding component **40b** is slidably sleeved on the guiding rod **36**, and connected to the clamp component **60** through the bottom opening **34**. The guiding rod **36** includes a rear end and a front end opposite to each other, and the rear end is disposed adjacent to the third end **31** and lower than the front end disposed adjacent to the fourth end **32**. Preferably but not exclusively, the lowest point of the guiding rod **36** is disposed adjacent to the third end **31** of the second arm **30**; and the highest point of the guiding rod **36** is disposed adjacent to the fourth end **32** of the second arm **30**. In the embodiment, the sliding component **40b** is further extended downward and connected to the clamp component **60** through the bottom opening **34**. Certainly, the slop of the guiding rod **36**, the types of the guiding rod **36** and the sliding component **40b** are adjustable according to the practical requirements, and the present disclosure is not limited thereto. In addition, the functions of the guiding rod **36** and the sliding component **40b** are similar to those of the guiding module **33** and the sliding component **40** in the above embodiments, and are not redundantly described herein.

[0078] Please refer to FIG. **21** to FIG. **31**. Notably, in the above embodiments, the swing-arm cable-management devices **1c**, **1d** include the buffering elements **73a**, **74a**, **75**, which are configured to provide a buffering function for collisions when the swing-arm cable-management devices **1c**, **1d** are operated. In the embodiment, the buffering element **73a** is disposed on the fourth end **32** of the second arm **30**, spatially corresponding to the first end **21** of the first arm **20**, and configured to provide the buffering function when the second arm **30** is folded relative to first arm **20**. In other embodiments, the buffering element **73a** is disposed between the fourth end **32** and the first end **21** to provide the buffering function. The function of the buffer element **73a** is similar to that of the buffer element **73** in the above embodiment (referring to FIG. **19**). The type and the arrangement of the buffering element **73a** are adjustable according to the practical requirements,

and not redundantly described herein. In the embodiment, the buffering element **74a** is disposed on the second end **22** of the first arm **20**, spatially corresponding to the third end **31** of the second arm **30**, and configured to provide the buffering function when the second arm **30** is folded relative to first arm **20**. In other embodiments, the buffering element **74a** is disposed between the second end **22** and the third end **31** to provide the buffering function. The function of the buffer element **74a** is similar to that of the buffer element **74** in the above embodiment (referring to FIG. **20**). The type and the arrangement of the buffering element **74a** are adjustable according to the practical requirements, and not redundantly described herein. In the embodiment, the buffering element **75** is disposed on the mounting base **10**, spatially corresponding to the first end **21** of the first arm **20**, and configured to provide the buffering function when the first arm **20** is folded relative to mounting base **10**. In other embodiments, the buffering element **75** is disposed between the mounting base **10** and the first end **21** to provide the buffering function. Certainly, the type and the arrangements of the buffering elements **75** are adjustable according to the practical requirements. The present is not limited thereto. The present disclosure is not limited thereto and not redundantly described hereafter.

[0079] In summary, the present disclosure provides a swing-arm cable-management device holding an electric vehicle charging cable by connecting a clamp component to a sliding component on a sloped guiding module and combining a swing arm, so as to manage the electric vehicle charging cable when in use and idle, avoid damage to the charging cable and the charging gun head. Furthermore, by connecting a clamp component to a sliding component disposed on a sloped guiding module and disposing the sloped guiding module on a multi-section swing arms with torsion springs, a basic function of expanded support for the charging gun and the charging cable is achieved. It also provides the function of automatically returning the charging gun and charging cable to avoid damage to the charging gun and charging cable. When the charging gun is not in use, the multi-section swing arms of the swing-arm cable-management device is folded to a minimum length through the action of the torsion springs. At the same time, the sliding component connected to the clamp component of the charging cable and slidably disposed on the sloped guiding module is automatically returned by the gravity action of the charging cable, and moved to the lowest point of the sloped guiding module, thereby driving the charging cable to an initial status with the smallest footprint. On the other hand, when the user uses the charging gun to pull the charging cable, the clamp component of the charging cable drives the sliding component to move to the highest point of the sloped guiding module, and at the same time the multi-section swing arms are fully expanded, so that the charging gun can be used to charge the electric vehicle in the charging operation easily. When the user has finished the operation of the charging gun, he only needs to release the charging gun. The gravity of the charging cable drives the sliding component to automatically return to the lowest point of the sloped guiding module through the clamp component. The multi-section swing arm is folded and merged as the minimum length through the action of the torsion spring, so that the charging cable and the charging gun are moved back to the initial status. With the swing-arm cable-management device of the present disclosure, no matter whether the multi-section swing arms are unfolded or folded, the charging gun and the charging cable will not touch the ground. It reduces the risk of damage to the charging gun and the charging cable. In addition, it allows to add a limiting mechanism for limiting a rotation angle of the first arm and the second arm, or add buffering elements for providing a buffering function between the first arm and the second arm. Compared with the conventional cable management device that uses counterweights and pulleys merely, the multi-section arm-folding structure constructed by the multi-section swing arms is significantly reduced in both volume and weight. It not only simplifies the structure, but also reduces the cost. The present disclosure includes the industrial applicability and the inventive steps.

[0080] While the disclosure has been described in terms of what is presently considered to be the most practical and preferred embodiments, it is to be understood that the disclosure needs not be

limited to the disclosed embodiment. On the contrary, it is intended to cover various modifications and similar arrangements included within the spirit and scope of the appended claims which are to be accorded with the broadest interpretation so as to encompass all such modifications and similar structures.

Claims

1. A swing-arm cable-management device comprising: a mounting base configured to be mounted on a lateral wall of a charging machine; a first arm comprising a first end and a second end opposite to each other, wherein the first end is pivotally connected to the mounting base through a first pivot shaft perpendicular to the ground, so that the first arm is allowed to rotate relative to the mounting base around the first pivot shaft; a second arm comprising a third end and a fourth end opposite to each other, wherein the third end is pivotally connected to the second end of the first arm through a second pivot shaft perpendicular to the ground, so that the second arm is allowed to rotate relative to the first arm through the second pivot shaft; a guiding module disposed on the second arm and slopped to increase height along a horizontal direction from third end to the fourth end, wherein the guiding module comprises a rear end and a front end opposite to each other, and the rear end is disposed adjacent to the third end and lower than the front end disposed adjacent to the fourth end; a sliding component slidably disposed on the guiding module; and a clamp component connected to the sliding component and configured to fasten a charging cable of the charging machine, wherein when the charging cable is idle, the clamp component is pulled downwardly to drive the sliding component to move to the rear end of the guiding module due to a gravity action of the charging cable, wherein when the charging cable is in use and expanded by a charging gun, the clamp component is pulled away from the mounting base to drive the sliding component to move to the front end of the guiding module due to a pull action on the charging gun.
2. The swing-arm cable-management device according to claim 1, wherein the charging machine is disposed on a ground and the lateral wall of the charging machine is perpendicular to the ground, the mounting base is mounted on the lateral wall of the charging machine and located adjacent to a top of the charging machine, and the charging cable is connected between the lateral wall of the charging machine and the charging gun.
3. The swing-arm cable-management device according to claim 1, further comprising at least one torsion spring, wherein the at least one torsion spring is disposed around the first pivot shaft or/and the second pivot shaft and configured to provide an elastic restoring force to keep the first arm and the second arm fold in an initial statue.
4. The swing-arm cable-management device according to claim 1, wherein when the clamp component on the first arm is pulled downwardly to drive the sliding component to move to the rear end of the guiding module due to the gravity action of the charging cable, the first arm and the second arm are folded and attached to the lateral wall of the charging machine, wherein when the clamp component is pulled away from the mounting base to drive the sliding component to move to the front end of the guiding module due to the pull action on the charging gun, the first arm and the second arm are unfolded in a front of the charging machine.
5. The swing-arm cable-management device according to claim 1, wherein the first arm and the second arm are an elongated hollow frame, respectively.
6. The swing-arm cable-management device according to claim 5, wherein the guiding module comprises two guiding grooves, the two guiding grooves pass through two opposite walls of the second arm, the sliding component is located between the two guiding grooves and comprises a horizontal shaft and two fastening nuts, and the horizontal shaft and the two fastening nuts are configured to install the sliding component on the guiding module.
7. The swing-arm cable-management device according to claim 5, wherein the elongated hollow frame of the second arm comprises a bottom opening, wherein the sliding component is placed

between two guiding grooves of the guiding module and comprises a horizontal shaft, and the horizontal shaft passes through the two guiding grooves of the guiding module and a central axis of the sliding component, wherein two ends of the horizontal shaft are limited by two fastening nuts, and the two fastening nuts are located outside two opposite walls of the elongated hollow frame, respectively, so that the sliding component is slidably disposed on the guiding module.

8. The swing-arm cable-management device according to claim 7, wherein the sliding component and the clamp component are connected through a rope, and the rope passes through the bottom opening.

9. The swing-arm cable-management device according to claim 8, wherein the rope is wound on the sliding component and comprises an end fixed to the clamp component and another end fixed to the third end of the second arm.

10. The swing-arm cable-management device according to claim 8, wherein the rope is wound on the sliding component and comprises two ends fixed to the clamp component.

11. The swing-arm cable-management device according to claim 5, wherein the elongated hollow frame of the second arm comprises a bottom opening, wherein the guiding module comprises a tubular guiding rail obliquely embedded in the second arm, and the sliding component comprises a pulley set slidably disposed in the tubular guiding rail.

12. The swing-arm cable-management device according to claim 11, wherein the sliding component and the clamp component are connected through a rope, and the rope passes through the bottom opening.

13. The swing-arm cable-management device according to claim 5, wherein the elongated hollow frame of the second arm comprises a bottom opening, wherein the guiding module comprises a guiding rod obliquely embedded in the second arm, and the sliding component is slidably sleeved on the guiding rod and connected to the clamp component through the bottom opening.

14. The swing-arm cable-management device according to claim 13, wherein the sliding component and the clamp component are connected through a rope, and the rope passes through the bottom opening.

15. The swing-arm cable-management device according to claim 1, further comprising a limiting mechanism, wherein the limiting mechanism is disposed between the second end of the first arm and the third end of the second arm, and configured to limit rotation angle of the first arm and the second arm.

16. The swing-arm cable-management device according to claim 1, further comprising a buffering element, wherein the buffering element is disposed between the mounting base and the first end and between the fourth end and the first end, and configured to provide a buffering function for collisions when the first arm is folded relative to the mounting base and the second arm is folded relative to the first arm.

17. The swing-arm cable-management device according to claim 1, further comprising a buffering element, wherein the buffering element is disposed between the second end and the third end, and configured to provide a buffering function for collisions when the second arm is unfolded relative to the first arm.
