

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410959
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Lim; Hyeonkyu et al.

Refrigerator

Abstract

A refrigerator including a water supplier; an ice-making housing in a storage compartment; a first tray in the ice-making housing and including a first ice-making cell, and a first sealing portion formed along an edge of the first ice-making cell; and a second tray including a second ice-making cell, and a second sealing portion formed along an edge of the second ice-making cell, wherein the second tray is movable horizontally to engage with the first tray and couple the first and second ice-making cell, and while the second tray is engaged with the first tray, the second sealing portion overlaps the first sealing portion to prevent leakage from the first and second ice-making cells, the first ice-making cell forms a first portion of ice with water from the water supplier, and the second ice-making cell forms a second portion of the ice with water from the water supplier.

Inventors: Lim; Hyeonkyu (Suwon-si, KR), Kim; Juyeong (Suwon-si, KR), Park; Hyunuk (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 81382937

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 18/124369

Filed: March 21, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230221052 A1	Jul. 13, 2023

Foreign Application Priority Data

KR	10-2020-0142254	Oct. 29, 2020
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/KR2021/013397 20210929 PENDING child-doc US 18124369

Publication Classification

Int. Cl.: F25C1/04 (20180101); F25C1/25 (20180101)

U.S. Cl.:

CPC F25C1/04 (20130101); F25C1/25 (20180101); F25C2400/10 (20130101)

Field of Classification Search

CPC: F25C (1/04); F25C (1/25); F25C (2400/10)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9074802	12/2014	Culley et al.	N/A	N/A
9074803	12/2014	Culley	N/A	N/A
9151527	12/2014	Boarman et al.	N/A	N/A
9234688	12/2015	Son et al.	N/A	N/A
9234689	12/2015	Son et al.	N/A	N/A
9335081	12/2015	Son et al.	N/A	N/A
9470448	12/2015	Culley et al.	N/A	N/A
9581372	12/2016	Lee et al.	N/A	N/A
9651290	12/2016	Boarman et al.	N/A	N/A
9696079	12/2016	Boarman et al.	N/A	N/A
11874048	12/2023	Kim et al.	N/A	N/A
2012/0007264	12/2011	Kondou et al.	N/A	N/A
2013/0014536	12/2012	Son	62/340	F25C 1/25
2013/0327074	12/2012	Lee et al.	N/A	N/A
2014/0165598	12/2013	Boarman et al.	N/A	N/A
2014/0165618	12/2013	Culley	62/71	F25C 1/18
2014/0165619	12/2013	Culley	N/A	N/A
2014/0165623	12/2013	Guarino et al.	N/A	N/A
2016/0138844	12/2015	Boarman et al.	N/A	N/A
2016/0252287	12/2015	Dirnberger et al.	N/A	N/A
2019/0293335	12/2018	Bertolini et al.	N/A	N/A
2020/0158403	12/2019	Hong et al.	N/A	N/A
2020/0158410	12/2019	Kim	N/A	F25C 1/24
2021/0310714	12/2020	Olvera	N/A	F25C 1/24
2022/0260296	12/2021	Ji	N/A	F25C 1/25
2023/0124642	12/2022	Kim	62/71	F25C 1/243

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
------------	------------------	---------	-----

102878743	12/2012	CN	N/A
206410387	12/2016	CN	N/A
209689245	12/2018	CN	N/A
111197886	12/2019	CN	N/A
0 326 144	12/1992	EP	N/A
2 549 207	12/2016	EP	N/A
3 261 449	12/2019	EP	N/A
6298123	12/2017	JP	N/A
10-2013-0009332	12/2012	KR	N/A
10-2014-0088321	12/2013	KR	N/A
10-1643635	12/2015	KR	N/A
20-2017-0000751	12/2016	KR	N/A
20-0482995	12/2016	KR	N/A
10-1850918	12/2017	KR	N/A
10-1890939	12/2017	KR	N/A
10-2019-0100119	12/2018	KR	N/A
10-1968563	12/2018	KR	N/A

OTHER PUBLICATIONS

Supplementary European Search Report dated Jan. 2, 2024 for European Application No. 21886587.1. cited by applicant

Extended European Search Report dated Mar. 25, 2024 for European Application No. 21886587.1. cited by applicant

International Search Report, PCT/ISA/210, dated Jan. 19, 2023, in International Application PCT/KR2021/013397. cited by applicant

Chinese Office Action dated May 24, 2025 for Chinese Application No. 202180067895.9. cited by applicant

Primary Examiner: Martin; Elizabeth J

Attorney, Agent or Firm: STAAS & HALSEY LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation application under 35 U.S.C. § 111(a) of international Application No. PCT/KR2021/013397, filed on Sep. 29, 2021, which claims priority to Korean Patent Application No. 10-2020-0142254, filed on Oct. 29, 2020, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

1. Field

(1) The present disclosure relates to a refrigerator, and more particularly, to a refrigerator including an improved ice making assembly.

2. Description of the Related Art

(2) In general, a refrigerator is a device for cooling and storing food using a refrigeration cycle composed of a compressor, a condenser, an expansion valve, and an evaporator. An ice maker configured to make ice may be provided inside the refrigerator.

(3) The ice maker includes an ice-making tray for making ice, an ejector for separating ice from the ice-making tray, an ice bucket for storing the ice separated from the ice-making tray, and a

controller for controlling the entire ice-making process. Accordingly, the ice may be automatically produced and separated.

(4) In this case, an ice maker that is not a pressing type may be provided with an open upper side so as to make ice having one flat surface. When the ice is made, adjacent ices are adhered to each other, and thus it is difficult to make ice in a certain size or shape.

(5) Further, in the pressing type ice maker, a plurality of trays may form an ice making cell. The plurality of trays may be separated vertically and one tray may be rotationally coupled to another tray.

(6) In this case, because the ice bucket is not provided in a rotation radius of the tray, an ice storage capacity may be reduced. In addition, remaining water may permeate into gaps between the plurality of trays, and thus the shape of the ice may not be neat and a large number of crumbs may be generated.

SUMMARY

(7) Aspects of embodiments of the disclosure will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

(8) According to an embodiment of the disclosure, a refrigerator may include a storage compartment; a water supplier to supply water received from an external water supply source; an ice-making housing in the storage compartment; a first tray disposed in the ice-making housing and including a first ice-making cell, and a first sealing portion formed along an edge of the first ice-making cell; and a second tray including a second ice-making cell, and a second sealing portion formed along an edge of the second ice-making cell. The first tray and the second tray may be configured so that the second tray is movable horizontally with respect to the first tray to engage with the first tray and couple the first ice-making cell to the second ice-making cell, and while the second tray is engaged with the first tray, the second sealing portion overlaps the first sealing portion to prevent leakage from the first ice-making cell and the second ice-making cell, the first ice-making cell forms a first portion of ice with water supplied from the water supplier, and the second ice-making cell forms a second portion of the ice with the water supplied from the water supplier.

(9) According to an embodiment of the disclosure, the first sealing portion includes a recess recessed inward from an outer circumferential surface of the first tray, and the second sealing portion includes a protrusion extending outward from an inner circumferential surface of the second tray and configured to be mountable on the recess to maintain a seal between the first tray and the second tray.

(10) According to an embodiment of the disclosure, the refrigerator further includes a cover frame coupled to the ice-making housing; a first case formed on one surface of the cover frame to receive the first tray; and a second case configured to be moved inside the cover frame, and to receive the second tray.

(11) According to an embodiment of the disclosure, the refrigerator further includes a rack gear connected to the second case and configured to be moved relative to the cover frame, wherein the second case is moved horizontally with respect to the cover frame in conjunction with a movement of the rack gear.

(12) According to an embodiment of the disclosure, the refrigerator further includes a driver configured to generate power; and a pinion configured to be rotated according to the drive of the driver; wherein the pinion and the rack gear are engaged to convert a rotational motion of the driver into a linear motion.

(13) According to an embodiment of the disclosure, the refrigerator further includes an elastic member to connect the rack gear to the second case, wherein in response to the rack gear being maximally moved in a direction in which the second case moves toward the first case, the elastic member is tensioned and airtightness between the second case and the first case is maintained by an

elastic restoring force.

(14) According to an embodiment of the disclosure, the refrigerator further includes a first ejector including a pressing portion, wherein the first case includes a through hole formed to correspond to a position of the ice-making cell, and the pressing portion is configured to pass through the through hole so as to press the first tray.

(15) According to an embodiment of the disclosure, the first ejector includes a body configured to support the pressing portion, and a leg extending from each of opposite ends of the body and inserted into respective side portions of the cover frame, the second case includes a protrusion extending from each of opposite ends of the second case to be respectively received in the legs, and in response to the second case being moved in a direction away from the first case, the protrusions interfere with the legs, and the first ejector is moved in a direction closer to the first case such that the pressing portion presses the first tray.

(16) According to an embodiment of the disclosure, the refrigerator further includes a second ejector fixed to one side of the cover frame and including a pressing portion extending toward the second case, wherein in response to the second case being moved in a direction away from the first case, the pressing portion of the second ejector passes through the second case so as to press the second tray.

(17) According to an embodiment of the disclosure, the ice-making cells of the first tray and the second tray are each configured in a semi-spherical shape.

(18) According to an embodiment of the disclosure, the refrigerator further includes a cover frame coupled to an inside of the ice making housing; and a water path configured on an upper surface of the cover frame to guide the water supplied from the water supplier to flow into the first tray and the second tray, wherein a plurality of ice-making cells are formed in the first tray and the second tray.

(19) According to an embodiment of the disclosure, the water path includes a plurality of flow paths to equally supply water to each of the plurality of ice-making cells of the first tray and the second tray.

(20) According to an embodiment of the disclosure, the refrigerator controls the water supplier to allow water to be divided and supplied in stages according to a water level of the plurality of ice-making cells.

(21) According to an embodiment of the disclosure, the water path includes a single flow path to guide the water to only one ice-making cell among the plurality of ice-making cells, and each of the plurality of ice-making cells is configured to have a height difference so that the water overflows the one ice-making cell among the plurality of ice-making cells to sequentially fill the remaining ice-making cells among the plurality of ice-making cells with the water.

(22) According to an embodiment of the disclosure, the water path includes a single flow path to guide the water to only one ice-making cell among the plurality of ice-making cells, and the first tray and the second tray include a connection flow path provided to allow the water, which is supplied to the one ice-making cell, to flow to an adjacent ice-making cell among the plurality of ice-making cells.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) These and/or other embodiments of the disclosure will become apparent and more readily appreciated from the following description of the embodiments, taken in conjunction with the accompanying drawings of which:

(2) FIG. 1 is a perspective view of a refrigerator according to an embodiment of the disclosure.

(3) FIG. 2 is an enlarged view of some components of the refrigerator according to an embodiment

of the disclosure.

(4) FIG. 3 is a view of an ice making assembly of the refrigerator according to an embodiment of the disclosure.

(5) FIG. 4 is an exploded perspective view of the ice making assembly of FIG. 3 according to an embodiment of the disclosure.

(6) FIG. 5 is an enlarged view of a part of a first tray of the refrigerator according to an embodiment of the disclosure.

(7) FIG. 6 is an enlarged view of a part of a second tray of the refrigerator according to an embodiment of the disclosure.

(8) FIG. 7 is a cross-sectional view illustrating a state in which the first tray and the second tray of the refrigerator according to an embodiment of the disclosure are coupled.

(9) FIG. 8 is a bottom perspective view of a cover frame of the refrigerator according to an embodiment of the disclosure.

(10) FIG. 9 is an exploded perspective view illustrating a coupling between a first ejector and a second case of the refrigerator according to an embodiment of the disclosure.

(11) FIG. 10 is a view illustrating a first state of the ice making assembly of the refrigerator according to an embodiment of the disclosure.

(12) FIG. 11 is a view illustrating a second state of the ice making assembly of the refrigerator according to an embodiment of the disclosure.

(13) FIG. 12 is a view illustrating a third state of the ice making assembly of the refrigerator according to an embodiment of the disclosure.

(14) FIG. 13 is a side cross-sectional view illustrating a state before a rack gear is maximally moved in the ice making assembly in the first state of FIG. 10 according to an embodiment of the disclosure.

(15) FIG. 14 is a side cross-sectional view illustrating a state in which the rack gear is maximally moved in the ice making assembly in the first state of FIG. 10 according to an embodiment of the disclosure.

(16) FIG. 15 is a cross-sectional view illustrating a relationship between the first and second ejectors and first and second trays in the ice making assembly in the second state of FIG. 11 according to an embodiment of the disclosure.

(17) FIG. 16 is a cross-sectional view illustrating the ice making assembly in the third state of FIG. 12 according to an embodiment of the disclosure.

(18) FIG. 17 is a cross-sectional view illustrating a relationship between the first ejector and the second case in the ice making assembly in the second state of FIG. 15 according to an embodiment of the disclosure.

(19) FIG. 18 is a cross-sectional view illustrating a relationship between the first ejector and the second case in the ice making assembly in the third state of FIG. 16 according to an embodiment of the disclosure.

(20) FIG. 19 is a top view illustrating a state in which a water path of the refrigerator according to an embodiment of the disclosure is coupled to the cover frame.

(21) FIG. 20 is a top view illustrating only the cover frame of the refrigerator according to an embodiment of the disclosure.

(22) FIG. 21 is a view illustrating a state, in which the first ejector and the cover frame are omitted in the ice making assembly of FIG. 3, when viewed from the first tray side, according to an embodiment of the disclosure.

(23) FIG. 22 is a view illustrating an ice making assembly of a refrigerator according to another embodiment of the disclosure.

(24) FIG. 23 is a top view of the ice making assembly of FIG. 22 according to an embodiment of the disclosure.

(25) FIG. 24 is a view illustrating a first tray and a second tray of the refrigerator according to

another embodiment of the disclosure.

(26) FIG. 25 is a cross-sectional view illustrating a state in which the first tray and the second tray are coupled in the ice making assembly of the refrigerator according to another embodiment of the disclosure.

(27) FIG. 26 is a cross-sectional view illustrating a method of supplying water in the ice making assembly of the refrigerator according to another embodiment of the disclosure.

(28) FIG. 27 is a view illustrating an ice making assembly of a refrigerator according to still another embodiment of the disclosure.

(29) FIG. 28 is a top view of the ice making assembly of FIG. 27 according to an embodiment of the disclosure.

(30) FIG. 29 is a view illustrating a first tray, a first fixing frame, a second fixing frame, a second tray, and a second case of the refrigerator according to still another embodiment of the disclosure.

(31) FIG. 30 is a front view of the first tray of the refrigerator according to still another embodiment of the disclosure.

(32) FIG. 31 is a cross-sectional view illustrating a method of supplying water in the ice making assembly of the refrigerator according to still another embodiment of the disclosure.

DETAILED DESCRIPTION

(33) Embodiments described in the disclosure and configurations shown in the drawings are merely examples of the embodiments of the disclosure, and may be modified in various different ways at the time of filing of the present application to replace the embodiments and drawings of the disclosure.

(34) In addition, the same reference numerals or signs shown in the drawings of the disclosure indicate elements or components performing substantially the same function.

(35) Also, the terms used herein are used to describe the embodiments and are not intended to limit and/or restrict the disclosure. The singular forms “a,” “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. In this disclosure, the terms “including”, “having”, and the like are used to specify features, numbers, steps, operations, elements, components, or combinations thereof, but do not preclude the presence or addition of one or more of the features, elements, steps, operations, elements, components, or combinations thereof.

(36) It will be understood that, although the terms first, second, third, etc., may be used herein to describe various elements, but elements are not limited by these terms. These terms are only used to distinguish one element from another element. For example, without departing from the scope of the disclosure, a first element may be termed as a second element, and a second element may be termed as a first element. The term of “and/or” includes a plurality of combinations of relevant items or any one item among a plurality of relevant items.

(37) In the following detailed description, the terms of “up and down direction”, “lower side”, “front and rear direction” and the like may be defined by the drawings, but the shape and the location of the component is not limited by the term.

(38) Embodiments of the disclosure may be directed to providing a refrigerator including an improved structure in which a plurality of trays are movable to be in horizontal contact with each other to make ice. Embodiments of the disclosure may be directed to providing a refrigerator including a sealing portion to maintain a seal between a plurality of horizontally coupled trays when ice is formed. Embodiments of the disclosure may be directed to providing a refrigerator capable of increasing a transparency of ice to be formed.

(39) An ice storage space under a plurality of trays may be increased because the plurality of trays are horizontally coupled to each other and separated from each other. By increasing airtightness between a plurality of trays, it is possible to form ice in a neat sphere shape and to minimize crumbs of the ice. By supplying water step by step according to a water level in an ice making cell, it is possible to ensure transparency of ice.

(40) Hereinafter embodiments of the disclosure will be described in detail with reference to the accompanying drawings.

(41) FIG. 1 is a perspective view of a refrigerator according to one embodiment of the present disclosure. FIG. 2 is an enlarged view of some components of the refrigerator according to one embodiment of the present disclosure.

(42) Referring to FIGS. 1 and 2, a refrigerator **1** may include a main body **10**, a storage compartment **20** provided inside the main body **10**, and a door configured to open and close the storage compartment **20**.

(43) A bottom mount freezer (BMF) refrigerator **1**, in which a refrigerating compartment **21** is provided at an upper side and a freezing compartment **22** is provided at a lower side, will be described as an example of the refrigerator **1** according to one embodiment of the present disclosure. However, the present disclosure is not limited thereto, but may be applied to various types of refrigerators **1** such as a top mount freezer (TMF) refrigerator **1**, a French door (FDR) refrigerator **1**, a 4DOOR type refrigerator **1**, and a side-by-side (SBS) refrigerator **1**.

(44) The storage compartment **20** may include the refrigerating compartment **21** and the freezing compartment **22**.

(45) At least one shelf **12** for loading food or goods may be installed inside the refrigerating compartment **21**. In addition, a storage container (not shown) for storing fresh foods may be provided inside the refrigerating compartment **21**.

(46) The refrigerating compartment **21** may be opened and closed by a refrigerating compartment door **30**, and the refrigerating compartment door **30** may be rotatably mounted on the main body **10**. The refrigerating compartment door **30** may be configured to open and close an open front surface of the refrigerating compartment **21**. The refrigerating compartment door **30** is hinged to the main body **10** so as to be rotatable forward.

(47) The freezing compartment **22** may be opened and closed by a freezing compartment door **40**. The freezing compartment door **40** may be rotatably mounted on the main body **10**. The freezing compartment door **40** is configured to open and close an open front surface of the freezing compartment **22**. The freezing compartment door **40** is hinged to the main body **10** so as to be rotatable forward.

(48) Door guards **13** for storing objects may be installed on inner surfaces of the refrigerating compartment door **30** and the freezing compartment door **40**. The door guard **13** may be provided in plurality.

(49) The inside of the refrigerator **1** may be cooled by a refrigeration cycle and maintained at a low temperature. Although not particularly shown, the refrigeration cycle may be configured to independently supply a refrigerant to the refrigerating compartment **21** and the freezing compartment **22**. The refrigerator **1** may include a compressor configured to compress a refrigerant and a condenser configured to condense the compressed refrigerant, and thus the refrigerant condensed in the condenser may be supplied along a flow path.

(50) The refrigerator **1** may include a mounting frame **70**. The mounting frame **70** may be coupled to an inner case **11** of the freezing compartment **22**.

(51) An ice making assembly **1000** (shown in FIG. 3) for making ice using cold air in the freezing compartment **22** may be disposed on one side of the freezing compartment **22**. In addition, an ice bucket **60** provided to store ice formed by the ice making assembly **1000** may be mounted on the mounting frame **70**.

(52) FIG. 2 illustrates a state in which an ice making housing **110** and the ice bucket **60** are arranged in the freezing compartment **22** without the mounting frame **70**.

(53) The ice making assembly **1000** may be accommodated inside the ice making housing **110** and the ice making housing **110** may be mounted on the mounting frame **70**. That is, the ice making housing **110** and the ice bucket **60** may be mounted on the mounting frame **70**.

(54) The refrigerator **1** may include a water supplier **50**. The water supplier **50** may be configured

to receive water from an external water supply source and deliver the water. Particularly, the water supplier **50** may be provided to receive water from the outside and deliver the water to the inside of the ice making assembly **1000**. The water supplier **50** may pass through the inner case **11** of the refrigerator **1** and communicate with the storage compartment **20**. Accordingly, a portion of the water supplier **50** may be embedded in a heat insulating material, and only one end of the water supplier **50** may be exposed to the storage compartment **20** of the refrigerator **1**.

(55) FIG. **3** is a view of an ice making assembly of the refrigerator according to one embodiment of the present disclosure. FIG. **4** is an exploded perspective view of the ice making assembly of FIG. **3**.

(56) Referring to FIGS. **3** and **4**, the ice making assembly **1000** may include a cover frame **120**. The cover frame **120** may be provided to be coupled to the ice making housing **110** inside the ice-making housing **110** (refer to FIG. **2**). The cover frame **120** may be provided in a box shape in which one side surface and a lower surface are open.

(57) The ice making assembly **1000** may include a water path **130**. The water path **130** may be mounted on one side of the cover frame **120**. Particularly, the water path **130** may be mounted on an upper surface of the cover frame **120**. The water path **130** may be provided to allow water, which is supplied from the water supplier **50**, to flow to the inside of the cover frame **120**. In other words, the water path **130** may be provided to allow water, which is supplied from the water supplier **50**, to flow to an inside of a first tray **170** and a second tray **270**.

(58) The ice making assembly **1000** may include a first case **140** formed on the cover frame **120**, and the first tray **170**, a first fixing frame **190**, and a first heating wire **160** that are accommodated in the first case **140**.

(59) The first case **140** may be formed on one surface of the cover frame **120**. The first case **140** may be integrally formed with the cover frame **120**, but may be provided as a separate member and then coupled to one surface of the cover frame **120**.

(60) The first case **140** may be provided to accommodate the first tray **170**. A detailed structure of the first case **140** will be described later with reference to FIG. **8**.

(61) The first tray **170** may be provided inside the ice making housing **110**. Particularly, the first tray **170** may be mounted inside the cover frame **120**. The first tray **170** may be formed of a material having elasticity.

(62) The first tray **170** may receive water from the water supplier **50**. The first tray **170** may include a first guide **172** to allow the supplied water to flow into an ice-making cell inside the first tray **170**. The first guide **172** may be formed on an upper side of the first tray **170**.

(63) The first tray **170** may include a first ice-making cell **173** provided to make a portion of ice. The first ice-making cell **173** may be provided in a substantially circular or semi-spherical shape. Accordingly, ice formed in the ice making assembly **1000** may be in a spherical shape. It is described that the ice making assembly **1000** of the refrigerator **1** according to one embodiment of the present disclosure includes three first ice-making cells **173**, but the number of first ice-making cells **173** is not limited thereto.

(64) The first tray **170** may include a first insertion hole **171**. The first insertion hole **171** may be provided in plurality.

(65) The first insertion hole **171** may be provided to allow a first coupling protrusion **191** of the first fixing frame **190** to be inserted thereinto. Accordingly, the first fixing frame **190** may fix the first tray **170** to the first case **140**. In other words, the first fixing frame **190** may fix the first tray **170** to one surface of the cover frame **120**.

(66) The first fixing frame **190** may include the first coupling protrusion **191**. The first coupling protrusion **191** may be provided in plurality in accordance with the number of first insertion holes **171**. The first coupling protrusion **191** may extend toward the first tray **170** from one surface of the first fixing frame **190**. The first coupling protrusion **191** may also be inserted into a first through hole **142** of the first case **140** to be described later and coupled to the first case **140**.

(67) The first fixing frame **190** may be provided to support an edge of the first ice-making cell **173** of the first tray **170**. Because the first tray **170** is formed of a material having elasticity, the first fixing frame **190** may reinforce an insufficient rigidity of the first tray **170**.

(68) The ice making assembly **1000** may include the first heating wire **160**. The first heating wire **160** may be disposed between the first tray **170** and the first case **140**. Particularly, the first heating wire **160** may be disposed between the first tray **170** and the cover frame **120**. By placing the first heating wire **160** to one surface of the first tray **170**, the ice may be easily separated from the first ice-making cell **173** after ice formation is completed in the first ice-making cell **173** of the first tray **170**.

(69) Therefore, the first case **140** formed on one surface of the cover frame **120**, and the first heating wire **160**, the first tray **170**, and the first fixing frame **190** may be fixed to one side of the cover frame **120**.

(70) The ice making assembly **1000** may include a second case **240**, and the second tray **270**, a second fixing frame **290**, and a second heating wire **260** that are accommodated in the second case **240**.

(71) The second case **240** may be configured to be moved inside the cover frame **120**.

(72) The second case **240** may be provided to accommodate the second tray **270**.

(73) The second case **240** may include a second tray receiving member **241**. The second tray receiving member **241** may be provided to accommodate a second ice-making cell **273** of the second tray **270**. Three second tray receiving members **241** may be provided in accordance with the number of second ice-making cells **273**.

(74) The second case **240** may include a second through hole **242**. The second through hole **242** may be formed by cutting the second tray receiving member **241**. The second through hole **242** may be provided to allow a pressing portion of a second ejector **250** to be described later to pass therethrough.

(75) The second case **240** may include a second fixer **243**. The second fixer **243** may be provided to allow a second coupling protrusion **291** of the second fixing frame **290** to be described later to be inserted therein.

(76) The second case **240** may include a second elastic member mounting member **244**. An elastic member **400** connecting a rack gear **330** to be described later and the second case **240** may be mounted on the second elastic member mounting member **244**.

(77) The second case **240** may include a protrusion **245**. The protrusion **245** may extend outward from a side surface of the second case **240**. The protrusion **245** may be inserted into a leg **153** of a first ejector **150** to be described later. A detail description thereof will be described later.

(78) The second tray **270** may be disposed inside the ice making housing **110**. Particularly, the second tray **270** may be mounted inside the cover frame **120**. The second tray **270** may be formed of a material having elasticity. The second tray **270** may be provided to make the rest of the ice by being engaged with the first tray **170**.

(79) The second tray **270** may receive water from the water supplier **50**. The second tray **270** may include a second guide **272** to allow the supplied water to flow into the second ice-making cell **273** inside the second tray **270**. The second guide **272** may be formed on an upper side of the second tray **270**.

(80) The second tray **270** may include the second ice-making cell **273** provided to form the remaining portion of the ice. The second ice-making cell **273** may be provided in a substantially circular shape. Accordingly, the ice formed in the ice making assembly **1000** may be in a spherical shape. It is described that the ice making assembly **1000** of the refrigerator **1** according to one embodiment of the present disclosure includes three second ice-making cells **273**, but the number of second ice-making cells **273** is not limited thereto.

(81) The second tray **270** may include a second insertion hole **271**. The second insertion hole **271** may be provided in plurality.

(82) The second insertion hole **271** may be provided to allow the second coupling protrusion **291** of the second fixing frame **290** to be inserted thereinto. Accordingly, the second fixing frame **290** may fix the second tray **270** to the second case **240**. In other words, the second fixing frame **290**, the second tray **270**, and the second case **240** may be integrally driven.

(83) The second fixing frame **290** may include the second coupling protrusion **291**. The second coupling protrusions **291** may be provided in plurality in accordance with the number of second insertion holes **271**. The second coupling protrusion **291** may extend toward the second tray **270** from one surface of the second fixing frame **290**. The second coupling protrusion **291** may also be inserted into the second through hole **242** of the second case **240** and coupled to the second case **240**. That is, the second coupling protrusion **291** may pass through the second insertion hole **271** of the second tray **270** and be coupled to the second through hole **242** of the second case **240**.

(84) The second fixing frame **290** may be provided to support an edge of the second ice-making cell **273** of the second tray **270**. Because the second tray **270** is formed of a material having elasticity, the second fixing frame **290** may reinforce an insufficient rigidity of the second tray **270**.

(85) The ice making assembly **1000** may include the second heating wire **260**. The second heating wire **260** may be disposed between the second tray **270** and the second case **240**. By placing the second heating wire **260** to one surface of the second tray **270**, the ice may be easily separated from the second ice-making cell **273** after ice formation is completed in the second ice-making cell **273** of the second tray **270**.

(86) Accordingly, the second case **240**, the second heating wire **260**, the second tray **270**, and the second fixing frame **290** are provided to move integrally on the other side of the cover frame **120**. In addition, the second case **240**, the second heating wire **260**, the second tray **270**, and the second fixing frame **290** are provided to be moved horizontally with respect to the cover frame **120**. In other words, the second tray **270** provided to form ice is configured to be moved horizontally with respect to the first tray **170**.

(87) The ice making assembly **1000** may include the first ejector **150** and a second ejector **250**.

(88) The first ejector **150** may be provided to press the first tray **170**. Particularly, the first ejector **150** may be provided to press the first ice-making cell **173** of the first tray **170**.

(89) The first ejector **150** may be provided to pass through the first through hole **142** formed in the first case **140** to be described later. Particularly, a first pressing portion **152** of the first ejector **150** may be provided to press the first tray **170** by passing through the first through hole **142**.

(90) The first ejector **150** may be configured to be moved with respect to the cover frame **120**. The first ejector **150** may be movable based on the movement of the second case **240**. A detail description of the coupling of the first ejector **150** and the second case **240** will be described later.

(91) The second ejector **250** may be fixed to one side of the cover frame **120**. The second ejector **250** may be configured to press the second tray **270**. Particularly, the second ejector **250** may be configured to press the second ice-making cell **273** of the second tray **270**.

(92) The second ejector **250** may include a second body **251**, a second pressing portion **252**, and a frame coupler **253**. The second body **251** may extend in a direction parallel to the second case **240**. The second pressing portion **252** may extend from the second body **251** toward the second case **240**. The frame coupler **253** may be formed at opposite ends of the second body **251** and coupled to the cover frame **120**.

(93) The second ejector **250** may be provided to pass through the second through hole **242** formed in the second case **240**. Particularly, the second pressing portion **252** of the second ejector **250** may pass through the second through hole **242** and press the second tray **270**.

(94) That is, as the second ejector **250** is fixed to the cover frame **120** and the second tray **270** is moved with respect to the cover frame **120**, the second ejector **250** may press the second tray **270**.

(95) The ice making assembly **1000** may include the driver **300**, a pinion **310**, a bar **320**, a rack gear **330**, and the elastic member **400**.

(96) The driver **300** may be configured to generate power. Various electrical components such as a

motor and a circuit board may be disposed inside the driver **300**. The driver **300** may be coupled to the cover frame **120**.

(97) The pinion **310** may be coupled to the driver **300** to transmit power generated from the driver **300**. The pinion **310** may be provided as a pair. A pair of pinions **310** may be connected by the bar **320**. The pinion **310** may be provided to be rotated according to driving of the driver **300**. The pinion **310** may be provided in a sawtooth shape to engage with the rack gear **330**.

(98) The rack gear **330** may be provided to be movable with respect to the cover frame **120**. Particularly, based on the rotational motion of the pinion **310**, the rack gear **330** may move linearly.

(99) The rack gear **330** may include a support member **332** supported by the cover frame **120**. The rack gear **330** may include a toothed member **331** formed on an upper surface of the support member **332**. The toothed member **331** of the rack gear **330** and the pinion **310** may be engaged and thus the rack gear **330** may be moved horizontally with respect to the cover frame **120**.

(100) The rack gear **330** may include a first elastic member mounting member **333** extending from the support member **332**. The elastic member **400** to be described later may be mounted on the first elastic member mounting member **333**.

(101) That is, the pinion **310** and the rack gear **330** are meshed with each other to convert a rotational motion of the driver **300** into a linear motion. However, embodiments of the present disclosure are not limited thereto, and any structure capable of converting a rotational motion into a linear motion may be applied.

(102) The elastic member **400** may be provided to connect the rack gear **330** and the second case **240**. That is, the rack gear **330** and the second case **240** may be connected.

(103) Accordingly, as the rack gear **330** receives power from the driver **300** and moves, the second case **240** may be moved horizontally with respect to the cover frame **120** in conjunction with the rack gear **330**. In other words, the second tray **270** and the second case **240** may be linearly moved with respect to the cover frame **120** by the rack gear **330**.

(104) That is, as the movement of the second case **240** is acted integrally with the second tray **270**, the second heat wire **260**, and the second fixing frame **290**, the second tray **270** may be moved horizontally with respect to the first tray **170**.

(105) FIG. 5 is an enlarged view of a part of a first tray of the refrigerator according to one embodiment of the present disclosure. FIG. 6 is an enlarged view of a part of a second tray of the refrigerator according to one embodiment of the present disclosure. FIG. 7 is a cross-sectional view illustrating a state in which the first tray and the second tray of the refrigerator according to one embodiment of the present disclosure are coupled.

(106) Referring to FIGS. 5 to 7, the ice making assembly **1000** may include a first sealing portion **180** and a second sealing portion **280**.

(107) The first sealing portion **180** may be formed along the edge of the first ice-making cell **173** of the first tray **170**. The first sealing portion **180** may include a recess **181** recessed inward from an outer circumferential surface of the first tray **170**. The recess **181** may be formed by being recessed inward from an outer side with respect to a radial direction of the first ice-making cell **173**.

(108) The second sealing portion **280** may be formed along an edge of the second ice-making cell **273** of the second tray **270**. The second sealing portion **280** may be provided to overlap the first sealing portion **180**. That is, the second sealing portion **280** may be provided to overlap a part of the first tray **170**.

(109) The second sealing portion **280** may include a protrusion **281** extending outward from an inner circumferential surface of the second tray **270**. The protrusion **281** may be provided to be seated on the recess **181** to maintain a seal between the first tray **170** and the second tray **270**. Particularly, the protrusion **281** of the second tray **270** may be provided to surround the recess **181** of the first tray **170**, and thus a sealing force in a portion, in which the first tray **170** and the second tray **270** are in contact with each other, may be improved.

(110) In other words, the first sealing portion **180** may be coupled to the second sealing portion **280**

in such a way that the second sealing portion **280** formed in the second ice-making cell **273** overlaps the inside of the first sealing portion **180** formed in the first ice-making cell **173**. That is, the second ice-making cell **273** may be coupled to the first ice-making cell **173** so as to overlap the inside of a partition wall of the first ice-making cell **173** to maintain an internal seal.

(111) In the refrigerator **1** according to one embodiment of the present disclosure, it is described that the first sealing portion **180** includes the recess **181** and the second sealing portion **280** includes the protrusion **281**, but it is not limited. Alternatively, the first sealing portion **180** may include the protrusion **281** and the second sealing portion **280** may include the recess **181**. That is, it is sufficient that the first sealing portion **180** and the second sealing portion **280** have overlapping portions to maintain the sealing force.

(112) FIG. **8** is a bottom perspective view of a cover frame of the refrigerator according to one embodiment of the present disclosure.

(113) Referring to FIG. **8**, the cover frame **120** may include a cutout **121**. The cutout **121** may be formed on the upper surface of the cover frame **120** to provide a space in which the water path **130** is mounted.

(114) The cover frame **120** may include a pinion receiving member **123**, a bar through hole **124**, and a gear mounting member **122**.

(115) The pinion receiving member **123** may be formed to be open on a side surface of the cover frame **120**. Accordingly, power of the driver **300** may be transmitted to the pinion **310**.

(116) The bar through hole **124** may be formed on the inner surface of the cover frame **120**. As the pair of pinions **310** are disposed on opposite sides of the cover frame **120**, respectively, the bar **320** provided to connect the pair of pinions **310** may pass through the bar through hole **124**.

(117) The gear mounting member **122** may be formed by the inner and outer surfaces of the cover frame **120**. The inner and outer surfaces of the cover frame **120** may be spaced apart from each other by a predetermined distance, and thus the rack gear **330** may be received therein. A part of the rack gear **330** may be inserted into the gear mounting member **122** and thus the rack gear **330** may be movable relative to the cover frame **120**.

(118) The cover frame **120** may include an ejector supporter **125** and an ejector coupler **126**.

(119) The ejector supporter **125** may be formed on a lower portion of a side surface of the cover frame **120**. The first ejector **150** may be inserted into the ejector supporter **125** to be movable relative to the cover frame **120**.

(120) The ejector coupler **126** may be formed on a lower portion of a side surface of the cover frame **120** and may be provided to face the outside of the cover frame **120**. The second ejector **250** may be coupled to the ejector coupler **126**. Accordingly, the second ejector **250** may be fixed to the cover frame **120**.

(121) The first case **140** may be formed on one surface of the cover frame **120**.

(122) The first case **140** may include a first tray receiving member **141**. The first tray receiving member **141** may be provided to receive the first ice-making cell **173** of the first tray **170**. Three first tray receiving members **141** may be provided in accordance with the number of first ice-making cells **173**.

(123) The first case **140** may include the first through hole **142**. The first through hole **142** may be formed by cutting the first tray receiving member **141**. The first through hole **142** may be provided to allow a pressing portion, to be described later, of the first ejector **150** to pass therethrough.

(124) The first case **140** may include a first fixer **143**. The first fixer **143** may be provided to allow the above-described first coupling protrusion **191** of the first fixing frame **190** to be inserted therinto. The first fixer **143** may be provided in plurality in accordance with the number of first coupling protrusions.

(125) The first case **140** may be integrally formed with the cover frame **120** as described in the present embodiment. Alternatively, the first case **140** may be provided as a component separated from the cover frame **120** and fixedly mounted to the cover frame **120**.

(126) FIG. 9 is an exploded perspective view illustrating a coupling between a first ejector and a second case of the refrigerator according to one embodiment of the present disclosure.

(127) Referring to FIG. 9, the first ejector 150 may include a first body 151, the first pressing portion 152 and the leg 153.

(128) The first body 151 may be formed to extend in a direction parallel to the second case 240. That is, the first body 151 may extend along a direction perpendicular to the moving direction of the first ejector 150.

(129) The first pressing portion 152 may be provided to extend from the first body 151. The first body 151 may be provided to support the first pressing portion 152. The first pressing portion 152 may pass through the first through hole 142 of the first case 140 and press the first tray 170. Particularly, the first pressing portion 152 may be provided to press each of the first ice-making cells 173 of the first tray 170. Therefore, the number of first pressing portions 152 may be in accordance with the number of first ice-making cells 173.

(130) The leg 153 may extend from opposite ends of the first body 151 and be inserted into the side part of the cover frame 120. The inserted leg 153 may be supported by the ejector supporter 125 of the cover frame 120 described above. The leg 153 may extend along a direction parallel to the moving direction of the first ejector 150. The leg 153 may be provided as a symmetrical pair.

(131) The leg 153 may include a protrusion receiving space 154. The protrusion receiving space 154 may be formed at an end of the leg 153. The protrusion 245 of the second case 240 may be received in the protrusion receiving space 154.

(132) The second case 240 may include the protrusion 245 extending toward the leg 153 from a side surface of the second case 240. The protrusion 245 may be received in the leg 153.

(133) Accordingly, when the second case 240 moves in a direction away from the first case 140, the protrusion 245 may interfere with the leg 153 and thus the first ejector 150 may also move along the moving direction of the second case 240. That is, because the first case 140 is disposed between the first ejector 150 and the second case 240, the first ejector 150 may move in a direction closer to the first case 140.

(134) In addition, when the second case 240 moves in a direction closer to the first case 140, the protrusion 245 may interfere with the leg 153 and thus the first ejector 150 may also move along the moving direction of the second case 240. That is, because the first case 140 is disposed between the first ejector 150 and the second case 240, the first ejector 150 may move in a direction away from the first case 140.

(135) A detailed description of the movement of the first ejector 150 will be described later.

(136) FIG. 10 is a view illustrating a first state of the ice making assembly of the refrigerator according to one embodiment of the present disclosure. FIG. 11 is a view illustrating a second state of the ice making assembly of the refrigerator according to one embodiment of the present disclosure. FIG. 12 is a view illustrating a third state of the ice making assembly of the refrigerator according to one embodiment of the present disclosure.

(137) As illustrated in FIG. 10, when the pinion 310 and the bar 320 are rotated clockwise by the driver 300, the rack gear 330 and the second case 240 connected to the rack gear 330 may be moved to one side of the cover frame 120. In other words, the second case 240 is moved in a direction closer to the first case 140.

(138) A state, in which the first tray 170 and the second tray 270 are engaged to maintain the airtightness as the second case 240 is moved, is referred to as a first state.

(139) That is, the first state may indicate a position of the ice making assembly 1000 in a stage in which ice is formed.

(140) The first state may include a state in which the rack gear 330 is not maximally moved with respect to the pinion 310, as illustrated in FIG. 10, and a state in which the rack gear 330 is maximally moved with respect to the pinion 310, as illustrated in FIG. 14 to be described later.

(141) In two states described above, the relative positions of the second case 240 and the second

tray **270** and the first case **140** and the first tray **170** are the same, and only the position of the rack gear **330** is changed. Accordingly, the above two states are defined as the same first state.

(142) When the airtightness is maintained between the first tray **170** and the second tray **270** in the first state, water may be supplied from the water supplier **50** to the inside of the first tray **170** and the second tray **270**. In other words, ice may be formed inside the first ice-making cell **173** of the first tray **170** and the second ice-making cell **273** of the second tray **270**. The ice may be formed in a spherical shape according to the shapes of the first ice-making cell **173** and the second ice-making cell **273**.

(143) As illustrated in FIG. **11**, when ice formation is completed inside the first ice-making cell **173** and the second ice-making cell **273**, the pinion **310** and the bar **320** may be rotated counterclockwise by the driver **300**. Accordingly, the rack gear **330** and the second case **240** connected to the rack gear **330** are moved to the other side of the cover frame **120**. In other words, the second case **240** is moved in a direction away from the first case **140**.

(144) A state, in which the first tray **170** is separated from the second tray **270** as the second case **240** is moved, is referred to as a second state.

(145) In the second state, the second ejector **250** passes through the second through hole **242** of the second case **240**. As the second ejector **250** is fixed to the cover frame **120** and the second case **240** is moved toward the second ejector **250**, the second ejector **250** may pass through the second case **240**.

(146) In the second state, the first ejector **150** is in a state of not passing through the first through hole **142** of the first case **140**.

(147) After the second state, the pinion **310** and the bar **320** may be further rotated counterclockwise by the driver **300** as illustrated in FIG. **12**. Accordingly, the rack gear **330** and the second case **240** connected thereto are further moved to the other side of the cover frame. In other words, the second case **240** is moved in a direction away from the first case **140**.

(148) A state, in which the first ejector **150** is moved in the same direction as the second case **240** as the second case **240** further is moved, is referred to as a third state. That is, the difference between the second state and the third state may be based on whether the first ejector **150** is moved.

(149) In the third state, the first ejector **150** passes through the first through hole **142** of the first case **140**. The first case **140** is integrally formed with the cover frame **120** and is fixed thereto. As the second case **240** is moved further toward the second ejector **250**, the first ejector **150** may be moved based on the movement of the second case **240**.

(150) That is, the second state and the third state may represent positions of the ice making assembly **1000** at a stage in which the formed ice is separated from the first tray **170** and the second tray.

(151) In addition, in the ice making assembly **1000** according to one embodiment of the present disclosure, the second tray **270** may be configured to be moved horizontally with respect to the first tray **170**, and thus it is possible to efficiently secure the lower space of the ice making assembly **1000**. Accordingly, the storage space of the ice bucket **60** may be increased.

(152) FIG. **13** is a side cross-sectional view illustrating a state before a rack gear is maximally moved in the ice making assembly in the first state of FIG. **10**. FIG. **14** is a side cross-sectional view illustrating a state in which the rack gear is maximally moved in the ice making assembly in the first state of FIG. **10**.

(153) An operation of the ice making assembly **1000** in the first state will be described with reference to FIGS. **13** and **14**.

(154) As illustrated in FIG. **13**, the pinion **310** is rotated clockwise to move the rack gear **330** to one side of the cover frame **120**. The rack gear **330** and the second case **240** may be connected by the elastic member **400**. The rack gear **330** may be moved in a direction in which the first case **140** and the second case **240** become closer.

(155) As the rack gear **330** and the second case **240** are moved horizontally in the state of FIG. **13**,

the first tray **170** may come into contact with the second tray **270**. The first sealing portion **180** may be formed on the first tray **170** and the second sealing portion **280** may be formed on the second tray **270** to maintain the airtightness between the first tray **170** and the second tray **270**.

Accordingly, it is possible to prevent leakage at a portion in which the first tray **170** and the second tray **270** come into contact. However, because the first tray **170** and the second tray **270** are formed to have elasticity, a gap may be formed between the first tray **170** and the second tray **270**.

(156) Therefore, as illustrated in FIG. **14**, the pinion **310** is rotated more clockwise than the state of FIG. **13** to further move the rack gear **330** to one side of the cover frame **120**. That is, the rack gear **330** may be in a state of being maximally moved with respect to the cover frame **120** in a direction in which the first case **140** and the second case **240** become closer. In this case, the pinion **310** may be located at the end of the toothed member **331** of the rack gear **330** and may be in a state in which the pinion **310** does not move the rack gear **330** to one side of the cover frame **120** any longer.

(157) The second case **240** is already in the state of being maximally moved in FIG. **13**, and thus even when the pinion **310** is further rotated as illustrated in FIG. **14**, the second case **240** may be not moved to the first case **140** side. However, as the pinion **310** is rotated, only the rack gear **330** connected to the second case **240** may be further moved to one side of the cover frame **120**, and thus the elastic member **400** connecting the rack gear **330** and the second case **240** may be stretched.

(158) Accordingly, when the elastic member **400** is stretched, the second case **240** may be pulled toward the first case **140** by an elastic restoring force. Accordingly, the first tray **170** and the second tray **270** may be in maximum contact, and thus it is possible to more reliably secure the airtightness between the first tray **170** and the second tray **270**.

(159) When water is supplied from the water supplier **50** and ice is formed in the above-mentioned state, the first tray **170** and the second tray **270** may come into close contact, and thus the shape of the ice may be clean and no crumb may be generated at the junction.

(160) FIG. **15** is a cross-sectional view illustrating a relationship between the first and second ejectors and first and second trays in the ice making assembly in the second state of FIG. **11**. FIG. **16** is a cross-sectional view illustrating the ice making assembly in the third state of FIG. **12**.

(161) An operation in which the formed ice is separated from the first tray **170** and the second tray **270** will be described with reference to FIGS. **15** and **16**.

(162) As illustrated in FIG. **15**, when the second case **240** is moved in a direction away from the first case **140** and becomes the second state, the second tray **270** fixed to the second case **240** may be also moved in a direction away from the first tray **170** fixed to the first case **140**.

(163) At this time, the ice formed in the tray may be received in the first tray **170** or in the second tray **270**.

(164) As the second case **240** and the second tray **270** are moved toward the second ejector **250** in the second state, the second pressing portion **252** of the second ejector **250** may press the second tray **270** by passing through the second through hole **242** of the second case **240**.

(165) Because the second tray **270** is formed to have elasticity, the shape of the second tray **270** may be deformed by the pressure of the second ejector **250**. When it is assumed that the ice is received in the second tray **270**, the ice may be separated from the second tray **270**.

(166) As illustrated in FIG. **16**, the second case **240** is moved in a direction away from the first case **140** more than in the second state, and becomes the third state.

(167) The third state is a state in which the first ejector **150** is moved. Particularly, the first ejector **150** may be moved toward the first case **140**. The first pressing portion **152** of the first ejector **150** may press the first tray **170** by passing through the first through hole **142** of the first case **140**.

(168) Because the first tray **170** is formed to have elasticity, the shape of the first tray **170** may be deformed by the pressure of the first ejector **150**. When it is assumed that ice is received in the first tray **170**, the ice may be separated from the first tray **170**.

(169) Accordingly, when the ice making assembly **1000** is in the second state, the second ejector

250 may press the second tray **270**, and when the ice making assembly **1000** is in the third state, the first ejector **150** may press the first tray **170**. Accordingly, regardless of whether the ice is stored in the first tray **170** or the second tray **270**, the ice may be automatically separated from the first tray **170** and the second tray **270**.

(170) FIG. **17** is a cross-sectional view illustrating a relationship between the first ejector and the second case in the ice making assembly in the second state of FIG. **15**. FIG. **18** is a cross-sectional view illustrating a relationship between the first ejector and the second case in the ice making assembly in the third state of FIG. **16**.

(171) An operation, in which the first ejector **150** is moved when the ice making assembly **1000** is changed from the second state to the third state as described in FIGS. **15** and **16**, will be described with reference to FIGS. **17** and **18**.

(172) As illustrated in FIG. **17**, when the pinion **310** is rotated counterclockwise and the rack gear **330** is moved to the other side of the cover frame **120**, the second case **240** connected to the rack gear **330** may also be moved to the other side of the cover frame **120**. The other side of the cover frame **120** is a direction away from the first case **140**.

(173) The second case **240** may be connected to the rack gear **330**, and may also be connected to the first ejector **150**. The protrusion **245** of the second case **240** may be inserted into the protrusion receiving space **154** formed in the leg **153** of the first ejector **150**. As the second case **240** is moved, the protrusion **245** may be moved inside the leg **153**. When the ice making assembly **1000** becomes the second state, the protrusion **245** of the second case **240** may come into contact with one closed end of the leg **153**. However, the second state is a state in which the first ejector **150** is not moved toward the first case **140**.

(174) As illustrated in FIG. **18**, when the pinion **310** is further rotated counterclockwise and the rack gear **330** is moved further to the other side of the cover frame **120**, the second case **240** connected to the rack gear **330** may also be moved further to the other side of the cover frame **120**.

(175) As illustrated in FIG. **17**, the protrusion **245** is in contact with the closed end of the leg **153** in the second state, and thus when the second case **240** is moved further as illustrated in FIG. **18**, the leg **153** of the first ejector **150** may interfere with the protrusion **245** and be moved in the moving direction of the second case **240**.

(176) That is, in the third state, the first ejector **150** may be moved toward the first case **140** and press the first tray **170**, which is performed in such a way that the protrusion **245** of the second case **240** interferes with the leg **153** of the first ejector **150**.

(177) Therefore, when the second case **240** is moved in a direction away from the first case **140**, the protrusion **245** and the leg **153** may interfere with each other and thus the first pressing portion **152** of the first ejector **150** may press the first tray **170**.

(178) Accordingly, when the formed ice is received in the first tray **170**, the formed ice may be automatically separated from the first tray **170**.

(179) FIG. **19** is a top view illustrating a state in which a water path of the refrigerator according to one embodiment of the present disclosure is coupled to the cover frame. FIG. **20** is a top view illustrating only the cover frame of the refrigerator according to one embodiment of the present disclosure.

(180) Referring to FIGS. **19** and **20**, the water path **130** may be mounted on the upper surface of the cover frame **120**. The water path **130** may be provided to allow water, which is supplied from the water supplier **50**, to flow into the first tray **170** and the second tray **270** received inside the cover frame **120**.

(181) The water path **130** may include a water collector **131** and a plurality of flow paths **132**, **133**, and **134**.

(182) The water collector **131** may be provided to receive water from the water supplier **50** in the refrigerator. The plurality of flow paths may include a first flow path **132**, a second flow path **133**, and a third flow path **134**. The first flow path **132**, the second flow path **133**, and the third flow

path **134** may be branched from the water collector **131**. The water collector **131** may be formed to form an inclined surface to allow water, which is supplied from the water supplier **50**, to easily flow into the ice-making cell.

(183) The first flow path **132**, the second flow path **133**, and the third flow path **134** may be provided to evenly supply water to each of the plurality of ice-making cells formed by the first tray **170** and the second tray **270**. The first flow path **132**, the second flow path **133**, and the third flow path **134** may also be provided as inclined surfaces to allow water to flow easily.

(184) The water path **130** may include a coupling member mounting member **135**. The coupling member mounting member **135** may be provided to be coupled to a water path coupler **128** of the cover frame **120** to be described later. Accordingly, the water path **130** and the cover frame **120** may be coupled to each other.

(185) The cover frame **120** may include a housing coupler **127** and the water path coupler **128**. The water path **130** may be mounted on the cover frame **120** through the water path coupler **128**. The cover frame **120** may be mounted to the ice making housing **110** through the housing coupler **127**. The cover frame **120** and the ice making housing **110**, and the cover frame **120** and the water pass **130** may be coupled as a separate fastening member is fastened to the housing coupler **127** and the water pass coupler **128**.

(186) The refrigerator **1** according to one embodiment of the present disclosure may include the plurality of flow paths to evenly supply water to each of the plurality of ice-making cells, thereby dividing water and supplying the water step by step to the plurality of ice-making cells.

(187) Particularly, by controlling the water supplier **50** through a controller, the refrigerator **1** may supply water by dividing the water in stages according to the water level inside the plurality of ice-making cells.

(188) Therefore, when bubbles are generated upon supplying water into the plurality of ice-making cells, it is possible to secure sufficient time for the bubbles to disappear. Accordingly, it may be easy to ensure the transparency of the ice that is finally formed.

(189) FIG. **21** is a view illustrating a state, in which the first ejector and the cover frame are omitted in the ice making assembly of FIG. **3**, when viewed from the first tray side.

(190) Referring to FIG. **21**, the first heating wire **160** may be mounted outside the first tray **170**. Particularly, the first heating wire **160** may be mounted between the first tray **170** and the cover frame **120**. As described above, the ice making assembly **1000** may include the first heating wire **160** on the first tray **170** side and the second heating wire **260** on the second tray **270** side.

(191) The first heating wire **160** may apply heat to the first tray **170** to allow the ice formed on the first tray **170** to be easily separated from the first tray **170**. Although not shown, the second heating wire **260** may play the same role.

(192) As the first heating wire **160** and the second heating wire **260** are provided, the first ejector **150** may be omitted from the ice making assembly **1000**. Further, the second ejector **250** may also be omitted from the ice making assembly **1000**.

(193) In addition, in the ice making assembly **1000** of the refrigerator **1** according to one embodiment of the present disclosure, the first ice making cell **173** of the first tray **170** and the second ice making cell **273** of the second tray **270** may be formed in approximately the same size and shape. However, the sizes and shapes of the first ice-making cell **173** and the second ice-making cell **273** are not limited thereto.

(194) For example, the size of the first ice-making cell **173** of the first tray **170** may be greater than the size of the second ice-making cell **273** of the second tray **270**.

(195) Conversely, the size of the first ice-making cell **173** of the first tray **170** may be less than the size of the second ice-making cell **273** of the second tray **270**.

(196) That is, a maximum recess depth of the first ice-making cell **173** of the first tray **170** according to the moving direction of the second ice-making cell **273** may be less than a maximum recess depth of the second ice-making cell **273** of the second tray **270**. The recess depth may be

defined as a horizontal distance from an open side to a closed side of each ice-making cell **173** or **273** of each tray **170** or **270**.

(197) In this case, when the second tray **270** is moved relative to the first tray **170** to separate the ice, the ice may be received in the second ice-making cell **273** of the second tray **270**.

(198) In the first ice-making cell **173** and the second ice-making cell **273** provided to make spherical ice, a width of the second ice-making cell **273** along the moving direction may be greater than that of the first ice-making cell **173**. Therefore, a portion higher than a lower curvature point of ice may be formed in the second ice-making cell **273**. At the same time, a portion lower than an upper curvature point of ice may be formed in the second ice-making cell **273**.

(199) Therefore, when the second tray **270** is moved relative to the first tray **170**, the ice may interfere with the edge of the second ice-making cell **273**, and accordingly, the ice may be moved along the second tray **270** while the ice is received in the second ice-making cell **273**.

(200) In addition, the heating wire may be formed only on the side of the first ice-making cell **173** to allow the ice to be more easily separated from the first ice-making cell **173**. That is, because the ice making assembly **1000** includes the first heating wire **160** and excludes the second heating wire **260**, only the first heating wire **160** may be mounted on the side of the first tray **170**.

(201) That is, by forming the widths of the first ice-making cell **173** and the second ice-making cell **273** with respect to the moving direction of the second ice-making cell **173** to be different from each other, the ice making assembly **1000** may be pre-designed to allow ice to be received in one single ice-making cell during the ice removal.

(202) When the ice is formed and the first tray **170** and the second tray **270** are separated in the state in which the first ice-making cell **173** and the second ice-making cell **273** are formed in different sizes, there is a high probability that ice is received in the larger ice-making cell.

Accordingly, in this case, it is possible to simplify the structure by providing the ejector to only the relatively larger ice-making cell.

(203) For example, when the size of the first ice-making cell **173** is greater than the size of the second ice-making cell **273**, the ice-making assembly **1000** may include the first ejector **150** on the side of the first ice-making cell **173**, and exclude the second ejector **250**.

(204) Conversely, when the size of the first ice-making cell **173** is less than the size of the second ice-making cell **273**, the ice-making assembly **1000** may include only the second ejector **250** on the side of the second ice-making cell **273**, and exclude the first ejector **150**.

(205) In addition, as a boss shape or an undercut shape is applied only to the inside of one of the first tray **170** and the second tray **270**, it is possible to more easily separate the ice from the first tray **170** and the second tray **270**. In this case, because the ice is highly likely to be received on the side of the tray to which no shape is applied, it is possible to implement the ice making assembly **1000** including only the ejector adjacent to the tray to which no shape is applied.

(206) In addition, the first ice-making cell **173** of the first tray **170** provided to be fixed to the cover frame **120** may be formed of aluminum, and the second ice-making cell **273** of the second tray **270** provided to be moved relative to the first ice-making cell **173** may be formed of a silicon material. That is, the first ice-making cell **173** and the second ice-making cell **273** have different thermal conductivities, and thus when the second ice-making cell **273** is moved, the ice may be separated from the first ice-making cell **173** and then moved in a state of being received in the second ice-making cell **273**.

(207) Accordingly, the ice making assembly **1000** may also be designed to include only the first heating wire **160** and thus ice may be easily separated from the first ice making cell **173** of the first tray **170**.

(208) In this case, because the ice is more likely to be moved in a state of being received in the second ice-making cell **273** having lower thermal conductivity than in the first ice-making cell **173** having high thermal conductivity, the ice-making assembly **1000** may be provided in a structure in which only the second ejector **250** is included and the first ejector **150** is excluded.

(209) FIG. 22 is a view illustrating an ice making assembly of a refrigerator according to another embodiment of the present disclosure. FIG. 23 is a top view of the ice making assembly of FIG. 22.

(210) As illustrated in FIGS. 22 and 23, an ice making assembly **2000** of a refrigerator according to another embodiment of the present disclosure may include a cover frame **120a**.

(211) The cover frame **120a** may be provided to be coupled to the ice-making housing inside the ice-making housing (refer to FIG. 2). The cover frame **120a** may be provided in a box shape in which one side surface and a lower surface are open. A driver may be mounted on one side surface of the cover frame **120a**.

(212) In the description of the refrigerator according to another embodiment of the present disclosure, components not separately mentioned may be described using the same names and reference numerals as the components of the refrigerator according to one embodiment of the present disclosure. Hereinafter differences from the refrigerator according to one embodiment of the present disclosure will be mainly described.

(213) The ice making assembly **2000** according to another embodiment of the present disclosure may include a water path **130a**. The water path **130a** may be mounted on one surface of the cover frame **120a**. Particularly, the water path **130a** may be mounted on an upper surface of the cover frame **120a**. The water path **130a** may be provided to allow water, which is supplied from the water supplier, to flow into the cover frame **120a**. In other words, the water path **130a** may be provided to allow water, which is supplied from the water supplier, to flow into a first tray **170a** and a second tray **270a**.

(214) Unlike the water path **130** of the ice making assembly **1000** according to one embodiment of the present disclosure, the water path **130a** of the ice making assembly **2000** according to another embodiment of the present disclosure may include a single flow path.

(215) The water path **130a** may include a water collector **131a**, and the water collector **131a** may include a single flow path. The water collector **131a** may be configured to receive water from the water supplier in the refrigerator. The water collector **131a** may be formed to form an inclined surface to allow water, which is supplied from the water supplier, to easily flow into the ice-making cell.

(216) The single flow path formed in the water collector **131a** may be provided to supply water to one ice-making cell among a plurality of ice-making cells formed by the first tray **170a** and the second tray **270a**.

(217) An operation, in which water is supplied to a single ice-making cell so as to fill the plurality of ice-making cells with the water, will be described later.

(218) FIG. 24 is a view illustrating a first tray and a second tray of the refrigerator according to another embodiment of the present disclosure. FIG. 25 is a cross-sectional view illustrating a state in which the first tray and the second tray are coupled in the ice making assembly of the refrigerator according to another embodiment of the present disclosure. FIG. 26 is a cross-sectional view illustrating a method of supplying water in the ice making assembly of the refrigerator according to another embodiment of the present disclosure.

(219) As illustrated in FIG. 24, the ice making assembly **2000** of the refrigerator according to another embodiment of the present disclosure may include the first tray **170a** and the second tray **270a**.

(220) The first tray **170a** may include a first guide **172a**, a first ice-making cell **173a**, and a first connection flow path **174a**.

(221) The first guide **172a** may be formed on an upper side of the first ice-making cell **173a**. When water overflows from the first ice-making cell **173a**, the first guide **172a** may allow the water to flow to the adjacent first ice-making cell **173a**.

(222) The first tray **170a** may include a plurality of first ice-making cells **173a**. The plurality of first ice-making cells **173a** may be provided to form a portion of ice.

(223) Unlike the first tray **170** of the refrigerator according to one embodiment of the present

disclosure, the first tray **170a** of the refrigerator according to another embodiment of the present disclosure may include the first connection flow path **174a**.

(224) The first connection flow path **174a** may be provided to connect adjacent first ice-making cells **173a** to each other. Particularly, the first connection flow path **174a** may be formed by being recessed inward from one surface of the first tray **170a**. The first connection flow path **174a** may be formed in the center of the first ice-making cell **173a**. However, the position of the first connection flow path **174a** is not limited thereto, and it is sufficient that the first connection flow path is provided to connect adjacent first ice-making cells **173a** to each other.

(225) The second tray **270a** may include a second guide **272a**, a second ice-making cell **273a**, and a second connection flow path **274a**.

(226) The second guide **272a** may be formed on an upper side of the second ice-making cell **273a**. When water overflows from the second ice-making cell **273a**, the second guide **272a** may allow water to flow to the adjacent second ice-making cell **273a**.

(227) The second tray **270a** may include a plurality of second ice-making cells **273a**. The plurality of second ice-making cells **273a** may be provided to form a portion of ice. The first ice-making cell **173a** and the second ice-making cell **273a** may be coupled to each other so as to form ice in a perfect shape.

(228) Unlike the second tray **270** of the refrigerator according to one embodiment of the present disclosure, the second tray **270a** of the refrigerator according to another embodiment of the present disclosure may include the second connection flow path **274a**.

(229) The second connection flow path **274a** may be provided to connect adjacent second ice making cells **273a**.

(230) Particularly, the second connection flow path **274a** may be formed by being recessed inward from one surface of the second tray **270a**. The second connection flow path **274a** may be formed at the center of the second ice-making cell **273a**. However, the position of the second connection flow path **274a** is not limited thereto, and it is sufficient that the second connection flow path is provided to connect adjacent second ice-making cells **273a** to each other.

(231) The second connection flow path **274a** is formed at a position corresponding to the first connection flow path **174a** described above, and thus, when the first tray **170a** and the second tray **270a** are coupled to each other, the first connection flow path **174a** and the second connection flow path **274a** may be provided to form one connection flow path.

(232) The ice making assembly **2000** of the refrigerator according to another embodiment of the present disclosure may include a first sealing portion **180a** formed on the first tray **170a**, and a second sealing portion **280a** formed on the second tray **270a**. Unlike the refrigerator according to one embodiment of the present disclosure, the first sealing portion **180a** of the refrigerator according to another embodiment of the present disclosure may include a protrusion, and the second sealing portion **280a** may include a recess.

(233) However, the positions of the recess and protrusion are not limited thereto. For example, the first sealing portion **180a** may include the recess and the second sealing portion **280a** may include the protrusion. That is, it is sufficient that the first sealing portion **180a** and the second sealing portion **280a** include overlapping portions to maintain the sealing force.

(234) Referring to FIGS. **25** and **26**, water supplied from the water supplier **50** may flow into the first ice-making cell **173a** and the second ice-making cell **273a**, which are coupled to each other, through the water collector **131a**. In this case, the first ice-making cell **173a** supplied with water may be the central first ice-making cell **173a** among the plurality of first ice-making cells **173a**, and the second ice-making cell **273a** supplied with water may be the central second ice-making cell **273a** among the plurality of second ice-making cells **273a**. However, the position of the ice-making cell to which water is supplied is not limited thereto, and water may be supplied to the ice-making cell located at both ends according to the mounting position of the water path **130a** and the design change of the cover frame **120a**.

(235) Because the first sealing portion **180a** and the second sealing portion **280a** are engaged to maintain a seal between the first tray **170a** and the second tray **270a**, the water contained in the first ice-making cell **173a** and the second ice-making cell **273a** may not leak.

(236) The flow of water in the following will be described using the first ice-making cell **173a** as an example, but the second ice-making cell **273a** may also have the same flow of water.

(237) Water is supplied through the water collector **131a** of the water path **130a**, and the supplied water is received in the central first ice-making cell **173a** among the plurality of first ice-making cells **173a**. When the first tray **170a** is filled with water up to the height at which the first connection flow path **174a** is formed, the water stored in the central first ice-making cell **173a** flows to the first ice-making cell **173a** on both sides. That is, water may flow to the first ice-making cell **173a** on one side through the first connection flow path **174a** formed on one side of the central first ice-making cell **173a**, and water may flow to the first ice-making cell **173a** on the other side through the second connection flow path **274a** formed on one the other side of the central first ice-making cell **173a**.

(238) Accordingly, even when a single flow path of the water path **130a** is formed, the water supplied through the water supplier **50** may be supplied to all of the plurality of ice-making cells to form ice.

(239) FIG. **27** is a view illustrating an ice making assembly of a refrigerator according to still another embodiment of the present disclosure. FIG. **28** is a top view of the ice making assembly of FIG. **27**.

(240) As illustrated in FIGS. **27** and **28**, an ice making assembly **3000** of a refrigerator according to still another embodiment of the present disclosure may include a cover frame **120b**.

(241) The cover frame **120b** may be coupled to the ice-making housing inside the ice-making housing (refer to FIG. **2**). The cover frame **120b** may be provided in a box shape in which one side surface and a lower surface are open. A driver may be mounted on one side surface of the cover frame **120b**.

(242) In the description of the refrigerator according to still another embodiment of the present disclosure, components not separately mentioned may be described using the same names and reference numerals as the components of the refrigerator according to one embodiment of the present disclosure. Hereinafter differences from the refrigerator according to one embodiment of the present disclosure will be mainly described.

(243) The ice making assembly **3000** according to still another embodiment of the present disclosure may include a water path **130b**. The water path **130b** may be mounted on one surface of the cover frame **120b**. Particularly, the water path **130b** may be mounted on an upper surface of the cover frame **120b**. The water path **130b** may be provided to allow water, which is supplied from the water supplier **50**, to flow into the cover frame **120b**. In other words, the water path **130b** may be provided to allow water, which is supplied from the water supplier **50**, to flow into a first tray **170b** and a second tray **270b**.

(244) Unlike the water path **130** of the ice making assembly **1000** according to one embodiment of the present disclosure, the water path **130b** of the ice making assembly **3000** according to still another embodiment of the present disclosure may include a single flow path.

(245) The water path **130b** may include a water collector **131b**, and the water collector **131b** may include a single flow path. The water collector **131b** may be configured to receive water from the water supplier **50** in the refrigerator. The water collector **131b** may be formed to form an inclined surface to allow water, which is supplied from the water supplier **50**, to easily flow into the ice-making cell.

(246) The single flow path formed in the water collector **131b** may be provided to supply water to one ice-making cell among a plurality of ice-making cells formed by the first tray **170b** and the second tray **270b**. This is the same as the water path **130**, **130a** of the refrigerator according to another embodiment of the present disclosure.

(247) However, an operation, in which water is supplied to a single ice-making cell so as to fill the plurality of ice-making cells with the water, may be different from the water path **130a** of the refrigerator according to another embodiment of the present disclosure, and a description thereof will be described later.

(248) FIG. **29** is a view illustrating a first tray, a first fixing frame, a second fixing frame, a second tray, and a second case of the refrigerator according to still another embodiment of the present disclosure. FIG. **30** is a front view of the first tray of the refrigerator according to still another embodiment of the present disclosure. FIG. **31** is a cross-sectional view illustrating a method of supplying water in the ice making assembly of the refrigerator according to still another embodiment of the present disclosure.

(249) As illustrated in FIG. **29**, the ice making assembly **3000** of the refrigerator according to still another embodiment of the present disclosure may include the first tray **170b**, a first fixing frame **190b**, the second tray **270b**, a second fixing frame **290b**, and a second case **240b**.

(250) The first tray **170b** may include a first guide **172b** and a first ice-making cell **173b**.

(251) The first guide **172b** may be formed on an upper side of the first ice-making cell **173b**. When water overflows from the first ice-making cell **173b**, the first guide **172b** may allow the water to flow to the adjacent first ice-making cell **173b**.

(252) The first tray **170b** may include a plurality of first ice-making cells **173b**. The plurality of first ice-making cells **173b** may be provided to form a portion of ice.

(253) Unlike the first tray **170a** of the refrigerator according to another embodiment of the present disclosure, the first tray **170b** of the refrigerator according to still another embodiment of the present disclosure may not include the first connection flow path **174a**.

(254) Referring to FIGS. **29** and **30**, the first trays **170b** of the refrigerator according to still another embodiment of the present disclosure may be formed at different heights. In other words, each of the plurality of first ice-making cells **173b** may be provided to have a height difference.

(255) Particularly, a line C connecting centers of each of the first ice-making cells **173b** of the first tray **170b** of the refrigerator according to still another embodiment of the present disclosure may have a predetermined angle with respect to a horizontal line L.

(256) As each of the plurality of first ice-making cells **173b** has a height difference, openings of the first fixing frame **190b** provided to support and fix the plurality of first ice-making cells **173b** may also have a height difference.

(257) The second tray **270b** may include a plurality of second ice making cells **273**.

(258) The plurality of second ice-making cells **273** may be provided to form a portion of ice. The first ice-making cell **173b** and the second ice-making cell **273** may be coupled to each other to form ice in a perfect shape.

(259) Unlike the second tray **270a** of the refrigerator according to another embodiment of the present disclosure, the second tray **270b** of the refrigerator according to still another embodiment of the present disclosure may not include the second connection flow path **274a**.

(260) Because the second tray **270b** of the refrigerator according to still another embodiment of the present disclosure corresponds to the first tray **170b**, the second tray **270b** may be formed at different heights in the same manner as the above-described first tray **170b**. In other words, each of the plurality of second ice making cells **273** may be provided to have a height difference.

(261) As each of the plurality of second ice-making cells **273** has a height difference, openings of the second fixing frame **290b** provided to support and fix the plurality of second ice-making cells **273** may also have a height difference. In addition, a receiving member of the second tray **270b** of the second case **240b** provided to receive the second tray **270b** may also have a height difference.

(262) Referring to FIG. **31**, water supplied from the water supplier **50** may flow into the first ice-making cell **173b** and the second ice-making cell **273** through the water collector **131b** of the water path **130b**.

(263) At this time, the first ice-making cell **173b**, to which water is supplied, may be the first ice-

making cell **173b**, which is farthest from the driver, among the plurality of first ice-making cells **173b**, and the second ice-making cell **273**, to which water is supplied, may be the second ice-making cell **273**, which is farthest from the driver, among the plurality of second ice-making cells **273**. However, the location of the ice-making cell, to which water is supplied, is not limited thereto, and water may be supplied to the ice-making cell at another location according to the mounting position of the water path **130b** and design change of the cover frame **120b**.

(264) The flow of water in the following will be described using the first ice-making cell **173b** as an example, but the second ice-making cell **273** may also have the same flow of water.

(265) Water is supplied through the water collector **131b** of the water path **130b**, and the supplied water is received in one of the plurality of first ice-making cells **173b**. When the first ice-making cell **173b** of the first tray **170b** is almost filled with water, the water stored in the first ice-making cell **173b** flows to the adjacent first ice-making cell **173b**. The water may flow through the first guide **172b** of the first tray **170b**. Thereafter, when the first ice-making cell **173b**, which is supplied with water from the water supplier **50**, and the first ice-making cell **173b** adjacent to the first ice-making cell **173b** are almost filled with water, water flows into the adjacent first ice-making cell **173b**. An ice-making cell, to which water is finally supplied, may be the first ice-making cell **173b** closest to the driver. That is, the plurality of ice-making cells is sequentially filled with water according to the arrangement position.

(266) Accordingly, even when the flow path of the water path **130b** is formed as a single unit, the water supplied through the water supplier may be supplied to all of the plurality of ice-making cells to form ice.

(267) Embodiments of the disclosure may provide a refrigerator including a storage compartment, and an ice making assembly mounted to one side of the storage compartment. The ice making assembly includes a cover frame, a first tray fixed to the cover frame to form a first portion of ice, a second tray engaged with the first tray so as to form a second portion of the ice, the second tray configured to be moved horizontally with respect to the first tray, and a water path mounted on the cover frame and provided to equally supply water to each of a plurality of ice-making cells formed by the first tray and the second tray. The refrigerator may further include a first sealing portion recessed along an edge of the ice-making cell of the first tray and a second sealing portion formed along an edge of the ice-making cell of the second tray, the second sealing portion provided to protrude to overlap the first tray so as to prevent leakage. The refrigerator may control a water supplier to divide and supply water to the plurality of ice-making cells according to a water level of the plurality of ice-making cells.

(268) Embodiments of the disclosure may provide a refrigerator including a storage compartment, an ice-making housing mounted on the storage compartment, a cover frame coupled to an inside of the ice-making housing, a first case fixed to the cover frame to receive a first tray provided to form a first portion of ice, a second case provided to receive a second tray provided to form a second portion of the ice, the second case configured to be moved with respect to the cover frame, a driver coupled to the cover frame to generate power, a pinion configured to be rotated according to the drive of the driver, and a rack gear configured to be moved by being engaged with the pinion, and coupled to the second case to allow the second tray and the second case to be linearly moved relative to the cover frame. The rack gear and the second case may be connected by an elastic member.

(269) While the present disclosure has been particularly described with reference to exemplary embodiments, it should be understood by those of skilled in the art that various changes in form and details may be made without departing from the spirit and scope of the present disclosure.

Claims

1. A refrigerator, comprising: a storage compartment; a water supplier to supply water received from an external water supply source; an ice-making housing in the storage compartment; a first tray disposed in the ice-making housing and including: a plurality of first ice-making cells, and a first sealing portion formed along an edge of each first ice-making cell of the plurality of first ice-making cells; and a second tray including: a plurality of second ice-making cells, and a second sealing portion formed along an edge of each second ice-making cell of the plurality of second ice-making cells, wherein the first tray and the second tray are configured so that: the second tray is movable horizontally with respect to the first tray to engage with the first tray and couple the plurality of first ice-making cells to the plurality of second ice-making cells, and while the second tray is engaged with the first tray, the second sealing portion of each second ice-making cell of the plurality of second ice-making cells overlaps a respective first sealing portion of each first ice-making cell of the plurality of first ice-making cells to prevent leakage from the plurality of first ice-making cells and the plurality of second ice-making cells, each first ice-making cell of the plurality of first ice-making cells forms a first portion of ice with water supplied from the water supplier, and each second ice-making cell of the plurality of second ice-making cells forms a second portion of the ice with the water supplied from the water supplier.
2. The refrigerator of claim 1, wherein the first sealing portion includes: a recess recessed inward from an outer circumferential surface of the first tray, and the second sealing portion includes: a protrusion extending outward from an inner circumferential surface of the second tray and configured to be mountable on the recess to maintain a seal between the first tray and the second tray.
3. The refrigerator of claim 1, further comprising: a cover frame coupled to the ice-making housing; a first case formed on one surface of the cover frame to receive the first tray; and a second case configured to be moved inside the cover frame, and to receive the second tray.
4. The refrigerator of claim 3, further comprising: a rack gear connected to the second case and configured to be moved relative to the cover frame, wherein the second case is moved horizontally with respect to the cover frame in conjunction with a movement of the rack gear.
5. The refrigerator of claim 4, further comprising: a driver configured to generate power; and a pinion configured to be rotated according to a drive of the driver; wherein the pinion and the rack gear are engaged to convert a rotational motion of the driver into a linear motion.
6. The refrigerator of claim 4, further comprising: an elastic member to connect the rack gear to the second case, wherein in response to the rack gear being maximally moved in a direction in which the second case moves toward the first case, the elastic member is tensioned and airtightness between the second case and the first case is maintained by an elastic restoring force.
7. The refrigerator of claim 3, further comprising: a first ejector including a pressing portion, wherein the first case includes a plurality of through holes corresponding to positions of the plurality of first ice-making cells, and the pressing portion is configured to pass through the plurality of through holes so as to press the first tray.
8. The refrigerator of claim 7, wherein the first ejector includes: a body configured to support the pressing portion, and a leg extending from each of opposite ends of the body and inserted into respective side portions of the cover frame, the second case includes: a protrusion extending from each of opposite ends of the second case to be respectively received in the legs, and in response to the second case being moved in a direction away from the first case, the protrusions interfere with the legs, and the first ejector is moved in a direction closer to the first case such that the pressing portion presses the first tray.
9. The refrigerator of claim 7, further comprising: a second ejector fixed to one side of the cover frame and including a pressing portion extending toward the second case, wherein in response to the second case being moved in a direction away from the first case, the pressing portion of the second ejector passes through the second case so as to press the second tray.

10. The refrigerator of claim 1, wherein each first ice-making cell of the plurality of first ice-making cells of the first tray and each second ice-making cell of the plurality of second ice-making cells of the second tray are configured in a semi-spherical shape.
 11. The refrigerator of claim 1, further comprising: a cover frame coupled to an inside of the ice-making housing; and a water path configured on an upper surface of the cover frame to guide the water supplied from the water supplier to flow into the first tray and the second tray.
 12. The refrigerator of claim 11, wherein the water path includes a plurality of flow paths to equally supply water to each first ice-making cell of the plurality of first ice-making cells of the first tray and each second ice-making cell of the plurality of second ice-making cells of the second tray.
 13. The refrigerator of claim 12, wherein the refrigerator further comprises a controller configured to control the water supplier to supply the water.
 14. The refrigerator of claim 11, wherein the second sealing portion of each second ice-making cell of the plurality of second ice-making cells overlaps a respective first sealing portion of each first ice-making cell of the plurality of first ice-making cells to respectively form a plurality of sealed ice-making cells, the water path includes a single flow path to guide the water to only one sealed ice-making cell among the plurality of sealed ice-making cells, and each sealed ice-making cell of the plurality of sealed ice-making cells is configured at a different height so that the water overflows the one sealed ice-making cell among the plurality of sealed ice-making cells to sequentially fill remaining sealed ice-making cells among the plurality of sealed ice-making cells with the water.
 15. The refrigerator of claim 11, wherein the second sealing portion of each second ice-making cell of the plurality of second ice-making cells overlaps a respective first sealing portion of each first ice-making cell of the plurality of first ice-making cells to respectively form a plurality of sealed ice-making cells, the water path includes a single flow path to guide the water to only one sealed ice-making cell among the plurality of sealed ice-making cells, and the first tray and the second tray include a connection flow path provided to allow the water, which is supplied to the one sealed ice-making cell, to flow to an adjacent sealed ice-making cell among the plurality of sealed ice-making cells.
-