

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12413313

Kind Code

B2

Date of Patent

September 09, 2025

Inventor(s)

Haylock; Robert David et al.

Top-of-rack switch of a rack assembly tuned to receive a band of wavelengths from a replicated spectrum of wavelengths provided by a power splitter

Abstract

An optical communication system including a hub optical transceiver, a power splitter, and a plurality of spoke transceivers. The hub optical transceiver is configured for receiving a spectrum of wavelengths. The power splitter is coupled to the hub optical transceiver, and operates as a passive device that is configured to replicate the spectrum of wavelengths and output a plurality of replicated spectrum of wavelengths, and each replicated spectrum of wavelengths has a corresponding power that is a fraction of a total power received from the hub optical transceiver. The plurality of spoke transceivers is coupled to the power splitter and each of the plurality of spoke transceivers is configured to receive a corresponding one of the plurality of replicated spectrum of wavelengths, wherein each spoke transceiver is tunable to select a band of wavelengths that set a bandwidth for the each spoke transceiver.

Inventors: Haylock; Robert David (South Turrumurra, AU), Caruana; Aaron Jason (North Adelaide, AU)

Applicant: Sony Interactive Entertainment Inc. (Tokyo, JP)

Family ID: 81327308

Assignee: Sony Interactive Entertainment Inc. (Tokyo, JP)

Appl. No.: 18/453161

Filed: August 21, 2023

Prior Publication Data

Document Identifier

US 20230396336 A1

Publication Date

Dec. 07, 2023

Related U.S. Application Data

Publication Classification

Int. Cl.: H04B10/40 (20130101); H04B10/564 (20130101); H04B10/572 (20130101);
H04L41/14 (20220101)

U.S. Cl.:

CPC H04B10/40 (20130101); H04B10/564 (20130101); H04B10/572 (20130101);
H04L41/145 (20130101);

Field of Classification Search

CPC: H04B (10/40); H04B (10/564); H04B (10/572); H04B (10/61); H04B (10/506); H04L
(41/145); H04J (14/02); H04J (14/0216); H04J (14/0286); H04Q (2011/0016); H04Q
(2011/0018); H04Q (11/0005); H04Q (2011/0052); H04Q (2011/0054); H04Q
(2011/0015); G02B (6/29395)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2012/0099863	12/2011	Xu	398/48	H04Q 11/0005
2016/0134375	12/2015	Kakande	398/135	H04J 14/02
2018/0348456	12/2017	Ho	N/A	G02B 6/4215
2019/0379477	12/2018	Tien	N/A	H04Q 11/0005
2020/0371295	12/2019	Jones	N/A	H04B 10/03
2021/0075536	12/2020	Hand	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2015535413	12/2014	JP	N/A
2020180475	12/2019	WO	N/A

OTHER PUBLICATIONS

Office Action issued in JP Application No. 2024-117676 issued in Dec. 17, 2024, 6 pages. cited by applicant

Primary Examiner: Woldekidan; Hibret A

Attorney, Agent or Firm: Kilpatrick Townsend & Stockton LLP

Background/Summary

CLAIM OF PRIORITY (1) The present application is a continuation of and claims priority to and the benefit of commonly owned patent application U.S. Ser. No. 17/752,784, filed on May 24, 2022, entitled “Controller For Tuning A Spoke Transceiver To Receive A Band Of Wavelengths From A Replicated Spectrum Of Wavelengths Provided By A Power Splitter”; which is a continuation of and claims priority to and the benefit of commonly owned patent application U.S. Ser. No. 17/243,337, filed on Apr. 28, 2021, entitled “Optimized Switching Fabric With Multi-Point Optics In A Data Center”; which claims priority to and the benefit of commonly owned, provisional patent application, U.S. Ser. No. 63/173,344, filed on Apr. 9, 2021, with entitled “Optimized Switching Fabric With Multi-Point Optics In A Data Center,” all of which are herein incorporated by reference in their entireties for all purposes.

TECHNICAL FIELD

(1) The present disclosure is related to internet protocol (IP) switching fabrics and/or topologies, and more specifically to an optical data center fabric (ODCF) which delivers the advantages of a full IP Clos fabric, and provides an express path between the edge of the data center and leaf nodes using cutting edge flexible optical technologies.

BACKGROUND OF THE DISCLOSURE

(2) In recent years there has been a continual push for online services that allow for online or cloud gaming in a streaming format between a cloud gaming server and a client connected through a network. The streaming format has increasingly become more popular because of the availability of game titles on demand, the ability to execute more complex games, the ability to network between players for multi-player gaming, sharing of assets between players, sharing of instant experiences between players and/or spectators, allowing friends to watch a friend play a video game, having a friend join the on-going game play of a friend, and the like.

(3) Unfortunately, the demand is also pushing up against the limits of the capabilities of network connections. In particular, internet protocol (IP) Fabrics based on Clos switching topologies or fabrics, providing multistage circuit switching networks, have dominated the cloud industry in recent years due to their ability to scale through cookie cutter elements and their highly flexible routing designs. However, as 5 stage or even greater CLOS switching topologies become necessary to deliver required host connectivity, the number of devices dedicated to “spine” functions, and having no user/host connectivity, rapidly explodes. These spine dedicated devices add cost in both switching hardware and transceivers, as well as additional operational complexity and active failure points that need to be managed.

(4) It would be beneficial to reduce capital, operational costs, and complexity of a large switching topology or fabric, and also reduce latency between hosts and end-user services. It is in this context that embodiments of the disclosure arise.

SUMMARY

(5) Embodiments of the present disclosure relate to an optical data center IP switching fabric (ODCF) and/or topology which delivers the advantages of a full internet protocol (IP) multi-stage switching fabric, and further provides reduced latency without the complexity and cost, and further provides for an express path between the edge of the data center and leaf nodes using cutting edge flexible optical technologies.

(6) Embodiments of the present disclosure disclose an optical communication system. The optical communication system including a hub optical transceiver configured for receiving a spectrum of wavelengths. The optical communication system including a power splitter coupled to the hub optical transceiver. The power splitter operates as a passive device that is configured to replicate the spectrum of wavelengths and output a plurality of replicated spectrum of wavelengths. Each replicated spectrum of wavelengths of the plurality of replicated spectrum of wavelengths has a corresponding power that is a fraction of a total power received from the hub optical transceiver. The optical communication system including a plurality of spoke transceivers coupled to the power

splitter. Each of the plurality of spoke transceivers is configured to receive a corresponding one of the plurality of replicated spectrum of wavelengths. Each spoke transceiver is tunable to select a band of wavelengths that set a bandwidth for the each spoke transceiver. For example, a spoke transceiver may be tuned to one or more wavelengths, wherein multiple tuned wavelengths may be contiguous or non-contiguous.

(7) Embodiments of the present disclosure disclose an optical communication system. The optical communication system including a hub optical transceiver configured for receiving a spectrum of wavelengths. The optical communication system including a power splitting layer coupled to the hub optical transceiver. The power splitting layer being configured to output a plurality of replicated spectrum of wavelengths. Each replicated spectrum of wavelengths of the plurality of replicated spectrum of wavelengths has a corresponding power that is fraction of a total power received from the optical transceiver. The power splitting layer includes a plurality of power splitters configured in one or more cascading layers, wherein each power splitter operates as a passive device. The optical communication system including a plurality of spoke transceivers coupled to the power splitting layer. Each of the plurality of spoke transceivers is configured to receive a corresponding one of the plurality of replicated spectrum of wavelengths. Each spoke transceiver is tunable to select a band of wavelengths that set a bandwidth for the each spoke transceiver. For example, a spoke transceiver may be tuned to one or more wavelengths, wherein multiple tuned wavelengths may be contiguous or non-contiguous.

(8) Embodiments of the present disclosure disclose an optical communication system. The optical communication system including a hub optical transceiver configured for receiving a spectrum of wavelengths. The optical communication system including a first power splitter coupled to the hub optical transceiver. The first power splitter operates as a passive device that is configured to replicate the spectrum of wavelengths and output a first plurality of replicated spectrum of wavelengths. Each replicated spectrum of wavelengths of the first plurality of replicated spectrum of wavelengths has a corresponding power that is a fraction of a total power received from the hub optical transceiver. The optical communication system including a spoke transceiver that is coupled to the first power splitter. The spoke transceiver is configured to receive a replicated spectrum of wavelengths from the first plurality of replicated spectrum of wavelengths. The optical communication system including a second power splitter coupled to the spoke transceiver. The second power splitter is configured to receive the replicated spectrum of wavelengths from the first plurality of replicated spectrum of wavelengths and output a second plurality of replicated spectrum of wavelengths. The optical communication system including a coherent transceiver of a server coupled to the second power splitter. The coherent transceiver is configured to receive a replicated spectrum of wavelengths from the second plurality of replicated spectrum of wavelengths. Also, the coherent transceiver is tunable to select a corresponding band of wavelengths from the replicated spectrum of wavelengths from the second plurality of replicated, wherein the band of wavelengths sets a bandwidth for the coherent transceiver. For example, the coherent transceiver may be tuned to one or more wavelengths, wherein multiple tuned wavelengths may be contiguous or non-contiguous.

(9) Other aspects of the disclosure will become apparent from the following detailed description, taken in conjunction with the accompanying drawings, illustrating by way of example the principles of the disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The disclosure may best be understood by reference to the following description taken in conjunction with the accompanying drawings in which:

- (2) FIG. 1 is a diagram of a game cloud system for providing gaming over a network between one or more compute nodes located at one or more data centers, in accordance with one embodiment of the present disclosure.
- (3) FIG. 2A is a diagram of a plurality of rack assemblies including a plurality of compute nodes at a representative data center of a game cloud system, in accordance with one embodiment of the present disclosure.
- (4) FIG. 2B is a diagram of a rack assembly including a top of rack switch configured to receive a full spectrum of wavelengths, in accordance with one embodiment of the present disclosure.
- (5) FIG. 3A illustrates an optical switching fabric with multi-point optics and configured with one super spine, in accordance with one embodiment of the present disclosure.
- (6) FIG. 3B illustrates an optical switching fabric with multi-point optics and configured with one or more super spines, in accordance with one embodiment of the present disclosure.
- (7) FIG. 4A illustrates an optical switching fabric configured with point to multipoint optics, in accordance with one embodiment of the present disclosure.
- (8) FIG. 4B illustrates the connections between components of the optical data center switching fabric of FIG. 4A, in accordance with one embodiment of the present disclosure.
- (9) FIG. 5A illustrates an exemplary layout of components of an optical switching fabric of a data center including a single splitter layer, in accordance with one embodiment of the present disclosure.
- (10) FIG. 5B illustrates an optical switching fabric of a data center including multiple and cascading splitter layers, in accordance with one embodiment of the present disclosure.
- (11) FIG. 6A is a diagram illustrating a switching fabric of a data center including the use of 1 by 4 (1*4) splitters across three cascading splitter layers connected to a super spine switching layer, in accordance with one embodiment of the present disclosure.
- (12) FIG. 6B is a diagram illustrating a physical data center layout implementing the switching fabric of FIG. 6A, in accordance with one embodiment of the present disclosure.
- (13) FIG. 7 is a diagram illustrating a switching fabric of a data center configured for performing switching at the host/server rack layer, in accordance with one embodiment of the present disclosure.

DETAILED DESCRIPTION

(14) Although the following detailed description contains many specific details for the purposes of illustration, anyone of ordinary skill in the art will appreciate that many variations and alterations to the following details are within the scope of the present disclosure. Accordingly, the aspects of the present disclosure described below are set forth without any loss of generality to, and without imposing limitations upon, the claims that follow this description.

(15) Generally speaking, embodiments of the present disclosure provide for an optical data center fabric (ODCF) and/or topology which deliver the advantages of a full internet protocol (IP) multi-stage switching network, and further provides for an express path between the edge of a data center and leaf nodes delivered using flexible optical technologies. In particular, intermediary layers of switches may be replaced with passive optical power splitters in the data fabric. Advantages include a reduction in capital and operational costs of a large optical data center fabric, as well as increased simplicity to implement the optical data center fabric. Additional advantages include ultra-low latency paths between hosts and end-user services as latency in the intermediary layers is improved through the use of passive optical splitters rather than switches because an optical power splitter is a pure passive optical device that essentially adds no latency, whereas a traditional switch performs an optical electrical optical (OEO) conversion along with some routing and/or switching operations (e.g., packet queuing, etc.) which introduce latency. That is, embodiments of the present disclosure significantly reduces latency through the optical data center fabric while also reducing capital expenditures through the removal of an intermediate switch layer(s) and replacement with intermediate power splitting layer(s) (e.g., replacing expensive switch hardware with less numbers

of cost effective passive optical devices in the fiber optic infrastructure) and a reduction in operational expenditures (e.g., reduction in power usage and less maintenance required) at the same time. In addition, embodiments of the present disclosure simplify the networking topology, leading to easier augmentation (e.g., scaling, multiple building implementation in or more geographic locations, etc.) and troubleshooting activities.

(16) With the above general understanding of the various embodiments, example details of the embodiments will now be described with reference to the various drawings.

(17) Throughout the specification, the reference to “application” or “game” or “video game” or “gaming application” or “game title” is meant to represent any type of interactive application that is directed through execution of input commands. For illustration purposes only, an interactive application includes applications for gaming, word processing, video processing, video game processing, etc. Further, the terms introduced above are interchangeable.

(18) Embodiments of the present disclosure are implemented within a data center supporting many multiples of computing systems. Each of the computing systems can be configured to perform one or more functionalities depending on the applications being executed on the corresponding computing system. The computing systems within a particular data center may be configured to mainly provide in general a service (e.g., cloud gaming, cloud storage, etc.), or may each be individually configured to provide unique services to a client. For example, the data center may be configured to generally provide cloud gaming services to many clients (e.g., remote computing devices each associated with a corresponding user). In another example, the data center may be configured to generally provide a financial service platform to many clients, such as those facilitating the trading of financial securities at high frequencies (e.g., stocks, etc.). These data centers having features of low latency, reduced infrastructure costs, simplicity in scaling, and multi-building implementations provided by embodiments of the present disclosure are desirable to provide these various services. For example, for cloud gaming services, these data centers are well suited for providing the best user experience to gamers playing complex games because there are little or no processing and/or display interruptions, and real on-demand gaming of any game title. Also, for financial services, these data centers are well suited for providing increased frequency and speed of trading (i.e., fast response times when submitting trading orders, etc.) over more traditionally configured data centers. For simplicity and ease of illustration, embodiments of the present disclosure are described within the context of data centers providing cloud gaming, but it is understood that the data centers could be configured to provide other services and/or functionalities, such as financial services, etc.,

(19) FIG. 1 is a diagram of a system **100** for providing gaming over a network **150** between one or more compute nodes located at one or more data centers, wherein the data centers are each configured using an optical data center IP switching fabric using passive optical power splitter devices which provides for an express path between the edge of the data center and leaf nodes with reduced latency, implementation simplicity, and reduced cost, in accordance with one embodiment of the present disclosure. The system is configured to provide gaming over a network between one or more cloud gaming servers, and more specifically is configured for high speed access to network storage, such as within a rack assembly, from compute nodes, in accordance with one embodiment of the present disclosure. Cloud gaming includes the execution of a video game at the server to generate game rendered video frames, which are then sent to a client for display. In other embodiments, system **100** including one or more data centers may be configured to provide other services, such as financial services, etc.

(20) It is also understood that cloud gaming may be performed using physical machines (e.g., central processing units—CPUs—and graphics processing units—GPU), or virtual machines, or a combination of both, in various embodiments (e.g. in a cloud gaming environment or within a stand-alone system). For example, virtual machines (e.g. instances) may be created using a hypervisor of a host hardware (e.g. located at a data center) utilizing one or more components of a

hardware layer, such as multiple CPUs, memory modules, GPUs, network interfaces, communication components, etc. These physical resources may be arranged in racks, such as racks of CPUs, racks of GPUs, racks of memory, etc., wherein the physical resources in the racks may be accessed using top of rack switches facilitating a fabric for assembling and accessing of components used for an instance (e.g. when building the virtualized components of the instance). Generally, a hypervisor can present multiple guest operating systems of multiple instances that are configured with virtual resources. That is, each of the operating systems may be configured with a corresponding set of virtualized resources supported by one or more hardware resources (e.g. located at a corresponding data center). For instance, each operating system may be supported with a virtual CPU, multiple virtual GPUs, virtual memory, virtualized communication components, etc. In addition, a configuration of an instance that may be transferred from one data center to another data center to reduce latency. Instant utilization defined for the user or game can be utilized when saving a user's gaming session. The instant utilization can include any number of configurations described herein to optimize the fast rendering of video frames for a gaming session. In one embodiment, the instant utilization defined for the game or the user can be transferred between data centers as a configurable setting. The ability to transfer the instant utilization setting enables for efficient migration of game play from data center to data center in case the user connects to play games from different geo locations.

(21) System **100** includes a game cloud system **190** as implemented through one or more data centers (e.g., data centers 1 through N). As shown, an instance of game cloud system **190** could be located in data center N that provides management functionality, wherein the management functionality of the game cloud system **190** may be distributed through multiple instances of the game cloud system **190** at each of the data centers. In some implementations, the game cloud system management functionality may be located outside of any of the data centers.

(22) That game cloud system **190** includes an assigner **191** that is configured to assign each of the client devices (e.g., 1-N) to corresponding resources in corresponding data centers. In particular, when client device **110** logs into the game cloud system **190**, the client device **110** may be connected with an instance of a game cloud system **109** at data center N, wherein data center N may be geographically closest to client device **110**. The assigner **191** is able to perform diagnostic testing to determine available transmit and receive bandwidth to the client device **110**. Based on the testing, the assigner **191** is able to assign resources to client device **110** with great specificity. For example, the assigner **191** is able to assign a particular data center to the client device **110**. In addition, the assigner **191** is able to assign to the client device **110** a particular compute node, of a particular compute sled, of a particular streaming array, of a particular rack assembly. Assignment may be performed based on knowledge of assets (e.g., games) that are available at the compute nodes. Previously, the client device is assigned general to a data center, without further assignment to rack assemblies. In this manner, the assigner **191** is able to assign a client device that is requesting execution of a particular gaming application that is compute intensive to a compute node that may not be running compute intensive applications. In addition, load management of assigning of compute intensive gaming applications as requested by clients may be performed at the assigner **191**. For example, the same compute intensive gaming application that is being requested over a short period of time, may be spread across different compute nodes, of different compute sleds in one rack assembly or different rack assemblies to reduce load on a particular compute node, compute sled, and/or rack assembly.

(23) In some embodiments, the assignment may be performed based on machine learning. In particular, resource demand may be predicted for a particular data center, and its corresponding resources. For example, if it can be predicted that a data center will soon be handling many clients running compute intensive gaming applications, then the assigner **191** may assign client device **110** with that knowledge, and assign resource that may not be currently utilizing all of its resource capabilities. In another case, assigner **191** may switch client device **110** from the game cloud

system **190** in data center N to resources available in data center 3, in anticipation of increased loading at data center N. In addition, future clients may be assigned to resources in a distributed fashion, such that the load and demand for resources may be distributed throughout the game cloud system, across multiple data centers, across multiple rack assemblies, across multiple compute sleds, and/or across multiple compute nodes. For example, client device **110** may be assigned resources from both game cloud systems on data center N (e.g., over path 1) and data center 3 (e.g., over path 2).

(24) Once the client device **110** is assigned to a particular compute node, of a corresponding compute sled, of a corresponding streaming array, the client device **110** connects to the corresponding data center through the network. That is, the client device **110** may be communicating with a different data center, such as data center 3, than the one performing assignment.

(25) System **100** provides gaming via a game cloud system **190**, wherein the game is being executed remote from client device (e.g. thin client) of a corresponding user that is playing the game, in accordance with one embodiment of the present disclosure. System **100** may provide gaming control to one or more users playing one or more games through the cloud game network or game cloud system **190** via network **150** in either single-player or multi-player modes. In some embodiments, the cloud game network or game cloud system **190** may include a plurality of virtual machines (VMs) running on a hypervisor of a host machine, with one or more virtual machines configured to execute a game processor module utilizing the hardware resources available to the hypervisor of the host. In some implementations, the game processor module may include a processing emulator to execute software applications configured for one processor or operating system to run on the processing emulator that may be configured with a different processor and/or operating system, wherein the processing emulator may or may not be virtualized. Network **150** may include one or more communication technologies. In some embodiments, network **150** may include 5.sup.th Generation (5G) network technology having advanced wireless communication systems.

(26) In some embodiments, communication may be facilitated using wireless technologies. Such technologies may include, for example, 5G wireless communication technologies. 5G is the fifth generation of cellular network technology. 5G networks are digital cellular networks, in which the service area covered by providers is divided into small geographical areas called cells. Analog signals representing sounds and images are digitized in the telephone, converted by an analog to digital converter and transmitted as a stream of bits. All the 5G wireless devices in a cell communicate by radio waves with a local antenna array and low power automated transceiver (transmitter and receiver) in the cell, over frequency channels assigned by the transceiver from a pool of frequencies that are reused in other cells. The local antennas are connected with the telephone network and the Internet by a high bandwidth optical fiber or wireless backhaul connection. As in other cell networks, a mobile device crossing from one cell to another is automatically transferred to the new cell. It should be understood that 5G networks are just an example type of communication network, and embodiments of the disclosure may utilize earlier generation wireless or wired communication, as well as later generation wired or wireless technologies that come after 5G.

(27) As shown, the system **100** including game cloud system **190** can provide access to a plurality of gaming applications. In particular, each of the client devices may be requesting access to different gaming applications from the cloud game network. For example, the game cloud system **190** may provide one or more game servers that may be configured as one or more virtual machines executing on one or more hosts to execute a corresponding gaming application. For example, a game server may manage a virtual machine supporting a game processor that instantiates an instance of a gaming application for a user. As such, a plurality of game processors of one or more game servers associated with a plurality of virtual machines is configured to execute multiple

instances of one or more gaming applications associated with gameplays of a plurality of users. In that manner, back-end server support provides streaming of media (e.g. video, audio, etc.) of gameplays of a plurality of gaming applications to a plurality of corresponding users. That is, a game server of the game cloud system **190** is configured to stream data (e.g. rendered images and/or frames of a corresponding gameplay) back to a corresponding client device through network **150**. In that manner, a computationally complex gaming application may be executing at the back-end server in response to controller inputs received and forwarded by client device. Each server is able to render images and/or frames that are then encoded (e.g. compressed) and streamed to the corresponding client device for display.

(28) In one embodiment, cloud game network or game cloud system **190** is a distributed game server system and/or architecture. In particular, a distributed game engine executing game logic is configured as a corresponding instance of a corresponding gaming application. In general, the distributed game engine takes each of the functions of a game engine and distributes those functions for execution by a multitude of processing entities. Individual functions can be further distributed across one or more processing entities. The processing entities may be configured in different configurations, including physical hardware, and/or as virtual components or virtual machines, and/or as virtual containers, wherein a container is different from a virtual machine as it virtualizes an instance of the gaming application running on a virtualized operating system. The processing entities may utilize and/or rely on servers and their underlying hardware on one or more servers (compute nodes) of the cloud game network or game cloud system **190**, wherein the servers may be located on one or more racks. The coordination, assignment, and management of the execution of those functions to the various processing entities are performed by a distribution synchronization layer. In that manner, execution of those functions is controlled by the distribution synchronization layer to enable generation of media (e.g. video frames, audio, etc.) for the gaming application in response to controller input by a player. The distribution synchronization layer is able to efficiently execute (e.g. through load balancing) those functions across the distributed processing entities, such that critical game engine components/functions are distributed and reassembled for more efficient processing.

(29) FIG. 2A is a diagram of a plurality of rack assemblies **220** including a plurality of compute nodes at a representative data center **200A** of a game cloud system, in accordance with one embodiment of the present disclosure. For example, multiple data centers may be distributed throughout the world, such as in North America, Europe and Japan. In one embodiment, the rack assemblies (e.g., configured for game streaming) are centered around compute nodes, which run gaming applications, video games and/or stream the audio/video of a game session to a one or more clients.

(30) The data center **200A** includes a plurality of rack assemblies **220** (e.g., rack assemblies **220A** through **220N**). Each of the rack assemblies includes corresponding top-of-rack (TOR) switches and a plurality of compute sleds. For example, representative rack assembly **220N** includes top-of-rack switch **240N** and a plurality of compute sleds **230** (e.g., sleds **230A** through **230N**). Other rack assemblies may be similarly configured with or without modification. In particular, each of the compute sleds includes one or more compute nodes providing hardware resources (e.g., processors, CPUs, GPUs, etc.). For example, compute sled **230N** in the plurality of compute sleds **230** of rack assembly **220N** is shown to include four compute nodes, though it is understood that the rack assembly may include one or more compute nodes. Each rack assembly is coupled to a top-of-rack switch that is configured to provide communication with a management server **210** that is configured for management of the corresponding data center. The top-of-rack switch may be coupled to the optical data center fabric configured to deliver data throughout the data center. For example, rack assembly **220N** is coupled to top-of-rack switch **240N**. The top-of-rack switch also provides communication to external communication networks (e.g., internet, etc.).

(31) As shown, the management server **210** of the data center **200A** communicates with the

assigner **191** (shown in FIG. 1) to assign resources to client device **110**. In particular, management server **210** may work with an instance of the game cloud system **190'** and in conjunction with the initial instance of the game cloud system **190** (e.g., of FIG. 1) to assign resources to client device **110**. In embodiments, the assignment is performed based on asset awareness, such as knowing what resources and bandwidth are required and that exist at the data center. As such, embodiments of the present disclosure are configured to assign client device **110** to a particular compute node **232** of a corresponding compute sled **231** of a corresponding rack assembly **220B**, for illustration.

(32) In addition, the management server **210** of the data center **200A** includes a switch controller **215** that is in communication with each of a plurality of top-of-rack (TOR) switches **240**. As described previously, each rack assembly may be configured with a corresponding cluster or top-of-rack switch. For example, rack assembly **220A** includes top-of-rack switch **240A**, rack assembly **220B** includes top-of-rack switch **240B**, rack assembly **220C** includes top-of-rack switch **240C**, . . . , and rack assembly **220N** includes top-of-rack switch **240N**. In particular, the switch controller **215** may configure each top-of-rack switch to tune to a selectable band of wavelengths, wherein the band sets a bandwidth for the spoke transceiver of a corresponding rack assembly. In that manner, each rack assembly may be reconfigured at various points in time depending on how the compute nodes in a corresponding rack assembly is to be utilized. For instance, during peak gaming periods, a rack assembly may be tuned to receive a band of wavelengths sufficient to support gaming. During off-peak gaming periods (e.g., dark periods), the same rack assembly may be tuned to receive a different band of wavelengths. For example, during off-peak periods the rack assembly may be tuned to receive less bandwidth (i.e., when compared to the bandwidth received during peak periods) that is sufficient to maintain a minimum amount of connectivity for gaming. In that manner, the extra bandwidth (i.e., unused by the rack assembly) may be dynamically allocated to other rack assemblies that are currently experiencing greater demand, such as rack assemblies having compute nodes performing data backup or maintenance, running deep learning algorithms, etc.

(33) FIG. 2B is a diagram of a rack assembly including a top-of-rack switch **250** configured to receive a full spectrum of wavelengths as part of an optical data center fabric, wherein the top-of-rack switch **250** is further tuned to receive and communicate on a discrete part of the full spectrum of wavelengths (e.g., a selected band of wavelengths setting a bandwidth for the rack assembly), in accordance with one embodiment of the present disclosure. In that manner, the optical data center fabric provides for an express path between the edge of a data center (e.g., super spine switch) and leaf nodes (e.g., top-of-rack switches) using one or more passive optical power splitter devices.

(34) In particular, rack assembly **220X** may be configured for providing game streaming capabilities using compute nodes executing one or more gaming applications. In other implementations, the compute nodes may be used for executing other types of applications. Rack assembly **220X** may include network storage (not shown) that is configured to store game content (e.g., gaming logic, gaming applications, game data, user data, etc.) for high speed access by one or more compute nodes and/or servers (**280A** to **280N**). One or more compute nodes and/or servers may be configured as a streaming array. In other embodiments, the network storage is remote from the rack assembly **220X**, such as within a distributed storage configured for storing a plurality of gaming applications (e.g., a full complement of game title packages for a game cloud system. As shown, the diagram of FIG. 2B shows a high-level rack design for the rack assembly **220X**, which may be representative of one or more of the plurality of rack assemblies **220** of FIG. 2A. For example, rack assembly **220X** may be representative of rack assembly **220N**.

(35) In addition, rack assembly **220X** includes a top-of-rack switch **250**, which may also be referred to as a leaf node or leaf node switch. The top-of-rack switch **250** is configured to receive a full spectrum of wavelengths provided within the optical data center fabric used for data networking throughout the data center, and is further tuned to receive and communicate on a discrete part of the full spectrum of wavelengths. For example, the top-of-rack switch **250** receives

the full spectrum of wavelengths from a passive optical power splitting layer or layers. In particular, the top-of-rack switch **250** may be communicatively coupled to other compute nodes and/or servers of the same rack assembly or different rack assemblies through the optical data center fabric. For instance, the top-of-rack switch may be communicatively coupled to a communications network (e.g., internet) to provide network communications that are external to the rack assembly and/or data center.

(36) As shown, the top-of-rack switch **250** includes a network interface card or controller (NIC) **260** that is configured for providing communications between the rack assembly **220X** and the optical data center fabric (e.g., via the full spectrum of wavelengths). In one embodiment, the NIC **260** includes a coherent receiver **275X** that is configured for tuning the rack assembly **220X** to select a band of wavelengths from the full spectrum of wavelengths received at the top-of-rack switch (e.g., select a band of wavelengths setting a bandwidth for the top-of-rack switch **250**). In one embodiment, the coherent receiver **275X** is configured within a hot-pluggable device **270**. For example, the hot-pluggable device may be a small form-factor pluggable (SFP) hot-pluggable network interface module **270** including a transceiver providing access to the optical data center fabric, wherein the top-of-rack switch is configured as a spoke transceiver. In another embodiment, the hot-pluggable device **270** is a quad small form-factor pluggable (QSFP) hot-pluggable network interface module including a transceiver providing access to the optical data center fabric providing higher speed data access and larger bandwidths, wherein the top-of-rack switch is configured as a spoke transceiver.

(37) In another embodiment, each of the compute nodes and/or servers **280A-280N** may optionally include a corresponding coherent receiver. For instance, server **280A** may include coherent receiver **275A**, server **280B** may include coherent receiver **275B**, . . . , and server **280N** may include coherent receiver **275N**. In that manner, tuning to a band of wavelengths may be performed at each of the compute nodes and/or servers instead of at the top-of-rack switch **250** of the corresponding rack assembly **220X**. A more detailed discussion for providing tuning at compute nodes and/or servers is provided in FIG. 7.

(38) As previously described, the top-of-rack switch **250** may be controlled by a management server over a control path (not shown). For instance, the top-of-rack switch **250** may be dynamically tuned to receive a particular band of wavelengths that set a bandwidth for the top-of-rack switch.

(39) FIG. 3A illustrates an optical data center switching fabric **300A** with point to multi-point optics configured between a super spine hub optical transceiver (e.g., switching device) **301A** and a plurality of leaf nodes **320** (e.g., spoke transceivers), in accordance with one embodiment of the present disclosure. Leaf nodes may be the top-of-rack switches of a plurality of rack assemblies in a data center. As shown, the super spine hub optical transceiver **301A** is communicatively coupled to each of the plurality of leaf nodes **320** (e.g., leaf switches or top-of-rack switches), such that the optical data center switching fabric **300A** effectively provides an express path between the edge of a data center (i.e., hub optical transceiver **301A**) and leaf nodes delivered using flexible optical technologies (e.g., passive optical power splitters).

(40) In particular, the optical data center switching fabric **300A** transmits data using the full spectrum of wavelengths to the leaf nodes, instead of splitting the full spectrum of wavelengths by frequency. This may be achieved through the use of passive optical devices in one or more intermediate layers (not shown), such as optical power splitters, instead of using switching devices, as will be further described below, such as in relation to FIGS. 4A-4B. For example, the super spine hub optical transceiver **301A** may be configured with multiple ports (e.g., greater than 2 lanes) for transmitting and receiving data. Depending on the number of leaf nodes, one or more intermediate layers may be inserted between the super spine hub optical transceiver **301A** and the plurality of leaf nodes **320**. That is, as the number of leaf switches increase, one lane coming from the super spine hub optical transceiver **301A** may be coupled to one or more layers of passive

optical power splitters for transmitting the full spectrum of wavelengths output by the super spine hub optical transceiver **301A** to more than one leaf node.

(41) In some embodiments, amplifiers may be implemented between the super spine hub optical transceiver **301A** and the plurality of leaf nodes **320** to improve the signal-to-noise ratio of the transmitted signals, although amplification is not anticipated to be necessary given the data length paths typically encountered within a data center. That is, the existing power from optics within the optical data center switching fabric **300A** should be high enough in a data center implementation, so that there is no need for amplifiers, but an amplification stage could be implemented if required, or in some other use cases, such as providing amplification at hub end.

(42) As shown, a switch controller **215A** may be configured within the super spine hub optical transceiver **301A**. The switch controller **215A** may be communicatively coupled to each of the plurality of leaf nodes **320** over control path **350**. In that manner, the switch controller **215A** may tune each of the leaf nodes to receive and/or process a band of wavelengths from the full spectrum of wavelengths transmitted from the super spine hub optical transceiver **301A** within the optical data center switching fabric **300A**. In some cases, the switch controller **215A** may be implemented within a management server **210**, as is shown in FIG. 2A, wherein the management server **210** may be configured within the super spine hub optical transceiver **301A**, or be located remote from the hub optical transceiver **301A**, as previously described. For example, a coherent receiver at a corresponding leaf node may be tuned to receive and/or process a band of wavelengths that set a bandwidth for that leaf node.

(43) The optical data center switching fabric **300A** includes a single super spine hub optical transceiver **301A** acting as a hub in a hub and plurality of spokes configuration, wherein the spokes are the leaf nodes. The super spine hub optical transceiver **301A** may provide data over a full spectrum of wavelengths. Purely for illustration, the full spectrum may be transmitted at 400 gigabits per second (400G) at selectable wavelengths carrying specific data rates (e.g., 16 or 32 or 64 gigabits per second, etc.). The full spectrum of wavelengths may be further compartmentalized into subcarriers (e.g., 25G or any other number of subcarrier wavelengths) through various multiplexing technologies. In one embodiment, the full spectrum of wavelengths is compartmentalized into 25G subcarrier wavelengths. In that manner, each of the spoke transceivers may be tuned to receive one or more 25G subcarrier wavelengths. For example, a spoke transceiver may be tuned to receive 25G subcarrier wavelengths, or 50G subcarrier wavelengths, or 75G subcarrier wavelengths, or 100G subcarrier wavelengths, or any increment or multiple of 25G subcarrier wavelengths.

(44) FIG. 3B illustrates an optical data center switching fabric **300B** with multi-point optics and configured with one or more super spines, in accordance with one embodiment of the present disclosure. Each super spine is communicatively coupled to the plurality of leaf nodes (e.g., spoke transceivers or top-of-rack switches) **320**. For example, each of the super spine hub optical transceivers (e.g., switching device) **301A** and **301B** is communicatively coupled to the plurality of leaf nodes **320**. Leaf nodes may be the top-of-rack switches of a plurality of rack assemblies in a data center. In that manner, the optical data center switching fabric **300B** effectively provides an express path between the edge of a data center (i.e., hub optical transceiver **301A** and **301B**) and leaf nodes delivered using flexible optical technologies (e.g., passive optical power splitters).

(45) The coupling between each of the super spine hub optical transceivers **301A** and **301B** and the plurality of leaf nodes **320** in the optical data center switching fabric **300B** is similar to the coupling between the super spine hub optical transceiver **301A** and the plurality of leaf nodes **320** described in FIG. 3A. In that manner, the optical data center switching fabric **300B** of FIG. 3B may provide approximately twice the operational capacity (e.g., throughput, bandwidth, etc.) as the optical data center switching fabric **300A** of FIG. 3A if data is transmitted using both the super spine optical transceivers **301A** and **301B**. Purely for illustration, if the optical data center switching fabric **300A** of FIG. 3A provides a full spectrum of wavelengths transmitted at 400

gigabits per second (i.e., 400 G) using the super spine hub optical transceiver **301A**, then the optical data center switching fabric **300B** of FIG. **3B** may be configured to provide a full spectrum of wavelengths transmitted at 800 gigabits per second (i.e., 800 G) using both super spine hub optical transceivers **301A** and **301B**. Also, the optical data center switching fabric **300B** of FIG. **3B** may provide the same operational capacity as the optical data center switching fabric **300A** of FIG. **3A**, but also provide for backup or failover services. That is, when paths data delivery paths over one or more ports on the super spine hub optical transceiver **301A** fail, those data paths may be resurrected using one or more ports of the super spine hub optical transceiver **301B**.

(46) As shown, a switch controller **215B** may be configured within the super spine hub optical transceiver **301B**. The switch controller **215B** may be communicatively coupled to each of the plurality of leaf nodes **320** over control path **355**. In that manner, the switch controller **215B** may tune each of the leaf nodes to receive and/or process a band of wavelengths from the full spectrum of wavelengths transmitted from the super spine hub optical transceiver **301B** within the optical data center switching fabric **300B**. In some cases, the switch controller **215B** may be implemented within a management server **210**, as is shown in FIG. **2A**, wherein the management server **210** may be configured within the super spine hub optical transceiver **301B**, or be located remote from the hub optical transceiver **301B**, as previously described. For example, a coherent receiver at a corresponding leaf node may be tuned to receive and/or process a band of wavelengths that set a bandwidth for that leaf node. Tuning of the leaf nodes is performed in cooperation between the switch controller **215A** and **215B** of super spine hub topical transceivers **301A** and **301B**.

(47) FIG. **4A** illustrates an optical data center switching fabric **400** configured with point-to-multipoint optics, in accordance with one embodiment of the present disclosure. In particular, the optical data center switching fabric uses point to multipoint optics to communicatively couple a hub optical transceiver **410** directly to a plurality of spoke optical transceivers **430** (e.g., leaf switches) through one or more intermediate layers including one or more passive optical devices.

(48) As shown, the optical data center switching fabric **400** includes a hub optical transceiver **410** (e.g., super spine switch) configured for receiving a spectrum of wavelengths, which is also referred to a full spectrum of wavelengths that is processed through the data center. The full spectrum of wavelengths **420** delivers a total bandwidth for data delivery within the optical data center switching fabric **400**. Purely for illustration, the full spectrum may be transmitted at 400 gigabits per second (e.g., 400 G) or 800 gigabits per second (800 G) aggregate at selectable data rates. The optical devices in the optical data center switching fabric **400** may be further compartmentalized into subcarriers, such as multiples of 25 G wavelengths and/or channels using various multiplexing technologies, as previously described. For example, as shown in FIG. **4A**, the full spectrum of wavelengths **420** can be split into 32 different 25 G wavelengths or bands of wavelengths.

(49) The hub optical transceiver **410** may be communicatively coupled to an optical power splitter **460**. That is, the point-to-multipoint optics of the optical data center switching fabric **400** may be broken out using optical power splitters that provide for a reduction in latency throughout the data center through the elimination of one or more switching layers including traditional switches. The reduction in latency is achieved as an optical power splitter is a pure passive optical device that essentially add no latency, whereas a traditional switch performs an optical electrical optical (OEO) conversion along with some routing and/or switching operations (e.g., packet queuing, etc.) which introduce latency. Further, the optical power splitter may be less complex and less costly than switches used at intermediate layers found in traditional switching fabrics. For instance, in some implementations, any standard optical power splitter can be used within the optical data center switching fabric **400**. The power splitter **460** operates as a passive device that is configured to replicate the spectrum of wavelengths **420** and outputs a plurality of replicated spectrum of wavelengths **420'**. For example, the plurality of replicated spectrum of wavelengths **420'** includes replicated spectrum of wavelengths **420A** replicated spectrum of wavelengths **420B**, . . . , and

replicated spectrum of wavelengths **420N**.

(50) In embodiments, each replicated spectrum of wavelengths includes the full spectrum of wavelengths **420** (e.g., 800 G wavelengths) transmitted by the hub optical transceiver **410**, but at lower power. That is, each replicated spectrum of wavelengths of the plurality of replicated spectrum of wavelengths **420'** has a corresponding power that is a fraction of a total power received from the hub optical transceiver **410** by the optical power splitter **460**. In one embodiment, a power splitter divides the total power or power received with a full spectrum or replicated full spectrum of wavelengths evenly or unevenly. For example, a power splitter may divide the total power of the full spectrum of wavelengths evenly or unevenly within the plurality of replicated spectrum of wavelengths.

(51) The optical data center switching fabric **400** includes a plurality of spoke transceivers **430** coupled to the power splitter. For instance, each spoke transceiver is coupled to the power splitter **460** through a separate connection (e.g., fiber optic cabling). In one implementation, each spoke transceiver is a leaf switch or leaf node, such as top-of-rack switch at each rack assembly of a corresponding data center. More particularly, each of the plurality of spoke transceivers is configured to receive a corresponding one of the plurality of replicated spectrum of wavelengths. That is, each spoke transceiver receives the full spectrum of wavelengths, such that the optical data center switching fabric **400** transmits data using the full spectrum of wavelengths to the spoke transceivers, instead of splitting the full spectrum of wavelengths by frequency. As such, the point-to-multipoint optics used between the hub optical transceiver **410** and each of the spoke optical transceivers split or break the power but still transfer the full spectrum of wavelengths. For example, spoke optical transceiver **430A** is configured to receive the replicated spectrum of wavelengths **420A**, spoke optical transceiver **430B** is configured to receive the replicated spectrum of wavelengths **420B**, . . . , and spoke optical transceiver **430N** is configured to receive the replicated spectrum of wavelengths **420N**.

(52) The plurality of spoke optical transceivers **430** is tunable to set a plurality of bandwidths based on the total bandwidth provided by the full spectrum of wavelengths **420**. More particularly, each spoke transceiver is tunable to select a band of wavelengths (i.e., select a discrete part of the corresponding full spectrum of wavelengths that is replicated) that set a bandwidth for the corresponding spoke transceiver. For example, each spoke transceiver may comprise a leaf switch, or top-of-rack switch that is deployed within a corresponding rack assembly servicing a plurality of hosts and/or servers. This can be achieved due to the use of tunable coherent receivers in the spoke optical transceivers. In particular, each spoke transceiver includes an optical coherent receiver that is configured to split the replicated spectrum of wavelengths (e.g., full spectrum of wavelengths) into selectable bands of wavelengths, such that each spoke transceiver can be dynamically tuned to receive a selectable band of wavelengths that define a bandwidth for the corresponding spoke transceiver. For instance, each spoke transceiver includes a coherent receiver configured for selecting a band of wavelengths from a corresponding one of the plurality of replicated spectrum of wavelengths that is received by the spoke transceiver.

(53) In particular, each spoke transceiver may be tuned to at least one subcarrier of wavelengths (e.g., 25 G wavelengths), but can be tuned to multiple subcarriers to increase bandwidth over an individual connection, such as to a corresponding spoke transceiver (e.g., top-of-rack switch). For example, spoke optical transceiver **430A** includes coherent receiver **440A** that is tuned to receive two 25 G subcarrier wavelengths for a total of 50 G wavelengths for its bandwidth, spoke optical transceiver **430B** includes coherent receiver **440B** that is tuned to receive one 25 G subcarrier wavelengths for a total of 25 G wavelengths for its bandwidth, . . . , and spoke optical transceiver **430N** includes coherent receiver **440N** that is tuned to receive four 25 G subcarrier wavelengths for a total of 100 G for its bandwidth. In addition, another spoke optical transceiver may include a coherent receiver that is tuned to receive any multiple of 25 G subcarrier wavelengths (e.g., 25 G, 50G, 75G, 100 G, 125 G, etc.), or may be tuned to receive any multiple of subcarrier wavelengths

that is more or less than 25 G. That is, while some components may be tuned for selecting multiples of 25 G increments, other components may be tuned for selecting larger or smaller increments based on the current technology or generation of communications within data centers.

(54) The optical data center switching fabric **400** achieves enhanced performance by reducing latency between the hub optical transceiver **410** and each of the plurality of spoke optical transceivers **430** through the removal of the intermediate layer(s) of switches. The one or more switches in one or more intermediate layers of switches is replaced with point-to-multipoint optics that are passive devices, which require no input power to operate. In one embodiment, the point-to-multipoint optics include passive optical power splitters. Depending on the number of spoke optical transceivers are needed within a data center, one or more intermediate layers of passive optical power splitters may be implemented, wherein each layer includes one or more power splitters. In one embodiment, multiple layers may include cascading layers of power splitters.

(55) In one embodiment, each of the hub optical transceiver **410**, optical power splitter **460**, and each of the plurality of spoke optical transceivers **430** may be hot pluggable. For instance, as previously described, each device may be included within a QSFP form factor. In one implementation, one or more hub optical transceivers and one or more optical power splitters (i.e., configured in one more layers or cascading layers) may be installed within a rack assembly. As previously described, each of the spoke optical transceivers may be installed in a corresponding rack assembly as a corresponding top-of-rack switch.

(56) In one embodiment, a control system is coupled to the plurality of coherent receivers of the plurality of spoke transceivers, wherein the control system is configured to tune the coherent receiver of the each spoke transceiver to select a corresponding band of wavelengths. For example, the control system may include a switch controller **215C** that is configured within the hub optical transceiver **410**. The switch controller **215C** may be communicatively coupled to each of the plurality of spoke optical transceivers **430** over control path **450**. In that manner, the switch controller **215C** may tune each of the spoke optical transceivers to receive and/or process a band of wavelengths from the full spectrum of wavelengths transmitted from the hub optical transceiver **410** within the optical data center switching fabric **400**. In some cases, the switch controller **215C** may be implemented within a management server **210**, as is shown in FIG. 2A, wherein the management server **210** may be configured within the hub optical transceiver **410**, or be located remote from the hub optical transceiver **410**, as previously described. For example, a coherent receiver at a corresponding spoke optical transceiver may be tuned to receive and/or process a band of wavelengths that set a bandwidth for that spoke optical transceiver.

(57) In one embodiment, the optical data center switching fabric **400** also allows for dynamic allocation of bandwidth to spoke optical transceivers. As traffic requirements vary over time the optical data center switching fabric **400** may be configured to increase and/or decrease capacity as required. For example, the optical data center switching fabric **400** used for a large business system may be heavily used during business hours, and as such can have more bandwidth allocated to selected rack assemblies and their corresponding hosts/servers during business hours or peak hours. During off-peak hours or dark time, the bandwidth allocated to each rack assembly may be dynamically tuned to allow for dynamic allocation of bandwidth between rack assemblies that are performing operations that may be more taxing or less taxing. For example, bandwidth can be tuned to be allocated and/or reallocated to various servers/network segments of various rack assemblies for purposes of performing data backups, management operations, performing machine learning algorithms, or other off peak applications. In addition, Software Defined Networking (SDN) may be configured to automate bandwidth allocation, such that bandwidth could be allocated dynamically and automatically as requirements dictate.

(58) In some embodiments, amplifiers may be implemented between the hub optical transceiver **410** and the plurality of spoke optical transceivers **430** to improve the signal-to-noise ratio of the transmitted signals, although amplification is not anticipated to be necessary given the data length

paths typically encountered within a data center. That is, an amplifier may be coupled between a spoke transceiver and the power splitter **460**, wherein the amplifier is configured to amplify power of a replicated spectrum of wavelengths received by the spoke transceiver. Also, an amplifier may be coupled between the hub optical transceiver **410** and the power splitter **460**, wherein the amplifier is configured to amplify power of a full spectrum of wavelengths received by the power splitter **460**.

(59) FIG. **4B** illustrates the optical data center switching fabric **400** introduced in FIG. **4A** that is configured with point-to-multipoint optics, in accordance with one embodiment of the present disclosure. The switching fabric **400** shown in FIGS. **4A** and **4B** is identically configured. That is, the optical data center switching fabric **400** uses point to multipoint optics to communicatively couple a hub optical transceiver **410** directly to a plurality of spoke optical transceivers **430** (e.g., leaf switches) through one or more intermediate layers including one or more passive optical devices.

(60) More particularly, the optical data center switching fabric **400** shown in FIG. **4B** illustrates the connections between components. As shown, the connections between the hub optical transceiver **410** and the optical power splitter **460** as well as connections between the power splitter **460** and each of the plurality of spoke optical transceivers **430** may be implemented through fiber optic cabling, which may be simplex or duplex fiber optic cabling. In simplex fiber optic cabling, signals flow in one direction (i.e., upstream or downstream). In duplex fiber optical cabling, signals can flow in both directions (i.e., upstream and downstream).

(61) In one embodiment, the connections between the hub optical transceiver **410** and the optical power splitter **460** is simplex fiber optic cabling, such that separate cabling is required for upstream data traffic and downstream data traffic. In another embodiment, the connections between the hub optical transceiver **410** and the optical power splitter **460** is duplex fiber optic cabling for handling both upstream and downstream data traffic.

(62) In one embodiment, the connections between the power splitter **460** and a corresponding spoke optical transceiver is simplex fiber optic cabling, such that separate cabling is required for upstream data traffic and downstream data traffic. In another embodiment, the connections between the power splitter **460** and a corresponding spoke optical transceiver is duplex fiber optic cabling for handling both upstream and downstream data traffic.

(63) FIGS. **5A-5B** show examples of optical splitting in a data center environment. Depending on the data center's purpose, capacity and the variability in bandwidth provisioning per rack assembly, multiple physical fiber optic infrastructure topologies can be used, in various embodiments. For purposes of illustration only, some examples are provided in FIGS. **5A-5B**, but it is understood that topologies are not limited to these examples. Whatever topology is implemented, the topologies for optical data center switching fabrics of embodiments of the present disclosure allow for maximum flexibility with minimal fiber optic count, meaning there is a significant reduction in fiber used and reduction in active switching infrastructure when compared with a traditional switching fabric design (e.g., using intermediate switching layer(s)) for the same rack assembly count within a data center (i.e., less passive optical devices used as compared to the number of active switches at intermediate layer(s)).

(64) In particular, FIG. **5A** illustrates an optical switching fabric **500A** of a data center including a single power splitter layer, in accordance with one embodiment of the present disclosure. The optical data center switching fabric **500A** uses point-to-multipoint optics to communicatively couple a super spine directly to a plurality of spoke optical transceivers **550** located in a plurality of rack assemblies **530**. As shown, the optical switching fabric **500A** includes a hub optical transceiver, a power splitter layer, and a plurality of spoke optical transceivers **550**.

(65) In particular, the optical switching fabric **500A** includes a super spine switching device (e.g., switch, hub optical transceiver, etc.) configured for receiving a spectrum of wavelengths (e.g., full spectrum of wavelengths) **420** delivering a total bandwidth for data delivery, wherein the full

spectrum of wavelengths **420** has a total power. The super spine switching device may be configured within a super spine rack assembly **501A** that also includes passive optical devices.

(66) In addition, the optical switching fabric **500A** includes a power splitting layer coupled to the super spine in the rack assembly **501A** (e.g., hub optical transceiver). The power splitting layer is configured to output a plurality of replicated spectrum of wavelengths, wherein each replicated spectrum of wavelengths has a corresponding power that is fraction of a total power received from the super spine **501A**. In one embodiment, the power splitting layer includes a plurality of power splitters configured in one or more cascading layers, wherein each power splitter operates as a passive device, and is configured to replicate the spectrum of wavelengths as received at a reduced power. The power splitting layer may also be included within the rack assembly **501A**.

(67) As shown in FIG. 5A, the power splitting layer includes one layer, and more specifically includes one power splitter **460A** configured as a one to 16 (1*16) power splitter. That is, the full spectrum of wavelengths is split into sixteen replicated spectrum of wavelengths. Each of the replicated spectrum of wavelengths has a corresponding power that is a fraction of the total power received from the super spine switching device, as previously described. In one embodiment, the fractions associated with the replicated spectrum of wavelengths is evenly distributed. In another embodiment, the fractions associated with the replicated spectrum of wavelengths is unevenly distributed.

(68) As shown, power splitter **460** has multiple outputs (e.g., channels) **540A** through **540P**, such as 16 channels. Each of the outputs has a corresponding replicated spectrum of wavelengths. The outputs are coupled to a plurality of top-of-rack switches **550** in a plurality of rack assemblies **530**. For example, channel **540A** output from power splitter **460A** is coupled to top-of-rack switch **550A** of rack assembly **530A**, channel **540B** is coupled to top-of-rack switch **550B** of rack assembly **530B**, channel **540C** is coupled to top-of-rack switch **550C** of rack assembly **530C**, channel **540D** is coupled to top-of-rack switch **550D** of rack assembly **530D**, channel **540E** is coupled to top-of-rack switch **550E** of rack assembly **530E**, channel **540F** is coupled to top-of-rack switch **550F** of rack assembly **530F**, channel **540G** is coupled to top-of-rack switch **550G** of rack assembly **530G**, channel **540H** is coupled to top-of-rack switch **550H** of rack assembly **530H**, channel **540I** is coupled to top-of-rack switch **550I** of rack assembly **530I**, channel **540J** is coupled to top-of-rack switch **550J** of rack assembly **530J**, channel **540K** is coupled to top-of-rack switch **550K** of rack assembly **530K**, channel **540L** is coupled to top-of-rack switch **550L** of rack assembly **530L**, channel **540M** is coupled to top-of-rack switch **550M** of rack assembly **530M**, channel **540O** is coupled to top-of-rack switch **550O** of rack assembly **530O**, and channel **540P** is coupled to top-of-rack switch **550P** of rack assembly **530P**. In that manner, one super spine switch port may be connected to 16 leaf switches or top-of-rack switches. It is understood that one switch port may be connected to any number of top-of-rack switches depending on the number of power splitting layer are implemented.

(69) In particular, the optical data center switching fabric **500A** includes plurality of spoke transceivers (e.g., top-of-rack switches) coupled to the power splitting layer. Each of the plurality of spoke transceivers is configured to receive a corresponding one of the plurality of replicated spectrum of wavelengths, wherein each spoke transceiver is tunable to select a band of wavelengths that set a bandwidth for the each spoke transceiver. As shown in FIG. 5A, a plurality of top-of-rack switches **530** is coupled to the power splitting layer or the power splitter **460A**. As previously described, each of the top-of-rack switches receives a replicated spectrum of wavelengths and can be further tuned to select a band of wavelengths that set a bandwidth for the corresponding top-of-rack switch. This is achieved using corresponding coherent optical receivers at each top-of-rack switch that is configured to split the replicated spectrum of wavelengths into selectable bands of wavelengths that define the bandwidth for the corresponding top-of-rack switch.

(70) As previously described, a control system coupled to coherent receivers of the plurality of top-of-rack switches **530**, wherein the control system is configured for tuning each top-of-rack switch

to select the corresponding band of wavelengths. Though the control system is not shown in FIG. 5A, the control system may include a switch controller that is communicatively coupled to each coherent receiver in order to tune each of the top-of-rack switches to receive a corresponding band of wavelengths from the full spectrum of wavelengths **420**.

(71) FIG. 5B illustrates an optical switching fabric **500B** of a data center including multiple and cascading splitter layers, in accordance with one embodiment of the present disclosure. The optical data center switching fabric **500B** uses point-to-multipoint optics to communicatively couple a super spine directly to a plurality of spoke optical transceivers **560** located in a plurality of rack assemblies **530**. As shown, the optical switching fabric **500B** includes a hub optical transceiver, cascading power splitting layers, and a plurality of spoke optical transceivers **550**

(72) In particular, the optical switching fabric **500B** includes a super spine switching device (e.g., switch, hub optical transceiver, etc.) configured for receiving a spectrum of wavelengths (e.g., full spectrum of wavelengths) **420** delivering a total bandwidth for data delivery, wherein the full spectrum of wavelengths **420** has a total power. The super spine switching device may be configured within a super spine rack assembly **501B** that also includes passive optical devices in the cascading power splitting layers.

(73) In particular, the optical switching fabric **500A** includes cascading power splitting layers configured to output a plurality of replicated spectrum of wavelengths, wherein each replicated spectrum of wavelengths has a corresponding power that is fraction of a total power received from the super spine in the rack assembly **501B**. In one embodiment, the cascading power splitting layers includes a plurality of power splitters configured in one or more cascading layers, wherein each power splitter operates as a passive device, and is configured to replicate the spectrum of wavelengths as received at a reduced power. The cascading power splitting layers may also be included within the rack assembly **501B**.

(74) As shown, the cascading power splitting layers includes a first layer that includes one power splitter **460B** configured as a one to four (1×4) power splitter. That is, the full spectrum of wavelengths is split into four replicated spectrum of wavelengths. For example, the power splitter **460** provides as an output over channel **560** a replicated spectrum of wavelengths, and provides as another output over channel **561** a replicated spectrum of wavelengths, and provides as another output over channel **562** a replicated spectrum of wavelengths, and provides as another output over channel **563** a replicated spectrum of wavelengths. Each of the replicated spectrum of wavelengths provided as output from the power splitter **460B** has a corresponding power that is a fraction of the total power received from the super spine switching device, as previously described. In one embodiment, the fractions associated with the replicated spectrum of wavelengths is evenly distributed. In another embodiment, the fractions associated with the replicated spectrum of wavelengths is unevenly distributed.

(75) In particular, the optical data center switching fabric **500B** includes plurality of spoke transceivers (e.g., top-of-rack switches) coupled to the cascading power splitting layers. Each of the plurality of spoke transceivers is configured to receive a corresponding one of the plurality of replicated spectrum of wavelengths, wherein each spoke transceiver is tunable to select a band of wavelengths that set a bandwidth for the each spoke transceiver. As shown in FIG. 5B, a plurality of top-of-rack switches **530** is coupled to the cascading power splitting layers. As previously described, each of the top-of-rack switches receives a replicated spectrum of wavelengths and can be further tuned to select a band of wavelengths that set a bandwidth for the corresponding top-of-rack switch. This is achieved using corresponding coherent optical receivers at each top-of-rack switch that is configured to split the replicated spectrum of wavelengths into selectable bands of wavelengths that define the bandwidth for the corresponding top-of-rack switch.

(76) As shown, the cascading power splitting layers is coupled to a plurality of top-of-rack switches **550** in a plurality of rack assemblies **530**. In particular, each of the outputs from the power splitter **460B** is coupled to corresponding top-of-rack switches through a corresponding power splitter. For

example, output over channel **560** is coupled to power splitter **460C** that is configured as a one to four (1*4) power splitter, output over channel **561** is coupled to power splitter **460D** that is configured as a one to four (1*4) power splitter, output over channel **562** is coupled to power splitter **460E** that is configured as a one to four (1*4) power splitter, and output over channel **563** is coupled to power splitter **460F** that is configured as a one to four (1*4) power splitter. Each of the outputs provides a replicated spectrum of wavelengths.

(77) In addition, each of the power splitters **460C**, **460D**, **460E**, and **460F** is coupled to multiple top-of-rack switches of corresponding rack assemblies. As shown, the power splitters **460C**, **460D**, **460E**, and **460F** may be installed in a corresponding rack assembly, though the power splitters may be located elsewhere, such as in another rack assembly. In particular, power splitter **460C** provides four outputs over channels **560A**, **560B**, **560C**, and **560D**. Each of the channels is further communicatively coupled to a corresponding top-of-rack switch. For example, from power splitter **460C** channel **560A** is coupled to top-of-rack switch **550A** of rack assembly **530A**, channel **560B** is coupled to top-of-rack switch **550B** of rack assembly **530B**, channel **560C** is coupled to top-of-rack switch **550C** of rack assembly **530C**, and channel **560D** is coupled to top-of-rack switch **550D** of rack assembly **530D**. Also, from power splitter **460D** channel **561A** is coupled to top-of-rack switch **550E** of rack assembly **530E**, channel **561B** is coupled to top-of-rack switch **550F** of rack assembly **530F**, channel **561C** is coupled to top-of-rack switch **550G** of rack assembly **530G**, and channel **561D** is coupled to top-of-rack switch **550H** of rack assembly **530H**. Also, from power splitter **460E** channel **562A** is coupled to top-of-rack switch **550I** of rack assembly **530I**, channel **562B** is coupled to top-of-rack switch **550J** of rack assembly **530J**, channel **562C** is coupled to top-of-rack switch **550K** of rack assembly **530K**, and channel **562D** is coupled to top-of-rack switch **550L** of rack assembly **530L**. Also, from power splitter **460F** channel **563A** is coupled to top-of-rack switch **550M** of rack assembly **530M**, channel **563B** is coupled to top-of-rack switch **550N** of rack assembly **530N**, channel **563C** is coupled to top-of-rack switch **550O** of rack assembly **530O**, and channel **563D** is coupled to top-of-rack switch **550P** of rack assembly **530P**.

(78) As previously described, a control system coupled to coherent receivers of the plurality of top-of-rack switches **530**, wherein the control system is configured for tuning each top-of-rack switch to select the corresponding band of wavelengths. Though the control system is not shown in FIG. 5B, the control system may include a switch controller that is communicatively coupled to each coherent receiver in order to tune each of the top-of-rack switches to receive a corresponding band of wavelengths from the full spectrum of wavelengths **420**.

(79) FIG. 6A is a diagram illustrating a switching fabric **600A** of a data center including the use of 1 by four (1*4) splitters across three cascading power splitter layers connected to a super spine switching layer **610**, in accordance with one embodiment of the present disclosure. In particular, the optical data center switching fabric **600A** uses point to multipoint optics to communicatively couple a super spine switching layer (e.g., hub optical transceiver) directly to a plurality of spoke optical transceivers (e.g., leaf switches, top-of-rack switches) through one or more intermediate layers including one or more passive optical devices.

(80) As shown, the optical data center switching fabric **600A** includes a super spine switching layer **610** configured for receiving a spectrum of wavelengths, which is also referred to a full spectrum of wavelengths that is processed through the data center. The full spectrum of wavelengths delivers a total bandwidth for data delivery within the optical data center switching fabric **600A**. Purely for illustration, the full spectrum may be transmitted at 400 gigabits per second (e.g., 400 G) or 800 gigabits per second (800 G) aggregate at selectable data rates. The optical devices in the optical data center switching fabric **400** may be further compartmentalized into subcarriers, such as multiples of 25 G wavelengths using various multiplexing technologies, as previously described. For example, the full spectrum of wavelengths can be split into 32 different 25 G wavelengths or bands of wavelengths.

(81) The optical switching fabric **600A** includes three cascading power splitter layers coupled to the

super spine switching layer **610**. For example, the cascading power splitter layers and the super spine switching layer could be located within one rack assembly of a data center. The three cascading splitter layers includes a first cascade stage of power splitters, a second cascade stage of power splitters, and a third cascade stage of power splitters. The three cascading power splitting layers are configured to output a plurality of replicated spectrum of wavelengths, wherein each replicated spectrum of wavelengths has a corresponding power that is fraction of a total power received from the super spine switching layer **610**. In one embodiment, the cascading power splitter layers includes a plurality of power splitters configured in one or more cascading layers, wherein each power splitter operates as a passive device, and is configured to replicate the spectrum of wavelengths as received at a reduced power.

(82) In particular, the first cascade stage includes a single one by four (1×4) power splitter **460G** that provides four outputs over channels. Each of the outputs provides a replicated spectrum of wavelengths that has a power that is fraction of the total power for the full spectrum of wavelengths provided by the super spine switching layer **610**.

(83) The second cascade stage includes four power splitters, wherein each power splitter is a one by four (1×4) power splitter, and each power splitter is coupled to the power splitter **460G** in the first cascade stage. For example, power splitter **460H** receives a replicated spectrum of wavelengths over a channel from power splitter **460G** in the first cascade stage, and provides four additional outputs over channels, each providing a replicated spectrum of wavelengths. Also, power splitter **460I** receives a replicated spectrum of wavelengths over a channel from power splitter **460G** in the first cascade stage, and provides four additional outputs over channels, each providing a replicated spectrum of wavelengths. Also, power splitter **460J** receives a replicated spectrum of wavelengths over a channel from power splitter **460G** in the first cascade stage, and provides four additional outputs over channels, each providing a replicated spectrum of wavelengths. Further, power splitter **460K** receives a replicated spectrum of wavelengths over a channel from power splitter **460G** in the first cascade stage, and provides four additional outputs over channels, each providing a replicated spectrum of wavelengths.

(84) The third cascade stage includes sixteen power splitters **460L**, **460M**, **460N**, **460O**, . . . , and **460X**. Each of the power splitters is similarly configured, wherein each power splitter is coupled to an output from one of the power splitters of the second cascade stage. As a representative example, power splitter **460H** from the second cascade stage provides four outputs coupled to power splitters **460L**, **460M**, **460N**, and **460O**. For example, each of the power splitter **460L** through **460O** receives a corresponding replicated spectrum of wavelengths over a corresponding channel from power splitter **460H**.

(85) The three cascading power splitter layers is coupled to a plurality of spoke optical transceivers, such as top-of-rack switches of a plurality of rack assemblies. Each of the plurality of spoke transceivers is configured to receive a corresponding replicated spectrum of wavelengths, wherein each spoke transceiver receives the full spectrum of wavelengths, but at a reduced power from the total power output by the super spine switching layer **610** providing the full spectrum of wavelengths, as previously described. As such, each spoke transceiver is configured to split the replicated spectrum of wavelengths (e.g., full spectrum of wavelengths) into a selectable band of wavelengths using a corresponding optical coherent receiver. That is, each spoke transceiver can be dynamically tuned to receive a selectable band of wavelengths that define a bandwidth for the corresponding spoke transceiver.

(86) FIG. **6B** is a diagram illustrating a physical data center layout implementing the optical data center switching fabric **600A** of FIG. **6A** including multiple and cascading power splitter layers, in accordance with one embodiment of the present disclosure. The optical data center switching fabric **600B** uses point-to-multipoint optics to communicatively couple a super spine switching layer directly to a plurality of spoke optical transceivers **550** located in a plurality of rack assemblies **530**. As shown, the optical switching fabric **600B** includes a super spine switching layer **690** (e.g.,

spine switch, a hub optical transceiver etc.), cascading power splitting layers, and a plurality of spoke optical transceivers **550**.

(87) The super spine switching layer (e.g., switch, hub optical transceiver, etc.) is configured for receiving a spectrum of wavelengths (e.g., full spectrum of wavelengths) delivering a total bandwidth for data delivery, wherein the full spectrum of wavelengths has a total power.

(88) The optical switching fabric **600B** includes cascading power splitting layers configured to output a plurality of replicated spectrum of wavelengths, wherein each replicated spectrum of wavelengths has a corresponding power that is fraction of a total power received from the super spine switching layer. In one embodiment, the cascading power splitting layers includes a plurality of power splitters configured in one or more cascading layers, wherein each power splitter operates as a passive device, and is configured to replicate the spectrum of wavelengths as received at a reduced power.

(89) The first cascade stage **631** includes one power splitter **460P** configured as a one to four (1×4) power splitter. That is, the full spectrum of wavelengths is split into four replicated spectrum of wavelengths. For example, the power splitter **460P** provides as an output over four channels, wherein each channel carries a replicated spectrum of wavelengths. Each of the replicated spectrum of wavelengths provided as output from the power splitter **460P** has a corresponding power that is a fraction of the total power received from the super spine switching layer, as previously described.

(90) The second cascade stage **632** of power splitters includes four power splitters, each configured as a one to four (1×4) power splitter. For example, the second cascade stage **632** includes power splitter **460R**, **460S**, **460T**, and **460U**, each coupled to the power splitter **460P** in the first cascade stage **631**. Each of the power splitters is coupled to top-of-rack switches in a corresponding row of rack assemblies.

(91) For example, power splitter **460R** receives a spectrum of wavelengths from the power splitter **460P** over a corresponding channel, and further provides over four corresponding channels additional spectrums of wavelengths of even lesser power to each of the top-of-rack switches **550A**, **550B**, **550C**, and **550D** in the 1st row of rack assemblies **551**. Also, power splitter **460S** receives a spectrum of wavelengths from the power splitter **460P** over a corresponding channel, and further provides over four corresponding channels additional spectrums of wavelengths of even lesser power to each of the top-of-rack switches **550E**, **550F**, **550G**, and **550H** in the 2nd row of rack assemblies **552**. Also, power splitter **460T** receives a spectrum of wavelengths from the power splitter **460P** over a corresponding channel, and further provides over four corresponding channels additional spectrums of wavelengths of even lesser power to each of the top-of-rack switches **550I**, **550J**, **550K**, and **550L** in the 3rd row of rack assemblies **553**. Further, power splitter **460U** receives a spectrum of wavelengths from the power splitter **460P** over a corresponding channel, and further provides over four corresponding channels additional spectrums of wavelengths of even lesser power to each of the top-of-rack switches **550M**, **550N**, **550O**, and **550P** in the 4th row of rack assemblies **554**.

(92) As previously described, each of the plurality of spoke transceivers **530** (e.g., top-of-rack switch) is configured to receive a corresponding one of the plurality of replicated spectrum of wavelengths, wherein each spoke transceiver is tunable to select a band of wavelengths that set a bandwidth for the each spoke transceiver. As shown in FIG. **6B**, a plurality of top-of-rack switches **530** is coupled to the cascading power splitting layers. As previously described, each of the top-of-rack switches receives a replicated spectrum of wavelengths and can be further tuned to select a band of wavelengths that set a bandwidth for the corresponding top-of-rack switch. This is achieved using corresponding coherent optical receivers at each top-of-rack switch that is configured to split the replicated spectrum of wavelengths into selectable bands of wavelengths that define the bandwidth for the corresponding top-of-rack switch.

(93) As is shown in FIG. **6B**, the optical data center switching fabric can be implemented using repeatable steps. Specifically, the physical connectivity of each rack assembly remains identical,

such as a power hookup, and a fiber cable to connect to the optical data center switching fabric. As such, the provisioned bandwidth can be dynamically adjusted to suit each rack type as it is added to the optical data center fabric. This would simplify data center architecture, and simplify the physical provisioning and cabling process, with a reduced number of optical connections needed. (94) In one embodiment, the first cascade stage **631** and second cascade stage **632** of one or more power splitters may be located within an overhead or underfloor cable tray **620**. Fiber optic cabling coupling the two cascade stages **631** and **632** to top-of-rack switches in each of the rows of rack assemblies **551-554** may be routed through the cable tray **620**. In particular, one consistent fiber cable drop may be provided for each rack assembly in the rows of rack assemblies **551-554** at install time. As previously described, control of each rack assembly provides for dynamic tuning of bandwidth received at each corresponding rack assembly, so that each rack assembly can be dynamically configured to receive a selectable bandwidth at any point in time.

(95) FIG. 7 is a diagram illustrating a switching fabric of a data center configured for performing switching at the host/server rack layer, in accordance with one embodiment of the present disclosure. The optical data center switching fabric uses point-to-multipoint optics to communicatively couple a super spine switching layer directly to a plurality of spoke optical transceivers located in a plurality of rack assemblies. In particular, data delivery is shown at a rack assembly **700**, wherein instead of providing coherent receivers at top-of-rack switches of corresponding rack assemblies, the coherent receivers could be moved further down the distribution stack from the switching fabric providing data to the rack assemblies to the hosts/servers generating the traffic within one or more rack assemblies. As bandwidth requirements become greater and low latency paths become more important, a reduction in the number of steps between end points in the network may provide higher bandwidth to the end points (e.g., hosts and/or servers).

(96) For example, the top-of-rack switch **550'** (e.g., spoke optical transceiver) may optically be configured with coherent receivers, as previously described. However, the operations performed by the coherent receivers may be further pushed to each of the compute nodes of the rack assembly, as will be further described below.

(97) In particular, the top-of-rack switch **550'** may be configured to receive a replicated spectrum of wavelengths from a power splitter. As previously described, a hub optical transceiver is configured for receiving a spectrum of wavelengths (e.g., full spectrum of wavelengths) delivering a total bandwidth for data delivery, wherein the full spectrum of wavelengths has a total power. A cascading power splitting layer includes one or more power splitters each configured to output a corresponding replicated spectrum of wavelengths, wherein each replicated spectrum of wavelengths has a corresponding power that is fraction of a total power associated with the full spectrum of wavelengths provided by the hub optical transceiver. For example, a power splitter may be configured to replicate the spectrum of wavelengths and provide a plurality of replicated spectrum of wavelengths.

(98) As shown, the top-of-rack switch **550'** may provide an output over port 0 to another power splitter **460X**, which may be configured as a one by eight (1*8) power splitter. The power splitter **460X** provides as output a corresponding replicated spectrum of wavelengths to each of eight servers and/or compute nodes (e.g., server 0 through server 7) in set **701** over corresponding channels **711A**, **711B**, . . . , and **711H**. Also, the top-of-rack switch **550'** may provide an output over port 1 to a another power splitter **460Y**, which may be configured as a one by eight (1*8) power splitter. The power splitter **460Y** provides as output a corresponding replicated spectrum of wavelengths to each of eight servers (e.g., server 0 through server 7) in set **702** over corresponding channels **712A**, **712B**, . . . , and **712H**. Also, the top-of-rack switch **550'** may provide an output over port 2 to another power splitter **460Z**, which may be configured as a one by eight (1*8) power splitter. The power splitter **460Z** provides as output a corresponding replicated spectrum of wavelengths to each of eight servers (e.g., server 0 through server 7) in set **703** over corresponding

channels 713A, 713B, . . . , and 713H. Ports 3 through 7 of top-of-rack switch 550' may be similarly configured to provide an output of a corresponding replicated spectrum of wavelengths to additional sets of eight servers (not shown).

(99) Furthermore, each of the servers may be configured with a corresponding coherent transceiver. As such, a coherent transceiver of a server that is coupled to a power splitter may be configured to receive a replicated spectrum of wavelengths. Further, the coherent receiver is tunable to select a corresponding band of wavelengths from the replicated spectrum of wavelengths that set a bandwidth for the coherent transceiver and correspondingly the corresponding server. That is, the coherent receiver of a server is configured to split the replicated spectrum of wavelengths into selectable bands of wavelengths that define the bandwidth for the corresponding server.

(100) Accordingly, the present disclosure describes an optical data center fabric (ODCF) and/or topology which deliver the advantages of a full internet protocol (IP) multi-stage switching network, and further provides for an express path between the edge of a data center and leaf nodes delivered using flexible optical technologies.

(101) It should be understood that the various embodiments defined herein may be combined or assembled into specific implementations using the various features disclosed herein. Thus, the examples provided are just some possible examples, without limitation to the various implementations that are possible by combining the various elements to define many more implementations. In some examples, some implementations may include fewer elements, without departing from the spirit of the disclosed or equivalent implementations.

(102) Embodiments of the present disclosure may be practiced with various computer system configurations including hand-held devices, microprocessor systems, microprocessor-based or programmable consumer electronics, minicomputers, mainframe computers and the like. Embodiments of the present disclosure can also be practiced in distributed computing environments where tasks are performed by remote processing devices that are linked through a wire-based or wireless network.

(103) With the above embodiments in mind, it should be understood that embodiments of the present disclosure can employ various computer-implemented operations involving data stored in computer systems. These operations are those requiring physical manipulation of physical quantities. Any of the operations described herein that form part of embodiments of the present disclosure are useful machine operations. Embodiments of the disclosure also relate to a device or an apparatus for performing these operations. The apparatus can be specially constructed for the required purpose, or the apparatus can be a general-purpose computer selectively activated or configured by a computer program stored in the computer. In particular, various general-purpose machines can be used with computer programs written in accordance with the teachings herein, or it may be more convenient to construct a more specialized apparatus to perform the required operations.

(104) The disclosure can also be embodied as computer readable code on a computer readable medium. The computer readable medium is any data storage device that can store data, which can be thereafter be read by a computer system. Examples of the computer readable medium include hard drives, network attached storage (NAS), read-only memory, random-access memory, CD-ROMs, CD-Rs, CD-RWs, magnetic tapes and other optical and non-optical data storage devices. The computer readable medium can include computer readable tangible medium distributed over a network-coupled computer system so that the computer readable code is stored and executed in a distributed fashion.

(105) Although the method operations were described in a specific order, it should be understood that other housekeeping operations may be performed in between operations, or operations may be adjusted so that they occur at slightly different times, or may be distributed in a system which allows the occurrence of the processing operations at various intervals associated with the processing, as long as the processing of the overlay operations are performed in the desired way.

(106) Although the foregoing disclosure has been described in some detail for purposes of clarity of understanding, it will be apparent that certain changes and modifications can be practiced within the scope of the appended claims. Accordingly, the present embodiments are to be considered as illustrative and not restrictive, and embodiments of the present disclosure is not to be limited to the details given herein, but may be modified within the scope and equivalents of the appended claims.

Claims

1. An optical communication system, comprising: a hub optical transceiver configured for receiving a spectrum of wavelengths, wherein the spectrum of wavelengths includes a plurality of subcarriers, wherein each of the plurality of subcarriers includes a corresponding and unique band of wavelengths taken from the spectrum of wavelengths; a power splitter coupled to the hub optical transceiver and configured to receive the spectrum of wavelengths, wherein the power splitter is configured to generate one or more replicated spectrum of wavelengths; a top-of-rack switch coupled to the power splitter and deployed within a rack assembly servicing a plurality of servers, wherein the top-of-rack switch is configured to receive a replicated spectrum of wavelengths; and a control system coupled to the top-of-rack switch, wherein the control system is configured to tune the top-of-rack switch to select one or more bands of wavelengths taken from the replicated spectrum of wavelengths.
2. The optical communication system of claim 1, further comprising: a coherent receiver in a network interface of the top-of-rack switch, wherein the coherent receiver is coupled to the control system, wherein the coherent receiver is tunable by the control system to select the one or more bands of wavelengths taken from the replicated spectrum of wavelengths.
3. The optical communication system of claim 2, wherein the coherent receiver is a hot pluggable device.
4. The optical communication system of claim 1 wherein the replicated spectrum of wavelengths received by the top-of-rack switch has a power that is a fraction of a total power for the spectrum of wavelengths received from the hub optical transceiver.
5. The optical communication system of claim 4, further comprising: an amplifier coupled between the top-of-rack switch and the power splitter and configured to generate the power for the replicated spectrum of wavelengths.
6. The optical communication system of claim 1, wherein one or more of the hub optical transceiver and the power splitter and the top-of-rack switch is a quad small form-factor pluggable (QSFP) device.
7. The optical communication system of claim 1, further comprising: a plurality of top-of-rack switches coupled to the power splitter and the control system, the plurality of top-of-rack switches deployed within a plurality of rack assemblies, each of the plurality of rack assemblies servicing a corresponding plurality of servers, wherein each of the plurality of top-of-rack switches is configured to receive a corresponding replicated spectrum of wavelengths from the one or more replicated spectrum of wavelengths generated by the power splitter, wherein the control system is configured to tune each of the plurality of top-of-rack switches to select a corresponding band of wavelengths taken from the corresponding replicated spectrum of wavelengths.
8. The optical communication system of claim 1, wherein the top-of-rack switch is configured to select a band of wavelengths taken from the replicated spectrum of wavelengths.
9. The optical communication system of claim 8, further comprising: a plurality of servers coupled to the top of top-of-rack switch, wherein the control system is configured to tune the top-of-rack switch to select a plurality of bands of wavelengths taken from the replicated spectrum of wavelengths, such that the top-of-rack switch receives the replicated spectrum of wavelengths; a first coherent receiver of a first server of the plurality of servers, wherein the first coherent receiver is coupled to the control system, wherein the first coherent receiver is tunable by the control system

to select a first band of wavelengths.

10. The optical communication system of claim 9, further comprising: a second coherent receiver of a second server of the plurality of servers, wherein the second coherent receiver is coupled to the control system, wherein the second coherent receiver is tunable by the control system to select the first band of wavelengths.

11. The optical communication system of claim 9, further comprising: a second coherent receiver of a second server of the plurality of servers, wherein the second coherent receiver is coupled to the control system, wherein the second coherent receiver is tunable by the control system to select a second band of wavelengths.

12. The optical communication system of claim 1, further comprising: a plurality of servers coupled to the top-of-rack switch, wherein each of the plurality of servers receives the one or more bands of wavelengths.

13. An optical communication system, comprising: a hub optical transceiver configured for receiving a spectrum of wavelengths, wherein the spectrum of wavelengths includes a plurality of subcarriers, wherein each of the plurality of subcarriers includes a corresponding and unique band of wavelengths taken from the spectrum of wavelengths; a power splitter coupled to the hub optical transceiver and configured to receive the spectrum of wavelengths, wherein the power splitter is configured to generate a plurality of replicated spectrum of wavelengths; a plurality of top-of-rack switches coupled to the power splitter, each of the plurality of top-of-rack switches configured to receive a corresponding one of the plurality of replicated spectrum of wavelengths; and a control system coupled to the plurality of top-of-rack switches, wherein the control system is configured to tune each of the plurality of top-of-rack switches to select a corresponding band of wavelengths taken from the corresponding one of the plurality of replicated spectrum of wavelengths.

14. The optical communication system of claim 13, wherein each of the plurality of top-of-rack switches includes: a coherent receiver in a network interface coupled to the control system, wherein the coherent receiver is tunable by the control system to select the corresponding band of wavelengths taken from the corresponding one of the plurality of replicated spectrum of wavelengths.

15. The optical communication system of claim 14, wherein the coherent receiver is a hot pluggable device.

16. The optical communication system of claim 13, wherein each of the plurality of replicated spectrum of wavelengths has a corresponding power that is a fraction of a total power recited for the spectrum of wavelengths received from the hub optical transceiver.

17. The optical communication system of claim 13, further comprising: an amplifier coupled between a top-of-rack switch and the power splitter and configured to generate power for a replicated spectrum of wavelengths received by the top-of-rack switch.

18. The optical communication system of claim 13, wherein one or more of the hub optical transceiver and the power splitter and the plurality of top-of-rack switches is a quad small form-factor pluggable (QSFP) device.

19. The optical communication system of claim 13, further comprising: a plurality of servers coupled to a top-of-rack switch configured to receive a band of wavelengths taken from a replicated spectrum of wavelengths, wherein each of the plurality of servers receives the band of wavelengths.
