

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414266
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Wang; Chao et al.

Cooling apparatus and electronic device

Abstract

A cooling apparatus is provided, including a jet plate and a carrier plate provided with an accommodating groove, a coolant inlet, and a coolant outlet. The jet plate is in the accommodating groove, with nozzles provided on the jet plate in a protruding manner. A distribution cavity is between the jet plate and the carrier plate, and the distribution cavity communicates with the coolant inlet, which is for injection of cooling liquid. A collection cavity for backflow of the cooling liquid is formed in the accommodating groove, and is separated from the distribution cavity. The coolant outlet communicates with the collection cavity. The cooling liquid is distributed to the jet plate through the distribution cavity, and is sprayed to the collection cavity through the nozzles for heat exchange, and the cooling liquid obtained through heat exchange is converged in the collection cavity and flows out through the coolant outlet.

Inventors:	Wang; Chao (Dongguan, CN), Sakamoto; Hitoshi (Yokohama, JP)
Applicant:	HUAWEI TECHNOLOGIES CO., LTD. (Guangdong, CN)
Family ID:	81358012
Assignee:	HUAWEI TECHNOLOGIES CO., LTD. (Shenzhen, CN)
Appl. No.:	18/308733
Filed:	April 28, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230269906 A1	Aug. 24, 2023

Foreign Application Priority Data

CN	202011197002.6	Oct. 31, 2020
----	----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/CN2021/123054 20211011 PENDING child-doc US 18308733

Publication Classification

Int. Cl.: H05K7/20 (20060101); H05K1/02 (20060101)

U.S. Cl.:

CPC H05K7/20272 (20130101); H05K1/0203 (20130101); H05K2201/064 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5168348	12/1991	Chu et al.	N/A	N/A
5959351	12/1998	Sasaki et al.	N/A	N/A
6105373	12/1999	Watanabe	62/3.7	F25B 21/02
6650542	12/2002	Chrysler et al.	N/A	N/A
7277283	12/2006	Campbell et al.	N/A	N/A
7362574	12/2007	Campbell et al.	N/A	N/A
7375962	12/2007	Campbell et al.	N/A	N/A
7762314	12/2009	Campbell et al.	N/A	N/A
7802442	12/2009	Bezama et al.	N/A	N/A
7928565	12/2010	Brunschwiler et al.	N/A	N/A
7948757	12/2010	Campbell et al.	N/A	N/A
7992627	12/2010	Bezama et al.	N/A	N/A
8081461	12/2010	Campbell et al.	N/A	N/A
8391008	12/2012	Dede	N/A	N/A
8413712	12/2012	Brunschwiler et al.	N/A	N/A
9131631	12/2014	Joshi	N/A	N/A
9165851	12/2014	Ozaki	N/A	H10D 30/015
9165857	12/2014	Song et al.	N/A	N/A
9247672	12/2015	Mehring	N/A	N/A
9477275	12/2015	Choudhury et al.	N/A	N/A
9484283	12/2015	Joshi et al.	N/A	N/A
9622380	12/2016	Joshi et al.	N/A	N/A
9903664	12/2017	Joshi	N/A	N/A
9943931	12/2017	Li et al.	N/A	N/A
10334755	12/2018	Oprins et al.	N/A	N/A
10651112	12/2019	Malouin, Jr. et al.	N/A	N/A
10665529	12/2019	Smith et al.	N/A	N/A

10903141	12/2020	Malouin, Jr.	N/A	H05K 7/20254
2003/0024689	12/2002	Nakahama et al.	N/A	N/A
2006/0250774	12/2005	Campbell	361/699	H01L 23/4735
2008/0278913	12/2007	Campbell et al.	N/A	N/A
2009/0314467	12/2008	Campbell	165/80.4	H01L 23/4735
2010/0039773	12/2009	Tilton et al.	N/A	N/A
2011/0157827	12/2010	Chao et al.	N/A	N/A
2012/0063091	12/2011	Dede et al.	N/A	N/A
2014/0190668	12/2013	Joshi et al.	N/A	N/A
2015/0043164	12/2014	Joshi	165/185	G06F 1/20
2015/0208555	12/2014	Flotta et al.	N/A	N/A
2017/0098593	12/2016	Eid et al.	N/A	N/A
2017/0196120	12/2016	Oprins et al.	N/A	N/A
2018/0145010	12/2017	Fukuoka et al.	N/A	N/A
2019/0364691	12/2018	Subrahmanyam et al.	N/A	N/A
2020/0126892	12/2019	Mahjoob et al.	N/A	N/A
2020/0328139	12/2019	Chiu	N/A	H01L 25/0657

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1652328	12/2004	CN	N/A
0878852	12/1997	EP	N/A
2151863	12/2009	EP	N/A
2018503057	12/2017	JP	N/A
2020507212	12/2019	JP	N/A
2018004861	12/2017	WO	N/A
2019005107	12/2018	WO	N/A
2019229415	12/2018	WO	N/A

OTHER PUBLICATIONS

Wei Tiwei et al: “Experimental Characterization of a Chip-Level 3-D Printed Microjet Liquid Impingement Cooler for High-Performance Systems”, IEEE Transactions on Components, Packaging and Manufacturing Technology, IEEE, USA, vol. 9, No. 9, Sep. 1, 2019 (Sep. 1, 2019), pp. 1815-1824, XP011750615. cited by applicant

Extended European Search Report dated Mar. 1, 2024, issued for European Application No. 21884913.1 (9 pages). cited by applicant

International Search Report dated Jan. 17, 2022 issued for International Application No. PCT/CN2021/123054 (9 pages). cited by applicant

Primary Examiner: Smith; Courtney L

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of International Application No. PCT/CN2021/123054, filed on Oct. 11, 2021, which claims priority to Chinese Patent Application No. 202011197002.6, filed on Oct. 31, 2020. The disclosures of the aforementioned applications are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

(1) This disclosure relates to the field of electronic device technologies, and in particular, to a cooling apparatus and an electronic device.

BACKGROUND

(2) With improvement of hardware integration in an electronic device, a quantity of chips and components integrated on a circuit board continuously increases. In a running process of the electronic device, the chips and the components may generate a large amount of heat. In addition, power of a high-performance chip on the circuit board continuously increases, and integration of a single cabinet in an equipment room in which the electronic device is placed also continuously improves, causing power density of the single cabinet in the equipment room to continuously increase, and posing higher requirements for cooling of the electronic device in the equipment room. To avoid impact of heat on the chips and the components, an air-cooled heat sink is usually used to synchronously take away the heat on the chips and auxiliary components. Currently, the air-cooled heat sink fails to meet an increasing heat dissipation requirement.

SUMMARY

(3) In view of this, it is necessary to provide a cooling apparatus and an electronic device with a good cooling effect.

(4) A first aspect of embodiments of this disclosure provides a cooling apparatus, including a jet plate and a carrier plate. The carrier plate is provided with an accommodating groove, a coolant inlet, and a coolant outlet. The jet plate is provided in the accommodating groove, and a plurality of nozzles are provided on the jet plate in a protruding manner. A distribution cavity is provided between the jet plate and the carrier plate, and the distribution cavity communicates with the coolant inlet. The coolant inlet is configured to inject cooling liquid. A collection cavity for backflow of the cooling liquid is formed in the accommodating groove, and the collection cavity is separated from the distribution cavity. The coolant outlet communicates with the collection cavity and is used for the cooling liquid to flow out of the collection cavity. The cooling liquid is distributed to the jet plate through the distribution cavity, and is sprayed to the collection cavity through at least one of the nozzles for heat exchange, and the cooling liquid obtained through the heat exchange is converged in the collection cavity and flows out through the coolant outlet.

(5) The cooling apparatus implements, by disposing the distribution cavity between the jet plate and the carrier plate, and disposing the nozzle on the jet plate, a spray of the cooling liquid in the distribution cavity by using the nozzle, and performs heat dissipation on the heater unit through an effect of forced convection heat transfer of the jet. In this way, an effect of the heat exchange is good.

(6) In a possible implementation of the first aspect, the nozzle extends from a side of the jet plate facing away from the carrier plate, the jet plate is provided with a nozzle hole, and the nozzle hole penetrates through the jet plate and the nozzle. Through an extended nozzle and the nozzle hole that is provided in the extended nozzle, the cooling liquid in the distribution cavity is able to form the jet under an action of driving force, and then be sprayed onto a surface of the heater unit.

(7) In a possible implementation of the first aspect, the carrier plate includes a top wall and a peripheral wall, the peripheral wall surrounds the top wall to form the accommodating groove, and the coolant inlet and the coolant outlet are both provided on the top wall.

(8) In a possible implementation of the first aspect, the distribution cavity is disposed on the jet plate.

(9) In a possible implementation of the first aspect, the distribution cavity includes the jet plate and

a side wall that surrounds the jet plate, one end of the side wall is in contact with the jet plate, the other end of the side wall is in contact with the top wall, and the coolant inlet penetrates through an area of the top wall that is surrounded by the side wall.

(10) In a possible implementation of the first aspect, a thickness range of a jet wall is 1 mm to 2 mm.

(11) In a possible implementation of the first aspect, a size of a port of the nozzle located in the distribution cavity is greater than a size of a port located in the collection cavity. Designs of different sizes at the two ends enable the cooling liquid in the distribution cavity to be distributed to the nozzle for ease of jet impingement.

(12) In a possible implementation of the first aspect, the nozzle hole in the nozzle is located in the middle of the nozzle. A centered design of the nozzle hole can facilitate, during metal injection molding (MIM) technology and injection molding technology processing, molding of a protruding nozzle.

(13) In a possible implementation of the first aspect, a length range of the nozzle extending out of the jet plate is 0.5 mm to 2 mm.

(14) In a possible implementation of the first aspect, a hole diameter range of the port of the nozzle located in the collection cavity is 0.2 mm to 1.5 mm.

(15) In a possible implementation of the first aspect, nozzles are uniformly distributed on the jet plate. Uniformly distributed nozzles facilitate uniform distribution of the cooling liquid onto each nozzle.

(16) In a possible implementation of the first aspect, the nozzle holes are provided on some of the nozzles. The nozzle may be provided with the nozzle hole based on different amounts of generated heat, so as to facilitate centralized cooling of a high heat flux area.

(17) In a possible implementation of the first aspect, the jet plate is provided with the nozzles of different sizes, and different quantities of nozzle holes are designed on the nozzles. The nozzle size may be designed based on different amounts of generated heat of the heater unit, so that a large nozzle is provided in the high heat flux area, and a plurality of nozzle holes are provided on the large nozzle, thereby helping reduce a spacing between the nozzle holes and improving a cooling effect of the area.

(18) In a possible implementation of the first aspect, the nozzle is of a cylindrical shape, a prism shape, a circular truncated cone shape, or a frustum shape.

(19) In a possible implementation of the first aspect, there is a gap between adjacent nozzles, and the gap forms a backflow channel for backflow of the sprayed cooling liquid. The design of the backflow channel facilitates outflow of the cooling liquid obtained through jet impingement, and improves the overall efficiency of the cooling apparatus.

(20) In a possible implementation of the first aspect, the gap is provided on the jet plate based on a flow topology design. A shape and a position of the nozzle can be set based on the flow topology design, so as to optimize the backflow channel between nozzles.

(21) In a possible implementation of the first aspect, the nozzle is obtained by machining, injection molding, metal injection molding, and 3D printing. Different processing methods can be used to obtain nozzles that can meet different requirements of jet impingement, so that the methods can be applied to electronic devices with different amounts of generated heat.

(22) In a possible implementation of the first aspect, a material of the nozzle is selected from a metal material or a non-metal material. The material of the nozzle can be selected based on different jet impingement and driving forces, which can prolong service life.

(23) In a possible implementation of the first aspect, the jet plate is fastened to the carrier plate by welding, bonding, and a screw. A plurality of different fastening manners may facilitate different selections based on a size and a requirement of the electronic device.

(24) In a possible implementation of the first aspect, a sealing member is further disposed between the jet plate and the carrier plate. The design of the sealing member can improve a sealing effect.

(25) In a possible implementation of the first aspect, a flow distribution plate is disposed in the distribution cavity, so as to perform flow distribution on the cooling liquid that enters the distribution cavity. In this way, a phenomenon of uneven flow distribution is avoided.

(26) In a possible implementation of the first aspect, the distribution cavity is disposed on the carrier plate. The distribution cavity arranged according to a requirement can facilitate different processing and assembly of the carrier plate and the jet plate.

(27) In a possible implementation of the first aspect, the carrier plate includes a top wall, a peripheral wall, and a side wall, where the coolant inlet and the coolant outlet are respectively provided on the top wall, the peripheral wall extends outward in a circumferential direction of the top wall, the top wall and the peripheral wall enclose the accommodating groove, the side wall extends outward from an interior of the accommodating groove of the top wall to surround the top wall to form the distribution cavity, and the side wall surrounds the coolant inlet; the jet plate includes a jet wall; and the jet wall is provided on the side wall and seals the distribution cavity. It is convenient to manufacture the carrier plate in a unified manner, and to design different jet plates based on a cooling requirement, so as to improve production efficiency, and flexibly design the cooling apparatus.

(28) In a possible implementation of the first aspect, the jet wall is provided on the side wall by using the sealing member. The design of the sealing member can improve the sealing effect.

(29) In a possible implementation of the first aspect, the cooling apparatus further includes a communicating pipe and an isolation plate, one end of the communicating pipe communicates with the coolant inlet, the other end of the communicating pipe communicates with a through hole provided on the isolation plate, the distribution cavity includes the isolation plate, the jet plate, and the side wall that surrounds the jet plate, and the isolation plate, the top wall, and the peripheral wall enclose the collection cavity.

(30) In a possible implementation of the first aspect, the communicating pipe is provided on the top wall by using the sealing member. The design of the sealing member can improve the sealing effect.

(31) In a possible implementation of the first aspect, the communicating pipe is provided on the top wall by welding. Welding connection can improve a sealing connection effect between the communicating pipe and the top wall.

(32) In a possible implementation of the first aspect, an isolation chamber is further disposed on the isolation plate, the isolation chamber is in communication with the communicating pipe, and the distribution cavity is in communication with the isolation chamber. A design of the isolation chamber can increase an amount of contained cooling liquid, thus improving density and uniformity of the jet.

(33) In a possible implementation of the first aspect, the jet plate is provided on the isolation plate by using the sealing member. The design of the sealing member can improve the sealing effect.

(34) In a possible implementation of the first aspect, the isolation plate is integrally formed on the carrier plate, the distribution cavity is disposed on the isolation plate, the jet plate includes the jet wall, and the jet wall is provided on the isolation plate and seals the distribution cavity. An integrated design can be used for manufacturing the carrier plate in the unified manner, and designing different jet plates based on the cooling requirement, so as to improve the production efficiency, and flexibly design the cooling apparatus.

(35) According to a second aspect of this embodiment of this disclosure, an electronic device is provided, including a circuit board, a heater unit, and a cooling apparatus, where the heater unit is provided on the circuit board, the cooling apparatus is the cooling apparatus according to any one of the first aspect and the possible implementations, the carrier plate is provided on the circuit board, the heater unit is provided in the collection cavity, and the jet plate is provided on a surface that is of the carrier plate and that faces the heater unit.

(36) The electronic device has a simple structure and is easy to process. The heater unit is sealed in

the collection cavity. It is only necessary to dispose the nozzle on the jet plate, and to dispose the distribution cavity between the jet plate and the carrier plate, and then jet cooling of the heater unit can be implemented through the nozzle. In this way, processing is convenient, and processing costs are reduced.

(37) In a possible implementation of the second aspect, the carrier plate is provided on the circuit board by using the sealing member. The design of the sealing member can improve the sealing effect.

(38) In a possible implementation of the second aspect, there is a gap between the nozzle and the heater unit, to form a jet chamber in the collection cavity.

(39) In a possible implementation of the second aspect, a distance between the nozzle and the heater unit ranges from 0.2 mm to 1.5 mm.

(40) In a possible implementation of the second aspect, a sputtering layer is provided on the heater unit. The sputtering layer can implement waterproof sealing of the heater unit, thereby improving safety performance.

(41) In a possible implementation of the second aspect, the sputtering layer is formed by sputtering on a surface of the heater unit.

(42) In a possible implementation of the second aspect, the heater unit is further provided with a resin layer. Arrangement of the resin layer can improve a waterproof effect of the heater unit.

(43) In a possible implementation of the second aspect, the cooling apparatus further includes a mounting bracket, where the mounting bracket is disposed on the circuit board and surrounds the heater unit, and the carrier plate is provided on the mounting bracket. The mounting bracket may be a metal reinforcing plate (Stiffener reinforcing rib, Ring, made of stainless steel or copper) of the heater unit (such as a chip) of the electronic device, or may be a mounting bracket provided additionally, so as to be installed according to the requirement.

(44) In a possible implementation of the second aspect, the mounting bracket is provided on the circuit board by using the sealing member, to seal the heater unit in the collection cavity. The design of the sealing member can improve the sealing effect.

(45) In a possible implementation of the second aspect, the carrier plate is provided on the mounting bracket by using the sealing member. A design of the sealing member such as a sealing adhesive or an O-ring can improve the sealing effect.

(46) In a possible implementation of the second aspect, a mounting surface is provided on a side that is of the mounting bracket and that is away from the circuit board, and the carrier plate is provided on the mounting surface. The design of the mounting surface facilitates installation of the cooling apparatus and improves assembly efficiency.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a stereoscopic schematic diagram of a cooling apparatus according to a first embodiment of this disclosure;

(2) FIG. 2 is a three-dimensional exploded view of the cooling apparatus shown in FIG. 1 from another perspective;

(3) FIG. 3 is a schematic cross-sectional diagram of a structure of the cooling apparatus shown in FIG. 1;

(4) FIG. 4 is a schematic cross-sectional diagram of a structure of an electronic device according to a second embodiment of this disclosure;

(5) FIG. 5 is a stereoscopic schematic diagram of a cooling apparatus according to a third embodiment of this disclosure;

(6) FIG. 6 is a stereoscopic schematic exploded diagram of the cooling apparatus shown in FIG. 5;

- (7) FIG. 7 is a schematic cross-sectional diagram of a structure the cooling apparatus shown in FIG. 5;
- (8) FIG. 8 is a stereoscopic schematic diagram of a jet plate of the cooling apparatus shown in FIG. 5;
- (9) FIG. 9 is another stereoscopic schematic diagram of the jet plate of the cooling apparatus shown in FIG. 5;
- (10) FIG. 10 is a schematic diagram of a structure of nozzle distribution of a jet plate;
- (11) FIG. 11 is a second schematic diagram of a structure of nozzle distribution of a jet plate;
- (12) FIG. 12 is a third schematic diagram of a structure of nozzle distribution of a jet plate;
- (13) FIG. 13 is a fourth schematic diagram of a structure of nozzle distribution of a jet plate;
- (14) FIG. 14 is a fifth schematic diagram of a structure of nozzle distribution of a jet plate;
- (15) FIG. 15 is a schematic cross-sectional diagram of a structure of an electronic device according to a fourth embodiment of this disclosure;
- (16) FIG. 16 is a schematic cross-sectional diagram of a structure of an electronic device according to a fifth embodiment of this disclosure; and
- (17) FIG. 17 is a schematic cross-sectional diagram of a structure of an electronic device according to a sixth embodiment of this disclosure.

REFERENCE NUMERALS OF MAIN COMPONENTS

- (18) TABLE-US-00001 Cooling apparatus 100, 300, 400, 600, 800, and 903 Carrier plate 10 Top wall 101 Peripheral wall 102 Coolant inlet 11 Coolant outlet 12 Accommodating groove 13 Jet chamber 131 Liquid inlet pipe 14 Liquid outlet pipe 15 Jet plate 20 Distribution cavity 21 Distribution hole 211 Nozzle 22 Nozzle hole 221 Jet wall 23 Side wall 24 Sealing member 30 Isolation plate 40 Communicating pipe 41 Communicating hole 411 Isolation chamber 42 Electronic device 200, 500, 700, and 900 Circuit board 201 Heater unit 202 Mounting bracket 203 Sputtering layer 204 Resin layer 205 Mounting surface 704
- (19) The present invention is further described with reference to the accompanying drawings in the following specific embodiments.

DESCRIPTION OF EMBODIMENTS

- (20) The following describes technical solutions in embodiments of this disclosure with reference to accompanying drawings in embodiments of this disclosure.
- (21) The following terms “first”, “second”, and the like are merely used for description, and shall not be understood as an indication or implication of relative importance or implicit indication of a quantity of indicated technical features. Therefore, a feature limited by “first” or “second” may explicitly or implicitly include one or more features. In the descriptions of this disclosure, unless otherwise stated, “a plurality of” means two or more than two. Orientation terms such as “up”, “down”, “left”, and “right” are defined relative to an orientation of schematic placement of components in the accompanying drawings. It should be understood that these directional terms are relative concepts and are used for relative description and clarification. These directional terms may vary accordingly depending on an orientation in which the components are placed in the accompanying drawings.
- (22) In this disclosure, unless otherwise explicitly specified and limited, a term “connection” should be understood in a broad sense. For example, the “connection” may be a fastened connection, a detachable connection, or an integrated connection; and may be a direct connection or an indirect connection by using an intermediate medium. The term “and/or” used in this specification includes any and all combinations of one or more related listed items.
- (23) When the following embodiments are described in detail with reference to schematic diagrams, for ease of description, a diagram indicating a partial structure of a component is partially enlarged not based on a general scale. In addition, the schematic diagrams are merely examples, and should not limit the protection scope of this disclosure herein.

Embodiment 1

(24) FIG. 1 to FIG. 3 show a cooling apparatus **100** according to a first embodiment of this disclosure. The cooling apparatus **100** is configured to cool a heater unit, especially a high heat flux density chip or a power device such as a CPU in an electronic device.

(25) The cooling apparatus **100** includes a carrier plate **10** and a jet plate **20**. The jet plate is provided on the carrier plate **10**. The carrier plate **10** is for entry and exit of cooling liquid. The jet plate **20** is configured to form a jet by using the cooling liquid that enters the cooling apparatus **100**, and spray the jet onto the heater unit, so as to cool the heater unit.

(26) A distribution cavity **21** is disposed on a side that is of the jet plate **20** and that is close to the carrier plate **10**. The carrier plate **10** is provided with a coolant inlet **11** and a coolant outlet **12**. The coolant inlet **11** is configured to inject the cooling liquid. The coolant outlet **12** is for outflow of the cooling liquid obtained through jet impingement. The distribution cavity **21** communicates with the coolant inlet **11**. The distribution cavity **21** is configured to accommodate the cooling liquid and distribute the cooling liquid to the jet plate **20**. A plurality of nozzles **22** are provided on the jet plate **20** in a protruding manner. The nozzle **22** is provided on a side that is of the jet plate **20** and that is away from the carrier plate **10**. The nozzle **22** is configured to spray the cooling liquid in the distribution cavity **21** to the heater unit, so as to cool the heater unit.

(27) The carrier plate **10** is provided with an accommodating groove **13**. The jet plate **20** is provided in the accommodating groove **13**. A collection cavity for cooling liquid backflow is formed in the accommodating groove **13**. The collection cavity is separated from the distribution cavity **21**. The coolant outlet **12** communicates with the collection cavity. The coolant outlet **12** is for outflow of the cooling liquid that flows into the collection cavity after being sprayed from the nozzle **22**. The collection cavity can seal the sprayed cooling liquid, to prevent the cooling liquid from flowing out of a remaining part of the carrier plate **10**.

(28) The carrier plate **10** includes a top wall **101** and a peripheral wall **102**. The peripheral wall **102** extends outward perpendicular to the top wall **101** in a circumferential direction of the top wall **101**. The peripheral wall **102** surrounds the top wall **101** to form the accommodating groove **13**. The coolant inlet **11** and the coolant outlet **12** are both provided on the top wall **101**.

(29) The jet plate **20** includes a jet wall **23**. The distribution cavity **21** includes the jet wall **23** and a side wall **24** that surrounds the jet wall **23**. The side wall **24** is perpendicular to the jet wall **23**. The jet wall **23** and the side wall **24** are integrated. One end of the side wall **24** is in contact with the jet plate **20**, and the other end of the side wall **24** is in contact with the top wall **101**. In addition, the coolant inlet **11** penetrates through an area that is of the top wall **101** and that is surrounded by the side wall **24**. The coolant outlet **12** penetrates through an area that is of the top wall **101** and that is not surrounded by the side wall **24**. An area of a region surrounded by the side wall **24** on the top wall **101** is less than an area of the top wall **101**.

(30) A liquid inlet pipe **14** and a liquid outlet pipe **15** are disposed on a side that is of the carrier plate **10** and that is away from the accommodating groove **13**. The coolant inlet **11** communicates with the liquid inlet pipe **14**. The coolant outlet **12** communicates with the liquid outlet pipe **15**. The liquid inlet pipe **14** is configured to communicate with an external cooling liquid delivery pipe. The liquid outlet pipe **15** is configured to communicate with an external cooling liquid recovery pipe.

(31) The nozzle **22** extends from the jet wall **23** to a side away from the carrier plate **10**. The jet wall **23** is provided with a nozzle hole **221**. The nozzle hole **221** penetrates through the jet wall **23** and the nozzle **22**, to connect the distribution cavity **21** and the collection cavity. The nozzle hole **221** is configured to jet, driven by power, the cooling liquid in the distribution cavity **21** onto a surface of the heater unit, so that the surface of the heater unit that is impacted generates a strong heat exchange effect.

(32) There is a gap between two adjacent nozzles **22**, and the gap forms a backflow channel for the cooling liquid to flow back after the jet impingement.

(33) When used, the carrier plate **10** is provided on the electronic device, and the heater unit is

sealed in the collection cavity. The cooling liquid flows into the coolant inlet **11** through the liquid inlet pipe **14**, enters the distribution cavity **21**, and is distributed in the distribution cavity **21** to each nozzle hole **221** located in the jet wall **23**. Then, driven by an external driving force (for example, a pump), the cooling liquid distributed to the nozzle holes **221** is respectively sprayed to the surface of the heater unit through the nozzle hole **221**, so as to be in contact with the surface of the heater unit and impact the surface of the heater unit, generate an effect of forced convection heat transfer with a region that is directly impacted, and absorb heat of the heater unit.

Subsequently, a part of the sprayed cooling liquid is blocked by the surface of the heater unit, and returns in a direction of the jet plate **20**, and flows out of the jet plate **20** from the gap between the nozzles **22** to a periphery of the heater unit, and remaining cooling liquid flows directly from the surface of the heater unit to the periphery of the heater unit. Finally, the cooling liquid flowing around the heater unit is collected, flows into the liquid outlet pipe **15** from the coolant outlet **12**, and is then sent out of the cooling apparatus **100** to complete cooling of the heater unit.

(34) The nozzle **22** of the jet plate **20** is manufactured by using a process such as machining, injection molding, metal injection molding, and 3D printing. A material of the nozzle **22** may be a metal material or a non-metal material.

(35) A thickness range of the jet wall **23** of the jet plate **20** is 1 mm to 2 mm Preferably, thickness of the jet wall **23** is 1.5 mm A length range of the nozzle **22** extending out of the jet wall **23** is 0.5 mm to 2 mm Preferably, an extension length of the nozzle **22** is 1 mm A hole diameter range of the nozzle hole **221** is 0.2 mm to 1.5 mm Preferably, a hole diameter of the nozzle hole **221** is 0.35 mm.

(36) The nozzle **22** may be of a cylindrical shape, a prism shape, a circular truncated cone shape, or a frustum shape. When the nozzle **22** is of the cylindrical shape, a wall thickness range of the nozzle **22** is 0.15 mm to 0.25 mm Preferably, the wall thickness of the nozzle **22** is 0.2 mm. When the nozzle **22** is of a quadrangular prism shape, the wall thickness range of the nozzle **22** is 0.15 mm to 0.35 mm Preferably, the wall thickness of the nozzle **22** is 0.25 mm.

(37) A distribution hole **211** is further formed at an end that is of the nozzle hole **221** and that is close to the distribution cavity **21**. A hole diameter of the distribution hole **211** is greater than a hole diameter of an opening at one end of the nozzle hole **221** that is close to the collection cavity, that is, a size of a port of the nozzle **22** located in the distribution cavity **21** is greater than a size of a port located in the collection cavity. The distribution hole **211** is configured to converge the cooling liquid in the distribution cavity **21** into the nozzle hole **221**, so as to facilitate the jet impingement performed by the nozzle **22**.

(38) In an embodiment, the distribution hole **211** is substantially conical. The distribution hole **211** may also be of a cylindrical shape, a prism shape, a frustum shape, or the like. Preferably, the nozzle hole **221** is located in the middle of the distribution hole **211**. A centered design of the nozzle hole can facilitate, during metal injection molding (MIM) technology and injection molding technology processing, molding of a protruding nozzle.

(39) In an embodiment, the jet plate **20** is fastened on the carrier plate **10** by welding, bonding, screw connection, or the like.

(40) In an embodiment, a sealing member such as a sealing adhesive and a seal ring is further disposed between the jet plate **20** and the carrier plate **10**, so as to prevent the cooling liquid from flowing out between the jet plate **20** and the carrier plate **10**.

(41) In an embodiment, a flow distribution plate (not shown in the figure) may be configured in the distribution cavity **21**, so as to distribute the cooling liquid that enters the distribution cavity **21**, and then the cooling liquid flows into each nozzle **22**, thereby avoiding a phenomenon of uneven flow distribution.

(42) The cooling apparatus **100** has a simple structure. By disposing the distribution cavity **21** on the jet plate **20**, disposing the accommodating groove **13** on the carrier plate **10**, disposing the nozzle **22** with the nozzle hole **221** on the side that is of the jet plate **20** and that is away from the

carrier plate **10**, and using the backflow channel formed by the gap between the nozzles **22**, backflow and outflow of the cooling liquid can be implemented through the collection cavity formed by the accommodating groove **13** and the heater unit. The cooling liquid in the distribution cavity **21** is jetted to the heater unit by using the nozzle **22**. In this way, an effect of forced convection heat transfer is strong, a heat dissipation effect is good, a processing precision requirement is low, installation is simple, and processing is convenient, thereby reducing processing costs.

(43) In a specific implementation of this disclosure, the cooling liquid may be cooling water. Another cooling liquid suitable for the heater unit, especially suitable for the electronic device, such as fluorinert electronic liquid or another liquid coolant, may also be selected.

Embodiment 2

(44) FIG. **4** shows an electronic device **200** according to a second embodiment of this disclosure. The electronic device **200** is provided with a cooling apparatus **300**.

(45) Specifically, the electronic device **200** includes a circuit board **201**, a heater unit **202**, a mounting bracket **203**, and the cooling apparatus **300**. The heater unit **202** is provided on the circuit board **201**. The mounting bracket **203** is provided on the circuit board **201** and surrounds the heater unit **202**. A carrier plate **10** of the cooling apparatus **300** is provided on the mounting bracket **203**. A jet plate **20** of the cooling apparatus **300** is provided on a side of the carrier plate that is close to the heater unit **202**.

(46) The cooling apparatus **300** differs from the cooling apparatus **100** in the first embodiment shown in FIG. **1** mainly in that a distribution cavity **21** is disposed on the carrier plate **10**.

(47) Specifically, the distribution cavity **21** includes a top wall **101** and a side wall **24** that surrounds the top wall **101**. The side wall **24** extends downward perpendicular to the top wall **101** from an interior of the accommodating groove **13** of the top wall **101**. The jet plate **20** is substantially flat-plate shaped and includes a jet wall **23**. The jet wall **23** is provided on the side wall **24** and seals the distribution cavity **21**.

(48) In an embodiment, the side wall **24** is separated from the jet wall **23**, and the side wall **24** is integrated with the carrier plate **10**. The jet wall **23** is provided on the side wall **24** by using a sealing member **30** such as a sealing adhesive and an O-ring, to seal the distribution cavity **21**.

(49) In an embodiment, a nozzle **22** of the jet wall **23** is opposite to the heater unit **202**.

(50) There is a gap between the nozzle **22** and the heater unit **202**, to form a jet chamber **131** for jetting in the collection cavity formed by the accommodating groove **13**. The jet chamber **131** is configured to emit the cooling liquid sprayed in the nozzle hole **221** to the heater unit **202** for heat exchange, so as to take away heat on the heater unit **202**.

(51) Specifically, a distance between the nozzle **22** and the heater unit, that is, a thickness (a jet height (Height) or a jet gap (gap)) of the jet chamber **131** ranges from 0.2 mm to 1.5 mm. Preferably, the distance is 0.5 mm.

(52) In an embodiment, the heater unit **202** may be a high heat flux density chip or a power device such as a CPU. The circuit board **201** is a substrate of the power device such as a chip.

(53) In an embodiment, the heater unit **202** is welded to the circuit board **201** by using a solder and is electrically connected to the circuit board **201**.

(54) In an embodiment, a surface of the heater unit **202** may be further processed by using a sputtering metal or another material (such as SiN) process to form a sputtering layer **204**. The sputtering layer **204** may implement sealing of the heater unit **202**, thereby achieving a waterproof effect.

(55) In an embodiment, a periphery of the heater unit **202** may be filled with or coated with epoxy resin to form a resin layer **205** between the heater unit **202** and the mounting bracket **203**, thereby improving the waterproof effect of the heater unit **202**.

(56) The mounting bracket **203** may be a metal reinforcing plate (Stiffener reinforcing rib, Ring, made of stainless steel or copper) of the heater unit (such as a chip) of the electronic device **200**. In

an embodiment, the mounting bracket **203** may also be a frame that is additionally disposed and configured to install the cooling apparatus.

(57) In an embodiment, the mounting bracket **203** may be sealed on the circuit board **201** on which the heater unit **202** is installed by using the sealing member **30** such as the sealing adhesive and the O-ring, so as to cooperate with the peripheral wall **102** to seal the heater unit **202** in the collection cavity.

(58) In an embodiment, the peripheral wall **102** is provided on the mounting bracket **203** by using the sealing member **30** such as the sealing adhesive and the O-ring.

(59) The electronic device **200** has a simple structure, and the carrier plate **10** is integrally formed, which facilitates processing. It is only necessary to dispose the nozzle **22** with the nozzle hole **221** on the jet plate **20**, and to seal the heater unit **202** in the collection cavity by using the sealing member **30**, and then the jet cooling of the heater unit **202** can be implemented through the nozzle **22**, which facilitates processing and reduces the processing costs.

Embodiment 3

(60) FIG. 5 to FIG. 7 show a cooling apparatus **400** according to a third embodiment of this disclosure.

(61) The cooling apparatus **400** differs from the cooling apparatus **100** in the first embodiment shown in FIG. 1 mainly in that the cooling apparatus **400** further includes an isolation plate **40**. The isolation plate **40** is provided in an accommodating groove **13** and is located on a side of a distribution cavity **21** that is close to a top wall **101**. The isolation plate **40**, a jet plate **20**, and a side wall **24** enclose the distribution cavity **21**. The isolation plate **40**, the top wall **101**, and a peripheral wall **102** enclose a collection cavity. The isolation plate **40** separates the distribution cavity **21** from the top wall **101**, so that a coolant outlet **12** and a liquid outlet pipe **15** can be flexibly provided on the top wall **101**.

(62) Specifically, the cooling apparatus **400** further includes a communicating pipe **41**. The communicating pipe **41** is provided with a communicating hole **411**, one end of the communicating pipe **41** communicates with a coolant inlet **11**, and the other end of the communicating pipe **41** communicates with a through hole provided on the isolation plate **40**.

(63) In an embodiment, the isolation plate **40** is further provided with an isolation chamber **42**. The isolation chamber **42** communicates with the communicating hole **411**. The jet plate **20** is provided on the isolation plate **40**, and the distribution cavity **21** communicates with the isolation chamber **42**.

(64) In an embodiment, the communicating pipe **41** is disposed on a carrier plate **10** by using a screw, and the communicating pipe **41** is sealed with the top wall **101** by using the sealing member **30**. The communicating pipe **41** may further be disposed on the top wall **101** by welding, so as to implement connection and sealing between the communicating pipe **41** and the carrier plate **10**.

(65) In an embodiment, the jet plate **20** is provided on the isolation plate **40** by using a screw and is sealed with the isolation plate **40** by using the sealing member **30**.

(66) In an embodiment, the carrier plate **10** is provided on the electronic device by using the sealing member **30**.

(67) The cooling apparatus **400** has a simple structure. One isolation plate **40** is added to the accommodating groove **13** to separate the distribution cavity **21** from the top wall **101**, so that the coolant outlet **12** and the liquid outlet pipe **15** may be disposed at any position on the top wall **101** of the carrier plate **10**, which facilitates flexible design of the liquid outlet pipe **15**, and can improve a problem of uneven flow caused by a shift of an outlet position of the cooling liquid.

(68) In an embodiment, as shown in FIG. 8, the nozzles **22** may be evenly distributed on a jet wall **23**, and each of the nozzles **22** is provided with the nozzle hole **221**. As shown in FIG. 9, some of the nozzles **22** may be further provided with the nozzle hole **221**, or after all of the nozzles **22** are provided with the nozzle hole **221**, some of nozzle holes **221** are sealed by using a filler such as the sealing adhesive, so that a position of the nozzle hole **221** on the jet wall **23** is flexibly disposed.

Therefore, the position of the nozzle hole **221** may be selectively disposed on the jet plate **20** based on different amounts of generated heat of the heater unit.

(69) In an embodiment, as shown in FIG. **10** and FIG. **11**, the nozzle **22** may be of a cylindrical shape, a prism shape, a circular truncated cone shape, a frustum shape, or the like that is evenly distributed. In this case, preferably, the nozzle hole **221** is provided in the middle of the nozzle **22**. The nozzles **22** of different shapes may also be provided on the jet wall **23** in a mixed manner.

(70) In an embodiment, as shown in FIG. **12**, a gap between the nozzles **22** may be further set to be of a strip shape, a wave shape, or the like based on a flow topology design. In this case, a plurality of nozzle holes **221** may be provided on one of the nozzles **22** according to a requirement.

(71) In an embodiment, as shown in FIG. **13**, a position of the nozzle **22** may be further designed based on the amount of generated heat of the heater unit. For example, when the heater unit is the chip, different quantities of nozzle holes **221** may be designed based on distribution (power map) of a power region of the chip. In this case, the nozzle holes **221** may be provided on each of the nozzles **22**.

(72) In an embodiment, as shown in FIG. **14**, the nozzle **22** may be further designed based on the amount of generated heat of the heater unit. For example, the nozzles **22** of different sizes may be designed based on the distribution of the power region of the chip. In this case, the different quantities of nozzle holes **221** may be designed on different nozzles **22**. In this case, because the plurality of nozzle holes **221** are provided on one nozzle **22**, a spacing between the nozzle holes **221** may be set to be smaller, so that more nozzle holes **221** may be distributed in a high power density region, thereby performing strong cooling on the high power density region.

(73) The nozzle **22** and the nozzle hole **221** are flexibly designed to meet heat dissipation requirements of different heater units, thereby improving cooling efficiency of the cooling liquid.

Embodiment 4

(74) FIG. **15** shows an electronic device **500** according to a fourth embodiment of this disclosure. The electronic device **500** is provided with a cooling apparatus **600**.

(75) The cooling apparatus **600** differs from the cooling apparatus **400** in the third embodiment shown in FIG. **5** mainly in that an isolation plate **40** and a communicating pipe **41** are integrated with a carrier plate **10**. A distribution cavity **21** is disposed on the isolation plate **40**.

(76) Specifically, the distribution cavity **21** includes the isolation plate **40** and a side wall **24** that surrounds the isolation plate **40**. A jet plate **20** includes a jet wall **23**. The jet wall **23** is provided on the side wall **24** and seals the distribution cavity **21**.

(77) The electronic device **500** may flexibly design a position of a liquid outlet pipe **15** by using an integrally designed carrier plate **10**, and may further select different jet plates **20** based on different heater units **202**.

Embodiment 5

(78) FIG. **16** shows an electronic device **700** according to a fifth embodiment of this disclosure. The electronic device **700** includes a circuit board **201**, a heater unit **202**, a mounting bracket **203**, and a cooling apparatus **800** disposed on the mounting bracket **203**.

(79) The electronic device **700** differs from the electronic device **200** in the second embodiment shown in FIG. **4** mainly in that a carrier plate **10** of the cooling apparatus **800** omits a peripheral wall **102**. A top wall **101** is directly provided on the mounting bracket **203**. The mounting bracket **203**, the circuit board **201**, and the top wall **101** enclose an accommodating groove **13**.

(80) Specifically, the mounting bracket **203** is relatively thick in a direction away from the circuit board **201**, and a mounting surface **704** is provided on a side that is of the mounting bracket **203** and that is away from the circuit board **201**. The top wall **101** is provided on the mounting surface **704**. In an embodiment, the mounting surface **704** is a groove formed by recessing the mounting bracket **203** in a direction in which top of the mounting bracket **203** faces the circuit board.

(81) In an embodiment, the carrier plate **10** may be fastened on the mounting bracket **203** by using a fastening member such as a screw. A sealing member such as a sealing adhesive and a seal ring is

further disposed between the mounting bracket **203** and the carrier plate **10** for sealing.

(82) In an embodiment, a wall surface of the mounting bracket **203** is also relatively thick, thereby allowing the carrier plate **10** to be fastened by using the screw or the like, and be sealed by using the seal ring or the like.

(83) In the electronic device **700**, by changing a structure of the mounting bracket **203**, the mounting bracket **203** is provided higher, thereby simplifying design of the carrier plate **10**. The carrier plate **10** may be conveniently provided on the top of the mounting bracket **203** by using the fastening member such as the screw. In addition, the carrier plate **10** is not provided with the peripheral wall **102**, and the jet plate **20** may protrude from the carrier plate **10**, thereby facilitating subsequent installation and replacement.

Embodiment 6

(84) FIG. **17** shows an electronic device **900** according to a sixth embodiment of this disclosure. The electronic device **900** includes a circuit board **201**, a heater unit **202**, and a cooling apparatus **903** disposed on the circuit board **201**.

(85) The electronic device **900** differs from an electronic device **200** in the second embodiment shown in FIG. **4** mainly in that there is no mounting bracket on the electronic device **900**, and a carrier plate **10** of the cooling apparatus **903** is directly provided on the circuit board **201**.

(86) Specifically, a peripheral wall **102** of the carrier plate **10** of the cooling apparatus **903** extends for a long distance in a direction away from a top wall **101**, and a side of the peripheral wall **102** that is away from the top wall **101** is provided on the circuit board **201**.

(87) The peripheral wall **102** of the carrier plate **10** is also thicker than the peripheral wall **102** of the carrier plate **10** in the Embodiment 3, so as to provide enough strength to implement a function of the mounting bracket.

(88) In an embodiment, a sealing member **30** such as a sealing adhesive and a seal ring is further disposed between the circuit board **201** and the peripheral wall **102** of the carrier plate **10** for sealing.

(89) The cooling apparatus **903** has a simple structure, and is easy to process and convenient to install. The electronic device **900** does not need the mounting bracket, and may be directly disposed on the circuit board **201** by using the carrier plate **10** of the cooling apparatus **903**, which can reduce the processing costs and improve heat dissipation efficiency.

(90) It may be understood that a distribution cavity **21** may be disposed on the carrier plate **10**, a jet plate **20**, or an isolation plate **40** according to a requirement. Alternatively, the distribution cavity **21** may be formed by using the carrier plate **10** and the jet plate **20**, or may be formed by using the isolation plate **40** and the jet plate **20**.

(91) It may be understood that the jet plate **20** in the cooling apparatus of this disclosure may further perform cooling on a plurality of heater units, provided that a plurality of heater units are sealed in a same collection cavity at the same time, and a nozzle **22** on the jet plate **20** corresponds to a corresponding heater unit.

(92) The foregoing description is merely specific implementations of this disclosure, but is not intended to limit the protection scope of this disclosure. Any variation or replacement within the technical scope disclosed in this disclosure shall fall within the disclosed scope of this disclosure.

Claims

1. A cooling apparatus comprising: a jet plate, and a carrier plate provided with an accommodating groove, a coolant inlet, and a coolant outlet; wherein: the jet plate is provided in the accommodating groove; a plurality of nozzles are provided on the jet plate; a distribution cavity is provided between the jet plate and the carrier plate, and the distribution cavity is configured to communicate with the coolant inlet; the coolant inlet is configured to inject cooling liquid; a collection cavity for backflow of the cooling liquid is formed in the accommodating groove, and

the collection cavity is separated from the distribution cavity; the coolant outlet is configured to communicate with the collection cavity and is configured for the cooling liquid to flow out of the collection cavity; the cooling liquid is configured to be distributed to the jet plate through the distribution cavity, and sprayed to the collection cavity through at least one of the nozzles for heat exchange, and the cooling liquid obtained through the heat exchange is configured to be converged in the collection cavity and to flow out through the coolant outlet, and at least two of the nozzles provided on the jet plate are different sizes, and the at two of the nozzles have different quantities of nozzle holes.

2. The cooling apparatus according to claim 1, wherein the carrier plate comprises a top wall and a peripheral wall, the peripheral wall surrounds the top wall to form the accommodating groove, and the coolant inlet and the coolant outlet are both provided on the top wall.

3. The cooling apparatus according to claim 2, wherein the distribution cavity is formed at least by the jet plate and a side wall that surrounds the jet plate, one end of the side wall is in contact with the jet plate, the other end of the side wall is in contact with the top wall, and the coolant inlet penetrates through a region that is of the top wall and that is surrounded by the side wall.

4. The cooling apparatus according to claim 1, wherein a size of a port of at least one of the nozzles located in the distribution cavity is greater than a size of a port located in the collection cavity.

5. The cooling apparatus according to claim 1, wherein there is a gap between two adjacent nozzles, and the gap forms a backflow channel for backflow of the sprayed cooling liquid.

6. The cooling apparatus according to claim 5, wherein the gap is provided on the jet plate and has a strip shape or a wave shape.

7. The cooling apparatus according to claim 1, wherein the distribution cavity is provided with a flow distribution plate to perform flow distribution on the cooling liquid entering the distribution cavity.

8. The cooling apparatus according to claim 2, wherein the cooling apparatus further comprises a communicating pipe and an isolation plate, one end of the communicating pipe is configured to communicate with the coolant inlet, the other end of the communicating pipe is configured to communicate with a through hole provided on the isolation plate, the distribution cavity is formed at least by the isolation plate, the jet plate, and the side wall that surrounds the jet plate, and the isolation plate, the top wall, and the peripheral wall enclose the collection cavity.

9. An electronic device comprising: a circuit board; a heater unit provided on the circuit board; and a cooling apparatus comprising: a jet plate, and a carrier plate provided with an accommodating groove, a coolant inlet, and a coolant outlet; wherein: the jet plate is provided in the accommodating groove; a plurality of nozzles are provided on the jet plate; a distribution cavity is provided between the jet plate and the carrier plate, and the distribution cavity is configured to communicate with the coolant inlet; the coolant inlet is configured to inject cooling liquid; a collection cavity for backflow of the cooling liquid is formed in the accommodating groove, and the collection cavity is separated from the distribution cavity; the coolant outlet is configured to communicate with the collection cavity and is configured for the cooling liquid to flow out of the collection cavity; and the cooling liquid is configured to be distributed to the jet plate through the distribution cavity, and sprayed to the collection cavity through at least one of the nozzles for heat exchange, and the cooling liquid obtained through the heat exchange is configured to be converged in the collection cavity and to flow out through the coolant outlet; and wherein the carrier plate is provided on the circuit board, the heater unit is provided in the collection cavity, and the jet plate is provided on a surface of the carrier plate facing the heater unit; and wherein at least two of the nozzles provided on the jet plate are different sizes, and the at two of the nozzles have different quantities of nozzle holes.

10. The electronic device according to claim 9, wherein the carrier plate comprises a top wall and a peripheral wall, the peripheral wall surrounds the top wall to form the accommodating groove, and the coolant inlet and the coolant outlet are both provided on the top wall.

11. The electronic device according to claim 10, wherein the distribution cavity is formed at least by the jet plate and a side wall that surrounds the jet plate, one end of the side wall is in contact with the jet plate, the other end of the side wall is in contact with the top wall, and the coolant inlet penetrates through a region that is of the top wall and that is surrounded by the side wall.
 12. The electronic device according to claim 9, wherein a size of a port of at least one of the nozzles located in the distribution cavity is greater than a size of a port located in the collection cavity.
 13. The electronic device according to claim 9, wherein there is a gap between two adjacent nozzles, and the gap forms a backflow channel for backflow of the sprayed cooling liquid.
 14. The electronic device according to claim 13, wherein the gap is provided on the jet plate and has a strip shape or a wave shape.
 15. The electronic device according to claim 9, wherein the distribution cavity is provided with a flow distribution plate to perform flow distribution on the cooling liquid entering the distribution cavity.
 16. The electronic device according to claim 10, wherein the cooling apparatus further comprises a communicating pipe and an isolation plate, one end of the communicating pipe is configured to communicate with the coolant inlet, the other end of the communicating pipe is configured to communicate with a through hole provided on the isolation plate, the distribution cavity is formed at least by the isolation plate, the jet plate, and the side wall that surrounds the jet plate, and the isolation plate, the top wall, and the peripheral wall enclose the collection cavity.
 17. The electronic device according to claim 9, wherein there is a gap between the nozzle and the heater unit, to form a jet chamber in the collection cavity.
 18. The electronic device according to claim 9, wherein a sputtering layer is provided on the heater unit.
 19. A cooling apparatus comprising: a jet plate, and a carrier plate provided with an accommodating groove, a coolant inlet, and a coolant outlet; wherein: the jet plate is provided in the accommodating groove; a plurality of nozzles are provided on the jet plate; a distribution cavity is provided between the jet plate and the carrier plate, and the distribution cavity is configured to communicate with the coolant inlet; the coolant inlet is configured to inject cooling liquid; a collection cavity for backflow of the cooling liquid is formed in the accommodating groove, and the collection cavity is separated from the distribution cavity; the coolant outlet is configured to communicate with the collection cavity and is configured for the cooling liquid to flow out of the collection cavity; the cooling liquid is configured to be distributed to the jet plate through the distribution cavity, and sprayed to the collection cavity through at least one of the nozzles for heat exchange, and the cooling liquid obtained through the heat exchange is configured to be converged in the collection cavity and to flow out through the coolant outlet; and a size of a port of at least one of the nozzles located in the distribution cavity is greater than a size of a port located in the collection cavity.
 20. The cooling apparatus according to claim 1, wherein: a spacing between the nozzle holes on one of the nozzles is different from a spacing between the nozzle holes on another one of the nozzles.
-