

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404052
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Barker; Mark E. et al.

Self-aligning liquid coupler systems and related methods

Abstract

Methods, apparatus, systems and articles of manufacture are disclosed for a first link to rotate about a pin joint, a second link rotatably coupled to the first link, the second link having a nozzle at a first end and a weight at a second end opposite the first end, and a fluid inlet including a funnel portion and an opening, the funnel portion having a conical taper converging towards the opening.

Inventors:	Barker; Mark E. (Johnston, IA), Wagher; Nikhil V. (Champaign, IL)
Applicant:	Deere & Company (Moline, IL)
Family ID:	72432763
Assignee:	Deere & Company (Moline, IL)
Appl. No.:	18/153867
Filed:	January 12, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230166840 A1	Jun. 01, 2023

Related U.S. Application Data

division parent-doc US 16888440 20200529 US 11618563 child-doc US 18153867
us-provisional-application US 62897376 20190908

Publication Classification

Int. Cl.: **B64C39/02** (20230101); **B64D1/18** (20060101); **B64D1/22** (20060101); **B64F1/28** (20060101); **B64U70/99** (20230101); **B67D7/02** (20100101); **B67D7/30** (20100101); **B67D7/40** (20100101); B64U10/14 (20230101); B64U101/45 (20230101)

U.S. Cl.:

CPC **B64U70/99** (20230101); **B64D1/18** (20130101); **B64D1/22** (20130101); **B64F1/28** (20130101); **B67D7/0294** (20130101); **B67D7/302** (20130101); **B67D7/406** (20130101); B64U10/14 (20230101); B64U2101/45 (20230101)

Field of Classification Search

CPC: B64U (70/99); B64U (10/14); B64U (2101/45); B64D (1/18); B64D (1/22); B64F (1/28); B67D (7/0294); B67D (7/302); B67D (7/406)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3095020	12/1962	Darwin	N/A	N/A
3581769	12/1970	Haley et al.	N/A	N/A
3651832	12/1971	Meyer	N/A	N/A
3805834	12/1973	Bily	141/387	B67D 9/02
4142551	12/1978	Wilms	212/308	B67D 9/02
4341242	12/1981	Hermanson	N/A	N/A
4416306	12/1982	Le Devehat	141/387	B67D 9/02
4418718	12/1982	Fusy	141/387	B67D 9/02
5906336	12/1998	Eckstein	N/A	N/A
7837151	12/2009	Garcia, Jr.	N/A	N/A
8006850	12/2010	Rotheisler	212/196	B66C 23/14
9139310	12/2014	Wang	N/A	N/A
9403669	12/2015	Fusy	N/A	B67D 9/02
9783075	12/2016	Henry et al.	N/A	N/A
10941032	12/2020	Waguespack	N/A	B63B 27/24
11618563	12/2022	Barker et al.	N/A	N/A
2006/0011242	12/2005	Meyerinck	N/A	N/A
2019/0211947	12/2018	Butcher	N/A	N/A
2020/0207483	12/2019	Meidad	N/A	N/A
2021/0147095	12/2020	Meidad	N/A	N/A
2021/0202959	12/2020	Sheerin	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108128747	12/2017	CN	N/A
207535770	12/2017	CN	N/A
109018413	12/2017	CN	N/A
0418744	12/1990	EP	N/A
20120140626	12/2011	KR	N/A
2017138803	12/2016	WO	N/A

OTHER PUBLICATIONS

European Patent Office, "European Search Report," issued in connection with European Appl. No. 20195117.5, dated Feb. 3, 2021, 10 pages. cited by applicant

United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with

Primary Examiner: Long; Donnell A

Attorney, Agent or Firm: Hanley, Flight & Zimmerman, LLC

Background/Summary

RELATED APPLICATIONS (1) This patent arises from a divisional of U.S. patent application Ser. No. 16/888,440 (now U.S. Pat. No. 11,618,563), which was filed on May 29, 2020, and claims the benefit of U.S. Provisional Patent Application No. 62/897,376, which was filed on Sep. 8, 2019. U.S. patent application Ser. No. 16/888,440 and U.S. Provisional Patent Application No. 62/897,376 are hereby incorporated herein by reference in their entireties. Priority to U.S. patent application Ser. No. 16/888,440 and U.S. Provisional Patent Application No. 62/897,376 is hereby claimed.

FIELD OF THE DISCLOSURE

(1) This disclosure relates generally to fluid exchange, and, more particularly, to self-aligning liquid coupler systems and related methods.

BACKGROUND

(2) Aerial vehicles are used in agriculture for the aerial application of, for example, fluid fertilizer and/or pesticides (e.g., herbicides, insecticides, etc.) onto crops. In recent years, unmanned aerial vehicles (UAVs) and have increasingly been used to distribute fluid fertilizer and/or pesticides. Some UAVs such as quadrotor helicopters (e.g., quadcopters) used in agriculture operate largely autonomously. These autonomous UAVs are often much smaller than their manned and/or non-autonomous counterparts (e.g., manned aerial vehicles, non-autonomous UAVs) in part due to the extensive cost and regulation associated with autonomous UAVs. These autonomous UAVs typically have much smaller fluid payloads compared to manned aerial vehicles and thus require refilling of their fluid stores (e.g. of fluid fertilizer or pesticide) and/or fuel stores at relatively shorter intervals.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a perspective view of example base components of an example self-aligning liquid coupler system that can be implemented in connection with the teachings of this disclosure.
- (2) FIG. 2 is a top view of the example base components of FIG. 1.
- (3) FIG. 3 is a perspective view of an example rotorcraft containing example vehicle components of the self-aligning liquid coupler system that can be implemented in connection with the base components of FIG. 1.
- (4) FIG. 4A is a top view of the example base components of FIG. 1 coupled to the example vehicle components of the example rotorcraft of FIG. 3.
- (5) FIG. 4B is a top view of the example base components of FIG. 1 not coupled to the example vehicle components of the example rotorcraft of FIG. 3.
- (6) FIG. 5 is a perspective enlarged view including a partial cross section of the example base components of FIG. 1 and the example vehicle components of FIG. 3 including an example nozzle

assembly and an example fluid inlet.

(7) FIG. 6 is another perspective enlarged view of the example nozzle assembly and the example fluid inlet of FIG. 3.

(8) FIG. 7 is a back view and partial cross section of the example base components of FIG. 1.

(9) FIG. 8 is a back view of an example first link of FIG. 7.

(10) FIG. 9 is a back view of an example second link of FIG. 7.

(11) FIG. 10 is an enlarged partial cross section of the base components of FIG. 1 and the vehicle components of FIG. 3 including the nozzle assembly.

(12) FIG. 11 is a block diagram of an example fluid dispenser controller to actuate the self-aligning liquid coupler system of FIGS. 1-10.

(13) FIG. 12 is a flowchart representative of machine readable instructions which may be executed to implement the fluid dispenser controller of FIG. 11 to actuate the self-aligning liquid coupler system of FIGS. 1-10.

(14) FIG. 13 is a block diagram of an example processing platform structured to execute the instructions of FIG. 12 to implement the example fluid dispenser controller of FIG. 11.

DETAILED DESCRIPTION

(15) The figures are not to scale. In general, the same reference numbers will be used throughout the drawing(s) and accompanying written description to refer to the same or like parts. As used in this patent, stating that any part (e.g., a layer, film, area, region, or plate) is in any way on (e.g., positioned on, located on, disposed on, or formed on, etc.) another part, indicates that the referenced part is either in contact with the other part, or that the referenced part is above the other part with one or more intermediate part(s) located therebetween. Connection references (e.g., attached, coupled, connected, and joined) are to be construed broadly and may include intermediate members between a collection of elements and relative movement between elements unless otherwise indicated. As such, connection references do not necessarily infer that two elements are directly connected and in fixed relation to each other. Stating that any part is in “contact” with another part means that there is no intermediate part between the two parts. Although the figures show layers and regions with clean lines and boundaries, some or all of these lines and/or boundaries may be idealized. In reality, the boundaries and/or lines may be unobservable, blended, and/or irregular.

(16) Descriptors “first,” “second,” “third,” etc. are used herein when identifying multiple elements or components which may be referred to separately. Unless otherwise specified or understood based on their context of use, such descriptors are not intended to impute any meaning of priority, physical order or arrangement in a list, or ordering in time but are merely used as labels for referring to multiple elements or components separately for ease of understanding the disclosed examples. In some examples, the descriptor “first” may be used to refer to an element in the detailed description, while the same element may be referred to in a claim with a different descriptor such as “second” or “third.” In such instances, it should be understood that such descriptors are used merely for ease of referencing multiple elements or components.

(17) Aerial vehicles may be used in the aerial application of fluid fertilizer and/or pesticides (e.g., herbicides, insecticides, etc.) onto crops. While fixed-wing aircraft have been used to distribute fluid pesticides, in recent years, rotorcraft have increasingly been used in place of fixed-wing aircraft because of rotorcraft's increased maneuverability compared to fixed-wing aircraft in aerial application. For example, rotorcraft allow aerial application of materials in geographic locations (e.g., fields, farms) that are small in size and/or contain, for example, aerial obstacles such as wind turbines and/or severely unlevel land.

(18) Unmanned aerial vehicles (UAVs) are increasingly being considered for use in aerial application. Many of the UAV's used in aerial application across the world are remotely controlled by an operator. Thus, in these instances, though the operator can conduct the aerial application remotely from a position of relative safety and comfort, the constant attention of a human is

required throughout the scope of aerial application. Some UAVs such as quadrotor rotorcraft (e.g., quadcopters) used in agriculture operate largely autonomously. These autonomous UAVs are often much smaller than their manned and/or non-autonomous counterparts (e.g., manned aerial vehicles, non-autonomous UAVs) in part due to the extensive cost and regulation associated with autonomous UAVs.

(19) Autonomous UAVs typically have much smaller fluid payloads compared to manned aerial vehicles and thus require refilling of their fluid stores (e.g. of fluid fertilizer or pesticide) and/or fuel stores at relatively shorter intervals. Additionally, a human is required to refill the fluid stores and/or fuel stores of agricultural autonomous UAVs. This is especially inconvenient and cumbersome as a human is not required for the autonomous aerial application.

(20) Disclosed herein are self-aligning liquid coupler systems to couple with, and subsequently refill or refuel autonomous UAVs. Some self-aligning liquid coupler systems disclosed herein include self-aligning liquid dispensing features (e.g., base components) of a coupler system along with vehicle components of a coupler system to create a closed fluid connection to transmit fluid to a vehicle. Though the examples disclosed herein are particularly advantageous to autonomous UAVs, these examples are also useful to non-autonomous UAVs or manned aerial vehicles. For example, the examples disclosed herein may allow the operator of a manned aerial vehicle to refuel without leaving a cockpit. For example, the examples disclosed herein may allow a remote operator of a non-autonomous UAV to operate the UAV from a considerable geographic distance from the UAV as manual refilling of liquid or fuel stores is not necessary. Additionally, the examples disclosed herein could be useful to any vehicle or apparatus that requires fluid transmission.

(21) With regards to autonomous and non-autonomous UAVs, the precision in landing location is not sufficient for aligning components for fluid distribution simply by extending the components towards a UAV. The examples disclosed herein describe self-aligning liquid coupler systems that may account for deviations in the position of a UAV from an expected position in three dimensions and thus further ease fluid distribution processes.

(22) FIG. 1 is a perspective view of example base components **100** of an example self-aligning liquid coupler system that can be implemented in connection with the teachings of this disclosure. The example base components **100** include an example actuating arm **102**, an example nozzle assembly **104**, an example pump **106**, an example fluid reservoir **108**, and an example fluid dispenser controller **110**. The actuating arm **102** can be actuated to translate the nozzle assembly **104** towards and away from an example vehicle (e.g., an autonomous UAV) containing corresponding (e.g., reciprocal) vehicle components of the self-aligning liquid coupler system. The pump **106** can be actuated to pump fluid from the example fluid reservoir **108** towards the example nozzle assembly **104**. In some examples, the fluid dispenser controller **110** implements machine-readable instructions to, based on sensor readings, actuate the pump **106** and the actuating arm **102** to translate the nozzle assembly **104** towards a vehicle such as a quadrotor helicopter, also referred to herein as a quadcopter.

(23) In the illustrated example of FIG. 1, the actuating arm **102** includes a support structure **112** that is rigidly fixed in place. In some examples, the support structure **112** extends to the ground or is rigidly coupled to further structural components extending to the ground (e.g., a table, a platform, a quadcopter storage structure, etc.). For example, the support structure **112** may move slightly due to geological movement, wind, the landing of a vehicle, etc. In the illustrated example of FIG. 1, the support structure **112** is rigidly coupled to a stationary member **114**. For example, the stationary member **114** can move slightly due to geological movement, wind, the landing of a vehicle, etc. In this example, the stationary member **114** has an aperture **116** extending therethrough. In this example, the actuating arm **102** also includes an example first arm member **118** and an example second arm member **120**. In some examples, the first arm member **118** and the second arm member **120** have substantially the same length and substantially the same geometrical and dimensional properties. As used herein, “substantially the same” means the same or almost the same due to, for

example, manufacturing tolerances.

(24) In the illustrated example of FIG. 1, the first arm member **118** is rotatably coupled to the support structure **112** via a first pin joint **122** (e.g., a revolute joint, a pinned connection, etc.) with the stationary member **114**, restricting the first arm member **118** to one degree of freedom. In FIG. 1, the stationary member **114** is substantially perpendicular to the support structure **112**. In FIG. 1, the second arm member **120** is rotatably coupled to the support structure **112** via a second pin joint **124** with the stationary member **114**. In FIG. 1, the first pin joint **122** contains a pin **126** to be received by a first bore of the first arm member **118**. In FIG. 1, the first arm member **118** is suspended apart from the support structure **112** by a first spacer **128** and a second spacer **130** disposed respectively vertically above and below the first arm member **118** within the aperture **116**. In the illustrated example of FIG. 1, the second pin joint **124** has substantially the same components as the first pin joint **122**. In the example of FIG. 1, the support structure **112** is a vertical structure and the first arm member **118** and the second arm member **120** are substantially perpendicular to the support structure **112**. As such, the first arm member **118** and the second arm member **120** rotate in a plane that is substantially parallel to the ground. As used herein, “substantially parallel” means parallel or within 20° of parallel. As used herein, “substantially perpendicular” means perpendicular or within 20° of perpendicular.

(25) FIG. 2 is a top view of the example base components **100** of FIG. 1. The example actuating arm **102** also includes a translating member **200** (e.g., a structure) coupled to the first arm member **118** (FIG. 1) via an example third pin joint **202** and coupled to the second arm member **120** (FIG. 1) via a fourth pin joint **204**. In the example of FIG. 2, the third pin joint **202** and the fourth pin joint **204** are substantially the same as the first pin joint **122** and the second pin joint **124** (both of FIG. 1). In the example of FIG. 2, the first pin joint **122** and the second pin joint **124** are spaced apart at substantially the same distance as the third pin joint **202** and the fourth pin joint **204** are spaced apart. The stationary member **114** (FIG. 1), the first arm member **118**, the second arm member **120**, and the translating member **200** together form a parallelogram linkage (e.g., a four-bar linkage with two sets of two equal length members). In this configuration, the translating member **200** (e.g., the coupler member of the four-bar linkage) can translate according to output curves formed by the rotation of the first arm member **118** at the position of the third pin joint **202** and the second arm member **120** at the position of the fourth pin joint **204**. Accordingly, the translating member **200** can translate relative to the stationary member **114** and/or the support structure **112** (FIG. 1) without rotating relative to the stationary member **114** and/or support structure **112**. In other examples in accordance with the teachings of this disclosure, the translating member **200** can rotate relative to the stationary member **114** and/or the support structure **112**.

(26) In the illustrated example of FIG. 2, the actuating arm **102** is actuated by an extension of an example linear actuator **206**. In some examples, the linear actuator **206**, upon receipt of a command (e.g., via one or more wired or wireless connections, one or more communications protocols, etc.) from the fluid dispenser controller **110**, extends or retracts an example inner tube **208** relative to an example outer tube **210**. Additionally or alternatively, the linear actuator **206** can be electric linear actuator driven by a lead and/or ball screw, a belt drive linear actuator, hydraulic linear actuator, pneumatic linear actuator, and/or any other suitable type of linear actuator. In the example of FIG. 2, the outer tube **210** of the linear actuator **206** is coupled to the first arm member **118** via an example fifth pin joint **212**. In this example, the inner tube **208** of the linear actuator **206** is coupled to the second arm member **120** via an example sixth pin joint **213**. In this example, the fifth pin joint **212** is a first distance from the first pin joint **122** and the sixth pin joint **213** is at a second distance longer than the first distance from the second pin joint **124**.

(27) In the illustrated example of FIG. 2, the linear actuator **206** extends and retracts in a plane coincident with or substantially parallel to a plane defined by the first arm member **118** and the second arm member **120**. In this manner, the extension or retraction of the inner tube **208** relative to the outer tube **210** drives the parallelogram linkage, rotating the first arm member **118** and the

second arm member **120** and translating the translating member **200**. In the illustrated example of FIG. **1**, the lengths of the first arm member **118** and the second arm member **120** are significantly longer than the distance between (a) first and second pin joints **122**, **124** and (b) the third and fourth pin joints **202**, **204**. In consequence, when the linear actuator **206** extends or retracts, the translating member **200** translates significantly further in the direction parallel to support structure (e.g., along a first axis **214**) than the translating member **200** translates in the direction perpendicular to the support structure (e.g. along a second axis **215**).

(28) The example of FIG. **2** also shows the nozzle assembly **104** rigidly coupled to the translating member **200** of the actuating arm **102**. In the example of FIG. **2**, the nozzle assembly **104** extends from the translating member **200** in a direction substantially parallel to the translating member **200** (e.g., positive or upwards on the page along the first axis **214**). In this example, the nozzle assembly **104** is positioned such that it leads the translating member **200** when the linear actuator **206** is extended to drive the translating member forward (e.g., positive or upwards on the page along the first axis **214**). As such, the nozzle assembly **104** trails the translating member **200** when the linear actuator **206** is retracted.

(29) In the illustrated example of FIG. **2**, the pump **106** can be actuated to pump fluid from the fluid reservoir **108** through a first channel **217** (e.g., a fluid channel, a duct, a first section of tubing, etc.) and subsequently a second channel **218** (e.g., a fluid channel, a duct, a second section of tubing, etc.) to the nozzle assembly **104**. In this example, the second channel **218** is composed of flexible tubing such that fluid can be pumped through the second channel **218** despite the position of the nozzle assembly **104** relative to the pump **106** (e.g., the extension or retraction of the actuating arm **102**). The pump **106** can be any pump sufficient to pump fluid to the nozzle assembly **104** from the fluid reservoir **108**, such as a positive displacement pump (e.g., a gear pump, a vane pump, etc.).

(30) In some examples, the fluid dispenser controller **110** is communicatively coupled to aspects of the linear actuator **206**, the nozzle assembly **104**, the pump **106**, and an example vehicle or vehicle sensor. In some examples, upon receiving a signal that an example vehicle has arrived (e.g., via a sensor indicating the vehicle has arrived), the fluid dispenser controller **110** actuates the linear actuator **206** to move the arm **102** towards an example vehicle. In some examples, a contact sensor is coupled to the nozzle assembly **104**. In these examples, the contact sensor indicates to the fluid dispenser controller **110** that the nozzle assembly **104** is aligned with a reciprocal portion of the vehicle (e.g., vehicle components). In some examples, the fluid dispenser controller **110** then actuates the pump **106** to pump a quantity of fluid from the fluid reservoir **108**.

(31) FIG. **3** is a perspective view of an example rotorcraft **300** containing example vehicle components **302** of the self-aligning liquid coupler system that can be implemented in connection with the base components of FIG. **1**. In this example, the rotorcraft **300** is a quadrotor helicopter (e.g., a quadcopter). Additionally or alternatively, another vehicle (e.g., aircraft, rotorcraft, etc.) can be implemented in accordance with the teachings of this disclosure. The vehicle components **302** are denoted as such because they are coupled to the example rotorcraft **300** during its operation. In the illustrated example of FIG. **3**, the rotorcraft **300** includes example first, second, third, and fourth propeller assemblies **304**, **306**, **308**, **310** spaced apart from one another and from a central body **312**. In some examples, the propeller assemblies **304-310** can be driven by internal motors (e.g., brushless DC motors).

(32) In the example of FIG. **3**, the central body **312** of the rotorcraft **300** may internally contain such aspects as a flight controller, motor controller such as an electronic speed controller (ESC), power distribution board (PDB), global positioning system (GPS) module, inertial measurement unit (IMU), and/or other onboard processors and modules. In this example, the central body **312** includes an example communications module **314**. In this example, the communications module **314** is capable of receiving and sending radio frequency (RF) signals and is be communicatively coupled to a flight controller. In this example, the central body **312** also includes an example

battery **316** (e.g., a removable battery, a swappable battery etc.), an example onboard fluid storage tank **318**, and example fixed landing gear **320**.

(33) In the illustrated example of FIG. **3**, the body **312** of the rotorcraft **300** also includes an example fluid inlet assembly **322**. In FIG. **3**, fluid inlet assembly **322** includes an example funnel portion **323** and an example first opening **324** (e.g., an opening, a central opening, a fluid inlet, a fuel inlet, a pesticide inlet, etc.). In FIG. **3**, the funnel portion **323** includes a conical taper converging towards the first opening **324**. In some examples, the fluid inlet assembly **322** extends from body **312** in a direction substantially parallel to the ground (e.g., parallel or within 20° of parallel) and/or substantially horizontal (e.g., horizontal or within 20° of horizontal). In some examples, the first opening **324** is fluidly coupled to the fluid storage tank **318** (e.g., the first opening **324** is an inlet to the fluid storage tank **318**).

(34) FIG. **4A** is a top view of the example base components **100** of FIG. **1** coupled to the example vehicle components **302** of the example rotorcraft **300** of FIG. **3**. In FIG. **4A**, the actuating arm **102** of FIG. **1** is in a first position relative to the rotorcraft **300**. In the illustrated example of FIG. **4A**, the nozzle assembly **104** of FIG. **1** is received by fluid inlet assembly **322** of FIG. **3**, such that the fluid dispenser controller **110** (FIG. **1**) can pump a fluid to the fluid storage tank **318** (FIG. **3**) of the rotorcraft **300** via the second channel **218** (FIG. **2**), the pump **106**, the first channel **217**, and the fluid reservoir **108** (All of FIG. **1**). Coupling (e.g., self-aligning coupling) between the nozzle assembly **104** and the fluid inlet assembly **322** is discussed in greater detail in connection with FIGS. **5-10**.

(35) FIG. **4B** is a top view of the example base components **100** of FIG. **1** not coupled to the example vehicle components **302** of the example rotorcraft **300** of FIG. **3**. In FIG. **4B**, the actuating arm **102** is in a second position (e.g., a retracted position) different from the first position of FIG. **4A**. In FIG. **4B**, the linear actuator **206** (FIG. **2**) is retracted relative to the position of the linear actuator **206** in FIG. **4A**. Accordingly, the actuating arm **102** is retracted (e.g., moved clockwise) from the rotorcraft **300** relative to the position of the actuating arm **102** in FIG. **4A**. In FIG. **4B**, the nozzle assembly **104** and the translating member **200** (FIG. **2**) are shifted relative to the positions of the nozzle assembly **104** and the translating member **200** in FIG. **4A**, while the rotorcraft **300** remains in the same position as in FIG. **4A**. In some examples, the channel **218** (e.g., the flexible tubing) is provided with enough slack to remain coupled to the nozzle assembly **104** in both the first position of FIG. **4A** and the second position of FIG. **4B**. In some examples, the rotorcraft **300** and the base components **100** are oriented in the position of FIG. **4B** when the rotorcraft **300** is not being fueled. In some examples, the fluid dispenser controller **110** (FIG. **1**) actuates the linear actuator **206** to initiate a filling event of the rotorcraft **300**. In some of these examples, the fluid dispenser controller **110** can actuate the linear actuator **206** to extend to cause the actuating arm **102** to move until the base components **100** are in the first position of FIG. **4A** or coupled with the vehicle components **302**.

(36) FIG. **5** is a perspective enlarged view including a partial cross section of the base components **100** of FIG. **1** and the vehicle components **302** of FIG. **3** including the nozzle assembly **104** of FIG. **1** and the fluid inlet assembly **322** of FIG. **3**. In the illustrated example of FIG. **5**, the translating member **200** of FIG. **2** is broken at a first break line **502** and the second channel **218** of FIG. **2** is broken at a second break line **504**. In FIG. **5**, the rotorcraft **300** (FIG. **3**) is removed from view along with accompanying aspects of the vehicle components such as the fluid storage tank **318** (FIG. **3**). In FIG. **5**, the funnel portion **323** (FIG. **3**) of the fluid inlet assembly **322** is cross sectioned. In the illustrated example of FIG. **5**, the nozzle assembly **104** includes an example first link **506** and an example second link **508**. In this example, the first link **506** is a rigid member and is coupled to the translating member **200** (FIG. **2**) (e.g., coupled to a base, coupled to a structure, etc.) via an example seventh pin joint **510** (e.g., a revolute joint, a pinned connection, etc.). In some examples, the seventh pin joint **510** is implemented by a rod at least partially encased in a bearing element (e.g., a rolling-element bearing). In the illustrated example of FIG. **5**, the first link **506**

includes an example second opening **512**. In this example, the second channel **218** is restricted (e.g., retained, enclosed, etc.) by the second opening **512** so as to guide the second channel **218** during movement of the actuation arm **102**. Accordingly, due to the second opening **512** of the first link **506**, the second channel **218** is advantageously prevented from becoming or otherwise less likely to become entangled with aspects of the nozzle assembly **104** and/or the rotorcraft **300** such as, for example, the second link **508**.

(37) In the example of FIG. 5, the second link **508** is coupled to the first link **506** via an example eighth pin joint **514** opposite the translating member **200** (e.g., opposite the base, opposite the structure, etc.). In some examples, the eighth pin joint **514** is implemented by a rod at least partially encased in a bearing element. In the illustrated example of FIG. 5, the second link **508** includes an example first end **516** and an example second end **518**. In this example, an example nozzle head **520** is disposed on the first end **516** of the second link **508**. The nozzle head **520** is fluidly coupled to the second channel **218**. In FIG. 5, an example counterweight **522** (e.g., a weight) is disposed on the second end **518** of the second link **508** and is heavier than the nozzle head **520**. In the illustrated example of FIG. 5, the eighth pin joint **514** is coupled to the second link **508** at a position between the first end **516** and the second end **518** of the second link **508**. In this arrangement, the counterweight **522** is urged to the vertically lowest possible position relative to the translating member **200** by way of gravitational force. In this manner, when no external force is applied to the nozzle assembly **104**, the nozzle head **520** is disposed in a position relatively vertically above counterweight **522**.

(38) In the illustrated example of FIG. 5, the nozzle head **520** includes example first valve components **524** (e.g., nozzle-side valve components). In FIG. 5, the fluid inlet assembly **322** (FIG. 3) also includes example second valve components **526** (e.g., inlet-side valve components) disposed in the first opening **324** (FIG. 3) to interface (e.g., to fluidly couple) with the first valve components **524**. In some examples, the first valve components **524** prevent fluid in second channel **218** from exiting the nozzle head **520** when the first valve components **524** are not in a locking interface with the second valve components **526**. The first and second valve components **524**, **526** can be pop-up valve components, check valve components, poppet valve components etc. In some examples, the second valve components **526** prevent fluid from exiting the fluid storage tank **318** (e.g., a backflow condition) when the second valve components **526** are not in a locking interface with the first valve components **524**. In some examples, when a locking interface is established between the first valve components **524** and the second valve components **526**, the second channel **218** is fluidly coupled to the fluid storage tank **318**. As used herein, a “locking interface” refers to a reversible condition (e.g., reversible by movement of the actuating arm **102**) wherein the first valve components **524** mate with the second valve components **526**.

(39) FIG. 6 is another perspective enlarged view of the nozzle assembly **104** of FIG. 1 and the fluid inlet assembly **322** of FIG. 3. In the illustrated example of FIG. 6, the translating member **200** (FIG. 2) is broken at a fourth break line **602** and at a fifth break line **603**. The second channel **218** (FIG. 2) is broken at a sixth break line **604**. In FIG. 6, the translating member **200** includes an example first face **610**. In FIG. 6, the first face **610** is substantially perpendicular to the ground (e.g., perpendicular to the ground or within 20° of perpendicular). In FIG. 6, the first link **506** (FIG. 5) is substantially parallel to the first face **610** (e.g., the plane defined by the length of the first link **506** is substantially parallel to the plane defined by the first face **610**) and the second link **508** (FIG. 5) is substantially parallel to the first link **506** and the first face **610** (e.g., parallel or within 20 degrees of parallel). In FIG. 6, the first link **506** is offset from (e.g., projected away from) the first face **610** in a direction substantially perpendicular to the first face **610**. Similarly, in the example of FIG. 6, the second link **508** is offset from the first link **506** in the same direction (e.g., perpendicular to the first face **610**). Accordingly, In FIG. 6, the first link **506** can rotate freely about the seventh pin joint **510** (FIG. 5) relative to the translating member **200** and the second link **508** can rotate freely about the eighth pin joint **514** (FIG. 5) relative to the first link **506**.

(40) In the illustrated example of FIG. 6, due to the free rotation of the first and second links **506**, **508** about the seventh and eighth pin joints **510**, **514**, the nozzle head **520** (FIG. 5) can move according to a range of motion defined by the first and second links **506**, **508** due to externally applied forces to the nozzle head **520**. In some examples, the rotorcraft **300** of FIG. 3 lands at different positions on a fixed platform relative to the base components **100** (FIG. 1). In some examples, the rotorcraft **300** lands at a different position on a platform at each landing instance (e.g., lands at many different positions on the platform). In many of these examples, the nozzle head **520** does not directly aligned with the fluid inlet assembly **322** when the nozzle head **520** is in a resting state. In some examples, the nozzle head **520** first interfaces with the funnel portion **323** of the fluid inlet assembly **322** (e.g., a position on the on the face of the funnel portion **323** away from the first opening **324**) when the actuating arm **102** (FIG. 2) is rotated towards the rotorcraft **300** and the translating member **200** moves towards the rotorcraft **300**. Since the first end **516** including the nozzle head **520** can move freely with reciprocal movement of the second end **518**, the nozzle head **520** is urged by the contour of the funnel portion **323** towards the first opening **324** (FIG. 3) (e.g., urged by the conical taper of the funnel portion **323** that converges towards the first opening **324**) with the forward movement of the translating member **200** until a locking condition is established by the first and second valve components **524**, **526** (both of FIG. 5). In some examples, the movement of the nozzle head **520** towards the first opening **324** accommodates any misalignment between the nozzle head **520** and the first opening **324**. In some examples, when the locking connection is established, the counterweight **522** will come to rest at a position vertically higher than its normal and/or resting position (e.g., the position of the counterweight **522** when no external forces are incident on the nozzle assembly **104**). In some examples, when the translating member **200** is retracted (e.g., by retraction of the actuating arm **102**), the counterweight **522** moves downward to alleviate gravitational potential energy and urges first end **516** and nozzle head **520** into their normal and/or resting positions (e.g., positions prior to the nozzle head **520** interfacing fluid inlet assembly **322**). Example self-aligning liquid coupler systems disclosed herein advantageously accommodate unpredictable misalignment between a nozzle and a fluid inlet (e.g., an opening of a fluid inlet, etc.). Examples disclosed herein can automatically refill the fluid storage of rotorcraft **300** despite an unplanned misalignment between a fluid inlet of the rotorcraft and a refilling nozzle.

(41) FIG. 7 is a back view and partial cross section of the base components **100** of FIG. 1. In the illustrated example of FIG. 7, the second arm member **120** (FIG. 1) is broken at seventh break line **702** and the nozzle head **520** (FIG. 5) is cross sectioned. In FIG. 7, a first broken line **704** describes the alignment of the counterweight **522**, the seventh pin joint **510**, and the eighth pin joint **514** along the first and second links **506**, **508** (all of FIG. 5). A second broken line **706** parallel to the first broken line **704** travels through the center of the nozzle head **520**. In FIG. 7, the second link **508** is nonlinear, such that the nozzle head **520** is offset from the counterweight **522** at a first distance **708**. In some examples disclosed herein, the first distance is 10 mm. In some examples disclosed herein, the first distance is between 5 and 15 mm. For example, the counterweight **522** causes the nozzle head **520** to come to a rest approximately 10 millimeters horizontally displaced from the weight.

(42) In illustrated example of FIG. 7, the first distance **708** reduces the propensity of the mechanism formed by the translating member **200** (FIG. 2), the first link **506** (FIG. 5), and the second link **508** to bind during the movement of the translating member **200**. In some examples, due to the position of fluid inlet assembly **322** (FIG. 3) of the rotorcraft **300** relative to the nozzle head **520**, the nozzle head **520** interfaces with the funnel portion **323** (FIG. 3) directly vertically above the first opening **324** during extension of the actuating arm **102** and translation of the translating member **200**. In these examples, a first force **710** is generated on the nozzle head **520** when the nozzle head **520** interfaces with the fluid inlet assembly **322** during translation of the translating member **200** towards an example vehicle. For example, in the absence of the first

distance **708** (e.g., wherein the first distance **708** is 0 millimeters), the first force **710** would be transmitted axially through both the first link **506** and the second link **508**. In this example, due to the absence of the first distance **708**, no lever arm relative to the seventh pin joint **510** or the eighth pin joint **514** would exist to urge the nozzle head **520** towards an opening such as the first opening **324** of FIG. 3. Rather, in this example, as the translating member **200** moves towards an example vehicle, the first force **710** increases without inducing movement in the first link **506** or the second link **508** and increases static friction between the nozzle head **520** and the funnel portion **323**, causing a binding condition that prevents and/or otherwise reduces movement of the base components **100**.

(43) In the illustrated example of FIG. 7, in the event the first distance **708** is a non-zero value (e.g., 10 millimeters) and the first force **710** is applied to the nozzle head **520** (e.g., because the first opening **324** of the fluid inlet assembly **322** is directly below the nozzle head **520**), a lever arm (e.g., a vertical lever arm) is created relative to the eighth pin joint **514**. In this example, as the first force **710** increases (e.g., as the translating member **200** moves towards an example vehicle), a torque is applied relative to the eighth pin joint **514** which urges the nozzle head **520** toward first opening **324** of FIG. 3. The nozzle head **520** can travel linearly in the direction of the first force **710** because of the linkage formed by the first link **506**, the second link **508**, the seventh pin joint **510**, and the eighth pin joint **514**. Because of the first distance **708**, there is no angle that the first force **710** can be applied relative to the nozzle head **520** that would result in direct axial force transmission through both the first link **506** and the second link **508** at the resting condition. Direct axial force transmission through the second link **508** refers to force transmission through the second link **508** on the axis containing the nozzle head **520** and the eighth pin joint **514**. Direct axial force transmission through the first link **506** refers to force transmission through the first link **506** the axis containing the seventh pin joint **510** and the eighth pin joint **514**.

(44) In some examples, the nozzle head **520** will interface the funnel portion **323** at a position other than vertically above first opening **324**. For example, if the nozzle head interfaces the funnel portion **323** at a position relatively to the left on the page in the view of FIG. 7, an example second force **712** is generated on the nozzle head. The second force **712** is perpendicularly displaced from the eighth pin joint **514** so as to have a lever arm (e.g., a vertical lever arm) about the eighth pin joint **514** regardless of the existence of the first distance **708**. Accordingly, in this example, as the translating member **200** moves towards the rotorcraft **300**, the nozzle head **520** is urged towards the center of the first opening **324** (e.g., a central opening).

(45) FIG. 8 is a back view of an example first link **506** of FIG. 5. The first link **506** includes an example first dimension **802**, an example second dimension **804**, and an example third dimension **805**. In some examples, the first dimension **802** is 100 mm, the second dimension **804** is 60 mm, and the third dimension **806** is 80 mm. An example first bore **808** can be implemented in connection with the seventh pin joint **510** (FIG. 5) and an example second bore **810** can be implemented in connection the eighth pin joint **514** (FIG. 5). In some examples, the first bore **808** has a diameter of 13 mm and the second bore **810** has a diameter of 9 mm. In some examples the first link **506** (FIG. 5) and the second link **508** have a thickness of 15 mm. In some examples, the dimensions **802**, **804**, **806**, the bores **808**, **810**, and the thicknesses of the first and second links **506**, **508** are manufactured within a tolerance of the stated dimension (e.g., a tolerance of ± 2 mm, a tolerance of ± 4 mm, a tolerance of ± 1 mm, a tolerance of ± 0.01 mm, etc.). While dimensions provide one example, other dimensions and dimensional relationships may be utilized.

(46) FIG. 9 is a back view of an example second link **508** of FIG. 5. The second link **508** includes an example fourth dimension **902**, an example fifth dimension **904**, and an example sixth dimension **906**. In some examples, the fourth dimension **902** is 99 mm, the fifth dimension **904** is 50 mm, and the sixth dimension **906** is 50 mm. An example third bore **908** can be implemented in connection with the nozzle head **520** (FIG. 5), an example fourth bore **910** can be implemented in connection the eighth pin joint **514** (FIG. 5), and an example fifth bore **912** can be implemented in

connection with the counterweight **522**. In some examples, the third bore **908** has a diameter of 31 mm, the fourth bore **910** has a diameter of 9 mm, and the fifth bore **912** has a diameter of 13 mm. In some examples, the dimensions **902**, **904**, **906** and the bores **908**, **910**, **912** are manufactured within a tolerance of the stated dimension (e.g., a tolerance of ± 2 mm, a tolerance of ± 4 mm, a tolerance of ± 1 mm, a tolerance of ± 0.01 , etc.). While dimensions are shown to provide one example, other dimensions and dimensional relationships may be utilized.

(47) FIG. **10** is an enlarged partial cross section of the base components **100** of FIG. **1** and the vehicle components **302** of FIG. **3** including the nozzle head **520** of FIG. **5**. The cross section of FIG. **10** is taken vertically bisecting the fluid inlet assembly **322** (FIG. **3**) and the nozzle head **520**. In the illustrated example of FIG. **10**, the first valve components **524** and second valve components **526** (both of FIG. **5**) are not in a locking connection. In FIG. **10**, the nozzle head **520** is aligned with the first opening **324** (FIG. **3**). The first valve components **524** include an example first annular flange **1002**. In FIG. **10**, the first annular flange **1002** interfaces with an example seat **1004** of the second valve components **526** in the first opening **324** when the nozzle head **520** is fully inserted into the first opening **324**. In FIG. **10**, the first valve components **524** and second valve components **526** are normally closed (e.g., a normally closed check valve and/or poppet valve, etc.).

(48) In the illustrated example of FIG. **10**, when the first valve components **524** are inserted into the first opening **324**, first poppet components **1006** are urged against second poppet components **1008** to allow fluid to move from the nozzle head **520**. For example, the first valve components **524** include a first spring (not shown) to bias first poppet components **1006** into a closed position and the second valve components **526** include a second spring (not shown) to bias second poppet components **1008** into a closed position. When the first valve components **524** meet the second valve components **526**, the interaction of the first poppet components **1006** and the second poppet components **1008** compresses the first and second springs allowing fluid flow from the nozzle head **520** past the second poppet components **1008**. In FIG. **10**, because of the interactions between the first valve components **524** and the second valve components **526**, when the first flange **1002** interfaces with the seat **1004**, a fluid connection is formed between the second channel **218** and the fluid storage tank **318** of FIG. **3** (e.g., due to the interaction of the poppet components **1006**, **1008**). In FIG. **10**, a contact sensor **1014** is coupled to the first flange **1002**. In some examples, contact sensor **1014** communicates to the fluid dispenser controller **110** that the first flange **1002** has interfaced the seat **1004**.

(49) FIG. **11** is a block diagram of the example fluid dispenser controller **110** of FIG. **1** to actuate the self-aligning liquid coupler system of FIGS. **1-9**. The fluid dispenser controller **110** includes an example sensor interface **1110**, an example local datastore **1120**, an example linear actuator interface **1130**, and an example pump actuator **1140**.

(50) In the illustrated example of FIG. **11**, the fluid dispenser controller **110** of FIG. **1** includes the sensor interface **1110** to obtain sensor readings from aspects of a self-aligning liquid coupler system. The example sensor interface **1110** of the illustrated example of FIG. **11** is implemented by a logic circuit such as, for example, a hardware processor. However, any other type of circuitry may additionally or alternatively be used such as, for example, one or more analog or digital circuit(s), logic circuits, programmable processor(s), application specific integrated circuit(s) (ASIC(s)), programmable logic device(s) (PLD(s)), field programmable logic device(s) (FPLD(s)), digital signal processor(s) (DSP(s)), graphics processing units (GPUs), etc. The example sensor interface **1110** receives signals from the contact sensor **1014** of FIG. **10** along with signals from the communications module **314** of the example rotorcraft **300** (both of FIG. **3**). In some examples, the sensor interface **1110** indicates to the fluid dispenser controller **110** that the rotorcraft **300** has arrived in range of the base components **100** (e.g., by receiving a signal and/or data from the communications module **314**) and indicates to the fluid dispenser controller **110** that the flange **1002** has interfaced the seat **1004** (e.g., by receiving a signal from the contact sensor **1014**).

However, any other methods may additionally or alternatively be used.

(51) In the illustrated example of FIG. 11, the fluid dispenser controller **110** of FIG. 1 includes the local datastore **1120** to store sensor readings and machine readable instructions to implement the fluid dispenser controller **110**. The example local datastore **1120** of the illustrated example of FIG. 11 is implemented by any memory, storage device and/or storage disc for storing data such as, for example, flash memory, magnetic media, optical media, solid state memory, hard drive(s), thumb drive(s), etc. Furthermore, the data stored in the example local datastore **1120** may be in any data format such as, for example, binary data, comma delimited data, tab delimited data, structured query language (SQL) structures, etc. While, in the illustrated example, the example local datastore **1120** is illustrated as a single device, the example local datastore **1120** and/or any other data storage devices described herein may be implemented by any number and/or type(s) of memories. In the illustrated example of FIG. 11, the local datastore **1120** stores sensor readings retrieved by the sensor interface **1110**. In FIG. 11, the local datastore **1120** also stores instructions or configuration values to receive signals and/or data from the sensor interface **1110**, and in turn to actuate the linear actuator **206** (FIG. 2) via the linear actuator interface **1130** and to actuate the pump **106** (FIG. 1) via the pump actuator **1140**.

(52) In the illustrated example of FIG. 11, the fluid dispenser controller **110** of FIG. 1 includes the linear actuator interface **1130** extend and/or retract the linear actuator **206**. The example linear actuator interface **1130** of the illustrated example of FIG. 11 is implemented by a logic circuit such as, for example, a hardware processor. However, any other type of circuitry may additionally or alternatively be used such as, for example, one or more analog or digital circuit(s), logic circuits, programmable processor(s), ASIC(s), PLD(s), FPLD(s), programmable controller(s), GPU(s), DSP(s), etc. In some examples, the example linear actuator interface **1130** actuates the linear actuator **206** to extend the actuating arm **102**. In some examples, the linear actuator interface **1130** actuates the linear actuator **206** to extend or retract the inner tube **208** relative to the outer tube **210**. However, any other methods to actuate the linear actuator **206** may additionally or alternatively be used.

(53) In the illustrated example of FIG. 11, the fluid dispenser controller **110** of FIG. 1 includes the pump actuator **1140** to activate a pump to pump fluid to a vehicle. The example pump actuator **1140** of the illustrated example of FIG. 8 is implemented by a logic circuit such as, for example, a hardware processor. However, any other type of circuitry may additionally or alternatively be used such as, for example, one or more analog or digital circuit(s), logic circuits, programmable processor(s), ASIC(s), PLD(s), FPLD(s), programmable controller(s), GPU(s), DSP(s), etc. The example pump actuator **1140** activates the pump **106** to pump a predetermined quantity of fluid from the fluid reservoir **108** to the rotorcraft **300**. In examples disclosed herein, the pump actuator **1140** activates the pump **106** by transmitting a signal. However, any other methods to activate the pump **106** may additionally or alternatively be used.

(54) While an example manner of implementing the example fluid dispenser controller **110** of FIG. 1 is illustrated in FIG. 11, one or more of the elements, processes and/or devices illustrated in FIG. 11 may be combined, divided, re-arranged, omitted, eliminated and/or implemented in any other way. Further, the example sensor interface **1110**, the example linear actuator interface **1130**, the example pump actuator **1140** and/or, more generally, the example fluid dispenser controller **110** of FIG. 11 may be implemented by hardware, software, firmware and/or any combination of hardware, software and/or firmware. Thus, for example, any of the example sensor interface **1110**, the example linear actuator interface **1130**, the example pump actuator **1140** and/or, more generally, the example fluid dispenser controller **110** could be implemented by one or more analog or digital circuit(s), logic circuits, programmable processor(s), programmable controller(s), graphics processing unit(s) (GPU(s)), digital signal processor(s) (DSP(s)), application specific integrated circuit(s) (ASIC(s)), programmable logic device(s) (PLD(s)) and/or field programmable logic device(s) (FPLD(s)). When reading any of the apparatus or system claims of this patent to cover a

purely software and/or firmware implementation, at least one of the example sensor interface **1110**, the example linear actuator interface **1130**, and/or the example pump actuator **1140** is/are hereby expressly defined to include a non-transitory computer readable storage device or storage disk such as a memory, a digital versatile disk (DVD), a compact disk (CD), a Blu-ray disk, etc. including the software and/or firmware. Further still, the example fluid dispenser controller **110** of FIG. **11** may include one or more elements, processes and/or devices in addition to, or instead of, those illustrated in FIG. **11**, and/or may include more than one of any or all of the illustrated elements, processes and devices. As used herein, the phrase “in communication,” including variations thereof, encompasses direct communication and/or indirect communication through one or more intermediary components, and does not require direct physical (e.g., wired) communication and/or constant communication, but rather additionally includes selective communication at periodic intervals, scheduled intervals, aperiodic intervals, and/or one-time events.

(55) A flowchart representative of example hardware logic, machine readable instructions, hardware implemented state machines, and/or any combination thereof for implementing the fluid dispenser controller **110** of FIGS. **1** and/or **11** is shown in FIG. **12**. The machine readable instructions may be one or more executable programs or portion(s) of an executable program for execution by a computer processor such as the processor **1312** shown in the example processor platform **1300** discussed below in connection with FIG. **13**. The program may be embodied in software stored on a non-transitory computer readable storage medium such as a CD-ROM, a floppy disk, a hard drive, a DVD, a Blu-ray disk, or a memory associated with the processor **1312**, but the entire program and/or parts thereof could alternatively be executed by a device other than the processor **1312** and/or embodied in firmware or dedicated hardware. Further, although the example program is described with reference to the flowchart illustrated in FIG. **12**, many other methods of implementing the example fluid dispenser controller **110** may alternatively be used. For example, the order of execution of the blocks may be changed, and/or some of the blocks described may be changed, eliminated, or combined. Additionally or alternatively, any or all of the blocks may be implemented by one or more hardware circuits (e.g., discrete and/or integrated analog and/or digital circuitry, an FPGA, an ASIC, a comparator, an operational-amplifier (op-amp), a logic circuit, etc.) structured to perform the corresponding operation without executing software or firmware.

(56) The machine readable instructions described herein may be stored in one or more of a compressed format, an encrypted format, a fragmented format, a compiled format, an executable format, a packaged format, etc. Machine readable instructions as described herein may be stored as data (e.g., portions of instructions, code, representations of code, etc.) that may be utilized to create, manufacture, and/or produce machine executable instructions. For example, the machine readable instructions may be fragmented and stored on one or more storage devices and/or computing devices (e.g., servers). The machine readable instructions may require one or more of installation, modification, adaptation, updating, combining, supplementing, configuring, decryption, decompression, unpacking, distribution, reassignment, compilation, etc. in order to make them directly readable, interpretable, and/or executable by a computing device and/or other machine. For example, the machine readable instructions may be stored in multiple parts, which are individually compressed, encrypted, and stored on separate computing devices, wherein the parts when decrypted, decompressed, and combined form a set of executable instructions that implement a program such as that described herein.

(57) In another example, the machine readable instructions may be stored in a state in which they may be read by a computer, but require addition of a library (e.g., a dynamic link library (DLL)), a software development kit (SDK), an application programming interface (API), etc. in order to execute the instructions on a particular computing device or other device. In another example, the machine readable instructions may need to be configured (e.g., settings stored, data input, network addresses recorded, etc.) before the machine readable instructions and/or the corresponding

program(s) can be executed in whole or in part. Thus, the disclosed machine readable instructions and/or corresponding program(s) are intended to encompass such machine readable instructions and/or program(s) regardless of the particular format or state of the machine readable instructions and/or program(s) when stored or otherwise at rest or in transit.

(58) The machine readable instructions described herein can be represented by any past, present, or future instruction language, scripting language, programming language, etc. For example, the machine readable instructions may be represented using any of the following languages: C, C++, Java, C#, Perl, Python, JavaScript, HyperText Markup Language (HTML), Structured Query Language (SQL), Swift, etc.

(59) As mentioned above, the example processes of FIG. 12 may be implemented using executable instructions (e.g., computer and/or machine readable instructions) stored on a non-transitory computer and/or machine readable medium such as a hard disk drive, a flash memory, a read-only memory, a compact disk, a digital versatile disk, a cache, a random-access memory and/or any other storage device or storage disk in which information is stored for any duration (e.g., for extended time periods, permanently, for brief instances, for temporarily buffering, and/or for caching of the information). As used herein, the term non-transitory computer readable medium is expressly defined to include any type of computer readable storage device and/or storage disk and to exclude propagating signals and to exclude transmission media.

(60) “Including” and “comprising” (and all forms and tenses thereof) are used herein to be open ended terms. Thus, whenever a claim employs any form of “include” or “comprise” (e.g., comprises, includes, comprising, including, having, etc.) as a preamble or within a claim recitation of any kind, it is to be understood that additional elements, terms, etc. may be present without falling outside the scope of the corresponding claim or recitation. As used herein, when the phrase “at least” is used as the transition term in, for example, a preamble of a claim, it is open-ended in the same manner as the term “comprising” and “including” are open ended. The term “and/or” when used, for example, in a form such as A, B, and/or C refers to any combination or subset of A, B, C such as (1) A alone, (2) B alone, (3) C alone, (4) A with B, (5) A with C, (6) B with C, and (7) A with B and with C. As used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, and (3) at least one A and at least one B. Similarly, as used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, and (3) at least one A and at least one B. As used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, and (3) at least one A and at least one B. Similarly, as used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, and (3) at least one A and at least one B.

(61) As used herein, singular references (e.g., “a”, “an”, “first”, “second”, etc.) do not exclude a plurality. The term “a” or “an” entity, as used herein, refers to one or more of that entity. The terms “a” (or “an”), “one or more”, and “at least one” can be used interchangeably herein. Furthermore, although individually listed, a plurality of means, elements or method actions may be implemented by, e.g., a single unit or processor. Additionally, although individual features may be included in different examples or claims, these may possibly be combined, and the inclusion in different examples or claims does not imply that a combination of features is not feasible and/or advantageous.

(62) FIG. 12 is a flowchart representative of machine-readable instructions for process 1200 which may be executed to implement the fluid dispenser controller 110 of FIGS. 1 and/or 11 to actuate the

self-aligning liquid coupler system of FIGS. 1-10. The program of FIG. 12 includes the sensor interface **1110**, the linear actuator interface **1130**, and the pump actuator **1140** (all of FIG. 11). In the example of FIG. 12, the process **1200** begins after a signal and/or data is received by the sensor interface **1110** of fluid dispenser controller **110** indicating that the rotorcraft **300** has arrived in range of the base components **100**. In some examples, the signal and/or data indicating that the rotorcraft **300** is in range of the base components **100** is communicated to the fluid dispenser controller by the communications module **314** (FIG. 3) of the example rotorcraft **300**, by a load cell positioned within a predetermined landing area for the example rotorcraft **300**, or via any other suitable manner. Though the process **1200** is discussed in connection with the rotorcraft **300**, other vehicles can additionally or alternatively be used in connection with the process **1200**.

(63) The example linear actuator interface **1130** actuates the linear actuator **206** of FIG. 2 to extend the actuating arm **102** of FIG. 1. (Block **1210**). In some examples, the linear actuator interface **1130** actuates the linear actuator **206** by sending a signal to the linear actuator **206**. In some examples, the linear actuator **206** extends the inner tube **208** relative to the outer tube **210** (all of FIG. 2) to move the actuating arm **102** in a first direction (e.g., in a counterclockwise direction in the view of FIG. 4B). The rotation of the actuating arm **102** translates the translating member **200** (FIG. 2) and the nozzle assembly **104** (FIG. 1) towards the rotorcraft **300**. However, any other methods to actuate the linear actuator **206** can additionally or alternatively be used.

(64) Once the actuating arm **206** has been extended by the linear actuator interface **1130**, the sensor interface **1110** determines whether the contact sensor **1014** indicates placement of the nozzle head **1020** (both of FIG. 10) in the center of the first opening **324** (FIG. 3). (Block **1220**). In some examples, the sensor interface **1110** determines whether the contact sensor **1014** indicates placement of the nozzle head **520** in the center of the first opening **324** by receiving a signal and/or data from the contact sensor **1014**. If the sensor interface **1110** determines that the contact sensor **1014** has not indicated placement of the nozzle head **1020** in the center of the first opening **324** (e.g., block **1220** returns a result of NO), control returns to the example sensor interface **1110** at block **1220** to continue determining whether the contact sensor **1014** indicates placement.

(65) If the sensor interface **1110** determines that the contact sensor **1014** indicates placement of the nozzle head **520** in the center of the first opening **324** (e.g., block **1220** returns a result of YES), the example pump actuator **1140** actuates the pump **106** to pump a predetermined quantity of fluid from the fluid reservoir **108** (both of FIG. 1) to the rotorcraft **300**. (Block **1230**). In examples disclosed herein, the pump actuator **1140** activates the pump **106** by sending a signal to the pump **106**. However, any other methods to activate the pump **106** may additionally or alternatively be used.

(66) After the predetermined quantity of fluid from the fluid reservoir **108** has been pumped to the rotorcraft **300** (e.g., into the fluid storage tank **318**), the example linear actuator interface **1130** actuates the linear actuator **206** to retract the actuating arm **102**. In examples disclosed herein, the linear actuator **206** retracts the inner tube **208** relative to the outer tube **210** to move the arm **102** in a second direction (e.g., clockwise in the view of FIG. 4A) to translate the translating member **200** away from the rotorcraft **300**. In examples disclosed herein, the linear actuator interface **1130** actuates the linear actuator **206** by communicating a signal to the linear actuator **206**. However, any other methods to actuate the linear actuator **206** may additionally or alternatively be used. In some examples, after block **1240**, the process **1200** ends.

(67) FIG. 13 is a block diagram of an example processor platform **1300** structured to execute the instructions of FIG. 12 to implement the example fluid dispenser controller **110** of FIG. 11. The processor platform **1300** can be, for example, a server, a personal computer, a workstation, a mobile device (e.g., a cell phone, a smart phone, a tablet such as an iPad™), a personal digital assistant (PDA), an Internet appliance, a gaming console, a set top box, a headset or other wearable device, or any other type of computing device.

(68) The processor platform **1300** of the illustrated example includes a processor **1312**. The

processor **1312** of the illustrated example is hardware. For example, the processor **1312** can be implemented by one or more integrated circuits, logic circuits, microprocessors, GPUs, DSPs, or controllers from any desired family or manufacturer. The hardware processor may be a semiconductor based (e.g., silicon based) device. In this example, the processor can implement the sensor interface **1110**, the linear actuator interface **1130**, and the pump actuator **1140**.

(69) The processor **1312** of the illustrated example includes a local memory **1313** (e.g., a cache). The processor **1312** of the illustrated example is in communication with a main memory including a volatile memory **1314** and a non-volatile memory **1316** via a bus **1318**. The volatile memory **1314** may be implemented by Synchronous Dynamic Random Access Memory (SDRAM), Dynamic Random Access Memory (DRAM), RAMBUS® Dynamic Random Access Memory (RDRAM®) and/or any other type of random access memory device. The non-volatile memory **1316** may be implemented by flash memory and/or any other desired type of memory device. Access to the main memory **1314**, **1316** is controlled by a memory controller.

(70) The processor platform **1300** of the illustrated example also includes an interface circuit **1320**. The interface circuit **1320** may be implemented by any type of interface standard, such as an Ethernet interface, a universal serial bus (USB), a Bluetooth® interface, a near field communication (NFC) interface, and/or a PCI express interface.

(71) In the illustrated example, one or more input devices **1322** are connected to the interface circuit **1320**. The input device(s) **1322** permit(s) a user to enter data and/or commands into the processor **1312**. The input device(s) can be implemented by, for example, an audio sensor, a microphone, a camera (still or video), a keyboard, a button, a mouse, a touchscreen, a track-pad, a trackball, isopoint and/or a voice recognition system.

(72) One or more output devices **1324** are also connected to the interface circuit **1320** of the illustrated example. The output devices **1324** can be implemented, for example, by display devices (e.g., a light emitting diode (LED), an organic light emitting diode (OLED), a liquid crystal display (LCD), a cathode ray tube display (CRT), an in-place switching (IPS) display, a touchscreen, etc.), a tactile output device, a printer and/or speaker. The interface circuit **1320** of the illustrated example, thus, typically includes a graphics driver card, a graphics driver chip and/or a graphics driver processor.

(73) The interface circuit **1320** of the illustrated example also includes a communication device such as a transmitter, a receiver, a transceiver, a modem, a residential gateway, a wireless access point, and/or a network interface to facilitate exchange of data with external machines (e.g., computing devices of any kind) via a network **1326**. The communication can be via, for example, an Ethernet connection, a digital subscriber line (DSL) connection, a telephone line connection, a coaxial cable system, a satellite system, a line-of-site wireless system, a cellular telephone system, etc.

(74) The processor platform **1300** of the illustrated example also includes one or more mass storage devices **1328** for storing software and/or data. Examples of such mass storage devices **1328** include floppy disk drives, hard drive disks, compact disk drives, Blu-ray disk drives, redundant array of independent disks (RAID) systems, and digital versatile disk (DVD) drives.

(75) The machine executable instructions **1332** of FIG. **8** may be stored in the mass storage device **1328**, in the volatile memory **1314**, in the non-volatile memory **1316**, and/or on a removable non-transitory computer readable storage medium such as a CD or DVD.

(76) From the foregoing, it will be appreciated that example methods, apparatus and articles of manufacture have been disclosed for self-aligning liquid coupler systems and related methods.

(77) Example 1 includes an apparatus, comprising a first link to rotate about a pin joint, a second link rotatably coupled to the first link, the second link having a nozzle at a first end and a weight at a second end opposite the first end, and a fluid inlet including a funnel portion and an opening, the funnel portion having a conical taper converging towards the opening.

(78) Example 2 includes the apparatus of example 1, further including a first arm, a second arm, a

structure, and a stationary member, and wherein each of the first and second arms are rotatably coupled to each of the structure and the stationary member.

(79) Example 3 includes the apparatus of example 2, further including a linear actuator rotatably coupled to the first arm at a first distance from the structure, the linear actuator rotatably coupled to the second arm at a second distance from the structure, the second distance greater than the first distance.

(80) Example 4 includes the apparatus of example 1, wherein the nozzle and the opening include poppet valve components to fluidly couple the nozzle to the opening.

(81) Example 5 includes the apparatus of example 1, wherein the second link is rotatably coupled to the first link at a pin joint, and wherein the nozzle has a vertical lever arm relative to the pin joint.

(82) Example 6 includes the apparatus of example 1, wherein the opening is fluidly coupled to a fluid storage tank of a rotorcraft.

(83) Example 7 includes the apparatus of example 6, wherein the rotorcraft is an Unmanned Aerial Vehicle (UAV).

(84) Example 8 includes the apparatus of example 1, wherein the conical taper of the funnel portion is to urge the nozzle towards the opening to accommodate misalignment between the nozzle and the opening.

(85) Example 9 includes the apparatus of example 1, further including a pump to pump fluid to the nozzle from a fluid reservoir.

(86) Example 10 includes a nozzle, comprising, a first link rotatably coupled to a base, a second link rotatably coupled to the first link opposite the base, a nozzle head disposed on a first end of the second link, and a weight disposed on a second end of the second link opposite the first end, the weight to urge the nozzle to a position vertically above the weight.

(87) Example 11 includes the nozzle of example 10, further including a fluid channel extending between the nozzle and a pump.

(88) Example 12 includes the nozzle of example 11, wherein the first link includes a central opening, the central opening to receive the fluid channel.

(89) Example 13 includes the nozzle of example 11, wherein the fluid channel is a first fluid channel, further including a second fluid channel fluidly coupled to a reservoir containing fluid fertilizer.

(90) Example 14 includes the nozzle of example 10, wherein the nozzle head includes a contact sensor.

(91) Example 15 includes the nozzle of example 10, wherein the nozzle head includes a check valve.

(92) Example 16 includes the nozzle of example 10, wherein the weight causes the nozzle to rest approximately 10 millimeters horizontally displaced from the weight.

(93) Example 17 includes a method for filling a vehicle, the method comprising actuate a linear actuator to extend an arm to project a nozzle assembly towards a fluid inlet of the vehicle, determining with a sensor interface that the nozzle assembly is located in the fluid inlet, actuating a pump to pump a predetermined quantity of fluid from a fluid reservoir to the vehicle to fill the vehicle, and retracting the arm away from the fluid inlet with the linear actuator.

(94) Example 18 includes the method for filling the vehicle of example 17, wherein the linear actuator is an electric linear actuator driven by a DC motor.

(95) Example 19 includes the method for filling the vehicle of example 17, wherein the determining with the sensor interface that the nozzle assembly is located in the fluid inlet includes accessing data from a contact sensor on the nozzle assembly.

(96) Example 20 includes the method for filling the vehicle of example 17, wherein the vehicle is an Unmanned Aerial Vehicle (UAV).

(97) Although certain example methods, apparatus and articles of manufacture have been disclosed

herein, the scope of coverage of this patent is not limited thereto. On the contrary, this patent covers all methods, apparatus and articles of manufacture fairly falling within the scope of the claims of this patent.

(98) The following claims are hereby incorporated into this Detailed Description by this reference, with each claim standing on its own as a separate embodiment of the present disclosure.

Claims

1. A nozzle, comprising; a first link rotatably coupled to a base; a second link rotatably coupled to the first link opposite the base; a nozzle head disposed on a first end of the second link; and a weight disposed on a second end of the second link opposite the first end, the weight to urge the nozzle to a position vertically above the weight.
 2. The nozzle of claim 1, further including a fluid channel extending between the nozzle and a pump.
 3. The nozzle of claim 2, wherein the first link includes a central opening, the central opening to receive the fluid channel.
 4. The nozzle of claim 2, wherein the fluid channel is a first fluid channel, further including a second fluid channel fluidly coupled to a reservoir containing fluid fertilizer.
 5. The nozzle of claim 1, wherein the nozzle head includes a contact sensor.
 6. The nozzle of claim 1, wherein the nozzle head includes a check valve.
 7. The nozzle of claim 1, wherein the weight causes the nozzle to rest approximately 10 millimeters horizontally displaced from the weight.
-