

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405350
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Brem; Erich et al.

Vehicle component for integrating an environment detection sensor into a vehicle

Abstract

A vehicle component integrates an environment detection sensor into a vehicle. The vehicle component is in the form of a plastic component and has a main body with a recess for receiving the environment detection sensor. Towards a visible side of the vehicle component, the recess is delimited by a cover portion which has a signal passage surface or a signal passage opening.

Inventors:	Brem; Erich (Mering, DE), Dix; Markus (Landshut, DE), Ginovski; Mirko (Augsburg, DE), Maidl; Franz (Eichendorf, DE), Schilling; Rudolf (Ergolding, DE), Veihelmann; Bernd (Landshut, DE)
Applicant:	Bayerische Motoren Werke Aktiengesellschaft (Munich, DE)
Family ID:	72521588
Assignee:	Bayerische Motoren Werke Aktiengesellschaft (Munich, DE)
Appl. No.:	17/633658
Filed (or PCT Filed):	September 08, 2020
PCT No.:	PCT/EP2020/075027
PCT Pub. No.:	WO2021/073806
PCT Pub. Date:	April 22, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220317306 A1	Oct. 06, 2022

Foreign Application Priority Data

Publication Classification

Int. Cl.: G01S7/02 (20060101); G01S13/931 (20200101); G01S17/931 (20200101)

U.S. Cl.:

CPC G01S7/027 (20210501); G01S2013/93275 (20200101); G01S17/931 (20200101)

Field of Classification Search

CPC: B60R (11/04); B60R (2011/0045); B60R (2011/0043); B60Q (1/2653); B60Q (1/2619); G01S (7/027); G01S (7/4813); G01D (11/245)

USPC: 296/210

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8149157	12/2011	Takeuchi	343/872	H01Q 1/3233
10144424	12/2017	Hara	N/A	G01S 13/931
10488494	12/2018	Nichols	N/A	G01S 17/931
11046255	12/2020	Miwa	N/A	B60R 19/483
11820297	12/2022	Li	N/A	F16M 13/02
12065025	12/2023	Nagai	N/A	B60R 1/001
12172503	12/2023	Huelsen	N/A	B60Q 1/2611
2006/0284515	12/2005	Nakajima	310/311	B60R 19/483
2012/0200121	12/2011	Wuerfel	296/193.09	B60R 19/483
2014/0210177	12/2013	Dicke et al.	N/A	N/A
2016/0282155	12/2015	Hara	N/A	G01S 7/4813
2016/0297437	12/2015	Hara et al.	N/A	N/A
2018/0284233	12/2017	Nichols et al.	N/A	N/A
2019/0071050	12/2018	Farooq et al.	N/A	N/A
2019/0204426	12/2018	Vaishnav et al.	N/A	N/A
2019/0263452	12/2018	Hogger et al.	N/A	N/A
2019/0267705	12/2018	Klar et al.	N/A	N/A

2020/0094498	12/2019	Lobo Casanova	N/A	N/A
2021/0148737	12/2020	Yamaji	N/A	G01S 7/4813
2023/0038114	12/2022	Davis	N/A	B32B 27/36
2023/0319381	12/2022	Meyer	348/148	H04N 23/54
2023/0365069	12/2022	Maeda	N/A	B60R 16/03
2023/0399057	12/2022	Sviberg	N/A	B62D 27/023
2024/0201332	12/2023	Robertson, Jr.	N/A	G01S 13/865
2024/0308434	12/2023	Schieder	N/A	B60R 11/00
2024/0416846	12/2023	Sviberg	N/A	B60R 11/04

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103963588	12/2013	CN	N/A
106043144	12/2015	CN	N/A
109789746	12/2018	CN	N/A
109991671	12/2018	CN	N/A
112193209	12/2020	CN	B60S 1/0411
103 47 098	12/2004	DE	N/A
10 2007 057 259	12/2008	DE	N/A
20 2011 052 507	12/2012	DE	N/A
10 2016 104 871	12/2015	DE	N/A
102016217057	12/2017	DE	B60Q 1/0023
10 2017 200 368	12/2017	DE	N/A
20 2017 006 640	12/2018	DE	N/A
102019120847	12/2020	DE	N/A
3 258 289	12/2016	EP	N/A

OTHER PUBLICATIONS

Machine Translation of DE-102016217057-A1, Mar. 14, 2025. cited by examiner

Machine Translation of CN-112193209-A, Mar. 14, 2025. cited by examiner

Machine Translation of DE-102019120847-A1, Mar. 14, 2025. cited by examiner

Machine Translation of EP3258289-A1, Mar. 14, 2025. cited by examiner

International Search Report (PCT/ISA/210) issued in PCT Application No. PCT/EP2020/075027 dated Oct. 26, 2020 with English translation (five (5) pages). cited by applicant

German-language Written Opinion (PCT/ISA/237) issued in PCT Application No. PCT/EP2020/075027 dated Oct. 26, 2020 (five (5) pages). cited by applicant

German-language Search Report issued in German Application No. 10 2019 128 013.3 dated Aug. 3, 2020 with partial English translation (11 pages). cited by applicant

Chinese-language Office Action issued in Chinese Application No. 202080058073.X dated Aug. 27, 2024 with English translation (20 pages). cited by applicant

Primary Examiner: Morrow; Jason S

Attorney, Agent or Firm: Crowell & Moring LLP

Background/Summary

BACKGROUND AND SUMMARY OF THE INVENTION

- (1) The invention relates to a vehicle component for integrating an environment detection sensor into a vehicle.
- (2) To make fully automated or autonomous driving possible, a multitude of environmental data is required. These data are provided by environment detection sensors on the vehicle and are further processed and evaluated in control devices. Lidar or radar sensors and cameras are used for example as environment detection sensors. In particular, lidar technology offers detection of a surrounding area with a great range and in combination with a wide coverage.
- (3) The required sensors must be fitted at various points of the vehicle, including in the roof area. In vehicle studies, lidar sensors have so far been placed on the vehicle roof. There, however, they form a disturbing visual and aerodynamic contour. Furthermore, it is known to integrate lidars in the area of the front bumper of the vehicle. For design reasons, there may be protective devices, which are arranged in front of the lidar and allow the lidar to retreat visually into the background. However, these protective devices disturb the function of the lidar and must be laboriously calibrated.
- (4) It is also known from the document DE 10 2016 104 871 A1 to attach an environment information detection sensor to an outer side of the vehicle, on an element of the body having a closed cross-sectional form. The sensor is covered with respect to the outside of the vehicle by a signal-transmissive covering. However, the proposed solution is technically complex in terms of production and the possibilities of integrating the sensor without adapting the outer vehicle contour are limited.
- (5) Against this background, the object of the invention is to provide a possible way in which the integration of an environment detection sensor into a motor vehicle can be improved. In particular, the integration is intended to be devised in such a way that the appearance and aerodynamics of the vehicle are influenced as little as possible.
- (6) The object is achieved by a vehicle component according to the independent claim. Further advantageous designs are provided by the dependent claims and the following description.
- (7) A vehicle component for integrating an environment detection sensor into a vehicle is provided. The vehicle component is formed as a plastic component and has a main body with a recess for receiving the environment detection sensor. The recess is delimited toward a visible side of the component by a covering portion which has a signal passing-through area or a signal passing-through opening.
- (8) In other words, a recess which is completely or largely covered from the outside and in which the environment detection sensor can be received is created in the main body. In the covering portion, either a signal passing-through opening is provided, or at least part of the covering portion is designed as a signal passing-through area, i.e. the signals emitted and received by the sensor can pass through the signal passing-through area or the signal passing-through opening. It is therefore possible to detect the environment outside the vehicle component or outside the vehicle by a sensor arranged inside the main body. A high degree of flexibility with regard to the geometrical design of

the recess is made possible by the vehicle component being formed as a plastic component. By means of plastics technology, forms which cannot be created with metal components, or only very laboriously, can be realized. By forming the component as a plastic component, it is possible to allow the sensor as it were to “disappear” inside the component, without the integration of the sensor having to result in externally perceptible changes to the component. By relocating the sensor to the interior of the component, the overall appearance and aerodynamics of the vehicle are improved, since the component contour can be designed to meet the visual or aerodynamic requirements.

(9) The recess in the main body is designed to receive the environment detection sensor. The recess may be designed for example as a depression in the main body or as a through-opening in the main body. The recess may be adapted to the form of the sensor and receive it for example—at least partially—in a form-fitting manner. The recess is preferably formed so as to be of such a size that the environment detection sensor can be received completely in the recess. In particular, it may be provided that a fitted environment detection sensor finishes flush with an outer contour of the main body or is set back from it. In this way, the environment detection sensor can be as it were “countersunk” in the component, whereby the shape of the outer contour of the vehicle component remains uninfluenced by the integration of the sensor.

(10) The recess extends up to a visible side of the vehicle component. There it is delimited by the covering portion. The visible side of the component remains visible in the fitted state on the vehicle, is therefore not covered by further components or add-on parts. The visible side of the vehicle component preferably forms part of the outer skin of the vehicle. The covering portion forms at least part of the visible side of the vehicle component.

(11) It is particularly preferred that the covering portion is formed in one piece with the main body. Saying that they are formed in one piece means here that the covering portion and the main body cannot be separated from one another without being damaged. This has the advantage that the sensor can be protected in the recess particularly well from external effects. Moreover, a one-piece form makes it easier for the vehicle component to be mounted on the vehicle.

(12) It is contemplated to form the covering portion and the main body as one part from the same plastics material. In order to be able to make better allowance for the different functions of the covering portion and the main body, and nevertheless provide a reliably sealed receptacle for the sensor, externally protected from dust and moisture, in one design the covering portion is molded onto the main body. Different plastics may be used for the covering portion and the main body.

(13) The covering portion may be at least partially formed as a signal passing-through area. This means that the covering portion is designed in form and choice of material such that, at least in a partial region, it is sufficiently transmissive to the sensor signals. The sensor function can therefore be ensured even though the sensor is arranged in the vehicle component and is externally covered. The covering portion is formed from a plastics material. Polycarbonate (PC) is suitable for example as the plastics material. PC is suitable in particular for the laser radiation used in the case of lidar sensors.

(14) The covering portion may be additionally colored, in order to mask the sensor. This makes it possible for the environment detection sensor to be integrated less obtrusively into the vehicle. The covering portion may also have different material thicknesses, and so the covering portion may have a reduced wall thickness in the region of the signal passing-through area, that is to say a smaller thickness than in the rest of the covering portion. As a result, the transmission through the signal passing-through area can be further improved and the sensor range and quality of the sensor data can be increased.

(15) The main body defines the structural and mechanical properties of the vehicle component. It may be formed from a thermosetting and/or thermoplastic material. The main body may preferably have a fiber reinforcement. This may be arranged only in the partial portions or in the entire main body. The main body of the component may for example consist of a fiber-reinforced plastic.

Carbon, glass or aramid fibers may preferably be used as reinforcing fibers. Fiber reinforcement may for example take the form of continuous fibers, which may be formed as a single-layer or multi-layer arrangement of a woven fabric, a braided fabric, a cross-laid structure or the like. The fiber reinforcement in the main body increases the strength and mechanical load-bearing capacity of the vehicle component. By suitable orientation of the reinforcing fibers, it is possible to create a component that meets the requirements for a body component and in particular for a structural component in a motor vehicle and nevertheless to create recesses for the sensor that are sufficiently large and adapted to the form of the sensor.

(16) Particularly great degrees of freedom with respect to the integration of the sensor are obtained if in one design the main body is formed in a skeleton type of construction. In the case of the skeleton type of construction, the stiffness of the components is achieved by way of a fiber-reinforced truss-like structure. This skeleton structure may be closed by way of additional material. The fiber reinforcement may be used appropriately for the load paths and only in the regions in which fiber reinforcement is necessary to achieve the desired component properties. For example, it is known to produce fiber-reinforced bars by the pultrusion process, to shape them into a skeleton and to use the injection-molding process to encapsulate them in a thermoplastic matrix, which then establishes the outer geometry of the component. This fundamental structure of a skeleton component can then be advantageously used within the scope of the invention. Therefore, the main body may in one design have a skeleton structure with multiple fiber-reinforced bars and the recess may be arranged between the bars. For example, the bars may be at least partially led around the recess. The skeleton type of construction makes it possible to provide a recess of almost any desired depth in the component, whereby the integration of even large sensors is made easier or is made possible in the first place. The skeleton type of construction also makes a great degree of freedom possible with regard to the positioning of the recess in the vehicle component.

(17) The vehicle component may be in particular a body component and preferably a structural component of a motor vehicle. For example, it may be a roof frame, a vehicle pillar (A, B, C, D pillar), a rear window frame, a roof or the like.

(18) In a further design, the vehicle component may be a node element in a vehicle body. Such nodes can be found for example at the transition of the roof frame to the A pillar or at the rear end of the roof at the transition of the roof frame to the C or D pillar. Such corner positions offer advantages for the integration of the environment information sensor, since they are arranged very high on the vehicle and consequently allow a good range and “view” of the other vehicles. Furthermore, the angular range that can be covered by the sensor is very great and may be for example approximately 270 degrees.

(19) It is advantageous if the environment detection sensor is only mounted in the vehicle component at a later point in time, for example after the vehicle body has been completed and painted. In an advantageous way, in one design the vehicle component may therefore also have an opening through which the environment detection sensor can be inserted into the recess. The opening may in this case be positioned in such a way that it is for example directed into an interior space of the vehicle and in the finished vehicle is covered by a further vehicle component, such as for example an interior paneling. This has the further advantage that the sensor is also subsequently still accessible with little effort.

(20) In order that the calibrating effort is low, it is important to mount the sensor at a precisely positioned point in the vehicle component. To reduce the mounting tolerances, it is advantageous if a fastening element for fastening the environment detection sensor is also molded on the main body of the vehicle component or the covering portion. If the sensor has a corresponding counter element, high-precision mounting and positioning of the sensor in the component can be achieved in an easy way. Such a fastening element may be for example a latching or clipping element. The fastening element may be formed for example from the plastics material of the main body or the covering portion and is advantageously also formed directly during the production of the

component, for example by a corresponding impression in the mold.

(21) The vehicle component described above serves for integrating an environment information sensor. This is arranged in the recess of the vehicle component such that the signal passing-through area or the signal passing-through opening lies within the coverage of the sensor. The coverage refers here to the space in which the sensor can, by virtue of the way in which it is constructed, detect the environment by emitting and receiving signals. This arrangement allows the sensor to be visually concealed behind the covering portion and nevertheless send and receive signals through the signal passing-through area. If the covering portion has a signal passing-through opening, the sensor can reach into this signal passing-through opening and for example end flush with the covering portion. This makes very unobtrusive integration of the sensor in the vehicle component possible.

(22) The environment detection sensor is preferably a lidar sensor. In principle, the use of other sensors is also contemplated, such as for example radar sensors or cameras, the choice of material and design of the signal passing-through area having to be adapted correspondingly. Lidar (light detection and ranging) is a method related to radar for optical distance and velocity measurement. A lidar sensor emits laser pulses and uses backscattered light for determining position and velocity. The lidar signals are in this case formed by diodes, filters and possibly deflecting elements and are radiated from the sensor.

(23) In a preferred design, the signal passing-through area therefore represents a first transmission area for the signals emerging from the sensor. The signal passing-through area in this design assumes the further function of a protective covering of the sensor. The sensor can therefore be mounted in the vehicle component without a separate housing. As a result, the transmission area in the signal path of the sensor can be omitted, which increases the range of the signals and quality of the signal evaluation.

(24) Further advantages, features and details of the invention are provided by the following description, in which exemplary embodiments of the invention are described in detail with reference to the drawings. The features mentioned in the claims and in the description may each be essential to the invention individually on their own or in any desired combination. Where the term “can” or “may” is used in this application, it relates both to the technical possibility and to the actual technical implementation.

(25) Exemplary embodiments are explained below on the basis of the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 shows a basic diagram of a vehicle component, given by way of example, in a perspective view.

(2) FIG. 1 shows a vehicle component **1**, given by way of example, for integrating an environment detection sensor **30**.

DETAILED DESCRIPTION OF THE DRAWINGS

(3) The vehicle component **1** comprises a main body **10**. The main body **10** is formed in a skeleton type of construction. It has multiple bar-like structures **12** of plastic reinforced with continuous fibers, which are arranged appropriately for the load paths and are connected to one another by multiple plastic webs **14** to form a truss-like main body.

(4) The component **1** shown represents by way of example a node for the attachment of an A pillar **2** and a roof frame **3**. Still further components (not shown) may be connected to the vehicle component **1**. For example, a roof may also be mounted on the upper side of the vehicle component **1**.

(5) The vehicle component **1** also has a covering portion **20**. The covering portion **20** is formed

from a plastic, such as for example (colored) polycarbonate. The covering portion **20** is preferably formed in one piece with the main body **10** and for example is molded on it. The covering portion **20** forms at least part of a visible side of the vehicle component **1**, which is visible in the finished vehicle.

(6) Formed in the main body **10** is a recess **16**, which is formed in such a way that an environment detection sensor **30** can be received in it. An approximately cylindrical recess **16** is shown by way of example, but it may in principle also have any other form. The recess **16** is delimited on one side by the main body **10**. Toward the visible side of the vehicle component **1**, the recess **16** is also delimited by the covering portion **20**.

(7) Arranged in the recess **16** is an environment detection sensor **30**, for example a lidar sensor. For mounting the sensor in the vehicle component **1**, the recess **16** has an opening **18**. In the drawing, this is shown on the underside of the vehicle component **1**, but it may also be positioned at a different point. Through the opening **18**, the environment detection sensor **30** is inserted into the recess **16** and positioned. The opening **18** may be covered later, for example by an interior paneling part.

(8) The environment detection sensor **30** is preferably received completely in the main body **10** and at no point projects beyond the outer contour defined by the bar-like structure **12**. The sensor may be fixed on the vehicle component **1** by a fastening element that is not shown and is for example also formed on the main body **10**.

(9) The environment detection sensor **30** has a coverage **32**, in which it can emit and receive signals, represented by the dashed arrows in FIG. **1**. In order to make detection of the environment possible with the environment detection sensor **30** integrated in the vehicle component **1**, the covering portion **20** is formed at least in a partial portion as a signal passing-through area **22**, i.e. is sufficiently transmissive to the signals of the environment detection sensor **30**. The function of the signal passing-through area **22** may be realized for example by suitable choice of material for the covering portion **20** and adapted geometrical dimensions, such as for example the wall thickness in the region of the signal passing-through area **22**. Alternatively, instead of the signal passing-through area **22**, a signal passing-through opening could also be provided, i.e. the covering portion could have an opening on this area.

LIST OF DESIGNATIONS

(10) **1** Vehicle component **2** A pillar **3** Roof frame **10** Main body **12** Bar-like structure **14** Plastic webs **16** Recess **18** Opening **20** Covering portion **22** Signal passing-through area **30** Environment detection sensor **32** Coverage

Claims

1. A vehicle component for integrating an environment detection sensor into a vehicle, comprising: a plastic component having a main body with a recess for receiving the environment detection sensor, wherein the recess is delimited toward a visible side of the vehicle component by a covering portion which has a signal passing-through area or a signal passing-through opening, and the main body has a fiber-reinforced truss-like structure.
2. The vehicle component as claimed in patent claim 1, wherein the recess completely receives the environment detection sensor.
3. The vehicle component as claimed in claim 1, wherein the covering portion is in one piece with the main body.
4. The vehicle component as claimed in claim 1, wherein the covering portion is a colored plastics material.
5. The vehicle component as claimed in claim 1, wherein the covering portion has a reduced wall thickness in a region of the signal passing-through area.
6. The vehicle component as claimed in claim 1, wherein the vehicle component is a body

component or a structural component of a motor vehicle.

7. The vehicle component as claimed in claim 1, wherein the vehicle component is a node in a vehicle body.

8. The vehicle component as claimed in claim 1, further comprising: an opening in the main body through which the environment detection sensor is insertable into the recess.

9. The vehicle component as claimed in claim 1, wherein the environment detection sensor is arranged in the recess, so that the signal passing-through area or the signal passing-through opening lies within a coverage area of the environment detection sensor.

10. The vehicle component as claimed in patent claim 9, wherein the environment detection sensor is a lidar sensor.

11. The vehicle component as claimed in patent claim 9, wherein the signal passing-through area represents a first transmission area for signals emerging from the environment detection sensor.

12. The vehicle component as claimed in claim 1, wherein the fiber-reinforced truss-like structure includes a plurality of fiber-reinforced bars.

13. The vehicle component as claimed in claim 12, wherein the recess is arranged between the plurality of fiber-reinforced bars.
