

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405451
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Park; Il Yong et al.

Optical imaging system including seven lenses of $+-+--+$ or $+-+--+$ refractive powers

Abstract

An optical imaging system includes a first lens, a second lens, a third lens, a fourth lens, a fifth lens, a sixth lens, and a seventh lens, sequentially arranged from an object side, wherein $TTL/(2*Img\ HT)<0.7$, where a distance on an optical axis from an object-side surface of the first lens to an imaging plane of an image sensor is TTL, and half of a diagonal length of the imaging plane of the image sensor is Img HT, and $Fno<1.9$, where an F-number of the optical imaging system is Fno.

Inventors: Park; Il Yong (Suwon-si, KR), Hwang; Hyo Jin (Suwon-si, KR), Jo; Yong Joo (Suwon-si, KR), Im; Min Hyuk (Suwon-si, KR)

Applicant: Samsung Electro-Mechanics Co., Ltd. (Suwon-si, KR)

Family ID: 72689243

Assignee: Samsung Electro-Mechanics Co., Ltd. (Suwon-si, KR)

Appl. No.: 17/892195

Filed: August 22, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220404591 A1	Dec. 22, 2022

Foreign Application Priority Data

KR	10-2019-0127853	Oct. 15, 2019
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc US 16750052 20200123 US 11860342 child-doc US 17892195

Publication Classification

Int. Cl.: G02B13/00 (20060101); G02B9/64 (20060101)

U.S. Cl.:

CPC G02B13/0045 (20130101); G02B9/64 (20130101);

Field of Classification Search

CPC: G02B (13/0045); G02B (9/64)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9706093	12/2016	Chen	N/A	N/A
10139598	12/2017	Wang et al.	N/A	N/A
11573408	12/2022	Hsu	N/A	G02B 9/64
2016/0085052	12/2015	Park	N/A	N/A
2016/0241756	12/2015	Chen	N/A	N/A

2017/0038567	12/2016	Wang et al.	N/A	N/A
2018/0180855	12/2017	Baik et al.	N/A	N/A
2018/0239115	12/2017	Hsu et al.	N/A	N/A
2019/0004285	12/2018	Tang et al.	N/A	N/A
2019/0146184	12/2018	Xu	359/755	G02B 27/0025
2019/0154967	12/2018	Son et al.	N/A	N/A
2019/0227279	12/2018	Yang	N/A	N/A
2020/0064595	12/2019	Huang	N/A	G02B 13/0045
2020/0209546	12/2019	Zhao et al.	N/A	N/A
2020/0209547	12/2019	Bian et al.	N/A	N/A
2020/0225449	12/2019	Zirkel et al.	N/A	N/A
2020/0249434	12/2019	Lin et al.	N/A	N/A
2021/0048643	12/2020	Lin	N/A	G02B 13/18
2021/0072507	12/2020	Huang	N/A	N/A
2021/0103129	12/2020	Ji	N/A	G02B 9/64
2021/0109316	12/2020	Jhang et al.	N/A	N/A
2021/0239947	12/2020	Geng et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
107678132	12/2017	CN	N/A
107817584	12/2017	CN	N/A
109358416	12/2018	CN	N/A
109613679	12/2018	CN	N/A
109683294	12/2018	CN	N/A
10-1471963	12/2013	KR	N/A
10-1670130	12/2015	KR	N/A
10-1748104	12/2016	KR	N/A
10-2018-0075151	12/2017	KR	N/A
10-2018-0103809	12/2017	KR	N/A
10-2019-0057664	12/2018	KR	N/A

OTHER PUBLICATIONS

United States Office Action issued on Oct. 27, 2022, in related U.S. Appl. No. 16/750,052 (11 pages in English). cited by applicant

Korean Office Action Issued on Feb. 18, 2023, in Counterpart Korean Patent Application No. 10-2022-0079040 (8 Pages in English, 5 Pages in Korean). cited by applicant

Chinese Office Action issued on Jan. 6, 2022, in counterpart Chinese Patent Application No. 202010316372.0 (3 pages in English and 5 pages in Chinese). cited by applicant

Korean Office Action issued on Oct. 28, 2020 in counterpart Korean Patent Application No. 10-2019-0127853 (5 pages in English and 5 pages in Korean). cited by applicant

Korean Office Action Issued on Apr. 30, 2021, in Counterpart Korean Patent Application No. 10-2019-0127853 (5 pages in English and 4 in Korean). cited by applicant

Korean Office Action issued on Nov. 24, 2021, in counterpart Korean Patent Application No. 10-2019-0127853 (7 pages in English and 5 pages in Korean). cited by applicant

Chinese Office Action issued on Aug. 18, 2022, in counterpart Chinese Patent Application No. 202010316372.0 (6 Pages in English, 7 Pages in Mandarin). cited by applicant

United States Office Action Issued on Feb. 24, 2023, in related U.S. Appl. No. 16/750,052 (10 Pages in English). cited by applicant

U.S. Non Final Office Action issued on Apr. 30, 2025, in corresponding U.S. Appl. No. 18/104,442 (7 pages in English). cited by applicant

Primary Examiner: Huang; Wen

Attorney, Agent or Firm: NSIP Law

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a Continuation Application of U.S. patent application Ser. No. 16/750,052 filed on Jan. 23, 2020, now U.S. Pat. No. 11,860,342, which claims the benefit under 35 USC § 119 (a) of Korean Patent Application No. 10-2019-0127853 filed on Oct. 15, 2019, in the Korean Intellectual Property Office, the entire disclosures of which are incorporated herein by reference for all purposes.

BACKGROUND

1. Field

(1) The present disclosure relates to an optical imaging system.

2. Description of the Background

(2) Recently, mobile communications terminals have been provided with camera modules including an optical imaging system composed of a plurality of lenses, enabling video calling and image capturing.

(3) In addition, as levels of functionality of cameras in such mobile communications terminals have gradually increased, the camera modules mounted in such mobile communications terminals have gradually been required to have higher levels of resolution.

(4) Furthermore, since mobile communications terminals tend to be miniaturized, the camera modules mounted in mobile communications terminals may also be required to be slimmer.

- (5) Therefore, the development of an optical imaging system realizing compactness and a high level of resolution may be desired.
- (6) The above information is presented as background information only to assist with an understanding of the present disclosure. No determination has been made, and no assertion is made, as to whether any of the above might be applicable as prior art with regard to the disclosure.
- SUMMARY**
- (7) This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.
- (8) In one general aspect, an optical imaging system includes a first lens, a second lens, a third lens, a fourth lens, a fifth lens, a sixth lens, and a seventh lens, sequentially arranged from an object side, wherein $TTL/(2 \times \text{Img HT}) < 0.7$, where a distance on an optical axis from an object-side surface of the first lens to an imaging plane of an image sensor is TTL, and half of a diagonal length of the imaging plane of the image sensor is Img HT, and $Fno < 1.9$, where an F-number of the optical imaging system is Fno.
- (9) The difference $v1 - v2$ may be between 25 and 45, where an Abbe number of the first lens is $v1$, and an Abbe number of the second lens is $v2$.
- (10) The difference $v1 - v3$ may be less than 25, where an Abbe number of the third lens is $v3$.
- (11) The difference $v1 - v5$ may be between 15 and 35, where an Abbe number of the fifth lens is $v5$.
- (12) The ratio $f1/f$ may be less than 2.0, where a focal length of the first lens is $f1$, and an overall focal length of the optical imaging system is f .
- (13) The ratio $f2/f$ may be between -10 and 0 , where a focal length of the second lens is $f2$.
- (14) The ratio $f3/f$ may be greater than 1.5, where a focal length of the third lens is $f3$.
- (15) The absolute value of the ratio $f4/f$ may be greater than 3.0, where a focal length of the fourth lens is $f4$.
- (16) The ratio $f2/f3$ may be between -2.0 and 0 .
- (17) The ratio $f12/f$ may be between 1.0 and 1.5, where a synthetic focal length of the first lens and the second lens is $f12$.
- (18) The ratio TTL/f may be less than 1.4, and the ratio BFL/f may be less than 0.4, where a distance on the optical axis from an image-side surface of the seventh lens to the imaging plane of the image sensor is BFL.
- (19) The ratio $D1/f$ may be less than 0.1, where a distance on the optical axis from an image-side surface of the first lens to an object-side surface of the second lens is $D1$.
- (20) The FOV may be less than 80° , where a field of view of the optical imaging system is FOV.
- (21) The first lens may have positive refractive power, the second lens may have negative refractive power, the third lens may have positive refractive power, the fourth lens may have negative refractive power, the fifth lens may have negative or positive refractive power, the sixth lens may have positive refractive power, and the seventh lens may have negative refractive power.
- (22) In another general aspect, an optical imaging system includes a first lens having positive refractive power, a second lens having negative refractive power, a third lens having positive refractive power, a fourth lens having negative refractive power, a fifth lens, a sixth lens, and a seventh lens, sequentially arranged from an object side, wherein $TTL/(2 \times \text{Img HT}) < 0.7$, where a distance on an optical axis from an object-side surface of the first lens to an imaging plane of an image sensor is TTL, and half of a diagonal length of the imaging plane of the image sensor is Img HT, $Fno < 1.9$, where an F-number of an optical imaging system is Fno, $FOV < 80^\circ$, where a field of view of the optical imaging system is FOV, and $15 < v1 - v5 < 35$, where an Abbe number of the first lens is $v1$, and an Abbe number of the fifth lens is $v5$.
- (23) The first lens may have a convex object-side surface and a concave image-side surface, the second lens may have a convex object-side surface and a concave image-side surface, and the third lens may have a convex object-side surface.
- (24) The fifth lens may have a convex object-side surface and a concave image-side surface, the sixth lens may have positive refractive power, a convex object-side surface and a concave image-side surface, and the seventh lens may have negative refractive power, a concave object-side surface and a concave image-side surface.
- (25) A refractive index of one or more of the first to seventh lenses may be no less than 1.66.
- (26) Other features and aspects will be apparent from the following detailed description, the drawings, and the claims.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a view illustrating one or more examples of an optical imaging system according to a first embodiment of the present disclosure.
- (2) FIG. 2 presents graphs representing aberration characteristics of the optical imaging system illustrated in FIG. 1.
- (3) FIG. 3 is a view illustrating one or more examples of an optical imaging system according to a second embodiment of the present disclosure.
- (4) FIG. 4 presents graphs representing aberration characteristics of the optical imaging system illustrated in FIG. 3.
- (5) FIG. 5 is a view illustrating one or more examples of an optical imaging system according to a third embodiment of the present disclosure.
- (6) FIG. 6 presents graphs representing aberration characteristics of the optical imaging system illustrated in FIG. 5.
- (7) FIG. 7 is a view illustrating one or more examples of an optical imaging system according to a fourth embodiment of the present disclosure.
- (8) FIG. 8 presents graphs representing aberration characteristics of the optical imaging system illustrated in FIG. 7.
- (9) FIG. 9 is a view illustrating one or more examples of an optical imaging system according to a fifth embodiment of the present disclosure.
- (10) FIG. 10 presents graphs representing aberration characteristics of the optical imaging system illustrated in FIG. 9.
- (11) Throughout the drawings and the detailed description, the same reference numerals refer to the same elements. The drawings may not be to scale, and the relative size, proportions, and depiction of elements in the drawings may be exaggerated for clarity, illustration, and convenience.

DETAILED DESCRIPTION

- (12) The following detailed description is provided to assist the reader in gaining a comprehensive understanding of the methods, apparatuses, and/or systems described herein. However, various changes, modifications, and equivalents of the methods, apparatuses, and/or systems described herein will be apparent after an understanding of this disclosure. For example, the sequences of operations described

herein are merely examples, and are not limited to those set forth herein, but may be changed as will be apparent after an understanding of this disclosure, with the exception of operations necessarily occurring in a certain order. Also, descriptions of features that are known in the art may be omitted for increased clarity and conciseness.

(13) The features described herein may be embodied in different forms, and are not to be construed as being limited to the examples described herein. Rather, the examples described herein have been provided merely to illustrate some of the many possible ways of implementing the methods, apparatuses, and/or systems described herein that will be apparent after an understanding of this disclosure. Hereinafter, while embodiments of the present disclosure will be described in detail with reference to the accompanying drawings, it is noted that examples are not limited to the same.

(14) Throughout the specification, when an element, such as a layer, region, or substrate, is described as being “on,” “connected to,” or “coupled to” another element, it may be directly “on,” “connected to,” or “coupled to” the other element, or there may be one or more other elements intervening therebetween. In contrast, when an element is described as being “directly on,” “directly connected to,” or “directly coupled to” another element, there can be no other elements intervening therebetween. As used herein “portion” of an element may include the whole element or less than the whole element.

(15) As used herein, the term “and/or” includes any one and any combination of any two or more of the associated listed items; likewise, “at least one of” includes any one and any combination of any two or more of the associated listed items.

(16) Although terms such as “first,” “second,” and “third” may be used herein to describe various members, components, regions, layers, or sections, these members, components, regions, layers, or sections are not to be limited by these terms. Rather, these terms are only used to distinguish one member, component, region, layer, or section from another member, component, region, layer, or section. Thus, a first member, component, region, layer, or section referred to in examples described herein may also be referred to as a second member, component, region, layer, or section without departing from the teachings of the examples.

(17) Spatially relative terms, such as “above,” “upper,” “below,” “lower,” and the like, may be used herein for ease of description to describe one element's relationship to another element as shown in the figures. Such spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, an element described as being “above,” or “upper” relative to another element would then be “below,” or “lower” relative to the other element. Thus, the term “above” encompasses both the above and below orientations depending on the spatial orientation of the device. The device may be also be oriented in other ways (rotated 90 degrees or at other orientations), and the spatially relative terms used herein are to be interpreted accordingly.

(18) The terminology used herein is for describing various examples only, and is not to be used to limit the disclosure. The articles “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. The terms “comprises,” “includes,” and “has” specify the presence of stated features, numbers, operations, members, elements, and/or combinations thereof, but do not preclude the presence or addition of one or more other features, numbers, operations, members, elements, and/or combinations thereof.

(19) Due to manufacturing techniques and/or tolerances, variations of the shapes shown in the drawings may occur. Thus, the examples described herein are not limited to the specific shapes shown in the drawings, but include changes in shape that occur during manufacturing.

(20) The features of the examples described herein may be combined in various ways as will be apparent after an understanding of this disclosure. Further, although the examples described herein have a variety of configurations, other configurations are possible as will be apparent after an understanding of this disclosure.

(21) Herein, it is noted that use of the term “may” with respect to an example, for example, as to what an example may include or implement, means that at least one example exists in which such a feature is included or implemented while all examples are not limited thereto.

(22) In the drawings, the thicknesses, sizes, and shapes of lenses may be somewhat exaggerated for convenience of explanation. In particular, the shapes of spherical surfaces or aspherical surfaces illustrated in the drawings are only illustrative. That is, the shapes of the spherical surfaces or the aspherical surfaces are not limited to those illustrated in the drawings.

(23) In the present specification, a first lens refers to a lens closest to an object, while a seventh lens refers to a lens closest to an image sensor.

(24) In addition, a first surface of each lens refers to a surface thereof closest to an object side (or an object-side surface) and a second surface of each lens refers to a surface thereof closest to an image side (or an image-side surface). Further, in the present specification, all numerical values of radii of curvature, thicknesses, distances, focal lengths, and the like, of lenses are indicated by millimeters (mm), and a field of view (FOV) is indicated by degrees.

(25) Further, in a description of a shape of each of the lenses, the meaning that one surface of a lens is convex is that a paraxial region portion of a corresponding surface is convex, the meaning that one surface of a lens is concave is that a paraxial region portion of a corresponding surface is concave, and the meaning that one surface of a lens is a plane is that a paraxial region portion of a corresponding surface is a plane. Therefore, although it is described that one surface of a lens is convex, an edge portion of the lens may be concave. Likewise, although it is described that one surface of a lens is concave, an edge portion of the lens may be convex. Moreover, although it is described that one surface of a lens is a plane, an edge portion of the lens may be convex or concave.

(26) Meanwhile, a paraxial region refers to a narrow region including an optical axis.

(27) One or more examples of the present disclosure may provide an optical imaging system capable of realizing high resolution, and having a small size.

(28) One or more examples of an optical imaging system according to an embodiment of the present disclosure may include seven lenses.

(29) For example, the optical imaging system according to an embodiment may include a first lens, a second lens, a third lens, a fourth lens, a fifth lens, a sixth lens, and a seventh lens, which are sequentially arranged from the object side. The first lens to the seventh lens may be respectively spaced apart from each other by a predetermined distance along the optical axis.

(30) However, the optical imaging system according to an embodiment is not limited to only including seven lenses, but may further include other components, when necessary.

(31) For example, the optical imaging system may further include an image sensor converting an image of a subject incident thereon into an electrical signal.

(32) In addition, the optical imaging system may further include an infrared filter (hereinafter, referred to as a filter) filtering infrared light. The filter may be disposed between the seventh lens and the image sensor.

(33) In addition, the optical imaging system may further include a stop controlling an amount of light.

(34) In the optical imaging system according to an embodiment, the first to seventh lenses may be formed of plastic.

(35) In addition, at least one of the first to seventh lenses may have an aspherical surface. Further, each of the first to seventh lenses may have at least one aspherical surface.

(36) That is, at least one of the first to seventh lenses may be aspherical. Here, the aspherical surfaces of the first to seventh lenses may be represented by the following Equation 1:

(37)

$$Z = \frac{cY^2}{1 + \sqrt{1 + Kc^2Y^2}} + AY^4 + BY^6 + CY^8 + DY^{10} + EY^{12} + FY^{14} + GY^{16} + HY^{18} + JY^{20} + KY^{22} + LY^{24} + MY^{26} + NY^{28} + OY^{30} \text{ .Math. Equation}$$

(38) Here, c is a curvature (an inverse of a radius of curvature) of a lens, K is a conic constant, and Y is a distance from a certain point on an aspherical surface of the lens to an optical axis in a direction perpendicular to the optical axis. In addition, constants A to O are aspherical coefficients. In addition, Z is a distance from the certain point on the aspherical surface of the lens to a tangential plane meeting the apex of the aspherical surface of the lens.

(39) The optical imaging system including the first to seventh lenses may have positive refractive power/negative refractive power/positive refractive power/negative refractive power/positive refractive power/positive refractive power/negative refractive power sequentially from the object side. Alternatively, the first to seventh lenses may have positive refractive power/negative refractive power/positive refractive power/negative refractive power/negative refractive power/positive refractive power/negative refractive power.

(40) The optical imaging system according to an exemplary embodiment may satisfy at least one of the following Conditional Expressions:

$0 < f_1/f < 2.0$ Conditional Expression 1

$25 < v_1 - v_2 < 45$ Conditional Expression 2

$v_1 - v_3 < 25$ Conditional Expression 3

$15 < v_1 - v_5 < 35$ Conditional Expression 4

$-10.0 < f_2/f < 0$ Conditional Expression 5

$f_3/f > 1.5$ Conditional Expression 6

$|f_4/f| > 3.0$ Conditional Expression 7

$f_6/f > 0$ Conditional Expression 8

$f_7/f < 0$ Conditional Expression 9

$TTL/f < 1.4$ Conditional Expression 10

$-2.0 < f_2/f_3 < 0$ Conditional Expression 11

$BFL/f < 0.4$ Conditional Expression 12

$D1/f < 0.1$ Conditional Expression 13

$FOV < 80^\circ$ Conditional Expression 14

$Fno < 1.9$ Conditional Expression 15

$TTL/(2 * Img HT) < 0.7$ Conditional Expression 16

$1.0 < f_{12}/f < 1.5$ Conditional Expression 17

(41) Here, f is an overall focal length of an optical imaging system, f_1 is a focal length of a first lens, f_2 is a focal length of a second lens, f_3 is a focal length of a third lens, f_4 is a focal length of a fourth lens, f_5 is a focal length of a fifth lens, f_6 is a focal length of a sixth lens, f_7 is a focal length of a seventh lens, and f_{12} is a synthetic focal length of the first lens and the second lens.

(42) v_1 is an Abbe number of the first lens, v_2 is an Abbe number of the second lens, v_3 is an Abbe number of the third lens, and v_5 is an Abbe number of the fifth lens.

(43) TTL is a distance from the object-side surface of the first lens to an imaging plane of an image sensor on the optical axis, BFL is a distance from the image-side surface of the seventh lens to the imaging plane of the image sensor on the optical axis, $D1$ is a distance between the image-side surface of the first lens and the object-side surface of the second lens on the optical axis, and $Img HT$ is a half of a diagonal length of the imaging plane of the image sensor.

(44) FOV is a field of view of the optical imaging system, and Fno is an F-number of the optical imaging system.

(45) Next, examples of the first to seventh lenses constituting the optical imaging system according to an embodiment are described.

(46) The first lens may have positive refractive power. In addition, the first lens may have a meniscus shape of which an object-side surface is convex. For example, a first surface of the first lens may be convex, and a second surface thereof may be concave.

(47) At least one of the first and second surfaces of the first lens may be aspherical. For example, both surfaces of the first lens may be aspherical.

(48) The second lens may have negative refractive power. In addition, the second lens may have a meniscus shape of which an object-side surface is convex. For example, a first surface of the second lens may be convex, and a second surface thereof may be concave.

(49) At least one of the first and second surfaces of the second lens may be aspherical. For example, both surfaces of the second lens may be aspherical.

(50) The third lens may have positive refractive power. In addition, the third lens may have a meniscus shape of which an object-side surface is convex. For example, a first surface of the third lens may be convex, and a second surface thereof may be concave.

(51) Alternatively, both surfaces of the third lens may be convex. In detail, first and second surfaces of the third lens may be convex.

(52) At least one of the first and second surfaces of the third lens may be aspherical. For example, both surfaces of the third lens may be aspherical.

(53) The fourth lens may have negative refractive power. In addition, both surfaces of the fourth lens may be concave. In detail, first and second surfaces of the fourth lens may be concave.

(54) Alternatively, the fourth lens may have a meniscus shape of which an object-side surface is convex. For example, a first surface of the fourth lens may be convex, and a second surface thereof may be concave.

(55) At least one of the first and second surfaces of the fourth lens may be aspherical. For example, both surfaces of the fourth lens may be aspherical.

(56) The fifth lens may have negative or positive refractive power. In addition, the fifth lens may have a meniscus shape of which an object-side surface is convex. For example, a first surface of the fifth lens may be convex in a paraxial region, and a second surface thereof may be concave in the paraxial region.

(57) At least one of the first and second surfaces of the fifth lens may be aspherical. For example, both surfaces of the fifth lens may be aspherical.

(58) At least one inflection point may be formed on at least one of the first and second surfaces of the fifth lens. For example, the first surface of the fifth lens may be convex in a paraxial region, and may be concave at an edge thereof. The second surface of the fifth lens may be concave in a paraxial region, and may be convex at an edge thereof.

(59) The sixth lens may have positive refractive power. In addition, the sixth lens may have a meniscus shape of which an object-side surface is convex. For example, a first surface of the sixth lens may be convex in a paraxial region, and a second surface thereof may be

concave in a paraxial region.

(60) At least one of the first and second surfaces of the sixth lens may be aspherical. For example, both surfaces of the sixth lens may be aspherical.

(61) At least one inflection point may be formed on at least one of the first and second surfaces of the sixth lens. For example, the first surface of the sixth lens may be convex in a paraxial region, and may be concave at an edge thereof. The second surface of the sixth lens may be concave in a paraxial region, and may be convex at an edge thereof.

(62) The seventh lens may have negative refractive power. In addition, both surfaces of the seventh lens may be concave. In detail, first and second surfaces of the seventh lens may be concave in the paraxial region.

(63) At least one of the first and second surfaces of the seventh lens may be aspherical. For example, both surfaces of the seventh lens may be aspherical.

(64) In addition, at least one inflection point may be formed on at least one of the first and second surfaces of the seventh lens. For example, the first surface of the seventh lens may be concave in a paraxial region, and may be convex at an edge thereof. The second surface of the seventh lens may be concave in a paraxial region, and may be convex at an edge thereof.

(65) The first lens and the second lens may be formed of plastic materials having different optical properties from each other, and the second lens and the third lens may be formed of plastic materials having different optical properties from each other.

(66) Meanwhile, a refractive index of at least one among the first to seventh lenses may be 1.66 or more. For example, a refractive index of at least one among the first to seventh lenses may be 1.67 or more.

(67) A refractive index of a lens having negative refractive power among the first to fourth lenses may be 1.66 or more. As an example, the second lens and the fourth lens have negative refractive power and refractive indices of the second lens and the fourth lens may be 1.66 or more.

(68) One or more examples of an optical imaging system according to a first embodiment of the present disclosure are hereinafter described with reference to FIGS. 1 and 2.

(69) The optical imaging system according to the first embodiment of the present disclosure may include a first lens **110**, a second lens **120**, a third lens **130**, a fourth lens **140**, a fifth lens **150**, a sixth lens **160**, and a seventh lens **170**, and may further include a stop, a filter **180**, and an image sensor **190**.

(70) Lens characteristics (radii of curvature, thicknesses of lenses or distances between the lenses, refractive indices, Abbe numbers, and focal lengths) of each lens are shown in Table 1.

(71) TABLE-US-00001 TABLE 1 Radius of Thickness or Refractive Abbe Focal Surface No. Remark Curvature Distance Index number Length S1 First Lens 1.98 0.768 1.547 56.1 4.4897 S2 8.89 0.175 S3 Second 6.08 0.225 1.680 19.2 -10.6334 Lens S4 3.25 0.389 S5 Third Lens 15.69 0.315 1.547 56.1 36.6547 S6 71.89 0.206 S7 Fourth Lens -17.91 0.335 1.680 19.2 -19.2755 S8 49.11 0.257 S9 Fifth Lens 6.92 0.290 1.621 26.0 20.2203 S10 15.17 0.569 S11 Sixth Lens 2.83 0.458 1.547 56.1 7.5233 S12 8.60 0.704 S13 Seventh -5.50 0.390 1.547 56.1 -3.9004 Lens S14 3.57 0.123 S15 Filter Infinity 0.110 1.519 64.2 S16 Infinity 0.691 S17 Imaging Infinity Plane

(72) Meanwhile, according to the present example of the first embodiment, an overall focal length f of the optical imaging system is 5.4 mm, f_{12} is 6.6016 mm, F_{no} is 1.87, FOV is 78.7°, and $Img\ HT$ is 4.54 mm.

(73) Here, f_{12} is a synthetic focal length of the first and second lenses, F_{no} is the number representing brightness of an optical imaging system, FOV is a field of view of the optical imaging system, and $Img\ HT$ is a half of a diagonal length of an imaging plane of an image sensor.

(74) In the first embodiment, the first lens **110** may have positive refractive power, and a first surface thereof may be convex while a second surface thereof may be concave.

(75) The second lens **120** may have negative refractive power, and a first surface thereof may be convex while a second surface thereof may be concave.

(76) The third lens **130** may have positive refractive power, and a first surface thereof may be convex while a second surface thereof may be concave.

(77) The fourth lens **140** may have negative refractive power, and the first and second surfaces thereof may be concave.

(78) The fifth lens **150** may have positive refractive power, and a first surface thereof may be convex in a paraxial area while a second surface thereof may be concave in the paraxial area.

(79) In addition, at least one inflection point may be formed on at least one of the first and second surfaces of the fifth lens **150**. For example, the first surface of the fifth lens **150** may be convex in a paraxial region, and may be concave at an edge thereof. In addition, the second surface of the fifth lens **150** may be concave in a paraxial region, and may be convex at an edge thereof.

(80) The sixth lens **160** may have positive refractive power, and a first surface thereof may be convex in a paraxial area while a second surface thereof may be concave in the paraxial area.

(81) In addition, at least one inflection point may be formed on at least one of the first and second surfaces of the sixth lens **160**. For example, the first surface of the sixth lens **160** may be convex in a paraxial region, and may be concave at an edge thereof. In addition, the second surface of the sixth lens **160** may be concave in a paraxial region, and may be convex at an edge thereof.

(82) The seventh lens **170** may have negative refractive power, and the first and second surfaces thereof may be concave in a paraxial area.

(83) In addition, at least one inflection point may be formed on at least one of the first and second surfaces of the seventh lens **170**. For example, the first surface of the seventh lens **170** may be concave in a paraxial region, and may be convex at an edge thereof. In addition, the second surface of the seventh lens **170** may be concave in a paraxial region, and may be convex at an edge thereof.

(84) Meanwhile, respective surfaces of the first to seventh lenses **110** to **170** may have aspherical coefficients as illustrated in Table 2. For example, all of object-side surfaces and image-side surfaces of the first to seventh lenses **110** to **170** may be aspherical.

(85) TABLE-US-00002 TABLE 2 S1 S2 S3 S4 S5 S6 S7 K -1.06 19.72 16.39 2.36 0.00 33.68 0.00 A 0.01 -0.04 -0.07 -0.07 -0.06 -0.06 -0.10 B 0.01 0.12 0.01 0.12 0.05 0.02 0.29 C -0.02 -0.68 0.27 0.03 0.15 -0.24 -2.04 D 0.12 2.95 0.34 -3.07 -4.78 1.82 9.74 E -0.63 -8.79 -8.23 24.14 34.85 -9.05 -31.65 F 2.00 18.13 36.48 -102.50 -140.21 29.95 71.86 G -3.98 -26.46 -89.72 275.47 363.75 -66.99 -116.13 H 5.22 27.68 142.53 -497.74 -645.50 103.44 135.03 J -4.66 -20.80 -153.67 620.42 801.54 -111.53 -113.18 K 2.85 11.12 113.87 -535.55 -696.97 83.82 67.75 L -1.18 -4.12 -57.20 314.72 416.06 -43.04 -28.25 M 0.31 1.00 18.63 -120.25 -162.45 14.40 7.80 N -0.05 -0.14 -3.55 26.95 37.36 -2.83 -1.28 O 0.00 0.01 0.30 -2.69 -3.84 0.25 0.09 S8 S9 S10 S11 S12 S13 S14 K 0.00 0.00 -28.08 -7.49 -90.86 -0.69 -30.71 A -0.11 -0.20 -0.19 -0.03 0.02 -0.13 -0.07 B 0.10 0.31 0.25 -0.01 -0.06 0.08 0.03 C 0.07 -0.73 -0.44 0.02 0.06 -0.02 0.00 D -1.42 1.65 0.76 -0.02 -0.04 0.00 -0.01 E 5.62 -2.94 -1.02 0.00 0.02 0.00 0.01 F -12.91 3.85 1.01 0.00 -0.01 0.00 0.00 G 19.73 -3.66 -0.71 0.00 0.00 0.00 0.00 H -21.01 2.52 0.36 0.00 0.00 0.00 0.00 J 15.83 -1.25 -1.25 0.00 0.00 0.00 0.00 K -8.41 0.44 0.44 0.00 0.00 0.00 0.00 L 3.08 -0.11 -0.11 0.00 0.00 0.00 0.00 M -0.74 0.02 0.02 0.00 0.00 0.00 0.00 N 0.10 0.00 0.00 0.00 0.00 0.00 0.00 O -0.01 0.00 0.00 0.00 0.00 0.00 0.00

(86) In addition, the imaging optical system configured as described above may have the aberration characteristics illustrated in FIG. 2.

(87) One or more examples of an optical imaging system according to a second embodiment of the present disclosure are hereinafter described with reference to FIGS. 3 and 4.

(88) The optical imaging system according to the second embodiment of the present disclosure may include a first lens **210**, a second lens **220**, a third lens **230**, a fourth lens **240**, a fifth lens **250**, a sixth lens **260**, and a seventh lens **270**, and may further include a stop, a filter **280**, and an image sensor **290**.

(89) Lens characteristics (radii of curvature, thicknesses of lenses or distances between the lenses, refractive indices, Abbe numbers, and focal lengths) of each lens are shown in Table 3.

(90) TABLE-US-00003 TABLE 3 Radius of Thickness or Refractive Abbe Focal Surface No. Remark Curvature Distance Index number
Length S1 First Lens 1.99 0.778 1.547 56.1 4.5274 S2 8.76 0.171 S3 Second 6.26 0.225 1.680 19.2 -10.9616 Lens S4 3.35 0.396 S5 Third
Lens 22.08 0.338 1.547 56.1 35.9847 S6 -178.81 0.191 S7 Fourth Lens -18.04 0.326 1.680 19.2 -21.1484 S8 71.21 0.265 S9 Fifth Lens
8.02 0.290 1.621 26.0 26.5633 S10 15.41 0.547 S11 Sixth Lens 2.81 0.443 1.547 56.1 6.7139 S12 11.26 0.711 S13 Seventh -4.98 0.390
1.547 56.1 -3.7533 Lens S14 3.58 0.129 S15 Filter Infinity 0.110 1.519 64.2 S16 Infinity 0.691 S17 Imaging Infinity Plane

(91) Meanwhile, according to the present example of the second embodiment, an overall focal length f of the optical imaging system is 5.4 mm, $f12$ is 6.592 mm, Fno is 1.86, FOV is 78.7° , and $Img\ HT$ is 4.54 mm.

(92) Here, $f12$, Fno , FOV , and $Img\ HT$ are defined the same as in the first embodiment.

(93) In the second embodiment, the first lens **210** may have positive refractive power, and a first surface thereof may be convex while a second surface thereof may be concave.

(94) The second lens **220** may have negative refractive power, and a first surface thereof may be convex while a second surface thereof may be concave.

(95) The third lens **230** may have positive refractive power, and the first and second surfaces thereof may be convex.

(96) The fourth lens **240** may have negative refractive power, and the first and second surfaces thereof may be concave.

(97) The fifth lens **250** may have positive refractive power, and a first surface thereof may be convex in a paraxial area while a second surface thereof may be concave in the paraxial area.

(98) In addition, at least one inflection point may be formed on at least one of the first and second surfaces of the fifth lens **250**. For example, the first surface of the fifth lens **250** may be convex in a paraxial region, and may be concave at an edge thereof. In addition, the second surface of the fifth lens **250** may be concave in a paraxial region, and may be convex at an edge thereof.

(99) The sixth lens **260** may have positive refractive power, and a first surface thereof may be convex in a paraxial area while a second surface thereof may be concave in the paraxial area.

(100) In addition, at least one inflection point may be formed on at least one of the first and second surfaces of the sixth lens **260**. For example, the first surface of the sixth lens **260** may be convex in a paraxial region, and may be concave at an edge thereof. In addition, the second surface of the sixth lens **260** may be concave in a paraxial region, and may be convex at an edge thereof.

(101) The seventh lens **270** may have negative refractive power, and the first and second surfaces thereof may be concave in a paraxial area.

(102) In addition, at least one inflection point may be formed on at least one of the first and second surfaces of the seventh lens **270**. For example, the first surface of the seventh lens **270** may be concave in a paraxial region, and may be convex at an edge thereof. The second surface of the seventh lens **270** may be concave in a paraxial region, and may be convex at an edge thereof.

(103) Meanwhile, respective surfaces of the first to seventh lenses **210** to **270** may have aspherical coefficients as illustrated in Table 4. For example, all of object-side surfaces and image-side surfaces of the first to seventh lenses **210** to **270** may be aspherical.

(104) TABLE-US-00004 TABLE 4 S1 S2 S3 S4 S5 S6 S7 K -1.01 20.32 16.47 2.09 0.00 74.55 0.00 A 0.00 -0.05 -0.08 -0.10 -0.02 -0.08
-0.08 B 0.17 0.26 0.09 0.63 -0.47 0.29 0.14 C -0.98 -1.73 -0.24 -5.45 4.83 -2.44 -1.01 D 3.67 7.86 1.97 33.66 -31.25 12.92 4.73 E
-9.41 -23.90 -10.19 -139.72 133.64 -45.61 -15.11 F 17.06 50.25 32.28 403.66 -392.79 111.96 33.88 G -22.30 -75.07 -67.51 -833.27
814.85 -195.48 -54.19 H 21.25 80.82 97.06 1245.90 -1211.16 245.42 62.47 J -14.74 -62.90 -97.51 -1351.83 1294.55 -221.83 -52.07 K
7.36 35.06 68.38 1053.30 -986.34 142.90 31.14 L -2.57 -13.64 -32.80 -573.90 522.45 -63.94 -13.05 M 0.60 3.52 10.26 207.43 -182.73
18.87 3.65 N -0.08 -0.54 -1.89 -44.65 37.92 -3.30 -0.61 O 0.01 0.04 0.15 4.33 -3.54 0.26 0.05 S8 S9 S10 S11 S12 S13 S14 K 0.00 0.00
-23.48 -8.45 -92.11 -1.83 -27.15 A -0.09 -0.17 -0.18 0.00 0.05 -0.10 -0.06 B 0.02 0.18 0.18 -0.05 -0.08 0.03 0.00 C 0.27 -0.28 -0.24
0.04 0.06 0.01 0.02 D -1.79 0.50 0.38 -0.01 -0.02 -0.01 -0.02 E 5.89 -0.84 -0.52 0.00 0.00 0.00 0.01 F -12.49 1.10 0.52 0.01 0.00 0.00
0.00 G 18.25 -1.04 -0.36 0.00 0.00 0.00 0.00 H -18.86 0.71 0.18 0.00 0.00 0.00 0.00 J 13.91 -0.35 -0.06 0.00 0.00 0.00 0.00 K -7.26 0.12
0.01 0.00 0.00 0.00 0.00 L 2.62 -0.03 0.00 0.00 0.00 0.00 0.00 M -0.62 0.00 0.00 0.00 0.00 0.00 0.00 N 0.09 0.00 0.00 0.00 0.00 0.00 0.00
O -0.01 0.00 0.00 0.00 0.00 0.00 0.00

(105) In addition, the imaging optical system configured as described above may have the aberration characteristics illustrated in FIG. 4.

(106) One or more examples of an optical imaging system according to a third embodiment of the present disclosure are hereinafter described with reference to FIGS. 5 and 6.

(107) The optical imaging system according to the third embodiment of the present disclosure may include a first lens **310**, a second lens **320**, a third lens **330**, a fourth lens **340**, a fifth lens **350**, a sixth lens **360**, and a seventh lens **370**, and may further include a stop, a filter **380**, and an image sensor **390**.

(108) Lens characteristics (radii of curvature, thicknesses of lenses or distances between the lenses, refractive indices, Abbe numbers, and focal lengths) of each lens are shown in Table 5.

(109) TABLE-US-00005 TABLE 5 Radius of Thickness or Refractive Abbe Focal Surface No. Remark Curvature Distance Index number
Length S1 First Lens 1.99 0.774 1.547 56.1 4.5239 S2 8.84 0.178 S3 Second 6.27 0.225 1.680 19.2 -10.8704 Lens S4 3.34 0.390 S5 Third
Lens 19.34 0.324 1.547 56.1 34.7582 S6 -1047.67 0.188 S7 Fourth Lens -16.32 0.345 1.680 19.2 -20.5053 S8 96.08 0.272 S9 Fifth Lens
7.95 0.290 1.621 26.0 25.4679 S10 15.76 0.558 S11 Sixth Lens 2.76 0.436 1.547 56.1 6.7249 S12 10.50 0.713 S13 Seventh -4.97 0.380
1.547 56.1 -3.7462 Lens S14 3.58 0.053 S15 Filter Infinity 0.110 1.519 64.2 S16 Infinity 0.766 S17 Imaging Infinity Plane

(110) Meanwhile, according to the present example of the third embodiment, an overall focal length f of the optical imaging system is 4.785 mm, $f12$ is 6.608 mm, Fno is 1.86, FOV is 78.7° , and $Img\ HT$ is 4.54 mm.

(111) Here, $f12$, Fno , FOV , and $Img\ HT$ are defined the same as in the first embodiment.

(112) In the third embodiment, the first lens **310** may have positive refractive power, and a first surface thereof may be convex while a second surface thereof may be concave.

(113) The second lens **320** may have negative refractive power, and a first surface thereof may be convex while a second surface thereof may be concave.

(114) The third lens **330** may have positive refractive power, and the first and second surfaces thereof are convex.

(115) The fourth lens **340** may have negative refractive power, and the first and second surfaces thereof may be concave in a paraxial area.

(116) The fifth lens **350** may have positive refractive power, and a first surface thereof may be convex in a paraxial area while a second surface thereof may be concave in the paraxial area.

(117) In addition, at least one inflection point may be formed on at least one of the first and second surfaces of the fifth lens **350**. For example, the first surface of the fifth lens **350** may be convex in a paraxial region, and may be concave at an edge thereof. The second surface of the fifth lens **350** may be concave in a paraxial region, and may be convex at an edge thereof.

(118) The sixth lens **360** may have positive refractive power, and a first surface thereof may be convex in a paraxial area while a second surface thereof may be concave in the paraxial area.

(119) In addition, at least one inflection point may be formed on at least one of the first and second surfaces of the sixth lens **360**. For example, the first surface of the sixth lens **360** may be convex in a paraxial region, and may be concave at an edge thereof. The second surface of the sixth lens **360** may be concave in a paraxial region, and may be convex at an edge thereof.

(120) The seventh lens **370** may have negative refractive power, and the first and second surfaces thereof may be concave in a paraxial area.

(121) In addition, at least one inflection point may be formed on at least one of the first and second surfaces of the seventh lens **370**. For example, the first surface of the seventh lens **370** may be concave in a paraxial region, and may be convex at an edge thereof. The second surface of the seventh lens **370** may be concave in a paraxial region, and may be convex at an edge thereof.

(122) Meanwhile, respective surfaces of the first to seventh lenses **310** to **370** may have aspherical coefficients as illustrated in Table 6. For example, all of object-side surfaces and image-side surfaces of the first to seventh lenses **310** to **370** may be aspherical.

(123) TABLE-US-00006 TABLE 6 S1 S2 S3 S4 S5 S6 S7 K -1.02 21.20 16.53 2.08 0.00 95.00 0.00 A 0.00 -0.05 -0.08 -0.09 -0.03 -0.08 -0.09 B 0.18 0.25 0.09 0.61 -0.42 0.27 0.19 C -0.97 -1.68 -0.25 -5.07 4.26 -2.28 -1.42 D 3.42 7.54 2.30 30.19 -27.07 12.18 7.16 E -8.33 -22.72 -12.04 -120.94 113.90 -43.63 -24.43 F 14.39 47.43 38.18 337.63 -329.86 108.94 58.18 G -18.00 -70.44 -79.91 -674.53 675.14 -193.73 -98.49 H 16.49 75.50 114.92 977.93 -991.22 247.99 119.95 J -11.05 -58.57 -115.52 -1031.15 1047.52 -228.72 -105.38 K 5.35 32.57 81.08 782.69 -789.80 150.45 66.19 L -1.82 -12.66 -38.95 -416.49 414.30 -68.78 -28.99 M 0.41 3.27 12.20 147.38 -143.60 20.75 8.41 N -0.06 -0.50 -2.25 -31.13 29.55 -3.71 -1.45 O 0.00 0.03 0.18 2.97 -2.73 0.30 0.11 S8 S9 S10 S11 S12 S13 S14 K 0.00 0.00 -20.74 -8.58 -94.63 -1.66 -25.77 A -0.10 -0.17 -0.18 0.00 0.05 -0.10 -0.06 B 0.12 0.19 0.17 -0.06 -0.09 0.03 0.01 C -0.33 -0.33 -0.23 0.05 0.06 0.01 0.02 D 0.59 0.67 0.37 -0.01 -0.02 -0.01 -0.01 E -0.47 -1.19 -0.50 0.00 0.00 0.00 0.01 F -0.68 1.55 0.50 0.01 0.00 0.00 0.00 G 2.62 -1.46 -0.34 0.00 0.00 0.00 0.00 H -3.95 0.99 0.17 0.00 0.00 0.00 0.00 J 3.63 -0.48 -0.06 0.00 0.00 0.00 0.00 K -2.20 0.17 0.01 0.00 0.00 0.00 0.00 L 0.89 -0.04 0.00 0.00 0.00 0.00 0.00 M -0.23 0.01 0.00 0.00 0.00 0.00 0.00 N 0.03 0.00 0.00 0.00 0.00 0.00 0.00 O 0.00 0.00 0.00 0.00 0.00 0.00 0.00

(124) In addition, the imaging optical system configured as described above may have the aberration characteristics illustrated in FIG. 6.

(125) One or more examples of an optical imaging system according to a fourth embodiment of the present disclosure is hereinafter described with reference to FIGS. 7 and 8.

(126) The optical imaging system according to the fourth embodiment of the present disclosure may include a first lens **410**, a second lens **420**, a third lens **430**, a fourth lens **440**, a fifth lens **450**, a sixth lens **460**, and a seventh lens **470**, and may further include a stop, a filter **480**, and an image sensor **490**.

(127) Lens characteristics (radii of curvature, thicknesses of lenses or distances between the lenses, refractive indices, Abbe numbers, and focal lengths) of each lens are shown in Table 7.

(128) TABLE-US-00007 TABLE 7 Radius of Thickness or Refractive Abbe Focal Surface No. Remark Curvature Distance Index number Length S1 First Lens 2.05 0.841 1.547 56.1 4.6721 S2 8.84 0.165 S3 Second 6.52 0.220 1.680 19.2 -10.7590 Lens S4 3.40 0.399 S5 Third Lens 18.15 0.343 1.547 56.1 43.7093 S6 75.13 0.166 S7 Fourth Lens -1125.42 0.286 1.669 20.4 -89.3217 S8 63.08 0.528 S9 Fifth Lens 5.94 0.330 1.571 37.4 -24.0283 S10 4.06 0.292 S11 Sixth Lens 1.85 0.370 1.547 56.1 4.6942 S12 6.20 0.768 S13 Seventh -5.71 0.381 1.547 56.1 -3.6398 Lens S14 3.12 0.131 S15 Filter Infinity 0.110 1.519 64.2 S16 Infinity 0.670 S17 Imaging Infinity Plane

(129) Meanwhile, according to the present example of the fourth embodiment, an overall focal length f of the optical imaging system is 5.35 mm, $f12$ is 6.9706 mm, Fno is 1.79, FOV is 78.7° , and $Img\ HT$ is 4.54 mm.

(130) Here, $f12$, Fno , FOV , and $Img\ HT$ are defined the same as in the first embodiment.

(131) In the fourth embodiment, the first lens **410** may have positive refractive power, and a first surface thereof may be convex while a second surface thereof may be concave.

(132) The second lens **420** may have negative refractive power, and a first surface thereof may be convex while a second surface thereof may be concave.

(133) The third lens **430** may have positive refractive power, and a first surface thereof may be convex while a second surface thereof may be concave.

(134) The fourth lens **440** may have negative refractive power, and the first and second surfaces thereof may be concave.

(135) The fifth lens **450** may have negative refractive power, and a first surface thereof may be convex in a paraxial area while a second surface thereof may be concave in the paraxial area.

(136) In addition, at least one inflection point may be formed on at least one of the first and second surfaces of the fifth lens **450**. For example, the first surface of the fifth lens **450** may be convex in a paraxial region, and may be concave at an edge thereof. The second surface of the fifth lens **450** may be concave in a paraxial region, and may be convex at an edge thereof.

(137) The sixth lens **460** may have positive refractive power, and a first surface thereof may be convex in a paraxial area while a second surface thereof may be concave in the paraxial area.

(138) In addition, at least one inflection point may be formed on at least one of the first and second surfaces of the sixth lens **460**. For example, the first surface of the sixth lens **460** may be convex in a paraxial region, and may be concave at an edge thereof. The second surface of the sixth lens **460** may be concave in a paraxial region, and may be convex at an edge thereof.

(139) The seventh lens **470** may have negative refractive power, and the first and second surfaces thereof may be concave in a paraxial area.

(140) In addition, at least one inflection point may be formed on at least one of the first and second surfaces of the seventh lens **470**. For example, the first surface of the seventh lens **470** may be concave in a paraxial region, and may be convex at an edge thereof. The second surface of the seventh lens **470** may be concave in a paraxial region, and may be convex at an edge thereof.

(141) Meanwhile, respective surfaces of the first to seventh lenses **410** to **470** may have aspherical coefficients as illustrated in Table 8. For example, all of object-side surfaces and image-side surfaces of the first to seventh lenses **410** to **470** may be aspherical.

(142) TABLE-US-00008 TABLE 8 S1 S2 S3 S4 S5 S6 S7 K -1.06 19.90 16.01 1.68 0.00 -95.00 0.00 A 0.00 0.00 -0.14 -0.14 0.00 -0.11 -0.02 B 0.07 -0.39 0.67 1.21 -0.73 0.49 -0.97 C -0.27 2.39 -4.28 -10.28 6.52 -2.87 7.23 D 0.74 -8.67 19.66 58.76 -36.62 11.17 -32.52 E -1.58 21.02 -61.12 -225.35 137.17 -29.77 96.86 F 2.56 -35.60 132.71 602.62 -356.57 55.57 -200.92 G -3.11 43.16 -206.12 -1152.97 659.52 -73.28 298.37 H 2.80 -37.91 231.85 1599.06 -879.40 68.18 -321.49 J -1.84 24.16 -189.10 -1610.29 847.09 -44.01 251.76 K 0.87 -11.04 110.66 1165.18 -583.69 18.90 -141.79 L -0.29 3.53 -45.24 -590.00 280.36 -4.88 55.94 M 0.06 -0.75 12.26 198.35 -89.11 0.54

-14.67 N -0.01 0.09 -1.98 -39.75 16.84 0.04 2.30 O 0.00 -0.01 0.14 3.59 -1.43 -0.01 -0.16 S8 S9 S10 S11 S12 S13 S14 K 0.00 0.00
-97.16 -7.60 -17.35 -2.18 -26.40 A -0.06 -0.18 -0.18 0.03 0.10 -0.15 -0.08 B -0.16 0.25 0.10 -0.12 -0.17 0.09 0.04 C 1.10 -0.33 0.03
0.15 0.19 -0.03 0.00 D -3.97 0.43 -0.13 -0.13 -0.15 0.00 0.00 E 9.30 -0.52 0.13 0.07 0.08 0.00 0.00 F -15.11 0.55 -0.08 -0.02 -0.03
0.00 0.00 G 17.62 -0.43 0.03 0.01 0.01 0.00 0.00 H -14.98 0.24 -0.01 0.00 0.00 0.00 0.00 J 9.30 -0.10 0.00 0.00 0.00 0.00 K -4.17
0.03 0.00 0.00 0.00 0.00 0.00 L 1.32 -0.01 0.00 0.00 0.00 0.00 0.00 M -0.28 0.00 0.00 0.00 0.00 0.00 0.00 N 0.04 0.00 0.00 0.00 0.00 0.00
0.00 O 0.00 0.00 0.00 0.00 0.00 0.00 0.00

(143) In addition, the imaging optical system configured as described above may have the aberration characteristics illustrated in FIG. 8.

(144) One or more examples of an optical imaging system according to a fifth embodiment of the present disclosure are hereinafter described with reference to FIGS. 9 and 10.

(145) The optical imaging system according to the fifth embodiment of the present disclosure may include a first lens 510, a second lens 520, a third lens 530, a fourth lens 540, a fifth lens 550, a sixth lens 560, and a seventh lens 570, and may further include a stop, a filter 580, and an image sensor 590.

(146) Lens characteristics (radii of curvature, thicknesses of lenses or distances between the lenses, refractive indices, Abbe numbers, and focal lengths) of each lens are shown in Table 9.

(147) TABLE-US-00009 TABLE 9 Radius of Thickness or Refractive Abbe Focal Surface No. Remark Curvature Distance Index number
Length S1 First Lens 2.04 0.839 1.547 56.1 4.6439 S2 8.77 0.168 S3 Second 6.60 0.220 1.680 19.2 -10.4084 Lens S4 3.37 0.397 S5 Third
Lens 14.78 0.354 1.547 56.1 36.8975 S6 54.84 0.177 S7 Fourth Lens 141.33 0.279 1.669 20.4 -82.8101 S8 39.75 0.528 S9 Fifth Lens 5.46
0.325 1.571 37.4 -25.0493 S10 3.87 0.304 S11 Sixth Lens 1.86 0.332 1.547 56.1 4.7871 S12 6.00 0.778 S13 Seventh -5.81 0.380 1.547
56.1 -3.6128 Lens S14 3.06 0.137 S15 Filter Infinity 0.110 1.519 64.2 S16 Infinity 0.641 S17 Imaging Infinity Plane

(148) Meanwhile, according to the present example of the fifth embodiment, an overall focal length f of the optical imaging system is 5.35 mm, $f12$ is 7.0122 mm, Fno is 1.79, FOV is 78.7°, and $Img\ HT$ is 4.54 mm.

(149) Here, $f12$, Fno , FOV , and $Img\ HT$ are defined the same as in the first embodiment.

(150) In the fifth embodiment, the first lens 510 may have positive refractive power, and a first surface thereof may be convex while a second surface thereof may be concave.

(151) The second lens 520 may have negative refractive power, and a first surface thereof may be convex while a second surface thereof may be concave.

(152) The third lens 530 may have positive refractive power, and a first surface thereof may be convex while a second surface thereof may be concave.

(153) The fourth lens 540 may have negative refractive power, and a first surface thereof may be convex while a second surface thereof may be concave.

(154) The fifth lens 550 may have negative refractive power, and a first surface thereof may be convex in a paraxial area while a second surface thereof may be concave in the paraxial area.

(155) In addition, at least one inflection point may be formed on at least one of the first and second surfaces of the fifth lens 550. For example, the first surface of the fifth lens 550 may be convex in a paraxial region, and may be concave at an edge thereof. The second surface of the fifth lens 550 may be concave in a paraxial region, and may be convex at an edge thereof.

(156) The sixth lens 560 may have positive refractive power, and a first surface thereof may be convex in a paraxial area while a second surface thereof may be concave in the paraxial area.

(157) In addition, at least one inflection point may be formed on at least one of the first and second surfaces of the sixth lens 560. For example, the first surface of the sixth lens 560 may be convex in a paraxial region, and may be concave at an edge thereof. The second surface of the sixth lens 560 may be concave in a paraxial region, and may be convex at an edge thereof.

(158) The seventh lens 570 may have negative refractive power, and the first and second surfaces thereof may be concave in a paraxial area.

(159) In addition, at least one inflection point may be formed on at least one of the first and second surfaces of the seventh lens 570. For example, the first surface of the seventh lens 570 may be concave in a paraxial region, and may be convex at an edge thereof. The second surface of the seventh lens 570 may be concave in a paraxial region, and may be convex at an edge thereof.

(160) Meanwhile, respective surfaces of the first to seventh lenses 510 to 570 may have aspherical coefficients as illustrated in Table 10. For example, all of object-side surfaces and image-side surfaces of the first to seventh lenses 510 to 570 may be aspherical.

(161) TABLE-US-00010 TABLE 10 S1 S2 S3 S4 S5 S6 S7 K -1.06 19.74 16.19 1.76 0.00 49.72 0.00 A -0.02 -0.02 -0.12 -0.12 0.01
-0.11 -0.03 B 0.27 -0.18 0.51 0.84 -0.95 0.64 -0.85 C -1.27 1.36 -3.31 -6.98 8.53 -4.70 6.55 D 3.86 -5.60 16.26 40.30 -47.54 22.18
-29.72 E -8.01 15.19 -53.72 -156.30 175.59 -70.51 88.86 F 11.82 -28.66 123.06 422.44 -449.03 155.93 -184.71 G -12.65 38.62
-200.34 -816.74 816.52 -245.30 274.70 H 9.91 -37.61 234.85 1144.57 -1070.42 277.95 -296.22 J -5.68 26.50 -198.60 -1164.56 1014.16
-227.34 231.95 K 2.35 -13.38 119.95 851.25 -687.71 132.92 -130.49 L -0.69 4.71 -50.41 -435.30 325.30 -54.16 51.36 M 0.13 -1.10
13.99 147.73 -101.90 14.60 -13.42 N -0.02 0.15 -2.31 -29.87 18.99 -2.34 2.09 O 0.00 -0.01 0.17 2.72 -1.59 0.17 -0.15 S8 S9 S10 S11
S12 S13 S14 K 0.00 0.00 -99.00 -8.27 -23.03 -1.95 -24.23 A -0.09 -0.21 -0.20 0.01 0.08 -0.15 -0.08 B -0.01 0.23 0.13 -0.08 -0.14
0.09 0.03 C 0.42 -0.07 0.06 0.13 0.18 -0.03 0.00 D -1.83 -0.49 -0.32 -0.12 -0.16 0.00 0.00 E 4.56 1.16 0.48 0.07 0.09 0.00 0.00 F -7.68
-1.47 -0.43 -0.03 -0.04 0.00 0.00 G 9.23 1.22 0.27 0.01 0.01 0.00 0.00 H -8.07 -0.72 -0.11 0.00 0.00 0.00 0.00 J 5.16 0.30 0.04 0.00 0.00
0.00 0.00 K -2.38 -0.09 -0.01 0.00 0.00 0.00 0.00 L 0.77 0.02 0.00 0.00 0.00 0.00 0.00 M -0.17 0.00 0.00 0.00 0.00 0.00 0.00 N 0.02 0.00
0.00 0.00 0.00 0.00 0.00 0.00 0.00 O 0.00 0.00 0.00 0.00 0.00 0.00 0.00

(162) In addition, the imaging optical system configured as described above may have the aberration characteristics illustrated in FIG. 10.

(163) Table 11 shows the conditional expression values of the imaging optical system according to the examples of each embodiment.

(164) TABLE-US-00011 TABLE 11 Conditional Embodiment Embodiment Embodiment Embodiment Embodiment Expression 1 2 3 4 5
 $f1/f$ 0.8314 0.8384 0.9454 0.8733 0.8680 $v1-v2$ 36.9 36.9 36.9 36.9 36.9 $v1-v3$ 0 0 0 0 0 $v1-v5$ 30.1 30.1 30.1 18.7 18.7 $f2/f$ -1.9692
-2.0299 -2.2718 -2.0110 -1.9455 $f3/f$ 6.7879 6.6638 7.2640 8.1700 6.8967 $t4/f$ 3.5695 3.9164 4.2853 16.6957 15.4785 $f6/f$ 1.3932 1.2433
1.4054 0.8774 0.8948 $f7/f$ -0.7223 -0.6951 -0.7829 -0.6803 -0.6753 TTL/f 1.1121 1.1113 1.2540 1.1215 1.1161 $f2/f3$ -0.2901 -0.3046
-0.3127 -0.2461 -0.2821 BFL/f 0.1711 0.1722 0.1941 0.1703 0.1660 $D1/f$ 0.0325 0.0317 0.0372 0.0308 0.0314 FOV 78.7 78.7 78.7 78.7
78.7 Fno 1.87 1.86 1.86 1.79 1.79 $TTL/(2 * Img\ HT)$ 0.6614 0.6609 0.6609 0.6608 0.6576 $f12/f$ 1.2225 1.2207 1.3810 1.3029 1.3124

(165) As set forth above, according to an embodiment in the present disclosure, an optical imaging system is capable of having high resolution and a small size in a direction from an object side of the optical imaging system to an imaging plane of the optical imaging system.

(166) While specific examples have been shown and described above, it will be apparent after an understanding of the disclosure of this application that various changes in form and details may be made in these examples without departing from the spirit and scope of the claims and their equivalents. The examples described herein are to be considered in a descriptive sense only, and not for purposes of

limitation. Descriptions of features or aspects in each example are to be considered as being applicable to similar features or aspects in other examples. Suitable results may be achieved if the described techniques are performed in a different order, and/or if components in a described system, architecture, device, or circuit are combined in a different manner, and/or replaced or supplemented by other components or their equivalents. Therefore, the scope of the disclosure is defined not by the detailed description, but by the claims and their equivalents, and all variations within the scope of the claims and their equivalents are to be construed as being included in the disclosure.

Claims

1. An optical imaging system, comprising: a first lens having positive refractive power, a second lens having negative refractive power, a third lens having positive refractive power, a fourth lens having negative refractive power, a fifth lens having positive refractive power, a sixth lens having a concave image-side surface in a paraxial region, and a seventh lens having a negative refractive power, sequentially arranged from an object side, wherein the optical imaging system includes a total of seven lenses, wherein the optical imaging system satisfies $f_3/f > 1.5$ and $-2.0 < f_2/f_3 < 0.0$, where a focal length of the second lens is f_2 , a focal length of the third lens is f_3 , and an overall focal length of the optical imaging system is f , wherein $F_{no} < 1.9$, where an F-number of the optical imaging system is F_{no} , wherein $v_1 - v_3 < 25$, where an Abbe number of the first lens is v_1 , and an Abbe number of the third lens is v_3 , wherein $TTL/(2 * \text{Img HT}) < 0.7$, where a distance on an optical axis from an object-side surface of the first lens to an imaging plane of an image sensor is TTL , and half of a diagonal length of the imaging plane of the image sensor is Img HT , and wherein a refractive index of the second lens is 1.66 or greater and a refractive index of the fourth lens is 1.66 or greater.
 2. The optical imaging system of claim 1, wherein the first lens comprises a convex object-side surface and a concave image-side surface.
 3. The optical imaging system of claim 2, wherein the second lens comprises a convex object-side surface and a concave image-side surface.
 4. The optical imaging system of claim 3, wherein the third lens comprises a convex image-side surface, and the fourth lens comprises a concave image-side surface.
 5. The optical imaging system of claim 3, wherein the sixth lens comprises a convex object-side surface and a concave image side surface, and the seventh lens comprises a concave image-side surface.
 6. The optical imaging system of claim 5, wherein the sixth lens comprises positive refractive power.
 7. The optical imaging system of claim 1, wherein $0 < f_1/f < 2.0$, where a focal length of the first lens is f_1 .
 8. The optical imaging system of claim 7, wherein $-10.0 < f_2/f < 0$.
 9. The optical imaging system of claim 8, wherein $|f_4/f| > 3.0$, where a focal length of the fourth lens is f_4 .
 10. The optical imaging system of claim 8, wherein $1.0 < f_{12}/f < 1.5$, where a synthetic focal length of the first lens and the second lens is f_{12} .
 11. The optical imaging system of claim 1, wherein $25 < v_1 - v_2 < 45$, where an Abbe number of the first lens is v_1 , and an Abbe number of the second lens is v_2 .
 12. The optical imaging system of claim 1, wherein $TTL/f < 1.4$, where $BFL/f < 0.4$, where a distance on the optical axis from an image-side surface of the seventh lens to the imaging plane of the image sensor is BFL .
 13. The optical imaging system of claim 10, wherein $D1/f < 0.1$, where a distance on the optical axis from an image-side surface of the first lens to an object-side surface of the second lens is $D1$.
 14. The optical imaging system of claim 1, wherein $FOV < 80^\circ$, where a field of view of the optical imaging system is FOV .
 15. An optical imaging system, comprising: a first lens having positive refractive power, a second lens having negative refractive power, a third lens having positive refractive power, a fourth lens having negative refractive power, a fifth lens having positive refractive power, a sixth lens having a concave image-side surface in a paraxial region, and a seventh lens having negative refractive power, sequentially arranged from an object side, wherein the optical imaging system includes a total of seven lenses, wherein the optical imaging system satisfies $f_3/f > 1.5$ and $-2.0 < f_2/f_3 < 0.0$, where a focal length of the second lens is f_2 , a focal length of the third lens is f_3 , and an overall focal length of the optical imaging system is f , wherein $F_{no} < 1.9$, where an F-number of the optical imaging system is F_{no} , wherein $v_1 - v_3 < 25$, where an Abbe number of the first lens is v_1 , and an Abbe number of the third lens is v_3 , wherein $TTL/(2 * \text{Img HT}) < 0.7$, where a distance on an optical axis from an object-side surface of the first lens to an imaging plane of an image sensor is TTL , and half of a diagonal length of the imaging plane of the image sensor is Img HT , and wherein a refractive index of the fourth lens is 1.66 or greater.
-