

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407525
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Mondello; Antonino et al.

Verifying vehicular identity

Abstract

Apparatuses, methods, and systems for verifying a vehicular identity are described. An embodiment includes a processing resource, memory, and a vehicular communication component configured to verify an identity of the particular vehicle using a public key, wherein the public key is received in response to a departure of the particular vehicle, and request, in response to verifying the identity of the particular vehicle, data corresponding to information associated with the departure of the particular vehicle.

Inventors:	Mondello; Antonino (Messina, IT), Troia; Alberto (Munich, DE)
Applicant:	Micron Technology, Inc. (Boise, ID)
Family ID:	72605214
Assignee:	Micron Technology, Inc. (Boise, ID)
Appl. No.:	17/685861
Filed:	March 03, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220224548 A1	Jul. 14, 2022

Related U.S. Application Data

continuation parent-doc US 16362954 20190325 US 11271755 child-doc US 17685861

Publication Classification

Int. Cl.: H04L29/06 (20060101); H04L9/08 (20060101); H04L9/30 (20060101); H04L9/32 (20060101)

U.S. Cl.:

CPC **H04L9/3268** (20130101); **H04L9/0825** (20130101); **H04L9/0866** (20130101);
H04L9/30 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10725764	12/2019	Rivas Silva	N/A	H04H 20/91
10855460	12/2019	Takemori	N/A	H04L 9/3242
2009/0235071	12/2008	Bellur	713/158	H04W 12/082
2014/0075186	12/2013	Austen	713/156	H04L 63/061
2015/0052352	12/2014	Dolev	713/156	H04L 9/3278
2016/0112206	12/2015	Cizas	713/158	H04L 9/3268
2016/0127895	12/2015	Bangole	380/279	H04W 4/48
2016/0210858	12/2015	Foster	N/A	G08G 1/0965
2016/0249180	12/2015	Li	N/A	G08G 1/20
2016/0344509	12/2015	Hayman	N/A	H04W 4/44
2017/0111353	12/2016	Tschache	N/A	H04L 9/006
2017/0170972	12/2016	Wu	N/A	B64D 45/0051
2018/0026949	12/2017	Kimn	713/156	H04W 12/069
2018/0027600	12/2017	Lawlis	713/168	H04W 12/02
2018/0040246	12/2017	Yonemura	N/A	H04W 4/027
2018/0159693	12/2017	Condeixa	N/A	H04L 63/0823
2018/0232819	12/2017	Stöcker	N/A	G01D 4/004
2018/0272886	12/2017	Stöcker	N/A	B60L 53/305
2018/0274943	12/2017	Stöcker	N/A	G06Q 40/04
2019/0053051	12/2018	Yu	N/A	H04L 61/00
2019/0141048	12/2018	Fallah	N/A	H04L 9/0643
2019/0190987	12/2018	Waffner	N/A	H04L 67/12
2019/0215404	12/2018	Stöcker	N/A	H04W 8/02
2019/0238343	12/2018	Racklyeft	N/A	H04L 9/3268
2019/0268277	12/2018	Asthana	N/A	H04L 9/50
2019/0278899	12/2018	Chen	N/A	G06F 21/34
2019/0281027	12/2018	Cao	N/A	H04L 63/0442
2019/0315245	12/2018	Kinomura	N/A	B60L 53/66
2019/0325125	12/2018	Pantfoerder	N/A	H04W 8/005
2019/0335304	12/2018	Yabuuchi	N/A	H04W 4/44
2019/0373137	12/2018	Krukar	N/A	H04N 1/444
2020/0008027	12/2019	Yabuuchi	N/A	G08G 1/096725
2020/0021981	12/2019	Mondello	N/A	H04L 63/061
2020/0029209	12/2019	Nölscher	N/A	H04W 12/069
2020/0145191	12/2019	Qi	N/A	H04L 9/3239
2020/0153636	12/2019	Takada	N/A	H04W 4/40

2020/0177398	12/2019	Takemori	N/A	H04L 63/0823
2020/0228988	12/2019	Yang	N/A	H04L 63/1466
2020/0234582	12/2019	Mintz	N/A	G08G 1/096811
2020/0312136	12/2019	Mondello	N/A	H04L 9/3242
2020/0313909	12/2019	Mondello	N/A	H04L 9/0866
2021/0073811	12/2020	Chan	N/A	G06Q 20/0658
2021/0075408	12/2020	Noguchi	N/A	G11C 11/40618
2021/0075600	12/2020	Trevethan	N/A	H04L 9/3066
2024/0056299	12/2023	Xie	N/A	H04L 9/3239
2024/0317179	12/2023	Sun	N/A	H04W 12/08

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
111163453	12/2019	CN	N/A
2571328	12/2012	EP	N/A
3393100	12/2017	EP	N/A
2011215712	12/2010	JP	N/A
20190102409	12/2018	KR	N/A
20190130114	12/2018	KR	N/A
20200110740	12/2019	KR	N/A
2019-027886	12/2018	WO	N/A
2019-027889	12/2018	WO	N/A

OTHER PUBLICATIONS

U.S. Appl. No. 15/853,498, entitled, “Physical Unclonable Function Using Message Authentication Code”, filed Dec. 22, 2017, 28 pages. cited by applicant

U.S. Appl. No. 16/201,652, entitled, “Parking Infrastructure Powered by a Decentralized, Distributed Database”, filed Nov. 27, 2018, 27 pages. cited by applicant

U.S. Appl. No. 15/993,119, entitled, “Transmission of Vehicle Route Information by Passive Devices”, filed May 30, 2018, 25 pages. cited by applicant

U.S. Appl. No. 16/034,763, entitled, “Secure Vehicular Communication”, filed Jul. 13, 2018, 37 pages. cited by applicant

U.S. Appl. No. 16/034,809, entitled, “Secure Vehicular Services Communication”, filed Jul. 13, 2018, 36 pages. cited by applicant

PCT International Application Number PCT/IB2019/000089, entitled, “Method for Improving Safety of a Component or System Running a Firmware or a Finite State Machine”, filed Feb. 22, 2019, 42 pages. cited by applicant

International Search Report and Written Opinion from related International Application No. PCT/us2020/021630, dated Jul. 2, 2020, 13 pages. cited by applicant

Sang-Woo Lee, Republic of Korea, “Revised Baseline Text For X.itssec-2, Security Guidelines for v2x Communication Systems; C522”, Jan. 22-30, 2019, Geneva, 37 pages. cited by applicant

“Intelligent Transport Systems (ITS); Security; ITS Communications Security Architecture and Security Management”, ETSI TS 102 940 V2.0.7, European Telecommunications Standards Institute, France, Apr. 16, 2018, 42 pages. cited by applicant

“Design Principles for C-ITS Short Term Certificate Policy”, ETSI Draft; European Telecommunications Standards Institute, France, May 17, 2016, 7 pages. cited by applicant

Primary Examiner: Shiferaw; Eleni A

Assistant Examiner: Hussein; Hassan A

Background/Summary

PRIORITY INFORMATION (1) This application is a continuation of U.S. application Ser. No. 16/362,954, filed on Mar. 25, 2019, the contents of which are incorporated herein by reference.

TECHNICAL FIELD

(1) The present disclosure relates generally to apparatuses and methods, and more particularly, to verifying a vehicular identity.

BACKGROUND

(2) Memory devices are typically provided as internal, semiconductor, integrated circuits and/or external removable devices in computers or other electronic devices. There are many different types of memory including volatile and non-volatile memory. Volatile memory can require power to maintain its data and can include random-access memory (RAM), dynamic random access memory (DRAM), and synchronous dynamic random access memory (SDRAM), among others. Non-volatile memory can provide persistent data by retaining stored data when not powered and can include NAND flash memory, NOR flash memory, read only memory (ROM), and resistance variable memory such as phase change random access memory (PCRAM), resistive random access memory (RRAM), and magnetic random access memory (MRAM), among others.

(3) Memory devices can be combined together to form a solid state drive (SSD), an embedded Multi Media Card (eMMC), and/or a universal flash storage (UFS) device. An SSD, eMMC, and/or UFS device can include non-volatile memory (e.g., NAND flash memory and/or NOR flash memory), and/or can include volatile memory (e.g., DRAM and/or SDRAM), among various other types of non-volatile and volatile memory. Non-volatile memory may be used in a wide range of electronic applications such as personal computers, portable memory sticks, digital cameras, cellular telephones, portable music players such as MP3 players, movie players, among others.

(4) Flash memory devices can include memory cells storing data in a charge storage structure such as a floating gate, for instance. Flash memory devices typically use a one-transistor memory cell that allows for high memory densities, high reliability, and low power consumption. Resistance variable memory devices can include resistive memory cells that can store data based on the resistance state of a storage element (e.g., a resistive memory element having a variable resistance).

(5) Memory cells can be arranged into arrays, and memory cells in an array architecture can be programmed to a target (e.g., desired) state. For instance, electric charge can be placed on or removed from the charge storage structure (e.g., floating gate) of a flash memory cell to program the cell to a particular data state. The stored charge on the charge storage structure of the cell can indicate a threshold voltage (V_t) of the cell. A state of a flash memory cell can be determined by sensing the stored charge on the charge storage structure (e.g., the V_t) of the cell.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates a diagram of a system including a vehicle capable of communicating with an emergency vehicle and a network for verifying an identity of the emergency vehicle in accordance with an embodiment of the present disclosure.

(2) FIG. 2 is a block diagram of an example emergency vehicle in accordance with an embodiment of the present disclosure.

(3) FIG. 3 is a block diagram of an example vehicle in accordance with an embodiment of the

present disclosure.

- (4) FIG. 4A is a block diagram of an example system including a plurality of traffic control devices and a control node in accordance with an embodiment of the present disclosure.
- (5) FIG. 4B illustrates a diagram of an example area, including traffic control devices, vehicles, and emergency vehicles in accordance with an embodiment of the present disclosure.
- (6) FIG. 5 is a block diagram of an example system including communication components in accordance with an embodiment of the present disclosure.
- (7) FIG. 6 is a block diagram of an example process to determine a number of parameters in accordance with an embodiment of the present disclosure.
- (8) FIG. 7 is a block diagram of an example process to verify a certificate in accordance with an embodiment of the present disclosure.
- (9) FIG. 8 is a block diagram of an example process to determine a number of parameters in accordance with an embodiment of the present disclosure.
- (10) FIG. 9 is a block diagram of an example process to verify a signature in accordance with an embodiment of the present disclosure.
- (11) FIG. 10 illustrates a diagram of a portion of a memory array having a number of physical blocks in accordance with an embodiment of the present disclosure.
- (12) FIG. 11A is a block diagram of a computing system including a host and an apparatus in the form of a memory device in accordance with an embodiment of the present disclosure.
- (13) FIG. 11B is a block diagram of a network of computing systems which can include many computing nodes in a public and/or private network connected in a wired and/or wireless manner using wireless protocols such as peer to peer and Internet Protocol (IP) in accordance with an embodiment of the present disclosure.
- (14) FIG. 12 illustrates an example of an exchange between a global ledger block chain and local ledger block chains as can be operated upon by circuitry and stored in a memory for secure updates stored in memory in accordance with an embodiment of the present disclosure.
- (15) FIG. 13 illustrates an example of a local ledger block chain for secure updates stored in memory in accordance with an embodiment of the present disclosure.
- (16) FIG. 14A illustrates an example of a pair of registers used to define a secure memory array in accordance with an embodiment of the present disclosure.
- (17) FIG. 14B illustrates a diagram of a portion of a memory array that includes a secure memory array defined in accordance with an embodiment of the present disclosure.
- (18) FIG. 15 is a block diagram of an example memory device in accordance with an embodiment of the present disclosure.

DETAILED DESCRIPTION

- (19) The present disclosure includes apparatuses, methods, and systems for verifying a vehicular identity. An embodiment includes a processing resource, memory, and a vehicular communication component configured to verify an identity of the particular vehicle using a public key, wherein the public key is received in response to a departure of the particular vehicle, and request, in response to verifying the identity of the particular vehicle, data corresponding to information associated with the departure of the particular vehicle.
- (20) Emergency entities (e.g., vehicle) such as ambulances, police cars, and/or firefighting cars have previously communicated with other vehicles using flashing lights, sirens, etc. However, using flashing lights and/or sirens to communicate with other vehicles are limited in that no further information (e.g., destination of an emergency vehicle) are communicated to the other vehicles. Embodiments of the present disclosure provides a mechanism of not only communicating those information to vehicles other than an emergency vehicle, but also providing a security to the communication. For example, the communication between the emergency vehicle and the vehicular vehicles (e.g., and/or an additional emergency vehicles) may be intercepted and/or manipulated by a hacker or other entities in order to change the communication, repeat the communication to gain

unauthorized access to the emergency vehicle or other vehicles, etc. In such instances, the emergency vehicle may not provide an ability to verify its identity to insure to the recipient of the communication that the emergency vehicle is authorized to provide such communication (e.g., to pull over, to stop the vehicle, to reduce a speed of the vehicle, to clear or exit a roadway, to park as soon as possible, to assist others on the road in an emergency, etc.). Absent an ability to verify the identity of the emergency vehicle, the communication may be unauthorized and may negatively affect the other vehicles or request the vehicular vehicle to perform actions that the emergency vehicle does not have authorization to request.

(21) Accordingly, embodiments of the present disclosure provides benefits such as making sure that requests made to other vehicles are from an authorized emergency vehicle. The embodiments of the present disclosure, therefore, result in secure communication and an increase in compliance by other vehicle's as verification of the identity of the emergency entity can indicate the emergency entity has proper authority to request such compliance.

(22) As used herein, “a”, “an”, or “a number of” can refer to one or more of something, and “a plurality of” can refer to two or more such things. For example, a memory device can refer to one or more memory devices, and a plurality of memory devices can refer to two or more memory devices. Additionally, the designators “R”, “B”, “S”, and “N”, as used herein, particularly with respect to reference numerals in the drawings, indicates that a number of the particular feature so designated can be included with a number of embodiments of the present disclosure. The number may be the same or different between designations.

(23) The figures herein follow a numbering convention in which the first digit or digits correspond to the drawing figure number and the remaining digits identify an element or component in the drawing. Similar elements or components between different figures may be identified by the use of similar digits. For example, **204** may reference element “**04**” in FIG. **2**, and a similar element may be referenced as **304** in FIG. **3**.

(24) FIG. **1** illustrates a diagram of a system **100** including a vehicle **104** capable of communicating with an emergency vehicle **102** and a network **106** for verifying an identity of the emergency vehicle **102** in accordance with an embodiment of the present disclosure. The vehicle **104** can be an autonomous vehicle, a traditional non-autonomous vehicle, a service vehicle, or the like, and that can be referred to as an apparatus. (e.g., vehicle that is not an emergency vehicle and/or an emergency vehicle that is not in service). The emergency vehicle **102** can be various types of emergency vehicles such as police cars, firefighting cars, and/or ambulances that can dispatch (e.g., initiate a departure) to a destination for various emergencies. It is noted that while two vehicles (e.g., one vehicle and one emergency vehicle) are shown in FIG. **1**, embodiments of the present disclosure do not limit systems to a particular quantity of vehicles.

(25) The network **106** can support a distributed ledger technology (DLT) such as “block chain” technology. A distributed ledger is a database that is spread over several nodes or computing devices. A “block chain” is a continuously growing encrypted list of records. Block chain is one form a DLT in which multiple nodes (nodes **408** and/or **410** as described in connection with FIG. **4**) can share and store the distributed list of records in a peer to peer network manner. As described herein a “block” in block chain is collection of information, e.g., data, headers, transactions, encryption, etc. A block may be added to the growing list of records in the ledger if it is validated. Blocks are added to the block chain ledger in chronological order.

(26) The network **106** can be a database storing those data associated with vehicles registered to an area associated with the network **106**. As used herein, an area can refer to a settlement or locality. For example, an area can encompass a portion or an entirety of a city, a town, a municipality, a township, a zip code, a borough, a village, or a hamlet. In some embodiments, an area can be geographically defined and can be bounded by particular coordinates (e.g., latitude and longitude) and/or geographic features (e.g., roads, rivers, etc.). Accordingly, vehicles (e.g., emergency vehicle **102** and/or vehicle **104**) can access network **106** for data having information associated with

vehicles registered to the area associated with the network **106**. In some examples, the vehicles may access other network and/or database associated with a different area for, for example, data having information associated with vehicles registered to the different area.

(27) A presence of the emergency vehicle **102** can be, while the emergency vehicle **102** is on its dispatch, detected (e.g., determined) in various ways. In one example, a dispatch of the emergency vehicle **102** may be detected by a detecting/communicating device distributed over a particular area. As an example, the emergency vehicle **102** may be visually detected by a monitoring device (e.g., surveillance camera) implemented in one or more traffic control devices. In this example, a particular traffic control device that has detected the dispatch of the emergency vehicle **102** can communicate (e.g., propagate) the dispatch to other nodes of a network (e.g., network **106**), such as other traffic control devices. As an example, the emergency vehicle **102** can, as it initiates its dispatch, provide a notice to a control node such that the control node can propagate the received notice to traffic control devices within the network. As used herein, a “traffic control device” refers to a device configured to inform, guide, and/or control traffic. Example traffic control devices include, but are not limited to: traffic signs, arrow boards, warning signs, variable message signs, and traffic lights. The detected dispatch can be ultimately communicated to the vehicle **104** along with other data for verifying an identity of the emergency vehicle **102**.

(28) In another example, the dispatch of the emergency vehicle **102** can be detected directly by the vehicle **104**. As an example, the emergency vehicle **102** can, while heading to a destination, broadcast its presence such that, when vehicle **104** is within a particular proximity to emergency vehicle **102**, the emergency vehicle **102** can be detected by the vehicle **104**. Further details of verifying an identity of vehicles (e.g., emergency vehicles) are described in connection with FIG. 7.

(29) Upon emergency vehicle **102** being detected, data corresponding to particular information can be communicated to vehicle **104**, and the vehicle **104** can verify an identity of the emergency vehicle **102** based on the received information. The information can include, as described herein, a public key, a public identification, and/or a certificate generated at the emergency vehicle **102**. In an example where the emergency vehicle **102** is directly detected by the vehicle **104**, the information may be provided from the emergency vehicle directly.

(30) In another example where the emergency vehicle **102** is detected by an entity other than the vehicle **104**, the information may be retrieved, as an example, from and provided (e.g., to the vehicle **104**) via the network **106**. The information may be retrieved via an intermediary device such as a query device. As used herein, a query device may be referred to as a programmable silicon device that is capable of performing high-speed symbolic pattern matching, which allows comprehensive search and analysis of complex and/or unstructured database (e.g., network **106**).

(31) Upon verifying an identity of the emergency vehicle **102**, various information associated with a dispatch of the emergency vehicle **102** can be communicated to the vehicle **102** either directly and/or indirectly. As an example, a route to a destination of the emergency vehicle **102** can be provided to vehicle **104**, as described herein in further details.

(32) The data exchanged among emergency vehicle **102**, vehicle **104**, and/or network **106** can be performed using a number of encryption and/or decryption methods as described below. The securing of the data can insure that nefarious activity is prevented from interfering with the emergency and/or vehicle data provided to the vehicular entity and/or the emergency entity.

(33) FIG. 2 is a block diagram of an example emergency vehicle **202**, in accordance with an embodiment of the present disclosure. The emergency vehicle **202** can be analogous to emergency vehicle **102** as described in connection with FIG. 1.

(34) The emergency vehicle **202** can include an emergency computing device **212**, such as an on-board computer. As shown in FIG. 2, the emergency computing device **212** can include a processor **214** coupled to an emergency communication component **216**, such as a reader, writer, transceiver, and/or other computing device or circuitry capable of performing the functions described below to exchange information, that is coupled to (e.g., or includes) an antenna **219**. The emergency

communication component **216** can include logic and/or circuitry that is used to perform the actions recited below (e.g., encrypt/decrypt, execute instructions, etc.). Emergency communication component **216** can include a processing resource **217** coupled to a memory **218**, such as a non-volatile flash memory, although embodiments are not so limited. The emergency computing device **212** can be coupled to or within an emergency vehicle **202** such as an ambulance, a police vehicle, a fire truck, etc.

(35) Emergency communication component **216** can transmit, broadcast, and/or provide data to various entities such as computing devices (e.g., vehicle **304** and/or traffic control devices **410** described in connection with FIGS. **3** and **4**, respectively) and/or network **406** shown in FIG. **4**. Similarly, emergency communication component **216** can receive traffic, road, and/or additional data from other computing devices, such as a vehicle **304** and/or traffic control device **410** described in association with FIG. **3** and FIG. **4**, respectively, or an additional electronic sign, electronic and/or digitized roadway, etc. As an example, a roadway and/or sign can be coupled to, or have embedded within the roadway and/or sign, a communication component (similar to emergency communication component **216**) that can communicate data associated with road/sign conditions, road/sign status, etc.

(36) FIG. **3** is a block diagram of an example vehicle **304** in accordance with an embodiment of the present disclosure. The vehicle **304** can be analogous to vehicle **104** as described in connection with FIG. **1**. The vehicle **304** can be coupled to a vehicular computing device **342**. The vehicular computing device **342** can use various communication methods, such as wireless communication, to communicate with the emergency computing device **212**. In the example of FIG. **3**, the vehicular computing device **342** can include a processor **344** to execute instructions and control functions of the vehicular computing device **342**. The processor **344** may be coupled to a vehicular communication component **346**, such as a reader, writer, transceiver, and/or other computing device or circuitry capable of performing the functions described below to exchange information, that is coupled to (e.g., or includes) an antenna **349**. Vehicular communication component **346** can include a processing resource **347** coupled to a memory **348**, such as a non-volatile flash memory, although embodiments are not so limited. The antenna **349** of the vehicular computing device **342** can be in communication with, e.g., communicatively coupled to, the antenna **219** of the emergency computing device **212** shown in FIG. **2**, and/or network **406** and/or traffic control devices **410** shown in FIG. **4**.

(37) In some examples, antennas **349** and **219** can be loop antennas configured as inductor coils, etc. Antenna **219** can loop around emergency computing device **212**, for example. Antenna **219** can generate an electromagnetic field in response to current flowing through antenna **219**. For example, the strength of the electromagnetic field can depend on the number of coils and the amount of current. The electromagnetic field generated by antenna **219** can induce current flow in an antenna **349** that powers the respective vehicular computing device **342**. As an example, antenna **219** in FIG. **1** can induce current flow in antenna **349** when the vehicular computing device **342** is brought within a communication distance (e.g., a communication range) of the antenna **219**. For example, the communication distance can depend on the strength of the electromagnetic field generated by antenna **219**. The electromagnetic field generated by antenna **219** can be set, by the number of coils of antenna **219** and/or the current passing through antenna **219**, such that the communication distance can span from the location of the emergency computing device **212** to the vehicular computing device **342**. In some examples, the communication distance can be about 50 centimeters to about 100 centimeters on either side of the emergency computing device **212**. In the alternative, the communication distance can depend on the strength of the electromagnetic field generated by antenna **349**. In this instance, the electromagnetic field generated by antenna **349** can be set by the number of coils of **349** and/or the current passing through antenna **349**.

(38) In some examples, the vehicular computing device **342** can include a number of wireless communication devices, such as transmitters, transponders, transceivers, or the like. As an example,

the vehicular communication component **346** can be such a wireless communication device. Wireless communication that can be used can include near field communication (NFC) tags, RFID tags, or the like. In at least one embodiment, wireless communication can be performed using non-volatile storage components that can be respectively integrated into chips, such as microchips. Each of the respective chips can be coupled to a respective antenna, such as antenna **349**. The respective storage components can store respective emergency, notification, vehicle, road, and/or sign data. Further wireless communication that can be used by the vehicular communication component **346** (e.g., as well as by the emergency communication component **216**) can include different generations of broadband mobile telecommunication technologies (e.g., first through fifth generation (1-5G)), device-to-device (e.g., vehicle to vehicle (v2v)) to communication including Bluetooth, Zigbee, 1-5G and/or long-term evolution (LTE) device-to-device communication technologies, and/or other wireless communication utilizing an additional device (e.g., WiFi utilizing an access point AP) may be utilized in communicating with different entities.

(39) Emergency data can be transmitted from the emergency communication component **216** of the emergency computing device **212** to the vehicular communication component **346** of the vehicular computing device **342** in response to the emergency computing device **212** passing within the communication distance of the respective vehicular computing device **342**. The emergency and/or notification data can be transmitted in the form of signals, such as radio frequency signals. For example, the emergency communication component **216** of the emergency computing device **212** and the vehicular communication component **346** of the vehicular computing device **342** can communicate using radio frequency signals.

(40) For examples in which wireless communication devices are NFC tags, emergency communication component **216** of the emergency computing device **212** can be an NFC reader and can communicate with wireless communication devices using an NFC protocol that can be stored in memory **218** for processing by processing resource **217**. In one example, the emergency communication component **216** and wireless communication devices, such as vehicular communication component **346**, can communicate at about 13.56 mega-Hertz according to the ISO/IEC 18000-3 international standard for passive RFID for air interface communications. For example, the information can be transmitted in the form of a signal having a frequency of about 13.56 mega-Hertz.

(41) In some examples, the emergency computing device **212** and/or the vehicular computing device **342** can use a passive wireless communication device, such as a short-range communication device (e.g., an NFC tag) that can be as described previously. The NFC tag can include a chip having a non-volatile storage component that stores information, such as emergency information, identity information, emergency device or apparatus information, and/or information about an emergency, a roadway, other vehicles, such as the location, quantity, etc. of other vehicles. Further, the NFC tag can include an antenna.

(42) The emergency communication component **216** can receive information from the NFC tag and/or can transmit information to the NFC tag. In some examples, a communications device can include a reader (e.g., an NFC reader), such as an emergency device reader.

(43) The memory **218** of the emergency communications component **216** can include instructions that operate according to an NFC protocol that allows emergency communications component **216** to communicate with the NFC tag. For example, the emergency communications component **216** and the NFC tag can communicate using the NFC protocol, such as at about 13.56 mega-Hertz and according to the ISO/IEC 18000-3 international standard.

(44) The emergency communications component **216** may also communicate with an emergency operations center, such as a hospital, a fire station, a police station, etc. For example, emergency communications component **216** can be wirelessly coupled or hardwired to the emergency operations center. In some examples, emergency communications component **216** can communicate with the emergency operations center via WIFI or over the Internet. The emergency

communications component **216** can energize the NFC tag when the antenna **219** associated with the NFC tag is brought within a communication distance of antenna **349**, as described previously. The communication distance can be shorter and bring the devices relatively near each other and can provide better security and use less power than previous approaches that use RFID tags.

(45) FIG. 4 is a block diagram of an example system, including a plurality of traffic control devices and a control node, in accordance with an embodiment of the present disclosure. As illustrated in FIG. 4, a system can include a plurality of traffic control devices **410-1** (traffic control device 1), **410-2** (traffic control device 2), **410-3** (traffic control device 3) (cumulatively referred to as “traffic control devices **410**”). It is noted that while three traffic control devices are shown in FIG. 4, embodiments of the present disclosure do not limit systems to a particular quantity of traffic control devices. As discussed below in connection with FIG. 4B, the traffic control devices **410** can be associated with a particular area, in some embodiments.

(46) Each of the traffic control devices **410** can operate as a node of a peer-to-peer network **406** to host a decentralized, distributed database (e.g., implemented using a block chain technique). Accordingly, the present disclosure makes alternate reference to both “traffic control devices **410**” and “nodes **410**.” The decentralized, distributed database can be configured to store redundant copies of activity records related to traffic, such as vehicles registered to the network **406**, emergency vehicles registered to the network **406**, etc. For example, each respective traffic control device **410** can broadcast a traffic record in the peer to peer network **406** to cause one or more additional nodes **410** in the peer to peer network **406** to store the traffic activity record in the decentralized, distributed database having a copy of the traffic activity record maintained by each of the one or more additional nodes **410**. The traffic control devices **410** can control traffic based, at least in part, on network consensus on the activity records stored in the decentralized, distributed database. For example, each node **410** in the network **406** can independently determine the validity of a record based on copies of records stored in the node **410**. In some embodiments, when a majority of active nodes **410** in the network **406** approves the validity of a record, the network **406** can reach network consensus that the activity record is valid; and the validated activity record can be used to control the operations of the traffic control devices **410**.

(47) A control node **408** can be configured to monitor traffic conditions within the area, determine the presence of vehicles in the area, and/or control the overall traffic flow through the area via the traffic control devices **410**. In some embodiments, the control node **408** can be associated with (e.g., located at) an emergency operations center, such as a hospital, a fire station, a police station, a dispatch center, etc. The control node **408** can be configured as the “owner” of the block chain, apprising the control node **408** of a status of the block, and allowing the control node **408** to create a backup of the network **406** and/or reconfigure the network **406**. In some embodiments, the control node **408** maintains a record of vehicles that are registered to the block chain and/or the network **406**. The control node **408** can be a distributed and/or local artificial intelligence in communication with the traffic control devices **410**. As described further in connection with FIG. 4B, the control node **408** can be further configured to determine a route (e.g., path) of vehicles, such as emergency vehicle **102** described in connection with FIG. 1.

(48) As described herein, the network **406** can be configured as a database storing data (e.g., corresponding to information) that can be retrieved by control node **408**, traffic control devices **410**, query device (e.g., as described in connection with FIG. 1), and/or vehicles, such as emergency vehicle **102** and/or vehicle **104** as described in connection with FIG. 1. The retrieved data can be communicated to a vehicle that is within, for example, a particular proximity to one of nodes of the network **406**. As an example, when a particular vehicle is within a particular proximity to the traffic control device **404-1**, data retrieved from the network **408** (e.g., nodes of the network **408**) can be communicated to the traffic control device **404-1** such that the data can be further communicated to the particular vehicle via the traffic control device **404-1**. In this example, the traffic control device is configured as intermediary device to communicate data between network

406 and vehicles.

(49) In some examples, the network **406** may further include nodes other than control node and/or nodes corresponding to traffic control devices. As an example, some of the nodes of the network **406** can include node configured as a database for storing indexed data from those data obtained by other nodes (e.g., control node **408** and/or traffic control devices **410**). As used herein, indexed data refers to data corresponding to information that are subject to a same category (e.g., transactions performed by a particular user). Often, information subject to a same category are stored over multiple blocks; therefore, retrieving the information may require reading all blocks of a block chain, which can be performed in a substantially inefficient manner in a block chain system.

Having a node (e.g., or multiple nodes) configured to as database dedicated for indexed data, therefore, can reduce a necessity of reading multiple blocks to retrieve particular information, which provides benefits such as faster processing query requests for the particular information.

(50) FIG. **4B** illustrates a diagram of an example area, including traffic control devices, vehicles, and emergency vehicles in accordance with an embodiment of the present disclosure. As illustrated in FIG. **4B**, an area can include a plurality of traffic control devices **410-1** and **410-2** (cumulatively referred to as “traffic control devices **410**”). It is noted that while two traffic control devices are shown in the area illustrated in FIG. **4B**, embodiments of the present disclosure do not limit a quantity of traffic control devices in an area.

(51) As previously discussed, each of the traffic control devices **410** can operate as a node of a peer-to-peer network to host a decentralized, distributed database (e.g., implemented using a block chain technique). As previously discussed, a control node **408** can be configured to monitor traffic conditions within the area, determine the presence of an emergency vehicle **402** in the area, control the overall traffic flow through the area via the traffic control devices **410**.

(52) The emergency vehicle **402** can be registered with the block chain and/or the network of nodes (e.g., the traffic control devices **410-3** and the control node **408**). In some embodiments, the emergency vehicle **402** can be permanently registered. In some embodiments, a status of the emergency vehicle **402** can be determined and/or set by the control node **408**. For instance, a vehicle normally not designated as an “emergency vehicle” can be temporarily promoted to the status of the emergency vehicle **402**.

(53) A route to a destination **421** can be communicated and/or determined in various ways. As an example, a route to the destination **421** can be determined by the emergency vehicle **402** and subsequently communicated to the control node **408**. In another example, a route to the destination **421** can be determined by the control node **408** and communicated to the emergency vehicle **402**. In this example, a determined route (e.g., determined by the control node **408**) can be communicated to the emergency vehicle **402**, which can travel based on the determined route, and/or the control node **408** can simultaneously guide the emergency vehicle **402** to the destination **421**.

(54) Data from emergency vehicle **402** can be directly and/or indirectly communicated to vehicles **404-1**, **404-2**, **404-3**, **404-4**, and/or **404-5** (collectively referred to as vehicles **404**). For example, the data may be communicated to vehicles **404** via control node **408** and/or traffic control devices **410**. In this example, a dispatch of emergency vehicle **402** along with data to be transmitted to vehicles **404** can be detected/received at a network (e.g., network **406**) including a control node **408** and traffic control node **410**. The control node **408** may redirect the data to those traffic control devices that are capable of communicating directly with vehicles **404**, as further described below.

(55) As illustrated in FIG. **4B**, vehicles **404-1** and **404-2** are within a particular proximity to emergency vehicle **402** (e.g., as indicated by an dotted circle **407-1**). Stated differently, vehicles **404-1** and **404-2** may be close (e.g., to emergency vehicle) sufficient to communicate with emergency vehicle **402** via device to device (D2D) and/or vehicle to vehicle (V2V) communication technologies, as previously described in connection with FIGS. **2** and **3**. In this example, accordingly, data being broadcasted by the emergency vehicle **402**, while on its dispatch, may be

directly communicable to and receivable at vehicles **404-1** and **404-2**.

(56) As illustrated in FIG. 4B, vehicles **404-3**, **404-4**, and **404-5** are within a particular proximity to traffic control devices **410-1** and **410-2**, respectively, without being within a particular proximity to emergency vehicle **402** (e.g., as indicated by dotted circles **407-2** and **407-3**, respectively). State differently, vehicles **404-3** and **404-4** may be close (e.g., to traffic control device **410-1**) sufficient to traffic control device **410-1** to be able to communicate with the traffic control device **410-1**. Similarly, vehicle **404-5** may be close (e.g., to traffic control device **410-2**) sufficient to traffic control device **410-2** to be able to communicate with the traffic control device **410-2**.

(57) Accordingly, although data and/or information being broadcasted by the emergency vehicle **402** may not be communicable to and/or receivable at vehicles **404-1**, **404-2**, and/or **404-3**, the data and/or information can be received indirectly via traffic control devices **410-1** and **410-2**. As an example, the emergency vehicle **402** may firstly communicate data with control node **408** and/or other traffic control devices **410**, which can further communicate the data with traffic control devices **410-1** and/or **410-2**, which can communicate the data to vehicles **404-3**, **404-4**, and/or **404-5**. In this example, the data that would not have been communicated directly from emergency vehicle **402** can still be communicated, which can cover a wider communication area.

(58) Therefore, various ways of verifying an identity of emergency vehicles (e.g., emergency vehicle **402**) and further exchanging information associated with dispatches of the emergency vehicles may be simultaneously and/or selectively employed to cover different scenarios. As an example, information associated with dispatches of emergency vehicles can be communicated to vehicles (e.g., vehicles **404-3**, **404-4**, and/or **404-5**) indirectly via traffic control devices (e.g., traffic control devices **410-1** and/or **410-2**) to cover those locations, in which vehicles may not be able to directly communicate with emergency vehicles. At the same time, direct communication between emergency vehicles and other vehicles may be simultaneously employed, which can provide benefits such as a faster exchange of information.

(59) The verification can involve providing a public key, a public identification, and a certificate (e.g., identity information) that were generated at emergency vehicle **402** to vehicle **404**. As described herein, the identity information can be received directly from emergency vehicle **402** or indirectly from traffic control devices **410**. As an example, the traffic control device **410-1** can provide identity information to vehicles **404-3** and **404-4**, while the traffic control device **410-2** can provide identity information to vehicles **404-5**.

(60) In response to receiving identity information, respective vehicles **404** can perform a particular process to verify an identity of emergency vehicle **402** as further described in connection with FIG. 8. When an identity of emergency vehicle **402** is verified, respective vehicle **404** can provide a host message back to emergency vehicle **404**, respective traffic control devices **410**, which can propagate to other traffic control devices **410** and/or emergency vehicle **404**. As an example, vehicles **404-1** and **404-2** that are within a communicable proximity to emergency vehicle **402** can provide a host message directly back to emergency vehicle **402**, while vehicles **404-3**, **404-4**, and/or **404-5** can provide a host message back to traffic control devices **410-1** and **410-2**, respectively. In contrast, when an identity of emergency vehicle **402** is not verified at respective vehicle **404**, the received identity information may be discarded.

(61) In some embodiments, the identity information may be provided as encrypted. For example, control node **408** and/or traffic control devices **410** can encrypt identity information of emergency vehicle **402** using a public key previously received from respective vehicles **404** such that the encrypted identity information, when received by the respective vehicles **404**, can be decrypted using a private key that was generated along with the public key of the respective vehicles **404**. As an example, vehicles **404-3** and **404-4** may receive identity information encrypted at traffic control device **410-1**, and vehicle **404-5** may receive identity information encrypted at traffic control device **410-2**. Further details of encryption and/or decryption are described in connection with FIGS. 6-8.

(62) Upon providing a host message, further information can be received directly and/or indirectly (e.g., via traffic control devices **410**) from emergency vehicle **402**. Such information can include a type of emergency vehicle (e.g., police cars, firefighting cars, and/or ambulances), a type of emergency (e.g., reason for the dispatch), a vehicle identification number (VIN), a Unified Diagnostic Services (UDS) key, license plate combinations (e.g., numbers and/or letters) a destination of the dispatch, an expected travel time to the destination, a route to the destination, and/or a distance between the emergency vehicle and the destination, although embodiments are not so limited. The information can, in some embodiments, further includes various requests (e.g., a notification to perform an action) from emergency vehicle **402** such as to pull over, to stop the vehicle, to reduce a speed of the vehicle, to clear or exit a roadway, to park as soon as possible, to assist others on the road in an emergency, etc.

(63) FIG. 5 is a block diagram of an example system including communication components in accordance with an embodiment of the present disclosure. For example, as illustrated in FIG. 5, communication (e.g., communication **554** and/or **556**) can be between a first communication component **516** (that may be analogous to emergency communication component **202** described in connection with FIG. 2) and a second communication component **546** (e.g., that may be analogous to vehicular communication component **346** described in connection with FIG. 3). However, embodiments are not so limited. For example, communication (e.g., communication **554** and/or **556**) can be between vehicles (e.g., vehicles **104**) and other devices (e.g., memory devices **1012**) that can be implemented in control node **408** and/or traffic control device **410**.

(64) A computing device can boot in stages using layers, with each layer authenticating and loading a subsequent layer and providing increasingly sophisticated runtime services at each layer. A layer can be served by a prior layer and serve a subsequent layer, thereby creating an interconnected web of the layers that builds upon lower layers and serves higher order layers. As is illustrated in FIG. 5, Layer 0 (“L.sub.0”) **551** and Layer 1 (“L.sub.1”) **553** are within the emergency communication component **516**. Layer 0 **551** can provide a Firmware Derivative Secret (FDS) key **552** to Layer 1 **553**. The FDS key **552** can describe the identity of code of Layer 1 **553** and other security relevant data. In an example, a particular protocol (such as robust internet of things (RIOT) core protocol) can use the FDS **552** to validate code of Layer 1 **553** that it loads. In an example, the particular protocol can include a device identification composition engine (DICE) and/or the RIOT core protocol. As an example, an FDS can include Layer 1 firmware image itself, a manifest that cryptographically identifies authorized Layer 1 firmware, a firmware version number of signed firmware in the context of a secure boot implementation, and/or security-critical configuration settings for the device. A device secret **558** can be used to create the FDS **552** and be stored in memory of the emergency communication component **516**, such that FDS **552** is unique to emergency communication component **516**.

(65) The emergency communication component **516** can transmit data, as illustrated by arrow **554**, to the vehicular communication component **546**. The transmitted data can include a vehicular identification that is public (e.g., **765** in FIG. 7), a certificate (e.g., a vehicular certificate **781**), and/or a vehicular public key (e.g., **783**). Layer 2 (“L.sub.2”) **555** of the vehicular communication component **546** can receive the transmitted data and execute the data in operations of the operating system (“OS”) **557** and on a first application **559-1** and a second application **559-2**.

(66) In an example operation, the emergency communication component **516** can read the device secret **558**, hash an identity of Layer 1 **553**, and perform a calculation including:

$$K_{sub.L1} = KDF[Fs(s), Hash(\text{“immutable information”})]$$

where $K_{sub.L1}$ is a vehicular public key, KDF (e.g., KDF defined in the National Institute of Standards and Technology (NIST) Special Publication 800-108) is a key derivation function (e.g., HMAC-SHA256), and $Fs(s)$ is the device secret **558**. FDS **552** can be determined by performing:
$$FDS = HMAC-SHA256[Fs(s), SHA256(\text{“immutable information”})]$$

(67) Likewise, the vehicular communication component **546** can transmit data, as illustrated by

arrow 556, including an identification that is public (e.g., vehicular public identification), a certificate (e.g., a vehicular certificate), and/or a public key (e.g., vehicular public key).

(68) FIG. 6 is a block diagram of an example process to determine a number of parameters in accordance with an embodiment of the present disclosure. FIG. 6 is an example of a determination of the parameters including emergency public identification, emergency certificate, and emergency public key that are then sent, indicated by arrow 654, to Layer 2 (e.g., Layer 2 555) of a vehicular communication component (e.g., 546 in FIG. 5). Layer 0 (“L.sub.0”) 651 in FIG. 6 corresponds to Layer 0 551 in FIG. 5 and likewise FDS 652 corresponds to FDS 552, Layer 1 653 corresponds to Layer 1 553, and arrows 654 and 656 correspond to arrows 554 and 556, respectively.

(69) The FDS 652 from Layer 0 651 is sent to Layer 1 653 and used by an asymmetric ID generator 661 to generate a public identification (“ID.sub.lk public”) 666 and a private identification 667. In the abbreviated “ID.sub.lk public,” the “lk” indicates Layer k (in this example Layer 1), and the “public” indicates that the identification is openly shared. The public identification (“ID.sub.L1public”) 666 is illustrated as shared by the arrow extending to the right and outside of Layer 1 653 of emergency communication component. The generated private identification 667 is used as a key input into an encryptor 673. The encryptor 673 can be any processor, computing device, etc. used to encrypt data.

(70) Layer 1 653 of an emergency communication component can include an asymmetric key generator 663. In at least one example, a random number generator (RND) 636 can optionally input a random number into the asymmetric key generator 663. The asymmetric key generator 663 can generate a public key (“K.sub.Lk public”) 684 (referred to as a vehicular public key) and a private key (“K.sub.LK private”) 671 (referred to as a vehicular private key) associated with an emergency communication component such as emergency communication component 516 in FIG. 5. The emergency public key 684 can be an input (as “data”) into the encryptor 673. The encryptor 673 can generate a result K’675 using the inputs of the emergency private identification 667 and the emergency public key 684. The emergency private key 671 and the result K’675 can be input into an additional encryptor 677, resulting in output K” 679. The output K” 679 is emergency certificate (“ID.sub.L1 certificate”) 682 transmitted to the Layer 2 (555 of FIG. 5). The vehicular certificate 682 can provide an ability to verify and/or authenticate an origin of data sent from the emergency communication component. As an example, data sent from the emergency communication component can be associated with an identity of the emergency communication component by verifying the certificate, as will be described further in association with FIG. 7. Further, the emergency public key (“K.sub.L1 public key”) 684 can be transmitted to Layer 2. Therefore, the public identification 666, the certificate 682, and the public key 684 of a Layer 1 653 of an emergency communication component can be transmitted to Layer 2 of a vehicular communication component.

(71) FIG. 7 is a block diagram of an example process to determine a number of parameters in accordance with an embodiment of the present disclosure. FIG. 7 illustrates a Layer 2 755 of a vehicular communication component (e.g., vehicular communication component 546 in FIG. 4B) generating a vehicular identification (“ID.sub.L2 public”) 765, an vehicular certificate (“ID.sub.L2 Certificate”) 781, and a vehicular public key (“K.sub.L2 public key”) 783.

(72) The vehicular public key (“K.sub.L1 public key”) 784 transmitted from Layer 1 of the vehicular communication component to Layer 2 755 of a vehicular communication component (e.g., vehicular component 546 as described in FIG. 5), is used by an asymmetric ID generator 762 of the vehicular communication component to generate a public identification (“ID.sub.lk public”) 765 and a private identification 768 of the vehicular communication component. In the abbreviated “ID.sub.lk public,” the “lk” indicates Layer k (in this example Layer 2), and the “public” indicates that the identification is openly shared. The public identification 765 is illustrated as shared by the arrow extending to the right and outside Layer 2 755. The generated private identification 768 is used as a key input into an encryptor 774.

(73) As shown in FIG. 7, the vehicular certificate **782** and public identification **766**, along with the vehicular public key **784**, are used by a certificate verifier **799**. The certificate verifier **799** can verify the vehicular certificate **782** received from the vehicular communication component, and determine, in response to the vehicular certificate **782** being verified or not being verified, whether to accept or discard data received from the vehicular communication component. Further details of verifying a vehicular certificate **781** are further described herein (e.g., in connection with FIG. 9).

(74) Layer 2 **755** of the vehicular communication component can include an asymmetric key generator **764**. In at least one example, a random number generator (RND) **738** can optionally input a random number into the asymmetric key generator **764**. The asymmetric key generator **764** can generate a public key (“K.sub.Lk public”) **783** (referred to as a vehicular public key) and a private key (“K.sub.LK private”) **772** (referred to as a vehicular private key) associated with a vehicular communication component such as vehicular communication component **546** in FIG. 5. The vehicular public key **783** can be an input (as “data”) into the encryptor **774**. The encryptor **774** can generate a result K' **776** using the inputs of the vehicular private identification **768** and the vehicular public key **783**. The vehicular private key **772** and the result K' **776** can be input into an additional encryptor **778**, resulting in output K'' **780**. The output K'' **780** is the vehicular certificate (“ID.sub.L2 certificate”) **781** transmitted back to the Layer 1 (**553** of FIG. 5). The vehicular certificate **781** can provide an ability to verify and/or authenticate an origin of data sent from the vehicular communication component. As an example, data sent from the vehicular communication component can be associated with an identity of the vehicular communication component by verifying the certificate, as will be described further in association with FIG. 7. Further, the vehicular public key (“K.sub.L2 public key”) **783** can be transmitted to Layer 1. Therefore, the public identification **765**, the certificate **781**, and the vehicular public key **783** of the vehicular communication component can be transmitted to Layer 1 of a vehicular communication component.

(75) In an example, in response to a vehicular communication component receiving a public key from a vehicular communication component, the vehicular communication component can encrypt data to be sent to the vehicular communication component using the vehicular public key. Vice versa, the vehicular communication component can encrypt data to be sent to the vehicular communication component using the vehicular public key. In response to the vehicular communication component receiving data encrypted using the vehicular public key, the vehicular communication component can decrypt the data using its own vehicular private key. Likewise, in response to the vehicular communication component receiving data encrypted using the vehicular public key, the vehicular communication component can decrypt the data using its own vehicular private key. As the vehicular private key is not shared with another device outside the vehicular communication component and the vehicular private key is not shared with another device outside the vehicular communication component, the data sent to the vehicular communication component and the vehicular communication component remains secure.

(76) FIG. 8 is a block diagram of an example process to verify a certificate in accordance with an embodiment of the present disclosure. In the illustrated example of FIG. 8, a public key **883**, a certificate **881**, and a public identification **865** is provided from a communication component (e.g., from Layer 1 **553** of emergency communication component **516** in FIG. 5). The data of the certificate **881** and the emergency public key **883** can be used as inputs into a decryptor **885**. The decryptor **885** can be any processor, computing device, etc used to decrypt data. The result of the decryption of the certificate **881** and the emergency public key **883** can be used as an input into a secondary decryptor **887** along with the public identification, result in an output. The A comparison **889** can be performed between emergency public key **883** and the output from the decryptor **887** to indicate, whether the certificate is verified, resulting in a yes or no **891** as an output. In response to the certificate being verified, data received from the device being verified can be accepted, decrypted, and processed. In response to the certificate not being verified, data received from the

device being verified can be discarded, removed, and/or ignored. In this way, nefarious devices sending nefarious data can be detected and avoided. As an example, a hacker sending data to be processed can be identified and the hacking data not processed.

(77) FIG. 9 is a block diagram of an example process to verify a signature in accordance with an embodiment of the present disclosure. In the instance where a device is sending data that may be verified in order to avoid subsequent repudiation, a signature can be generated and sent with data. As an example, a first device may make a request of a second device and once the second device performs the request, the first device may indicate that the first device never made such a request. An anti-repudiation approach, such as using a signature, can avoid repudiation by the first device and insure that the second device can perform the requested task without subsequent difficulty.

(78) A vehicle **904** (such as vehicle **104** in FIG. 1) can send data **990** to an emergency vehicle **902** (such as vehicle **102** in FIG. 1). The vehicle **904** can generate, at **994**, a signature **996** using a remote private key **972**. The signature **996** can be transmitted to the emergency vehicle **902**. The emergency vehicle **902** can verify, at **998**, using data **992** and the vehicle public key **969**. In this way, signature verification operates by using a private key to encrypt the signature and a public key to decrypt the signature. In this way, the private key used to generate a unique signature can remain private to the device sending the signature while allowing the receiving device to be able to decrypt the signature using the public key of the sending device for verification. This is in contrast to encryption/decryption of the data, which is encrypted by the sending device using the public key of the receiving device and decrypted by the receiving device using the private key of the receiver. In at least one example, the vehicle can verify the digital signature by using an internal cryptography process (e.g., Elliptical Curve Digital signature (ECDSA) or a similar process.

(79) FIG. 10 illustrates a diagram of a portion of a memory array **1001** having a number of physical blocks in accordance with an embodiment of the present disclosure. Memory array **1001** can be, for example, a flash memory array such as a NAND, and/or NOR flash memory array. In one example embodiment, the memory array **1001** is a NOR flash memory array. As an additional example, memory array **1001** can be a resistance variable memory array such as a PCRAM, RRAM, MMRAM, or spin torque transfer (STT) array, among others. However, embodiments of the present disclosure are not limited to a particular type of memory array. Further, memory array **1001** can be a secure memory array, as will be further described herein. Further, although not shown in FIG. 10, memory array **1001** can be located on a particular semiconductor die along with various peripheral circuitry associated with the operation thereof.

(80) As shown in FIG. 10, memory array **1001** has a number of physical blocks **1007-0** (BLOCK **0**), **1007-1** (BLOCK **1**), . . . , **1007-B** (BLOCK **B**) of memory cells. The memory cells can be single level cells and/or multilevel cells such as, for instance, two level cells, triple level cells (TLCs) or quadruple level cells (QLCs). As an example, the number of physical blocks in memory array **1001** may be 128 blocks, 512 blocks, or 1,024 blocks, but embodiments are not limited to a particular power of two or to any particular number of physical blocks in memory array **1001**.

(81) A number of physical blocks of memory cells (e.g., blocks **1007-0**, **1007-1**, . . . , **1007-B**) can be included in a plane of memory cells, and a number of planes of memory cells can be included on a die. For instance, in the example shown in FIG. 10, each physical block **1007-0**, **1007-1**, . . . , **1007-B** can be part of a single die. That is, the portion of memory array **1001** illustrated in FIG. 10 can be a die of memory cells.

(82) As shown in FIG. 10, each physical block **1007-0**, **1007-1**, . . . , **1007-B** includes a number of physical rows (e.g., **1003-0**, **1003-1**, . . . , **1003-R**) of memory cells coupled to access lines (e.g., word lines). The number of rows (e.g., word lines) in each physical block can be thirty two rows, but embodiments are not limited to a particular number of rows **1003-0**, **1003-1**, . . . , **1003-R** per physical block. Further, although not shown in FIG. 10, the memory cells can be coupled to columns of sense lines (e.g., data lines and/or digit lines).

(83) As one of ordinary skill in the art will appreciate, each row **1003-0**, **1003-1**, . . . , **1003-R** can

include a number of pages of memory cells (e.g., physical pages). A physical page refers to a unit of programming and/or sensing (e.g., a number of memory cells that are programmed and/or sensed together as a functional group). In the embodiment shown in FIG. 1, each row **1003-0**, **1003-1**, . . . , **1003-R** comprises one physical page of memory cells. However, embodiments of the present disclosure are not so limited. For instance, in an embodiment, each row can comprise multiple physical pages of memory cells (e.g., one or more even pages of memory cells coupled to even-numbered data lines, and one or more odd pages of memory cells coupled to odd numbered data lines). Additionally, for embodiments including multilevel cells, a physical page of memory cells can store multiple pages (e.g., logical pages) of data (e.g., an upper page of data and a lower page of data, with each cell in a physical page storing one or more bits towards an upper page of data and one or more bits towards a lower page of data).

(84) As shown in FIG. 10, a page of memory cells can comprise a number of physical sectors **1005-0**, **1005-1**, . . . , **1005-S** (e.g., subsets of memory cells). Each physical sector **1005-0**, **1005-1**, . . . , **1005-S** of cells can store a number of logical sectors of data. Additionally, each logical sector of data can correspond to a portion of a particular page of data. As an example, a first logical sector of data stored in a particular physical sector can correspond to a logical sector corresponding to a first page of data, and a second logical sector of data stored in the particular physical sector can correspond to a second page of data. Each physical sector **1005-0**, **1005-1**, . . . , **1005-S**, can store system and/or user data, and/or can include overhead data, such as error correction code (ECC) data, logical block address (LBA) data, and metadata.

(85) Logical block addressing is a scheme that can be used by a host for identifying a logical sector of data. For example, each logical sector can correspond to a unique logical block address (LBA). Additionally, an LBA may also correspond (e.g., dynamically map) to a physical address, such as a physical block address (PBA), that may indicate the physical location of that logical sector of data in the memory. A logical sector of data can be a number of bytes of data (e.g., 256 bytes, 512 bytes, 1,024 bytes, or 4,096 bytes). However, embodiments are not limited to these examples.

(86) It is noted that other configurations for the physical blocks **1007-0**, **1007-1**, . . . , **1007-B**, rows **1003-0**, **1003-1**, . . . , **1003-R**, sectors **1005-0**, **1005-1**, . . . , **1005-S**, and pages are possible. For example, rows **1003-0**, **1003-1**, . . . , **1003-R** of physical blocks **1007-0**, **1007-1**, . . . , **1007-B** can each store data corresponding to a single logical sector which can include, for example, more or less than 512 bytes of data.

(87) FIG. 11A is a block diagram of a computing system **1100** including a host **1137** and an apparatus in the form of a memory device **1141** in accordance with an embodiment of the present disclosure. As used herein, an “apparatus” can refer to, but is not limited to, any of a variety of structures or combinations of structures, such as a circuit or circuitry, a die or dice, a module or modules, a device or devices, or a system or systems, for example. Further, in an embodiment, computing system **1100** can include a number of memory devices analogous to memory device **1141**. In one example embodiment, as shown more in FIG. 11A, computing system **1100** may represent a node within a larger network of nodes such as a distributed, peer to peer network.

(88) In the embodiment illustrated in FIG. 11A, memory device **1141** can include a memory **1140** having a memory array **1101**. As shown in FIG. 11A, memory **1140** can store “block chain data” **1120**, used in block chain technology systems, in the memory array **1101**. A “block” of block chain data in a block chain technology system can include data (e.g., payload), headers, encryption, history, timestamps, etc. As will be described further herein in connection with FIGS. 12 and 13, the block chain data **1120** may be “local block chain” data and/or “global block chain” data and may include a stored global block chain ledger (e.g., “global ledger block chain” data) and/or a stored local block chain ledger (e.g., “local ledger block chain” data).

(89) Memory array **1101** can be analogous to memory array **1001** previously described in connection with FIG. 10. However, as used herein a block of block chain data in a block chain architecture does not have to equate to the size of a block of memory as described previously in

connection with FIG. 1. Hence, the term “global block” and/or “local block”, when stored in memory in memory as block chain data, do not have to equate to a block size unit of memory. A global block and/or local block may be smaller, equivalent, and/or larger than a block size unit, e.g., denomination, associated with a particular memory architecture or design. Further, memory array **1101** can be a secure array, as will be further described herein in connection with FIGS. **14A** and **14B**. Although one memory array **1101** is illustrated in FIG. **11A**, memory **1140** can include any number of memory arrays analogous to memory array **1101**.

(90) As illustrated in FIG. **11A**, host **1137** can be coupled to the memory device **1141** via interface **1109**. Host **1137** and memory device **1141** can communicate (e.g., send commands and/or data such as block chain data **1120**) on interface **1109**. Host **1137** and/or memory device **1141** can be, or be part of, a laptop computer, personal computer, digital camera, digital recording and playback device, mobile telephone, PDA, memory card reader, interface hub, or Internet of Things (IoT) enabled device, such as, for instance, an automotive (e.g., vehicular and/or transportation infrastructure) IoT enabled device or a medical (e.g., implantable and/or health monitoring) IoT enabled device, among other host systems, and can include a memory access device (e.g., a processor). One of ordinary skill in the art will appreciate that “a processor” can intend one or more processors, such as a parallel processing system, a number of coprocessors, etc.

(91) Interface **1109** can be in the form of a standardized physical interface. For example, when memory device **1141** is used for information storage in computing system **1100**, interface **1109** can be a serial advanced technology attachment (SATA) physical interface, a peripheral component interconnect express (PCIe) physical interface, a universal serial bus (USB) physical interface, or a small computer system interface (SCSI), among other physical connectors and/or interfaces. Interface **1109** can provide an interface for passing control, address, information (e.g., data), and other signals between memory device **1141** and a host (e.g., host **1137**) having compatible receptors for interface **1109**.

(92) Memory device **1141** includes controller **1148** to communicate with host **1137** and with memory **1140** (e.g., memory array **1101**). For instance, controller **1148** can send commands to perform operations on memory array **1101**, including operations to sense (e.g., read), program (e.g., write), move, and/or erase data (e.g., “local” and/or “global” block chain data), among other operations. Again, the intended meaning of the terms “global block” and/or “local block” for block chain data in block chain technology and systems are defined in connection with FIGS. **12** and **13**.

(93) Controller **1148** can be included on the same physical device (e.g., the same die) as memory **1140**. Alternatively, controller **1148** can be included on a separate physical device that is communicatively coupled to the physical device that includes memory **1140**. In an embodiment, components of controller **1148** can be spread across multiple physical devices (e.g., some components on the same die as the memory, and some components on a different die, module, or board) as a distributed controller.

(94) Host **1137** can include a host controller (not shown FIG. **11A**) to communicate with memory device **1141**. The host controller can send commands to memory device **1141** via interface **1109**. The host controller can communicate with memory device **1141** and/or the controller **1148** on the memory device **1141** to read, write, and/or erase data (e.g., “local” and/or “global” block chain data), among other operations. Further, in an embodiment, host **1137** can be an IoT enabled device, as previously described herein, having IoT communication capabilities.

(95) Controller **1148** on memory device **1141** and/or the host controller on host **202** can include control circuitry and/or logic (e.g., hardware and firmware) configured to perform the block chain operations described herein, e.g., in connection with FIGS. **12** and **13**, according to, for example DICE-RIOT architecture and/or protocol. In an embodiment, controller **1148** on memory device **206** and/or the host controller on host **1137** can be an application specific integrated circuit (ASIC) coupled to a printed circuit board including a physical interface. Also, memory device **1141** and/or host **1137** can include a buffer of volatile and/or non-volatile memory and a number of registers.

(96) For example, as shown in FIG. 11A, memory device can include circuitry **1150**. In the embodiment illustrated in FIG. 11A, circuitry **1150** is included in controller **1148**. However, embodiments of the present disclosure are not so limited. For instance, in an embodiment, circuitry **1150** may be included in (e.g., on the same die as) memory **1140** (e.g., instead of in controller **1148**). Circuitry **1150** can comprise, hardware, firmware, and/or communicate instructions to a processing resource to perform the block chain operations described herein, e.g., in connection with FIGS. 12 and 13 using encryption techniques explained in FIGS. 5-9, according to, for example DICE-RIOT architecture and/or protocol.

(97) For example, circuitry **1150** can be configured to receive a global block of block chain data (defined in FIGS. 12 and 13) to be added as a local block of block chain data, e.g., **1120**, on a local ledger block chain (also defined in FIGS. 12 and 13) within an array **1101** in memory **1140**. For example, a local block of block chain data, e.g., **1120**, may be a validated received global block of block chain data and may be generated and/or added to the local ledger block chain (shown in FIGS. 12 and 13) for validating (e.g., authenticating and/or attesting) an update to data stored in memory **1140** (e.g., in memory array **1101**). The global block to be added as a local block in the local ledger block chain can include multiple headers.

(98) In an embodiment, a subset of array **1101**, or the whole array **1101** can be a secure array (e.g., an area of memory **1140** to be kept under control). FIG. 11A illustrates a pair of registers **1139-1** and **1139-2** although embodiments are not so limited, and one or more registers could be used. For example, the data stored in memory array **1101** can include sensitive (e.g., non-user) data, such as host firmware and/or code to be executed for sensitive applications. In such an embodiment, a pair of non-volatile registers can be used to define the secure array. For example, in the embodiment illustrated in FIG. 11A, circuitry **1150** includes registers **1139-1** and **1139-2** that can be used to define the secure array. For instance, register **1139-1** can define the address (e.g., the starting LBA of the data) of the secure array, and register **1139-2** can define the size (e.g., the ending LBA of the data) of the secure array. An example of such registers, and their use in defining a secure array, will be further described herein in connection with FIGS. 14A-14B).

(99) Once the secure array has been defined, circuitry **1150** can be used to generate (e.g., calculate) a cryptographic hash associated with the secure array, which may be referred to herein as a golden hash, using authenticated and anti-replay protected commands (e.g., so that only memory device **1141** knows the golden hash, and only memory device **1141** is capable of generating and updating it). The golden hash may be stored in inaccessible portion of memory array **1101** (e.g., the same inaccessible portion in which block chain data **1120** and the local ledger block chain is stored) and can be used during the process of validating the data of the secure array.

(100) In one example embodiment, memory device **1141** (e.g., using circuitry **1150**) can send, via interface **1109**, the block chain data **1120** (which may be a received global block from the global ledger block chain), along with the digital signature associated with block chain data **1120**, to the host **1137** for validation of the update (e.g., the payload of the block chain data) before updating data stored in memory array **1101**. For example, circuitry **1150** can sense (e.g., read) the block chain data **1120** received and stored in memory array **1101**, and send the sensed block chain data **1120** to host **1137** for validation of the update to the data stored in array **1101**, responsive to a powering (e.g., a powering on and/or powering up) of memory device **1141**. As such, a validation of the update to the data stored in memory array **1101** can be initiated (e.g., automatically) upon the powering of memory device **1141**.

(101) As an additional example, circuitry **1150** can send the block chain data **1120**, along with the digital signature associated with block chain data **1120**, to host **1137** upon an external entity, such as host **1137**, initiating a validation of an update to the data stored in memory array **1101**. For instance, host **1137** can send a command to memory device **1141** (e.g., circuitry **1150**) to sense the block chain data **1120**, and circuitry **1150** can operate on the command to sense the block chain data **1120** and send the sensed block chain data **1120** to host **1137** for validation of the data stored

in array **1101**, responsive to receipt of the command.

(102) Upon receiving the block chain data **1120**, host **1137** can validate (e.g., determine whether to validate) the data stored in memory array **1101** using the received block (e.g., the payload of the received global block). For example, as will be explained further in connection with FIGS. **3** and **4**, host **1137** can use the cryptographic hash of the previous block in the block chain and the cryptographic hash of the data stored in memory array **1101** to validate the data. Further, host **1137** can validate the digital signature associated with the block chain data **1120** to determine the local block is included (e.g., is eligible to be included) in the local ledger block chain. As used herein, validating the update to the data stored in memory array **1101** can include, and/or refer to, authenticating and/or attesting that the update is genuine (e.g., is the same as originally programmed), and has not been altered by hacking activity, frequently provided by a hacker, or other including unauthorized changes.

(103) In embodiments in which memory array **1101** is a secure array, a golden hash, as described further in connection with FIGS. **3** and **4**, may also be used to validate the update to the data stored in memory array **1101**. For example, a run-time cryptographic hash can be generated (e.g., calculated), and compared with the golden hash. If the comparison indicates the run-time and golden hashes match, it can be determined that the secure array has not been altered, and therefore the data stored therein is valid. If, however, the comparison indicates the run-time and golden hashes do not match, this may indicate that the data stored in the secure array has been changed (e.g., due to a hacker or a fault in the memory), and this can be reported to host **1137**.

(104) In one example embodiment, in addition to the validation of the data stored in memory array **1101**, circuitry **1150** can validate the block chain data **1120** (e.g., the received global block from the global ledger block chain) to determine if the block chain data **1120** is from an authorized entity (e.g., a known entity), and that the hash indicated on the received block chain data **1120** matches the most recent local block of block chain data on the local ledger block chain. In response to the validation of the block chain data **1120**, the circuitry **1150** can be configured to provide the update included in the block chain data **1120** to augment, modify, and/or replace code (or a portion of code) stored in the secure array.

(105) As will be explained further in connection with FIGS. **12** and **13**, after the validation of the block chain data **1120** serving as a local block in a local ledger block chain stored in memory array **1101**, circuitry **1150** can generate an additional (e.g., the next) local block (e.g., receive the next global block from the global ledger block chain) to be added to the local ledger block chain for updating the data stored in memory array **1101**, in a manner analogous to which the previous block chain data **1120** was generated/received. For example, this additional local block of block chain data **1120** can include a cryptographic hash of the previous block in the local ledger block chain, and a new cryptographic hash of a new update to the data stored in memory array **1101**. Further, this additional local block can include a header having a timestamp indicating when this block was generated (e.g., received as an additional global block), and can have a digital signature associated therewith that indicates this additional local block is from an authorized entity and may be included in the local ledger block chain. An example illustrating such an additional local block will be further described herein (e.g., in connection with FIG. **3**). Further, in embodiments in which memory array **1101** is a secure array, an additional (e.g., new) golden hash can be generated.

(106) The additional local block of block chain data, as well as the digital signature associated with the additional local block, and the additional golden hash, can be stored in memory array **1101** as part of the local ledger block chain. For example, the additional local block can replace the block chain data **1120** (e.g., the previous block chain data **1120**) in memory array **1101**. The additional block chain data, digital signature, and additional golden hash can then be used by host **1137** to validate the update (e.g., the payload) to the data stored in memory array **1101**, in a manner analogous to that previously described herein for block chain data **1120**. Additional local blocks in the local ledger block chain can continue to be generated by circuitry **1150** when they are received

as global blocks, validated by the host **1137**, and used by host **1137** to validate the update to the data stored in memory array **1101**, in such manner throughout the lifetime of memory device **1141**. (107) The embodiment illustrated in FIG. **11A** can include additional circuitry, logic, and/or components not illustrated so as not to obscure embodiments of the present disclosure. For example, memory device **1141** can include address circuitry to latch address signals provided over I/O connectors through I/O circuitry. Address signals can be received and decoded by a row decoder and a column decoder, to access memory array **1101**. Further, memory device **1141** can include a main memory, such as, for instance, a DRAM or SDRAM, that is separate from and/or in addition to memory array **1101**. An example further illustrating additional circuitry, logic, and/or components of memory device **1141** will be further described herein (e.g., in connection with FIG. **15**).

(108) FIG. **11B** is a block diagram of a network of computing systems which can include many computing nodes in a public and/or private distributed network, such as a peer to peer network, connected in a wired and/or wireless manner using wireless protocols and Internet Protocol (IP) in accordance with an embodiment of the present disclosure. In the example of FIG. **11B**, multiple nodes, **1143-1**, **1143-2**, **1143-3**, . . . , **1143-N**, are shown connected in a network such as a peer to peer network. The network can support a distributed ledger technology (DLT) such as “block chain” technology. A distributed ledger is a database that is spread over several nodes or computing devices.

(109) A “block chain” is a continuously growing, encrypted list of records. Block chain is one form of a DLT in which multiple nodes, **1143-1**, **1143-2**, **1143-3**, . . . , **1143-N**, can share and store the distributed list of records in a peer to peer network manner. As described herein a “block” in block chain is collection of information, e.g., data, headers, transactions, encryption, etc. A block may be added to the growing list of records in the ledger if it is validated. Blocks are added to the block chain ledger in chronological order.

(110) Hence, in the example of FIG. **11B**, a given node, **1143-1** (H1), **1143-2** (H2), **1143-3** (H3), . . . , **1143-N**, may maintain a copy of a current list or records in ledger. The multiple nodes, **1143-1**, **1143-2**, **1143-3**, . . . , **1143-N**, may each represent a different host, e.g., computing device with processing resources. For ease of illustration, the hosts or multiple nodes, **1143-1**, **1143-2**, **1143-3**, . . . , **1143-N**, may be considered in relation to a block chain for autonomous and/or non-autonomous transportation vehicles, cars, buses, emergency vehicles, etc. Embodiments, however, are not limited to this example.

(111) In this example, a public or private entity's (e.g., a military entity, an airport manager, a hotel owner, a hospital entity, etc.) servers may represent one node, e.g., **1143-1**, on the network of nodes, **1143-1**, **1143-2**, **1143-3**, . . . , **1143-N**, shown in FIG. **11B**. A certified repair facility such as a dealership repair shop may represent another node, e.g., **1143-2**. Node **1143-3** may be another host, e.g., another computing device, connected to the peer to peer network via the Internet and/or other wireless connections.

(112) The public or private entity associated with node **1143-1** may maintain a “first block chain ledger” having chronologically linked blocks of data related to a particular subject matter associated with node **1143-1**, e.g., maintain a first block chain ledger for all the vehicles associated with that public or private entity. For ease of illustration, and not by way of limitation, the referenced “first block chain ledger”, having chronologically linked blocks of data related to a particular subject matter associate with a particular node, e.g., for all the vehicles associated with a given public or private entity, may also be referred to herein as a “global block chain ledger” (or, “global ledger block chain”). The public or private entity can distribute the first block chain ledger (“global ledger block chain”) to other nodes, **1143-2**, **1143-3**, etc., in the peer to peer network and to its vehicles, connected as nodes to the network, in a wired and/or wireless manner. Various wireless communication technologies can be utilized in communicating with different nodes, **1143-1**, **1143-2**, **1143-3**, . . . , **1143-N**. For example, different generations of broadband mobile

telecommunication technologies (e.g., first through fifth generation (1-5G)), device-to-device (e.g., vehicle to vehicle (v2v)), to communication including Bluetooth, Zigbee, and/or LTE device-to-device communication technologies, and/or other wireless communication utilizing an intermediary devices (e.g., WiFi utilizing an access point (AP)) may be utilized in communicating with different nodes.

(113) In the example of FIG. 11B, node **1143-4** may represent a particular vehicle belonging to a subset or class of vehicles associated with a public or private entity by the particular public or private entity represented by node **1143-1**. In this example, node **1143-5** may represent another particular vehicle, in the same or different subset or class of vehicles associated with the public or private entity or, alternatively, not be related to the public or private entity associated with node **1143-1**. Similarly, node **1143-N** may represent another particular vehicle, in the same or different subset or class of vehicles associated with the public or private entity or, alternatively, not be related to the public or private entity associated with node **1143-1**.

(114) Each node may have its own processing resource, e.g., host connected to one or more memory devices such as illustrated in FIG. 11A. Thus, vehicle nodes **1143-4**, **1143-5**, and **1143-N** may each include a single and/or multiple host, e.g., processing resources, **1137-4**, **1137-5**, **1137-N**, respectively. Each host on a given vehicle node, **1143-4**, **1143-5**, and **1143-N**, may connect to multiple memory devices on each vehicle. For example, memory devices **1141-4-1**, **1141-4-2**, **1141-4-X** may be associated with host **1137-4** on node **1143-4**, memory devices **1141-5-1**, **1141-5-2**, and **1141-5-B** may be associated with host **1137-5** on node **1143-5**, and memory devices **1141-N-1**, **1141-N-2**, and **1141-N-Z** may be associated with host **1137-N** on node **1143-N**.

(115) In this example, node **1143-1** may regularly send, e.g., distribute, to nodes **1143-4**, **1143-5**, . . . , and **1143-N** an updated copy of the continuously growing first, e.g., “global”, block chain ledger (also referred to herein as “global ledger block chain”) maintained by node **1143-1** containing chronological blocks, e.g., data, related to the subject matter of all the vehicles associated with the public or private entity. According to block chain technology, node **1143-1** may share a copy of the first, e.g., “global”, ledger block chain with other nodes, **1143-1**, **1143-2**, **1143-3**, . . . , **1143-N** in the distributed network. However, not all of the “blocks” in the growing first, e.g., “global” ledger block chain maintained by node **1143-1** and received to other particular nodes, **1143-4**, **1143-5**, . . . , **1143-N**, may be authentic and/or relevant to other particular nodes. For example, particular vehicles, e.g., nodes **1143-4**, **1143-5**, . . . , **1143-N**, may belong to a subset or sub-class of vehicles associated with the public or private entity associated with node **1143-1**, but only particular blocks in the first, e.g., “global”, ledger block chain may relate to a particular node **1143-4**, **1143-5**, . . . , **1143-N**, e.g., particular vehicle, in that subset or sub-class of vehicles. As such, according to embodiments disclosed herein, a particular node, **1143-4**, **1143-5**, . . . , **1143-N**, may validate only those blocks authenticated and relevant to that node, **1143-4**, **1143-5**, . . . , **1143-N**.

(116) According to example embodiments, a particular node, e.g., **1143-4**, may validate and add blocks, authenticated and relevant to the node, to a second block chain ledger which may be a subset of fewer than all of the blocks contained in the global ledger block chain received from node **1143-1** to node **1143-4**. Node **1143-4** may store the subset of the “global ledger block chain” as a “local block chain ledger” (also referred to herein as “local ledger block chain”) on the respective node, **1143-4**, **1143-5**, . . . , **1143-N**. Node **1143-4** may also share the local ledger block chain with other nodes. However, same is not required and the local ledger block chain is termed “local” in that it may remain “local” only to that particular node **1143-4**, e.g., the host and/or memory devices of a particular vehicle. Thus, for ease of illustration, the second block chain ledger (“local ledger block chain”) may be referred to herein as a local ledger block chain. The node, e.g., **1143-4**, may receive many global blocks associated with other global ledger block chains, pertaining to various subject matter, via the network of nodes to which it is connected. However, the node, e.g., **1143-4**, may be selective as to which blocks it accepts add allows to be added to its local ledger block chain. As explained in greater detail in connection with FIGS. 12 and 13, embodiments of the

present disclosure may use the encryption techniques described in FIGS. 5-9 to validate and add blocks relevant to a particular node, **1143-4**, **1143-5**, . . . , **1143-N**, and store and maintain those blocks on the particular node, **1143-4**, **1143-5**, . . . , **1143-N**, as a “local ledger block chain” data, e.g., as transactions associated with a particular vehicle (e.g., emergency vehicle) that is in possession of a local ledger block chain. In one example, a single host (such as shown in FIG. **11A**) or multiple host on a particular vehicle, e.g., nodes **1143-4**, **1143-5**, . . . , **1143-N**, can maintain a local ledger block chain. As an example, a single or multiple host can maintain a distributed ledger on the node according to techniques described in co-pending, co-filed U.S. application Ser. No. 16/362,877, entitled “USING MEMORY AS A BLOCK IN A BLOCK CHAIN”. In this example, a transaction (e.g., record of a dispatch) relevant to a particular vehicle, e.g., node **1143-4**, **1143-5**, . . . , **1143-N**, may be validated and added to the “local ledger block chain” of the node, **1143-4**, **1143-5**, . . . , **1143-N**, or alternatively discarded.

(117) FIG. **12** illustrates an example of an exchange between a global ledger block chain **1222** and local ledger block chains **1224**, **1226**, and **1228** as can be operated upon by circuitry and stored in a memory and/or secure array, e.g., by circuitry **1150** and memory **1140** in FIG. **11A**. In this example secure updates to data may be validated and stored in memory such as memory array **1101** described in connection with FIG. **11A**. As used herein, “block” according to block chain technology in a block chain ledger or system can include data (e.g., payload), headers, encryption, history, timestamps, etc. Again, a “block” in a block chain does not have to correlate to or equate to the size of a block of memory, as explained as a storage unit of memory in FIG. **10**.

(118) Further, as used herein, the term “global block” is a block in the first block ledger which in the example is maintained and shared across a larger system or network of entities. A “local block” is a block only in a local ledger block chain, maintained as a subset of data relevant to a particular node, e.g., **1100-4**, as a subset of particular subject matter relevant to a subset of vehicles or more specific class of entities within a system or network of entities, e.g., memory device **1101** in FIG. **11A**. Neither a global block or a local block chain have to equate to a block size of a particular memory architecture. A global block and/or local block may be smaller, equivalent, and/or larger than a block size denomination associated with a particular memory architecture or design.

(119) As shown in FIG. **12**, a first, e.g., global ledger block chain **1222** can be related to subject matter associated with node **1100-1** in FIG. **11B**. The global ledger block chain can include global blocks **1220-1**, **1220-2**, **1220-3**, **1220-4**, **1220-5**, **1220-6**, and **1220-N**. When operated upon by circuitry and logic described herein, the global blocks **1220** can be validated and accepted into second, e.g., local, ledger block chains **1224**, **1226**, and **1228**, shown as local blocks **1221-1**, **1221-2**, **1221-3**, **1221-4**, **1221-5**, **1221-6**, and **1221-N**. Second, e.g., local, ledger block chains **1224**, **1226**, and **1228** may be maintained by nodes **1100-4**, **1100-5**, . . . , **1100-N** shown in FIG. **11B**, respectively therein. Alternatively, if not validated to a local ledger block chain maintained on a particular node, e.g., nodes **1100-4**, **1100-5**, . . . , **1100-N** shown in FIG. **11B**, the respective global blocks of the global ledger block chain can be rejected therefrom.

(120) For example, when global block chain data is received by a particular memory to be validated and stored as a local block within local ledger block chain, global block chain data has to be validated by circuitry and logic, e.g., circuitry **1150** in FIG. **11A**, before it becomes a local block within local ledger block chain. In the example of FIG. **12**, global block **1220-1** has been validated, e.g., by circuitry **1150**, to become local block **1221-1** in local ledger block chain **1224**, global block **1220-2** has been validated to become local block **1221-2** in local ledger block chain **1226**, global block **1220-3** has been validated to become local block **1221-3** in local ledger block chain **1228**, global block **1220-4** has been validated to become local block **1221-4** in local ledger block chain **1224**, global block **1220-5** has been validated to become local block **1221-5** in local ledger block chain **1224**, global block **1220-6** has been validated to become local block **1221-6** in local ledger block chain **1226**, and global block **1220-N** has been validated to become local block **1221-N** in local ledger block chain **1228**.

(121) In one example embodiment, the global blocks **1220** can be received to a memory device, e.g., **1101** in FIG. **11A**, validated, and added (e.g., generated) to a local ledger block chain **1224**, **1226**, or **1228**, by using the circuitry **1150** described in FIG. **11A**. In the example of FIG. **12**, global block **1220-4** has been received and validated to become local block **1221-4**. Local block **1221-4** can be added to the local ledger block chain **1224** after local block **1221-1** has been validated by the circuitry and logic described herein. As described further in connection with FIG. **13**, local block **1221-1** is used to validate global block **1220-4** as an update of data stored in the memory. In this example, local block **1221-4** can be accepted and stored as the next block in the local ledger block chain **1224** after local block **1221-1**. The global ledger block chain **1222** can include blocks in a block chain configuration, architecture, and/or protocol from multiple hosts (e.g., the host **1102** described in connection with FIG. **11A**).

(122) A host and/or memory may maintain, e.g., store, local ledger block chains **1224**, **1226**, **1228** and include only the validated global blocks that are relevant to a particular host and/or memory. As an example, a local ledger block chain associated with a particular entry node may only store data that relates to traffic in and out of that entry point as blocks in that particular local ledger block chain. Global blocks **1220** may include identifiers for a particular host and/or memory associated with the data included in the global block. For example, local ledger block chain **1224** is shown associated with a particular host/memory identifier (**ID_1**). Thus, circuitry associated with this host/memory relationship will validate only related global blocks such that local ledger block chain **1224** will include only local blocks **1221-1** (global block **1220-1** from global ledger block chain **1220**), local block **1221-4** (global block **1220-4** from global ledger block chain **1220**), and local block **1221-5** (global block **1220-5** from global ledger block chain **1220**). As an example, local ledger block chain **1224** may be associated with a first node or device (e.g., control node **408**). Local ledger block chain **1226** is shown associated with another host and/or memory identifier (**ID_2**). As an example, local ledger block chain **1226** may be associated with a second node or device (e.g., traffic control device **410-1**). Thus, circuitry associated with this host/memory relationship will validate only related global blocks such that local ledger block chain **1226** will include local block **1221-2** (global block **1220-2** from global ledger block chain **1220**), and local block **1221-6** (global block **1220-6** from global ledger block chain **1220**). Local ledger block chain **1228** is shown associated with another host and/or memory identifier (**ID_k**) (e.g., a third node or device such as traffic control device **410-3**). Thus, circuitry associated with this host/memory relationship will validate only related global blocks (related to all entry points into a location) such that local ledger block chain **1228** will include the local block **1221-3** (global block **1220-3** from global ledger block chain **1220**), and local block **1221-N** (global block **1220-N** from global ledger block chain) as these blocks pertain to that particular entry node or access point.

(123) Using a local ledger block chains (e.g., **1224**, **1226**, **1228**) to store appropriate block chain data as updates to the memory of a respective host and/or memory relationship (e.g., **ID_1**, **ID_2**, and **ID_k**) can provide secure updates to data stored in a given memory device (e.g., the memory device **1141** of FIG. **11A**) in association with a given host. As such, the circuitry and logic described herein allow for the exchange and organization shown in FIG. **12**. For example, circuitry is configured to receive a global block e.g., **1220-4** from a global ledger block chain **1222** and determine whether the global block **1220-4** is related to a particular the host and/or memory relationship. If the global block **1220-4** is related to the particular host and/or memory, e.g., a comparison of encrypted hash for respective identifiers (e.g., **ID_1**, **ID_2**, and **ID_k**) according to block chain techniques match, the circuitry may add the global block **1220-4** to its local ledger block chain **1224**. Global block **1220-4** of block chain data can include a payload of an update to data included in a secure array associated with the host and/or memory. The circuitry described herein, e.g., circuitry **1150**, may validate the global block **1220-4** by checking, e.g., comparing, a cryptographic hash of a current local block e.g., **1221-1** in the local ledger block chain **1224** and a cryptographic hash of the data stored in the memory to be updated, contained in global block **1220-**

4. The current local block **1221-1** of the local ledger block chain **1224** also has a digital signature associated therewith which is similarly compared to indicate whether the global block **1220-4** is from an authorized entity (e.g., includes an identifier **ID_1** evidencing that global block **1220-4** is from an entity associated with the particular host and/or memory relationship including the local ledger block chain **1224**). As explained in connection with FIG. 13, if validated the current local block **1221-1** will become the “previous” local block and global block **1220-4** will become the then “current” local block **1221-4** in the local ledger block chain **1224**. The contents of the local blocks **1221** of the local ledger block chain **1224** (e.g., and/or **1226**, **1228**) are described in detail in connection with FIG. 13.

(124) An authorized entity may provide the global ledger block chain **1222** as a public ledger which may be distributed to all and/or a portion of the hosts and/or memory that concur the global ledger block chain **1222** to receive access to a particular location. For example, the global ledger block chain **1222** may be generated and maintained by an entity which may monitor traffic into and out of a particular location, roadway, etc. For example, the global ledger block chain **1222** may be generated and monitored by a public or private entity (e.g., a military entity, an airport manager, a hotel owner, a hospital entity, etc.) that then monitors particular vehicles as they move in and out of a location. Each of the global blocks **1220** within the global ledger block chain **1222** may include entrance and exit data for a vehicle with a particular identifier. For instance, as illustrated by FIG. 12, the global blocks **1220-1**, **1220-4**, **1220-5** correspond to host and/or memory **ID_1**, global blocks **1220-2**, **1220-6**, correspond to host and/or memory **ID_2**, and global blocks **1220-3**, **1220-N** correspond to host and/or memory **ID_k**. Where the different ID's correspond to a different host and/or memory relationship (e.g., different vehicles).

(125) In this instance, the public or private entity generates and monitors the global ledger block chain **1222** such that each instance of an update of dispatch of particular vehicles (e.g., or a particular subset of vehicles sharing the identifier) is recorded as an immutable record in the global ledger block chain **1222**. For example, global block **1220-1** includes an update for a vehicle (e.g., or data in the memory associated with the vehicle) associate with **ID_1**, global block **1220-2** includes an update for vehicles associated with **ID_2** and so on. The global blocks **1220** are assembled in sequential order as they are produced by the public or private entity and each global block **1220** can include a digital signature indicating an identity of particular vehicles (e.g., emergency vehicles). In this way, the public or private entity may keep an immutable record of all of the updates (e.g., enters and exits, movements, etc.) generated for the different vehicles monitored.

(126) As used in block chain technology, and described more in connection with FIG. 13, the global blocks **1220** in the global ledger block chain **1222** can include multiple headers and encryption. For example, the global block of a global ledger block chain can include a global block header including a cryptographic hash data (e.g., a link to) to the previous global block and a hash including a cryptographic hash data to a previous local block. Thus, when the global block is received by the host **1102** and/or memory device **1141** in FIG. 11A, the global block to be added to the local ledger block chain can include a cryptographic hash (e.g., a link to) a current local block (e.g., in block chain data **1120**) in the local ledger block chain and a cryptographic hash of the update to data stored in the memory device **1141** (e.g., a payload). The block chain data **1120** in a local ledger block chain can also include a digital signature associated therewith that indicates that the global block is from an authorized entity.

(127) Stated differently, a global block from a global ledger block chain may be received by the host and/or the memory, e.g., host **1102** and/or memory **1140** shown in FIG. 11A, and the circuitry and/or logic on the host and/or the memory may determine if the global block is related to the host and/or the memory. If so, the global block and its contents may be validated to become a new local block of block chain data stored in a local ledger block chain (e.g., as part of block chain data **1120** stored on the array **1101** of the memory **1140** in FIG. 11A). The local block can also include a

header having a timestamp indicating when the local block was generated/received.

(128) The cryptographic hash of the data stored in a memory array, e.g., memory array **1101** of FIG. **11A**) to be updated, altered, configured, an/or otherwise changed by the data included in the received/generated local blocks, and/or the cryptographic hash of the previous local block in the local ledger block chain, can comprise, for instance, a SHA-256 cryptographic hash. Further, the cryptographic hash of the data stored in memory array, and the cryptographic hash of the previous local block in the local ledger block chain, can each respectively comprise 256 bytes of data.

(129) The cryptographic hash of the data stored in memory array can be generated (e.g., calculated), by circuitry, e.g., circuitry **1150** in FIG. **11A**. In such an example, the cryptographic hash of the data stored can be internally generated by memory device, e.g., memory device **1141** in FIG. **11A**, without having external data moving on a host/memory device interface, e.g., interface **1109** in FIG. **11A**. As an additional example, the cryptographic hash of the data can be communicated from an external entity. For instance, a host can generate the cryptographic hash of the data stored in a memory array and send the generated cryptographic hash to a memory device e.g., circuitry of the memory device can receive the cryptographic hash of the data stored in memory array from host.

(130) Further, a digital signature associated with a local block can be generated (e.g., calculated), by circuitry based on (e.g., responsive to) an external command, such as a command received from a host. The digital signature can be generated using symmetric or asymmetric cryptography. The digital signature may include a freshness field in the form of the previous local block on the global ledger block chain (which should match the current local block on the local ledger block chain when the block is added). As an additional example, a host can generate the digital signature, and send (e.g., provide) the generated digital signature to a memory device.

(131) The freshness field, described herein, may change with each global block that is added to the local ledger block chain. Accordingly, the freshness field may be used to validate the incoming global block is the correct block to be added as the next block in the local ledger block chain. The incoming global block is verified to be the next local block to be added to the local ledger when the digital signature indicates that the incoming global block is related to the host, and the previous local block field (the freshness) of the incoming global block is the same as the current local block in the local ledger block chain. Because the freshness can also be used to calculate the digital signature, the digital signature can be different with each incoming global block.

(132) As mentioned, the digital signature can be, for instance, a digital signature generated using asymmetric cryptography (e.g., based on a public and/or private key), and can comprise, for instance, an elliptical curve digital signature. As an additional example, the signature can be generated using symmetric cryptography (e.g., based on a unique secret key shared between a host and a memory device). The secret key can be exchanged by using any asymmetric protocol (e.g., the Diffie-Hellman protocol). In other examples, the key may be shared with a host in a secure environment (e.g., factory production, secure manufacturing, as a vehicle is associated with a public or private entity, etc.). The generation and validation of the secret key is discussed further in connection with FIGS. **5-9**.

(133) As described in connection with FIG. **11A**, such block chain data **1120** can be stored in a memory array, e.g., memory array **1101** in FIG. **11A**. The block chain data **1120** can be stored in a portion of memory array **1101** that is inaccessible to a user of memory device and/or host (e.g., in a “hidden” region of memory array). Storing a local block and/or local ledger block chain of block chain data in a particular memory array can simplify the storage of the local block by removing the need for software storage management for the local block.

(134) In the example of FIG. **12**, global block **1220-6** can include a global header having a field for a hash of a previous global block **1220-5**, where the previous global block field indicates the preceding block in the global ledger block chain **1222**. A different hash in the global header can include a previous local block field, where the previous local block field indicates the preceding

global block with an identifier of same host and/or memory ID.

(135) For example, global block **1220-6** may include a local block field with a hash for global block **1220-2** (the previous related global block) because they are both vehicle ID_2. In this way, a particular host and/or memory device relationship (e.g., for a vehicles, or subset of vehicles) may receive multiple global blocks **1220** from the global ledger block chain **1222**, and determine which global blocks **1220** to accept as a local blocks and which global blocks **1220** to discard.

(136) For example, the local ledger block chain **1224** may be included in a memory device and/or memory associated with a particular host through an identifier in the form of a host (e.g., a vehicle) with ID_1. The circuitry as described herein can be configured to store global blocks **1220** in the memory associated with the host vehicle as part of the local ledger block chain **1224**. In other words, the circuitry is configured to receive multiple global blocks **1220** from the global ledger block chain **1222**, and when the circuitry determines that the global block(s) **1220** belong to the host vehicle associated with vehicle ID_1, they are accepted as local blocks **1221** and added to the local ledger block chain **1224**.

(137) Specifically, in an example, a host vehicle and/or memory associated with the host vehicle with an ID_1 includes, e.g., may store, the local ledger block chain **1224** and the circuitry and/or memory may receive multiple global blocks **1220-1**, **1220-2**, **1220-3**, **1220-4**, **1220-5**, **1220-6**, and **1220-N** from the global ledger block chain **1222**. The circuitry is configured to determine whether the multiple global blocks **1220** received from the global ledger block chain **1222**, by the circuitry are related to the host vehicle and/or memory associated with the host vehicle ID_1. Thus, the circuitry may determine that the global blocks **1220-1**, **1220-4**, and **1220-5** are related to the host vehicle ID_1, and the circuitry is configured to validate and, if validated, to sequentially add global blocks **1220-1**, **1220-4**, **1220-5** of the multiple global blocks received from the global ledger block chain **1222** to the local ledger block chain **1224** as local blocks **1221-1**, **1221-4**, and **1221-5** because it has been verified that they are related to the host vehicle ID_1. In another example, a determination of whether the multiple global blocks **1220** are related to a particular gate of a location. In this way, different blocks can be sorted and associated with different entities where one local block chain ledger may be associated with a vehicle (including all enters and exits a vehicle makes) and another local block chain ledger may be associated with a gate (including all vehicles that enter and exit that gate), etc.

(138) In one example, the global blocks **1220-1**, **1220-4**, and **1220-5** can be added (sequentially) to the local ledger block chain **1224** when a previous local block field in each of the respective global blocks **1220** matches a current local block field in the current local block of the local ledger block chain **1224**. Specifically, the circuitry can validate the incoming global block **1220-4** by confirming that the global block **1220-4** is from an authorized entity (e.g., the vehicle identity in the global ledger block chain **1222**) and checking that the previous local block field of global block **1220-4** is a hash for local block **1221-1** (which is the same as the global block **1220-1**), and checking that the current local block **1221-1** has a matching hash in its own current local block field. This procedure can be applied to add the global block **1220-5** to the local ledger block chain **1224**. Thus, the global blocks **1220-1**, **1220-4**, and **1220-5** can become local blocks **1221-1**, **1221-4**, and **1221-5** in the local ledger block chain **1224**. Using this method and configuration, the local ledger block chain **1224** includes multiple local blocks related to a host and/or memory associated with (ID_1) assembled in sequential order.

(139) Additionally, the circuitry is configured to refrain from adding global blocks **1220** to the local ledger block chain **1224**, when they are unrelated to the host and/or memory ID_1. Thus, the circuitry may determine that global blocks **1220-2**, **1220-6**, **1220-3**, and **1220-N** are not related to the host and/or memory ID_1 and may discard the unrelated global blocks from local ledger block chain **1224**. The mechanisms described in connection with FIG. 12 may be applied to multiple hosts and/or multiple memories e.g., local ledger block chain **1226**, and local ledger block chain **1228**.

(140) For example, the circuitry may generate a local ledger block chain (e.g., **1224**) for validating an update to data stored in the memory (e.g., associated with ID_1) and receive global blocks (e.g., **1220-1, 1220-2, 1220-3, 1220-4, 1220-5, 1220-6, 1220-N**) from a global ledger block chain **1222**. The circuitry may add a first portion (e.g., **1220-1, 1220-4, 1220-5**) of the global blocks to the local ledger block chain **1224** when a digital signature associated with each of the global blocks of the first portion is verified by the circuitry to be related to the host and/or memory (e.g., ID_1). The circuitry may discard a second portion (e.g., **1220-2, 1220-6, 1220-3, 1220-N**) of the received global blocks when the second portion of the global blocks are determined to be unrelated to the host and/or memory associated with ID_1, (e.g., the second portion is associated with ID_2, and/or ID_k).

(141) As is described further in connection with FIG. 13, a freshness field may be used by the circuitry to verify a global block belongs in the local ledger block chain (e.g., **1224, 1226, 1228**). In the example above, each of the global blocks of the first portion (e.g., **1220-1, 1220-4, 1220-5**) include a freshness field used to generate the digital signature. The freshness field for each of the global blocks of the first portion (e.g., **1220-1, 1220-4, 1220-5**) corresponds to a current local block of the local ledger block chain **1224**. As such, the global blocks of the first portion (e.g., **1220-1, 1220-4, 1220-5**) are added to the local ledger block chain **1224** in sequential order (as local blocks **1221-1, 1221-4, and 1221-5**) and stored in the memory associated with the host.

(142) Specifically, the circuitry can generate a digital signature based on a freshness field of the global block. For instance, the circuitry may generate the freshness field of global block **1220-4** by identifying a previous local block field in the header of the global block **1220-4** (in this instance, this would be a hash of global block **1220-1** because it is the previous global block with the ID_1). Where the current local block **1221-1** of the local ledger block chain **1224** and the previous local block field (again, in this instance this would be global block **1220-1**) of the global block **1220-4** of the global ledger block chain **1222** are the same.

(143) Embodiments of the present disclosure, by utilizing local ledger block chain, can provide benefits such as implementing a block chain technology in each vehicle, which may have a limited size of storage. Unlike the global ledger block chain, a size of local ledger block chain can be comparably small, which can be implementable in each vehicle such that the vehicle may refer to the local ledger block chain instead of the global ledger block chain. The embodiments of the present disclosure can further provide benefits such as convenient way to retrieve information that are corresponding to a particular vehicle. While transactions associated with a particular vehicle may be stored over multiple blocks in a global block chain (e.g., which may result in a search of a global ledger block chain having a complex structure), transactions associated with the a particular vehicle may be readily retrieved from local ledger block chain (e.g., such that information of the transactions may be readily retrieved for a litigation associated with the particular vehicle).

(144) FIG. 13 illustrates an example of a local ledger block chain (e.g., local ledger block chain **1324**) for secure updates stored in memory (e.g., in memory array **1101** previously described in connection with FIG. 11A) in accordance with an embodiment of the present disclosure. The local ledger block chain **1324** can be similar to the local ledger block chain **1224** described in connection with FIG. 12. For ease of illustration, FIG. 13 illustrates only local ledger block chain **1324**. However, examples described in connection with FIG. 13, and local ledger block chain **1324**, may also be applied for other local ledger block chains (e.g., local ledger block chains **1226** and **1228** described in connection with FIG. 3). Local ledger block chain **1324** is a block chain used for validating identities of vehicles using data stored in a memory of a respective host and/or memory exchange. As one example, the host and/or memory exchange is associated with a particular identifier, e.g., identifier ID_1.

(145) In this example, the local blocks **1321-1, 1321-4, 1321-5** of the local ledger block chain **1324** are blocks that were received as, e.g., previously, global blocks **1220-1, 1220-4, 1220-5** in the example of FIG. 3). In one example, circuitry **1150** in FIG. 11A operates on the received global

blocks using block chain encryption and decryption techniques described in connection with FIGS. 5-9 to compare and validate respective a hash of the block chain data, e.g., using an SHA256 hash. When the global blocks are verified as being related to the host and/or memory (e.g., ID_1), they may become local blocks **1321-1**, **1321-4**, and **1321-5** and be stored as an immutable record in the local ledger block chain **1324** for the host and/or memory associated with ID_1. In this example, circuitry operates to compare a block chain hash for local block **1321-4** (e.g., previously global block **1220-4**) to local block **1321-1** (e.g., previously global block **1220-1**), for storage in the memory associated with the host ID_1. Once validated by the circuitry associated with the host and/or memory, the circuitry may link to the local block **1321-1**. Likewise, local block **1321-5** (e.g., previously global block **1220-5**) once validated by the circuitry associated with the host and/or memory may link to the local block **1321-4**.

(146) In the example of FIG. 13, each local block (e.g., **1321-1**, **1321-4**, and/or **1321-5** etc.) may respectively include the following information: a global block header, e.g., **1330-1**, **1330-4**, **1330-5**, and a local block header, e.g., **1332-1**, **1332-4**, **1332-5**. In this example, each local block header **1332-1**, **1332-4**, **1332-5** includes a previous local block hash **1345-1**, **1345-4**, **1345-5**, a current local block hash **1334-1**, **1334-4**, **1334-5**, and a block signature **1335-1**, **1335-4**, **1335-5**. As shown in the example of FIG. 13, each local block, e.g., **1321-1**, **1321-4**, and **1321-5**, includes a payload, e.g., **1336-1**, **1336-4**, **1336-5** as part of the block's information, e.g., data. As mentioned in connection with FIG. 3, each of the blocks (e.g., global and local) may include multiple headers (e.g., **1330-1**, **1332-1**) to link a current block to a previous block in their respective block chain ledgers (global or local).

(147) For example, referring to the method of adding local block **1321-4** to the local ledger block chain **1324**, the global block header **1330-4** may include a freshness field in the form of a hash for a previous global block having the same associated ID_1 within the global ledger block chain, as well as a hash for the current global block (to link the global ledger block chain together). Put another way, when the global block (e.g., **1220-4** of FIG. 12) is in a global ledger block chain (e.g., **1222** of FIG. 12), the freshness field in the global block header is a hash for a previous global block (e.g., **1220-1** of FIG. 12) having the same associated identifier (e.g., ID_1) in the global ledger block chain (e.g., **1222** of FIG. 12). In this example, when local block **1321-4** is being verified to be added to the local ledger block chain **1324**, the current local block hash **1334-1** of the local block **1321-1** in the local ledger block chain **1324** will be the same as the freshness field in the global block header **1330-4** when the circuitry validates the incoming global block (e.g., **1220-4**) to add it to the local ledger block chain **1324** as local block **1321-4**. Put even another way, the freshness field of the of the global block header **1330-4** should match the current local block hash **1334-1** of the local block **1321-1** of the local ledger block chain **1324** because the current local block **1321-1** was previously global block **1220-1**.

(148) The local block headers e.g., **1332-1**, **1332-4**, and **1332-5** each respectively include a previous local block hash e.g., **1345-1**, **1345-4**, and **1345-5** (to link together the local ledger block chain **1324**), and a current local block hash e.g., **1334-1**, **1334-4**, and **1334-5** (which is the same as an incoming global block freshness field), and block signatures e.g., **1335-1**, **1335-4**, **1335-5** to indicate that the block is from an authorized entity (e.g., a listed vehicle identity and/or an entity associated with a host and/or memory) and related to the host and/or memory (e.g., ID_1). The payload e.g., **1336-1**, **1336-4**, and **1336-5** can be data which includes a hardware, configuration, and/or software update (e.g., configuration, change in configuration, alteration to a device of the host and/or memory associated with the host, etc.) and and/or a cryptographic hash of the data stored in the memory to be updated.

(149) For example, a host, in the form of a vehicle and/or memory associated with the vehicle having an identifier of ID_1, may include a memory and circuitry to generate a local ledger block chain **1324** for validating an update to data stored in the memory. In this example, the local ledger block chain **1324** is comprised of local block **1321-4** (e.g., global block **1220-4** of FIG. 12) taken

from a global ledger block chain (e.g., **1222** of FIG. **12**). The local block **1321-4** includes a current local block cryptographic hash **1334-4** of the current local block **1321-4**. The current local block cryptographic hash **1334-4** may be compared to a previous local block cryptographic hash **1345-4** which was current local block hash **1334-1**, as a freshness field to validate an order (e.g., a sequence) and link the local ledger block chain **1324** and a cryptographic hash of data stored in the memory to be updated (e.g., the payload **1336-1**, **1336-4**, and **1336-5**). The local block **1321-4** of the local ledger block chain **1324** has a digital signature **1335-4** associated therewith that indicates the global block (e.g., **1220-4** of FIG. **12**) was from an authorized entity and was correctly added as the local block **1321-4**. In some examples, the authorized entity may be a public or private entity associated with the vehicles which is monitoring all vehicles associated with the public or private entity. In this way, the host and/or memory associated with ID_1 may check the block signature (e.g., **1335-4**) and may discard global blocks received from the global ledger block chain (e.g., the global ledger block chain **1322**) that are not related to the host and/or memory associated with ID **1**. (150) The host and/or memory ID_1 can be configured to receive the local ledger block chain **1324** from the memory, validate the update (e.g., the payload **1336-1**, **1336-4**, and **1336-5**) to the data stored in the memory using the received local ledger block chain **1324**. In this way, the host and/or memory associated with ID_1 can maintain and/or monitor each of the updates provided to the host and/or memory from the authorized entity. Because the assembly of the local ledger block chain **1324** generates an immutable record, the circuitry may maintain control over what updates have taken place. This may prevent fraudulent updates, unintentional changes, unintentional error, and nefarious hacking attempts. Additionally, the maintenance of a local ledger block chain **1324** on the memory associated with the host can provide a record of updates which may be produced upon demand. After a global block from the global ledger block chain (e.g., the global ledger block chain **1222** of FIG. **12**) has been validated and added to the local ledger block chain **1324**, the circuitry may implement the update included in the payload e.g., **1336-1**, **1336-4**, and **1336-5**.

(151) For example, the local ledger block chain **1324** may validate a global block (e.g., the global block **1220-1** of FIG. **12**) and add it to the local ledger block chain **1324** as the local block **1321-1**. After the validation, the circuitry can execute the update **1338-1** included in the payload **1336-1** of the local block **1321-1**. The authorized entity may push another update to the host and/or memory associated with ID_1, as such, the circuitry may receive a second global block (e.g., the global block **1220-4** of FIG. **12**) which may be validated by the circuitry and added sequentially as local block **1321-4**, linked to local block **1321-1**. The circuitry may check and compare a cryptographic hash of a freshness field e.g., previous local block hash **1345-4**. If valid, this validation and linking in the local ledger block chain **1324**, the circuitry may execute the update **1338-2** included in the payload **1336-4** of local block **1321-4**. Using this method, the memory may continue to add global blocks as local blocks to the local ledger block chain **1324** as described for local block **1321-5**, etc. In some examples, the host and/or memory associated with ID_1 may remove an older portion of the local ledger block chain **1324** to create vacancy in the memory as the local ledger block chain **1324** increases when more updates are generated by the authorized entity.

(152) For example, the host and/or memory may be a computing device of a vehicle having an ID_1, and the local ledger block chain **1324** can indicate those transactions associated with the vehicle (e.g., previous records of dispatches the vehicle has initiated). The computing device may include a threshold amount of immutable records that can be stored in the memory. In some examples, updates (e.g., **1338-1**, **1338-2**) are pushed from the authorized entity via global blocks to update a software and/or hardware component of the computing device, the circuitry may remove a local block (e.g., an older local block) from the local ledger block chain **1324** when the local ledger block chain **1324** has reached the threshold. The circuitry may remove an older local block (e.g., **1321-1**) to create vacancy in the memory of the computing device for a newer local block (e.g., **1321-5**) by executing firmware to alter the root (e.g., the root of the consensus, root of a Merkle tree, etc.) of the local ledger block chain **1324**. In this way, the circuitry can maintain control of the

updates as the local ledger block chain **1324** adds new local blocks.

(153) In one embodiment, the above described global block chain and local ledger block chains can be used to securely verify identities of vehicles. As an example, as an emergency vehicle can dispatch for emergency reasons, and data can be exchanged between the vehicle and a node to securely verify identities of the vehicle. The node can use the global block chain to verify the identity of the vehicle and any other data related to that particular vehicle. The local ledger block chains can be used to pinpoint those information associated with a particular vehicle (e.g., date on which a particular emergency vehicle has dispatched, a number of times the particular emergency vehicle has dispatched during a particular period) without having to monitor the entire global block chain.

(154) FIG. **14A** illustrates an example of a pair of registers **1439-1** and **1439-2** used to define a secure memory array in accordance with an embodiment of the present disclosure, and FIG. **14B** illustrates a diagram of a portion of a memory array **1401** that includes a secure memory array defined using registers **1439-1** and **1439-2** in accordance with an embodiment of the present disclosure. Registers **1439-1** and **1439-2** can be, for instance, registers **1139-1** and **1139-2**, respectively, previously described in connection with FIG. **11A**, and secure memory array **1401** can be, for instance, memory array **1101** previously described in connection with FIG. **11A**. For instance, as shown in FIG. **14B**, secure memory array **1401** can include a number of physical blocks **1407-0**, **1407-1**, . . . , **1407-B** of memory cells, each including a number of physical rows **1403-0**, **1403-1**, . . . , **1403-R** having a number of sectors of memory cells, in a manner analogous to memory array **1001** previously described in connection with FIG. **10**.

(155) As shown in FIG. **14A**, register **1439-1** can define addresses of the secure array (e.g., the addresses of different portions of the secure array), and register **1439-2** can define sizes of the secure array (e.g., the sizes of the different portions of the secure array). The addresses of the secure array defined by register **1439-1** can correspond to, for instance, starting points (e.g., starting LBAs) of the secure array (e.g., the starting points of the different portions of the secure array), and the sizes of the secure array defined by register **1439-2** can correspond to, for instance, ending points (e.g., ending LBAs) of the secure array (e.g., the ending points of the different portions of the secure array).

(156) For example, as shown in FIG. **14A**, registers **1439-1** and **1439-2** can define N pairs of values, with each respective pair comprising an address value (e.g., addr) defined by register **1439-1** and a size value (e.g., size) defined by register **1439-2**. For instance, in the example illustrated in FIG. **14A**, Pair.sub.0 comprises address value addr.sub.0 and size value size.sub.0 (e.g., Pair.sub.0=[addr.sub.0, size.sub.0]), Pair.sub.1 comprises address value addr.sub.1 and size value size.sub.1 (e.g., Pair.sub.1=[addr.sub.1, size.sub.1]), and so on, with Pair.sub.N comprising address value addr.sub.N and size value size.sub.N (e.g., Pair.sub.N=[addr.sub.N, size.sub.N]). The address value of a pair can correspond to a starting point (e.g., starting LBA) of a portion of the secure array, and the sum of the address value and the size value of that pair can correspond to the ending point (e.g., ending LBA) of that portion of the secure array. As such, the entire secure array (e.g., the portions that comprise the entire secure array) can be given by: [addr.sub.0, addr.sub.0+size.sub.0]∪[addr.sub.1, addr.sub.1+size.sub.1]∪ . . . ∪[addr.sub.N, addr.sub.N+size.sub.N].

(157) The first pair whose size value defined by register **1439-2** is zero can stop the definition of the secure array. For instance, in the example illustrated in FIG. **14A**, if the size value of Pair.sub.2 is zero, then the secure array would be given by: [addr.sub.0, addr.sub.0+size.sub.0]∪[addr.sub.1, addr.sub.1+size.sub.1].

(158) An example of a secure array defined by registers **1439-1** and **1439-2** (e.g., with all size values defined by register **1439-2** as non-zero) is illustrated in FIG. **14B**. For instance, as shown in FIG. **14B**, the address (e.g., LBA) associated with sector **1405-0** of memory array **1401** is addr.sub.0, the address associated with sector **1405-1** of memory array **1401** is

addr.sub.0+size.sub.0, the address associated with sector **1405-2** of memory array **1401** is
addr.sub.1, the address associated with sector **1405-3** of memory array **1401** is
addr.sub.1+size.sub.1, the address associated with sector **1405-4** of memory array **1401** is
addr.sub.N, and the address associated with sector **1405-5** of memory array **1401** is
addr.sub.N+size.sub.N. As such, the secure array comprises sectors (e.g., the data stored in sectors)
1405-0 through **1405-1**, sectors **1405-2** through **1405-3**, and **1405-4** through **1405-5**. However, the
sectors of memory array **1401** that are before sector **1405-0**, and sectors **1405-1** through **1405-2** of
memory array **1401**, are not part of the secure array (e.g., the secure array comprises a subset of
array **1401**).

(159) FIG. **15** is a block diagram of an example memory device **1541** in accordance with an
embodiment of the present disclosure. Memory device **1541** can be, for example, memory device
1141 previously described in connection with FIG. **11A**.

(160) As shown in FIG. **15**, memory device **1541** can include a number of memory arrays **1501-1**
through **1501-7**. Memory arrays **1501-1** through **1501-7** can be analogous to memory array **1001**
previously described in connection with FIG. **10**. Further, in the example illustrated in FIG. **15**,
memory array **1501-3** is a secure array (sometimes referred to simply as a memory array or an
array also), subset **1511** of memory array **1501-6** comprises a secure array, and subsets **1513** and
1515 of memory array **1501-7** comprise a secure array. Subsets **1511**, **1513**, and **1515** can each
include, for instance, 4 kilobytes of data. However, embodiments of the present disclosure are not
limited to a particular number or arrangement of memory arrays or secure arrays.

(161) As shown in FIG. **15**, memory device **1541** can include a remediation (e.g., recovery) block
1560. Remediation block **1560** can be used as a source of data in case of errors (e.g., mismatches)
that may occur during operation of memory device **1541**. Remediation block **1560** may be outside
of the area of memory device **1541** that is addressable by a host.

(162) As shown in FIG. **15**, memory device **1541** can include a serial peripheral interface (SPI)
1509 and a controller **1548**. Memory device **1541** can use SPI **1509** and controller **1548** to
communicate with a host and memory arrays **1501-1** through **1501-7**, as previously described
herein (e.g., in connection with FIG. **11A**).

(163) As shown in FIG. **15**, memory device **1541** can include a secure register **1586** for managing
the security of memory device **1541**. For example, secure register **1586** can configure, and
communicate externally, to an application controller. Further, secure register **1586** may be
modifiable by an authentication command.

(164) As shown in FIG. **15**, memory device **1541** can include keys **1521**. For instance, memory
device **1541** can include eight different slots to store keys such as root keys, DICE-RIOT keys,
and/or other external session keys.

(165) As shown in FIG. **15**, memory device **1541** can include an electronically erasable
programmable read-only memory (EEPROM) **1523**. EEPROM **1523** can provide a secure non-
volatile area available for a host, in which individual bytes of data can be erased and programmed.

(166) As shown in FIG. **15**, memory device **1541** can include counters (e.g., monotonic counters)
1525. Counters **1525** can be used as an anti-replay mechanism (e.g., freshness generator) for
commands (e.g., to sign a command set or sequence) received from and/or sent to a host. For
instance, memory device **1541** can include six different monotonic counters, two of which may be
used by memory device **1541** for the authenticated commands, and four of which may be used by
the host.

(167) As shown in FIG. **15**, memory device **1541** can include an SHA-256 cryptographic hash
function **1527**, and/or an HMAC-SHA256 cryptographic hash function **1529**. SHA-256 and/or
HMAC-SHA256 cryptographic hash functions **1527** and **1529** can be used by memory device **1541**
to generate cryptographic hashes, such as, for instance, the cryptographic hashes of block **220**
previously described herein, and/or a golden hash used to validate the data stored in memory arrays
1501-1 through **1501-7** as previously described herein. Further, memory device **1541** can support

(168) Although specific embodiments have been illustrated and described herein, those of ordinary skill in the art will appreciate that an arrangement calculated to achieve the same results can be substituted for the specific embodiments shown. This disclosure is intended to cover adaptations or variations of a number of embodiments of the present disclosure. It is to be understood that the above description has been made in an illustrative fashion, and not a restrictive one. Combination of the above embodiments, and other embodiments not specifically described herein will be apparent to those of ordinary skill in the art upon reviewing the above description. The scope of a number of embodiments of the present disclosure includes other applications in which the above structures and methods are used. Therefore, the scope of a number of embodiments of the present disclosure should be determined with reference to the appended claims, along with the full range of equivalents to which such claims are entitled.

(169) In the foregoing Detailed Description, some features are grouped together in a single embodiment for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the disclosed embodiments of the present disclosure have to use more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive subject matter lies in less than all features of a single disclosed embodiment. Thus, the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separate embodiment.

Claims

1. An apparatus, comprising: a processing resource; and a memory coupled to the processing resource and configured to store instructions, wherein the instructions, when executed by the processing resource, cause the processing resource to: generate a public key; generate a certificate using the public key as an input; and in response to a departure of the apparatus: transmit the certificate and the public key to a first vehicle or a second vehicle, wherein: the public key and the certificate transmitted to the first vehicle and the second vehicle are input to a respective first decryptor of the first vehicle or a respective first decryptor of and the second vehicle, or both to perform a respective decryption using the public key and the certificate; and an output of the first decryptor and a public identification are input to a respective second decryptor of the first vehicle or a respective second decryptor of and the second vehicle, or both to perform a respective decryption using the output and the public identification for verification of the certificate; and wherein the certificate is transmitted to directly to the first vehicle that is within a particular proximity of the apparatus or indirectly to the second vehicle that is not within the particular proximity of the apparatus via a third vehicle, a traffic control device, or any combination thereof that are respectively configured as one or more nodes of a network comprising a block chain distributed ledger that is spread over multiple nodes.
2. The apparatus of claim 1, wherein the network comprises a control node configured to manage the network, and wherein the instructions further cause the processing resource to transmit, in response to the departure, a notice to the control node such that the control node propagates the notice to the multiple nodes of the network.
3. The apparatus of claim 1, wherein the instructions further cause the processing resource to: generate the certificate prior to transmitting the certificate to the first vehicle or the second vehicle; generate the public identification and the public key; and transmit the public identification, the public key, and the certificate to the first vehicle and the second vehicle to cause the first vehicle and the second vehicle to verify the identity of the apparatus based on a comparison of the public identification, the public key, and the certificate.
4. The apparatus of claim 1, wherein the instructions further cause the processing resource to, subsequent to transmitting the certificate to the first vehicle and the second vehicle, or both:

encrypt, in response to receipt of the public key from the first vehicle or the second vehicle, or both, data corresponding to information associated with a route the apparatus is to travel along after the departure; and transmit the data corresponding to the information to the first vehicle or the second vehicle, or both.

5. The apparatus of claim 1, wherein the first and the second vehicles are on a route the apparatus is to travel along after the departure.

6. An apparatus, comprising: a processing resource; and a memory coupled to the processing resource and configured to store instructions, wherein the instructions, when executed by the processing resource, cause the processing resource to: perform, in response to receipt of a certificate and a public key from a vehicle, a first decryption using the public key and the certificate as inputs for the first decryption; perform a second decryption using a public identification and an output of the first decryption as inputs; and compare a same public key that was used as the input for the first decryption to an output of the second decryption for verification of the certificate, wherein: the certificate is generated using the public key as an input and at the vehicle; and the certificate and the public key are received from the vehicle; wherein the certificate is received directly from the vehicle when the apparatus is within a particular proximity of the vehicle and indirectly via a different vehicle, a traffic control device, or any combination thereof that are respectively configured as one or more nodes of a network comprising a block chain distributed ledger that is spread over multiple nodes when the apparatus is not within the particular proximity of the vehicle.

7. The apparatus of claim 6, wherein the instructions further cause the processing resource to generate a private key prior to providing the public key to the vehicle.

8. The apparatus of claim 7, wherein the instructions further cause the processing resource to decrypt, in response to receipt of the data encrypted using the public key, the data using the private key.

9. The apparatus of claim 7, wherein the instructions further cause the processing resource to: generate a digital signature based on the private key; and transmit the digital signature to the vehicle to cause the vehicle to verify the digital signature based at least in part on the public key transmitted to the vehicle.

10. The apparatus of claim 9, wherein the instructions further cause the processing resource to transmit, to the vehicle, a request for data corresponding to information associated with a route the vehicle is to travel along in response to the identity or the digital signature received from the vehicle being verified.

11. The apparatus of claim 6, wherein the instructions further cause the processing resource to discard the certificate in response to the identity of the vehicle being not verified.

12. The apparatus of claim 6, wherein the certificate is sent from the vehicle in response to a dispatch of the vehicle, and wherein the dispatch is detected by one of the multiple nodes of the network.

13. The apparatus of claim 6, wherein the certificate is sent from the vehicle in response to a dispatch of the vehicle, and wherein the dispatch is detected by one of a number of vehicles registered to the network.

14. A method, comprising: generating, at a first vehicle, a public key; generating, at the first vehicle, a certificate using the public key as an input; and responsive to a dispatch of the first vehicle: transmitting the certificate and the public key to a second vehicle, wherein: the public key and the certificate transmitted to the second vehicle are input to a first decryptor of the second vehicle to perform decryption using the public key and the certificate; and an output of the first decryptor and a public identification are input to a second decryptor of the second vehicle to perform a decryption using the output and the public identification for verification of the certificate; wherein the certificate is transmitted to the second vehicle directly when the second vehicle is within a particular proximity of the first vehicle and indirectly via a third vehicle, a

traffic control device, or any combination thereof that are respectively configured as one or more nodes of a network comprising a block chain distributed ledger that is spread over multiple nodes when the second vehicle is not within the particular proximity of the first vehicle.

15. The method of claim 14, further comprising generating the certificate based at least in part on a device secret and the public key.

16. The method of claim 14, further comprising: receiving the public key from the second vehicle responsive to providing the certificate to the second vehicle; receiving a digital signature, wherein the digital signature is generated using a private key that was generated at the second vehicle; and verifying the digital signature using the public key received from the second vehicle.

17. The method of claim 16, further comprising verifying the digital signature using an internal cryptography process including an Elliptical Curve Digital Signature (ECDSA).
