

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12387213
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Kurani; Ashish B.

Third party products and services via ATM

Abstract

A computer system and a transaction machine, such as an automated teller machine (ATM), can provide for any payor to make a payment to a payee at the transaction machine. The transaction machine provides the payor a user interface to enter a passcode that uniquely identifies the payment transaction. The passcode can be generated by a provider computing system associated with the transaction machine and provided directly to the payee or through the payor prior to the transaction. The transaction machine provides the payor a user interface to enter an amount. The transaction machine receives a cash deposit and provides a deposit user interface that displays deposit information based on at least one bill of the cash deposit.

Inventors:	Kurani; Ashish B. (Hillsborough, CA)
Applicant:	Wells Fargo Bank, N.A. (San Francisco, CA)
Family ID:	87767160
Assignee:	Wells Fargo Bank, N.A. (San Francisco, CA)
Appl. No.:	18/438856
Filed:	February 12, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240185241 A1	Jun. 06, 2024

Related U.S. Application Data

continuation parent-doc US 17960216 20221005 US 11900375 child-doc US 18438856
continuation parent-doc US 17689918 20220308 US 11741470 child-doc US 17960216
continuation parent-doc US 16943675 20200730 US 11379839 child-doc US 17689918
continuation-in-part parent-doc US 16706157 20191206 US 11282051 child-doc US 16943675
continuation-in-part parent-doc US 16239332 20190103 US 11270277 child-doc US 16706157

us-provisional-application US 62881055 20190731
us-provisional-application US 62798362 20190129
us-provisional-application US 62614283 20180105
us-provisional-application US 62672971 20180517

Publication Classification

Int. Cl.: **G06Q40/00** (20230101); **G06Q20/10** (20120101); **G06Q20/18** (20120101); **G06Q20/32** (20120101); **G06Q20/40** (20120101)

U.S. Cl.:

CPC **G06Q20/4012** (20130101); **G06Q20/102** (20130101); **G06Q20/1085** (20130101); **G06Q20/18** (20130101); **G06Q20/3226** (20130101);

Field of Classification Search

CPC: G06Q (20/102); G06Q (20/4014); G06Q (20/1085); G06Q (20/0855)

USPC: 705/37; 705/38; 705/39; 705/44; 705/40; 705/41; 705/26; 705/75; 709/26; 709/201; 709/227; 726/9; 726/6; 235/379; 235/380; 700/245; 715/708

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5465206	12/1994	Hilt et al.	N/A	N/A
5649117	12/1996	Landry	705/40	G06Q 20/102
5787403	12/1997	Randle	N/A	N/A
5899982	12/1998	Randle	N/A	N/A
5956700	12/1998	Landry	N/A	N/A
6173272	12/2000	Thomas et al.	N/A	N/A
6317745	12/2000	Thomas	705/40	G06Q 20/14
6341272	12/2001	Randle	N/A	N/A
6996542	12/2005	Landry	705/40	G06Q 20/04
7076458	12/2005	Lawlor et al.	N/A	N/A
7182252	12/2006	Cooper	705/17	G06Q 20/204
7200551	12/2006	Senez	N/A	N/A
7240031	12/2006	Kight	705/40	G06Q 20/108
7287009	12/2006	Liebermann	705/42	G06Q 20/10
7370014	12/2007	Vasavada et al.	N/A	N/A
7395241	12/2007	Cook	705/40	G06Q 20/0855
7676431	12/2009	O'Leary et al.	N/A	N/A
7813983	12/2009	Wottowa	705/36R	G06Q 40/00
7979348	12/2010	Thomas et al.	N/A	N/A
8005754	12/2010	McCoy et al.	N/A	N/A
8042733	12/2010	Smith	235/379	G06Q 40/02
8190521	12/2011	O'Leary et al.	N/A	N/A
8380622	12/2012	Bushman et al.	N/A	N/A

8527381	12/2012	Gerstner	705/35	G06Q 20/14
8543506	12/2012	Grandcolas	705/42	G06Q 40/00
8554671	12/2012	Ballout	N/A	N/A
8725632	12/2013	Tompkins	705/39	G06Q 40/02
8732044	12/2013	Lovelett et al.	N/A	N/A
9520033	12/2015	Freedman et al.	N/A	N/A
9633346	12/2016	Goodwin, III	N/A	N/A
9652758	12/2016	Zhou et al.	N/A	N/A
9773236	12/2016	Mohsenzadeh	N/A	N/A
9842322	12/2016	Johnston et al.	N/A	N/A
10354246	12/2018	Janiga	N/A	N/A
11354632	12/2021	Hill et al.	N/A	N/A
11429976	12/2021	Jain et al.	N/A	N/A
2001/0032182	12/2000	Kumar	705/40	H04L 67/567
2003/0105711	12/2002	O'Neil	705/39	G06Q 40/00
2003/0191711	12/2002	Jamison	705/40	G06Q 20/14
2003/0216960	12/2002	Postrel	N/A	N/A
2006/0173779	12/2005	Bennett et al.	N/A	N/A
2006/0206425	12/2005	Sharma	705/40	G06Q 20/02
2007/0011104	12/2006	Leger et al.	N/A	N/A
2010/0114677	12/2009	Carlson et al.	N/A	N/A
2011/0238573	12/2010	Varadarajan	N/A	N/A
2011/0251956	12/2010	Cantley et al.	N/A	N/A
2013/0046687	12/2012	Simpson, Jr.	N/A	N/A
2013/0124411	12/2012	Kobres et al.	N/A	N/A
2013/0232064	12/2012	Bosch	N/A	N/A
2015/0199681	12/2014	Salgado et al.	N/A	N/A
2015/0324768	12/2014	Filter et al.	N/A	N/A
2016/0104140	12/2015	Harrow et al.	N/A	N/A
2017/0124544	12/2016	Recriwal et al.	N/A	N/A
2017/0161700	12/2016	Salgado et al.	N/A	N/A
2017/0364899	12/2016	Watson et al.	N/A	N/A
2018/0068281	12/2017	Johnston et al.	N/A	N/A
2018/0204193	12/2017	Cacheria et al.	N/A	N/A

OTHER PUBLICATIONS

Responsibility of Net-bank in Electronic Payment; 2008 International Symposium on Electronic Commerce and Security (pp. 771-775); Liu Han-xia, Li Rong-jun; Aug. 3, 2008. (Year: 2008). cited by examiner

Authorization mechanisms for mobile commerce implementations in enhanced prepaid solutions; Bell Labs Technical Journal (vol. 8, Issue: 4, pp. 121-131); Yigang Cai, Jack Kozik, Helmut L. Raether, John B. Reid, Guy H. Starner, Kumar V. Vemuri, Sunil Thadani; Mar. 15, 2014. (Year: 2014). cited by examiner

A generative solution for ATM cash management; 2010 International Conference of Soft Computing and Pattern Recognition; R Armenise, C Birtolo, E Sangianantoni, L Troiano; Dec. 7, 2010. (Year: 2010). cited by applicant

A secure mobile payment system using QR code; 2013 5th International Conference on Computer Science and Information Technology (pp. 111-114); Sana Nseir, Nael Hirzallah, Musbah Aqel; Mar. 27, 2013. (Year: 2013). cited by applicant

Adaptive & dynamic interfaces for automated teller machines using clusters; 2018 International

Conference on Computing, Mathematics and Engineering Technologies (iCoMET) (pp. 1-6); Muhammad Imran, Aarij Mahmood Hussaan; Mar. 3, 2018. (Year: 2018). cited by applicant

Authorization mechanisms for mobile commerce implementations in enhanced prepaid solutions; Bell Labs Technical Journal (vol. 8, Issue: 4, pp. 121-131); Yigang Cai, Jack Kozik, Helmut L. Raether, John B. Reid, Guy H. Starner, Sunil Thadani, Kumar V. Vemuri, Jan. 1, 2004. (Year: 2004). cited by applicant

Boddupalli, P.; Al-Bin-Ali, F, Davies, N., Friday, A., Storz, O., Wu, M., Payment support in ubiquitous computing environments; 2003 Proceedings Fifth IEEE Workshop on Mobile Computing Systems and Applications (pp. 110-120); Jan. 1, 2003 (Year: 2003). cited by applicant

Design of Embedded Based Dual Identification ATM Card Security System; 2019 9th International Conference on Emerging Trends in Engineering and Technology—Signal and Information Processing (ICETET-SIP-19) (pp. 1-5); Priyanka Hemant Kale, K. K. Jajulwar; Nov. 1, 2019. (Year: 2019). cited by applicant

E-charging API: outsource charging to a payment service provider; IEEE Intelligent Network 2001 Workshop. IN 2001 Conference Record (Cat. No. 01TH8566) (pp. 216-222); K. Luttge; May 6, 2001. (Year: 2001). cited by applicant

Liu Han-xia, Li Rong-jun; Responsibility of Net-bank in Electronic Payment; 2008 International Symposium on Electronic Commerce and Security (pp. 771-775); Aug. 3, 2008 (Year: 2008). cited by applicant

P2P-Paid: A Peer-to-Peer Wireless Payment System; Second IEEE International Workshop on Mobile Commerce and Services (pp. 102-111); J. Gao, K. Edunuru, J. Cai, S. Shim; Jan. 1, 2005. (Year: 2005). cited by applicant

Payment support in ubiquitous computing environments; 2003 Proceedings Fifth IEEE Workshop on Mobile Computing Systems and Applications (pp. 110-120); Boddupalli, P.; Al-Bin-Ali, F, Davies, N., Friday, A., Storz, O., Wu, M., Jan. 1, 2003. (Year: 2003). cited by applicant

Research on E-Payment Model; 2010 International Conference on E-Business and E-Government (pp. 339-341); Zhu Junxuan; May 7, 2010. (Year: 2010). cited by applicant

S. Singh, Emergence of payment systems in the age of electronic commerce: The state of art; 2009 First Asian Himalayas International Conference on Internet (pp. 1-18); S. Singh; Nov. 1, 2009 (Year: 2009). cited by applicant

P2P-Paid: A Peer-to-Peer Wireless Payment System; Second IEEE International Workshop on Mobile Commerce and Services (pp. 102-111); J. Gao, K. Edunuru, J. Cai, S. Shim; Jan. 1, 2005. (Year: 2005). cited by applicant

Sirbu et al., “NetBill: An Internet commerce system optimized for network delivered services,” 1995, Digest of Papers, COMPCON'95, Technologies for the Information Superhighway, pp. 20-25. cited by applicant

Singh et al., “Comparative study on various methods and types of mobile payment system,” 2012 International Conference on Advances in Mobile Network, Communication and Its Applications, pp. 143-148. cited by applicant

Primary Examiner: Nguyen; Tien C

Attorney, Agent or Firm: Foley & Lardner LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/960,216 filed Oct. 5, 2022, which is a continuation of U.S.

patent application Ser. No. 17/689,918 filed Mar. 8, 2022, now U.S. Pat. No. 11,741,470, which is a continuation of U.S. patent application Ser. No. 16/943,675 filed Jul. 30, 2020, now U.S. Pat. No. 11,379,839, which claims the benefit of and priority to U.S. Provisional Patent Application No. 62/881,055 filed Jul. 31, 2019 and is a continuation-in-part of U.S. patent application Ser. No. 16/706,157 filed Dec. 6, 2019, now U.S. Pat. No. 11,282,051, which claims the benefit of and priority to U.S. Provisional Patent Application No. 62/798,362 filed Jan. 29, 2019 and is a continuation-in-part of U.S. patent application Ser. No. 16/239,332 filed Jan. 3, 2019, now U.S. Pat. No. 11,270,277, which claims the benefit of and priority to U.S. Provisional Patent Application No. 62/672,971 filed May 17, 2018 and to U.S. Provisional Patent Application No. 62/614,283 filed Jan. 5, 2018, each of which are incorporated herein by reference in their entirety.

BACKGROUND

(1) Financial institutions provide various ways for customers to access account information and perform transactions, such as transaction machines, websites, and brick and mortar locations (e.g., retail bank branches). Transaction machines, such as automated teller machines (ATMs), may be accessed at various geographic locations, such as bank locations, convenience stores or other stores to facilitate the account holder's interaction with banking systems. Transaction machines accept transaction cards such as debit, credit or stored value cards that are often used by account holders to purchase items or services or to obtain funds.

SUMMARY

(2) A first example embodiment relates to a method. The method includes receiving, at a transaction machine via a payment user interface, a request from a payor for a transaction to make a payment to a payee. The method further includes providing, by the transaction machine, a passcode user interface that allows receipt of a passcode unique to the request for the transaction. The method also includes receiving, by the transaction machine via the passcode user interface, the passcode. The method additionally includes determining, by the transaction machine, that the passcode is valid. The method further includes providing, by the transaction machine, responsive to determining that the passcode is valid, an amount user interface that requests an amount associated with the request for the transaction. The method also includes receiving, by the transaction machine via the amount user interface, the amount associated with the request for the transaction. The method additionally includes providing, by the transaction machine subsequent to receiving the amount, a payment user interface configured to accept a payment. The method further includes receiving, by the transaction machine via the payment user interface, a payment.

(3) Another example embodiment relates to a system. The system includes a transaction machine associated with a provider computing system, the transaction machine comprising a one or more processors and computer readable storage medium storing instructions that when executed by one or more processors, cause the one or more processors to perform operations that include receive, via a payment user interface, a request from a payor for a transaction to make a payment to a payee. The operations further include provide a passcode user interface that allows receipt of a passcode unique to the request for the transaction. The operations also include receive, via the passcode user interface, the passcode. The operations additionally include determine that the passcode is valid. The operations further include provide, responsive to determining that the passcode is valid, an amount user interface that requests an amount associated with the request for the transaction. The operations also include receive, via the amount user interface, the amount associated with the request for the transaction. The operations further include provide, subsequent to the receipt of the amount, a payment user interface configured to accept a payment. The operations also include receive, via the payment user interface, a payment.

(4) Another example embodiment relates to a system. The system includes a transaction machine associated with a provider computing system. The transaction machine includes one or more processors and computer readable storage medium storing instructions that when executed by one

or more processors, cause the one or more processors to perform operations including providing a passcode user interface, an amount user interface, and a payment user interface in succession, wherein the passcode user interface allows receipt of a passcode unique to a request for a transaction to make a payment to a payee, the amount user interface requests an amount associated with the request for the transaction, and the payment user interface is configured to accept a payment; and receive, via the payment user interface, a payment to the payee.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1A is a schematic diagram of a system that includes a transaction machine that communicates with a provider computing system.
- (2) FIG. 1B shows a block diagram of an example customer computing device.
- (3) FIG. 2 shows a process flow for a third party customer registration and passcode generation.
- (4) FIG. 3 shows a screenshot of an example computing device displaying a user interface.
- (5) FIG. 4 shows a screen shot of the example computing device displaying a passcode.
- (6) FIG. 5 shows a process flow for an example bill pay process.
- (7) FIG. 6 shows a screenshot of an example user interface that can be displayed on a display of the transaction machine.
- (8) FIG. 7 shows a screenshot of an example user interface to allow passcode entry.
- (9) FIG. 8 shows a screenshot of an example user interface providing bill pay information.
- (10) FIG. 9 shows a snapshot of an example user interface providing cash deposit information.
- (11) FIG. 10 shows a snapshot of an example user interface providing payment notification information.
- (12) FIG. 11 shows a schematic diagram of an example system that includes a transaction machine that communicates with a third party computing system.
- (13) FIG. 12 shows a process flow for another example bill pay process executed by the system shown in FIG. 11.
- (14) FIG. 13 shows a process flow for another example bill pay process using an account number of the third party customer.
- (15) FIG. 14 shows a snapshot of an example user interface providing selection of a third party by the customer.
- (16) FIG. 15 shows a snapshot of an example user interface providing ability for the third party customer to enter account information.
- (17) FIG. 16 shows a snapshot of an example user interface providing bill pay information to the third party customer.
- (18) FIG. 17 shows a snapshot of an example user interface providing cash deposit information.
- (19) FIG. 18 shows a snapshot of an example user interface providing payment information.
- (20) FIG. 19 shows a process flow for an example payment process for purchasing items.
- (21) FIG. 20 shows a snapshot of an example user interface for selecting a payment method provided by a third party on a third party customer device.
- (22) FIG. 21 shows a snapshot of an example user interface for placing an order provided by a third party on the third party customer device.
- (23) FIG. 22 shows a snapshot of an example user interface providing a customer ID provided by a third party on the third party customer device.
- (24) FIG. 23 shows a snapshot of an example user interface showing payment information provided by a transaction machine to the third party customer.
- (25) FIG. 24 shows a snapshot of an example user interface providing cash deposit information.
- (26) FIG. 25 shows a snapshot of an example user interface providing payment information.

- (27) FIG. 26 shows a process flow for an example bill pay process.
- (28) FIG. 27 shows an example screenshot of a user interface shown on a customer device.
- (29) FIG. 28 shows an example screenshot of a user interface shown on a customer device allowing the user to enter a user selected amount for deposit.
- (30) FIG. 29 shows a screenshot of a user interface shown on a customer device providing the user with a passcode.
- (31) FIG. 30 shows a screenshot of a user interface shown at a transaction machine.
- (32) FIG. 31 shows a screenshot of a user interface shown at a transaction machine allowing the user to enter a passcode or an access code.
- (33) FIG. 32 shows a screenshot of a user interface shown at a transaction machine providing the user with information about the user selected amount to be deposited at the transaction machine.
- (34) FIG. 33 shows a screenshot of a user interface shown at a transaction machine providing deposit information.
- (35) FIG. 34 shows a screenshot of a user interface shown at a transaction machine providing information about the denominations of bills being scanned by the transaction machine.
- (36) FIG. 35 shows a screenshot of a user interface shown at a transaction machine providing a list of denominations of bills verified by the transaction machine.
- (37) FIG. 36 shows a screenshot of a user interface shown at a transaction machine providing the user deposit information including a name of the bill pay recipient and the amount deposited.
- (38) FIG. 37 shows a screenshot of a user interface shown at a transaction machine providing the user an option to request for a receipt.
- (39) FIG. 38 shows a process flow for an example payor to payee or person to person payment process.
- (40) FIG. 39 shows a screenshot of an example amount user interface on which the payor can enter an amount.
- (41) FIG. 40 shows a screenshot of an example payment user interface that allows the payor to select a mode of payment.

DETAILED DESCRIPTION

(42) Transaction machines, such as, for example, automatic teller machines (ATMs) provide users with convenient and secure terminals for carrying out banking and other transactions. In some instances, the transaction machine may also have the capability to accept payments of third party products and services. For example, a payee, such as a merchant, having a bank account with Bank A can request the bank to generate a passcode associated with a transaction that the payee expects a payor to make. The payor may approach a transaction machine associated with the Bank A and make the payment to the payee using the passcode.

(43) As discussed below, the transaction machines can be configured to allow payors to make payments to payee accounts even if the payor may not hold an account with the bank or financial institution associated with the transaction machine. In one example, the transaction machine can accept payments by an individual to another individual. Such payments can be referred to as person-to-person (or “P2P”) payments. In some such examples, the payee individual can hold an account with the financial institution associated with the transaction machine. Another individual—a payor—can carry out a transaction at the transaction machine to make a payment to the payee. The payment received by the transaction machine can be credited to the payee's account. In the context of the P2P payments at the transaction machine, the payor and the payee can be any pair of individuals wanting to undertake a transfer of payment. Utilizing the transaction machine allows the payor to make a payment in a manner that is convenient for the payor. For example, some payors may not have access to the Internet or may not possess devices that can enable access to the Internet. Without access to the Internet, such individuals may not be able to make online payments to the payee. In some other examples, even with access to the Internet, some individuals may be averse to online transactions due to the security risks known to be associated with online transaction

in the form of hacking, phishing, etc. On the other hand, transaction machines are ubiquitous, and therefore may be more easily accessible to the payor. In addition, the transaction machine can provide a terminal of payment that can be relatively more secure than a user device such as a cellphone or a laptop connected to the Internet. The increased security provided by the transaction machine can lead an individual to feel more comfortable making a payment at the transaction machine instead of making a payment on the user device. The transaction machine can also provide the payor multiple payment modes. For example, the transaction machine can be configured to accept various payment modes such as cash, credit cards, cryptocurrency, etc. Thus a payor, who otherwise would have to hold a bank account that allows online payments (which in some instances may involve additional costs), can instead make a payment in a mode of his or her choosing by merely walking up to the transaction machine. One or more examples of this approach are discussed below in relation to FIGS. 38-40.

(44) Referring to FIG. 1A, a system **100** is shown according to an example embodiment. The system **100** may include a provider computing system **101**, a third party computer system **131**, one or more transaction machines **130**, such as automated teller machines (ATMs), and one or more customer computing devices **170**. The system **100** may be accessed by a third party customer **190** who seeks to perform a financial transaction, such as, for example, paying bills for the third party at the one or more transaction machines **130**.

(45) In an example embodiment, the provider computing system **101** may be provided or controlled by a bank or other financial institution. The provider computing system **101** may provide services to users, customers, or account holders of the financial institution. The provider computing system **101** also provides services to users who do not hold an account with the institution. These services can be provided to the users through the transaction machine **130**. For example, as shown in FIG. 1A, an account holder or a third party customer **190** communicates with the provider computing system **101** through the transaction machine **130**. In practice, the provider computing system **101** may include server computing systems, for example, comprising one or more networked computer servers having a processor and non-transitory machine readable media. The logic or logics described herein may therefore be implemented as program logic that is stored on the machine-readable media and that, when executed by the processor, causes the processor to perform the operations described.

(46) The provider computing system **101** may further include, among other systems, account management circuit **103**, provider network interface circuit **105**, provider user interface circuit **107**, bill pay circuit **111**, provider passcode circuit **109**, and provider data storage system **125**. The account management circuit **103** may perform various tasks in connection registered customers of one or more third parties, such as the third party associated with the third party computer system **131**. Account management circuit **103** may receive customer data from the third party computer system **131**, where the customer data can include one or more of customer name, customer address, customer date of birth, third party unique customer ID, and other customer related information. The account management circuit **103** may store the customer data received from the third party computer system in the provider data storage system **125**. The account management circuit **103** may also maintain a log of all transactions that occurred in the past associated with one or more customer data and store data related to the transactions in a provider data storage system **125**.

(47) The provider network interface circuit **105** may be used to connect the provider computing system **101** to communicate with other systems such as the transaction machine **130** and the third party computer system **131**. An embodiment of the provider network interface circuit **105** may be configured to communicate with the transaction machine **130** over a proprietary encrypted network. Another embodiment of the provider network interface circuit **105** may be configured to communicate with the transaction machine **130** over a public encrypted network. The provider network interface circuit **105** may also comprise logic that is configured to provide an interface for other types of devices, including mobile devices such as cell phones, smart phones, mobile slate, or

tablets. Similarly, the provider network interface circuit **105** may be configured to communicate with the third party computer system **131** over a proprietary or public encrypted network.

(48) The provider user interface circuit **107** may generate customized sequences of menus and menu options. As previously indicated, the provider computing system **101** and the transaction machine **130** may cooperate to provide a user interface at the transaction machine **130**. As indicated in FIG. 1A, the user interface circuit **107** includes program logic located at the provider computing system **101**, at the transaction machine **130**, or at both the provider computing system **101** and the transaction machine **130**. That is, the operations described herein as being performed by the user interface circuit **107** may be performed either at the provider computing system **101**, at the transaction machine **130**, or at both the provider computing system **101** and the transaction machine **130**. The user interface circuit **107** generates a graphical user interface for presentation to the third party customer **190** at the transaction machine **130** via a display **138**. The user interface circuit **107** may receive information or adjust the sequence of user interfaces on the display **138** according to data provided by the user interface circuit **107**. Other configurations are also possible, some of which are described below.

(49) The bill pay circuit **111** may be configured to receive bill payment information from the transaction machine **130**. For example, the bill pay circuit **111** may receive verification queries from the transaction machine **130** in responsive to the third party customer **190** initiating a bill payment transaction at the transaction machine **130**. The bill pay circuit **111** may also send verification results to the transaction machine **130** in response to receiving the verification queries. The bill pay circuit **111** may also receive notifications of payment or deposits made by the third party customer **190** associated with a customer account. The bill pay circuit **111** may, in response, send a notification to the third party computer system **131** of the bill payment associated with the customer account.

(50) Provider passcode circuit **109** can be configured to generate passcodes, which may be one time or multiple use types. The provider passcode circuit **109** may generate the passcode in response to each request for a new passcode received from the third party computer system **131**. The passcode can be a token that is generated based on a random number. In some other embodiments, the provider passcode circuit **109** can include an encryption circuit which can output a passcode based on a random number, third party data, customer data, or a combination thereof. In some embodiments, the provider passcode circuit **109** can store the generated passcode in the provider data storage system **125** in association with customer data. For example, the request for the generation of the passcode received from the third party computer system **131** can include a customer identifier. The provider passcode circuit **109** can store the generated passcode in the provider data storage system **125** in association with the received customer identifier. The provider passcode circuit **109**, or the bill pay circuit **111** can access the provider data storage system **125** in response to a verification request received from the transaction machine **130**. That is, the provider passcode circuit **109** or the bill pay circuit **111** can access the passcode associated with the customer identifier received in the verification request, and compare the passcode retrieved from the provider data storage system **125** with the passcode received with the verification request to verify if the passcodes match.

(51) The provider data storage system **125** may include a provider account database **127**. The provider account database **127** can be structured according to various database types, such as, relational, hierarchical, network, flat or object relational. The provider account database **127** may be configured to store account balances and a log of each transaction processed by the account management circuit **103**. The provider account database **127** may be configured to store other activity profile information such as account preferences the user has specified, whether the user has previously chained transactions, whether the user has lost bank cards, and so on. In addition to storing data on accounts associated with the bank, the provider account database **127** can store third party customer data, which can include customer name, customer address, customer date of birth,

third party unique customer ID, and other customer related information, received from the third party computer system **131**. The provider account database **127** may also include any passcodes generated in association with a third party customer.

(52) The transaction machine **130** may, for example, be an automated teller machine, a point of sale device, or other device. For example, the transaction machine **130** may include a currency dispenser **132**, deposit mechanism **134**, card reader **136**, display **138**, authentication circuit **140**, transaction processing circuit **142**, and receipt generation circuit **144**. Other hardware may also be included, such as a keypad, a microphone, a camera, or buttons for receiving user inputs. The transaction machine **130** can serve as a terminal for a user, such as a user that has an account with the bank or financial institution associated with the provider computing system **101**, to carry out financial transactions in conjunction with the user's account at the bank. Such transactions can include, for example, withdrawals, deposits, transfer, and other financial transactions. In addition to serving as a terminal for financial transactions associated with the bank, the transaction machine **130** also can serve as a terminal for carrying out bill pay transactions associated with a third party.

(53) The currency dispenser **132** may dispense currency notes ("cash") or other forms of currency to an account holder from their financial institution accounts. The currency dispenser **132** may be configured to dispense currency in various denominations, as specified by the account holder. The deposit mechanism **134** may be configured to accept deposits of currency, such as envelope or envelope-free deposits of cash and/or checks.

(54) The card reader **136** may be configured to read information from a transaction card. The transaction card may include many different types of cards, for example, a credit card, debit card, check card, ATM card, stored value card, or the like. The card reader **136** may be configured to scan information from a magnetic stripe ("magstripe") of a transaction card. Some transaction machines may require the user to "dip" or "swipe" their transaction card, while other transaction machines may require the user to insert their transaction card, in which case the user's card may be retained by the machine for the duration of the session. Alternatively, the card reader **136** may be configured to communicate with the transaction card via near field communications (NFC). While performing the read operation, the card reader **136** may be configured to read the account information and the PIN associated with the card and the account.

(55) The display **138** may be configured to display graphics such as menus, instructions, background photos (e.g., advertisements, etc.), logos, and so on. In one embodiment, the display **138** is a touch screen display that is capable of detecting user touches, e.g., to make menu selections. The display **138** allows the account holder or a third party customer **190** to interact with the transaction machine **130** in order to process transactions. The transactions may include withdrawing funds, purchasing one or more goods or services, transferring funds from one account to another account, paying a bill or mortgage and so on. As will be discussed further below, the display **138** may be used to display various custom sequences of user interfaces to the account holder **190**.

(56) The authentication circuit **140** may be configured to authenticate information received by the transaction machine **130** to approve or reject a transaction. The authentication circuit **140** may approve or deny authentication for transaction data received by the transaction machine **130**. The authentication circuit **140** authenticates a user as being a valid account holder associated with the transaction card and the corresponding account at the bank or financial institution.

(57) The transaction processing circuit **142** processes each transaction requested by the account holder or a third party customer **190**. For example, the transaction processing circuit **142** may cooperate with the account management circuit **103** of the provider computing system **101** to ensure that transactions are properly debited/credit to the account held by the account holder **190**. The receipt generation circuit **144** generates a receipt for each transaction.

(58) The third party computer system **131** may be provided or controlled by a third party merchant, seller, or service provider. The third party computer system **131** may provide services to third party

customers **190**. For example, the third party computer system **131** may provide customer registration services to the third party customer **190** once the third party customer **190** has purchased products or services from the third party. The third party computer system **131** also can facilitate bill payment at a transaction machine **130** associated with a bank. In particular, the third party computer system **131** can communicate with the provider computing system **101** to exchange data that can be used to carry out bill payments by the third party customer **190** at the transaction machine **130**.

(59) The third party computer system **131** can include a registration circuit **152**, a third party network interface circuit **154**, a notification circuit **156**, a third party passcode circuit **158**, and a third party data storage system **160**. The registration circuit **152** can facilitate the registration of a third party customer **190** at the provider computing system **101**. For example, a third party customer **190** can communicate with the third party computer system **131** to register a customer account with the third party computer system **131**. The registration circuit **152** can receive with the request customer data such as, for example customer name, customer date of birth, customer address, customer email address, customer phone number, and other information related to the customer. The registration circuit **152** stores the third party customer **190** information in a data storage system or a database in association with a unique identifier such as a customer ID. In addition the registration circuit **152** can communicate the customer information and/or the unique identifier to the provider computing system **101** along with a request to register the customer, or create an account for the user, as a customer for the third party.

(60) The third party network interface circuit **154** may be used to connect the provider computing system **101** to other systems, such as the provider computing system **101**, over proprietary or public encrypted networks. In some embodiments, the third party network interface circuit **154** may also comprise circuit that is configured to provide in interface for other types of devices, including mobile devices such as cell phones, smart phones, mobile slate or tablets.

(61) The third party passcode circuit **158**, responsive to a third party registration request, can generate and send a passcode generation request to the provider computing system **101**. The third party passcode circuit **158** also can receive the passcode generated by the provider computing system **101**. The third party passcode circuit **158** or the registration circuit **152** can provide the third party customer **190** with the received passcode (e.g., via the customer computing device **170**).

(62) The notification circuit **156** generates and sends bill pay notifications to the third party customer **190**. For example, the notification circuit **156** generates notifications indicating that a bill pay transaction was completed successfully. In some embodiments, the third party passcode circuit **158** or the registration circuit **152** provides the bill pay transaction complete notification to the third party customer **190** (e.g., via the customer computing device **170**) only after receiving a notification from the provider computing system **101** that a bill payment was successfully received from the third party customer **190**.

(63) The third party data storage system **160** can include a third party account database **162**. The third party account database **162** can be structured according to various database types, such as, relational, hierarchical, network, flat or object relational. The third party account database **162** can be configured to store account information associated with third party customers. For example, the account information can include customer name, customer date of birth, customer address, customer email address, customer phone number, a unique customer ID, and other information related to the customer. The account information may also include the current account balance, payment due date, and a list of banks where the third party customer may potentially pay the bills. The list of banks can include the bank associated with the provider computing system **101**.

(64) The system **100** can also include a customer computing device **170**. The customer computing device **170** can be accessed by the third party customer **190** to communicate and carry out transactions with other components of the system **100**, such as the third party computer system **131**, and the provider computing system **101**. FIG. 1B shows a block diagram of an example customer

computing device **170**. The customer computing device **170** can include a communication circuit **172**, a network interface circuit **174**, a user interface circuit **176**, a display **178**, a processing circuit **180**, and a memory circuit **182**. The communication circuit **172** can be configured to provide communication capability to the customer computing device **170**. For example, the communication circuit **172** can include analog and/or digital components that can allow the customer computing device **172** to communicate over wireless communication channels such as 2G, 3G, 4G, LTE, etc. The network interface circuit **174** may be used to connect the customer computing device **170** to other systems such as the provider computing system **101**, the third party computer system **131** and the transaction machine **130** over proprietary or public encrypted networks. The user interface circuit **176** may generate customized sequences of menus or menu options for presentation to the third party customer **190**. The third party computer system **131** and the customer computing device **170** can cooperate to provide a user interface at the customer computing device **170**. For example, the third party computer system **131** may provide applications or programs to the customer computing device **170** that when executed on the customer computing device **170** can provide appropriate user interfaces to allow the third party customer **190** to carry out transactions. Some examples of user interfaces provided at the customer computing device **170** are discussed below in relation to FIGS. **3** and **4**. The processing circuit **180** and the memory circuit **182** can provide computing capabilities to the customer computing device **170** and can aid in executing instructions or programs for the operation of the customer computing device **170**. In one or more embodiments, the customer computing device **170** can include one or more of portable electronic devices such as cellphones, tablets, laptops, smart watches, or other computing devices such as desktops.

(65) FIG. **2** shows a process flow **200** for a third party customer registration and passcode generation. In particular FIG. **2** shows interactions between the third party customer **190**, the third party computer system **131**, the transaction machine **130**, and the provider computing system **101** during a third party customer **190** registration at the provider computing system **101**. The process flow **200** includes the third party computer system **131** receiving an activation request **202** from the third party customer **190**. The activation request **202** may be received from a new third party customer **190** who does not previously have an account or service with the third party. In one example, the third party customer **190** may purchase a cellular phone plan from a third party, and may register with the third party as a customer. In registering with the third party, the third party customer **190** may provide the third party computer system **131** with third party customer **190** information, such as, for example, customer name, customer date of birth, customer address, customer email address, customer phone number, and other information related to the third party customer **190**.

(66) The third party computer system **131**, responsive to receiving the activation request **202** from the third party customer **190**, registers (**204**) the third party customer **190** at the third party computer system **131**. In particular, the registration circuit **152** creates an account associated with the third party customer **190** in the third party account database **162**. The registration circuit **152** creates a unique third party customer ID associated with the third party customer **190**, and stores the customer information in the third party account database **162** indexed to the unique third party customer ID. The registration circuit **152** also stores account information associated with the third party customer **190** in the third party account database **162**. For example, the registration circuit **152** stores the current account balance, payment due date, and a list of banks where the third party customer may potentially pay the bills. In one or more embodiments, the list of banks can include those banks that are near the user and that allow third party bill payment transactions. In one or more embodiments, the registration circuit **152** may also verify the third party customer **190** prior to registration. For example, if the third party customer **190** purchases cellphone service from a store (online or brick-and-mortar), the registration circuit **152** may receive the purchase information. When the third party customer **190** sends the activation request **202**, the registration circuit **152** may compare the purchase information with the customer information provided with the

activation request **202**. If at least part of the information matches, the registration circuit **152** can determine that the third party customer **190** is the same customer that purchased the cellphone service at the store, and is verified. If there is no match, the registration circuit **152** may determine that the third party customer is not verified, and determine not to proceed with registering the third party customer **190**.

(67) The third party computer system **131** also can send a register customer request **206** to the provider computing system **101**. In particular, the registration circuit **152** can generate the register customer request **206** and send the request **206** to the provider computing system **101** via the third party network interface circuit **154**. The register customer request **206** can include the unique customer ID associated with the third party customer **190**, and may also include additional customer information such as customer name, customer date of birth, customer address, customer email address, customer phone number, or other customer information.

(68) The account management circuit **103** at the provider computing system **101** receives the register customer request **206** from the third party computer system **131**. Responsive to the receipt of the register customer request **206**, the account management circuit **103** registers the customer (**208**) at the provider account database **127**. In particular, the account management circuit **103** creates a record in the provider account database **127** associated with the customer ID, or some other identifier based on the customer ID. The account management circuit **103** stores in the record the customer ID and the customer information received with the register customer request **206**. By storing the customer ID and the associated customer information, the account management circuit **103** registers the customer at the provider computing system **101**. In one or more embodiments, the account management circuit **103** may send a message to the third party computer system **131** indicating that the third party customer **190** associated with the register customer request **206** was successfully registered at the provider computing system **101**. In one or more embodiments, the registration circuit **152** updates the record associated with the third party customer **190** in the third party account database **162** to indicate that the third party customer **190** has been registered with the bank associate with the provider computing system **101**.

(69) In one or more embodiments, the third party computer system **131** initiates the registration process discussed above in relation to the provider computing system **101**, with computer systems of more than one bank that can provide third party bill payment services. In some such instances, the registration circuit **152** updates the record associated with the third party customer **190** in the third party account database **162** to indicate a list of banks at which the third party customer **190** has been successfully registered.

(70) Once the third party computer system **131** and the provider computing system **101** register the third party customer **190**, the third party computer system **131** may wait for a request for a passcode from the third party customer **190**. For example, the third party passcode circuit **158** may receive a passcode generation request **210** from the third party customer **190**. In some embodiments, the passcode generation request **210** can be generated by the third party customer **190** over a webpage hosted by the third party. In some embodiments, the passcode generation request **210** can be received from a text message send by the third party customer **190**. In some other embodiments, the passcode generation request **210** may be received from a third party application running on a computing device.

(71) FIG. 3 shows a screenshot of an example computing device **300** displaying a user interface **302**. In particular, the user interface **302** can be used by the third party customer **190** to request a passcode. In one or more embodiments, third party computer system **131** can provide the user interface **302** to the computing device **300**. The user interface **302** can allow display information related to the account associated with the third party customer **190**. For example, the user interface **302** can display the current amount due, the due date, as well as an option to pay the bill at ATM belonging to a bank. In particular, the user interface can provide an option get a passcode or access ID. Once the third party customer **190** presses the "Get Access ID" button, the computing device

300 can send a passcode request to the third party computer system **131**.

(72) In one or more embodiments, the passcode generation request **210** (FIG. 2) received by the third party passcode circuit **158**, can include customer information, such as, an account number, customer name, customer phone number, customer ID, etc. The third party passcode circuit **158** can generate and send a passcode generation request **212** to the provider computing system **101**. The passcode generation request **212** can include a unique identifier associated with the third party customer **190**.

(73) The passcode generation request **212** can be received by the provider passcode circuit **109** (FIG. 1A) at the provider computing system **101** (FIG. 1A). The provider passcode circuit **109** can generate a passcode (**214**). In one or more embodiments, the provider passcode circuit **109** can include a pseudo-random number generator for generating a random number. In one or more embodiments, the random number can be of a substantially long length, such as, for example, between about 32 bits to about 256 bits. The provider passcode circuit **109** can use the random number as the passcode. In one or more embodiments, the provider passcode circuit **109** can include an encryption engine to generate the passcode based on an encryption algorithm, such as for example AES, a hash algorithm, or other encryption algorithms. In one or more embodiments, the encryption engine may use, in part, customer information received with the passcode generation request **212** to generate the passcode. In one or more embodiments, the provider passcode circuit **109** may transform the random number or the output of the encryption engine into another number to use as a passcode. For example, the provider passcode circuit **109** can transform binary numbers into decimal numbers, alphabets, or alpha-numeric characters.

(74) In one or more embodiments, the provider passcode circuit **109** can assign a lifetime to the generated passcode. For example, the provider passcode circuit **109** can assign a lifetime of about 1 minute to a few hours or to a few days. The lifetime of the passcode can define the amount of time after generation can the passcode be valid. After the lifetime of the passcode has elapsed, the passcode, when presented to the provider passcode circuit **109** by the third party customer **190**, may be declined.

(75) In one or more embodiments, the provider passcode circuit **109** may store, in the provider account database **127** (FIG. 1A) the generated passcode. As discussed above, during third party customer registration process at the provider computing system **101**, the account management circuit **103** can create a record associated with the registered third party customer **190**. The provider passcode circuit **109** can use the customer information received with the passcode generation request **212** to access the record associated with the third party customer **190**, and store the generated passcode.

(76) The provider passcode circuit **109** can transmit the generated passcode (**216**) to the third party computer system **131**. The provider passcode circuit **109** can send the passcode as well corresponding customer information to the third party computer system **131**. For example, the provider passcode circuit **109** may include the customer ID received with the passcode generation request **212**. The provider passcode circuit **109** may also send the lifetime associated with the passcode to the third party computer system **131**.

(77) The third party passcode circuit **158** (FIG. 1A) can receive the passcode sent by the provider passcode circuit **109**. The third party passcode circuit **158** may perform two operations upon receiving the passcode. One, the third party passcode circuit **158** may store the passcode in the third party account database **162** (FIG. 1A) in the record associated with the third party customer **190**. In addition, the third party passcode circuit **158** can transmit the passcode (**218**) to the third party customer **190**. In some embodiments, the third party passcode circuit **158** can transmit the passcode to the third party customer device, such as the device **300** shown in FIG. 3. For example, FIG. 4 shows a screen shot of the example computing device **300** displaying a passcode. In particular, the screenshot shows a user interface **402** displaying a passcode or Access ID **404** received from the third party computer system **131**. The user interface **402** may also offer the user the options of

sending the passcode as a text message or requesting a new passcode. The third party passcode circuit **158** may also send the lifetime associated with the passcode, which the user interface **402** can display as a message **406**. The third party passcode circuit **158**, can alternatively, send the passcode via email to an email address associated with the third party customer **190**.

(78) FIG. 5 shows a process flow **500** for an example bill pay process. In particular, the process flow **500** depicts a bill pay process for a third party. As discussed above in relation to FIG. 2, the third party customer **190** possesses a passcode generated by the provider passcode circuit **109**. The third party customer **190** can walk or drive to the transaction machine **130** associated with the bank that can accept bill payments for the third party, and interact (**502**) with the transaction machine **130** to initiate a bill pay transaction. The transaction machine **130** can provide a bill pay interface (**504**) to the third party customer **190** to enable initiation of the bill pay transaction.

(79) FIG. 6 shows a screenshot of an example user interface **600** that can be displayed on a display **138** (FIG. 1A) of the transaction machine **130** (FIG. 1A). The user interface **600** can include a selectable button **602** that can be selected by the third party customer **190** to pay the bill.

(80) Referring again to FIG. 5, the third party customer **190** can select bill pay (**506**) on the user interface provided by the transaction machine **130**. For example, the third party customer **190** can select the button **602** (FIG. 6) labeled “Bill pay” displayed on the display **138** of the transaction machine **130**. Responsive to the third party customer **190** initiating the bill pay transaction, the transaction machine **130** can request (**508**) the third party customer **190** to provide the passcode.

(81) FIG. 7 shows a screenshot of an example user interface **700** to allow passcode entry. The user interface **700**, for example, can be displayed on a display **138** (FIG. 1A) of the transaction machine **130** (FIG. 1A). The user interface **700** can include a passcode field **702** where the user can enter the passcode, a selectable OK button **704** to allow the third party customer **190** to instruct the transaction machine **130** to accept the entered passcode, and a CLEAR button **706**, which can allow the user to clear the contents of the passcode field **702**. While not shown in FIG. 7, the transaction machine **130** can include a keypad, which the third party customer **190** can use to enter the passcode in the passcode field **702**.

(82) Referring again to FIG. 5, the third party customer **190** can present (**510**) the passcode to the transaction machine **130**. For example, the third party customer **190** can enter the passcode **404** shown in FIG. 4 in the passcode field **702** on the user interface **700** shown in FIG. 7 and press the OK button **704**. In response to receiving the passcode from the third party customer **190**, the transaction machine **130** can send a verification request **512** to the provider computing system **101**. The verification request **512** can include the passcode provided by the third party customer **190**.

(83) In response to receiving the verification request **512** from the transaction machine **130**, the bill pay circuit **111** or the account management circuit **103** can access the provider account database **127** to verify (**514**) if the passcode presented by transaction machine **130** matches a passcode stored in a record associated with a third party customer. If a match is found, the bill pay circuit **111** or the account management circuit **103** can send a verification notification (**516**) to the transaction machine. In addition, the bill pay circuit **111** or the account management circuit **103** can send additional bill pay information to the transaction machine **130**. For example, the additional bill pay information can include service information, third party account information, payment due date, payment due amount, etc. In one or more embodiments, the additional information may also include a billing document detailing the current bill. In some such embodiments, the billing document may be received from the third party computer system **131** in conjunction with the register customer request (FIG. 2, **206**) or with the passcode generation request (FIG. 2, **212**). The billing document may also be received at any time after the customer has been registered at the provider computing system **101**.

(84) Referring again to FIG. 5, the transaction machine **130**, responsive to receiving the verification notification (**516**) from the provider computing system **101**, can display a user interface that provides bill pay information (**518**) and the ability to initiate payment. FIG. 8 shows a screenshot

of an example user interface **800** providing bill pay information that can be displayed on a display **138** of the transaction machine **130**. The user interface **800** provides bill pay information **802**, which can include the name of the service (e.g., “Wireless”), a portion of the account number (e.g., “2004”), payment date (e.g., “Dec. 5, 2017”), and the amount due (e.g., “\$40”). The user interface **800** also includes selectable deposit button **804** (“Deposit Cash”) and a selectable view bill button **806** (“View Bill”). Selection of the deposit button **804** can initiate a cash deposit mechanism, while selection of the view bill button **806** can initiate a bill display process, in which the current bill can be presented to the user on the display **138** of the transaction machine **130**.

(85) FIG. **9** shows a snapshot of an example user interface **900** providing cash deposit information that can be displayed on a display **138** of the transaction machine **130**. The user interface **900** shown in FIG. **9** provides the user instructions for depositing cash in cash deposit mechanism (FIG. **1A**, **134**). For example, the user interface **900** can display the amount due as well as instructions on the number of bills that can be inserted into the deposit mechanism **134**. Referring again to FIG. **5**, the third party customer **190**, in response to the transaction machine **130** displaying bill pay information (**518**), can make a payment (**520**) at the transaction machine **130**.

(86) The transaction machine **130**, responsive to receiving the payment from the third party customer **190**, can process the payment (**522**). For example, the transaction machine **130** can count the deposited cash and determine if the deposited cash is at least equal to the amount due. The transaction machine **130** may also provide a notification on the display **138** indicating the amount that was deposited. FIG. **10** shows a snapshot of an example user interface **1000** providing payment notification information that can be displayed on a display **138** of the transaction machine **130**. In particular, the user interface **1000** can display the amount paid information **1002**, and also display selectable buttons such as a text receipt button **1008**, a print receipt button **1004**, and a done button **1006**. Selection of the text receipt button **1008** can cause the receipt generation circuit **144** of the transaction machine **130** to initiate sending the receipt in a text to a phone number associated with the third party customer **190**. The text receipt button **1008** may also display the phone number on record, so that the third party customer **190** can verify the phone number. Selection of the print receipt button **1004** can cause the receipt generation circuit **144** to initiate printing the receipt at a printer on or near the transaction machine **130**. Selection of the done button **1006** can cause the transaction processing circuit **142** to complete the transaction.

(87) The transaction processing circuit **142** can also send a payment notification (**524**) to the provider computing system **101**, indicating that the payment was successfully received from the third party customer **190**. The payment notification (**524**) may also include additional information such as the customer ID associated with the third party customer **190**. The bill pay circuit **111** at the provider computing system **101** can receive the payment notification (**524**) and the customer ID and update (**526**) the payment information in the record associated with the third party customer **190** stored in the provider account database **127**. For example, the bill pay circuit **111** can access the database using the customer ID received from the transaction machine **130** and locate the record associated with the customer ID. The bill pay circuit **111** can then update the record to indicate that the payment of the current bill has been received. In some embodiments, the bill pay circuit **111** can maintain a list of bill identifiers corresponding to a list of current and past bills associated with the third party customer **190**. The bill pay circuit **111** can update payment information associated with each of the bill identifiers.

(88) The bill pay circuit **111** can also transmit a payment notification (**528**) to the third party computer system **131**, indicating that a bill payment has been received. The payment notification can include additional information such as the customer ID, the bill payment amount, an identification of the bill paid, and any other customer information. The notification circuit **156** at the third party computer system **131** can receive the payment notification (**528**) from the bill pay circuit **111**, and, in turn, can send a notification (**530**) to the third party customer **190** that a payment was successfully received. In some embodiments, the notification circuit **156** may send a

text message to a phone number associated with the third party customer **190**. In some other implementations, the notification circuit **156** can push a message through an application running on a device associated with the third party customer **190**. Alternatively, the notification circuit **156** can employ other means to notify the user of the successful completion of payment.

(89) Referring to FIG. **11**, a system **1100** is shown according to an example embodiment. The system **1100** is similar to the system **100** discussed above in relation to FIG. **1**, in that similar to the system **100** shown in FIG. **1**, the system **1100** in FIG. **11** also includes a provider computer system **101** and a third party computer system **131**. The system **1100** further includes one or more transaction machines **1130**, which are similar in many respects to the one or more transaction machines **130** discussed above in relation to FIG. **1A**. However, unlike the transaction machine **130** shown in FIG. **1A**, the transaction machine **1130** shown in FIG. **11** includes a transaction machine account database **1127**. The transaction machine account database **1127** can be stored in a data storage system **1125**, which while not shown in FIG. **1A**, can be included in the transaction machine **130** as well. The inclusion of the transaction machine account database **1127** in the transaction machine **130** provides additional capabilities and features that improve the performance of the system **1100**, as discussed below.

(90) The transaction machine account database **1127** can be similar to the provider account database **127** discussed above, and can be configured to store account information related to account holders with the financial institution associated with the transaction machine **1130**. In addition, the transaction machine account database **1127** can be configured to store third party customer data, which can include customer name, customer address, customer date of birth, third party customer ID, and other customer related information. In addition, the transaction machine account database **1127** can include any passcodes generated in association with a third party customer. As discussed above in relation to FIG. **1A**, the passcodes can be stored in the provider account database **127** subsequent to their generation in response to a passcode generation request received from the third party computer system **131** (FIG. **2**). The passcodes generated by the provider computer system **101** can be transmitted to the transaction machine **1130** for storage in the transaction machine account database **1127**.

(91) In one example, the provider computer system **101** can transmit the passcodes to all transaction machines **130** that are configured to accept payments from third party customers. In another example, the provider computer system **101** can transmit the passcodes to a subset of transaction machines that satisfy one or more criteria, such as, for example, location of the transaction machine (e.g., being within a certain distance from the location of the third party customer address), amount of the bill (e.g., identity of the third party (e.g., select location and number of transaction machines assigned to a particular third party), identity of the user (e.g., select location and number of transaction machines designated by the third party for the particular user), and other criteria. In one example, the provider computer system **101** can transmit the passcodes to the transaction machine **1130** over the bank network interface circuit **105**. The provider computer system **101** also can transmit user data associated with the passcodes, where the user information can include user name, user identity, bill amount, third party identity, and any other user information. The transaction machine **1130**, in turn, can receive the passcodes and associated user information over the transaction machine's bank network interface circuit (not shown). The data storage system **1125** can store the passcodes and the associated user information in the transaction machine account database **127**.

(92) FIG. **12** shows a process flow **1200** for an example bill pay process. In particular, the process flow **1200** depicts a bill pay process for a third party. As discussed below, the process flow **1200** is similar to the process flow **500** discussed above in relation to FIG. **5**, in that like the process flow **500**, the process flow **1200** also includes interaction with the third party customer **190** to request and receive passcodes. However, unlike in the process flow **500**, where the passcode verification is carried out by the provider computing system **101**, in the process flow **1300**, the passcode

verification is carried out by the transaction machine **1130** instead of the provider computing system **101**. In addition, unlike in the process flow **500**, in the process flow **1200**, the transaction machine **1130** verifies the billing amount with the third party computing system **131** prior to accepting and processing the payment from the third party customer **190**. Furthermore, unlike in the process flow **500**, where the provider computing system **101** notifies the third party computing system **131** of the third party customer payment, in the process flow **1200**, the transaction machine **1130**, instead of the provider computing system **101**, notifies the third party computing system **131** of the third party customer payment.

(93) The process flow **1200** includes the interaction (**1202**) of the third party customer **190** with the transaction machine **1130**. The third party customer **190** can walk or drive to the transaction machine **1130** associated with the bank that can accept bill payments on behalf of the third party. The user interface circuit **107** of the transaction machine **1130** can provide a bill pay interface (**1204**) similar to that discussed above in relation to FIG. **6**. The third party customer **190** can select bill pay (**1206**) on the user interface provided by the transaction machine **1130**. For example, the third party customer **190** can select the button **602** (FIG. **6**) labeled “Bill pay” displayed on the display **138** of the transaction machine **1130**. Responsive to the third party customer **190** initiating the bill pay transaction, the user interface circuit **107** of the transaction machine **1130** can request (**1208**) the third party customer **190** to provide the passcode. The user interface circuit **107** can provide a passcode entry user interface that is similar to that discussed above in relation to FIG. **7**. As an example, referring to FIG. **7**, the third party customer **190** can preset the passcode (**1210**) by entering the passcode in the passcode field **702** and selecting the OK button **704** to instruct the transaction machine **1130** to accept the entered passcode.

(94) Responsive to receiving the passcode from the third party customer **190**, the transaction machine **1130** can verify the passcode (**1214**) based on the information stored in the transaction machine account database **1127**. For example, the authentication circuit **140** can compare the passcode received from the user interface with the passcodes stored in the transaction machine account database **1127**. If a match is found, the authentication circuit **140** can indicate that the passcode has been verified.

(95) Once the passcode has been verified, the transaction processing circuit **142** can determine the bill pay amount stored in the transaction machine account database **1127** in association with the passcode. For example, the transaction processing circuit **142** can communicate the bill pay amount determined from the transaction machine account database **1127** to the third party computer system **131** (**1216**). The communication to the third party computer system **131** can also include the passcode, and any other third party customer information stored in the transaction machine account database **1127**. The third party computer system **131** can compare the bill pay amount received from the transaction machine **1130** with the bill pay amount stored in the database in association with an identity (or passcode) of the third party customer. If the bill pay amount is verified as correct, the transaction processing engine **142** can receive a message from the third party computer acknowledging that the bill pay amount is correct. If the bill pay amount does not match with the one stored at the third party computer system **131**, the transaction processing engine **142** may receive a message indicating that the amount is incorrect. The transaction processing circuit **142** can terminate the bill pay transaction with the third party customer if the message indicating that the bill pay amount is incorrect is received. On the other hand, the transaction processing circuit **142** can proceed with the bill pay transaction with the third party customer if a message indicating that the bill pay amount is correct is received from the third party computer system **131**.

(96) The transaction machine **1130**, responsive to receiving the verification notification **1216** indicating that the bill pay amount is correct, can display a user interface that provides the verified bill pay amount (**518**) and the ability to initiate payment. FIG. **8**, discussed above, shows a screenshot of an example user interface **800** providing bill pay information that can be displayed on a display **138** of the transaction machine **1130**. FIG. **9**, discussed above, shows a snapshot of an

example user interface **900** providing cash deposit information that can be displayed on a display **138** of the transaction machine **130**. The user interface **900** shown in FIG. **9** provides the user instructions for depositing cash in cash deposit mechanism (FIG. **1A**, **134**). For example, the user interface **900** can display the amount due as well as instructions on the number of bills that can be inserted into the deposit mechanism **134**. Referring again to FIG. **12**, the third party customer **190**, in response to the transaction machine **1130** displaying bill pay information (**1218**), can make a payment (**1220**) at the transaction machine **130**.

(97) The transaction machine **1130**, responsive to receiving the payment from the third party customer **190**, can process the payment (**1222**). For example, the transaction machine **1130** can count the deposited cash and determine if the deposited cash is at least equal to the amount due. The transaction machine **1130** may also provide a notification on the display **138** indicating the amount that was deposited. FIG. **10**, discussed above, shows a snapshot of an example user interface **1000** providing payment notification information that can be displayed on a display **138** of the transaction machine **130**. In particular, the user interface **1000** can display the amount paid information **1002**, and also display selectable buttons such as a text receipt button **1008**, a print receipt button **1004**, and a done button **1006**. Selection of the text receipt button **1008** can cause the receipt generation circuit **144** of the transaction machine **1130** to initiate sending the receipt in a text to a phone number associated with the third party customer **190**. The text receipt button **1008** may also display the phone number on record, so that the third party customer **190** can verify the phone number. Selection of the print receipt button **1004** can cause the receipt generation circuit **144** to initiate printing the receipt at a printer on or near the transaction machine **1130**. Selection of the done button **1006** can cause the transaction processing circuit **142** to complete the transaction.

(98) The transaction processing circuit **142** can also send a payment notification (**1224**) to the third party computer system **131**. In contrast with the process **500** discussed above in relation to FIG. **5**, where the transaction machine **130** sends a payment notification (**524**) to the provider computing system **101**, the transaction machine **1130** instead sends a payment notification (**1224**) to the third party computer system **130**. By bypassing the provider computing system **101**, the transaction machine **1130** can reduce the risk of degraded performance in the payment notification process that may be caused by delays in the communication between the transaction machine **1130** and the provider computing system **101** and the communication between the provider computing system **101** and the third party computer system **131**, and the delay due to the performance of the provider computing system **101**. As a result, the speed of notification to the third party customer can be improved. The third party computer system **131**, responsive to receiving the payment notification (**1224**) from the transaction machine **1130**, can notify (**1230**) the third party customer of a successful receipt of the bill payment.

(99) FIG. **13** shows a process flow **1300** for an example bill pay process. In particular, the process flow **1300** depicts a bill pay process for a third party. Unlike the process flow **1200** discussed in relation to FIG. **12**, in which the transaction machine **1130** requests a passcode from the third party customer **190**, the process flow **1300** in FIG. **13** depicts an example where the transaction machine instead requests an account number. The account number can correspond to an account that the third party customer **190** holds with the third party associated with the third party computer system **131**. In this manner, the process flow **1300** abstains from generating and storing passcodes as well as customer information related to the third party customer **190**.

(100) The process **1300** includes the interaction (**1302**) of the third party customer **190** with the transaction machine **1130**. The third party customer **190** can walk or drive to the transaction machine **1130** associated with the bank that can accept bill payments on behalf of the third party. In response to the third party customer **190** interacting with the transaction machine **1130**, the transaction machine **1130** can present a user interface (**1304**) to the third party customer **190**. The user interface circuit **107** of the transaction machine **1130** can provide a bill pay interface (**1304**) similar to that discussed above in relation to FIG. **6**. The third party customer **190** can select bill

pay (1306) on the user interface provided by the transaction machine 1130. For example, the third party customer 190 can select the button 602 (FIG. 6) labeled “Bill pay” displayed on the display 138 of the transaction machine 1130.

(101) Responsive to the third party customer 190 initiating the bill pay transaction, the user interface circuit 107 of the transaction machine 1130 can present an user interface that requests the user to select a third party (1308). For example, FIG. 14 shows an example user interface 1400 that can be presented on a display 138 of the transaction machine 1130. In particular, the user interface circuit 107 can present the user interface 1400 on the display 138 of the transaction machine 1130. The user interface 1400 can include a number of selectable buttons associated with various third parties for which the transaction machine 1130 can accept bill payments. For example, the user interface 1400 shows a company A button 1402, a company B button 1404, and a company C button 1406. The user interface 1400 also can display a Cancel button 1408. The third party customer 190 can identify the third party for which a bill is to be paid by selecting (1310) the appropriate button on the user interface 1400.

(102) Responsive to the third party customer 190 selecting a company or third party (1310) on the user interface 1400, the transaction machine 1130 can display a user interface to request, from the third party customer 190, account information related to the selected third party (1312). FIG. 15 shows an example user interface 1500 that the user interface circuit 107 can display on the display screen 138 of the transaction machine 1130. The user interface 1500 can include an account field 1502, a ZIP code field 1504, a cancel button 1506, a clear button 1508, and an OK button 1510. The account field 1502 can accept the account number entered by the third party customer 190. The account number can correspond to an account number that the third party customer 190 holds with the selected third party or company, such as, for example Company A. In some examples, the account number can be a customer number, a phone number, a unique ID number, or any other number that can uniquely identify the third party customer 190 to the third party. The user interface 1500 can optionally include the ZIP code field 1504, in which the third party customer 190 can enter the ZIP code associated with the account with Company A. The ZIP code can offer an additional layer of authentication to the transaction. To that end, the user interface 1500 can include additional fields requesting information, such as, for example, “password,” “address,” “phone number,” etc. Once the third party customer 190 has entered the requested information on the user interface 1500, the third party customer 190 can press the OK button 1510 (1314).

(103) Responsive to receiving the account number from the third party customer 190, the transaction machine 1130 can communicate with the third party computer system 131 to request the bill amount. The third party computer system 131 can correspond to the third party or company selected by the user in the user interface 1400 shown in FIG. 14. The transaction machine 1130 can store in the data storage system 1125 a list of companies that can be displayed to the third party customer 190. The transaction machine 1130 also can store the communication information, such as the server address, in the data storage system 1125, of a third party computer system associated with each company in the list of companies. In response to the third party customer 190 selecting a company or third party, the transaction machine 1130 can look up the identity of the selected company or third party to determine the communication information to communicate with the third party computer system 130 associated with the selected third party or company.

(104) The transaction machine 1130 can send a request (1316) to the third party computer system 131 to retrieve bill information. The request can include the account information entered by the third party customer 190 at the user interface 1500 shown in FIG. 15. For example, the request can include the account number and the ZIP code entered by the third party customer 190 in the account field 1502 and the ZIP code field 1504.

(105) The transaction machine 1310 can receive (1318) bill information from the third party computer system 131. For example, the transaction machine 1130 can receive from the third party computer system 131 the bill information subsequent to the transaction machine 1130 sending the

request (1316). The bill information can include the bill amount that the third party customer 190 owes the third party or company. The bill information may also include additional information such as the due date, the service the bill amount corresponds to, the account information, etc.

(106) The transaction machine 1310 can provide the bill amount to the third party customer 190 (1320). For example, FIG. 16 shows an example user interface 1600 providing the third party customer 190 with the bill information received from the third party computer system 130. The user interface circuit 107 can display the user interface 1600 shown in FIG. 16 on the display screen 138. The user interface 1600 can include bill information such as the service (e.g., Electricity) for which the bill amount is provided, information about the account (e.g., last four digits of the account number), the payment due date, and the amount due. The interface 1600 can also include a deposit cash button 1604, which the third party customer 190 can activate, for example, after verifying the billing information 1602. The user interface 1600 can further include a cancel button 1606, which the third party customer 190 can activate if the third party customer 190 wishes to cancel the bill payment transaction.

(107) Responsive to the third party customer 190 activating the deposit cash button 1604, the user interface circuit 107 can display cash deposit information on the display screen 138. FIG. 17 shows a snapshot of an example user interface 1700 providing cash deposit information. The user interface 1700 shown in FIG. 17 provides the user instructions for depositing cash in cash deposit mechanism (FIG. 11, 134). For example, the user interface 1700 can display the amount due 1702 as well as instructions on the number of bills that can be inserted into the deposit mechanism 134. Referring again to FIG. 13, the third party customer 190, in response to the transaction machine 1130 displaying bill pay information, can make a payment (1322) at the transaction machine 130.

(108) The transaction machine 1130, responsive to receiving the payment from the third party customer 190, can process the payment (1324). For example, the transaction machine 1130 can count the deposited cash and determine if the deposited cash is at least equal to the amount due. The transaction machine 1130 may also provide a notification on the display 138 indicating the amount that was deposited. FIG. 18 shows a snapshot of an example user interface 1800 providing a payment notification information that can be displayed on a display 138 of the transaction machine 1130. In particular, the user interface 1800 can display the amount paid information 1810, and also display selectable buttons such as a print receipt button 1802, and a done button 1804. Selection of the print receipt button 1802 can cause the receipt generation circuit 144 to initiate printing the receipt at a printer on or near the transaction machine 1130. Selection of the done button 1804 can cause the transaction processing circuit 142 to complete the transaction.

(109) The transaction machine 1130 can also send a payment notification (1326) to the third party computer system 131, indicating that the payment was successfully received from the third party customer 190. The payment notification (1326) may also include additional information such as the account number associated with the third party customer 190. A notification circuit 156 at the third party computer system 130 can receive the payment notification (1326) and the additional information and update the payment information in the record associated with the third party customer 190 stored in the provider account database 127. For example, the notification circuit 156 can access the database using the account number received from the transaction machine 1130 and locate the record associated with the account number. The notification circuit 156 can then update the record to indicate that the payment of the current bill has been received. In some embodiments, the notification circuit 156 can maintain contact information, such as a phone number, of the third party customer 190. The notification circuit 156, upon receiving the payment notification (1326) from the transaction machine 1130, can send a notification, such as a text message 1808 to the cell phone 1806 of the third party customer 190 notifying that the payment was received. The notification circuit 156 can include in the notification the amount deposited by the third party customer 190 as well as any credit or any additional amount owed.

(110) FIG. 19 shows a process flow 1900 for an example bill pay process for a purchase made on a

third party application. The transaction machine **1130** can enable a third party customer **190** to make purchases on the third party application, and make cash payments for the purchase at the transaction machine **1300**. The transaction machine **1300** can process the cash payments and notify the third party computer system **190** of the cash payment. In response the third party computer system **130** can complete the purchase.

(111) FIG. **20** shows an example screen shot of a user interface **2000** shown on a customer device **2002**. The user interface **2000** can represent a user interface displayed on the display screen of the customer device **2002** during the process of making a purchase using a third party application or on a third party website. In particular, the user interface **2000** can provide the customer with options in selecting a payment method to pay for the desired purchase. The user interface **2000** can include payment options such as a store card selection **2006**, a cash payment selection **2008**, a first credit card selection **2010**, a second credit card selection **2012**, and a Continue button **2004**. The customer can select any one of the payment options (for example by selecting a corresponding radio button) and activate the Continue button **2004** to initiate the payment. For example, the customer may select the cash payment selection **2008** and activate the Continue button **2004** to indicate that the customer would like to make cash payment towards the purchase.

(112) FIG. **21** shows an example screen shot of a user interface **2100** shown in the customer device **2002**. The user interface **2100** can provide the customer the ability to place the order for the purchase using one or more options. For example, the user interface **2100** can provide the customer with purchase information **2110** including the product being purchased and the price of the product. The user interface **2100** also can include options for selecting the payment method. For example, the user interface **2100** can provide a cash payment option **2101** and a store card rewards option **2104**. The user interface **2100** also can provide the customer with the option **2106** to update the billing address and a field **2112** for entering gift cards and promotional codes.

(113) FIG. **22** shows an example screen shot of a user interface **2200** including a payment ID shown on the customer device **2002**. Responsive to the customer selecting the cash payment method **2102** on the user interface **2100** shown in FIG. **21**, the third party can display the user interface **2200** shown in FIG. **22** on the display screen of the customer device **2002**. The user interface **2200** can provide the customer with a payment or customer ID **2202**, customer ID expiration duration **2204**, a new payment ID button **2206**, a find ATM button **2208**, and order details **2210**. The customer ID **2202** can be generated by the third party passcode circuit **158** or by the passcode circuit **109** of the provider computing system **101** and provided to the customer device **2002**. The customer ID expiration duration **2204** can indicate the amount of time for which the customer ID **2202** is valid. If the customer ID expiration duration **2204** has elapsed or expired, the third party customer **190** may have to activate the New Payment ID button **2206** to request the generation and delivery of a new customer ID. The find an ATM button **2208** can invoke a new interface, such as for example a map interface that shows the locations of ATMs in relation to the current location of the third party customer **190**. The user interface **2200** may also display order details **2210** including the items being purchased by the third party customer **190**.

(114) Referring again to the process flow **1900** shown in FIG. **19**, the third party customer **190** can approach the transaction machine **1130** and interact (**1902**) with the user interface on the transaction machine **1130**. For example, the user interface circuit **107** can display (**1904**) the user interface **600** shown in FIG. **6** on the display screen **138** of the transaction machine **1130**. The third party customer **190** can select the Pay Bills **602** button to proceed paying the purchase amount (**1906**). Responsive to the third party customer **190** selecting the Pay Bills button **602**, the user interface circuit **107** can provide a user interface that allows the third party customer **190** to select the third party to which a payment is to be made. For example, the user interface circuit **107** can provide the user interface **1400** shown in FIG. **14**, which provides a selectable list of companies or third parties to which the third party customer **190** can make a payment. The third party customer **190** may, for example, select company A **1402** that is associated with the third party application or

web page on which the purchase is being made. In instances where the transaction machine **130** provide bill pay service to a single third party, the user interface circuit **107** may refrain from displaying the user interface **1400** on the display screen **138**.

(115) The user interface circuit **107** can provide a user interface requesting the third party customer **190** to enter a passcode or a customer ID (**1908**). For example, the user interface circuit **107** can present the user interface **700** discussed above in relation to FIG. 7, where the user interface **700** includes a passcode field **702** in which the third party customer **190** can enter a passcode (**1910**). The third party customer **190** can enter the payment or customer ID **2202** provided on the customer device **2000**, shown in FIG. 22, into the passcode field **702**. After entering the customer ID **2202**, the third party customer **190** can activate the OK button **704**.

(116) Responsive to the third party customer **190** providing the customer ID, the transaction machine **1130** can request payment information from the third party computer system **131** (**1912**). The request can be similar to the request **1316** discussed above in relation to the flow diagram **1300** shown in FIG. 13. The request **1912** can include the customer ID provided by the third party customer **190**. The request may also include identification information of the transaction machine **1130**, location information of the transaction machine **1130**, authentication information, etc.

(117) The transaction machine **1130** can receive payment information (**1914**) from the third party computer system **131**. The payment information can indicate the amount that is due for the completing the purchase of the order initiated by the third party customer **190** with the third party. The payment information may also include additional information such as the order details, duration of time for which the purchase price is valid, the name or identity of the account held by the third party customer **190** with the third party, the identity of the third party, etc.

(118) Responsive to receiving the payment information (**1914**) from the third party computer system **131**, the transaction machine **1130** can provide the payment information (**1916**) to the third party customer **190**. For example, the user interface circuit **107** can display a user interface that allows the third party customer **190** to view the payment amount. FIG. 23 shows a screen shot of an example user interface **2300** providing payment information to the third party customer **190**. The user interface **2300** can display the name **2302** of the company or the third party from which the third party customer **190** is making the purchase, the amount due **2304**, a deposit cash button **2306** and a view order button **2308**. The name **2302** of the company can be the name of the company or third party selected by the third party customer **190**, such as, for example, customer A selected on the user interface **1400** shown in FIG. 14. The amount due **2304** can indicate the amount due for the purchase initiated by the third party customer **190**. The amount due **2304** can match the amount appearing in the order details **2210** on the user interface **2200** shown on the display screen of the customer device **2002** (FIG. 22). The view order button **2308**, when activated, can provide the order details received from the third party computer system **131**. For example, the order details can include the order details such as the name of the product being purchase, the quantity of the product being purchased, a photograph of the product being purchased, etc. Activation of the deposit cash button **2306** can indicate that the third party customer **190** would like to proceed with the cash payment for the purchase.

(119) Responsive to the third party customer **190** activating the deposit cash button **2306**, the user interface **107** can display cash deposit information on the display screen **138**. FIG. 24 shows a snapshot of an example user interface **2400** providing cash deposit information. The user interface **2400** shown in FIG. 24 provides the user instructions for depositing cash in cash deposit mechanism (FIG. 11, **134**). For example, the user interface **2400** can display the amount due **2402** as well as instructions on the number of bills that can be inserted into the deposit mechanism **134**. Referring again to FIG. 19, the third party customer **190**, in response to the transaction machine **1130** displaying bill pay information can make a payment (**1918**) at the transaction machine **130**.

(120) The transaction machine **1130**, responsive to receiving the payment from the third party customer **190**, can process the payment (**1922**). For example, the transaction machine **1130** can

count the deposited cash and determine if the deposited cash is at least equal to the amount due. The transaction machine **1130** may also provide a notification on the display **138** indicating the amount that was deposited. FIG. 25 shows a snapshot of an example user interface **2500** providing a payment notification information that can be displayed on a display **138** of the transaction machine **1130**. In particular, the user interface **2500** can display the amount paid information **2502**, and also display selectable buttons such as a text receipt button **2508**, a print receipt button **2504**, and a done button **2506**. Selection of the text receipt button **2508** can cause the receipt generation circuit **144** of the transaction machine **1130** to initiate sending the receipt in a text to a phone number associated with the third party customer **190**. The text receipt button **2508** may also display the phone number on record, so that the third party customer **190** can verify the phone number. Selection of the print receipt button **2504** can cause the receipt generation circuit **144** to initiate printing the receipt at a printer on or near the transaction machine **1130**. Selection of the done button **2506** can cause the transaction processing circuit **142** to complete the transaction.

(121) The transaction machine **1130** can also send a payment notification (**1924**) to the third party computer system **131**, indicating that the payment was successfully received from the third party customer **190**. The payment notification (**1924**) may also include additional information such as the customer ID associated with the third party customer **190**. A notification circuit **156** at the third party computer system **130** can receive the payment notification (**1924**) and the additional information and update the payment information in the record associated with the third party customer **190** stored in the provider account database **127**. For example, the notification circuit **156** can access the database using the customer ID received from the transaction machine **1130** and locate the order associated with the customer ID. The notification circuit **156** can then update order indicate that the payment for the order has been received. In some embodiments, the notification circuit **156** can maintain contact information, such as a phone number, of the third party customer **190**. The notification circuit **156**, upon receiving the payment notification (**1924**) from the transaction machine **1130**, can send a notification, such as a text message to the cell phone or other device of the third party customer **190** notifying that the payment for the purchase order was received. The notification circuit **156** can include in the notification the amount deposited by the third party customer **190** as well as any credit or any additional amount owed.

(122) In some instances, the third party customer **190** may overpay or underpay the amount due. For example, referring to FIGS. 24 and 25, the third party customer may make a payment of \$25 towards an amount due of \$22.94. The overpayment or underpayment may be due to the particular cash denominations available to the third party customer **190** at the time of payment and/or the cash denominations accepted by the transaction machine **1130**. In the case of underpayment or overpayment, the transaction machine **1130** passes on the amount deposited to the third party computer system **130**. The transaction machine **1130** may notify the third party computer system **130** that an overpayment or an underpayment was made, but the transaction machine **1130** does not halt the transaction with the third party customer **190**. Instead, the transaction machine **130** completes the transaction of accepting the cash payment, be that for a bill payment or for purchasing items, and notifies the third party computer system **130** the amount of cash deposited, the identification of the deposit (e.g., account number, customer ID, passcode, etc.).

(123) In some instances, such as, for example, in the process flows **1300** and **1900** discussed above in relation to FIGS. 13 and 19, the transaction machine **130** may not store in the long term any information regarding the third party customer **190**. For example, the transaction machine **1130**, or for that matter the provider computing system **101**, may not store in the long term any third party customer information. For example, the transaction machine **1130** may not store the customer ID or the account number provided by the third party customer **190** during the process of depositing cash. In some examples, the transaction machine **130** and the provider computing system **101** may not maintain an account database related to the third party customers **190** of the one or more third parties. The transaction machine **1130** can temporarily store the account number and the customer

ID while the transaction is in the process, but delete this information after notifying the third party computer **130** that the cash was deposited. Refraining to store, or deleting, third party customer information **190** can have the technical advantage of improving the performance of the transaction machine **130** or the provider computer system **101**. With multiple third parties, and multiple customers associated with each of the third parties, the number of third party customers can be quite large. Storing information for each of these customers can occupy a large amount of space on the data storage system **1125** and **125**. This can affect the performance of the data storage system **1125** and **125**. The transaction machine **1130** and the provider computing system **101** can instead only temporarily store the customer information until the transaction is complete, and then delete the customer information to free up space on, and improve the performance of, the storage system **1125** and **125**.

(124) In some instances, the process flow **1900** shown in FIG. **19** can represent an example bill pay process in which the passcode is static. That is unlike the payment or customer ID **2202** shown in FIG. **22**, where the customer ID **2202** had an associated expiration duration **2204**, the static passcode may not have an expiration duration, or can have an expiration duration that is substantially longer, such as, for example, a few months, up to the next billing date, etc. This can allow the transmission of the passcode to the user over a medium other than the user interface **2100** of an application shown in FIG. **21**. As an example, the passcode can be provided to the user in a payment bill that has the passcode printed on its face. In another example, the passcode can be provided to the user in an email delivered to the user's email address. The user can access the email using an email client that connects to the user's email server. The email client can access an email that includes the passcode. In yet another example, the passcode can be provided to the user on the user's device via a text message (e.g., short message service (SMS)).

(125) The provider computing system **101** can generate the passcode or payment or customer ID and provide the passcode to the third party computer system **131** over a computer network. For example, the passcode circuit **109** discussed above in relation to FIG. **11** can generate the passcode. The passcode also can be stored in the account database **127**. In some instances, the provider computing system **101** can transmit the generated passcode to the transaction machine **1130**. The transaction machine **1130** can store the passcode in the account database **1127**.

(126) FIG. **26** shows a process flow **2600** for an example bill pay process. The process flow **2600** depicts an example bill pay process that provides the user with passcode and allows the user to select an amount of a payment that the user expects to make at the transaction machine **1130**. As discussed below, the transaction machine **1130** can utilize the passcode and the selected amount to verify the transaction.

(127) FIG. **27** shows an example screenshot of a user interface **2700** shown on a customer device **2702**. The user interface **2702** can represent a user interface displayed on the display screen of the customer device **2702** during the process of viewing a bill. In particular, the user interface **2700** can display account information associated with an account held by the user with a third party associated with the third party computer system **131**. The third party computing system **131** can transmit information to the customer device **2702** for display on the user interface **2702**. The information can include, for example, a current bill amount **2704**, which is displayed on the display screen of the customer device **2702**. The user interface **2700** can further include user inputs, such as “Pay bill” button **2706**, a “Pay now with cash” button **2708**, and “Find an ATM” button **2710**. The “Pay bill” button **2706** can allow the user to make payments over the customer device **2702**, such as for example, using a credit card or other electronic payment system. However, the user interface **2702** can also allow the user to make payments in cash at an ATM. For example, the user can select the “Pay now with cash” button **2708** to indicate that the user wishes to make a payment at an ATM. The user may also click on the “Find an ATM” button **2710**, in response to which, the user interface **2700** can display a list of ATMs near the user's location that are authorized to accept cash for bill payment.

(128) Responsive to the user selecting the “Pay now with cash” button **2708**, the customer device **2702** can display a user interface **2800** on the display screen of the customer device **2702**. The user interface **2800** can allow the user to select the amount of cash that the user expects to deposit at an ATM. For example, the user interface **2800** can include an amount field **2802** that can display a payment amount. In addition, the user interface **2800** can include “+” and “-” buttons **2804** and **2806**, which the user can use to increase or decrease the amount displayed in the amount field **2802**. The user interface **2802** also can display the amount due, which in the example shown in FIG. **28**, includes the amount \$48.18. In some examples, an ATM may accept cash in the form of bills only and may not accept coins. Thus, the user may not be able to deposit an amount that includes fractions of a dollar, such as \$0.18. Thus, the user can select an amount that is greater than the amount due, and that can be rendered in bills. For example, user can click on the “+” button **2804** to increase the amount to \$50. Once the amount is set by the user, the user can select the “Get access code” button **2808** to request a passcode.

(129) Referring to FIG. **26**, responsive to receiving the request for a passcode from the customer device **2702**, the third party computing system **131** can send a request to the provider computing system **101** to generate the passcode (**2602**). For example, the third party passcode circuit **158** of the third party computing system **131** can generate and send a request **2602** to the provider computing system **101** to generate a passcode. In some examples, the request **2602** can include a unique identifier associated with the third party customer or user operating the customer device **2702**.

(130) Responsive to receiving the passcode generation request **2602** from the third party computing system **131**, the passcode circuit **109** of the provider computing system **101** can generate a passcode **2604**. In one or more embodiments, the provider passcode circuit **109** can include a pseudo-random number generator for generating a random number. In one or more embodiments, the random number can be of a substantially long length, such as, for example, between about 32 bits to about 256 bits. The provider passcode circuit **109** can use the random number as the passcode. In one or more embodiments, the provider passcode circuit **109** can include an encryption engine to generate the passcode based on an encryption algorithm, such as for example AES, a hash algorithm, or other encryption algorithms. In one or more embodiments, the encryption engine may use, in part, customer information received with the passcode generation request **2602** to generate the passcode. In one or more embodiments, the provider passcode circuit **109** may transform the random number or the output of the encryption engine into another number to use as a passcode. For example, the provider passcode circuit **109** can transform binary numbers into decimal numbers, alphabets, or alpha-numeric characters.

(131) In some embodiments, the passcode circuit **109** may assign a lifetime to the generated passcode. In some examples, the request **2602** received from the third party computing system **131** can include information regarding the lifetime of the passcode to be generated. As discussed above, the passcode can be a static passcode or have a substantially long lifetime, such as for example, a month, a next billing period, etc. The passcode circuit **109** can assign a lifetime based on the lifetime information received from the third party computing system **131**.

(132) In one or more embodiments, the provider passcode circuit **109** may store the generated passcode in the provider account database **127** (FIG. **11**). The account management circuit **103** can create a record associated with the registered third party customer **190**. The provider passcode circuit **109** can use the customer information received with the passcode generation request **2602** to access the record associated with the third party customer **190**, and store the generated passcode.

(133) The provider computing system **101** can transmit the generated passcode to the third party computing system **131** (**2606**). The third party computing system **131** can, in turn, transmit the passcode to the customer device **2702** (**2608**). For example, FIG. **29** shows a user interface **2900** presented on a display screen of the customer device **2700**. The user interface **2900** can be presented responsive to receiving a passcode from the third party computing system **131**. The user

interface **2900** can display the passcode **2904** as well as a lifetime **2906** associated with the passcode **2904**. The user interface **2900** can also display the payment amount selected by the user on the user interface **2800** shown in FIG. **28**. The payment amount displayed can inform the user that the user has selected the displayed payment amount as the amount that the user plans on depositing at the ATM for the due bill amount. The user interface **2800** also can display a “New Access Code” button **2908**, which when pressed by the user, can send a request to the third party computing system **131** to generate a new passcode. The user interface **2800** can also include a “Send as Text” button, which when activated by the user, can send a request to the third party computing system **131** to send the passcode via an SMS text.

(134) In some examples, the third party computing system **131** may also send the user selected payment amount to the provider computing system **101**. For example, the third party computing system **131** can transmit the amount selected by the user on the interface **2800** shown in FIG. **28**. The third party computing system **131** can transmit the user selected amount to the provider computing system **101** along with the request for passcode **2602**. In some examples, the third party computing system **131** can transmit the user selected amount to the provider computing system **101** in a separate communication. The provider computing system **101** can store the user selected amount in association with the passcode in the provider account database **127**. In some instances, the provider computing system **101** can transmit at least a portion of the information stored in the provider account database **127** associated with a third party customer to the transaction machine **1130** (**2610**). For example, the provider computing system **101** can transmit the passcode and the user selected amount to the transaction machine **1130**, which can store the passcode and the user selected amount in the transaction machine account database **1127** (**2612**).

(135) The user can approach and interact with the transaction machine **1130** (**2614**). In response to the user's interaction with the transaction machine **1130**, the user interface circuit **107** can display (**2616**) a bill pay interface **3000** shown in FIG. **30** on the display screen **138** of the transaction machine **1130**. For example, the bill pay interface **3000** can include a “Use an Access Code” button **3002**, which the user can click to initiate the bill pay using an access code (FIG. **26**, **2618**). Responsive to the user selecting the “Use an Access Code” button **3002**, the user interface circuit **107** can provide a user interface that allows the user to enter the access code.

(136) FIG. **31** shows a screenshot of an example user interface **3100** for requesting a passcode (FIG. **26**, **2620**). The user interface circuit **107** can display the user interface **3100** on the display screen **138** of the transaction machine **1130**. The user interface **3100** can include a passcode field **1302** where the user can enter the passcode, a selectable OK button **3104**, the activation of which can indicate to the transaction machine **1130** to accept the entered passcode, a selectable Clear button **3106**, which can allow the user to clear the contents of the passcode field **1302**. While not shown in FIG. **31**, the transaction machine **1130** can include a keypad, which the user can use to enter the passcode in the passcode field **1302**.

(137) Referring to FIG. **26**, the user can enter the passcode in the passcode field **1302** of the user interface **3100** (**2622**). For example, the user can enter the access code **2904** provided to the user on the user interface **2900** on the user device **2702** shown in FIG. **29**. Responsive to the user entering the passcode, the transaction processing circuit **142** can access the transaction machine account database **1127** to access a database entry associated with the passcode. If an entry exists, the transaction processing circuit **142** can access and provide the user selected amount to the user interface circuit **107** for display. For example, the user interface circuit **107** can generate a user interface **3200** shown in FIG. **32**, which includes an “Amount due” field **3202**, in which the user selected amount is displayed (FIG. **26**, **2624**). As an example, the amount displayed in the “Amount due” field **3202** can be the same as the user selected amount appearing in the amount field **2802** on the user interface **2800** displayed on the user device **2702** shown in FIG. **28**. The user interface **3200** can also include an “Insert Cash” button **3204**, which the user can activate to begin the process of inserting cash into the transaction machine. For example, the user may verify that the

amount displayed in the “Amount due” field **3202** is the appropriate amount, and then proceed to activating the “Insert Cash” button **3204**.

(138) In some instances, the transaction machine **1130** can communicate with the third party computer system **131** to retrieve the user selected amount. This process step can be carried out in cases where the transaction machine **1130** does not receive the user selected amount from the provider computing system **101** in the communication **2610** shown in FIG. **26**. The transaction machine **1130** can request payment information from the third party computing system **131** and in response receive payment information from the third party computing system **131** similar to the process steps **1912** and **1914** shown in FIG. **19**. However, the payment information received from the third party computing system **131** can indicate the user selected amount. The transaction processing circuit **142** can communicate with the third party computing system **131** to request and receive the payment information. The transaction processing circuit **142** also can store the user selected amount in the transaction machine account database **1127** in association with the passcode. The user interface circuit **107** can include the user selected amount received from the third party computing system **131** in the “Amount due” field **3202** of the user interface **3200** shown in FIG. **32**.

(139) Responsive to the user activating the “Insert Cash” button **3204** on the user interface **3200**, the user interface circuit **107** can generate and display a user interface **3300** on the display **138** of the transaction machine **1130**, an example of which is shown in FIG. **33**. The user interface **3300** can provide cash deposit information to the user. For example, as shown in FIG. **33**, the user interface **3300** can display the amount due **3302**, as well as instructions on the number of bills that can be inserted into the deposit mechanism **134**. The deposit mechanism **134** can also open the deposit slot through which the user can insert cash.

(140) Responsive to the user inserting cash into the deposit mechanism **134** (FIG. **26**, **2626**), the user interface circuit **107** can display a user interface showing the progress of scanning the bills inserted by the user. For example, FIG. **34** shows a user interface **3400** that displays the progress of scanning the bills inserted by the user. The user interface **3400** can display an image **3402** of a denomination of a bill that the deposit mechanism **134** has scanned and verified. The user interface **3400** also can show images **3404** and **3406** indicating that the deposit mechanism **134** is scanning and verifying additional bills inserted by the user.

(141) Once all the bills inserted by the user are scanned and verified by the deposit mechanism **134**, the user interface circuit **107** can display a user interface **3500** on the display **138** listing the denominations of the bills inserted by the user, the number of bills of each denomination, and the total amount. The user interface **3500** also can include a “Confirm Total” button **3502**, which indicates the total amount that the deposit mechanism **134** has verified. An actuation of the “Confirm Total” button **3502** can indicate that the user confirms the total amount displayed on the user interface **3500** is the amount inserted by the user. The user interface **3500** also includes a “Cancel and Return Cash” button **3504**, the actuation of which by the user, can indicate to the deposit mechanism **134** that the user wishes to cancel the transaction and would like for the bills previously inserted to be returned to the user. The deposit mechanism **134** in response can return the bills through the currency dispenser **132** of the transaction machine **1130**.

(142) If the transaction processing circuit **142** identifies that the amount deposited by the user does not match the selected amount, the transaction processing circuit **142** can generate a user interface (not shown) indicating as such to the user. The user may then be given the opportunity to deposit additional bills such that the deposited cash matches the user selected amount. In case the user is unable to deposit the amount of cash matching the user selected amount, the transaction processing circuit can decline processing the bill pay transaction, and notify the third party computing system **131** that the user associated with the passcode was unable to deposit the user selected amount, and that the transaction was therefore unsuccessful. The transaction processing circuit **142** may also notify the third party computing system **131** of an unsuccessful transaction if the user actuates the

“Cancel and Return Cash” button **3504**.

(143) Responsive to the user actuating the “Confirm Total” button **3502**, the user interface circuit **107** can display a user interface **3600** shown in FIG. **36** on the display **138** of the transaction machine **1130**. The user interface **3600** can display bill pay information **3606** including the name of the merchant to which the payment was made and the amount paid. The user interface **3600** may also include a “Confirm” button **3602** and a “Cancel and Return Cash” button **3604**. The actuation of the “Confirm” button **3602** can indicate that the user confirms the information displayed on the user interface **3600** to be correct.

(144) Responsive to the user actuating the “Confirm” button **3602**, the transaction processing circuit **142** can process the payment (FIG. **26**, **2628**). In particular, the transaction processing circuit **142** can send a notification (FIG. **26**, **2630**) to the third party computing system **131** that a user has deposited cash for a bill payment. The notification **2630** can include information stored in the transaction machine account database **1127** associated with the processed payment. For example, the notification can include the passcode entered by the user and the amount deposited by the user. In some instances, the transaction machine **1130** can also send a notification to the provider computing machine **101** indicating that the user associated with the passcode has deposited cash at the transaction machine, where the notification can include the amount deposited. The third party computing machine **131** can, in turn, notify (**2632**) the user that the payment was successfully received. For example, the third party computing system **131** can send a text, email, or a message on a third party application installed on the user computing device.

(145) Also, responsive to the user actuating the “Confirm” button **3602** on the user interface **3600** shown in FIG. **36**, the user interface circuit **107** can generate and display on the display **138** the user interface **3700** shown in FIG. **37**. The user interface **3700** can allow the user to print a receipt for the deposit. For example, the user interface **3700** can include a “Yes” button **3704**, the actuation of which can indicate to the user interface **107** that the user would like to receive a receipt. The user interface **3700** also can include a “No” button **3702**, the actuation of which can indicate that the user does not need a receipt.

(146) FIG. **38** shows a process flow **3800** for an example payor **3895** to payee **3890** or person to person payment process. The process flow **3800** depicts an example payment process that provides the payor **3895** to make a payment to the payee **3890** at the transaction machine **1130**. As discussed below, the transaction machine **1130** can utilize the passcode to verify the payment transaction.

(147) The process flow **3800** includes the provider computing system **101** receiving a request to generate a passcode (**3802**). This process step is similar to the process step **2602** for requesting generation of a passcode discussed above in relation to FIG. **26**. However, in the process step **2602**, the request for the generation of the passcode was generated by a third party computer system **131**. In contrast, in the process stage **3802**, the request for the generation of the passcode can be received from the payee **3890**. The payee **3890** can be an individual or a corporation. The user interface circuit **107** (FIG. **11**) of the provider computing system **101** can provide the payee a user interface to request the generation of the passcode. In some examples, the user interface circuit **107** can provide a web interface to a payee **3890** device over which the payee can request the generation of the passcode. In some examples, the user interface circuit **107** can receive the request over a text message over the network from the payee **3890** device. In some other examples, the user interface circuit **107** can provide an automated phone voice response system to receive a request for the generation of the passcode over a payee **3890** phone.

(148) In some examples, the request for the generation of the passcode can be received from a payee that is an individual. The account management circuit **103** of the provider computing system **101** can establish, if not already existing, an individual account associated with the payee **3890**. The request **3802** can include an identity or account number of the payee **3890**, which the provider computing system **101** can use to access or determine the existence of an account in the account database **127**. In some examples, the request can be received from a merchant. The merchants can

include, for example, event ticket vendors, local produce vendors, or other small business owners. Such payees may not be sophisticated enough to maintain computing resources, such as a third party computing system **131**, but can still request passcode based transactions using personal computing devices or workstations.

(149) Responsive to receiving the request to generate a passcode, the provider computing system **101** can generate a passcode (**3804**). In one or more embodiments, the provider passcode circuit **109** (FIG. **11**) can include a pseudo-random number generator for generating a random number. In one or more embodiments, the random number can be of a substantially long length, such as, for example, between about 32 bits to about 256 bits. The provider passcode circuit **109** can use the random number as the passcode. In one or more embodiments, the provider passcode circuit **109** can include an encryption engine to generate the passcode based on an encryption algorithm, such as for example AES, a hash algorithm, or other encryption algorithms. In one or more embodiments, the provider passcode circuit **109** may transform the random number or the output of the encryption engine into another number to use as a passcode. For example, the provider passcode circuit **109** can transform binary numbers into decimal numbers, alphabets, or alpha-numeric characters.

(150) In some embodiments, the passcode circuit **109** may assign a lifetime to the generated passcode. In some examples, the request **3802** received from the payee **3890** can include information regarding the lifetime of the passcode to be generated. As discussed above, the passcode can be a static passcode or have a substantially long lifetime, such as for example, a week, a month, etc. The passcode circuit **109** can assign a lifetime based on the lifetime information received from the payee **3890** either with the request (**3802**) or based on a pre-established lifetime policy. In some embodiments, the payee **3890** or some other entity can generate the passcode and provide the passcode to the provider computing system **101**. For example, the payee **3890** device can be used to generate the passcode and communicate the passcode to the provider computing system **101** over a network.

(151) In one or more embodiments, the provider passcode circuit **109** may store the passcode in the account database **127** (FIG. **11**). The account management circuit **103** can create a record associated with payee **3890**. The provider passcode circuit **109** can use the payee information received with the passcode generation request **3802** to access the record associated with the payee **3890**, and store the generated passcode.

(152) The provider computing system **101** can transmit the generated passcode to the payee **3890** (**3806**). The payee **3890** can, in turn, transmit the passcode to the payor **3895**. In some examples, the payee **3890** can electronically transmit the passcode to the payor **3895** via text, email, chat, etc. In some examples, the payee **3890** can also choose to convey the passcode to the payor **3895** in person or over the phone. In some examples, the provider computing system **101** can instead transmit the generated passcode directly to the payor **3895** (**3834**). In this instance as well, the provider computing system **101** may utilize electronic means to transmit the passcode to the payor **3895**. In some other examples, the provider computing system **101** may initiate a work order to have the passcode printed and mailed to the payor **3895**.

(153) The provider computing system **101** can store the passcode in the provider account database **127**. In some instances, the provider computing system **101** can transmit at least a portion of the information stored in the provider account database **127** associated with the payee **3890** to the transaction machine **1130** (**3810**). For example, the provider computing system **101** can transmit the passcode to the transaction machine **1130**, which can store the passcode in the transaction machine account database **1127** (**3812**).

(154) The payor **3895** can approach and interact with the transaction machine **1130** (**3814**). In response to the payee's interaction with the transaction machine **1130**, the user interface circuit **107** can provide (**3816**) a passcode user interface to the payor **3895**. In some embodiments, the transaction machine **1130** can display a passcode interface on a display **138** of the transaction

machine **1130**. One example of the user interface can be similar to the interface **3000** shown in FIG. **30**. In some other embodiments, the transaction machine **1130** can provide an audio user interface in place of or in addition to the display interface. Referring to the interface **3000** shown in FIG. **30**, the interface **3000** can include a “Use an Access Code” button **3002**, which the user can click to initiate the transaction using a passcode (FIG. **38**, **3818**). Responsive to the payor selecting the “Use an Access Code” button **3002**, the user interface circuit **107** can provide a user interface that allows the payor to enter the passcode. A screenshot of an example user interface **3100** is shown in FIG. **31**, and discussed above. The payor can utilize the passcode user interface **3100** to enter the passcode in the passcode field **1302** and click the OK button **3104**.

(155) Responsive to the payor entering the passcode, the transaction machine **1130** can determine the validity of the passcode (**3820**). For example, the transaction processing circuit **142** (FIG. **11**) can access the transaction machine account database **1127** to access a database entry associated with the passcode. If the database entry exists the transaction processing circuit **142** can determine that the passcode is valid. Responsive to determining that the passcode is valid, the transaction machine **1130** can provide an amount user interface requesting an amount associated with the transaction. FIG. **39** shows a screenshot of an example amount user interface **3900** on which the payor can enter an amount. The amount user interface **3900** can include an amount field **3902**, an OK button **3905**, a CLEAR button **3906**, and a CANCEL button **3908**. The payor can use a keypad (not shown) or voice commands to enter the amount in the amount field **3902**. The payor can then press the OK button **3904** to enter the amount (**3822**), or press the CLEAR button **3906** to clear the amount field **3902**, and re-enter a different amount. The payor can press the CANCEL button **3908** to terminate the transaction.

(156) In some embodiments, the transaction machine can verify the amount entered with an expected amount stored in association with the passcode in the account database **1127**. The expected amount can be received as part of the request for the passcode from the payee. In such instances, the transaction machine can match the amount entered by the payor in the amount field **3902** with the expected amount. If the amount matches, the transaction machine can proceed with providing a payment user interface. If the amounts do not match, the transaction machine can indicate the mismatch to the payor on the amount user interface **3900**. The transaction machine **1130** can terminate the transaction if the payor enters an incorrect amount for a pre-determined number of times. Alternatively, the transaction machine **1130** can proceed with providing the payment user interface regardless of the mismatch, and merely indicate to the payor of the mismatch on the amount user interface **3900**.

(157) In some embodiments, the transaction machine can determine whether the amount entered by the payor **3895** exceeds a threshold value above the amount. The threshold value can be set by the payee or by the financial institution associated with the provider computing system **101**. The threshold value can set a safe upper limit to the transactions to reduce mistake or fraud. As an example, the threshold value can be equal to \$500, but other desired threshold values can also be selected. Responsive to determining that the amount entered exceeds the threshold value, the transaction machine can indicate to the payor on the amount user interface to re-enter an amount below the threshold value.

(158) Responsive to receiving the amount from the amount user interface the transaction machine **1130** can provide a payment user interface (**3824**). The payment user interface can allow the user to select a mode of payment. FIG. **40** shows a screenshot of an example payment user interface **4000** that allows the payor to select a mode of payment. The payment user interface **4000** includes a Cash button **4002**, a Credit Card button **4004**, a Cryptocurrency button **4006**, an Account button **4008**, and a Cancel button **4010**. Selection of the appropriate buttons can indicate the mode of payment with which the payor **3895** would like to make the payment in the amount specified in the amount user interface. In the instance where the payor **3895** selects the Cash button **4002**, the transaction machine **1130** can display to the payor **3895** user interfaces similar to those discussed

above in relation to FIGS. 33-36. In some instances, the payor **3895** may select the cash payment mode because the payor **3895** does not hold an account with a provider or financial institution associated with the transaction machine **1130** or the provider computing system **101**.

(159) Similar user interfaces can be provided to the payor **3895** in response to the selection of other modes of payments. For example, responsive to the payor **3895** selecting the Credit Card button **4004**, the transaction machine can provide a credit card user interface that allows the payor **3895** to enter credit card information on the user interface. The transaction machine **1130** can send the credit card information to the provider computing system **101** to process the credit card transaction and provide a notification if the credit card transaction is successful. The transaction machine **1130** can then indicate to the payor **3895** whether the credit card transaction was successfully completed or failed. Similarly, responsive to the payor **3895** selecting the Cryptocurrency button **4006**, the transaction machine **1130** can provide the payor **3895** with a cryptocurrency user interface that allows the payor **3895** to select the type of currency (e.g., Bitcoin, Dash, Ethereum, etc.), and enter the cryptocurrency account information. The transaction machine **1130** can provide the cryptocurrency account information to the provider computing system **101** to process the transaction and receive a notification of success or failure of the transaction. Also similarly, if the user selects the Account button **4008**, the transaction machine can provide an account user interface that allows the payor **3895** to enter details of a bank account, such as a checking or saving account that the payor **3895** holds with the financial institution associated with the provider computing system **101**.

(160) Responsive to successfully receiving the payment, the transaction machine **1130** send a notification of the completion of the transaction to the payee (**3830**). In particular, the transaction processing circuit **142** (FIG. 11) can send a notification to the payee **3890** that a payor has deposited money associated with the passcode. The notification can include the amount deposited, the passcode or information related to the passcode, mode of payment, the time and date of the payment transaction, the location of the transaction machine, etc. The transaction machine **1130** can send the notification electronically, such as for example in a text message or an email. In some instances, the transaction machine **1130** can also send a notification to the provider computing machine **101** indicating that a payment was made in association with the passcode at the transaction machine **1130**, where the notification can include the amount deposited and any other information discussed above. The provider computing system **101** can, in turn, notify the user that the payment was successfully received. For example, the third party computing system **131** can send a text, email, or a message on a third party application installed on the user computing device.

(161) The embodiments of the methods and system have been described with reference to drawings. The drawings illustrate certain details of specific embodiments that implement the systems and methods and programs of the present invention. However, describing the invention with drawings should not be construed as imposing on the invention any limitations that may be present in the drawings. The embodiments described above contemplate methods, systems and program products stored on any non-transitory machine-readable storage media for accomplishing its operations. The embodiments may be implemented using an existing computer processor, or by a special purpose computer processor incorporated for this or another purpose or by a hardwired system.

(162) As noted above, embodiments can include program products comprising non-transitory machine-readable storage media for carrying or having machine-executable instructions or data structures stored thereon. Such machine-readable media may be any available media that may be accessed by a general purpose or special purpose computer or other machine with a processor. By way of example, such machine-readable storage media may comprise RAM, ROM, EPROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium which may be used to carry or store desired program code in the form of machine-executable instructions or data structures and which may be accessed by a general

purpose or special purpose computer or other machine with a processor. Combinations of the above are also included within the scope of machine-readable media. Machine-executable instructions comprise, for example, instructions and data which cause a general purpose computer, special purpose computer, or special purpose processing machines to perform a certain function or group of functions.

(163) Embodiments of the present invention have been described in the general context of method steps which may be implemented in one embodiment by a program product including machine-executable instructions, such as program code, for example in the form of program modules executed by machines in networked environments. Generally, program modules include routines, programs, logics, objects, components, data structures, etc. that perform particular tasks or implement particular abstract data types. Machine-executable instructions, associated data structures, and program modules represent examples of program code for executing steps of the methods disclosed herein. The particular sequence of such executable instructions or associated data structures represent examples of corresponding acts for implementing the functions described in such steps.

(164) As previously indicated, embodiments of the present invention may be practiced in a networked environment using logical connections to one or more remote computers having processors. Those skilled in the art will appreciate that such network computing environments may encompass many types of computers, including personal computers, hand-held devices, multi-processor systems, microprocessor-based or programmable consumer electronics, network PCs, minicomputers, mainframe computers, and so on. Embodiments of the invention may also be practiced in distributed computing environments where tasks are performed by local and remote processing devices that are linked (either by hardwired links, wireless links, or by a combination of hardwired or wireless links) through a communications network. In a distributed computing environment, program modules may be located in both local and remote memory storage devices.

(165) An exemplary system for implementing the overall system or portions of the invention might include a general purpose computing computers in the form of computers, including a processing unit, a system memory or database, and a system bus that couples various system components including the system memory to the processing unit. The database or system memory may include read only memory (ROM) and random access memory (RAM). The database may also include a magnetic hard disk drive for reading from and writing to a magnetic hard disk, a magnetic disk drive for reading from or writing to a removable magnetic disk, and an optical disk drive for reading from or writing to a removable optical disk such as a CD ROM or other optical media. The drives and their associated machine-readable media provide nonvolatile storage of machine-executable instructions, data structures, program modules and other data for the computer. It should also be noted that the word “terminal” as used herein is intended to encompass computer input and output devices. User interfaces, as described herein may include a computer with monitor, keyboard, a keypad, a mouse, joystick or other input devices performing a similar function.

(166) It should be noted that although the diagrams herein may show a specific order and composition of method steps, it is understood that the order of these steps may differ from what is depicted. For example, two or more steps may be performed concurrently or with partial concurrence. Also, some method steps that are performed as discrete steps may be combined, steps being performed as a combined step may be separated into discrete steps, the sequence of certain processes may be reversed or otherwise varied, and the nature or number of discrete processes may be altered or varied. The order or sequence of any element or apparatus may be varied or substituted according to alternative embodiments. Accordingly, all such modifications are intended to be included within the scope of the present invention. Such variations will depend on the software and hardware systems chosen and on designer choice. It is understood that all such variations are within the scope of the invention. Likewise, software and web implementations of the present invention could be accomplished with standard programming techniques with rule

based logic and other logic to accomplish the various database searching steps, correlation steps, comparison steps and decision steps.

(167) The foregoing description of embodiments of the invention has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise form disclosed, and modifications and variations are possible in light of the above teachings or may be acquired from practice of the invention. The embodiments were chosen and described in order to explain the principals of the invention and its practical application to enable one skilled in the art to utilize the invention in various embodiments and with various modifications as are suited to the particular use contemplated. Other substitutions, modifications, changes and omissions may be made in the design, operating conditions and arrangement of the embodiments without departing from the scope of the present invention.

(168) Throughout the specification, numerous advantages of the exemplary embodiments have been identified. It will be understood of course that it is possible to employ the teachings herein without necessarily achieving the same advantages. Additionally, although many features have been described in the context of a particular data processing unit, it will be appreciated that such features could also be implemented in the context of other hardware configurations.

(169) While the exemplary embodiments illustrated in the figures and described above are presently preferred, it should be understood that these embodiments are offered by way of example only. Other embodiments may include, for example, structures with different data mapping or different data. The invention is not limited to a particular embodiment, but extends to various modifications, combinations, and permutations that nevertheless fall within the scope and spirit of the appended claims.

Claims

1. A method comprising: receiving, at a transaction machine via a payment user interface, a request from a payor for a transaction to make a payment to a payee; providing, by the transaction machine, a passcode user interface that allows receipt of a passcode input; receiving, by the transaction machine via the passcode user interface, the passcode input; determining, by the transaction machine, that the passcode input is valid; providing, by the transaction machine, based on determining that the passcode input is valid, an amount user interface that requests an amount input associated with the request for the transaction; receiving, by the transaction machine via the amount user interface, the amount input associated with the request for the transaction; activating, by the transaction machine and in response to the amount input, a cash deposit mechanism to receive a cash deposit; receiving, by the transaction machine via the cash deposit mechanism, the cash deposit; scanning, by the transaction machine, at least one bill of the cash deposit to determine a denomination of the at least one bill; determining, by the transaction machine and based on scanning the at least one bill, a sequence of user interfaces to be displayed on a display of the transaction machine; and providing, by the transaction machine using the determined sequence, a deposit user interface that displays deposit information based on the at least one bill.
2. The method of claim 1, further comprising displaying, via the deposit user interface, a progress of the scanning of the at least one bill.
3. The method of claim 1, further comprising: scanning, by the transaction machine, a plurality of bills of the cash deposit; identifying, by the transaction machine, at least one denomination of the plurality of bills; determining, by the transaction machine, a number of bills associated with the at least one denomination of the plurality of bills; counting, by the transaction machine, a total amount of the cash deposit; and displaying, by the transaction machine via the deposit user interface, at least one of a list of the at least one denomination of the plurality of bills, the number of bills associated with each of the at least one denomination of the plurality of bills, or the total amount of the cash deposit.

4. The method of claim 1, further comprising: providing, by the transaction machine via the deposit user interface, a total amount of the cash deposit.
5. The method of claim 1, further comprising: generating, by a provider computing system associated with the transaction machine, a passcode unique to the request from the payor; transmitting, by the provider computing system, the generated passcode; receiving, by the transaction machine from the provider computing system communicably coupled to the transaction machine, the generated passcode; and determining, by the transaction machine, that the passcode input received via the passcode user interface matches the generated passcode received from the provider computing system.
6. The method of claim 1, further comprising: verifying, by the transaction machine based on receiving the amount input, that an amount associated with the amount input does not exceed a threshold value.
7. The method of claim 1, further comprising: generating, by a provider computing system associated with the transaction machine, a passcode unique to the request from the payor, wherein the generated passcode is generated based on a request received from an individual account holder.
8. The method of claim 7, further comprising: transmitting, by the provider computing system, the generated passcode to the payor via at least one of a text message or an email.
9. The method of claim 7, further comprising: transmitting, by the provider computing system, the generated passcode to the payee via at least one of a text message, an email, or an account webpage of the payee.
10. The method of claim 1, further comprising: transmitting, by the transaction machine to a provider computing system, a payment notification message including a payment amount and the passcode input.
11. The method of claim 1, wherein the payor does not hold an account with a provider associated with the transaction machine.
12. A system comprising: a transaction machine comprising one or more processors and a computer readable storage medium storing instructions that when executed cause the transaction machine to perform transaction machine operations comprising: receiving, via a payment user interface, a request from a payor for a transaction to make a payment to a payee; providing a passcode user interface that allows receipt of a passcode input; receiving, via the passcode user interface, the passcode input; determining that the passcode input is valid; providing, based on determining that the passcode input is valid, an amount user interface that requests an amount input associated with the request for the transaction; receiving, via the amount user interface, the amount input associated with the request for the transaction; activating, in response to the amount input, a cash deposit mechanism to receive a cash deposit; receiving, via the cash deposit mechanism, the cash deposit; scanning at least one bill of the cash deposit to determine a denomination of the at least one bill; determining, based on scanning the at least one bill, a sequence of user interfaces to be displayed on a display of the transaction machine; and providing, using the determined sequence, a deposit user interface that displays deposit information based on the at least one bill.
13. The system of claim 12, wherein the transaction machine operations further comprise: displaying, via the deposit user interface, a progress of the scanning of the at least one bill.
14. The system of claim 12, wherein the transaction machine operations further comprise: scanning a plurality of bills of the cash deposit; and displaying, via the deposit user interface, at least one of a list of denominations of the plurality of bills, a number of bills of each of the denominations, or a total amount of the cash deposit.
15. The system of claim 12, wherein the transaction machine operations further comprise: providing, via the deposit user interface, a total amount of the cash deposit.
16. The system of claim 12, wherein the one or more processors are one or more first processors, the computer-readable storage medium is a first computer-readable storage medium, and the instructions are first instructions, the system further comprising: a provider computing system

comprising one or more second processors and a second computer readable storage medium storing second instructions that when executed cause the provider computing system to perform provider operations comprising: generating a passcode unique to the request from the payor for the transaction to make the payment to the payee; and transmitting the generated passcode; and wherein the transaction machine operations further comprise: receiving, from the provider computing system, the generated passcode; and determining that the passcode input received via the passcode user interface matches the generated passcode received from the provider computing system.

17. The system of claim 16, wherein the generated passcode is generated based on a request received from an individual account holder.

18. The system of claim 12, wherein the transaction machine operations further comprise: verifying, based on receiving the amount input, that an amount associated with the amount input does not exceed a threshold value.

19. A system comprising: a transaction machine associated with a provider computing system, the transaction machine comprising one or more processors and computer readable storage medium storing instructions that when executed cause the transaction machine to perform transaction machine operations comprising: providing a passcode user interface that allows receipt of a passcode input; receiving, via the passcode user interface, the passcode input; determining that the passcode input is valid; providing, based on determining that the passcode input is valid, an amount user interface that requests an amount input associated with a transaction; receiving, via the amount user interface, the amount input associated with the transaction; activating, in response to the amount input, a cash deposit mechanism to receive a cash deposit; receiving, via the cash deposit mechanism, the cash deposit; scanning at least one bill of the cash deposit to determine a denomination of the at least one bill; determining, based on scanning the at least one bill, a sequence of user interfaces to be displayed on a display of the transaction machine; and providing, using the determined sequence, a deposit user interface that displays deposit information based on the at least one bill.

20. The system of claim 19, wherein the transaction machine operations further comprise: scanning a plurality of bills of the cash deposit; displaying, via the deposit user interface, a progress of the scanning of the plurality of bills; and displaying, via the deposit user interface, at least one of a list of denominations of the plurality of bills, a number of bills of each of the denominations, or a total amount of the cash deposit.
