



US012408942B2

(12) **United States Patent**
Pigott

(10) **Patent No.:** **US 12,408,942 B2**

(45) **Date of Patent:** **Sep. 9, 2025**

(54) **INTRAVASCULAR CATHETER HAVING AN EXPANDABLE INCISING PORTION AND EMBOLIC PROTECTION DEVICE**

17/320708; A61B 17/3207; A61B 2017/320741; A61B 17/320758; A61B 2017/320766; A61B 2017/320755;
(Continued)

(71) Applicant: **VentureMed Group, Inc.**, Plymouth, MN (US)

(56)

References Cited

(72) Inventor: **John P. Pigott**, Sylvania, OH (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **VentureMed Group, Inc.**, Plymouth, MN (US)

2,655,154 A 10/1953 Richter
3,557,794 A 1/1971 Van Patten
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 380 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **17/886,605**

EP 0727194 A1 8/1996
WO 8102109 A1 8/1981
(Continued)

(22) Filed: **Aug. 12, 2022**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2022/0378463 A1 Dec. 1, 2022

Cardiovascular Systems Inc., Diamondback 360 Coronary Orbital Atherectomy System, <http://www.csi360.com/products/coronary-diamondback-360-coronary-orbital-atherectomy-system-crowns/>, 2016.

(Continued)

Related U.S. Application Data

(63) Continuation of application No. 15/200,767, filed on Jul. 1, 2016, now Pat. No. 11,413,062.

Primary Examiner — Ashley L Fishback

Assistant Examiner — Chima U Igboko

(74) *Attorney, Agent, or Firm* — Standley Law Group LLP; Adam J. Smith; Jeffrey S. Standley

(51) **Int. Cl.**

A61B 17/3207 (2006.01)

A61B 17/3209 (2006.01)

A61B 17/00 (2006.01)

(52) **U.S. Cl.**

CPC .. **A61B 17/320725** (2013.01); **A61B 17/3209** (2013.01); **A61B 2017/00986** (2013.01);

(Continued)

(57)


ABSTRACT

An intravascular device and methods for using the same are provided. The intravascular device includes an expandable portion with struts operable between a first position and a second position where the struts are moved outward from the first position. An incising element is provided at, and extends outward from, at least one of the struts. An embolic protection device covers at least a portion of the expandable portion.

(58) **Field of Classification Search**

CPC .. A61B 17/320783; A61B 2017/00986; A61B 17/3209; A61B 17/320725; A61B

17 Claims, 9 Drawing Sheets



(52)	U.S. CL.	CPC	<i>A61B 2017/320716</i> (2013.01); <i>A61B 17/32075</i> (2013.01)	7,850,685	B2	12/2010	Kunis et al.
				7,850,710	B2	12/2010	Huss
(58)	Field of Classification Search	CPC	<i>A61B 2017/320791</i> ; <i>A61B 17/3439</i> ; <i>A61B 5/6858</i> ; <i>A61B 17/320016</i> ; <i>A61B 17/32002</i> ; <i>A61B 2017/320024</i> ; <i>A61B 2017/320028</i> ; <i>A61B 2017/320032</i>	7,887,557	B2	2/2011	Kelley et al.
				7,914,549	B2	3/2011	Morsi
				7,955,350	B2	6/2011	Konstantino et al.
				8,308,754	B2	11/2012	Belson
				8,323,307	B2	12/2012	Hardert
				8,328,829	B2	12/2012	Olson
				8,348,987	B2	1/2013	Eaton
				8,366,661	B2	2/2013	Weber et al.
				8,398,662	B2	3/2013	Granada et al.
				8,430,904	B2	4/2013	Belson
				8,454,636	B2	6/2013	Konstantino et al.
				8,500,789	B2	8/2013	Wuebbeling et al.
(56)	References Cited	U.S. PATENT DOCUMENTS		8,613,721	B2	12/2013	Wulfman
				8,685,049	B2	4/2014	Schur et al.
				8,685,050	B2	4/2014	Schur et al.
				8,702,736	B2	4/2014	Schur et al.
				8,740,849	B1	6/2014	Fischell et al.
				8,870,816	B2	10/2014	Chambers et al.
				8,968,354	B2	3/2015	Wang et al.
				8,974,490	B2	3/2015	Jonsson
				9,039,727	B2	5/2015	Kusleika
				9,079,000	B2	7/2015	Hanson et al.
				9,192,747	B2	11/2015	Hardert
				9,282,991	B2	3/2016	Schur et al.
				9,314,329	B2	4/2016	Dickinson et al.
				9,364,255	B2	6/2016	Weber
				9,364,284	B2	6/2016	Groff et al.
				9,510,901	B2	12/2016	Steinke et al.
				9,532,798	B2	1/2017	Schur et al.
				9,545,263	B2	1/2017	Lenihan et al.
				9,592,386	B2	3/2017	Mathur et al.
				9,604,036	B2	3/2017	Burton et al.
				9,615,848	B2	4/2017	Pigott
				10,463,387	B2	11/2019	Pigott
				10,485,572	B2	11/2019	Pigott
				10,610,255	B2	4/2020	Pigott
				10,842,971	B2	11/2020	Iwano et al.
				10,874,837	B2	12/2020	Iwano et al.
				2001/0007059	A1	7/2001	Mirzaee
				2002/0010489	A1	1/2002	Grayzel et al.
				2002/0029052	A1	3/2002	Evans et al.
				2002/0143350	A1	10/2002	Heitzmann et al.
				2002/0143362	A1	10/2002	Macovial et al.
				2002/0161394	A1	10/2002	Macovial et al.
				2003/0069547	A1	4/2003	Gonon
				2003/0125756	A1	7/2003	Shturman et al.
				2003/0144677	A1	7/2003	Lary
				2003/0208215	A1	11/2003	Uflacker
				2004/0034384	A1	2/2004	Fukaya
				2004/0098014	A1	5/2004	Flugelman
				2004/0122457	A1	6/2004	Weber
				2004/0204738	A1*	10/2004	Weber A61B 17/22031
				2004/0267345	A1	12/2004	Lorenzo et al.
				2005/0055077	A1	3/2005	Marco et al.
				2005/0149102	A1	7/2005	Radisch, Jr. et al.
				2005/0149159	A1	7/2005	Andreas et al.
				2005/0151304	A1	7/2005	Boelens et al.
				2005/0240176	A1	10/2005	Oral et al.
				2006/0020285	A1	1/2006	Niermann
				2006/0089637	A1	4/2006	Werneth et al.
				2006/0106413	A1	5/2006	Bence et al.
				2006/0111736	A1	5/2006	Kelley
				2006/0116701	A1	6/2006	Crow
				2006/0184191	A1	8/2006	O'Brien
				2006/0253148	A1	11/2006	Leone et al.
				2007/0005093	A1	1/2007	Cox
				2007/0060863	A1	3/2007	Goeken et al.
				2007/0083194	A1	4/2007	Kunis et al.
				2007/0106215	A1	5/2007	Olsen et al.
				2007/0156225	A1	7/2007	George et al.
				2007/0181157	A1	8/2007	Dadourian
				2008/0140051	A1	6/2008	Bei et al.
				2008/0294116	A1	11/2008	Wolter et al.
				2008/0300594	A1	12/2008	Goto
				2008/0300610	A1	12/2008	Chambers
				2009/009583	A1	4/2009	Butterfield et al.

(56)

References Cited**U.S. PATENT DOCUMENTS**

2009/0105686	A1	4/2009	Snow et al.
2009/0192508	A1	7/2009	Lauffer et al.
2009/0204068	A1	8/2009	Nguyen et al.
2009/0254172	A1	10/2009	Grewe
2009/0306690	A1	12/2009	Rivers et al.
2009/0312807	A1	12/2009	Boudreault et al.
2010/0010521	A1	1/2010	Kuruss
2010/0023035	A1	1/2010	Kontos
2010/0076482	A1	3/2010	Shu et al.
2010/0121270	A1	5/2010	Gunday et al.
2010/0168737	A1	7/2010	Grunewald
2010/0168778	A1	7/2010	Braido
2010/0228333	A1	9/2010	Drasler et al.
2010/0330147	A1	12/2010	Hossainy et al.
2011/0060182	A1	3/2011	Kassab et al.
2011/0152683	A1	6/2011	Gerrans et al.
2011/0160645	A1	6/2011	Sutermeister et al.
2011/0184447	A1	7/2011	Leibowitz et al.
2011/0288479	A1	11/2011	Burton
2012/0053485	A1	3/2012	Bloom
2012/0143054	A1	6/2012	Eaton et al.
2012/0150142	A1	6/2012	Weber et al.
2012/0157988	A1	6/2012	Stone et al.
2012/0172901	A1	7/2012	Manderfeld et al.
2012/0191111	A1	7/2012	Aggerholm et al.
2013/0066346	A1 *	3/2013	Pigott A61B 17/3209 606/159
2013/0116715	A1 *	5/2013	Weber A61F 2/014 606/159
2013/0131594	A1	5/2013	Bonnette et al.
2013/0150874	A1	6/2013	Kassab
2013/0237950	A1	9/2013	Gianotti et al.
2013/0253467	A1	9/2013	Gianotti et al.
2014/0121672	A1	5/2014	Folk
2014/0257367	A1	9/2014	Jonsson
2014/0257368	A1	9/2014	Jonsson
2014/0277002	A1	9/2014	Grace
2014/0350523	A1	11/2014	Dehdashtian et al.
2014/0364896	A1	12/2014	Consigny
2014/0371783	A1	12/2014	Shu et al.
2015/0133978	A1	5/2015	Paul, Jr.
2015/0182324	A1	7/2015	Naor et al.
2016/0143721	A1	5/2016	Rosenbluth et al.

2017/0056048	A1	3/2017	Erpen
2017/0238960	A1	8/2017	Hatta et al.
2018/0177985	A1	6/2018	Nakagawa et al.
2020/0289102	A1	9/2020	Wilson et al.
2020/0297376	A1	9/2020	Marks et al.
2021/0023347	A1	1/2021	Iwano et al.
2021/0220008	A1	7/2021	Pigott

FOREIGN PATENT DOCUMENTS

WO	9502370	A2	1/1995
WO	1996039997	A2	12/1996
WO	9918862	A1	4/1999
WO	02078511	A2	10/2002
WO	02078511	A3	10/2002
WO	2007095125	A2	8/2007
WO	2013159066	A1	10/2013
WO	2013169596	A1	11/2013
WO	2014106226	A2	7/2014
WO	2014142801	A1	9/2014
WO	2015190578	A1	12/2015
WO	2015195606	A1	12/2015
WO	2016210167	A1	12/2016

OTHER PUBLICATIONS

Boston Scientific Corporation, FilterWire EZ, Embolic Protection System for Carotid Arteries, Sep. 2015, <http://www.bostonscientific.com/en-US/products/embolic-protection/filterwire-ez-embolic-protection-system.html>.

International Search Report, Application No. PCT/US2012/055079, dated Jan. 31, 2013.

Boston Scientific, Rotablator Rotational Atherectomy System, <http://www.bostonscientific.com/en-US/products/plaque-modification/rotaablator-rotational-atherectomy-system.html>, 2017.


Covidien, SpiderFX Embolic Protection Device, 2015, <https://www.ev3.net/peripheral/us/embolic-protection/spiderfxtrade-embolic-protection-device.htm>.


Boston Scientific, Sterling .018" Balloon Catheter, Jun. 2015.

Ham, S. et al., Safety of Carbon Dioxide Digital Subtraction Angiography, Archives of Surgery, Dec. 2011


Alexander, J., CO2 Angiography in Lower Extremity Arterial Disease, Endovascular Today, Sep. 2011, pp. 27-34.

* cited by examiner






2012









30




FIG. 5













FIG. 7

FIG. 6










FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22

1

INTRAVASCULAR CATHETER HAVING AN EXPANDABLE INCISING PORTION AND EMBOLIC PROTECTION DEVICE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 15/200,767 filed Jul. 1, 2016, the disclosures of which are incorporated herein by reference as if fully restated herein.

BACKGROUND OF THE INVENTION

This invention relates in general to intravascular catheters, such as can be used during minimally invasive surgical procedures. In particular, this invention relates to an intravascular catheter having an expandable incising portion.

Atherosclerosis is a chronic condition in which atherosclerotic plaque accumulates on the inner walls of a blood vessel. As a result, the blood vessel walls can become inflamed and, over time, may harden to form atherosclerotic lesions that cause a narrowing of the vessel lumen. In severe cases, the atherosclerotic lesions can rupture and induce the formation of thrombus (i.e., blood clots), which can prevent blood flow through the narrowed vessel lumen.

There are known procedures and devices for treating or otherwise reducing the risks associated with atherosclerosis. For example, an angioplasty is a procedure in which a balloon catheter is inserted into a narrowed region of the vessel lumen via a delivery catheter. The balloon catheter includes a flexible tube having an inflatable balloon at an end thereof. Once positioned in the narrowed region, the balloon is inflated in order to dilate the narrowed vessel lumen. The pressure in the balloon is generally sufficient to compress the accumulated plaque. However, in some cases it would be desirable to fragment the atherosclerotic lesions. Thus, it would be desirable to provide an intravascular catheter having an expandable portion that can be selectively controlled by a user and adapted to create incisions in atherosclerotic material to facilitate fragmentation of the material during an angioplasty procedure.

Embolism is a risk sometimes associated with many surgical procedures, such as angioplasty and the treatment of other peripheral artery diseases. A blood clot, air bubble, plaque fragment, or other embolism may be formed or be dislodged and travel through the patient's vascular system and cause damage. Embolic protection devices are sometimes placed in the patient's vascular system during surgical procedures in order to catch and remove emboli that may form or be dislodged. Use of such devices generally requires selection of the proper device, insertion and positioning of the device, performing the treatment, and removing said device. Proper design, inventory, and selection of embolic protection devices can be difficult as different treatment sites, procedures, and varying patient anatomy may require a healthcare provider to keep an inventory of many different devices to provide proper protection in the various conditions that may be encountered. Further, placement of these devices can be time consuming and expensive. Further still, the placed devices may be cumbersome and difficult to work around.

SUMMARY OF THE INVENTION

This invention relates to an intravascular catheter device for use during a surgical procedure. The catheter device

2

includes a catheter tube having an expandable portion with a plurality of struts each defining an outer surface. The expandable portion is operable between a closed position, wherein the expandable portion has a first diameter, and an opened position, wherein the expandable portion has a second diameter that is larger than the first diameter. An incising element is provided on the outer surface of at least one of the struts. The incising element has a sharpened edge that extends outwardly in a radial direction from the outer surface of the strut for creating an incision in atherosclerotic material located within a blood vessel when the expandable portion is in the opened position.

An embolic protection device may be integrated with the expandable portion. In exemplary embodiments, the embolic protection device is a mesh or film having a series of apertures located thereon. The embolic protection device may be positioned on the distal end of the expandable portion such that the embolic protection device forms a catch net when the expandable portion is placed in the opened position. The intravascular catheter device, and thus the net, may be positioned downstream of the treatment area with the net in the opened position such that the blood flow runs through the net once the intravascular device is positioned. The intravascular device may be retracted against the blood flow during treatment, thereby capturing any emboli that may be formed or dislodged as the intravascular device negotiates the treatment area. Once reaching the end of the treatment site, the surgeon may close the net, thereby trapping any captured emboli. The intravascular device, and thus the trapped emboli, may then be removed from the patient.

Various aspects of this invention will become apparent to those skilled in the art from the following detailed description of the preferred embodiments, when read in light of the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a plan view of a catheter device that includes a handle assembly and a catheter tube having an expandable incising portion, in accordance with a first embodiment of this invention.

FIG. 2 is a cross-sectional side view of the handle assembly taken along section line 2-2 shown in FIG. 1 when the catheter device is in a first operating mode.

FIG. 3 is an enlarged cross-sectional side view of the catheter tube taken along section line 3-3 shown in FIG. 1 illustrating the expandable incising portion disposed within a blood vessel.

FIG. 4 is a cross-sectional end view of the expandable incising portion taken along section line 4-4 shown in FIG. 3.

FIG. 5 is a cross-sectional side view of the handle assembly taken along section line 2-2 shown in FIG. 1 when the catheter device is in a second operating mode.

FIG. 6 is an enlarged cross-sectional side view of the catheter tube taken along section line 3-3 shown in FIG. 1 illustrating the expandable incising portion in an opened position.

FIG. 7 is a cross-sectional end view of the expandable incising portion taken along section line 7-7 shown in FIG. 6.

FIG. 8 is an enlarged side view of a catheter tube having an expandable incising portion, in accordance with a second embodiment of this invention.

3

FIG. 9 is a side view of the catheter tube shown in FIG. 8 illustrating the expandable incising portion in an opened position.

FIG. 10 is a cross-sectional end view of the expandable incising portion taken along section line 10-10 shown in FIG. 9.

FIG. 11 is an enlarged side view of a catheter tube having an expandable incising portion, in accordance with a third embodiment of this invention.

FIG. 12 is a side view of the catheter tube shown in FIG. 11 illustrating the expandable incising portion in an opened position.

FIG. 13 is an end view of the catheter tube as shown in FIG. 12.

FIG. 14 is an enlarged side view of a catheter tube having an expandable incising portion, in accordance with a fourth embodiment of this invention.

FIG. 15 is a side view of the catheter tube shown in FIG. 14 illustrating the expandable incising portion in an opened position.

FIG. 16 is an end view of the catheter tube as shown in FIG. 15.

FIG. 17 is a side view of the device shown in FIG. 8 with an exemplary embolic protection device installed thereon.

FIG. 18 is a side view of the device shown in FIG. 17 with the expandable incising portion in the opened position.

FIG. 19 is a side view of the device shown in FIG. 11 with the exemplary embolic protection device installed thereon.

FIG. 20 is a side view of the device shown in FIG. 19 with the expandable incising portion in the opened position.

FIG. 21 is a side view of the device shown in FIG. 11 with another exemplary embolic protection device installed thereon.

FIG. 22 is a side view of the device shown in FIG. 21 with the expandable incising portion in the opened position.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the drawings, there is illustrated in FIG. 1 a catheter device, indicated generally at 10, in accordance with this invention. The illustrated catheter device 10 is configured to treat or reduce the risks associated with atherosclerosis. In general, the catheter device 10 includes an expandable incising portion that can be inserted into a blood vessel and expanded to create incisions in atherosclerotic material that has accumulated on inner walls of the blood vessel. The incisions facilitate the fragmentation of the atherosclerotic material during a subsequent angioplasty or atherectomy procedure. Although the catheter device 10 will be described and illustrated in the context of treating atherosclerosis, it should be appreciated that the catheter device 10 can be used in any desired environment and for any desired purpose.

Referring now to FIGS. 1 and 2, the illustrated catheter device 10 includes a handle assembly, indicated generally at 20. The illustrated handle assembly 20 includes an elongated, cylindrical handle body 21. The handle body 21 may alternatively have any other shape that is suitable for easy handling by a surgeon. Further, the handle body 21 can be made from any suitably rigid material including, but not limited to, stainless steel or polymers.

As shown in FIG. 2, the illustrated handle body 21 defines an internal chamber 22. A passage 23 extends into an end portion of the handle body 21 for communication with the internal chamber 22. The handle body 21 further includes a slot 24 that extends through a side wall thereof for commu-

4

nication with the internal chamber 22. The illustrated slot 24 may have any length or width as desired. As shown in FIG. 1, an indicator 24A may be provided on the handle body 21 adjacent to the slot 24. For example, the indicator 24A can be a visual scale or any other indicating means, the purpose of which will be explained below.

The illustrated handle assembly 20 also includes a control member 25 that is supported on the handle body 21 for sliding movement within the slot 24. For example, the control member 25 is movable between a forward position (shown in FIG. 2), a rearward position (shown in FIG. 5), or any position therebetween, which will be further explained below. As shown in FIG. 2, the illustrated control member 25 includes a base portion 26 that is disposed within the internal chamber 22 of the handle body 21. The base portion 26 may define an outer cross-sectional shape that generally corresponds with a cross-sectional shape of the internal chamber 22, although such is not required. Alternatively, (or in addition), the control member 25 may be movably supported on the handle body 21 by a bearing, a bushing, a guide rail, or any other structural means. In other embodiments, the control member 25 may be supported for rotational movement, pivotal movement, or any other type of movement relative to the handle body 21, the purpose of which will become apparent below. The visual indicator 24A, described above, is configured to identify the relative position of the control member 25 with respect to the handle body 21.

The illustrated handle assembly 20 also includes a locking mechanism 27 that is configured to temporarily secure the control member 25 in a desired position, although such is not required. As shown in FIG. 2, the illustrated locking mechanism 27 includes a plurality of protrusions that are spaced apart from one another along an inner surface of the slot 24. The control member 25 frictionally engages the protrusions to hold the control member 25 in the desired position. Alternatively, the locking mechanism 27 may be a threaded fastener, a pivotal latch, a push-button release, or any other mechanism that is configured to secure the control member 25 in a desired position.

Referring now to FIGS. 1 through 3, the illustrated catheter device 10 also includes a catheter tube 30 that extends from the handle assembly 20. The catheter tube 30 is an elongated, flexible member having a proximal end that is secured to the handle assembly 20 and a distal end that extends therefrom. The catheter tube 30 can be made from any biocompatible material including, but not limited to, polyvinyl, polyethylene, nitinol, or stainless steel. Further, the catheter tube 30 can have any outer diameter, length, or wall thickness.

As shown in FIG. 2, the proximal end of the catheter tube 30 is secured to the handle body 21 and communicates with the internal cavity 22 through the passage 23. The catheter tube 30 may be secured to the handle body 21 using a flanged connection, a fused connection, an adhesive, a press-fit connection, a threaded connection, or any other securing means. Alternatively, the catheter tube 30 may be secured to the handle body 21 using a connector or any other type of attachment device.

As shown in FIGS. 1 and 3, an expandable portion 32 is provided on the distal end of the catheter tube 30. The illustrated expandable portion 32 is a cylindrical member having a longitudinal axis. The expandable portion 32 can be made from a generally resilient material that is able to flex between various positions, such as polyvinyl, polyethylene, nitinol, or stainless steel. The expandable portion 32 can be secured to the catheter tube 30 in any manner including, but

5

not limited to, a fused connection, an adhesive, a press-fit connection, a threaded connection, or any other securing means. Alternatively, the expandable portion 32 can be integrally formed from the catheter tube 30. Further, the expandable portion 32 can have any outer diameter, length, or wall thickness.

The illustrated expandable portion 32 has a pair of struts 34A and 34B. The illustrated struts 34A and 34B are separated by a pair of longitudinally extending slits 35A and 35B that extend through side walls of the expandable portion 32. As shown in FIG. 4, the slits 35A and 35B are equally spaced apart from one another around the circumference of the expandable portion 32 such that the struts 34A and 34B have the same circumferential widths, although such is not required. The struts 34A and 34B may have any length, circumferential width, or cross-sectional shape as desired.

As shown in FIGS. 3 and 4, the illustrated expandable portion 32 also includes a pair of incising elements 36 that are respectively provided along outer surfaces of the struts 34A and 34B. The incising elements 36 can be atherotomes or other incising members having arcuate shaped sharpened edges, for example, that are configured to create incisions in atherosclerotic material as will be explained below. The illustrated incising elements 36 extend parallel with the longitudinal axis of the expandable portion 32 and outwardly in a radial direction therefrom. The incising elements 36 are equally spaced apart from one another around the circumference of the expandable portion 32. The expandable portion 32 may, however, have any number or configuration of incising elements 36 provided around the circumference thereof. Further, the incising elements 36 can have any cross-sectional shape, longitudinal length, or height and can be made from any suitable material including, but not limited to, tempered steel, stainless steel, high carbon steel, or ceramics. The incising elements 36 can be molded with the struts 34A and 34B or may otherwise be secured thereto in any manner such as, for example, using a welded or soldered connection, an adhesive, or any other fastening means.

The distal end of the expandable portion 32 may optionally include a tip member 38. The illustrated tip member 38 has a generally conical shape that facilitates insertion of the catheter tube 30 within a blood vessel 50 (see FIGS. 3 and 4) and subsequent travel therethrough. The tip member 38 may, however, have any desired shape. An aperture may axially extend through the tip member 38, the purpose of which will be explained below. The tip member 38 can be integrally formed with the expandable portion 32 or may be secured thereto, such as with an adhesive or the like. Further, the tip member 38 can be made from any biocompatible material including, but not limited to, polyvinyl, polyethylene, nitinol, stainless steel, or polyether block amide.

As shown in FIGS. 2 through 4, the illustrated catheter device 10 also includes an inner sleeve 40, although such is not required. The inner sleeve 40 is a flexible, tubular member that is supported for sliding movement within the catheter tube 30, the purpose of which will be explained below. The inner sleeve 40 can be made from any biocompatible material including, but not limited to, polyvinyl, polyethylene, nitinol, stainless steel, or a woven material. Further, the inner sleeve 40 can have any outer diameter, length, or wall thickness. The inner sleeve 40 need not be a tubular member but may alternatively be a solid wire, a braided wire, or the like.

As shown in FIG. 2, a proximal end of the inner sleeve 40 extends from the catheter tube 30 and into the internal chamber 22 of the handle body 21. The proximal end of the

6

inner sleeve 40 is secured to the base portion 26 of the control member 25 for sliding movement therewith, the purpose of which will be explained below. The inner sleeve 40 can be secured to the base portion 26 by a flanged connection, a fused connection, an adhesive, a threaded connection, or any other securing means.

As shown in FIG. 3, the inner sleeve 40 extends through an entire length of the catheter tube 30. A distal end of the inner sleeve 40 that is opposite the handle assembly 20 is secured to the tip member 38, which is in turn secured to the expandable portion 32. The inner sleeve 40 may be secured to the tip member 38 in any manner including, but not limited to, a fused connection, an adhesive, a fastener, or the like.

Referring back to FIGS. 1 and 2, the illustrated catheter device 10 also includes a protective sheath 42 that is supported for sliding movement along an outer surface of the catheter tube 30, although such is not required. The protective sheath 42 can be made from any biocompatible material including, but not limited to, polyvinyl, polyethylene, nitinol, or stainless steel. Further, the protective sheath 42 can have any outer diameter, length, or wall thickness. The purpose of the protective sheath 42 will be explained below.

The illustrated protective sheath 42 includes a flange 44 that facilitates sliding movement of the protective sheath 42 relative to the catheter tube 30. The illustrated flange 44 is an annular member that is located at an end of the protective sheath 42 nearest the handle assembly 20. The flange 44 can be integrally formed with the protective sheath 42 or may otherwise be secured thereto in any manner, such as with an adhesive or the like. It should be appreciated that the flange 44 can have any shape or may alternatively be configured in any manner to accomplish the functions described herein and below.

The operation of the catheter device 10 will now be described with reference to FIGS. 1 through 7. Referring initially to FIGS. 1 through 4, the catheter device 10 is illustrated in a first operating mode. In the first operating mode, the control member 25 on the handle assembly 20 is located in the forward position relative to the handle body 21. The inner sleeve 40 fully extends into the catheter tube 30 such that the expandable portion 32 is in a closed position, as shown in FIGS. 3 and 4. In the closed position, the struts 34A and 34B are generally parallel with one another and with the inner sleeve 40. The slits 35A and 35B (illustrated by the dashed lines in FIG. 3) remain in a generally closed configuration. As such, the expandable portion 32 defines an initial diameter D1, which is generally the same diameter as the remaining length of the catheter tube 30. The initial diameter D1 of the expandable portion 32 may, however, be any desired dimension.

When the catheter device 10 is in the first operating mode, the distal end of the catheter tube 30 can be percutaneously inserted into a blood vessel 50, as shown in FIGS. 3 and 4. The illustrated catheter tube 30 is then advanced through the blood vessel 50 along a guide wire 52, which extends through the catheter device 10. For example, the guide wire 52 may fully extend through the inner sleeve 40, into the internal chamber 22 of the handle body 21, and exit a rear end of the handle assembly 20 (see FIG. 2). The catheter tube 30 is advanced along the guide wire 52 until the expandable portion 32 is positioned in a narrowed region of the blood vessel 50 caused by atherosclerotic material 54. Alternatively, the catheter tube 30 can be inserted into the blood vessel 50 and guided therethrough by a delivery catheter (not shown) or any other suitable procedure. During

insertion and advancement of the catheter tube **30** through the blood vessel **50**, the optional protective sheath **42** is preferably positioned over the expandable portion **32**, thereby preventing the incising elements **36** from coming into contact with inner walls of the blood vessel **50**.

Once the expandable portion **32** is positioned in the narrowed region of the blood vessel **50**, the incising elements **36** can be exposed by sliding the protective sheath **42** back from the distal end of the catheter tube **30**, as indicated by the direction arrows in FIG. 3. The illustrated protective sheath **42** can be moved in this manner by pulling the flange **44** towards the handle assembly **20**, which is indicated by the direction arrows in FIG. 2.

Referring now to FIGS. 5 through 7, the catheter device **10** is illustrated in a second operating mode. To achieve the second operating mode, the control member **25** is moved from the forward position to the rearward position, as indicated by the direction arrow in FIG. 5. As the control member **25** is moved to the rearward position, the inner sleeve **40** is drawn within the catheter tube **30** thereby reducing the relative length of the inner sleeve **40** with respect to the catheter tube **30**. The distal end of the inner sleeve **40** is attached to the tip member **38**, as described above, causing the expandable portion **32** to become axially compressed between the tip member **38** and the distal end of the catheter tube **30**. As a result, the struts **34A** and **34B** bow or expand outwardly in a generally arcuate fashion thereby defining an opened position. In the opened position, the expandable portion **32** defines a second diameter **D2** that is larger than the initial diameter **D1** when the expandable portion **32** is in the closed position. As shown in FIG. 6, the incising elements **36** are respectively positioned along the radially outer most surfaces of the struts **34A** and **34B**. Further, the outer most surfaces of the struts **34A** and **34B** may define a generally flat portion along a length thereof in the opened position, the purpose of which will be explained below, although such is not required. It should be appreciated that the struts **34A** and **34B** can have any lengths such that the expandable portion **32** can achieve a desired overall second diameter **D2** in the opened position.

During operation of the catheter device **10**, the second diameter **D2** can be increased or decreased by selective movement of the control member **25** between the forward and rearward positions. For example, a larger second diameter **D2** can be achieved by moving the control member **25** further towards the rearward position. Conversely, a smaller second diameter **D2** can be achieved by moving the control member **25** further towards the forward position. The visual indicator **24A** can be used to identify the instantaneous second diameter **D2** of the expandable portion **32**. Alternatively (or in addition), the struts **34A** and **34B** may be biased in the opened position so as to automatically expand outwardly to the second diameter **D2** when the protective sheath **42** is slid back from the expandable portion **32**. As such, sliding movement of the protective sheath **42** relative to the struts **34A** and **34B** can be used to selectively control the second diameter **D2**. In this configuration, the inner sleeve **40** and the movable components of the handle assembly **20** may not be necessary.

When the catheter device **10** is in the second operating mode, the expandable portion **32** can be pulled along the guide wire **52** through the narrowed region of the blood vessel **50**. This can be accomplished by pulling on the handle assembly **20**. In doing so, the incising elements **36** engage the atherosclerotic material **54** and create longitudinal incisions **56** therein. As shown in FIGS. 6 and 7, the outer surface area of the arcuate shaped struts **34A** and **34B**, which

is adjacent to the incising element **36**, is configured to ride along a surface of the atherosclerotic material **54**, thereby limiting the depth of the incisions **56** and preventing the incising members **36** from cutting the walls of the blood vessel **50**. The expandable portion **32** can be moved any distance along the guide wire **52** to create incisions **56** having any desired length. After the incisions **56** are made in the atherosclerotic material **54**, the catheter device **10** can be returned to the first operating mode (shown in FIGS. 1 through 4) by moving the control member **25** to the forward position. In doing so, the expandable portion **32** returns to the closed position. The protective sheath **42** can be slid over the expandable portion **32** and the catheter tube **30** may be removed from the blood vessel **50**.

Alternatively, the catheter device **10** can be used to create additional incisions **56** in the atherosclerotic material **54**. For example, after the catheter device **10** has been returned to the first operating mode, the expandable portion **32** can be relocated within the narrowed region of the blood vessel **50**. The catheter tube **30** can then be rotated within the blood vessel **50** by rotating the handle assembly **20** so as to align the incising elements **36** with other portions of the atherosclerotic material **54**. The previous steps can then be repeated any number of times to make multiple passes through the narrowed region of the blood vessel **50** and create additional incisions in the atherosclerotic material **54**.

Thus, it should be appreciated that the illustrated catheter device **10** is advantageous in many respects. In one example, the second diameter **D2** of the expandable portion **32** can be selectively controlled by operation of the handle assembly **20** or by sliding movement of the protective sheath **42**. This enables the catheter device **10** to be adapted for use in blood vessels **50** of different sizes or varying diameters. In another example, the illustrated catheter device **10** can apply varying magnitudes of radial forces to the atherosclerotic material **54** by controlling the amount of force being applied to the control member **25** on the handle assembly **20**. This enables the catheter device **10** to generate sufficient radial force to create incisions **56** in atherosclerotic material **54** while reducing the potential for tearing the walls of the blood vessel **50**. In yet another example, the catheter device **10** can be used to make any number of passes during a single procedure to make multiple incisions **56** in atherosclerotic material **54** of varying lengths and shapes.

Referring now to FIGS. 8 through 10, there is illustrated a catheter tube **130** having an expandable portion **132**, in accordance with a second embodiment of this invention. The catheter tube **130** and the expandable portion **132** may include any structural features as described and illustrated above in the previous embodiment, although such is not required. Similar features have been numbered with common reference numerals but have been increased by 100 (i.e., 110, 120, 130, etc.). It should be appreciated that similar features are structured similarly, operate similarly, and/or have the same function unless otherwise indicated by the drawings or this specification.

For example, the catheter tube **130** may extend from a handle assembly (not shown) as described above in the first embodiment. The expandable portion **132** is provided on a distal end of the catheter tube **130** and may include a tip member **138**. The catheter tube **130** may also include an inner sleeve **140** and a protective sheath (not shown), which is also described above in the first embodiment.

In the illustrated embodiment, however, the expandable portion **132** includes four struts **134A**, **134B**, **134C**, and **134D** that are respectively separated by four longitudinally extending slits **135A**, **135B**, **135C**, and **135D**. The illustrated

struts **134A**, **134B**, **134C**, and **134D** each include an incising element **136**, although such is not required. It should be appreciated that the expandable portion **132** may have any number or configuration of struts and incising elements as desired.

As shown in FIG. 8, the illustrated expandable portion **132** further includes recessed portions **160** that respectively extend into the outer surfaces of the struts **134A**, **134B**, **134C**, and **134D**. For example, the struts **134A**, **134B**, **134C**, and **134D** can be slightly bowed inwardly toward the inner sleeve **140** when in the closed position or, alternatively, may have a reduced thickness along a central portion thereof to create the recessed portions **160**. The illustrated incising elements **136** are respectively disposed within the recessed portions **160**. Thus, when the catheter tube **130** is inserted into a blood vessel, as described above, the recessed portions **160** help to prevent the incising elements **136** from coming into contact with inner walls of the blood vessel. On the other hand, when the expandable portion **132** is expanded to an opened position, as explained below, the incising elements **136** become exposed from the recessed portions **160**. It should be appreciated that the recessed portions **160** can eliminate or reduce the need for the protective sheath (not shown). The guide wire **152** may extend through the entire device.

The expandable portion **132** can be operated between a closed position (shown in FIG. 8) and an opened position (shown in FIGS. 9 and 10) by selective movement of the inner sleeve **140** relative to the catheter tube **130**, as described above in the first embodiment. Alternatively (or in addition), the struts **134A**, **134B**, **134C**, and **134D** can be biased in the opened position. In such an embodiment, the protective sheath (not shown) can be used to effect movement of the expandable portion **132** between the closed position and the opened position.

Referring now to FIGS. 11 through 13, there is illustrated a catheter tube **230** having an expandable portion **232**, in accordance with a third embodiment of this invention. The catheter tube **230** and the expandable portion **232** may include any structural features as described and illustrated above in the previous embodiments, although such is not required. Similar features have been numbered with common reference numerals but have been increased by 200 (i.e., 210, 220, 230, etc.). It should be appreciated that similar features are structured similarly, operate similarly, and/or have the same function unless otherwise indicated by the drawings or this specification.

For example, the catheter tube **230** may extend from a handle assembly (not shown) as described above in the first embodiment. The expandable portion **232** is provided on a distal end of the catheter tube **230** and includes a pair of struts **234A** and **234B** that are separated by a pair of longitudinally extending slits **235A** and **235B**. The catheter tube **230** may also include a tip member **238**, an inner sleeve **240**, and a protective sheath (not shown), which is described above in the first embodiment. The guide wire **252** may extend through the entire device.

In the illustrated embodiment, however, the expandable portion **232** includes a first pair of weakened regions **237A**, **237B** and a second pair of weakened regions **239A**, **239B** that are respectively located at opposite ends of the struts **234A** and **234B**. The illustrated weakened regions **237A**, **237B** and **239A**, **239B** are formed by enlarged apertures that extend through side walls of the expandable portion **232** that function as hinges. The weakened regions **237A**, **237B** and **239A**, **239B** may help reduce the amount of bending stress in the side walls of the expandable portion **232** when the

struts **234A** and **234B** are moved to an opened position. The struts **234A** and **234B** may include any number or configuration of weakened regions. Further, it should be appreciated that any of the other embodiments in this disclosure may also include weakened regions **237A**, **237B** and **239A**, **239B**.

The illustrated struts **234A** and **234B** remain generally flat along respective lengths thereof in both a closed position (shown in FIG. 11) and an opened position (shown in FIGS. 12 and 13) so as to form an apex, although such a configuration is not required. The incising elements **236** are provided along the generally flat portion of the respective struts **234A** and **234B**. As such, the incising elements **236** may also function as stiffening members for increasing the strength of the struts **234A** and **234B**. Further, this configuration can reduce the amount of stress in the connection between the incising elements **236** and the struts **234A** and **234B**, which may otherwise be caused by bowing of the struts **234A** and **234B**.

As shown in FIG. 12, end portions of the incising elements **236** may extend beyond the apex that is formed by each of the respective struts **234A** and **234B**. This configuration can increase the effective height of the incising elements **236** when the expandable portion **232** is in the opened position. As such, the incising elements **236** may have a reduced height when the expandable portion **232** is in the closed position, which may eliminate the need for the protective sheath (not shown).

The expandable portion **232** can be operated between the closed position and the opened position by selective movement of the inner sleeve **240** relative to the catheter tube **230**, as described above in the first embodiment. Alternatively (or in addition), the struts **234A** and **234B** can be biased in the opened position. In such an embodiment, the protective sheath (not shown) can be used to effect movement of the expandable portion **232** between the closed position and the opened position.

Referring now to FIGS. 14 through 16, there is illustrated a catheter tube **330** having an expandable portion **332**, in accordance with a fourth embodiment of this invention. The catheter tube **330** and the expandable portion **332** may include any structural features as described and illustrated above in the previous embodiments, although such is not required. Similar features have been numbered with common reference numerals but have been increased by 300 (i.e., 310, 320, 330, etc.). It should be appreciated that similar features are structured similarly, operate similarly, and/or have the same function unless otherwise indicated by the drawings or this specification.

For example, the catheter tube **330** may extend from a handle assembly (not shown) as described above in the first embodiment. The expandable portion **332** is provided on a distal end of the catheter tube **330** and may include a tip member **338**. The catheter tube **330** may also include an inner sleeve **340** that is attached to the tip member **338** and a protective sheath (not shown), which is also described above in the first embodiment. The guide wire **352** may extend through the entire device.

In the illustrated embodiment, however, the expandable portion **332** includes a pair of struts **334A** and **334B** that are supported thereon in a cantilevered manner (i.e., not attached to one another or to the tip member **338** at their distal ends), the purpose of which will be explained below. The struts **334A** and **334B** are separated by a pair of longitudinally extending slits **335A** and **335B** that extend from the end of the expandable portion **332**. A pair of incising elements **336** is respectively provided along outer

11

surfaces of the struts **334A** and **334B**. It should be appreciated, however, that the expandable portion **332** may have any number or configuration of struts and incising elements as desired.

As shown in FIGS. **15** and **16**, the illustrated struts **334A** and **334B** are supported on the expandable portion **332** so that they can be splayed open in a Y-shaped configuration. For example, the struts **334A** and **334B** can be splayed open by drawing the inner sleeve **340** within the catheter tube **330**, as described above in the first embodiment. In doing so, the tip member **338** slides along the inner surfaces of the struts **334A** and **334B** and pivots them outwardly. Alternatively (or in addition), the struts **334A** and **334B** can be biased in the splayed open position. In such an embodiment, the protective sheath (not shown) can be used to effect movement of the expandable portion **332** between a closed position and the splayed open position.

The struts **334A** and **334B** remain generally flat along their respective lengths in both a closed position (shown in FIG. **14**) and the splayed open position, although such is not required. As such, the incising elements **336** may also function as stiffening members for increasing the strength of the struts **334A** and **334B**. Further, this configuration can reduce the amount of stress in the connection between the incising elements **336** and the struts **334A** and **334B**, which may otherwise be caused by bowing of the struts **334A** and **334B**.

As shown in FIG. **15**, end portions of the incising elements **336** may extend beyond the distal ends of the respective struts **334A** and **334B**. This configuration can increase the effective height of the incising elements **336** when the expandable portion **332** is in the splayed open position. As such, the incising elements **336** may have a reduced height when the expandable portion **332** is in the closed position, which may eliminate the need for the protective sheath (not shown).

FIGS. **17** and **18** illustrate another exemplary embodiment of the present invention. Specifically, FIG. **17** illustrates the device of FIG. **8** with an exemplary embolic protection device **90** installed thereon, while FIG. **18** illustrates the device of FIG. **17** with the expandable portion **132** in the opened position. The embolic protection device **90** may comprise a basket configured to trap emboli for subsequent removal from the treatment site.

The basket may surround the outer surface of the struts **134A**, **1348**, and **134C** as well as cover the gaps between said struts **134A**, **1348**, and **134C** when the expandable portion **132** is in both the closed and the opened positions. To accomplish this, the basket may be configured to stretch and deform or may comprise excess and/or overlapping material when the expandable portion **132** is in the closed position that unfurls when the expandable portion **132** is in the opened position.

The basket may also cover the front and/or rear of the expandable portion **132**. However, in exemplary embodiments of the present invention, the basket may be open on the proximal end and attached, sealed, bonded, or otherwise adhered to the tip member **138** on the distal end. In this way, the basket creates an opening on the proximal end, and is substantially or partially sealed on the distal end by the combination of the basket, guide wire **152**, inner sleeve **140**, and struts **134A**, **1348**, and **134C**. As will be explained in greater detail herein, the basket may be comprised of a woven material or otherwise comprise a plurality of apertures along the side walls thereof. In exemplary embodiments of the present invention, these apertures may be configured to permit blood to flow therethrough while

12

preventing emboli and other particulate over a specified size from traveling therebeyond. In this way, the blood flow, and any emboli or other particulate contained therein, are forced to enter the basket's opening on the proximal end and leave only if the matter fits through the apertures provided in the sidewalls of the basket.

In exemplary embodiments of the present invention, the basket is comprised of a mesh. The mesh may be of any size, shape, or configuration. The mesh may be comprised of nitinol, polytetrafluoroethylene (PTFE), a metallic, a polymer, or the like and may extend over any section or the entirety of the expandable portion **132**. The mesh may be woven such that the apertures are sized to permit blood (including, for example without limitation, healthy cells, plasma, and platelets) flow therethrough, while trapping emboli and other particulate larger than the apertures provided in the mesh.

The embolic protection device **90** may extend over some or all of the expandable portion **132**. In exemplary embodiments of the present invention, the embolic protection device **90** extends over substantially the distal half of the expandable portion **132** while the incising elements **136** may extend over substantially the proximal half of the expandable portion **132**. Regardless, an expandable hoop **91** may be located on the outer surface of the expandable portion **132** and may assist in securing and preserving the shape of the basket. The expandable hoop **91** may be located at substantially the midline of the expandable portion **132**, though any location is contemplated. The expandable hoop **91** may be comprised of nitinol, PTFE, a metallic, a polymer, or the like and may be configured to expand and collapse when the expandable portion is moved between the opened and the closed positions.

The expandable hoop **91** may be configured to match the outer diameter of the expandable portion **132** when the expandable portion **132** is in both the opened and the closed positions and may be configured to fit inside the sheath **42** if one is being used. In exemplary embodiments of the present invention, the expandable hoop **91** may operate by a telescoping mechanism such that portions of the expandable hoop **91** slide atop one another. In other exemplary embodiments, the expandable hoop **91** may be configured to deform by elongating and reorienting at an increased lateral angle such that the expandable hoop **91** may be placed substantially flush with the outer surface of the expandable portion **132**, when the expandable portion **132** is in the collapsed position and/or is forced inside the sheath **42**.

The expandable hoop **91** may provide an attachment point for the basket. For example, but not to serve as a limitation, in embodiments where the basket is the mesh or other woven material, the mesh may be woven around the expandable hoop **91**. In other exemplary embodiments, the basket may be welded, soldered, adhered, or otherwise bonded to the expandable hoop **91** and/or directly to the struts **134A**, **1348**, and **134C** or other parts of the intravascular catheter device **10**.

In exemplary methods utilizing the present invention, the expandable portion **132** may be placed in the closed position and positioned downstream from the treatment area. The expandable portion **132** may be placed in the opened position. The embolic protection device **90** may be automatically deployed when the expandable portion **132** is placed in the opened position as the basket, and the optional expandable hoop **91** if utilized, may expand when the struts **134A**, **1348**, and **134C** are placed in the opened position and collapse when the struts **134A**, **1348**, and **134C** are placed in the closed position. However, in exemplary embodiments of the

13

present invention, the expandable hoop **91** may be moved between the closed and the opened positions independently of the expandable portion **132**. For example, but without limitation, the expandable hoop **91** may be configured to automatically expand when removed from the sheath **42**. Regardless, the expandable portion **132** may next be retracted along some or all of the treatment area to facilitate fragmentation of the atherosclerotic plaque. The expandable portion **132** and the embolic protection device **90** may then be placed in the closed position, thereby trapping any emboli caught in the basket during the procedure. This process may be repeated multiple times over the same treatment area or over multiple treatment areas.

Similarly, FIG. **19** illustrates the device of FIG. **11** with another exemplary embolic protection device **90** installed thereon, while FIG. **20** illustrates the device of FIG. **19** with the expandable portion **232** in the opened position. The embolic protection device **90** may be similar to the one shown and described with respect to FIGS. **17** and **18**, and may be similarly operated.

FIGS. **21** and **22** illustrate another exemplary embodiment of the embolic protection device **90**. The basket of the embolic protection device **90** may be a film or covering having a number of apertures **92** located therein. Any size, shape, number, and configuration of the apertures **92** are contemplated. In exemplary embodiments of the present invention, the film or covering is comprised of PTFE, though any material is contemplated. Similarly, the film or covering may be attached to the expandable hoop **91**, though such is not required. The embolic protection device **90** may otherwise be similar to the one shown and described with respect to FIGS. **17-20**, and may be similarly operated.

It is notable that while the embolic protection device **90** is illustrated with respect to the devices of FIGS. **8-9** and **11-12**, it is contemplated that the embolic device **90** may be utilized with any of the embodiments of the present invention as shown and/or described herein.

The principle and mode of operation of this invention have been explained and illustrated in its preferred embodiments. However, it must be understood that this invention may be practiced otherwise than as specifically explained and illustrated without departing from its spirit or scope.

What is claimed is:

1. An intravascular catheter device comprising:
a flexible catheter tube;

an expandable portion secured to a distal end of said flexible catheter tube and comprising struts operable between a first position and a second position where the struts are moved outward from the first position, wherein a longitudinal axis of each of said struts extends in a linear fashion in line with a longitudinal axis of the expandable portion, at least when the expandable portion is in the first position;

an incising element provided at, and extending outward from, an outer surface of at least one of the struts such that the outer surface of the at least one of the struts extends laterally beyond the incising element; and

an embolic protection device covering at least a portion of the outer surface of each of the struts of the expandable portion.

2. The intravascular catheter device of claim 1 wherein: said incising element is provided at a proximal half of said at least one of the struts; and

said embolic protection device is provided at a distal half of said expandable portion.

14

3. The intravascular catheter device of claim 2 wherein: said incising element, including an upper surface thereof, extends longitudinally in a linear fashion along said longitudinal axis of said at least one of the struts.

4. The intravascular catheter device of claim 3 wherein: a longitudinal axis of said incising element extends along a midline of the outer surface of said at least one of the struts.

5. The intravascular catheter device of claim 1 further comprising:

an inner sleeve configured for sliding movement within the flexible catheter tube to move the struts between the first position and the second position.

6. The intravascular catheter device of claim 5 further comprising:

a tip member connecting each of the struts to said inner sleeve at the distal end.

7. The intravascular catheter device of claim 6 wherein: each of the struts are connected to said inner sleeve at a distal end by way of the tip member and the flexible catheter tube at a proximal end so as to bow at least a mid-portion outwardly when the expandable portion is placed in the second position.

8. The intravascular catheter device of claim 6 wherein: each of the struts comprise two sections configured for hinging movement relative to one another and said inner sleeve and said flexible catheter tube so as to form a peak at a mid-portion thereof when the expandable portion is placed in the second position.

9. The intravascular catheter device of claim 6 wherein: the embolic protection device comprises a mesh and an expandable hoop;

said mesh is attached to said tip member at a first end and said expandable hoop at a second end; and

said mesh surrounds an outer surface of each of the struts.

10. The intravascular catheter device of claim 6 wherein: the embolic protection device comprises a covering, apertures in said covering, and an expandable hoop;

said covering is attached to said tip member at a first end and said expandable hoop at a second end; and

said covering surrounds an outer surface of each of the struts.

11. The intravascular catheter device of claim 5 further comprising:

a tip member connected to said inner sleeve, wherein each of the struts are connected to the flexible catheter tube at a proximal end and are free at a distal end, and where said tip member is configured to ride along inner surfaces of each of said struts to force said struts to splay outward in said second position.

12. The intravascular catheter device of claim 1 further comprising:

a sheath configured for movement between a first position where the expandable portion is covered and a second position where the expandable portion is exposed.

13. The intravascular catheter device of claim 12 wherein: the struts are biased in the second position.

14. The intravascular catheter device of claim 1 wherein: said incising element is provided at a longitudinal mid-portion of said at least one of the struts; and

said embolic protection devices surrounds a distal portion of said expandable portion.

15. The intravascular catheter device of claim 14 wherein: said incising element extends outward in a radial manner from an outer surface of said at least one of the struts; and

15

a longitudinal axis of said incising element extends along a midline of the outer surface of said at least one of the struts.

16. The intravascular catheter device of claim **1** wherein: a footprint of the outer surface of the at least one of the struts is larger than a footprint of said incising element. 5

17. An intravascular catheter device comprising:

a handle assembly;

a flexible catheter tube extending from said handle assembly; 10

an inner sleeve configured for sliding movement within the flexible catheter tube;

an expandable portion secured to a distal end of said flexible catheter tube and comprising struts connected at a proximal end thereof to said flexible catheter tube and operable between a first position and a second position where the struts are moved outward from the first position, wherein a longitudinal axis of each of said struts extends in a linear fashion along a longitudinal axis of the expandable portion, and wherein each 15

16

of the struts are spaced apart from one another, at least when in the second position;

a tip member connected to the inner sleeve and each of the struts, wherein said expandable portion is moved between said first position and said second position by axial movement of said tip member by way of said inner sleeve;

an incising element provided at, and extending outward from, an outer surface of a proximal half of each of the struts, wherein each of said incising elements extend linearly and lengthwise along a midline of the outer surface of an associated one of the struts such that the outer surface of the associated one of the struts extends laterally beyond the incising element; and

an embolic protection device surrounding the outer surface of a distal half of the struts and comprising an expandable hoop located at a mid-portion of said expandable portion and a mesh extending between said expandable hoop and said tip member.

* * * * *