

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410588
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Nakajima; Hideki et al.

Hydraulic control system in working machine

Abstract

PROBLEM: To avoid the pressure of the actuator oil passage from becoming higher or equal to the upper limit pressure that is set depending on an individual option hydraulic actuator, during non-operation of an option operation lever, even if the actuator oil passage connected to the option hydraulic actuator is not provided with a variable relief valve. **SOLUTION:** It is configured to release the pressure of the actuator oil passage into the oil tank via the option control valve, the load pressure introducing oil passage, the variable relief valve, by switching the option control valve to load pressure relief positions at which the pressure of the actuator oil passage is allowed to flow into the load pressure introducing oil passage, when the pressure of the actuator oil passages exceeds the upper limit pressure during non-operation of the option operation lever; as well as by controlling the relief setting pressure of the variable relief valve connected to the load pressure introducing oil passage so as to be less than or equal to the upper limit pressure.

Inventors:	Nakajima; Hideki (Akashi, JP), Kiyasu; Koichi (Akashi, JP)
Applicant:	Caterpillar SARL (Geneva, CH)
Family ID:	84535869
Assignee:	Caterpillar SARL (Geneva, CH)
Appl. No.:	18/719959
Filed (or PCT Filed):	December 07, 2022
PCT No.:	PCT/EP2022/025555
PCT Pub. No.:	WO2023/110145
PCT Pub. Date:	June 22, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250052035 A1	Feb. 13, 2025

Foreign Application Priority Data

JP 2021-202417 Dec. 14, 2021

Publication Classification

Int. Cl.: E02F9/22 (20060101); E02F9/20 (20060101); F15B13/02 (20060101); F15B13/04 (20060101)

U.S. Cl.:

CPC E02F9/2203 (20130101); E02F9/2004 (20130101); E02F9/226 (20130101); E02F9/2292 (20130101); F15B13/026 (20130101); F15B13/0401 (20130101); E02F9/2285 (20130101); E02F9/2296 (20130101); F15B2211/526 (20130101)

Field of Classification Search

CPC: E02F (9/2225); E02F (9/226); E02F (9/2203); E02F (9/2292)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2021/0095443	12/2020	Fukuda	N/A	E02F 9/2232

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102016110310	12/2016	DE	B66F 17/003
3283696	12/2017	EP	E02F 9/2225
3283696	12/2018	EP	N/A
S09158903	12/1996	JP	N/A
2005249157	12/2004	JP	N/A
2010168738	12/2009	JP	N/A
2022120978	12/2021	JP	N/A
2021132514	12/2020	WO	N/A

OTHER PUBLICATIONS

International Search Report for related to Application No. PCT/EP2022/025555; reported on Mar. 24, 2023. cited by applicant

Primary Examiner: Teku; Abiy

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This Application is a 35 USC § 371 US National Stage filing of International Application No.

FIELD OF THE INVENTION

(2) The present invention relates to the technical field of hydraulic control systems in working machines such as hydraulic shovels.

BACKGROUND OF THE INVENTION

(3) Generally, among working machines such as hydraulic shovels, some are available, which a plurality of option hydraulic actuators is configured to be selectively attachable thereto. For example, in a hydraulic shovel, an option tool such as hydraulically driven breaker or crusher can be detachably attached, in place of a bucket for general purpose use as a working attachment.

(4) In case where a hydraulic circuit for an option hydraulic actuator that drives such an option tool intends to be provided in a hydraulic circuit for a working machine, a circuit that can be shared by a plurality of option hydraulic actuators is required, for the purpose of space-saving and reduction of the number of parts; on the other hand, a circuit capable of responding to the control of an individual option hydraulic actuator is also required. For example, in case where a fork bucket is mounted as an option hydraulic actuator, by setting the supply pressure to the fork cylinder that actuates the fork to be lower than the supply pressure to the bucket cylinder that actuates the bucket, the bucket can be actuated strongly, and the fork can be actuated softly. In this manner, it is required to create a circuit that can control the supply pressure to the option hydraulic actuator in correspondence with the working pressure of individual option hydraulic actuator.

(5) Thus, conventionally, there is known a technique that has enabled to arbitrarily change the supply pressure of an option hydraulic actuator depending on an individual hydraulic actuator, by disposing a relief valve respectively in a pair of actuator oil passages extending from the option control valve, which performs oil supply and discharge control to and from the option hydraulic actuator, to the option hydraulic actuator, and controlling the supply pressure to the option hydraulic actuator in accordance with the setting pressure of the relief valve; as well as by using a variable relief valve capable of changing the setting pressure in response to control signals from the control device as a relief valve (for example, refer to Patent Literature 1).

PRIOR ART DOCUMENTS

Patent Documents

(6) PATENT DOCUMENT 1: Japanese Patent Application Laid-Open No. 2010-168738.

SUMMARY OF THE INVENTION

Problems to be Solved by the Invention

(7) However, the hydraulic control system disclosed in the Patent Literature 1 requires a pair of variable relief valves disposed in a pair of actuator oil passages respectively, upon controlling a supply pressure to an option hydraulic actuator so as to be a pressure corresponding to a working pressure of an individual option hydraulic actuator, which hinders reduction of the number of parts and cost reduction. Thus, there may be studied a circuit capable of controlling the supply pressure corresponding to individual option hydraulic actuator, even if the pair of variable relief valves is omitted; but in this case, if the variable relief valves are omitted, even when a pressure in the actuator oil passage is increased due to external force or gravity, etc. while the option operation lever is not operated, that is, while oil supply and discharge to and from the option hydraulic actuator is not performed, the pressure that is set corresponding to the individual option hydraulic actuator cannot be released via the variable relief valves, and therefore there arises a problem that an overload might be applied to the option hydraulic actuator, and here there are problems to be solved by the present invention.

Means for Solving the Problem

(8) The present invention has been created with an object of solving these problems in view of the above circumstances, and a Claim 1 of the present invention provides a hydraulic control system in a working machine equipped with an option control circuit that is shared for a plurality of option

hydraulic actuators that is selectively mounted in the working machine, the option control circuit further comprising: option control valves for performing oil supply and discharge control to and from the option hydraulic actuators; a pair of actuator oil passages that connect the option control valve and the option hydraulic actuator; a pressure detecting means for detecting pressures of the actuator oil passages; a pressure compensating valve which is disposed on an upstream-side of the option control valve and is actuated in order to maintain a differential pressure, by an inlet-side pressure and an outlet-side pressure of the option control valve being introduced, between the introduced inlet-side pressure and outlet-side pressure at a predetermined pressure; a control device for controlling an actuation of the option control valves; as well as wherein the option control circuit is configured such that, by connecting a variable relief valve capable of varying a relief setting pressure in response to control signals from the control device, to a load pressure introducing oil passage that introduces the outlet-side pressure of the option control valves to the pressure compensating valve, and lowering a pressure of the load pressure introducing oil passage down to a relief setting pressure by the variable relief valve and introducing the pressure to the pressure compensating valve, the pressure of the inlet-side of the option control valves can be variably controlled in accordance with change of the relief setting pressure of the variable relief valve; on the other hand, wherein the option control circuit is configured such that, by providing a load pressure relief position at which oil supply and discharge to and from the option hydraulic actuators is not performed, but the pressure of the actuator oil passage is allowed to flow into the load pressure introducing oil passage, in a switching position of the option control valves, and by switching the option control valve to the load pressure relief position, when the pressure in the actuator oil passage exceeds the upper limit pressure that is preset depending on individual optional hydraulic actuator during non-operation of an option operation lever; as well as by controlling the relief setting pressure of the variable relief valve so as to be less than or equal to the upper limit pressure, the pressure in the actuator oil passage exceeding the upper limit pressure is released to an oil tank via the optional control valve, the load pressure introducing oil passage, and the variable relief valve.

(9) The invention of Claim 2 provides the hydraulic control system in the working machine according to the Claim 1, wherein the hydraulic control system in the working machine comprises first, second hydraulic pumps serving as hydraulic supply sources for other hydraulic actuators to be provided in the working machine other than the option hydraulic actuators, wherein the option hydraulic actuator uses either one or both of these first, second hydraulic pumps as the hydraulic supply sources; as well as wherein the option control circuit comprises first, second option supply oil passages connected to the first, second hydraulic pumps respectively, and an option merging oil passage that allows these first, second option supply oil passages to be merged thereinto, wherein the pressure compensating valve and the option control valve are disposed in the option merging oil passage.

(10) The invention of Claim 3 provides the hydraulic control system in the working machine according to the Claim 2, wherein the hydraulic control system in the working machine is configured to comprise first, second bleed valves for controlling a bleed flow rate that flows into an oil tank from the first, second hydraulic pumps in response to control signals output from the control device, and to control discharge pressures of the first, second hydraulic pumps in accordance with bleed flow rate control by the first, second bleed valves; as well as the control device performs bleed flow rate control so that, in case where the option hydraulic actuator uses either one of these first, second hydraulic pumps as the hydraulic supply source, the discharge pressure of one hydraulic pump serving as the hydraulic supply source will be set higher than discharge pressure of another hydraulic pump not serving as the hydraulic supply source; when the option hydraulic actuator uses both the first, second hydraulic pumps as the hydraulic supply sources, the discharge pressures of the first, second hydraulic pumps will be equalized.

Favorable Effects of the Invention

(11) According to the invention of Claim 1, the upper limit pressure of supply pressurized oil to the optional hydraulic actuator can be variably controlled so as to become a pressure corresponding to individual option hydraulic actuator without installing a variable relief valve in a pair of actuator oil passages respectively; as well as the pressure in the actuator oil passage during non-operation of the option operation lever can be controlled so as not to exceed the upper limit pressure set depending on individual option hydraulic actuator.

(12) According to the invention of Claim 2, even if the option hydraulic actuator uses or relies on only the first hydraulic pump, or only the second hydraulic pump, or both the hydraulic pumps as hydraulic supply source, whichever the case may be, oil supply and discharge control to and from the option hydraulic actuator can be performed by only one option control valve disposed in the option merging oil passage, thereby enabling contribution to a reduction in the number of parts.

(13) According to the invention of Claim 3, the option hydraulic actuator uses or relies on either one of the first, second hydraulic pumps as hydraulic supply source, without separately providing valves for opening and closing the first and second option supply oil passages. Even if both hydraulic pumps are used as hydraulic supply sources, only the supply pressurized oil from the hydraulic pump serving as the hydraulic supply source can be supplied to the option merging oil passage, thereby achieving reduction of the number of parts and cost reduction.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a side view of a hydraulic shovel.

(2) FIG. 2 is a hydraulic circuit diagram of a hydraulic shovel.

(3) FIG. 3 is an enlarged view of an option control circuit associated with an option hydraulic actuator.

(4) FIG. 4(A) is a diagram illustrating a relationship between travel strokes of spool of an option control valve positioned at first, second load pressure relief positions; first, second actuation positions and opening areas of a supply valve passage, a discharge valve passage, a load pressure valve passage. FIG. 4(B) is a diagram illustrating opening area characteristics of a switching valve.

(5) FIG. 5 is a block diagram illustrating the configuration of a controller.

(6) FIG. 6 is a control block diagram of first, second operation amounts setting unit.

(7) FIGS. 7(A), 7(B), 7(C) are diagrams each illustrating the relationship between operation amount of operation lever and required flow rate.

(8) FIG. 8 is a control block diagram of required flow rate setting unit and a pump control unit.

(9) FIG. 9 is a control block diagram of a valve opening area control unit.

(10) FIG. 10 is a control block diagram of a bleed control unit.

(11) FIG. 11 is a control block diagram of first, second pump target pressure setting in the bleed control unit.

(12) FIG. 12 is a flowchart illustrating a control procedure for load pressure relief control.

DETAILED DESCRIPTION OF THE INVENTION

(13) Hereinbelow, embodiments of the present invention will be discussed with reference to the drawings.

(14) FIG. 1 is a view illustrating a hydraulic shovel 1 which is an example of a working machine provided with a hydraulic control system of the present invention. The hydraulic shovel 1 is constituted of a lower traveling structure 2 of crawler type; an upper slewing structure 3 that is supported so as to slew freely above the lower traveling structure 2; and a working implement 4 that is mounted on the upper slewing structure 3, and other parts. Further the working implement 4 is constituted of a boom 5 whose base end portion is supported so as to swing freely upwardly and downwardly on the upper slewing structure 3; a stick 6 that is supported so as to swing freely

backwardly and forwardly at the tip end portion of the boom **5**; a bucket **7** that is attached so as to swing freely to the tip end portion of the stick **6**, and others; as well as the hydraulic shovel **1** is equipped with various types of hydraulic actuators including a boom cylinder **8**, a stick cylinder **9**, a bucket cylinder **10** for causing the boom **5**, the stick **6**, the bucket **7** to swing, respectively, and left and right traveling motors (not illustrated) for causing the lower traveling structure **2** to travel, a slewing motor **11** (illustrated in FIG. **2**) for causing the upper slewing structure **3** to slew. Furthermore, the hydraulic shovel **1** is adapted such that various hydraulically operated option tools (option attachments) including breaker, a crusher, a grapple, a tilt bucket, a rotary cutting attachment (all not illustrated) can be mounted selectively in place of the bucket **7**, depending on their work contents. If an option tool is mounted, the bucket cylinder **10** operates as a hydraulic cylinder for causing the option tool to swing with respect to the stick **6**.

(15) Next, a hydraulic control system provided in the hydraulic shovel **1** will be discussed with reference to the hydraulic circuit diagram illustrated in FIG. **2**. In FIG. **2**, the hydraulic circuit of the portion relating to the traveling motor is omitted.

(16) In FIG. **2**, reference symbols A, B denote a first, a second hydraulic pumps of variable displacement type; Aa, Ba denote a displacement varying means for varying the displacements of the first, second hydraulic pumps A, B; and reference numeral **12** denotes an oil tank. **8**, **9**, **10**, **11** denote the boom cylinder, the stick cylinder, the bucket cylinder, the slewing motor, which are hydraulic actuators permanently mounted in the hydraulic shovel **1**. Further, **13** denotes an option hydraulic actuator, and the option hydraulic actuator **13** is a hydraulic actuator equipped in the option tool in order to drive the option tool that is selectively mounted to the hydraulic shovel **1**; for example, a breaker hydraulic actuator (hereinafter simply referred to as a breaker) when the breaker is mounted as an option tool, and a grapple hydraulic actuator when a grapple is mounted. In the present embodiment, the boom cylinder **8** and the stick cylinder **9** are configured to use both the first, second hydraulic pumps A, B as hydraulic supply sources; the bucket cylinder **10** to use the first hydraulic pump A as a hydraulic supply source; and the slewing motor **11** to use the second hydraulic pump B as a hydraulic supply source. Further, the option hydraulic actuator **13** as described below, is configured to use either one or both of the first, second hydraulic pumps A, B as a hydraulic supply source, depending on the flow rate required by the option hydraulic actuator **13** and on whether the option hydraulic actuator **13** performs independent operation or combined operation (simultaneous operation) with the other hydraulic actuators. In the present embodiment, the boom cylinder **8**, the stick cylinder **9**, the bucket cylinder **10**, and the slewing motor **11** correspond to the other hydraulic actuators of the present invention.

(17) Moreover, in FIG. **2**, reference symbol C denotes a first pump line connected to the discharge side of the first hydraulic pump A; and a first boom supply oil passage **14**, a first bucket supply oil passage **15**, a first stick supply oil passage **16**, and a first option supply oil passage **17** are connected to the first pump line C in a state where they are parallel with each other. D denotes a second pump line connected to the discharge side of the second hydraulic pump B, and a second boom supply oil passage **18**, a second stick supply oil passage **19**, a second slewing supply oil passage **20**, and a second option supply oil passage **21** are connected to the second pump line D in a state where they are parallel with each other. The first, second boom supply oil passages **14**, **18** are oil passages connecting respectively the first, second hydraulic pumps A, B to a boom control valve **23** described below. The first bucket supply oil passage **15** is an oil passage connecting the first hydraulic pump A to a bucket control valve **25**. The first, second stick supply oil passages **16**, **19** are oil passages connecting the first, second hydraulic pumps A, B to a stick control valve **24**. The second slewing supply oil passage **20** is an oil passage connecting the second hydraulic pump B to a slewing control valve **26**. The first, second option supply oil passages **17**, **21** are oil passages connecting respectively the first, second hydraulic pumps A, B to an option merging oil passage **22** described below.

(18) A boom flow rate control valve **31** for controlling the supply flow rate from the second

hydraulic pump B to the boom control valve **23** is disposed in the second boom supply oil passage **18**; and a first, a second stick flow rate control valves **32**, **33** for controlling the supply flow rates from the first, second hydraulic pumps A, B to the stick control valve **24** are disposed in the first, second stick oil supply passages **16**, **19**. The boom flow rate control valve **31**, the first, second stick flow rate control valves **32**, **33** serve as poppet valves that perform flow rate control by being pilot-operated by a boom flow rate control solenoid proportional valve **41**; first, second stick flow rate control solenoid proportional valves **42**, **43** (all illustrated in FIGS. 5 and 9) that are actuated in response to control signals output from a controller **30**, and have a backflow prevention function, thereby enabling adaption to allow for the flow of oil from the first, second hydraulic pumps A, B to the boom control valve **23**, the stick control valve **24**, but to block off the backflow.

(19) On the other hand, in the first boom supply oil passage **14**, the first bucket supply oil passage **15**, the second slewing supply oil passage **20**, the first, second option supply oil passages **17**, **21**, there are disposed no flow rate control valves like the boom flow rate control valve **31**, the first, second stick flow rate control valves **32**, **33** described above; and pressurized oil from the first hydraulic pump A or the second hydraulic pump B via the first boom supply oil passage **14**, the first bucket supply oil passage **15**, the second slewing supply oil passage **20**, the first, second option supply oil passages **17**, **21** is supplied directly to the boom control valve **23**, the bucket control valve **25**, the slewing control valve **26**, the option merging oil passage **22** without the flow rate being controlled. A check valve **34** is disposed in each of the first boom supply oil passage **14**, the first bucket supply oil passage **15**, the second slewing supply oil passage **20**, the first, second option supply oil passages **17**, **21**, and is adapted to allow for the flow of oil from the first, second hydraulic pumps A, B into the boom control valve **23**, the bucket control valve **25**, the slewing control valve **26**, the option merging oil passage **22**, but to block off the backflow.

(20) Thus, pressurized oil from the first hydraulic pump A via the first boom supply oil passage **14**, and pressurized oil from the second hydraulic pump B via the second boom supply oil passage **18** can be supplied to a pump port **23p** of the boom control valve **23**; as well as the pressurized oil from the second hydraulic pump B will be supplied to the boom control valve **23** in a state where (including the shut-off state) its flow rate is controlled by the boom flow rate control valve **31** disposed in the second boom supply oil passage **18**. Also, the pressurized oil from the first hydraulic pump A via the first stick supply oil passage **16** and the pressurized oil from the second hydraulic pump B via the second stick supply oil passage **19** can be supplied to the pump port **24p** of the stick control valve **24**; as well as the pressurized oil from the first, second hydraulic pumps A, B will be supplied to the stick control valve **24** in a state where (including the shut-off state) its flow rate is controlled by the first, second stick flow rate control valves **32**, **33** disposed respectively in the first, second stick supply oil passages **16**, **19**.

(21) The boom, the stick, the bucket, the slewing control valves **23** to **26**, which are spool valves of closed center type that control the supply and discharge flow rate to and from the boom cylinder **8**, the stick cylinder **9**, the bucket cylinder **10**, the slewing motor **11** as well as switches between the supply/discharge directions, includes a pair of pilot ports **23a**, **23b** to **26a**, **26b**, connected respectively to a boom, a stick, a bucket, a slewing solenoid proportional valves **44a**, **44b** to **47a**, **47b** (illustrated in FIGS. 5 and 9) that outputs a pilot pressure in response to control signals from the controller **30**; supply valve passages **23c** to **26c** that allow for the supply of pressurized oil from the first or/and second hydraulic pumps A, B to the boom cylinder **8**, the stick cylinder **9**, the bucket cylinder **10**, the slewing motor **11**; discharge valve passages **23d** to **26d** that allow for the flow of discharged oil from the boom cylinder **8**, the stick cylinder **9**, the bucket cylinder **10**, the slewing motor **11** into a tank line T extending to the oil tank **12**. The boom, stick, the bucket, the slewing control valves **23** to **26** are configured to be positioned at a neutral position N where to close the supply valve passages **23c** to **26c** and the discharge valve passages **23d** to **26d** and not to perform supply and discharge control to and from corresponding hydraulic actuators (the boom cylinder **8**, the stick cylinder **9**, the bucket cylinder **10**, the slewing motor **11**) in a state where a

pilot pressure is not input to both the pilot ports **23a**, **23b** to **26a**, **26b**, but to be switched to an actuation position X or Y where to open the supply valve passages **23c** to **26c** and the discharge valve passages **23d** to **26d**, to perform the supply and discharge control to and from the hydraulic actuators, by a pilot pressure being input to one or another pilot ports **23a**, **23b** to **26a**, **26b**. Then, the opening areas of the supply valve passages **23c** to **26c** and the discharge valve passages **23d** to **26d** when positioned at the actuation position X or Y is controlled to increase or decrease depending on a travel stroke of spool associated with an increase or decrease of a pilot pressure output from the boom, the stick, the bucket, the slewing solenoid proportional valves **44a**, **44b** to **47a**, **47b** to the pilot ports **23a**, **23b** to **26a**, **26b** of the boom, the stick, the bucket, the slewing control valves **23** to **26**.

(22) Then, the supply flow rate and discharge flow rate to and from the bucket cylinder **10**, the slewing motor **11** are controlled in accordance with an opening area of the supply valve passages **25c**, **26c**, the discharge valve passages **25d**, **26d** of the bucket, the slewing control valves **25**, **26**.

(23) Further, the supply flow rate to the boom cylinder **8** is controlled in accordance with an opening area of the supply valve passage **23c** of the boom control valve **23**, regarding the supply flow rate from the first hydraulic pump A via the first boom supply oil passage **14** provided with no flow rate control valve; on the other hand, regarding the supply flow rate from the second hydraulic pump B via the second boom supply oil passage **18** provided with the boom flow rate control valve **31**, the supply flow rate to the boom cylinder **8** becomes “zero” in a state where the boom flow rate control valve **31** is closed, and in a state where the boom flow rate control valve **31** is open, the supply flow rate to the boom cylinder **8** is controlled in accordance with an opening area of the boom flow rate control valve **31** and an opening area of the supply valve passage **23c** of the boom control valve **23**. On the other hand, the discharge flow rate from the boom cylinder **8** is controlled in accordance with an opening area of the discharge valve passage **23d** of the boom control valve **23**.

(24) Also, the supply flow rate to the stick cylinder **9**, regarding the supply flow rate from the first hydraulic pump A via the first stick supply oil passage **16** provided with the first stick flow rate control valve **32**, becomes “zero” in a state where the first stick flow rate control valve **32** is closed; and is controlled in accordance with an opening area of the first stick flow rate control valve **32** and an opening area of the supply valve passage **24c** of the stick control valve **24** in a state where the first stick flow rate control valve **32** is open; on the other hand, regarding the supply flow rate from the second hydraulic pump B via the second stick supply oil passage **19** provided with the second stick flow rate control valve **33**, the supply flow rate to the stick cylinder **9** becomes “zero” in a state where the second stick flow rate control valve **33** is closed, and in a state where the second stick flow rate control valve **33** is open, and is controlled in accordance with an opening area of the second stick flow rate control valve **33**, and an opening area of the supply valve passage **24c** of the stick control valve **24**. On the other hand, the discharge flow rate from the stick cylinder **9** will be controlled in accordance with an opening area of the discharge valve passage **24d** of the stick control valve **24**.

(25) On the other hand, the option merging oil passage **22** serves as an oil passage formed by the downstream side of the first option supply oil passage **17** connected to the first hydraulic pump A and the downstream side of the second option supply oil passage **21** connected to the second hydraulic pump B being merged thereinto, and in the option merging oil passage **22**, there are disposed an option control valve **60** described below and a compensator valve **61** (which corresponds to the pressure compensating valve of the present invention) located on the upstream-side of the option control valve **60**.

(26) The option control valve **60**, which is a spool valve of closed center type that controls the supply and discharge flow rate to and from the option hydraulic actuator **13** as well as switches between the supply and discharge directions, as illustrated in the enlarged hydraulic circuit diagram of FIG. 3, includes first, second pilot ports **60a**, **60b** respectively connected to first, second option

solenoid proportional valves **48a**, **48b** (illustrated in FIGS. 5 and 9) that output pilot pressure in response to control signals output from the controller **30**; a pump port **60p** connected to the option merging oil passage **22**; a tank port **60t** connected to the tank line T; a first actuator port **60c** connected via a first hydraulic actuator oil passage **67** to one port **13a** of the option hydraulic actuator **13**; a second actuator port **60d** connected via a second hydraulic actuator oil passage **68** to another port **13b** of the option hydraulic actuator **13**; and a load pressure output port **60e** connected to a second pilot port **61b** of the compensator valve **61** described below via a load pressure introducing oil passage **62**. Then, the option control valve **60**, is configured, in a state where no pilot pressure is being input to both the first, second pilot ports **60a**, **60b**, to be positioned at the neutral position N where to close the pump port **60p**, the first and second actuator ports **60c**, **60d**, not to perform the supply and discharge control to and from the option hydraulic actuator **13**, and to cause the load pressure output port **60e** to communicate with the tank port **60t**; but by a pilot pressure being input to the first pilot port **60a**, causing the spool to be moved in one direction, to be positioned at a first load pressure relief position R1 or a first actuation position X, and by a pilot pressure being input to the second pilot port **60b**, causing the spool to be moved in another direction, to be positioned at a second first load pressure relief position R2 or a second actuation position Y. The first, second hydraulic actuator oil passage **67**, **68** are oil passages that connects the option control valve **60** and the option hydraulic actuator **13**, which correspond to an actuator oil passage of the present invention.

(27) The first, second actuation positions X, Y of the option control valve **60** are regions where a travel stroke of spool from the neutral position N is greater than that of the first, second load pressure relief positions R1, R2 (regions where the pilot pressure to be input to the first, second pilot ports **60a** and **60b** is greater than that of the first, second load pressure relief positions R1, R2), and the option control valve **60** is configured, at the first operating position X, to open a supply valve passage **60f** extending from the pump port **60p** to the first actuator port **60c**; a discharge valve passage **60g** extending from the second actuator port **60d** to the tank port **60t**; and a load pressure valve passage **60h** extending from the first actuator port **60c** to the load pressure output port **60e**; and at the second operating position Y, to open a supply valve passage **60f** extending from the pump port **60p** to the second actuator port **60d**; a discharge valve passage **60g** extending from the first actuator port **60c** to the tank port **60t**; and a load pressure valve passage **60h** extending from the second actuator port **60d** to the load pressure output port **60e**. Then, the opening areas of the supply valve passage **60f** and the discharge valve passage **60g** are adapted to be controlled to increase or decrease in proportion to the travel stroke of the spool moved by the pilot pressure output from first, second option solenoid proportional valves **48a**, **48b**; as well as the supply flow rate, discharge flow rate to and from the option hydraulic actuator **13** are adapted to be controlled in accordance with the opening areas of the supply valve passage **60f**, the discharge valve passage **60g**, respectively. Further, the option control valve **60** at the first, second operating positions X, Y is adapted such that, by the load pressure valve passage **60h** being opened, the outlet-side pressure of the option control valve **60** (the load pressure of the option hydraulic actuator **13**, the pressure of the first or second hydraulic actuator oil passages **67**, **68** supplied with pressurized oil from the supply valve passage **60f**) is introduced into the load pressure introducing oil passage **62**.

(28) On the other hand, the first, second load pressure relief positions R1, R2 of the option control valve **60** are regions where the travel stroke of spool from the neutral position N is smaller than that of the first, second actuation positions X, Y (regions where pilot pressures input to the first, second pilot ports **60a**, **60b** are smaller than pressures at the first, second operating positions X, Y). The option control valve **60** is adapted, on the other hand, at the first load pressure relief position R1, to close the pump port **60p**, the tank port **60t** and the second actuator port **60d**, to open the load pressure valve passage **60h** extending from the first actuator port **60c** to the load pressure output port **60e**; and at the second load pressure relief position R2, to close the pump port **60p**, the tank

port **60t** and the first actuator port **60c**; on the other hand, to open the load pressure valve passage **60h** extending from the second actuator port **60d** to the load pressure output port **60e**. In other words, when the option control valve **60** is positioned at the first, second load pressure relief positions **R1**, **R2**, the supply valve passage **60f** (valve passage extending from the pump port **60p** to first or second actuator ports **60c**, **60d**) for supplying pressurized oil from the first, second hydraulic pumps **A**, **B** via the option merging oil passage **22** to the option hydraulic actuator **13**, and the flow discharge valve passage **60g** (valve passage extending from the second or first actuators **60d**, **60c** to the tank port **60t**) for causing discharged oil from the option hydraulic actuator **13** to flow into oil tank **12** are closed, and the option control valve **60** does not perform oil supply and discharge to and from the option hydraulic actuator **13**, but is adapted to enable pressurized oil of the first or second hydraulic actuator oil passages **67**, **68** to flow into the load pressure introducing oil passage **62**, by opening the load pressure valve passage **60h** extending from the first or second actuator ports **60c**, **60d** to the load pressure output port **60e**.

(29) Now, FIG. 4(A) illustrates one example of relationship between travel stroke of spool when the option control valve **60** is positioned at the first or second load pressure relief positions **R1**, **R2**, the first or second operating positions **X**, **Y**, and opening area of the supply valve passage **60f**, the discharge valve passage **60g**, the load pressure valve passage **60h**. As illustrated in FIG. 4(A), when positioned at the first or second load pressure relief positions **R1**, **R2**, the supply valve passage **60f** and the discharge valve passage **60g** are closed; as well as the load pressure valve passage **60h** is adapted to be opened by the travel stroke of spool exceeding a dead zone. On the other hand, when the first or second operating position **X**, **Y** is reached, the supply valve passage **60f** and the discharge valve passage **60g** are opened, and its opening area is adapted to increase with an increase of the travel stroke of spool. Further, the load pressure valve passage **60h** when positioned at the first or second actuation positions **X**, **Y** is adapted to maintain an opening area opened at the first or second load pressure relief positions **R1**, **R2**, but the opening area is smaller compared to a maximum opening area of the supply valve passage **60f**, the discharge valve passage **60g**.

(30) By the way, as the option hydraulic actuator **13**, there are various kinds including ones whose pressurized oil supply direction is one direction like a one-direction rotary motor or a single-acting cylinder (e.g. breakers), ones whose pressurized oil supply direction is bi-direction like a bi-directional rotary motor or a double-acting cylinder (e.g. crushers), ones requiring a large flow rate (e.g. large-sized breakers and crushers), and ones requiring only a small flow rate (e.g. small-sized breakers and crushers), and the option control valve **60** shares the use of the option hydraulic actuator **13** available in various types. In other words, switching the option control valve **60** between the first actuation position **X** and the second actuation position **Y** enables performing bi-directional supply of pressurized oil to the option hydraulic actuator **13**; and using only either one actuation position of the first actuation positions **X** and the second actuation positions **Y** enables performing one-directional supply of pressurized oil; but in the present embodiment, the use of the first actuation positions **X** is set, in case of performing one-directional supply of pressurized oil.

(31) On the other hand, the load pressure introducing oil passage **62** serves as an oil passage extending from the load pressure output port **60e** of the option control valve **60** to the second pilot port **61b** of the compensator valve **61**. In the load pressure introducing oil passage **62** is disposed a first throttle **63**; as well as a load pressure relief oil passage **66** extending to the tank line **T** via a second throttle **64** and a variable relief valve **65** is branched and formed from the load pressure introducing oil passage **62** extending from the load pressure output port **60e** of the option control valve **60** to the first throttle **63**. The variable relief valve **65** serve as a solenoid proportional relief valve capable of changing a relief setting pressure **LP** in response to control signals from the controller **30**, and is adapted to lower a load pressure to be input to the second pilot port **61b** of the compensator valve **61** down to the relief setting pressure **LP**, by a load pressure that has been introduced into the load pressure introducing oil passage **62** being released into the oil tank **12** via the variable relief valve **65**, in case where the relief setting pressure **LP** of the variable relief valve

65 is lower than a load pressure of the option hydraulic actuator **13** to be introduced into the load pressure introducing oil passage **62**.

(32) The compensator valve **61** includes a first pilot port **61a** to which a first pilot pressure that presses the valve body of the compensator valve **61** to a closed side is input; and a second pilot port **61b** to which a second pilot pressure that presses the valve body to an open side is input; and a spring **61c** that presses to the open side, and an opening area is controlled such that a differential pressure between the first pilot pressure and the second pilot pressure is held at a predetermined pressure K that is determined by the spring **61c**. Then, the first pilot port **61a** of the compensator valve **61** is connected to an option merging oil passage **22** on the inlet-side of the option control valve **60**, and a pressure of the option merging oil passage **22** is input thereto. Further, the second pilot port **61b** is connected to the load pressure introducing oil passage **62**, and when a load pressure of the option hydraulic actuator **13** is less than or equal to the relief setting pressure LP of the variable relief valve **65**, the load pressure of the option hydraulic actuator **13** is adapted to be input; on the other hand, the load pressure of the option hydraulic actuator **13** is higher than the relief setting pressure LP , a load pressure reduced to the relief setting pressure LP as described above is adapted to be input. Thus, when a load pressure of the option hydraulic actuator **13** is less than or equal to the relief setting pressure LP , in a state where the option control valve **60** is positioned at the first, second actuation positions, positioned at the first, second actuation positions X , Y , and oil supply and discharge to and from the option hydraulic actuator **13** is performed, a pressure PO of the option merging oil passage **22** is controlled so as to be higher than the load pressure of the option hydraulic actuator **13** by the predetermined pressure K due to the action of the compensator valve **61**; on the other hand, when the load pressure of the option hydraulic actuator **13** is higher than the relief setting pressure LP , the pressure PO of the option merging oil passage **22** is controlled so as to be higher than the relief setting pressure LP by the predetermined pressure K . Accordingly, by variably controlling the relief setting pressure LP of the variable relief valve **65** in response to control signals from the controller **30**, the pressure PO of the option merging oil passage **22** on the inlet-side of the option control valve **60** can be controlled so as to be a pressure less than or equal to $(LP+K)(PO \leq (LP+K))$, which is higher than the relief setting pressure LP by the predetermined pressure K .

(33) On the other hand, in a state where the option control valve **60** is positioned at the first, second load pressure relief positions $R1$, $R2$, the supply valve passage **60f** and the discharge valve passage **60g** are closed, as described above; on the other side, the load pressure valve passage **60h** for introducing the load pressure of first, the second hydraulic actuator oil passages **67**, **68** to the load pressure introducing oil passage **62** is open. Then, when the pressure in the first, second hydraulic actuator oil passages **67**, **68** introduced into the load pressure introducing oil passage **62** is higher than the relief setting pressure LP of the variable relief valve **65**, the pressurized oil in the first, second hydraulic actuator oil passages **67**, **68** flows into the oil tank **12** via the load pressure introducing oil passage **62** and the variable relief valve **65** from the load pressure valve passage **60h**. Consequently, in a state where the option control valve **60** is positioned at the first, second load pressure relief positions $R1$, $R2$, it is configured such that the pressure in the first, second hydraulic actuator oil passages **67**, **68** can be reduced to the relief setting pressure LP of the variable relief valve **65**.

(34) Moreover, first, second option relief oil passages **71**, **72** extending into the tank line T via first, second option relief valves **69**, **70** are branched and formed from the first, second hydraulic actuator oil passages **67**, **68**. The first, second option relief valves **69**, **70** are actuated so as to release high pressurized oil to the oil tank **12** when the first, second hydraulic actuator oil passages **67**, **68** become high pressure due to dynamic pressure fluctuations such as when a surge pressure is generated due to an external force like a collision, but a relief setting pressure of the first, second option relief valves **69**, **70** is set to a driving pressure of the highest pressure among the driving pressures of the option hydraulic actuator **13** selectively mounted to the hydraulic shovel **1**. The

first, second option relief valves **69, 70** use inexpensive ones that cannot change electrically their relief setting pressure. In addition, the relief valves similar to the first, second option relief valves **69, 70** are provided also in oil passages that connects the boom control valve **23**, the stick control valve **24**, the bucket control valve **25**, the slewing control valve **26**, and the boom cylinder **8**, the stick cylinder **9**, the bucket cylinder **10**, the slewing motor **11** respectively, but they are omitted in FIG. 2.

(35) Moreover, in FIGS. 2 and 3, reference numeral **73** denotes a bypass oil passage that is branched and formed from the first or second hydraulic actuator oil passages **67, 68** extending into the oil tank **12**. In a bypass oil passage **73** is disposed a switching valve **74**. The switching valve **74**, as illustrated in FIG. 4(B), is a two-position switching valve that is turned into ON/OFF by an applied voltage from the controller **30** and switched to a closed position N, and an open position X; and switching the switching valve **74** to the open position X is adapted to enable discharged oil from the option hydraulic actuator **13** to flow directly into the oil tank **12** without passing through the discharge valve passage **60g** of the option control valve **60**. Then, when there is mounted an option hydraulic actuator **13** which requires back pressure reduction and has pressurized oil supply direction in one direction like a breaker for example, the back pressure exerted on the option hydraulic actuator **13** is adapted to be reliably reduced by opening the switching valve **74** (switching to the open position X) and allowing the discharged oil from the option hydraulic actuator **13** to flow into the oil tank **12** from the bypass oil passage **73**. In addition, the switching valve **74** is an inexpensive one that is switched by ON/OFF as described above, and therefore it is adapted to enable performing the back pressure reduction control at a low cost compared to the case of using the variable relief valve, for example. In addition, when there is mounted an option hydraulic actuator **13** having pressurized oil supply direction in one direction and requiring the back pressure reduction, the bypass oil passage **73** is branched and formed from an actuator oil passage serving as a return oil passage from the option hydraulic actuator **13**. In the present embodiment, the bypass oil passage **73** is branched and formed from a second hydraulic actuator oil passage **68**; but when a first hydraulic actuator oil passage **67** serves as the return oil passage from the option hydraulic actuator **13**, the bypass oil passage **73** is branched and formed from the first hydraulic actuator oil passage **67**.

(36) Moreover, in FIG. 2, E, F denote first, second bleed lines branched and formed respectively from upstream-side positions of all the supply oil passages **14** to **21** connected to the first, second pump lines C, D, extending into the tank line T. In a first, a second bleed valves **75, 76** are disposed the first, second bleed lines E, F respectively. These first, second bleed valves **75, 76** are actuated by a pilot pressure output from first, second bleed solenoid proportional valves **49a, 49b** (illustrated in FIGS. 5 and 10) to increase or decrease the opening area, and thereby being adapted to control so as to increase or decrease a bleed flow rate flowing from the first, second hydraulic pumps A, B via the first, second bleed lines E, F into the oil tank **12**. Then, the pressure of the first, second pump lines C, D (discharge pressures of the first, second hydraulic pumps A, B) is adapted to be controlled by the bleed flow rate control by the first, second bleed valves **75, 76**.

(37) Moreover, in FIG. 2, **77** denotes a valve block in which are incorporated various types of valves for performing oil supply and discharge control to and from the above-described various types of hydraulic actuators (the boom cylinder **8**, the stick cylinder **9**, the bucket cylinder **10**, the slewing motor **11**, the option hydraulic actuator **13**). The valve block **77** is formed by an option valve block **77Y** incorporating therein various types of valves for controlling the option hydraulic actuator (the option control valve **60**, the compensator valve **61**, the variable relief valve **65**, the first, second option relief valves **69, 70**, etc.) being assembled integrally to the main valve block **77X** incorporating therein various types of valves for controlling permanently provide hydraulic actuators (the boom, the stick, the bucket, the slewing control valves **23** to **26**, the boom, the first, the second stick flow rate control valves **31** to **33**, etc.) and the first, second bleed valves **75, 76**, etc. The bypass oil passage **73** and a switching valve **74** are provided outside the valve block **77**.

(38) On the other hand, the controller **30** (corresponding to a control means of the present invention), as illustrated in the block diagram of FIG. 5, is configured such that, to its input-side are connected a boom operation detecting means **80**, a stick operation detecting means **81**, a bucket operation detecting means **82**, a slewing operation detecting means **83**, an option operation detecting means **84** for detecting an operation direction and an operation amount of a boom operation lever, a stick operation lever, a bucket operation lever, a slewing operation lever, an option operation lever (all not illustrated) respectively; an option hydraulic actuator notifying means **85** described below; pressure sensors (not illustrated) for detecting pump pressures of the first, second hydraulic pumps A, B; pressure sensors (all not illustrated) for detecting load pressures of the boom cylinder **8**, the stick cylinder **9**, the bucket cylinder **10**, the slewing motor **11** respectively; a first, a second option pressure sensors (equivalent to a pressure detecting means for detecting the pressure of the actuator oil passage of the present invention) **97**, **98** for detecting the load pressure of the option hydraulic actuator **13** (pressures of the first, second actuator oil passages **67**, **68**), etc.; and to its output-side are connected the displacement varying means Aa, Ba of the first, second hydraulic pumps A, B; the boom flow rate control solenoid proportional valve **41** for outputting a pilot pressure to the boom flow rate control valve **31**; the first, second stick flow rate control solenoid proportional valves **42**, **43** for outputting a pilot pressure to the first, second stick flow rate control valves **32**, **33** respectively; the boom, the stick, the bucket, the slewing solenoid proportional valves **44a**, **44b** to **47a**, **47b** for outputting a pilot pressure to the boom, the stick, the bucket, the slewing control valves **23** to **26** respectively; first, second option solenoid proportional valves **48a**, **48b** for outputting a pilot pressure to the option control valve **60**; first, second bleed solenoid proportional valves **49a**, **49b** for outputting a pilot pressure to the first, second bleed valves **75**, **76**; the variable relief valve **65**; the switching valve **74**, etc.; as well as discharge flow rate control for the first, second hydraulic pumps A, B; bleed flow rate control for the first, second bleed lines E, F; oil supply and discharge control to and from the boom cylinder **8**, the stick cylinder **9**, the bucket cylinder **10**, the slewing motor **11**; oil supply and discharge control, supply pressure control, load pressure relief control, backpressure reduction control with respect to the option hydraulic actuator **13** etc. are performed, in a first/second operation amount setting unit **90**, a required flow rate setting unit **91**, a pump control unit **92**, a valve opening area control unit **93**, a bleed control unit **94**, an option control unit **95** etc. described below. The option hydraulic actuator notifying means **85** is a means, when the option hydraulic actuator **13** is mounted, for notifying the controller **30** of various types of information such as the type and specification of the option hydraulic actuator **13**, or values of option upper limit pressure PU described below. In the present embodiment, a monitor device (not illustrated) disposed in a cab **3a** of the hydraulic shovel **1** is provided as the option hydraulic actuator notifying means **85**, and it is adapted to enable notifying various pieces of information about the option hydraulic actuator **13** to the controller **30** by the operation of the monitor device, and to enable changing various pieces of information. Also, in FIG. 5, the option hydraulic actuator notifying means **85** is provided outside the controller **30**, but it is configured to provide at least a part of the information and functions contained in the option hydraulic actuator notifying means **85** within the controller **30**.

(39) Next, control performed by a setting unit and a control unit provided in the controller **30** will be discussed.

(40) The first/second operation amount setting unit **90**, when operation signals are input from the boom, the stick, the bucket, the slewing, the option operation detecting means **80** to **84**, in response to these operation signals, sets a first operation amount which the first hydraulic pump A serves and a second operation amount which the second hydraulic pump B serves, regarding respective operation amounts of operation levers. The setting of the first, second operation amounts is performed in accordance with pre-stored data, depending on the first, second hydraulic pumps A, B serving as the hydraulic supply sources for operated hydraulic actuators (the boom cylinder **8**, the stick cylinder **9**, the bucket cylinder **10**, the slewing motor **11**, the option hydraulic actuator **13**), the

operation amounts of the operation levers, hydraulic actuators to be combinedly operated (operated simultaneously), the type and specification of the option hydraulic actuator **13**. For example, in the present embodiment, since the bucket cylinder **10** uses only the first hydraulic pump A as a hydraulic supply source, only a bucket first operation amount is set when a bucket operation lever is operated; and since the slewing motor **11** uses only the second hydraulic pump B as a hydraulic supply source, only a slewing second operation amount is set when the slewing operation lever is operated. When the boom cylinder **8** is supplied with pressurized oil from both the first, second hydraulic pumps A, B, boom first, second operation amounts are set; but only a first operation amount is set when supplied with pressurized oil from only the first hydraulic pump A. When the stick cylinder **9** is supplied with pressurized oil from both the first, second hydraulic pumps A, B, stick first, second operation amounts are set; but only stick first operation amount is set when supplied with pressurized oil from only the first hydraulic pump A, and only stick second operation amount is set when supplied with pressurized oil from only the second hydraulic pump B. When the option hydraulic actuator **13** is supplied with pressurized oil from both the first, second hydraulic pumps A, B, option first, second operation amounts are set, but when supplied with pressurized oil only from the first hydraulic pumps A, only option first operation amount is set, and when supplied with pressurized oil only from the second hydraulic pumps B, only option second operation amount is set (see FIG. 6). Data for setting the first, second operation amount is stored in the first/second operation amount setting unit **90** as control parameters and is adapted to be changed using the monitor device or the like, depending on work contents performed by the hydraulic shovel **1** and the type and specification of the option hydraulic actuator **13**.

(41) Further, the required flow rate setting unit **91** determines required flow rates (a boom first required flow rate, a boom second required flow rate, a stick first required flow rate, a stick second required flow rate, a bucket first required flow rate, a slewing second required flow rate, an option first required flow rate, an option second required flow rate), which respective hydraulic actuators (the boom cylinder **8**, the stick cylinder **9**, the bucket cylinder **10**, the slewing motor **11**, the option hydraulic actuator **13**) require from the first, second hydraulic pumps A, B, in accordance with the first, second operation amounts set by the first, second operation amounts setting unit **90**.

Furthermore, the required flow rate setting unit **91** sets option first, second margin-added required flow rates by adding a margin flow rate a to the option first, second required flow rates (refer to FIG. 8). The margin flow rate a , when pressurized oil is supplied to the option hydraulic actuator **13** from the first, second hydraulic pumps A, B, is a flow rate to be added to the option first, second required flow rates in order to avoid the shortage of pressurized oil to be supplied to the option hydraulic actuator **13** by the flow rate control performed by the above-described compensator valve **61** for the purpose of differential pressure adjustment. In case where the option first, second required flow rates are “zero”, the option first, second margin-added required flow rates become also “zero”.

(42) Now, FIGS. 7(A), 7(B), 7(C) illustrate relationships among option first, second operation amounts of operation lever, option first, second required flow rates, and an option total required flow rate (a total of then option first required flow rate and the option second required flow rate). However, 7(A) illustrates a case where, in the first/second operation amount setting unit **90**, when operation amount of operation lever is small, only operation first operation amount is set (pressurized oil is supplied only from the first hydraulic pump A), and when operation amount of operation lever is large, option first, second operation amounts are set (pressurized oil is supplied from both the first, second hydraulic pumps A, B); 7(B) illustrates a case where option first, second operation amounts are set to the same values (the same amounts of pressurized oil are supplied from the first, second hydraulic pumps A, B); and 7(C) illustrates a case where only either one of the first, second operation amounts is set (pressurized oil is supplied only from either one of the first hydraulic pump A or the second hydraulic pump B).

(43) The required flow rate setting unit **91** is provided with data such as a map, for example,

illustrating a relationship between the first, second operation amounts and the required flow rates for each hydraulic actuator, and determines a required flow rate corresponding to an operation amount of operation lever using the data. Such data is adapted to be incorporated into the required flow rate setting unit **91** as control parameters; for example, according to work contents that the hydraulic shovel **1** performs and the type and the specification of the option hydraulic actuator **13**, values of the required flow rates corresponding to the first, second operation amounts can be changed using the monitor device or the like.

(44) Moreover, the pump control unit **92** computes a target discharge flow rate of the first, second hydraulic pumps A, B in accordance with required flow rates set by the required flow rate setting unit **91**. In this case, regarding the required flow rates of the boom cylinder **8**, the stick cylinder **9**, the bucket cylinder **10**, and the slewing motor **11**, there are used the boom first, second required flow rates, the stick first, second required flow rates, the bucket first required flow rate, the slewing second required flow rate which have been set by the required flow rate setting unit **91**; and regarding the required flow rate of the option hydraulic actuator **13**, there is used the option first, second margin-added required flow rates obtained by adding the margin flow rate a. Then, the target discharge flow rate of the first hydraulic pump A is obtained by taking the total of the first required flow rates which respective hydraulic actuators operated requires from the first hydraulic pump A and the first margin-added required flow rate (the boom first required flow rate+the stick first required flow rate+the bucket first required flow rate+the option first margin-added required flow rate) as the target discharge flow rate. If a total flow rate exceeds a maximum discharge flow rate of the first hydraulic pump A, the maximum discharge flow rate is taken as the target discharge rate. Further, similarly, the target discharge flow rate of the second hydraulic pump B is obtained by taking the total of the second required flow rate which respective hydraulic actuators operated requires from the second hydraulic pump A and the second margin-added required flow rate (the boom second required flow rate+the stick second required flow rate+the slewing second required flow rate+the option second margin-added required flow rate) as the target discharge flow rate. If the total flow rate exceeds the maximum discharge flow rate of the second hydraulic pump B, the maximum discharge flow rate is taken as the target discharge flow rate. Then, the pump control unit **92** outputs control signals to the displacement varying means Aa, Ba of the first, second hydraulic pumps A, B so that the target discharge flow rate can be obtained (refer to FIG. **8**). In case where the first operation amounts of respective hydraulic actuators are all “zero”, in case where the second operation amounts are all “zero”, the first, second hydraulic pumps A, B are controlled so that each has a minimum flow rate.

(45) In addition, the valve opening area control unit **93** determines opening areas of the supply valve passages **23c** to **26c** of the boom, the stick, the bucket, the slewing control valves **23** to **26**, the boom flow rate control valve **31**, the first, second stick flow rate control valves **32**, **33**, and the supply valve passage **60f** of the option control valve **60**, in accordance with the required flow rates, which respective hydraulic actuators require the first, second hydraulic pumps A, B, determined by the required flow rate setting unit **91**.

(46) In this case, since a control process for determining opening areas of the control valves (the boom, the stick, the bucket, the slewing control valves) **23** to **26** for permanently mounted hydraulic actuators (the boom cylinder **8**, the stick cylinder **9**, the bucket cylinder **10**, the slewing motor **11**) and the flow rate control valves (the boom, the first, the second stick flow rate control valves) **31** to **33** is different from a control process for determining an opening area of the option control valve **60**; first, the control of the opening areas of the control valves **23** to **26** of the permanently mounted hydraulic actuators and the flow rate control valves **31** to **33** will be discussed.

(47) Upon determination of the opening areas of the control valves **23** to **26** and the flow rate control valves **31** to **33** for the permanent mounted hydraulic actuators, the valve opening area control unit **93**, first, determines a distributed flow rate of each permanent hydraulic actuator. The

computation of the distributed flow rate is performed separately by the first hydraulic pump A and the second hydraulic pump B. In other words, as for the distributed flow rate of the permanently mounted hydraulic actuator supplied with pressurized oil from the first hydraulic pump A, the target discharge flow rate of the first hydraulic pump A is distributed at a ratio between an option first margin-added required flow rate, a boom first required flow rate, a stick first required flow rate, a bucket first required flow rate, to determine a boom first distributed flow rate, a stick first distributed flow rate, a bucket first distributed flow rate. Also, as for the distributed flow rate of the permanently mounted hydraulic actuator supplied with pressurized oil from the second hydraulic pump B, the target discharge flow rate of the second hydraulic pump B is distributed at a ratio between the option second margin-added required flow rate, the boom second required flow rate, the stick second required flow rate, the slewing second required flow rate, to determine a boom second distributed flow rate, a stick second distributed flow rate, and a slewing second distributed flow rate. In case where the option first, second margin-added required flow rates are “zero”, there is performed a distributed flow rate computation for distributing the entire rate of the target discharge flow rate to the permanently hydraulic actuators. Then, the valve opening area control unit **93** computes opening areas of the supply valve passages **23c** to **26c** of the boom, the stick, the bucket, the slewing control valves **23** to **26** for supplying these boom first, second distributed flow rates, the stick first, second distributed flow rates, the bucket first distributed flow rate, the slewing second distributed flow rate, respectively from the first, second hydraulic pumps A, B to the boom cylinder **8**, the stick cylinder **9**, the bucket cylinder **10**, the slewing motor **11** and opening areas of the boom, the first, second stick flow rate control valves **31** to **33**. Then, the valve opening area control unit **93** switches respective control valves **23** to **26** to the actuation position X or Y in correspondence with operation directions of respective operation levers for the boom, the stick, the bucket, the slewing motor, as well as outputs control signals to the boom, the stick, the bucket, the slewing solenoid proportional valves **44a**, **44b** to **47a**, **47b**, the boom flow rate control solenoid proportional valve **41**, the first, second stick flow rate control solenoid proportional valves **42**, **43** so as to attain the computed opening areas (refer to FIG. 9).

(48) Upon controlling the opening areas of the control valves **23** to **26** and the flow rate control valves **31** to **33** for the permanently mounted hydraulic actuators, by adopting such a constitution of distributing the discharge flow rates of the first, second hydraulic pumps A, B at a ratio between the option first, second margin-added required flow rates and the required flow rate of the permanently mounted hydraulic actuator, even in case where the option hydraulic actuator **13** is combinedly operated with the other hydraulic actuators (the permanently mounted hydraulic actuators) that share the hydraulic pump A or/and B, it is configured such that the option first, second margin-added required flow rates are adapted to be supplied to the option merging oil passage **22**, and thereby enabling to ensure reliably the supply flow rate to the option hydraulic actuator **13**. In addition, as an example of control, it is also possible to adjust the option first, second margin-added required flow rates by multiplying the option first, second margin-added required flow rates with a flow rate limiting coefficient dedicated to combined operation, and to control so as to maintain the supply flow rate to the option hydraulic actuator **13** at a constant level.

(49) On the other hand, the valve opening area control unit **93**, in case of determining an opening area of the option control valve **60**, computes an opening area of the supply valve passage **60f** of the option control valve **60** for supplying a total flow rate of the option first, second required flow rates which is set by the required flow rate setting unit **91** to the option hydraulic actuator **13**. Then, the valve opening area control unit **93** switches the option control valve **60** to the first actuation position X or the second actuation position Y, in correspondence with information of the option hydraulic actuator **13** input from the option hydraulic actuator notifying means **85** and the operation direction of the option operation lever; as well as to output control signals to the first, second option solenoid proportional valves **48a**, **48b** so as to attain the above computed opening areas (refer to FIG. 9). In this case, the differential pressure between front and behind of the supply valve

passage **60f** of the option control valve **60** is maintained at a constant level (the predetermined pressure **K**) by the compensator valve **61** described above. The supply flow rate from the option control valve **60** to the option hydraulic actuator **13** is controlled with a high precision so as to become a total flow rate of the option first, second required flow rates.

(50) Further, the bleed control unit **94** performs control of the bleed flow rate which flows from the first, second hydraulic pumps A, B to the oil tank **12**, in accordance with the first, second operation amounts determined by the first/second operation amount setting unit **90**; and controls the discharge pressures of the first, second hydraulic pumps A, B, by the control of the bleed flow rate.

(51) In this case, the bleed control unit **94**, firstly determines first, second required pressures (boom first required pressure, boom second required pressure, stick first required pressure, stick second required pressure, bucket first required pressure, slewing second required pressure, option first required pressure, option second required pressure) which corresponding respective hydraulic actuators require the first, second hydraulic pumps A, B, in accordance with the boom first, second operation amounts, the stick first, second operation amounts, the bucket first operation amount, the slewing second operation amount, the option first operation amount. The bleed control unit **94** is provided with, for example, data such as a map illustrating a relationship between the first, second operation amounts and the required pressures for respective hydraulic actuators; and determines the required pressures corresponding to the operation amounts of the operation levers using the data, but such data is adapted to be incorporated in the bleed control unit **94** as control parameters. The values of the required pressures corresponding to the operation amounts can be changed, according to the work contents performed by the hydraulic shovel **1** and the type and the specification of the option hydraulic actuator **13**.

(52) Subsequently, the bleed control unit **94** determines first, second pump required pressures, in accordance with the first, second required pressures. In this case, a maximum value of the required pressures (the boom first required pressure, the stick first required pressure, the bucket first required pressure, the option first required pressure) which the respective hydraulic actuators require from the first hydraulic pump A is taken as a first pump required pressure **PR1**; a maximum value of the required pressures (the boom second required pressure, the stick second required pressure, the slewing second required pressure, the option second required pressure) which the respective hydraulic actuators require from the second hydraulic pump B is taken as a second pump required pressure **PR2**. In accordance with these first, second pump required pressures **PR1**, **PR2**, target pressures (first, second pump target pressures) **PT1** and **PT2** of the first, second hydraulic pumps A, B are set (refer to FIG. **10**).

(53) Upon setting the first, second pump target pressures **PT1**, **PT2**, the bleed control unit **94**, firstly determines whether or not an option operation lever is being operated; if the option operation lever is not being operated (when both the option first, second operation amounts are “zero”), the first, second pump required pressures **PR1**, **PR2** are set as the target pressures **PT1**, **PT2** of the first, second hydraulic pumps A, B. On the other hand, if the option operation lever is being operated (when at least one of the option first, second operation amounts is not “zero”), the bleed control unit **94** performs an option priority control described below.

(54) In case where the bleed control unit **94** performs the option priority control, the bleed control unit **94**, firstly determines whether a hydraulic pump that supplies pressurized oil to the option hydraulic actuator **13** is only the first hydraulic pump A (only the option first operation amount is set) or only the second hydraulic pump B (only the option second operation amount is set) or both the first, second hydraulic pumps A, B (the option first, second operation amounts are set). Then, the first pump required pressure **PR1** and the second pump required pressure **PR2** are compared, in respective cases: a case where the determination result is only the first hydraulic pump A (hereinafter referred to as a determination result (A)); a case where only the second hydraulic pump B is determined (hereinafter referred to as a determination result (B)); a case where both the first, second hydraulic pumps A, B are determined (hereinafter referred to as a determination result

(A+B)).

(55) Then, if the first pump required pressure $PR1$ is higher than the second pump required pressure $PR2$ ($PR1 > PR2$) in the determination result (A), then these first, second pump required pressures $PR1$, $PR2$ are set as the target pressures $PT1$, $PT2$ of the second hydraulic pumps A, B, respectively. On the other hand, if the first pump required pressure $PR1$ is equal to or lower than the second pump required pressure $PR2$ ($PR1 \leq PR2$) in the determination result (A), a pressure ($PR2 + \beta$) obtained by adding the margin pressure R to the second pump required pressure $PR2$ is taken as the first pump target pressure $PT1$, and the second pump required pressure $PR2$ is set as the second pump target pressure $PT2$. As a result, in the case of the determination result (A), that is, if a hydraulic pump which supplies pressurized oil to the option hydraulic actuator **13** is only the first hydraulic pump A, then the target pressure $PT1$ of the first hydraulic pump A is the second hydraulic pump is set to a higher pressure than the target pressure $PT2$ of the second hydraulic pump B. The margin pressure R is a pressure to be added in order to ensure that the discharge pressure of the hydraulic pump that supplies pressurized oil to the option hydraulic actuator **13** is always higher than the discharge pressure of the hydraulic pump that does not supply pressurized oil to the option hydraulic actuator **13**.

(56) Further, if the first pump required pressure $PR1$ is higher than or equal to the second pump required pressure $PR2$ ($PR1 \geq PR2$) in the determination result (B), then the first pump required pressure $PR1$ is taken as the first pump target pressure $PT1$, and a pressure ($PR1 + P$) obtained by adding the margin pressure R to the first pump required pressure $PR1$ is set as the second pump target pressure $PT2$. On the other hand, if the first pump required pressure $PR1$ is smaller than the second pump required pressure $PR2$ ($PR1 < PR2$), in the determination result (B), then these first, second pump required pressures $PR1$, $PR2$ are set as the target pressures $PT1$, $PT2$ of the first, second pumps. As a result, in the case of the determination result (B), that is, in case where a hydraulic pump that supplies pressurized oil to the option hydraulic actuator **13** is only the second hydraulic pump B, then the target pressure $PT2$ of the second hydraulic pump B is set so as to be higher than the target pressure $PT1$ of the first hydraulic pump A.

(57) Further, if the first pump required pressure $PR1$ is larger than the second pump required pressure $PR2$ ($PR1 > PR2$) in the determination result (A+B), then the first pump required pressure $PR1$ is set as the first, second pump target pressures $PT1$, $PT2$. On the other hand, if the first pump required pressure $PR1$ is less than or equal to the second pump required pressure $PR2$ ($PR1 \leq PR2$) in the determination result (A+B), then the second pump required pressure $PR2$ is set as the first, second pump target pressures $PT1$, $PT2$. As a result, in the case of the determination result (A+B), that is, if hydraulic pumps that supply pressurized oil to the option hydraulic actuator **13** are both the first, second hydraulic pumps A, B, then these target pressures $PT1$, $PT2$ of the first, second hydraulic pumps A, B are set so as to be the same pressures by matching them with the higher pressure in the first, second pump required pressures $PR1$, $PR2$ (see FIG. 11).

(58) In this way, if a hydraulic pump that supplies pressurized oil to the option hydraulic actuator **13** is either one of the first or second hydraulic pump A, B (in the case of the determination result (A) or (B)), the discharge pressure of the one hydraulic pump that supplies the pressurized oil is controlled to be higher than the discharge pressure of the another hydraulic pump that does not supply the pressurized oil, so that the pressurized oil supplied from the one hydraulic pump preferentially is adapted to flow into the option merging oil passage **22**, and the pressurized oil supplied from the another hydraulic pump not to flow into the option merging oil passage **22**. On the other hand, if both the first, second hydraulic pumps A, B supply the pressurized oil to the option hydraulic actuator **13** (in the case of the determination result (A+B)), the discharge pressures of both the hydraulic pumps A, B are controlled to be the same pressures, so that the pressurized oil supplied from both the first, second hydraulic pumps A, B is adapted to be supplied and merged to the option merging oil passage **22**.

(59) Then, the bleed control unit **94**, after setting the target pressures $PT1$, $PT2$ of the first, second

hydraulic pumps A, B is adapted to compute opening areas of the first, second bleed valves **75**, **76** to reach the target pressures **PT1**, **PT2**; to output control signals to the first, second bleed solenoid proportional valves **49a**, **49b** to form opening areas; and to control the bleed flow rate flowing into the oil tank **12** from the first, second hydraulic pumps A, B (refer to FIG. **10**). If all the first operation amounts of the respective hydraulic actuators are “zero”, and if all the second operation amounts are “zero”, then the bleed flow rate is controlled so that the discharge pressures of the first, second hydraulic pumps A, B become the preset lowest discharge pressure.

(60) Also, the option control unit **95** performs option supply pressure control for setting a relief setting pressure **LP** of the variable relief valve **65** in order to perform supply pressure control to the option hydraulic actuator **13**, in accordance with information input from the option hydraulic actuator notifying means **85** when an operation signal of the option operation lever is input from the option operation detecting means **84**.

(61) In this case, the option control unit **95** inputs from the option hydraulic actuator notifying means **85**, values of the option upper limit pressure **PU** preset as the upper limit pressure of each option hydraulic actuator **13** depending on the type and specification of the option hydraulic actuator **13**. Then, the option control unit **95** outputs control signals to the variable relief valve **65** in order to vary the relief setting pressure **LP** of the variable relief valve **65** to a pressure ($LP=PU-K$) obtained by subtracting the predetermined pressure (the pressure specified depending on a spring **61c** of the compensator valve **61**) **K** from the option upper limit pressure **PU**. As a result, an inlet-side pressure **PO** of the option control valve **60** is controlled to be less than or equal to $PO \leq (LP+K)$ a pressure, which is higher than the relief setting pressure **LP** of the variable relief valve **65** by the predetermined pressure **K**, ($LP+K$), that is, to be less than or equal to the option upper limit pressure **PU** ($PO \leq PU$), by the action of the compensator valve **61** described above. Then, by controlling the inlet-side pressure of the option control valve **60** so as to be less than or equal to the option upper limit pressure **PU**, through the setting of the relief setting pressure **LP** of the variable relief valve **65** in this manner, the supply pressure to the option hydraulic actuator **13** can be less than the option upper limit pressure **PU** which is set depending on each option hydraulic actuator **13**, even without providing variable relief valves respectively in the pair of first, second hydraulic actuator oil passages **67**, **68** extending from the option control valve **60** to the option hydraulic actuator **13**.

(62) Moreover, the option control unit **95** performs load pressure relief control, when pressures of the first, second hydraulic actuator oil passages **67**, **68** connected to the option hydraulic actuator **13** exceed the preset option upper limit pressure **PU**, for relieving the pressures, in accordance with information input from the option hydraulic actuator notifying means **85** and detection values of the first, second option pressure sensors **97**, **98**, when an operation signal for the option operation lever is not input from the option operation detecting means **84**, that is, when the option operation lever is not operated.

(63) When the load pressure relief control is described with reference to the flowchart illustrated in FIG. **12**, firstly the option control unit **95** determines whether or not an option operation lever is being operated (step **S1**).

(64) If it is determined that the option operation lever is not operated (non-operation), the option control unit **95** recognize a high pressure holding side of the option hydraulic actuator **13** during non-operation of the option operation lever, in accordance with the information input from the option hydraulic actuator notifying means **85**, and reads from the first or second option pressure sensors **97**, **98**, pressure detection values **Pd** of the first hydraulic actuator oil passage **67** or the second hydraulic actuator oil passage **68** connected to the high pressure holding side (step **S2**).

(65) Further, the option control unit **95** reads from the option hydraulic actuator notifying means **85**, the value of the option upper limit pressure **PU**, which is preset as the upper limit pressure of each option hydraulic actuator **13** depending on the type and specification of the option hydraulic actuator **13** (step **S3**).

(66) Subsequently, the option control unit **95** compares (determination of $P_d \leq P_U$) the pressure detection values P_d of the first hydraulic actuator oil passage **67** or the second hydraulic actuator oil passage **68** on the high pressure holding-side on the high pressure holding side with the option upper limit pressure P_U (step **S4**).

(67) If the pressure detection value P_d is lower than or equal to the option upper limit pressure P_U ($P_d \leq P_U$), by determination in step **S4**, the option control unit **95** controls the option control valve **60** so as to be positioned at the neutral position **N**, and causes the variable relief valve **65** to be de-energized (step **S5**). Consequently, the first, second hydraulic actuator oil passages **67**, **68** are allowed to enter a state in which oil inflow and outflow is blocked by the option control valve **60** in the neutral position **N**. Then, after the processing of step **S5**, the process returns to the determination of step **S1**. The non-excited variable relief valve **65** has the maximum relief setting pressure LP .

(68) On the other hand, if the pressure detection value P_d is greater than the option upper limit pressure P_U ($P_d > P_U$), by the determination in step **S4**, outputs a control command so as to be switched to the first or second load pressure relief positions **R1**, **R2** (to the first load pressure relief position **R1** when the first actuator oil passage **67** is on the high pressure holding-side; to the second load pressure relief position **R2** when the second actuator oil passage **68** is on the high pressure holding-side) to the option control valve **60**, in order to open the load pressure valve passage **60h** extending from the first or second actuator port **60c**, **60d** connected to the first or second hydraulic actuator oil passages **67**, **68** on the high pressure holding-side to the load pressure output port **60e**. Moreover, the option control unit **95** outputs a control command to the variable relief valve **65** so that the relief setting pressure LP is equalized to the option upper limit pressure P_U (or the relief setting pressure LP so as to be a value slightly lower than the option upper limit pressure P_U) (Step **S6**). Consequently, the pressurized oil in the first or second hydraulic actuator oil passages **67**, **68** on the high pressure holding-side is allowed to flow into the load pressure introducing oil passage **62** through the load pressure valve passage **60h** of the option control valve **60**, to flow into the oil tank **12** via the variable relief valve **65** connected to the load pressure introducing oil passage **62**, thereby lowering the first or second hydraulic actuator oil passages **67**, **68** on the high pressure holding-side. Then, after the processing of step **S6**, the process returns to the determination of step **S1**; but until it is determined that the option operation lever has been operated in the step **S1**, or the pressure detection value P_d is lower than or equal to the option upper limit pressure P_U ($P_d \leq P_U$) in step **S4**, the control of step **S6** is continued.

(69) On the other hand, if it is determined in the step **S1** that the option operation lever has been operated, then the above load pressure relief control ends. In other words, the load pressure relief control starts only when the option operation lever is not operated, and when the option operation lever is operated, the control ends even on the halfway of the load pressure relief control. Then, when the option operation lever is operated, the option control valve **60** is positioned at the first operating position **X** or the second operating position **Y** under the control of the valve opening area control unit **93** described above, and setting of the relief setting pressure LP is performed by the option supply pressure control performed by the option control unit **95**, and the variable relief valve **65** is controlled so as to become the set relief setting pressure LP .

(70) By the load pressure relief control being executed in this manner, in case where a pressure in the first or second hydraulic actuator oil passages **67**, **68** on the high pressure holding-side in the non-operating state of the option operation lever exceeds the option upper limit pressure P_U , the pressure will flow into the oil tank **12** via the option control valve **60** at the first or second load pressure relief positions **R1**, **R2**, the load pressure introducing oil passage **62**, and the variable relief valve **65**. Thus, even if the first, second hydraulic actuator oil passages **67**, **68** are not provided with variable relief valves, the pressure in the first, second hydraulic actuator oil passages **67**, **68** in the non-operating state of the option operation lever will be able to be controlled so as to become lower than or equal to the option upper limit pressure P_U which is set in correspondence

with individual option hydraulic actuator. Besides, since the load pressure relief control is a control performed utilizing the load pressure valve passage **60h** formed in the option control valve **60** and the variable relief valve **65** used for option supply pressure control, it is possible to achieve common use of parts without separately requiring members dedicated to the load pressure relief control.

(71) In this embodiment, the value of the option upper limit pressure used for the option supply pressure control and the value of the option upper limit pressure used for the load pressure relief control are set to the same values, but the option upper limit pressures with different values between the option supply pressure control and the load pressure relief control may be set.

(72) Moreover, the option control unit **95** determines whether the option hydraulic actuator **13** is a hydraulic actuator of pressurized oil supply direction is one direction like a breaker, for example, and needs to reduce the back pressure, in accordance with the information input from the option hydraulic actuator notifying means **85**, if an operation signal of the option operation lever is input the option operation detecting means **84**. Then, if it is determined to be an applicable hydraulic actuator, then the option control unit **95** outputs a control signal to cause the switching valve **74** to be positioned at the open position X. As a result, a return oil from the option hydraulic actuator **13** to the oil tank **12** will flow directly to the oil tank **12** without passing through the option control valve **60**, so that the back pressure can be reliably reduced.

(73) Next, control performed when an option operation lever is operated, will be discussed, by illustrating Examples 1 to 4. In each Example, in case of a similar control to that in another Examples, the description will be brief or will be omitted.

Example 1

(74) First, a case where the option operation lever is operated independently, and the option hydraulic actuator **13** is supplied with pressurized oil only from the first hydraulic pump A will be discussed as the Example 1.

(75) In this case, the controller **30**, when an operation signal is input from the option operation detecting means **84**, firstly sets an option first operation amount, which is an operation amount for which the first hydraulic pump A serves. Moreover, depending on the option first operation amount, the option hydraulic actuator **13** determines an option first required flow rate which is required to the first hydraulic pump A, and an option first margin-added required flow rate obtained by adding a margin flow rate a to the option first required flow rate. Then, the discharge flow rate control of the first hydraulic pump A is performed by taking the option first margin-added required flow rate as the target discharge flow rate. Furthermore, the controller **30** sets an option first required pressure required by the option hydraulic actuator **13** of the first hydraulic pump A, depending on the option first operation amount; as well as the option first required pressure is set as a first pump required pressure $PR1$, moreover the first pump required pressure $PR1$ is set as a target pressure $PT1$ of the first hydraulic pump A, and an opening area of the first bleed valve **75** is controlled so as to reach the target pressure $PT1$. On the other hand, the discharge flow rate and discharge pressure of the second hydraulic pump B are controlled so as to be the lowest. Then, the pressurized oil supplied from the first hydraulic pump A flows into the option merging oil passage **22** via the first pump line C, the first option supply oil passage **17**, and is supplied to the option hydraulic actuator **13** via the compensator valve **61** disposed in the option merging oil passage **22**, the option control valve **60**. Furthermore, the controller **30** controls the supply pressure to the option control valve **60** so as to be less than or equal to the option upper limit pressure PU , by setting the relief setting pressure LP of the variable relief valve **65** to a pressure ($LP=PU-K$) obtained by subtracting the predetermined pressure K from the option upper limit pressure PU that is set according to the type and specification of the option hydraulic actuator **13**. In addition, the opening area of the supply valve passage **60f** of the option control valve **60** is controlled so as to an opening area corresponding to the option first required flow rate; but in this case, since the differential pressure between front and behind of the option control valve **60** is held at the

predetermined pressure K by the compensator valve **61**, a highly accurate supply flow rate control can be performed; as well as the supply flow rate from the first hydraulic pump A is equivalent to the option first margin-added required flow rate obtained by adding the margin flow rate a to the option first required flow rate, even if the flow rate is controlled by the compensator valve **61** for purpose of differential pressure adjustment, the supply flow rate to the option control valve **60** will not come short. Moreover, in case where the option hydraulic actuator **13** is a hydraulic actuator that requires reduction in back pressure, a control signal is output so that the switching valve **74** be switched to the open position X, thereby enabling to cause the return oil from the option hydraulic actuator **13** to flow into the oil tank **12** via the bypass oil passage **73** without passing through the option control valve **60**.

(76) In this manner, in the Example 1, pressurized oil is supplied to the option hydraulic actuator **13** only from the first hydraulic pump A, but in this case, the supply pressure to the option control valve **60** is controlled to be less than or equal to the option upper limit pressure PU that is set depending on individual option hydraulic actuator **13**, as well as the supply flow rate to the option hydraulic actuator **13** can be controlled with a high accuracy.

Example 2

(77) Next, a case where an option operation lever is operated independently and pressurized oil is supplied to the option hydraulic actuator **13** from both the first, second hydraulic pumps A, B will be discussed as the Example 2.

(78) In this case, the controller **30**, when an operation signal is input from the option operation detecting means **84**, firstly sets option first, second operation amounts. Furthermore, the controller **30** determines option first, second required flow rates, and option first, second margin-added required flow rates, depending on the option first, second operation amounts. Then, the discharge flow rates of the first, second hydraulic pumps A, B are controlled taking the option first, second margin-added required flow rates as the target discharge flow rates. Furthermore, the controller **30** sets option first, second required pressures depending on the option first, second operation amounts; as well as the option first, second required pressures are taken as the first, second pump required pressures PR1, PR2, respectively, moreover, higher pressures of these first, second pump required pressures PR1, PR2 are set as the target pressures PT1, PT2 ($PT1=PT2$) of both the first, second hydraulic pumps A, B, and opening areas of the first, second bleed valves **75**, **76** are controlled so as to reach the target pressures PT1, PT2. As a result, the discharge pressures of the first, second hydraulic pumps A, B are controlled so as to be equalized. Then, the supply pressurized oil from the first, second hydraulic pumps A, B merges at the option merging oil passage **22** via the first, second pump lines C, D, the first, second option supply oil passages **17**, **21**, respectively; but in this case, since the discharge pressures of the first, second hydraulic pumps A, B are equalized, the supply oil from both the hydraulic pumps A, B flows into the option merging oil passage **22** without the supply of pressurized oil from either one of the hydraulic pumps A, B being prioritized at the time of merging, and is supplied to the option hydraulic actuator **13** via the compensator valve **61** disposed in the option merging oil passage **22**, the option control valve **60**. Then, the opening area of the supply valve passage **60f** of the option control valve **60** is controlled so as to become an opening area corresponding to a total flow rate of the option first, second required flow rates; but in this case, similarly to the above-described Example 1, highly accurate supply flow rate control can be performed. Furthermore, the controller **30** sets the relief setting pressure LP of the variable relief valve **65** and performs switching control of the switching valve **74** depending on necessity, but these are similar to the Example 1 and therefore description will be omitted.

(79) Thus, in the Example 2, the option hydraulic actuator **13** is supplied with pressurized oil from both the first, second hydraulic pumps A, B. Even in this case, similarly to the Example 1, the supply pressure to the option control valve **60** is controlled so as to be less than or equal to the option upper limit pressure PU that is set depending on individual option hydraulic actuator **13**; as

well as the supply flow rate to the option hydraulic actuator **13** can be controlled with a high accuracy. Besides, in this case, since the discharge pressures of the first, second hydraulic pumps A, B are controlled to be equalized, and the supply oil from both the hydraulic pumps A, B can be merged into the option merging oil passage **22**, without the pressurized oil supply from either one of the hydraulic pumps A, B being prioritized.

Example 3

(80) Next, a case where the option operation lever is being combinedly operated with the stick operation lever and the slewing operation lever, and the option hydraulic actuator **13** is supplied with pressurized oil from the first hydraulic pump A, and the stick cylinder **9** and the slewing motor **11** are supplied with pressurized oil from the second hydraulic pump B will be discussed as the Example 3.

(81) In this case, the controller **30**, when operation signals are input from the option, the stick, the slewing operation detecting means **84**, **81**, **83**, firstly sets option first, stick second, slewing second operation amounts. Furthermore, the controller **30** determines option first, stick second, slewing second required flow rates, and option first margin-added required flow rate, corresponding to the option first, stick second, slewing second operation amounts. Then, the discharge flow rate of the first hydraulic pump A is controlled taking the option first margin-added required flow rate as the target discharge flow rate, and the discharge flow rate of the second hydraulic pump B is controlled, taking a total of the stick second required flow rate and the slewing second required flow rate as the target discharge flow rate (if a total flow rate exceeds the maximum discharge flow rate of the second hydraulic pump B, then the maximum discharge flow rate is taken as the target discharge flow rate). Furthermore, the controller **30** sets option first required pressure, stick second required pressure, slewing second required pressure corresponding to the option first, stick second, slewing second operation amounts. Then, the controller **30** uses the option first required pressure as the first pump required pressure **PR1** and uses a higher pressure of the stick second and slewing second required pressures as the second pump required pressure **PR2**. Furthermore, the first pump required pressure **PR1** and the second pump required pressure **PR2** are compared, and the target pressures **PT1**, **PT2** of the first, second hydraulic pumps A, B are set in accordance with the comparison result; but in this case, the target pressure **PT1** of the first hydraulic pump A that supplies pressurized oil to the option hydraulic actuator **13** is set at a higher pressure than the target pressure **PT2** of the second hydraulic pump B that does not supply pressurized oil to the option hydraulic actuator **13**, and the opening areas of the first, second bleed valves **75**, **76** are controlled so that the target pressures **PT1**, **PT2** be reached, by the control of the bleed control unit **94** described above. Then, the supply pressurized oil from the first hydraulic pump A flows into the option merging oil passage **22** via the first pump line C, the first option supply oil passage **17**; but in this case, since the discharge pressure of the first hydraulic pump A is higher than the discharge pressure of the second hydraulic pump B, the supply pressurized oil from the first hydraulic pump A preferentially flows into the option merging oil passage **22**, and the supply pressurized oil from the second hydraulic pump B is adapted not to flow into the option merging oil passage **22**. Then, the supply pressurized oil from the first hydraulic pump A that has flowed into the option merging oil passage **22** is supplied to the option hydraulic actuator **13** via the compensator valve **61** disposed in the option merging oil passage **22**, the option control valve **60**. The control of the opening area of the supply valve passage **60f** of the option control valve **60** in this case, the setting of the relief setting pressure **LP** of the variable relief valve **65**, and the switching control of the switching valve **74** performed depending on necessity are similar to the Example 1, and therefore the description will be omitted. On the other hand, the supply pressurized oil from the second hydraulic pump B flows into the second stick supply oil passage **19** from the second pump line D, and is supplied to the stick cylinder **9** via the second stick flow rate control valve **33**, the stick control valve **24**; as well as flows into the second slewing supply oil passage **20** from the second pump line D, and is supplied to the slewing motor **11** via the slewing control valve **26**. In this case,

the control of opening areas of the second stick flow rate control valve **33**, the supply valve passages **24c**, **26c** of the stick, the slewing control valves **24**, **26** is performed, discharge flow rate of the second hydraulic pump B are controlled so as to have the opening areas corresponding to the stick second distributed flow rate, the slewing second distributed flow rate, which is obtained by distributing the stick second required flow rate, the slewing second required flow rate, by the control of the valve opening area control unit **93** described above. In the Example 3, since it is configured such that the stick cylinder **9** is supplied with pressurized oil only from the second hydraulic pump B, the first stick flow rate control valve **32** disposed in the first stick supply oil passage **16** is controlled to be closed.

(82) Thus, in the Example 3, the option operation lever is being combinedly operated with the operation levers for the other hydraulic actuators (the stick cylinder **9**, the slewing motor **11**), and the option hydraulic actuator **13** is supplied with pressurized oil from the first hydraulic pump A, and the other hydraulic actuators are supplied with pressurized oil from the second hydraulic pump B. In this case as well, similarly to the Examples 1, 2, the supply pressure to the option control valve **60** is controlled so as to be less than or equal to the option upper limit pressure PU that is set depending on individual option hydraulic actuator **13**; as well as the supply flow rate to the option hydraulic actuator **13** can be controlled with a high accuracy. Besides in this case, since the discharge pressure of the first hydraulic pump A that supplies pressurized oil to the option hydraulic actuator **13** is controlled to become a higher than the discharge pressure of the second hydraulic pump B, only the supply pressurized oil from the first hydraulic pump A can be reliably caused to flow into the option merging oil passage **22**. On the other hand, the discharge flow rate of the second hydraulic pump B is distributed to the other hydraulic actuators, thereby enabling to ensure good, combined operability between the option hydraulic actuator **13** and the other hydraulic actuators (the stick cylinder **9** the slewing motor **11**).

Example 4

(83) Next, a case in which the option operation lever is combinedly operated with the boom operation lever, the slewing operation lever, and the option hydraulic actuator **13** and the boom cylinder **8** are supplied with pressurized oil from the first hydraulic pump A, and the slewing motor **11** is supplied with pressurized oil from the second hydraulic pump B will be discussed as Example 4.

(84) In this case, the controller **30**, when operation signals are input from the option, the boom, the slewing operation detecting means **84**, **80**, **83**, firstly sets an option first, boom first, slewing second operation amounts. Furthermore, the controller **30** determines an option first, boom first, slewing second required flow rate, and an option first margin-added required flow rate, depending on the option first, the boom first, the slewing second operation amounts. Then, the discharge flow rate control of the first hydraulic pump A is performed taking a total of the option first margin-added required flow rate and the boom first required flow rate as a target discharge flow rate (if the total flow rate exceeds the maximum discharge flow rate of the first hydraulic pump A, taking the maximum discharge flow rate as the target discharge flow rate), and the discharge flow rate control of the second hydraulic pump B is performed taking the slewing second required flow rate as a target discharge flow rate. Furthermore, the controller **30** sets option first, boom first, slewing second required pressures, depending on the option first, the boom first, the slewing second operation amounts. Then, a higher pressure of the option first, the boom first required pressures is taken as a first pump required pressure PR1, and the slewing second required pressure is taken as a second pump required pressure PR2. Furthermore, the first pump required pressure PR1 and the second pump required pressure PR2 are compared, and the target pressures PT1, PT2 of the first, second hydraulic pumps A, B are set in accordance with the comparison result; but in this case, the target pressure PT1 of the first hydraulic pump A that supplies pressurized oil to the option hydraulic actuator **13** is set at a higher pressure than the target pressure PT2 of the second hydraulic pump B that does not supply pressurized oil to the option hydraulic actuator **13**, and the opening

areas of the first, second bleed valves **75**, **76** are controlled so that the target pressures **PT1**, **PT2** be reached, by the control of the bleed control unit **94** described above. Then, the supply pressurized oil from the first hydraulic pump A flows into the first boom supply oil passage **14** from the first pump line C, and is supplied to the boom cylinder **8** via the boom control valve **23**; as well as flows into the option merging oil passage **22** via the first option supply oil passage **17** from the first pump line C; but in this case, since the discharge pressure of the first hydraulic pump A is a higher pressure than the discharge pressure of the second hydraulic pump B, the supply pressurized oil from the first hydraulic pump A preferentially flows into the option merging oil passage **22**, and the supply pressurized oil from the second hydraulic pump B is adapted not to flow into the option merging oil passage **22**. The pressurized oil from the first hydraulic pump A which has been supplied from the first boom supply oil passage **14** to the boom control valve **23** is controlled such that the supply flow rate of the boom cylinder **8** is controlled in accordance with an opening area of the supply valve passage **23c** of the boom control valve **23**; but in this case, by the control of the valve opening area control unit **93** described above, an opening area of the supply valve passage **23c** of the boom control valve **23** is controlled so as to attain an opening area corresponding to the boom first distributed flow rate obtained by distributing the discharge flow rate of the first hydraulic pump A at a ratio of the option first margin-added required flow rate, the boom first required flow rate. Consequently, the option first margin-added required flow rate obtained by adding the margin flow rate a to the option first required flow is allowed to flow into the option merging oil passage **22** from the first hydraulic pump A. Then, the supply pressurized oil from the first hydraulic pump A that has flowed into the option merging oil passage **22** is supplied to the option hydraulic actuator **13** via the compensator valve **61**, the option control valve **60** disposed in the option merging oil passage **22**. In this case, an opening area of the supply valve passage **60f** of the option control valve **60** is controlled so as to become an opening area correspond to the option first required flow rate; but the control of the opening area, the setting of the relief setting pressure **LP** of the variable relief valve **65**, the action of the compensator valve **61**, the switching control of the switching valve **74** performed depending on necessity are similar to those in the Example 1, and thus the description thereof will be omitted. On the other hand, the supply pressurized oil from the second hydraulic pump B flows into the second slewing supply oil passage **20** from the second pump line D and is supplied to the slewing motor **11** via the slewing control valve **26**. The control of an opening area of the supply valve passage **26c** of the slewing control valve **26** of this case is performed so as to become an opening area corresponding to the slewing second required flow rate, because a hydraulic actuator supplied with pressurized oil from the second hydraulic pump B is only the slewing motor **11**. In the Example 4, due to a configuration in which the boom cylinder **8** is supplied with pressurized oil only from the first hydraulic pump A, the boom flow rate control valve **31** disposed in the second boom supply oil passage **18** is controlled to close.

(85) In this manner, in the Example 4, the option operation lever is combinedly operated with the operation levers for two other hydraulic actuators (the boom cylinder **8**, the slewing motor **11**), and the option hydraulic actuator **13** and the one of the other hydraulic actuators are supplied with pressurized oil from the first hydraulic pump A, and the another of the other hydraulic actuators is supplied with pressurized oil from the second hydraulic pump B; but even if the option hydraulic actuator **13** shares the other hydraulic actuators and the first hydraulic pump A in this manner, since the option first margin-added required flow rate obtained by adding the margin flow rate a to the option first required flow rate is supplied to the option merging oil passage **22**. Consequently, even when the flow rate is controlled for purpose of differential pressure adjustment by the compensator valve **61**, the supply flow rate to the option control valve **60** will never come short; then in this case also, similarly to the Examples 1 to 3, the supply pressure to the option control valve **60** is controlled so as to be less than or equal to the option upper limit pressure **PU** that is set depending on an individual option hydraulic actuator **13**; as well as the supply flow rate to the option hydraulic actuator **13** can be controlled with a high accuracy. Besides in this case, since the

discharge pressure of the first hydraulic pump A that supplies pressurized oil to the option hydraulic actuator **13** is controlled to become a higher than the discharge pressure of the second hydraulic pump B, only the supply pressurized oil from the first hydraulic pump A can be reliably caused to flow into the option merging oil passage **22**. On the other hand, the discharge flow rate of the second hydraulic pump B is supplied to the another of the other hydraulic actuators, thereby enabling to ensure good, combined operability between the option hydraulic actuator **13** and the other hydraulic actuators (the boom cylinder **8**, the slewing motor **11**).

(86) In the present embodiment configured as described above, a hydraulic control system for a hydraulic shovel **1** is provided with an option control circuit that is shared for a plurality of option hydraulic actuators **13** selectively mounted thereon; but the option control circuit is provided with an option control valve **60** that performs oil supply and discharge control to and from the option hydraulic actuator **13** in accordance with an operation of the option operation lever; the first, second hydraulic actuator oil passages **67**, **68** that connects the option control valve **60** and the option hydraulic actuator **13**; the first, second option pressure sensors **97**, **98** for detecting pressures of these first, second hydraulic actuator oil passages **67**, **68**, respectively; a compensator valve **61** disposed on upstream-side of the option control valve **60**, introduces the inlet-side pressure and the outlet-side pressure of the option control valve **60**, and operates in order to maintain a differential pressure between the introduced inlet-side pressure and the outlet-side pressure at a predetermined pressure K; and a controller **30** for controlling the operation of the option control valve **60**. Furthermore, the variable relief valve **65** capable of varying the relief setting pressure LP in response to control signals from the controller **30** is connected to the load pressure introducing oil passage **62** for introducing the pressure on the outlet-side of the option control valve **60** to the compensator valve **61**. By lowering the pressure of the load pressure introducing oil passage **62** down to the relief setting pressure LP by the variable relief valve **65** and introducing it to the compensator valve **61**, the inlet-side pressure of the option control valve **60** can be variably controlled in accordance with the change in the relief setting pressure LP of the variable relief valve **65**; but in the option control circuit, the switching positions of the option control valve **60** include the first, second load pressure relief positions R1, R2 that does not allow oil supply and discharge to be performed to and from the option hydraulic actuator **13**, but allows the pressures of the first, second hydraulic actuator oil passages **67**, **68** to flow into the load pressure introducing oil passage **62**. In case where the pressure in the first or second hydraulic actuator oil passages **67**, **68** exceeds the option upper limit pressure PU, which is preset depending on individual option hydraulic actuator **13**, during non-operation of an option operation lever, by switching the option control valve **60** to the first or second load pressure relief position R1 or R2 and controlling the relief setting pressure LP of the variable relief valve **65** so as to become lower than or equal to the option upper limit pressure PU, the pressure in the first or second hydraulic actuator oil passages **67**, **68** that has exceeded the option upper limit pressure PU can be released to the oil tank **12** via the option control valve **60**, the load pressure introducing oil passage **62**, the variable relief valve **65**.

(87) As a result, the upper limit pressure of pressurized oil, of which flow rate is controlled by the option control valve **60** and is supplied to the option hydraulic actuator **13**, can be variably controlled so as to become a pressure corresponding to an individual option hydraulic actuator **13**, by changing the relief setting pressure LP of the variable relief valve **65** connected to the load pressure introducing oil passage **62** in response to control signal from the controller **30**; and therefore compared to the option control circuit that is configured to dispose variable relief valves respectively in a pair of the first, second hydraulic actuator oil passages **67**, **68** extending from the option control valve **60** to the option hydraulic actuator **13**, and to variably control the upper limit pressure of the supply pressurized oil to the option hydraulic actuator **13**, thereby enabling reduction of the variable relief valves, and contribution to cost reduction. Besides, in this option control circuit, in case where a pressure in the first, second hydraulic actuator oil passages **67**, **68**

exceeds the option upper limit pressure PU during non-operation of the option operation lever, the pressure can be released to the oil tank **12** via the option control valve **60**, the load pressure introducing oil passage **62**, the variable relief valve **65**. Accordingly, even when the variable relief valves are not provided in the first, second hydraulic actuator oil passages **67**, **68**, the pressure in the first, second hydraulic actuator oil passages **67**, **68** in a non-operating state of the option operation lever will be able to be controlled so as to become less than or equal to the option upper limit pressure PU which is set corresponding to individual option hydraulic actuator. Besides, this control is a control performed utilizing the option control valve **60** for performing the oil supply and discharge control of the option hydraulic actuator **13** in accordance with the operation of the operation lever, and the variable relief valve **65** used for variable control of the supply pressure to the option hydraulic actuator **13**, thereby enabling to achieve common use of parts without the need for separate dedicated members.

(88) Moreover, the hydraulic control system includes other hydraulic actuators (the boom cylinder **8**, the stick cylinder **9**, the bucket cylinder **10**, slewing motor **11**) provided in the hydraulic shovel **1** other than the option hydraulic actuator **13**, and the first, second hydraulic pumps A, B serving as hydraulic supply sources for these other hydraulic actuators; but the option hydraulic actuator **13** uses either one or both of the first, second hydraulic pumps A, B as hydraulic supply sources; as well as the option control circuit includes the first, second option supply oil passages **17**, **21** connected to the first, second hydraulic pumps A, B, respectively, and the option merging oil passage **22** that allows these first, second option supply oil passages **17**, **21** to be merged therein, and the compensator valve **61** and the option control valve **60** are disposed in the option merging oil passage **22**. Consequently, even if the option hydraulic actuator **13** uses only the first hydraulic pump A, only the second hydraulic pump B, or both the hydraulic pumps A, B, whichever the case may be, as the hydraulic supply sources, one option control Oil supply and discharge control to and from the option hydraulic actuator **13** can be performed only by one option control valve **60**, thereby enabling contribution to reduction in the number of parts.

(89) Moreover, the hydraulic control system includes the first, second bleed valves **75**, **76** for controlling bleed flow rate that flows into the oil tank **12** from the first, second hydraulic pumps A, B respectively in accordance with control signals output from the controller **30**, and is configured such that the discharge pressure of the first, second hydraulic pumps A, B is controlled by the bleed flow rate control by the first, second bleed valves **75**, **76**; but in this case, the controller **30**, when the option hydraulic actuator **13** uses only either one of the first, second hydraulic pumps A, B as the hydraulic supply source, causes the discharge pressure of the one hydraulic pumps acting as the hydraulic supply source to be higher than the discharge pressure of the another hydraulic pump not acting as the hydraulic supply source, and when the option hydraulic actuator **13** uses both the first, second hydraulic pumps A, B as the hydraulic supply sources, performs bleed flow rate control so that the discharge pressures of the second hydraulic pumps A, B will be equalized. As a result, when the option hydraulic actuator **13** uses only one of the first, second hydraulic pumps A, B as the hydraulic supply source, the supply pressurized oil from the one hydraulic pump acting as the hydraulic supply source can be caused preferentially to flow into the option merging oil passage **22**, and the supply pressurized oil from the another hydraulic pump not acting as the hydraulic supply source will not flow into the option merging oil passage **22**; and when the option hydraulic actuator **13** uses both of the hydraulic pumps A, B as the hydraulic supply source, the supply pressurized oil from both of the hydraulic pumps A, B is adapted to be merged into the option merging oil passage **22**. Therefore, even if the first, second option supply oil passages **17**, **21** are not provided with valves for opening and closing the oil passages **17**, **21** respectively, in both cases where either one of the first, second hydraulic pumps A, B acts as the hydraulic supply source, and where both the first, second hydraulic pumps act as the hydraulic supply sources, only the supply pressurized oil from the hydraulic pump acting as the hydraulic supply source can be supplied to the option merging oil passage **22**, thereby enabling reduction of the number of parts, and contribution to cost

reduction. In addition, when the option hydraulic actuator **13** uses either one of the first, second hydraulic pumps A, B as the hydraulic supply source, and the other hydraulic actuators use the another hydraulic pump as the hydraulic supply sources, the supply pressurized oil from the one hydraulic pump flows into the option merging oil passage **22** and is used only for the option hydraulic actuator **13**; on the other hand, the supply pressurized oil from the another hydraulic pump does not flow into the option merging oil passage **22**, and the entire amount of the supply pressurized oil will be used only for the other hydraulic actuators, thereby enabling to ensure good, combined operability between the option hydraulic actuator **13** and the other hydraulic actuators.

INDUSTRIAL APPLICABILITY

(90) The present invention, in a working machine such as a hydraulic shovel, can be utilized for a hydraulic control system when an option hydraulic actuator is mounted on the working machine.

Claims

1. A hydraulic control system in a working machine equipped with an option control circuit that is shared for a plurality of option hydraulic actuators that is selectively mounted in the working machine, the option control circuit further comprising: an option control valve for performing oil supply and discharge control to and from an option hydraulic actuator in accordance with an operation of an option operation lever; a pair of actuator oil passages that connect the option control valve and the option hydraulic actuator; a pressure sensor for detecting a pressure of the actuator oil passages; a pressure compensating valve which is disposed on an upstream-side of the option control valve and is actuated in order to maintain a differential pressure, by an inlet-side pressure and an outlet-side pressure of the option control valve being introduced, between the introduced inlet-side pressure and outlet-side pressure at a predetermined pressure; and a control device for controlling an actuation of the option control valve; wherein the option control circuit is configured such that, by connecting a variable relief valve capable of varying a relief setting pressure in response to control signals from the control device, to a load pressure introducing oil passage that introduces the outlet-side pressure of the option control valve to the pressure compensating valve, and lowering a pressure of the load pressure introducing oil passage down to the relief setting pressure by the variable relief valve and introducing the pressure of the load pressure introducing oil passage to the pressure compensating valve, a pressure of the inlet-side of the option control valve can be variably controlled in accordance with change of the relief setting pressure of the variable relief valve; wherein the option control circuit is configured such that, by providing a load pressure relief position at which oil supply and discharge to and from the option hydraulic actuator is not performed, but the pressure of the actuator oil passages is allowed to flow into the load pressure introducing oil passage, in a switching position of the option control valve, and by switching the option control valve to the load pressure relief position, when the pressure in the actuator oil passages exceeds an upper limit pressure that is preset depending on individual optional hydraulic actuator during non-operation of the option operation lever; as well as by controlling the relief setting pressure of the variable relief valve so as to be less than or equal to the upper limit pressure, the pressure in the actuator oil passages exceeding the upper limit pressure is released to an oil tank via the option control valve, the load pressure introducing oil passage, and the variable relief valve.

2. The hydraulic control system in the working machine according to claim 1, wherein the hydraulic control system in the working machine comprises first, second hydraulic pumps serving as hydraulic supply sources for other hydraulic actuators to be provided in the working machine other than the option hydraulic actuator, wherein the option hydraulic actuator uses either one or both of these first, second hydraulic pumps as the hydraulic supply sources; as well as wherein the option control circuit comprises first, second option supply oil passages connected to the first, second hydraulic pumps respectively, and an option merging oil passage that allows these first,

second option supply oil passages to be merged therein, wherein the pressure compensating valve and the option control valve are disposed in the option merging oil passage.

3. The hydraulic control system in the working machine according to claim 2, wherein the hydraulic control system in the working machine is configured to comprise first, second bleed valves for controlling a bleed flow rate that flows into an oil tank from the first, second hydraulic pumps in response to control signals output from the control device, and to control discharge pressures of the first, second hydraulic pumps in accordance with bleed flow rate control by the first, second bleed valves; as well as the control device performs bleed flow rate control so that, in case where the option hydraulic actuator uses either one of these first, second hydraulic pumps as the hydraulic supply sources, the discharge pressure of one hydraulic pump serving as the hydraulic supply source will be set higher than discharge pressure of the another hydraulic pump not serving as the hydraulic supply source; in case where the option hydraulic actuator uses both the first, second hydraulic pumps as the hydraulic supply sources, the discharge pressures of the first, second hydraulic pumps will be equalized.
