

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410782
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Brown; Andrew Benjamin Simpson et al.

Actuator assembly

Abstract

An actuator assembly comprising: a support structure comprising a first friction surface; a movable part comprising a second friction surface engaging the first friction surface; one or more SMA wires arranged, on contraction, to move the movable part relative to the support structure to any position within a range of movement; a biasing arrangement arranged to bias the first and second friction surfaces against each other with a normal force, thereby generating a static frictional force that constrains the movement of the movable part relative to the support structure at any position within the range of movement when the one or more SMA wires are not contracted; wherein the one or more SMA wires are arranged, on contraction, to reduce the normal force between first and second friction surfaces.

Inventors:	Brown; Andrew Benjamin Simpson (Cambridge, GB), Bunting; Stephen Matthew (Cambridge, GB), Eddington; Robin (Cambridge, GB), Hart; Oliver (Cambridge, GB), Howarth; James (Cambridge, GB)
Applicant:	CAMBRIDGE MECHATRONICS LIMITED (Cambridge, GB)
Family ID:	84370600
Assignee:	CAMBRIDGE MECHATRONICS LIMITED (Cambridge, GB)
Appl. No.:	18/713045
Filed (or PCT Filed):	November 24, 2022
PCT No.:	PCT/GB2022/052977
PCT Pub. No.:	WO2023/094813
PCT Pub. Date:	June 01, 2023

Prior Publication Data

Foreign Application Priority Data

GB	2116960	Nov. 24, 2021
GB	2116961	Nov. 24, 2021

Publication Classification

Int. Cl.: F03G7/06 (20060101); G03B5/04 (20210101); G03B13/36 (20210101)

U.S. Cl.:

CPC F03G7/06143 (20210801); F03G7/0665 (20210801); G03B5/04 (20130101); G03B13/36 (20130101); G03B2205/0076 (20130101)

Field of Classification Search

CPC: H02N (11/00); F03G (7/06)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2022/0059712	12/2021	Barbot	N/A	H02S 30/20

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3650691	12/2019	EP	N/A
2020/120997	12/2019	WO	N/A
2020/183360	12/2019	WO	N/A
2021/130481	12/2020	WO	N/A

OTHER PUBLICATIONS

Great Britain Search Report and Written Opinion received for GB Application No. 2116960.2, mailed on Apr. 7, 2022, 6 pages. cited by applicant

Great Britain Search Report and Written Opinion received for GB Application No. 2116961.0, mailed on Apr. 7, 2022, 3 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/GB2022/052977, mailed on Jan. 31, 2023, 9 pages. cited by applicant

Primary Examiner: Mian; Shafiq

Attorney, Agent or Firm: Van Hoven PC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is a national stage application under 35 U.S.C. § 371 of International Application No. PCT/GB2022/052977, filed Nov. 24, 2022, which claims priority of GB Patent Applications 2116960.2, filed Nov. 24, 2021, and 2116961.0, filed Nov. 24, 2021, the disclosures of each of which are hereby incorporated by reference herein in their entireties.

FIELD

(2) The present application generally relates to an actuator assembly, and in particular to a shape memory alloy (SMA) actuator assembly.

BACKGROUND

(3) Shape memory alloy (SMA) actuators are used in camera assemblies for effecting a range of motions of a lens carriage or an image sensor. For example, WO 2013/175197 A1 describes a camera with an SMA actuator assembly having SMA wires that are configured to, on contraction, move the movable part in directions perpendicular to an optical axis to provide optical image stabilization (OIS). This actuator assembly includes flexure arms that provide a lateral biasing force that biases a lens assembly towards a central position. However, in some cases where it is desirable to hold the lens assembly at a given position, such a known actuator assembly would have relied on continuously energising the SMA wires over a prolonged period of time. Such an arrangement not only consumes energy during the holding period, but the stability of the lens carriage may also be susceptible to sudden movements and other external factors.

(4) WO2020/120997 A1 discloses various means for retaining a lens carriage at a given position by friction. In particular, a lens carriage is biased against a surface of a support structure by a biasing element to hold the lens carriage in any given position when the SMA wires are not energised. Upon actuation, the SMA wires act against the biasing element to reduce frictional forces, thereby enabling the lens carriage to be driven to a new position.

SUMMARY

(5) The present invention provides various means for retaining a moveable part at the desired position when the SMA wires in an SMA actuator assembly are not energised, thereby eliminating the need for continuously energising the SMA actuator as required by known techniques.

(6) According to the present invention, there is provided an actuator assembly comprising: a support structure comprising a first friction surface; a movable part comprising a second friction surface engaging the first friction surface; one or more SMA wires arranged, on contraction, to move the movable part relative to the support structure to any position within a range of movement; a biasing arrangement arranged to bias the first and second friction surfaces against each other with a normal force, thereby generating a static frictional force that constrains the movement of the movable part relative to the support structure at any position within the range of movement when the one or more SMA wires are not contracted, wherein the biasing arrangement is comprised by the movable part or by the support structure so as to move with the movable part or remain static relative to the support structure, and is arranged to apply the normal force only in a direction perpendicular to the range of movement at any position within the range of movement; wherein the one or more SMA wires are arranged, on contraction, to reduce the normal force between first and second friction surfaces.

(7) The frictional force constrains movement of the movable part relative to the support structure when the SMA wires are not energized. The movable part may be held in position without power consumption, thus reducing the overall power consumption of the actuator assembly. Upon contraction of the SMA wires, the normal force between first and second friction surfaces reduces, and so the frictional force reduces as well. The reduction in frictional force assists in overcoming the frictional force such that the movable part may be moved by the SMA wires. The biasing arrangement is comprised by the movable part or support structure, such that the normal force is applied only in a direction perpendicular to the range of movement at any position within the range

of movement. This ensures that the biasing arrangement does not oppose the stresses in the SMA wires used to move the movable part.

(8) According to the present invention, there is also provided an actuator assembly comprising: a support structure comprising a first friction surface; a movable part comprising a second friction surface engaging the first friction surface; a bearing arrangement for bearing movement of the movable part relative to the support structure within a range of movement; one or more SMA wires arranged, on contraction, to move the movable part relative to the support structure to any position within the range of movement; a biasing arrangement arranged to bias the first and second friction surfaces against each other with a normal force, thereby generating a static frictional force that constrains the movement of the movable part relative to the support structure at any position within the range of movement when the one or more SMA wires are not contracted, wherein the one or more SMA wires are arranged, on contraction, to lift the movable part off the first friction surface such that the movable part bears on the bearing arrangement.

(9) The frictional force constrains movement of the movable part relative to the support structure when the SMA wires are not energized. The movable part may be held in position without power consumption, thus reducing the overall power consumption of the actuator assembly. Upon contraction of the SMA wires, the movable part lifts off the first friction surface, thus eliminating the frictional force that keeps the movable part in position when the SMA wires are not powered. The movable part may thus more readily be moved by the SMA wires within the range of movement. After lift-off from the first friction surface, the movable part bears only on the bearing arrangement, thus ensuring that movement of the movable part is guided by the bearing arrangement. This makes controlled movement of the movable part by the SMA wires more accurate and reliably compared to a situation in which the movable part is suspended solely by the SMA wires after lift-off.

(10) According to the present invention, there is also provided an actuator assembly comprising a support structure comprising a first friction surface; a movable part comprising a second friction surface engaging the first friction surface; one or more SMA wires arranged, on contraction, to move the movable part relative to the support structure to any position within a range of movement; a biasing arrangement arranged to bias the first and second friction surfaces against each other with a normal force, thereby generating a static frictional force that constrains the movement of the movable part relative to the support structure at any position within the range of movement when the one or more SMA wires are not contracted, wherein the one or more SMA wires are arranged, on contraction, to reduce the normal force between first and second friction surfaces.

(11) According to the present invention, there is also provided an actuator assembly comprising a support structure comprising a first friction surface; a movable part comprising a second friction surface engaging the first friction surface; a helical bearing arrangement supporting the movable element on the support structure and arranged to guide helical movement of the movable element with respect to the support structure around a helical axis, wherein the helical bearing arrangement is formed by the first and second friction surfaces; and one or more SMA wires arranged, on contraction, to drive rotation of the movable element around the helical axis which the helical bearing arrangement converts into said helical movement; and biasing arrangement configured to load the helical bearing arrangement, thereby biasing the first and second friction surfaces against each other with a normal force and generating a static frictional force that constrains the movement of the movable part relative to the support structure at any position within the range of movement when the one or more SMA wires are not contracted, wherein the one or more SMA wires are arranged, on contraction, to reduce the normal force between first and second friction surfaces.

(12) Further aspects of the present invention are set out in the dependent claims and clauses below, as well as in the detailed description.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Certain embodiments of the present invention will now be described, by way of example only, with reference to the accompanying drawings, in which:
- (2) FIG. 1 is a schematic side view of a prior art actuator assembly;
- (3) FIGS. 2A-D are schematic side views of actuator assemblies according to embodiments of the present invention, in which the biasing arrangement is comprised by the movable part;
- (4) FIGS. 3A-C are schematic side views of actuator assemblies according to embodiments of the present invention, in which the biasing arrangement is comprised by the support structure;
- (5) FIGS. 4A-D are schematic side views of actuator assemblies according to embodiments of the present invention, in which an endstop is provided;
- (6) FIGS. 5A-D are schematic side views of further embodiments of the actuator assembly;
- (7) FIGS. 6A-C are schematic views of an embodiment of the present invention, in which the actuator assembly may act as an autofocus (AF) actuator assembly in a camera apparatus;
- (8) FIGS. 7A and B are schematic views of another embodiment of the present invention, in which the actuator assembly may act as an autofocus (AF) actuator assembly in a camera apparatus;
- (9) FIGS. 8A and 8B are partial schematic views of further embodiments of the present invention;
- (10) FIGS. 9A-D are schematic views of an actuator assembly that may act as an autofocus (AF) actuator assembly in a camera apparatus; and
- (11) FIGS. 10A-D are schematic views of an actuator assembly that may act as an optical image stabilization (OIS) actuator assembly in a camera apparatus;
- (12) FIGS. 11A-B are schematic views of another actuator assembly that may act as an optical image stabilization (OIS) actuator assembly in a camera apparatus; and
- (13) FIGS. 12A-B are schematic views of another actuator assembly that may act as an optical image stabilization (OIS) actuator assembly in a camera apparatus.

DETAILED DESCRIPTION

- (14) The present invention provides various means for retaining a movable part of an actuator assembly at a desired position when the SMA wires are not energised, thereby eliminating the need for continuously energising the SMA wires as required by known techniques.
- (15) FIG. 1 schematically depicts a schematic diagram of an actuator assembly **100** as disclosed in WO2020/120997 A1. The actuator assembly **100** includes a static part **101** and a movable part **104**. The movable part **104** is movable with respect to the static part **101**. The static part **101** includes a body **102** and a surface **106** held in a fixed position with respect to the body **102**, for example by a connecting portion (not shown). A gap is provided between the body **102** and the surface **106**.
- (16) The movable part **104** is located in the gap between the body **102** and the surface **106**. The movable part **104** is capable of movement relative to the static part **101** across the surface **106**. In this example, the movable part **104** is capable of movement across the surface **106** in any direction in two dimensions.
- (17) The actuator assembly **100** also includes a spring **110** connected between the static part **101** and the movable part **104** by being connected at one end to the body **102** and at the other end to the movable part **104**. The spring **110** extends orthogonally to the surface **106** in this example, although that is not essential. The spring **110** is held in compression and is therefore a resilient biasing element that acts as a biasing arrangement biasing the movable part **104** into contact with the surface **106**. This generates a reaction between the movable part **104** and the surface **106**, as well as generating frictional forces between the movable part **104** and the surface **106**.
- (18) The first actuator assembly **100** also includes two SMA wires **108** connected at one end to the body **102** and at the other end to the movable part **104**. Each SMA actuator wire **108** is inclined at an acute angle α of greater than 0° with respect to the surface **106** so as to apply a force, on

contraction of the SMA actuator wire **108**, with a component normal to the surface **106** that biases the movable part **104** away from the surface **106** and with a component parallel to the surface **106**. A control circuit **200** in use applies drive signals to the SMA wires **108**

(19) In the actuator assembly **100** of FIG. **1**, the spring **110** is connected between the static part **101** and the movable part **102**. The spring **110** may thus give rise to a lateral force, i.e. a force parallel to the direction of movement, upon movement of the movable part **102** away from an initial, central position. Such a lateral force may make accurate and reliable control of the movement of the movable part **102** more complex. The lateral force may also oppose frictional forces between the movable part **102** and the static part **101**.

(20) In instances in which the movable part **102** is lifted out of contact with the surface **106** by the SMA wires **108**, the movable part **102** is held solely by the SMA wires **108** and the spring **110**. Stable positioning of the movable part **102** is difficult to achieve. Control of the SMA wires **108** so as to reliably and accurately move the movable part **102** while out of contact with the surface **106** is complex.

(21) Embodiments of the present invention provide improvements to the prior art actuator assembly **100** of FIG. **1**.

(22) Overview of the Actuator Assembly

(23) Embodiments of the present invention are described below with reference to the schematic views of FIGS. **2** to **5**.

(24) The actuator assembly comprises a support structure **10** and a movable part **20**. The movable part **20** is movable relative to the support structure **10**. In general, the support structure **10** and the movable part **20** may be referred to as a first part and a second part respectively, and the terms support structure **10** and movable part **20** are used herein for purely illustrative purposes. The support structure **10** may also be referred to as a static part. In this regard, the support structure **10** is used herein as a reference structure. Movement of any components of the actuator assembly **1** is described relative to the support structure **10**, unless otherwise indicated. However, in general the support structure **10** may itself be movable, for example within a larger device into which the actuator assembly **1** is incorporated. In some embodiments, the support structure **10** may be made up of components that are movable relative to each other.

(25) The movable part **20** is movable relative to the support structure **10** within a range of movement. The range of movement may define movement in any number of degrees of freedom (DOF). Preferably, the range of movement defines movement in up to three DOFs, for example one or three DOFs. The movable part **20** may be movable relative to the support structure **10** in a movement plane within the range of movement, and/or along a movement axis within the range of movement, for example.

(26) The actuator assembly **1** comprises one or more SMA wires **40**. Preferably, the actuator assembly **2** comprises at least two SMA wires **40**. The SMA wires **40** are arranged, on contraction, to move the movable part **20** relative to the support structure **10**. The SMA wires **40** move the movable part **20** to any position within the range of movement. For example, the SMA wires **40** may move the movable part **20** in one DOF, in two DOFs or in three DOFs. Preferably, the actuator assembly **1** comprises at least two opposed SMA wires **40**, wherein one of the two SMA wires **40** is arranged to move the movable part **20** in one direction within the range of movement, and the other of the two SMA wires **40** is arranged to move the movable part **20** in another, opposite, direction within the range of movement.

(27) Each of the SMA wires **40** may be connected at one end to the support structure **10** by a corresponding coupling element (not shown) and at the other end to the movable part **20** by a corresponding coupling element (not shown). The coupling elements may be crimps, for example. The coupling elements may provide both mechanical and electrical connection to the SMA wires **40**. In general, any other mechanisms or arrangements for transferring stresses in the SMA wires **40** to the movable part **20** so as to drive movement of the movable part **20** may be used.

(28) The SMA wires **40** may each be electrically connected (via the coupling elements) to a control circuit (not shown) which may be implemented in an integrated circuit (IC) chip, for example. The control circuit in use applies drive signals to the SMA wires **40** which resistively heat the SMA wires **40**, causing them to contract. The plural SMA wires **40** may be driven independently or otherwise. The control circuit may also measure the resistance of the SMA wires **40**, and use the measured resistance to calculate/determine the position of the movable part **20**. In general, however, the SMA wires **40** may be heated so as to contract by any other suitable means, such as via an external heat source, radiative heating or inductive heating.

(29) In this regard, the range of movement comprises any movement of the movable part **20** relative to the support structure **10** that can be achieved by selective contraction of the arrangement of SMA wires **40**. The range of movement may be defined as the movement achievable by selective contraction of the SMA wires **40**. Optionally, the range of movement may be limited by endstops between support structure **10** and movable part **20**, in particular when contraction of the SMA wires **40** causes an endstop between support structure **10** and movable part to engage. The range of movement may also be affected, at least in part, by a bearing arrangement defining the DOFs in which the movable part **20** may be moved.

(30) The range of movement may thus be defined as the collection of locations and orientations to which the movable part **20** may be moved relative to the support structure **10** by the SMA wires **40**. The range of movement may be affected by one or more of i) the arrangement of SMA wires **40** as well as control for driving the SMA wires **40**, ii) the provision of endstops between movable part **20** and support structure **10** that limit the range of movement, iii) the provision of bearing arrangements that define the DOFs of movement of the movable part **20** relative to the support structure **10**. In some embodiments, the range of movement may define movement of the movable part **20** relative to the support structure **10** in a movement plane (in 2 or 3 DOFs) or along a movement path (in 1 DOF).

(31) Friction Surfaces for Zero Hold Power

(32) The support structure **10** comprises a first friction surface **10f**. The movable part **20** comprises a second friction surface **20f**. The second friction surface **20f** of the movable part **20** engages the first friction surface **10f** of the support structure **10**. The first and second friction surfaces **10f**, **20f** may engage each other throughout the range of movement. So, in normal use (i.e. under contraction of the SMA wires **40** for moving the movable part **20**), the first and second friction surfaces **10f**, **20f** may remain in engagement with one another.

(33) The actuator assembly **1** further comprises a biasing arrangement **30**. The biasing arrangement **30** is arranged to bias the first and second friction surfaces **10f**, **20f** against each other. The biasing arrangement **30** applies a biasing force between support structure **10** and movable part **20**. The biasing force comprises a component that is perpendicular to the first and second friction surfaces, and so the biasing arrangement **30** applies a normal force N between support structure **10** and movable part **20**. The normal force N is perpendicular to the range of movement and perpendicular to the friction surfaces **10f**, **20f**. Preferably, the biasing arrangement **30** applies the biasing force in the direction perpendicular to the range of movement and perpendicular to the friction surfaces **10f**, **20f**. The biasing force of the biasing arrangement may be equal to the normal force N . So, the biasing force may not have a component parallel to the range of movement, and thus not affect movement of the movable part **20** relative to the support structure **10**.

(34) This normal force N generates or gives rise to a static frictional force F between the first and second friction surfaces **10f**, **20f**. The static frictional force F constrains movement of the movable part **20** relative to the support structure **10**, in particular when the SMA wires **40** are not contracted. Such movement is constrained at any position and/or orientation within the range of movement of the movable part **20** relative to the support structure **10**.

(35) The SMA wires **40** may be used to move the movable part **20** to any position within the range of movement of the movable part **20** relative to the support structure **10**. Upon energising (i.e.

when drive signals are applied to the SMA wires by the control circuit), the SMA wires **40** contract and apply an actuating force for moving the movable part **20** in respective directions. The actuating force is sufficient to overcome the frictional forces at the friction surfaces **10f**, **20f** (in particular after reduction or elimination of the frictional forces due to SMA wire contraction), in order to drive relative movement between the movable part **20** and the support structure **10**. Upon ceasing power supply to the SMA wires **40**, and so when stopping contraction of the SMA wires **40**, the movable part **20** remains at its position within the range of movement due to the frictional forces between the first and second friction surfaces **10f**, **20f**. In this state, the movable part **20** is retained in position with zero power consumption by the actuator assembly **1**, so the actuator assembly **1** may be referred to as a zero hold power actuator assembly, as may the other actuator assemblies disclosed herein. The movable part **20** is thus held in place without requiring power supply to the SMA wires **40**, reducing the power consumption of the actuator assembly compared to a situation in which the SMA wires **40** need to be powered to hold the movable part **20** in place.

(36) The SMA wires **40** are arranged, on contraction, to reduce the normal force N between first and second friction surfaces **10f**, **20f**. Put another way, the composite force acting on the movable part **20** due to stresses in the SMA wires **40** has a component that is parallel to and opposite in direction to the normal force N . The stresses in the SMA wires **40** affect (in particular reduce) the normal force N . In some embodiments, equal stresses (or tensions or strains) in the SMA wires **40** may reduce the normal force N without moving the movable part **20**. Unequal strains in the SMA wires **40** may result in movement of the movable part **20**.

(37) Such an arrangement in which the normal force N is reduced by the SMA wires **40** allows selective reduction in the frictional forces by appropriate contraction of the SMA wires **40**. This reduction of the frictional forces assists with the overcoming of the frictional forces to allow movement of the movable part **20** within the range of movement. So, the stress in the SMA wires **40** required to move the movable part **20** may be reduced compared to a situation in which the frictional forces are not reduced. Furthermore, the frictional forces in the absence of contraction of the SMA wires **40** may be designed to be higher compared to a situation in which the frictional forces cannot be reduced, thus reducing the risk of inadvertent movement of the movable part **20** in the absence of SMA wire contraction.

(38) Characteristics of the Frictional Forces

(39) As described above, the normal force N generates or gives rise to a static frictional force F between the first and second friction surfaces **10f**, **20f**. The static frictional force F constrains movement of the movable part **20** relative to the support structure **20**. The magnitude of the static frictional force F is thus large enough to constrain such movement. The magnitude of the static frictional force F is proportional to the normal force N and the coefficient of static friction μ , such that $F = \mu * N$. The static frictional force F may be increased by increasing the normal force N , which is achieved by appropriate design of the biasing arrangement **30**, and/or by increasing the coefficient of static friction, which is achieved by appropriate design of the friction surfaces **10f**, **20f**.

(40) The magnitude of the static frictional force is great enough to constrain movement of the movable part, in particular before reduction due to contraction of the SMA wires **40**. The ratio of the static frictional force to weight of the movable part may be greater than 1. So, the magnitude of the static frictional force is greater than the weight of the movable part. This ensures that movement of the movable part is constrained by the frictional force even when the actuator assembly **1** is turned on its side, for example. The weight of the movable part is considered to be equal to the mass of the movable part times earth's average gravitational acceleration (9.81 m/s^2). Preferably, the ratio of the static frictional force to the weight of the movable part is greater than 3, further preferably greater than 5, further preferably greater than 10. This ensures that movement of the movable part **20** is constrained even when the actuator assembly **1** accelerates. A larger ratio of static frictional force to weight of the movable part reduces the risk of movement of

the movable part due to acceleration (e.g. impact events) of the actuator assembly **1**. Higher frictional forces may also in some situations compensate for any lateral biasing forces of the biasing arrangement **30**, for example when the biasing arrangement is connected between the support structure **10** and the movable part **20** (as in FIG. 4D).

(41) The SMA wires may be arranged to reduce the normal force upon contraction. In some embodiments, the normal force between first and second friction surfaces is reduced by at least 10%, preferably at least 20%, most preferably by at least 50%. The normal force N may be reduced by at least 90%. In some embodiments, the normal force N is reduced by 100%, i.e. the movable part **20** lifts off the first friction surface **10f**.

(42) Similarly, the static frictional force F between first and second friction surfaces may be reduced by at least 10%, preferably at least 20%, most preferably by at least 50%. The static frictional force F may be reduced by at least 90%. In some embodiments, the static frictional force F is reduced by 100%, i.e. the movable part **20** lifts off the first friction surface **10f**. The overall frictional force between movable part **20** and support structure **10** may thus be reduced, for example by at least 10%, at least 20%, at least 50%, or at least 90%. Some residual frictional forces may remain in any bearing arrangement (if provided), even upon lift-off of the movable part from the first friction surface **10f**.

(43) The magnitude of the static frictional force is low enough to allow the SMA wires **40** to overcome the static frictional force so as to move the movable part **20** relative to the support structure **10**, in particular after reduction due to contraction of the SMA wires **40**. So, the magnitude of the reduced static frictional force is less than the force applied to the movable part **20** by the SMA wires **40** in the movement direction. The static frictional force may be less than 50%, preferably less than 20%, further preferably less than 10% of the force generated by a stress of 200 MPa in the SMA wires **40** for moving the movable part **20** relative to the support structure **10**.

(44) The coefficient of static friction between the first and second friction surfaces **10f**, **20f** directly affects the magnitude of the static frictional force F . The coefficient of static friction may be modified by appropriately processing or selecting the material of the first and second friction surfaces **10f**, **20f**. The coefficient of static friction may be in the range between 0.05 and 0.6. Preferably, the coefficient of static friction is in the range between 0.1 and 0.4. In general, lower coefficients of static friction can be compensated for by higher normal forces N imparted by the biasing arrangement **30**.

(45) The requirements for the static frictional forces F between first and second friction surfaces **10f**, **20f** have been described above. These requirements may ensure that the movable part **20** remains in place relative to the support structure **10** once in position. Preferably, the same requirements apply to the dynamic or kinetic frictional forces between first and second friction surfaces **10f**, **20f**, thus ensuring that the movable part **20** rapidly comes to rest after being moved by the SMA wires **40**. For this purpose, the ratio of the dynamic frictional force to weight of the movable part, the relation between dynamic frictional force and forces due to the SMA wires **40**, and the coefficient of dynamic friction between the first and second friction surfaces **10f**, **20f** may be as described in relation to the static frictional force F . Preferably, the static friction coefficient between the first and second friction surfaces **10f**, **20f** is substantially equal (e.g. varying by less than 5%, preferably less than 1%) to the dynamic friction coefficient between the first and second friction surfaces **10f**, **20f**. This makes the forces acting on the movable part more predictable, reducing the complexity of movement control.

(46) Biasing Arrangements

(47) FIGS. 2A-D and 3A-C schematically depict embodiments of the actuator assembly **1**. Compared to the prior art actuator assembly **100** of FIG. 1, in which the spring **110** is connected between static part **101** and movable part **102**, the biasing arrangement **30** of the depicted actuator assemblies **1** is comprised by the movable part **20** in FIGS. 2A-D or by the support structure **10** in FIGS. 3A-C. So, the biasing arrangement **30** moves with the movable part **20** in FIGS. 2A-D or

remains static relative to the support structure **10** in FIGS. 3A-C.

(48) As such, the biasing arrangement **30** is arranged to apply the normal force N only in a direction perpendicular to the range of movement at any position within the range of movement. Compared to the spring **110** of the prior art actuator assembly **100** of FIG. **1**, no lateral force acting parallel to the range of movement is created by the biasing arrangement **30** of the embodiments of FIGS. **2** and **3** when moved away from an initial, central position. As such, there is no lateral force opposing the frictional forces between the movable part **20** and support structure **10**, reducing the risk of inadvertent movement of the movable part **20** in the absence of contraction of the SMA wires **40**. Controlled and accurate movement of the movable part **20** relative to the support structure **10** may be made simpler due to the absence of a varying lateral force acting on the movable part **20**.

(49) FIGS. 2A-D depict embodiments of the present invention in which the biasing arrangement **30** forms part of the movable part **20**. The movable part **20** comprises the biasing arrangement **30**. The biasing arrangement **30** moves (in its entirety) with the movable part **20** relative to the support structure. In such an arrangement, it is easier to ensure that the biasing force of the biasing arrangement **30** acts in a direction perpendicular to the range of movement. Although the support structure **10** is depicted in the figures as two parts **10** for ease of illustration, the support structure **10** in practice may be one part, i.e. the two parts **10** depicted in FIGS. 2A-C are connected.

(50) As shown, the movable part **20** comprises two portions **20a**, **20b**. The biasing arrangement **30** applies a biasing force between the two portions **20a**, **20b**. The two portions **20a**, **20b** may be coupled via the biasing arrangement **30**. One end of the biasing arrangement **30** may be connected to one of the two portions **20a**, **20b**, and the other end of the biasing arrangement **30** may be connected to the other of the two portions **20a**, **20b**.

(51) In the embodiment of FIG. 2A, for example, a bearing arrangement **50** is provided between one of the portions **20b** and the support structure **10**. The SMA wires **40** are connected between the other of the portions **20a** and the support structure **10**. The second friction surface **20f** is provided on the other of the portions **20a**. The SMA wires **40** are angled away from the friction surfaces **10f**, **20f**, and arranged to move the movable part in opposite directions. So, upon equal contraction of (or equal tension in) the SMA wires **40**, the normal force N between first and second friction surfaces **10f**, **20f** is reduced. A difference in contraction between the SMA wire **40** moves the movable part **20** relative to the support structure **10** on the bearing arrangement **50**.

(52) FIG. 2B shows another embodiment of the present invention in which the biasing arrangement **30** is part of the movable part **20**. Here, the biasing arrangement **30** is a resilient element, in particular comprising flexures. In the depicted embodiment, one portion **20b** of the movable part **20** is a body to which the flexures are connected, and the other portion of the movable part **20** is formed integrally with the flexures. In general, either one or both of the portions of the movable part **20** may be formed integrally with the biasing arrangement **30**, be it in the form of a resilient element (such as one or more flexures) or any other form. As described in relation to FIG. 2A, a bearing arrangement **50** is provided between one portion **20b** of the movable part **20** and the support structure **10**. The SMA wires **40** are connected between the other portion **20a** of the movable part **20** and the support structure **10**. The second friction surface **20f** is formed on the other portion **20a**. So, the second friction surface **20f** is formed integrally with the biasing arrangement **30** (in the form of the flexures).

(53) FIG. 2C shows another embodiment of the present invention in which the biasing arrangement **30** is part of the movable part **20**. The movable part **20** comprises two portions **20a**, **20b**. One of the SMA wires **40** is connected to one portion **20a**, and another of the SMA wires **40** is connected to the other portion **20b**. The second friction surface **20f** is formed between the support structure **10** and both portions of the movable part **20**. Upon equal contraction of (or equal tension in) the SMA wires **40**, the normal force N acting between the first and second friction surfaces **10f**, **20f** is reduced. A difference in contraction between the SMA wire **40** moves the movable part **20** relative

to the support structure. In the embodiment of FIG. 2C, the friction surfaces **10f**, **20f** act as a bearing arrangement **50**, in particular a plain bearing, for guiding movement of the movable part **20** relative to the support structure **10**.

(54) FIG. 2D shows another embodiment of the present invention in which the biasing arrangement **30** is part of the movable part **20**. Compared to the embodiments shown in FIGS. 2A-C, the biasing arrangement **30** is a magnetic biasing arrangement **30**. The magnetic biasing arrangement **30** provides a magnetic biasing force for biasing the first friction surface **10f** against the second friction surface **20f**. The magnetic biasing arrangement comprises a magnet (preferably a permanent magnet) on one portion **20a** of the movable part **20**, and a magnet (preferably a permanent magnet) or ferromagnetic material on the other portion **20b** of the movable part **20**. The biasing force of the biasing arrangement **30** corresponds to the magnetic force between the magnetic components. A bearing arrangement **50** is provided between one portion **20b** and the support structure **10**. The SMA wires **40** are connected between the other portion **20a** and the support structure **10**, and the second friction surface **20f** is provided on the other portion **20a**.

(55) FIG. 2D also schematically depicts a bearing arrangement **22** between the two portions **20a**, **20b**. In FIG. 2D, the bearing arrangement **22** is a plain bearing, although in general the bearing arrangement **22** may comprise any other form of bearing, such as a rolling bearing or flexure bearing. The bearing arrangement **22** may allow movement of the two portions **20a**, **20b** in a direction perpendicular to any movement direction of the movable part **20** relative to the support structure **10** within the range of movement. So, the bearing arrangement **22** may constrain movement of the two portions **20a**, **20b** in a direction parallel to any movement direction of the movable part **20** relative to the support structure **10** within the range of movement. Provision of the bearing arrangement **22** may be particularly beneficial in embodiments with magnetic biasing arrangement, due to the relatively low lateral stiffness of the magnetic biasing arrangement **30**. In general, however, the bearing arrangement **22** may be provided between any two portions **20a**, **20b** of the movable part **20** or between any two portions **10a**, **10b** of the support structure **10**.

(56) FIGS. 3A-C depict embodiments of the present invention in which the biasing arrangement **30** forms part of the support structure **10**. The support structure **10** comprises the biasing arrangement **30**. The biasing arrangement **30** (in its entirety) remains static relative to the support structure **10**, and the movable part **20** moves relative to the biasing arrangement **30**. In such an arrangement, it is easier to ensure that the biasing force of the biasing arrangement **30** acts in a direction perpendicular to the range of movement.

(57) As shown, the support structure **10** comprises two portions **10a**, **10b**. The biasing arrangement **30** applies a biasing force between the two portions **10a**, **10b**. The two portions **10a**, **10b** may be coupled via the biasing arrangement **30**. One end of the biasing arrangement **30** may be connected to one of the two portions **10a**, **10b**, and the other end of the biasing arrangement **30** may be connected to the other of the two portions **10a**, **10b**.

(58) In the embodiment of FIG. 3A, for example, a bearing arrangement **50** is provided between one of the portions **10b** and the movable part **20**. The SMA wires **40** are connected between the other of the portions **10a** and the movable part **20**. The first friction surface **10f** is provided on the other of the portions **10a**. The SMA wires **40** are angled away from the friction surfaces **10f**, **20f**, and arranged to move the movable part in opposite directions. So, upon equal contraction of (or equal tension in) the SMA wires **40**, the normal force N between first and second friction surfaces **10f**, **20f** is reduced. A difference in contraction between the SMA wire **40** moves the movable part **20** relative to the support structure on the bearing arrangement **50**.

(59) FIG. 3B depicts another embodiment in which the biasing arrangement **30** is provided between two portions **10a**, **10b** of the support structure **10**. A bearing arrangement **50** is provided between one of the portions **10a** and the movable part **20**. The SMA wires **40** are connected between the other of the portions **10b** and the movable part **20**. The first friction surface **10f** is provided on the other of the portions **10b**. The SMA wires **40** are angled away from the friction surfaces **10f**, **20f**,

and arranged to move the movable part in opposite directions. So, upon equal contraction of (or equal tension in) the SMA wires **40**, the normal force **N** between first and second friction surfaces **10f**, **20f** is reduced. A difference in contraction between the SMA wire **40** moves the movable part **20** relative to the support structure on the bearing arrangement **50**.

(60) FIG. 3C depicts another embodiment in which the biasing arrangement **30** is provided between two portions **10a**, **10b** of the support structure **10**. The embodiment of FIG. 3C is similar to the embodiment of FIG. 3B, except for the arrangement of the SMA wires **40**. In particular, in FIG. 3C, the SMA wires **40** are not angled relative to the friction surfaces **10f**, **20f**. The SMA wires **40** are connected between one of the portions **10a** of the support structure **10** and the movable part **20**. The SMA wires **40** further bend around portion of the other portion **10b** of the support structure **10**. So, the SMA wires **40** comprise a first length of SMA wire extending between the portions of the support structure **10**, and a second length of SMA wire extending between the other portion **10b** of the support structure **10** and the movable part **20**. Upon equal contraction of (or equal tension in) the SMA wires **40**, the normal force **N** between first and second friction surfaces **10f**, **20f** is reduced. A difference in contraction between the SMA wire **40** moves the movable part **20** relative to the support structure on the bearing arrangement **50**.

(61) As shown in the embodiments of FIGS. 2B-D, the support structure **10** may comprise multiple separated first friction surfaces **10f** and/or the movable part **20** may comprise multiple separated second friction surfaces **20f**. The normal forces **N** acting between each of these friction surfaces may be reduced upon contraction of the SMA wires **40**, or the overall normal force **N** may be reduced so as to reduce the overall frictional forces. In general, multiple separated first and/or second friction surfaces **10f**, **20f** may be provided in any embodiment of the present invention, e.g. also in the embodiments of FIG. 2A or 3A-C. The multiple separated friction surfaces may be provided in different planes (as in FIG. 2C), for example, or may be provided in the same plane (as in FIGS. 2B and 2D). The support structure and/or the movable part may optionally comprise one or more protrusions on which the first and/or second friction surface **10f**, **20f** is formed, which allows the area of contact between first and second friction surfaces **10f**, **20f** to be defined.

(62) In general, even though the biasing arrangement **30** is schematically depicted as a spring element in FIGS. 2A-C and 3A-C, the biasing arrangement **30** may comprise any component capable of applying a biasing force between movable part **20** and support structure **10**. The biasing arrangement **30** may, for example, comprise a resilient element such as a flexure, a coil spring, a leaf spring, an elastomer, or any other suitable biasing element such a pair of a magnet and a ferromagnetic element (as shown in FIG. 2D).

(63) In arrangements in which the biasing arrangement **30** comprises a resilient element, the resilient element (e.g. the flexure) is preferably compliant (or only compliant) in at least a direction orthogonal to the friction surfaces **10f**, **20f**. In general, the resilient element (e.g. the flexure) may also be compliant in other directions other than the one normal to the surface, particularly in embodiments in which the biasing arrangement is connected between movable part **20** and support structure **10**. In embodiments in which the movable part **20** or support structure **10** comprise plural portions **10a,b**, **20a,b**, movement of the portions **10a,b**, **20a,b** relative to each other in a direction parallel to the range of movement may be constrained. For example, with reference to FIGS. 2A-C, the biasing arrangement **30** may be relatively stiff in a direction parallel to the range of movement. An additional bearing arrangement **22** as described in relation to FIG. 2D, may optionally be provided to constrain relative movement of the two portions **10a,b**, **20a,b**. An endstop **70** (as described in relation to FIGS. 4A-D) may also constrain such relative movement. Generally, relative movement of the two portions of the movable part **20** or support structure **10** in a direction along a movement direction or in a movement plane within the range of movement may be constrained.

(64) Even though the biasing arrangement **30** is schematically depicted as being arranged between the support structure **10** and the movable part **20** in a direction along the normal force **N**, in practice

the biasing arrangement **30** may be arranged in a lateral direction, i.e. in a direction from a side of the movable part **20** and to a side of the support structure **10**. A flexure or leaf spring may, for example, generally extend in a direction parallel to the frictional force **F** while applying a normal force **N** to the movable part **20**. This may provide a more compact actuator assembly.

(65) In some embodiments, the biasing arrangement **30** may be arranged to also provide a biasing force to the bearing arrangement **50**. So, the biasing arrangement **30** may be arranged to load the bearing arrangement **50**. The biasing arrangement **30** may keep the bearing arrangement **50** in engagement. This is particularly advantageous when the bearing arrangement **50** comprises a rolling bearing or a plain bearing.

(66) Furthermore, even though the biasing arrangement **30** is depicted to push the portions of the movable part **20** or support structure **10** apart in FIGS. 2A-C and 3A-C (e.g. due to compression in a resilient element), the biasing arrangement **30** may instead be arranged pull these portions together (e.g. due to tension in a resilient element). Similarly, even though the magnetic biasing arrangement **30** is depicted to pull the portions of the movable part **20** or support structure **10** together in FIG. 2D (e.g. due to attractive magnetic forces), the magnetic biasing arrangement **30** may instead be arranged pull these portions together.

(67) The biasing arrangement **30** may comprise plural biasing elements that work in concert to provide the biasing force. So, the biasing arrangement **30** may comprise any combination of the biasing arrangements described above.

(68) Bearing Arrangements

(69) In FIGS. 2A, B, D and 3A-C, a dedicated bearing arrangement **50** is provided between the support structure **10** and the movable part **20**, in particular between the support structure **10** and a portion of the movable part **20**.

(70) The bearing arrangement **50** may be provided independently from the friction surfaces **10f**, **20f**. This may make controlled movement of the movable part **20** relative to the support structure **10** by the SMA wires **40** simpler.

(71) Except where the context requires otherwise, the bearing arrangement **50** is used herein as follows. The bearing arrangement **50** is used herein to encompass the terms “sliding bearing” or “plain bearing”, “rolling bearing” (including “ball bearing” or “roller bearing”) and “flexure bearing”. The term “bearing” is used herein to generally mean any element or combination of elements that functions to constrain motion to only the desired motion. The term “sliding bearing” is used to mean a bearing in which a bearing element slides on a bearing surface, and includes a “plain bearing”. The term “rolling bearing” is used to mean a bearing in which a rolling bearing element, for example a ball or roller, rolls on a bearing surface. In embodiments, the bearing may be provided on, or may comprise, non-linear bearing surfaces. In some embodiments, more than one type of bearing arrangement may be used in combination to provide the bearing functionality. Accordingly, the term “bearing” used herein includes any combination of, for example, plain bearings, rolling bearings and flexure bearings.

(72) In the depicted embodiments, for example, the bearing arrangement **50** comprises a rolling bearing. A rolling bearing is a roller bearing or a ball bearing, for example. The rolling bearing comprising a support bearing surface on the support structure **10**, a movable bearing surface on the movable part **20** and a rolling bearing element (such as a roller or ball) arranged between the support bearing surface and the movable bearing surface. In some embodiments, for example in embodiments in which the range of movement is defined in a movement plane, the support bearing surface and movable bearing surface are parallel to the first and second friction surfaces **10f**, **20f**.

(73) In alternative embodiments, the bearing arrangement **50** comprises a plain bearing or sliding bearing. So, the bearing arrangement **50** in any of the embodiments described herein may be a plain bearing. The plain bearing is formed between an engaging surface on the support structure that is in engagement with a corresponding engaging surface on the movable part **20**. The plain bearing may be considered to be separate from the friction surfaces **10f**, **20f** for example in instances in which

the friction coefficients in the plain bearing are lower, e.g. significantly lower (e.g. less than 50%, or less than 90%), than the friction coefficients between the first and second friction surfaces **10f**, **20f**. For this purpose, the plain bearing may comprise a friction reducing coating or material on the support structure **10** and/or movable part **20**, or a friction reducing lubricant between the engaging surfaces. Such plain bearings may, for example, comprising a polymer or a polymer coating. The coefficient of static friction between the engaging surfaces of the plain bearing may be less than 5 times, preferably less than 10 times, of the coefficient of static friction between the first and second friction surfaces **10f**, **20f**.

(74) Alternatively, the bearing arrangement **50** in any one of the embodiments may comprise a flexure bearing (not shown). The flexure bearing comprises one or more flexures, the flexures resisting deformation along their longitudinal extent and being relatively deformable lateral to their longitudinal extent. The flexures of the bearing arrangement **50** may be held in tension, at least partly due to the biasing force of the biasing arrangement **30**. The flexures allow movement of the movable part **20** within the range of movement, but constrain movement outside the range of movement.

(75) In general, the actuator assembly **1** comprises a bearing arrangement **50** for bearing movement of the movable part **20** relative to the support structure **10**. The bearing arrangement **50** may be separate from the first and second friction surfaces **10f**, **20f** (as in FIGS. 2A, B, D, 3A-C).

Alternatively, the bearing arrangement **50** may, at least in part, be formed from the first and second friction surfaces **10f**, **20f** (as in FIG. 2C).

(76) The bearing arrangement **50** constrains movement of the movable part **20** to movement within the range of movement. The bearing arrangement **50** may constrain movement of the movable part **20** relative to the support structure **10** to movement in three degrees of freedom. For example, the bearing arrangement **50** may constrain movement of the movable part relative to the support structure to movement in a movement plane. The movement may comprise three DOFs, for example i) translation in a first direction in the movement plane, ii) translation in a second direction in the movement plane, perpendicular to the first direction, and iii) rotation in the movement plane. Alternatively, the movement may comprise two DOFs, for example i) translation in a first direction in the movement plane, ii) translation in a second direction in the movement plane, perpendicular to the first direction. This may allow the actuator assembly to be used in applications requiring such 3 DOF or 2 DOF movement, for example as an optical image stabilization (OIS) actuator assembly implementing sensor shift OIS or lens shift OIS.

(77) In other embodiments, the bearing arrangement **50** may constrain movement of the movable part **20** relative to the support structure **10** to movement in one degree of freedom. This may allow the actuator assembly to be used in applications requiring such 1 DOF movement, for example as an autofocus (AF) actuator assembly. An actuator assembly with 1 DOF of movement may be simpler to manufacture and control compared to an actuator assembly with more DOFs. For example, the bearing arrangement **50** may constrain movement of the movable part relative to the support structure to helical movement about a helical axis. Alternatively, the bearing arrangement may constrain movement of the movable part **20** relative to the support structure **10** to translational movement along a movement axis. Further alternatively, the bearing arrangement **50** may constrain movement of the movable part **20** relative to the support structure **10** to rotational movement about a rotation axis.

(78) As such, there may be provided actuator assembly comprising a support structure comprising a first friction surface; a movable part comprising a second friction surface engaging the first friction surface; a helical bearing arrangement supporting the movable element on the support structure and arranged to guide helical movement of the movable element with respect to the support structure around a helical axis, wherein the helical bearing arrangement is formed by the first and second friction surfaces; and one or more SMA wires arranged, on contraction, to drive rotation of the movable element around the helical axis which the helical bearing arrangement converts into said

helical movement; and biasing arrangement configured to load the helical bearing arrangement, thereby biasing the first and second friction surfaces against each other with a normal force and generating a static frictional force that constrains the movement of the movable part relative to the support structure at any position within the range of movement when the one or more SMA wires are not contracted, wherein the one or more SMA wires are arranged, on contraction, to reduce the normal force between first and second friction surfaces.

(79) The first and second friction surfaces **10f**, **20f** may be arranged to allow movement of the movable part **20** relative to the support structure **10** in the DOFs allowed by the bearing arrangement **50**. For example, one or both of the first and second friction surfaces **10f**, **20f** is or are planar. This may allow movement in up to 3 DOFs. In embodiments in which movement in one DOF is allowed, one of the first and second friction surfaces **10f**, **20f** may be provided on a protrusion and the other of the first and second friction surfaces **10f**, **20f** may be provided on a guide channel shaped complementary to the protrusion. The range of movement of the movable part **20** relative to the support structure **10** may thus comprise movement along a line parallel to the guide channel.

(80) Endstops

(81) As described above, the SMA wires **40** may reduce the normal force N between first and second friction surfaces **10f**, **20f**. The first and second friction surfaces **10f**, **20f** may remain in contact upon contraction of the SMA wires **40**. Alternatively, in any of the embodiments described herein, the one or more SMA wires **40** may, on contraction, lift the first and second friction surfaces **10f**, **20f** out of engagement. So, the first and second friction surfaces **10f**, **20f** may separate upon contraction of the SMA wires **40**. The movable part **20** is not in direct contact with the first friction surface **10f** after contraction of the SMA wires **40**.

(82) Preferably, after separating the first and second friction surfaces **10f**, **20f**, the movable part **20** bears on the bearing arrangement **50**, preferably only on the bearing arrangement **50**. The bearing arrangement **50** thus continues to guide movement of the movable part **20** relative to the support structure **10**. This makes controlled movement of the movable part **20**, after having been lifted out of contact with the first friction surface **10f**, simpler compared to a situation in which no dedicated bearing arrangement **50** is provided. An actuator assembly **1** in which the SMA wires **40** lift the first and second friction surfaces out of engagement may also be referred to as a discrete friction actuator assembly **1**, because the frictional forces between movable part **20** and support structure **10** may in use vary between two discrete values: Relatively high frictional forces before contraction of the SMA wires **40** to keep the movable part **20** in position relative to the support structure **10**, and relatively low (e.g. residual) frictional forces due to the bearing arrangement **50** after contraction of the SMA wires **40**.

(83) Preferably, in embodiments in which the first and second friction surfaces **10f**, **20f** are lifted out of engagement, an endstop **70** is provided. Upon contraction of the SMA wires **40**, the endstop **70** engages. The endstop **70**, upon engagement, constrains movement of the movable part **20** in a direction perpendicular to the range of movement. The SMA wires **40** may thus drive movement of the movable part **20** more reliably and effectively. Once the endstop **70** is engaged, any strain in the SMA wires **40** may contribute to movement of the movable part **20**.

(84) The endstop **70** may be implemented in any of the embodiments described herein. The endstop may be formed, for example, between the two portions **20a**, **20b** of the movable part **20** or the two portions **10a**, **10b** of the support structure **10**. The endstop, upon engagement, may constrain relative movement of the two portions **10a**, **10b**. The endstop, upon engagement, may constrain relative movement of the two portions **10a**, **10b** in a direction perpendicular to any movement direction of the movable part **20** relative to the support structure **10**.

(85) In some embodiments, the endstop, upon engagement, may further constrain relative movement of the two portions **10a**, **10b** in a direction parallel to any movement direction of the movable part **20** relative to the support structure **10**. Such movement may be constrained, for

example, due to frictional forces between the endstop surfaces. Constraining such movement using the endstop may avoid the need for providing any other arrangements (such as a resilient element with relatively high stiffness in the movement direction, or an additional bearing arrangement **22** between the portions as in FIG. 2D) for constraining such relative movement. The endstop surfaces may optionally be provided with complementary teeth (not shown) to constrain sliding between the endstop surfaces in a direction parallel to any movement direction of the movable part **20** relative to the support structure **10**.

(86) FIGS. 4A-D schematically depict various embodiments in which an endstop **70** is provided.

(87) FIG. 4A depicts in essence the actuator assembly **1** already described with reference to FIG. 2A, with the addition of an endstop **70**. The endstop **70** is formed by an endstop surface on one portion **20a** of the movable part **20** and an endstop surface on the other portion **20b** of the movable part **20**. Upon contraction of the SMA wires **40**, the one portion **20a** of the movable part may move out of engagement with the first friction surface **10f** and into engagement with the endstop **70**, as illustrated by the arrows in FIG. 4A. In FIG. 4A, the endstop **70** is depicted as being provided by a protrusion on the other portion **20b**. Additionally or alternatively, a protrusion may be provided on the one portion **20a**. In general, a protrusion need not be provided, and the endstop **70** may be formed between any corresponding surfaces on the first and second portions **20a**, **20b** of the movable part **20**.

(88) FIG. 4B depicts in essence the actuator assembly **1** already described with reference to FIG. 3B, with the addition of an endstop **70**. The endstop **70** is formed by an endstop surface on one portion **10a** of the support structure **10** and an endstop surface on the other portion **10b** of the support structure **10**. Upon contraction of the SMA wires **40**, the other portion **20b** of the support structure **10** may move out of engagement with the movable part **20**, and the other portion **10b** of the support structure **10** may move into engagement with the endstop **70**, as illustrated by the arrows in FIG. 4B. In FIG. 4B, the endstop **70** is depicted as being provided by a protrusion on the one portion **10a**. Additionally or alternatively, a protrusion may be provided on the other portion **10b**. In general, a protrusion need not be provided, and the endstop **70** may be formed between any corresponding surfaces on the portions **10a**, **10b**.

(89) FIG. 4C depicts in essence the actuator assembly **1** already described with reference to FIG. 3A, with the addition of an endstop **70**. The endstop **70** is formed by an endstop surface on one portion **10a** of the support structure **10** and an endstop surface on the other portion **10b** of the support structure **10**. Upon contraction of the SMA wires **40**, the movable part **20** may move out of engagement with the one portion **10a** of the support structure **10**, and the other portion **10b** of the support structure **10** may move into engagement with the endstop **70**, as illustrated by the arrows in FIG. 4C. In FIG. 4C, the endstop **70** is depicted as being provided by a protrusion on the one portion **10a**. Additionally or alternatively, a protrusion may be provided on the other portion **10b**. In general, a protrusion need not be provided, and the endstop **70** may be formed between any corresponding surfaces on the portions **10a**, **10b**.

(90) FIG. 4D depicts another embodiment of the present invention. Here, the biasing arrangement **30** is arranged, e.g. connected, between the movable part **20** and the support structure **10**. So, one end of the biasing arrangement **30** is connected to the movable part **20** and the other end of the biasing arrangement **30** is connected to the support structure **10**. When using a magnetic biasing arrangement **30**, one component of the magnetic biasing arrangement **30** is provided on the support structure **10** and the other component is provided on the movable part **20**.

(91) In the embodiment of FIG. 4D, the endstop **70** is formed between the movable part and the bearing arrangement **50**. In particular, upon contraction of the SMA wires **40**, the movable part **20** may move out of engagement with the first friction surface **10f**, so out of engagement with the support structure **10**. The movable part **20** may move into engagement with the endstop **70**, as illustrated by the arrows in FIG. 4D, in particular by moving into engagement with the bearing arrangement **50**. The movable part **20** is thus lifted off the first friction surface **10f** and onto the

bearing elements of the bearing arrangement **50**. In general, the SMA wires **40** may be arranged, on contraction, to lift the movable part **20** out of engagement with the first friction surface **10f** and into engagement with the bearing arrangement **50** (which may comprise a rolling bearing, plain bearing or flexure bearing, for example). Upon ceasing power to the SMA wires **40**, the biasing arrangement **30** may bias the movable part **20** out of engagement with the bearing arrangement **50** and into engagement with the first friction surface **10f**.

(92) SMA Wire Arrangements

(93) In FIGS. 2A-C, 3A-C and 4A-D, the SMA wires **40** are arranged angled away from the friction surfaces **10f**, **20f**. This is one way to ensure that strains and/or stresses in the SMA wires **40** may reduce the normal force N while driving movement of the movable part **20** within the range of movement. Such an arrangement of SMA wires **40** provides a relatively simple manner of reducing the normal force N .

(94) In general, the one or more SMA wires **40** may be arranged, on contraction, to apply actuating forces to the movable part **20** relative to the support structure **10** that are angled relative to (e.g. away from) the first and second friction surfaces **10f**, **20f**. The actuating forces are not necessarily be parallel to the SMA wires **40**. In some embodiments (such as the embodiment of FIG. 3C), the actuating forces to the movable part **20** may even be parallel to the friction surfaces **10f**, **20f**.

(95) For example, each of the SMA wires **40** may be a V-shaped wire. The V-shaped wire may be connected at both ends to the support structure **10** or movable part **20**, and may bend around a contact portion with the movable part **20** or support structure **10**. So, the SMA wire **40** need not be connected directly between movable part **20** and support structure **10**.

(96) Optionally, a force-modifying mechanism (not shown) may be arranged between SMA wire **40** and movable part **20** or between SMA wire **40** and support structure **10**. The force-modifying mechanism may redirect the stress in an SMA wire **40** to act on the movable part in a direction along the actuating force. As such, the stresses and/or strains in the SMA wires **40** may reduce the normal force N , even if the SMA wires **40** are arranged parallel to the friction surfaces **10f**, **20f**. Such a force-modifying mechanism may also implement stroke or force amplification.

(97) FIG. 3C depicts a particular arrangement of SMA wires **40** in which the SMA wires **40** are connected at one end to one portion **10a** of the support structure **10** and at the other end to the movable part **20**. The SMA wires **40** bend around the other portion **10b** of the support structure. The SMA wires **40** may thus apply actuating forces to the movable part **20** that are substantially parallel to the friction surfaces **10f**, **20f**.

(98) In general, the SMA wires **40** are arranged on contraction, to reduce the normal force between first and second friction surfaces **10f**, **20f**. The SMA wires **40** may reduce the normal force due to equal stress and/or strain in the SMA wires **40**. The SMA wires **40** further are arranged to move the movable part **20** relative to the support structure **10**. The SMA wires **40** may move the movable part **20** due to unequal stress and/or strain in the SMA wires **40**.

(99) Furthermore, the SMA wires **40** may be arranged, on contraction, to provide a biasing force to the bearing arrangement **50**. The SMA wires **40** may thus help keeping the bearing arrangement **50** in engagement.

(100) Further Embodiments of the Actuator Assembly

(101) FIGS. 5A-D depict further embodiments of the actuator assembly **1**, in which the biasing arrangement **30** is comprised by the movable part **20**. The actuator assembly **1** of FIGS. 5A-D is functionally similar to the actuator assembly **1** described in relation to FIGS. 2A and 2B.

(102) FIG. 5A is one side view of the actuator assembly **1**, and FIG. 5B is another side view of the actuator assembly **1**. The movable part **20** moves in the left-right direction (movement direction M) in FIG. 5A and into and out of the page in FIG. 5B.

(103) As shown in FIG. 5A, the actuator assembly **1** comprises a flexure **30** having a first end fixedly attached to the movable part **20**, and a free end forming a contact portion **32** for engaging with the support structure **10** and generating frictional forces thereat. The contact portion **32** may

be considered a second portion of the movable part **20**, with the flexure **30** acting as a biasing arrangement **30** between the two portions of the movable part **20**. FIG. 5B shows one of the contact portions **32a** fully engaged with the first friction surface **10f** of the support structure **10**, while the other contact portion of the other flexure is disengaged from the surface.

(104) The actuator assembly further comprises SMA wires **40** that are angled to the direction of movement **M**, as well as a direction normal to the surface of the support structure **10**, and along the biasing force from a flexure. The SMA wires **40** are attached to the support structure and the end of the flexure **30** having the contact portion. On contraction, the SMA wires **40** apply an actuating force upon the flexure **30** where a second force component, normal to the surface of the support structure **1a**, retracts the contact portion from the surface, reducing the frictional forces thereat. The SMA wires **40**, also apply a first force component, along the direction of movement, to drive movement in the moveable part **20**. Further contraction in the SMA wires **40** not only drives continuous movement in the movable part **20**, but also disengages the contact portion **32** from the first friction surface **10f**, eliminating frictional forces caused by the flexure **30**. For example, contact portion **32b** is shown fully disengaged from the surface of the support structure **10** due to contraction in the corresponding SMA wire **40b**.

(105) Upon seizing energy supply to the SMA wires **40**, e.g., upon withdrawal of the actuating forces, the flexure **30** reengages with the surface of the support structure **10** and applies a biasing force thereon for constraining free movement in the moveable part **20**.

(106) The moveable part **20** also comprises an endstop **70**. The endstop defines a limit of movement of the contact portion **32** in a direction perpendicular to the friction surfaces **10f**, **20f**. As shown in FIG. 5B, when the SMA wire **40a** is not energised, the contact portion **32a** of the flexure **30** engages with the surface of the support structure **10**, and the free end of the flexure **30** is spaced from the endstop **70**. When the SMA wire **40b** is energised, its actuating force causes the contact portion **32b** to recede until the free end of the flexure **30** abuts the endstop. Further contraction of the SMA wire **40b** does not cause further retraction in the contact portion **32b**. Instead, the actuating force applies solely for driving the movement in the moveable part **20**, thus allowing a more precise position control in the moveable part **20**.

(107) Upon engaging the flexure **30** with the endstop **70**, the second actuating force from the SMA wire **40b** applies a torque on the movable part **20**. Such resultant torque is countered by the other flexure **30** to prevent tilting in the movable part **20**. More specifically, the surface of the support structure **10** reacts to the torque by contact portion **32a**.

(108) Preferably, the endstop **70** is arranged to protrude from the surface of the moveable part at a height which, upon making contact with the free end of the flexure **30**, leaves a minimal clearance between the contact portion **32** and the surface of the support structure **10**.

(109) FIG. 5C is a side sectional view of another embodiment of an actuator assembly **1**. The actuator assembly **1** has a flexure **30** and an SMA wire **40** arranged in a manner similar to the embodiment of FIGS. 5A and 5B. Only a single SMA **40** is illustrated, although plural SMA wires may be present. Like features are not described again.

(110) In this embodiment, the flexure **30** comprises an upwardly extending lip towards its free end, which forms the contact portion **32** for engaging the surface of the support structure **10**. Similarly to the embodiment of FIG. 5B, the moveable part **20** comprises an endstop **70** for limiting the displacement of the contact portion **32** during SMA wire contraction. Advantageously, the use of an upwardly extending lip reduces the extent of bending in the flexure **30** during wire contraction, thus allowing the contact portion **32** to be retracted in a more effective and precise manner.

(111) In the absence of a second flexure, the actuator assembly **6** further comprises a second bearing **50b** for countering the torque induced by the second actuating force component, e.g. the force component acting in a direction normal to the surface of the support structure **10**. The second bearing **50b** is shown as a ball bearing but can be other suitable bearings such as a plain bearing. The second bearing **50b** prevents tilting in the moveable part **20**, but allows relative movement

between the support structure **10** and the moveable part **20**.

(112) FIG. 5D is a side sectional view of another embodiment of the actuator assembly **1**. Features already described with reference to FIGS. 5A and 5B are not described again.

(113) As shown in FIG. 5D, the actuator assembly **1** comprises a flexure **30** fixedly attached to the movable part **20** at anchoring point **34** by a flexure arm **38**. The flexure arm **38** extends from a position along the length of the flexure **30**, which is spaced from the free ends of the flexure **30**. As such, the flexure **30**, as well as the two free ends of the flexure **30**, are pivotable about the anchoring point.

(114) One of the free ends forms a contact portion **32** for engaging with the support structure **10** and generating frictional forces thereat. That is, as illustrated in FIG. 5D, the contact portion **32** is shown fully engaged with the surface of the support structure **10**.

(115) The actuator assembly **1** further comprises an SMA wire **40** that is angled to the direction of movement (e.g. into the page in FIG. 5D), as well as a direction normal to the surface of the support structure **10**, e.g. the biasing force from a flexure. The SMA wire **40** is attached between the support structure and the other free end of the flexure **30**. Thus, the flexure acts as a class 1 lever.

(116) On contraction, the SMA wire **40** applies an actuating force upon the flexure **30** where the second force component draws downwardly on the end of the flexure **30** that is attached to the SMA wire **40**, causing the flexure arm **38** to rotate about the anchoring point **34**. As such, by the lever, the free end of the flexure moves upwardly and thereby retracts the contact portion **32** from the surface, thus reducing the frictional forces thereat. The SMA wire **40** also applies the first force component, along the direction of movement, to drive movement in the moveable part **20**. Further contraction in the SMA wire **40** not only drives continuous movement in the movable part **20**, but also disengages the contact portion **32** from the surface of the support structure **10**, eliminating frictional forces caused by the flexure **30**. For example, contact portion **32** is shown (along a dotted line) fully disengaged from the surface of the support structure **10** due to contraction in the SMA wire **40**.

(117) As described in relation to the embodiment shown in FIGS. 5A and 5B, the moveable part **20** also comprises an endstop **70** which defines a limit of movement of the contact portion **32**. Once the SMA wire **40** is energised, its actuating force causes the contact portion **32** to recede until the free end of the flexure **30** abuts the endstop **70**. Further contraction in the SMA wire **40** does not cause further retraction in the contact portion **32**. Instead, the actuating force is solely applied for driving the movement in the moveable part **20**, thus allowing a more precise position control in the moveable part **20**.

(118) In the illustrated embodiment of FIG. 5D, where force is applied at a distance closer to the fulcrum (e.g. anchoring point **34**) than the load, the contacting point **32** is arranged to displace by a greater amount than a given contraction in the SMA wire **40**. Advantageously, such an arrangement allows the contacting point **32** to be promptly retracted. Alternatively, the force may be applied at the same distance as, or at a distance further to the fulcrum, than the load, so as to overcome the biasing force by a stiffer biasing element. More specifically, the flexure **30** is a force-modifying mechanism where the ratio of the input force to the output force can be suitable tailored to different applications.

(119) Applications of Actuator Assembly

(120) The actuator assembly **1** may generally be applied in any application in which it is desired to move a movable part **20** within a range of movement using SMA wires **40**, and to keep the movable part **20** in place at any position within the range of movement upon ceasing power supply to the SMA wires **20**. The following description provides specific application examples of the present invention, but it will be appreciated that the actuator assembly **1** need not be used in these particular applications.

(121) In some embodiments, the actuator assembly **1** may be a micro-actuator for a camera or a

mobile phone. The actuator assembly may, for example, be configured to provide optical image stabilization (OIS) or auto-focus (AF) in a camera apparatus. For these purposes, the actuator assembly may implement 3 DOF or 2 DOF movement (for OIS) or 1 DOF movement (for AF), as described above in relation to the bearing arrangement **50**.

(122) There is thus provided a camera apparatus comprising the actuator assembly **1**, an image sensor and a lens assembly comprising at least one element. One of an image sensor and the at least one lens element may be fixed relative to the movable part **20** and/or one (e.g. the other) of the image sensor and the at least one lens element may be fixed relative to the support structure **10**. Moving the movable part **20** relative to the support structure **10**, upon contraction of the SMA wires **40**, may effect relative movement between lens element and image sensor. Moving the lens element relative to the image sensor along an optical axis of the lens assembly may effect AF in the camera apparatus. Moving the lens element relative to the image sensor in directions perpendicular to the optical axis and/or rotating the image sensor may effect OIS in the camera apparatus.

(123) Actuator assemblies **1** that may effect OIS are described in WO 2013 175197 A1 or WO 2017 072525 A1, which are herein incorporated by reference. The present invention may be applied to these actuator assemblies **1**. Embodiments of such actuator assemblies **1** are shown in FIGS. **11** and **12**, for example. In this regard, the movable part **20** may be movable in a movement plane within the range of movement. The actuator assembly **1** may comprise a total of four SMA wires **40** connected between the movable part **20** and the support structure **10** in an arrangement wherein none of the SMA wires **40** are collinear, and wherein the SMA wires **40** are capable of being selectively driven to move the movable part **10** relative to the support structure to any position in said range of movement without applying any net torque to the movable part **20** around a primary axis perpendicular to the movement plane.

(124) For example, two of the SMA wires **40** may be connected between the movable part **20** and the support structure **10** to each apply a torque to the movable part **20** in said movement plane around the primary axis in a first sense around the primary axis and the other two SMA wires **40** are connected between the movable part **20** and the support structure **10** to each apply a torque to the movable part in said movement plane around the primary axis in a second, opposite sense around the primary axis. The four SMA wires **40** may be arranged in a loop at different angular positions around the primary axis, successive SMA wires around the primary axis being connected to apply a force to the movable element in alternate senses around the primary axis.

(125) Alternatively, the movable part **10** may comprise a camera module with both lens assembly and image sensor. Tilting the camera module, upon contraction of the SMA wires, is another way to achieve OIS.

(126) FIGS. **6-11** describe in further detail specific embodiments of the actuator assembly **1**, where the actuator assembly effects movement of the movable part **20** along a movement axis. These specific embodiments may be used to effect AF or OIS in a camera apparatus, for example.

(127) FIGS. **6A**, **6B** and **6C** are respectively a plan view and side sectional views of an actuator assembly **1** according to an embodiment of the present invention.

(128) The actuator assembly **1** comprises a support structure **10** that has an image sensor (not shown) mounted thereon. The support structure **10** acts as a mounting platform for various elements as described below and also defines any reference features that are needed during the assembly process.

(129) The actuator assembly **1** further comprises a lens element that is part of the movable part in this example. The lens element comprises a lens carriage **20** which holds a lens (not shown), although alternatively, plural lenses may be present. The lens may be made of glass or plastic. The lens element has an optical axis **O** aligned with the image sensor and is arranged to focus an image on the image sensor.

(130) Alternatively, although not shown, the image sensor may be part of the movable part, and the lens element may be fixed relative to the support structure.

(131) Although the actuator assembly **1** in this example is a camera apparatus, that is not in general essential. In some examples, the actuator assembly **1** may be an optical device in which the movable part is a lens element but there is no image sensor. In other examples, actuator assembly **1** may be a type of apparatus that is not an optical device, and in which the movable element is not a lens element and there is no image sensor. In some examples, the actuator assembly **1** may be an optical device in which the movable part is a carriage supporting an image sensor where the lens carriage may be driven by another actuator, or not moveable at all.

(132) The actuator assembly **1** also comprises a bearing arrangement **50** in the form of ball bearings **50** along plural guides **52** that supports the lens carriage **20** on the support structure **10**. The ball bearings **50** and the guide are configured to guide movement of the lens carriage **20** with respect to the support structure **10** along the optical axis **O** which is therefore the movement direction in this example, while constraining movement of the lens carriage **20** with respect to the support structure **10** in other degrees of freedom.

(133) The actuator assembly **1** also comprises a pair of SMA wires **40a**, **40b** arranged at an angle to each other, as well as to the movement direction. In operation, the SMA wires **40a**, **40b** drive movement of the lens carriage **20** along the optical axis **O**. Each of the SMA wires **40a**, **40b** is connected, at a first end, to the support structure **10** by a static crimp portion **42a** fixed at the sidewall of the support structure. The static crimp portions **42a** crimp the respective SMA wires **40a**, **40b** to provide both mechanical and electrical connection by respective electrical connectors **44a**. The SMA wires **40a**, **40b** are also connected to moving crimp portions **42b** provided on a flexure **30**, which is attached to the lens carriage **20** at a connection tab **34**. The crimp portions **42b** are commonly connected to an electrical connector **44b** by an electrical path **43**. In the illustrated embodiment, the electrical path **43** is shown as a straight connector. In some other embodiment, the electrical path **43** may be replaced by a labyrinth path or a spring similar to the crimp plate **43** as shown in FIG. 3B. As a result, each of the SMA wire **40** is connected at one end to the support structure **10** and at the other end to the lens carriage **20** by the flexure **30**.

(134) Upon contraction the SMA wire **40a** drive the lens carriage in the upward direction, whereas the SMA wire **40b** drive the lens carriage in the opposite direction. The actuating forces by the SMA wires **40** also draw the lens carriage **20** towards, and therefore presses against, the respective sets of ball bearings **50**. Advantageously, such an arrangement allows the actuating force from the SMA wire **40** to act directly against the ball bearings **50**, and thereby reduces the amount of rattle between the lens carriage **20** and the support structure **10**.

(135) The flexure **30** have two opposite ends, one of which is attached to the SMA wire **40** whilst another end forms a contact portion **32** for engaging a corresponding surface of the support structure **10**. More specifically, the flexure **30** causes the contact portions **32** to bias against the support structure **10** so as to generate frictional forces that constrain free movement in the lens carriage **20**.

(136) Compared to the embodiment of FIG. 5D, the flexure **30** of the embodiment as shown in FIG. 6B comprises two serially connected pivots. Such an arrangement allows the contact portion **32** to retract in the same direction as the wire contraction.

(137) The flexure **30** generally comprises a set of inner flexure arms **33** nested inside a set of outer flexure arms **35**. The outer flexure arms **35** have a static crimp **42b** for connecting to the SMA wire **40**. The outer flexure arms **35** comprises a protrusion **31** at a first end which is aligned with a corresponding protrusion **22** of the lens carriage **20**. That is, the protrusion **31** is positioned further towards the first end of the outer flexure arms **35** than the crimp **42b**.

(138) The outer flexure arms **35**, towards their second ends, are each pivotally connected to a corresponding inner flexure arm **33** by a linkage **36**, at a location along the length of the inner flexure arms **33**. Therefore, the outer flexure arms **35** are pivotable about the linkage **36**, in relation to the inner flexure arms **33**.

(139) The inner flexure arms **33** are connected to a moveable end of the connection tab **34** at a first

end by another linkage **38**. Therefore, the inner flexure arms **33** are pivotable about the linkage **38**, in relation to the lens carriage. The inner flexure arms **33** join up at their second end to form the contact portion **32**, which is opposite to the first end of the outer flexure arms **35**. Thus, the linkages **36** and **38** are serially connected by pivots along the flexure **30**, between the protrusion **31** at the first end of the outer flexure arms **35** and the contact portion **32** towards the second end of the inner flexure arms **33**.

(140) Upon energising, the SMA wire **40** contracts and draws the protrusion **31** of the outer flexure arms **35** towards the corresponding protrusion **32** on the lens carriage **20** until they engage with each other. Therefrom, a pivot is formed between the protrusions **31**, **32**, thus allowing the actuating force to transfer through the outer flexure arms **35** to compress on the inner flexure arms **33** at the linkage **36** which, by pivoting motion at the linkage **38**, causes the contact portion **32** to retract and to disengage from the surface of the support structure **10**.

(141) In the illustrated embodiment of FIGS. **6A** to **6C**, where the actuating force is applied at a distance closer to the fulcrum (e.g. linkage **36**) than the load (e.g. the contacting point **32**), the contacting point **32** is arranged to displace by a greater amount than a given contraction in the SMA wire **40**. Advantageously, such an arrangement allows the contacting point **32** to be promptly retracted. Alternatively, the force may be applied at the same distance as, or at a distance further to the fulcrum, than the load, so as to overcome the biasing force by a stiffer biasing element. More specifically, the flexure **30** is a force modifying mechanism where the ratio of the input force to the output force can be suitable tailored to different applications.

(142) Additionally, the actuating force comprises a force component along the movement direction for driving movement in the lens carriage **20**.

(143) The surface of the lens carriage **20** forms an endstop **70** which defines a limit of movement in the contact portion **32**. As shown in FIG. **6A**, as the SMA wires **40** energise, the actuating force causes the contact portion **32** to recede until the end of the inner flexure arms **33** (e.g. a portion adjacent to the linkage **38**) abut or engage the endstop **70**. Further contraction in the SMA wires **40** does not cause further retraction in the contact portion **32**. Instead, the actuating force would solely be applied for driving the movement in the lens carriage **20**, thus allowing a more precise position control.

(144) Generally, the frictional forces are sufficient to constrain free movement in the lens carriage **20**, yet not significant enough to resist relative movement between the lens carriage **20** and the support structure **10** when the SMA wires **40** are energised. In some embodiments, one or both of the contact portion **32** or the protrusion **22** of the support structure **10** may be provided with a material or a coating.

(145) FIGS. **7A** and **7B** are respectively a truncated plan view and a side sectional view of an actuator assembly **1** according to an embodiment of the present invention.

(146) The actuator assembly **1** is structurally and functionally similar to the actuator assembly **1** of FIGS. **6A** to **6C**. Like features are not described again. In this embodiment, the flexure **30** is a planar flexure of a different design.

(147) The flexure **30** comprises two opposite ends, one of which is attached to the SMA wire **40** whilst another end forms a contact portion **32** for engaging a corresponding surface of the support structure **10**. In this embodiment, the contact portion **32** of the flexure **30** is curved or bended inwardly, which corresponds to a curved or tapered surface profile on the support structure **10**. More specifically, the flexure **30** causes the contact portions **32** to bias against the support structure **10** so as to generate frictional forces that constraints free movement in the lens carriage **20**. The biasing force, therefore, is angled to the quadrilateral sides of the support structure **10**.

(148) Similar to the embodiment of FIGS. **6A** to **6C**, the flexure **30** of this embodiment as shown in FIG. **7B** comprises two serially connected pivots. Such an arrangement allows the contact portion **32** to retract in the same direction as the wire contraction.

(149) The flexure **30** generally forms from a set of inner flexure arms **33** nested inside a set of outer

flexure arms **35**. The flexure **30**, as shown in FIG. 7A, has a planar profile. The outer flexure arms **35** having a crimp **42b** for connecting to the SMA wire **40**. The outer flexure arms **35** comprises a protrusion **31** at a first end which engages with a corresponding protrusion **22** of the lens carriage **20**. Therefore, the outer flexure arms are pivotable about the protrusion **22** of the lens carriage **20**. That is, the protrusion **31** is positioned further towards the first end of the outer flexure arms **35** than the crimp **42b**.

(150) The outer flexure arms **35**, towards their second ends, are each pivotally connected to a corresponding inner flexure arm **33** by a linkage **36**, at a location along the length of the inner flexure arms **33**. Therefore, the outer flexure arms **35** are pivotable about the linkage **36**, in relation to the inner flexure arms **33**.

(151) The inner flexure arms **33** are connected to a moveable end of the connection tab **34** at a first end by another linkage **38**. Therefore, the inner flexure arms **33** are pivotable about the linkage **38**, in relation to the lens carriage. The inner flexure arms **33** joins up at their second end to form the contact portion **32**, which is opposite to the first end of the outer flexure arms **35**. Thus, the linkages **36** and **38** are serially connected pivots along the flexure **30**, between the protrusion **31** at the first end of the outer flexure arms **35** and the contact portion **32** towards the second end of the inner flexure arms **33**.

(152) Upon energising, the SMA wire **40** contracts and by the pivot formed between the protrusions **31**, **32**, the actuating force transfers through the outer flexure arms **35** to compress on the inner flexure arms **33** at the linkage **36** which, by pivoting motion at the linkage **38**, causes the contact portion **32** to retract and to disengage from the surface of the support structure **10**.

(153) In the illustrated embodiment of FIGS. 7A and 7B, where the actuating force is applied at a distance closer to the fulcrum (e.g. linkage **36**) than the load (e.g. the contacting point **32**), the contacting point **32** is arranged to displace by a greater amount than a given contraction in the SMA wire **40**. Advantageously, such an arrangement allows the contacting point **32** to be promptly retracted. Alternatively, the force may be applied at the same distance as, or at a distance further to the fulcrum, than the load, so as to overcome the biasing force by a stiffer biasing element. More specifically, the flexure **30** is a force modifying mechanism where the ratio of the input force to the output force can be suitable tailored to different applications.

(154) Additionally, the actuating force comprises a force component along the movement direction for driving movement in the lens carriage **20**.

(155) The surface of the lens carriage **20** forms an endstop **70** which defines the range of movement in the contact portion **32**. As shown in FIG. 7A, as the SMA wires **40** energise, the actuating force causes the contact portion **32** to recede until the end of the inner flexure arms **33** (e.g. a portion adjacent to the linkage **38**) abut or engage the endstop **70**. Further contraction in the SMA wires **40** do not cause further retraction in the contact portion **32**. Instead, the actuating force is solely applied for driving the movement in the lens carriage **20**, thus allowing a more precise position control.

(156) FIG. 8A is a truncated plan view of an actuator assembly **1** according to another embodiment of the present invention. Similar to the embodiment of FIGS. 6A to 6C, the actuator assembly **1** comprises a moveable part **20** that is supported on ball bearings and moveable along an optical axis O. For conciseness, like features are not shown again.

(157) As shown in FIG. 8A, the actuator assembly **1** comprises a pair of opposing SMA wires **40** each having an end attached to the support structure **10** by a static crimp **42a** and another end attached to the moveable part **20** by a moving crimp **42b**. More specifically, the moving crimps **42b** are connected to the moveable part **20** by flexible elements, e.g. planar crimp plates, so as to allow a degree of relative movement between the moving crimps **42b** and the movable part **20**. The SMA wires **40** are angled to the movement direction such that, upon contraction, they apply respective first force components for moving the moving part **20** in opposite movement direction for driving movement along the optical axis O, and respective second force components in opposite directions

lateral to the optical axis O (shown as the arrows in FIG. 8A).

(158) The actuator assembly **1** comprises a buckling flexure **30** having both ends fixedly attached to the moving crimps **42b**. The term buckling flexure **30** herein generally refers to a flexible member having at least one kink **36** adjoining plural flexure arms. When subject to a compressive force, the kink **36** may increase in curvature, causing the two ends of the two buckling flexure **30** to move towards each other. The flexure arms may be stiff under compression, or they may bend.

(159) Generally, the buckling flexure **30** may be used in lieu of the pivots arrangement as shown in FIGS. 5D, **6** and **7** as a force modifying mechanism. More specifically, when the SMA wires **40** are not energised, the buckling flexure **30**, at its contact portions **32**, biases against corresponding protrusions **22** extending from the support structure **10**, and thereby generates frictional forces for constraining free movement in the moveable part **20**.

(160) Upon contraction in the SMA wires **40**, the second force component compresses the buckling flexure **30**, further bending the kink **36** of the buckling flexure **30**, thereby causing the contact portions **32** to recede from their respective protrusion **22**, e.g. along the arrows as shown in FIG. 8A. Advantageously, because of the bending in the kink **36**, the use of buckling arms **30** permits the contact portions **32** to promptly retract from the protrusions **22** of the support structure.

(161) The protrusion **22** also functions as an endstop which defines a limit of movement in the contact portion **32**. As shown in FIG. 8A, as the SMA wires **40** energise, the actuating force causes the contact portion **32** to recede until the moving crimp **42b** abuts or engages the protrusion **22**. Further contraction in the SMA wires **40** do not cause further retraction in the contact portion **32**. Instead, the actuating force would solely be applied for driving the movement in the lens carriage **20**, thus allowing a more precise position control.

(162) Generally, the frictional forces are sufficient to constrain free movement in the lens carriage **20**, yet not significant enough to resist relative movement between the lens carriage **20** and the support structure **10** when the SMA wires **40** are energised. In some embodiments, one or both of the contact portion **32** or the protrusion **22** of the support structure **10** may be provided with a material or a coating as described.

(163) In some other embodiments, the buckling flexure **30** may be toggled between a first configuration (e.g. when the contact portions **32** engage with the protrusions **22**) and a second configuration (e.g. when the contact portions **32** disengage from the protrusions **22**). More specially, the buckling flexure **30** may only be stable at the first configuration and the second configuration. Therefore, upon energising the SMA wires **40**, the buckling flexure **30** may promptly toggle towards the second configuration.

(164) FIG. 8B is a truncated plan of an actuator assembly **1** according to another embodiment of the present invention. Similar to the embodiment of FIGS. 6A to 6C, the actuator assembly **1** comprises a moveable part **20** that is supported on ball bearings and moveable along an optical axis O. For conciseness, like features are not shown again.

(165) As shown in FIG. 8B, the actuator assembly **1** comprises a pair of opposing SMA wires **40** each having an end attached to the support structure **10** by a static crimp **42a** and another end attached to the moveable part **20** by a moving crimp **42b**. More specifically, the moving crimps **42b** are connected to the moveable part **20** by flexible elements, e.g. planar crimp plates, so as to allow a degree of relative movement between the moving crimps **42b** and the moveable part **20**. The SMA wires **40** are angled to the movement direction such that, upon contraction, they apply respective first force components for moving the moving part **20** in opposite movement direction for driving movement along the optical axis O, and respective second force components in opposite directions lateral to the optical axis O (shown as the arrows in FIG. 8B).

(166) The actuator assembly **1** comprises a buckling flexure **30** having both ends fixedly attached to the moving crimps **42b**. The buckling flexure **30** comprises plural kinks **36** adjoining plural flexure arms. When subject to a compressive force, the kinks **36** may increase in curvature, causing the two ends of the two buckling flexure **30** to move towards each other. The flexure arms may be

stiff under compression, or they may bend.

(167) Similar to the embodiment of FIG. 8A, the buckling flexure **30** may be used as a force modifying mechanism. More specifically, when the SMA wires **40** are not energised, the buckling flexure **30**, at its contact portions **32** (e.g. between the two kinks **36**), biases against corresponding protrusions **22** extending from the support structure **10**, and thereby generates frictional forces for constraining free movement in the moveable part **20**.

(168) Upon contraction in the SMA wires **40**, the second force component compresses the buckling flexure **30**, further bending the kinks **36** of the buckling flexure **30**, thereby causing the contact portion **32** to move towards the moveable part **20** and to recede from the protrusion **22**, e.g. along the arrows as shown in FIG. 8B. Advantageously, because of the bending in the kinks **36**, the use of buckling arms **30** permits the contact portions **32** to promptly retract from the protrusions **22** of the support structure.

(169) The surface of the movement part **20** also functions as an endstop **70** which limits movement of the contact portion **32**. As shown in FIG. 8B, as the SMA wires **40** energise, the actuating force causes the contact portion **32** to recede until the buckling flexure **30** abuts or engages the protrusion. Further contraction in the SMA wires **40** do not cause further retraction in the contact portion **32**. Instead, the actuating force is solely applied for driving the movement in the lens carriage **20**, thus allowing a more precise position control.

(170) In some other embodiments, the buckling flexure **30** may be toggled between a first configuration (e.g. when the contact portions **32** engage with the protrusions **22**) and a second configuration (e.g. when the contact portions **32** disengage from the protrusions **22**). More specially, the buckling flexure **30** may only be stable at the first configuration and the second configuration. Therefore, upon energising the SMA wires **40**, the buckling flexure **30** may promptly toggle towards the second configuration.

(171) FIGS. 9A and 9B are respectively a plan view and a side sectional view of an actuator assembly **1** according to an embodiment of the present invention.

(172) The SMA actuation apparatus **102** comprises a support structure **10** and a movable part **20**. The support structure **10** and the movable part **20** are flat parallel sheets that face each other. A suspension system, comprising at least one or more flexures **30**, supports the movable part **20** on the support structure **10** and guides movement of the movable part **20** with respect to the support structure **10** along the Z axis which is the movement axis O in this example. More specifically, the flexure **30** bears the moveable part **20** on the support structure and therefore can be considered as the bearing, or the only bearing. As described further below, the suspension system constrains translational movement of the movable part **20** with respect to the support structure **10** along the X and Y axes which are perpendicular to the Z axis.

(173) Two SMA wires **40** are arranged as follows to drive movement of the movable part **20** with respect to the support structure **10** along the movement axis. The SMA wires **40** are each connected at one end to the support structure **10** by static crimp portions **42a** and at the other end to the moveable part **20** by moveable crimp portions **42b**. The static and moveable crimp portions **42a**, **42b** crimp the SMA wires **40** to provide both mechanical and electrical connection.

(174) The SMA wires **40** are inclined at a first acute angle θ with respect to a plane normal to the Z axis. The first acute angle θ is greater than 0 degrees so that it applies a first force component to the support structure **10** and the movable portion **10** along the Z axis, and so can drive movement along the Z axis. However, the inclination of the SMA wires **40** at the first acute angle θ provides gain as the SMA wires **40** rotate when they contract to drive the relative movement, thereby causing the amount of relative movement along the Z axis to be higher than the change in length of the wire.

(175) The two SMA wires **40** are under tension and are opposed in the sense that they apply forces to the movable part **20** with respective first force components parallel to the Z axis that are in opposite directions. That is, as viewed in FIG. 9B, the SMA wire **40** that is uppermost is connected to the movable part **20** at its upper end and so applies a force on the movable part **20** with a

downwards component along the Z axis, and the SMA wire **40** that is lowermost is connected to the movable part **20** at its lower end and so applies a force on the movable part **20** with an upwards component along the Z axis. Thus, the SMA wires **40** drive movement of the movable part **20** in opposite directions along the Z axis.

(176) As shown in the plan view of FIG. **9A** in which the two SMA wires **40** are inclined from parallel, as projected on the plane normal to the Z axis which is the movement axis. The components of force applied by the lengths of SMA wire **4** along the Y axis are in the same direction and so do not generate a couple.

(177) In some embodiments, the suspension system does not comprise conventional bearings. That is, the flexure **30** bears the moveable part **20** on the support structure **10**. Since the flexure **30** is most compliant in the movement direction, the flexure **30** may be considered to be a bearing for guiding movement of the moveable part **20**.

(178) In the illustrated example, the suspension system further comprises a bearing arrangement of two bearings **50** which are arranged as follows to permit movement of the movable part **20** with respect to the support structure **10** along the Z axis. The bearings **50** permits some degree of movement in the moveable part **20** along the Y-axis, while constraining or limiting other undesired movements that are not constrained by the flexures **30**. The bearings **50** may alternatively be plain bearing elements. Each of the two bearings **50** may extend along the Z axis so as to permit movement of the movable part **20** with respect to the support structure **10** along the Z axis. There may be more than 2 bearings, and preferably they are spaced apart as far as possible within the extent of the actuator.

(179) FIGS. **9C** and **9D** are respectively an enlarged plan view and an enlarged side sectional view of a bearing **50**, applicable in the embodiment of FIGS. **9A** and **9B**. The bearing **50** comprises a ball bearing **52** running in a bearing race **54** extending along the Z-axis, so as to permit relative movement in the movement direction. The bearing race **54** is connected to the support structure **10** and the moveable part **20** by resilience elements **56** that are compliant only in the Y direction. More specifically, the resilience elements **56** are planar flexures which is sufficiently thin (as view in FIG. **13C**) to comply along the Y-axis so as to provide a limited movement in the bearing race **54** orthogonal to the Z-axis. As such, the flexure **30** may bias the moveable part **20** against the protrusions **22** of the support structure **10** to generate frictional forces.

(180) The two bearings **50** are spaced apart along the X axis. As a result, the reactive forces generated within the bearings **50** act together to constrain rotational movement of the movable part **50** with respect to the support structure **10** about the Z axis.

(181) As described, the moveable part **20** is supported by the pair of flexures **30** and the bearings **50**. FIGS. **9A** and **9B** only show a single flexure **30** where the other flexure **30**, arranged in an opposite manner, is not shown. The flexure **30** is attached to the support structure **10** and the moveable part **20** by respectively a first end **34** and a second end **36**. The first end **34** and the second end **38** are connected by a flexure arm **38** and are moveable relative to each other along at least the Y and Z axes. More specifically, the flexure arm **38** is compliant in Y and Z direction which allows such relative movements.

(182) As shown in the plan view of FIG. **9A**, the flexure arm **38** is curved along its length. When the SMA wire **40a** is not energised, the flexure **30** is configured to bias the moveable part **20** against the support structure **10**. More specifically, the moveable part **20** is engaged with, and biased against contacting surfaces at protrusions **22** that are formed on a sidewall of the support structure. The biasing force from the flexure **30** generates frictional forces at the contacting surfaces, which are sufficient for constraining movement in the second part when the one or more SMA wires are not energised.

(183) As the SMA wire **40** energises, a second force component of the actuating force acts against the biasing force exerted by the flexure **30**, causing the moveable part **20** to recede, in a direction lateral to the optical axis, from the contacting surface of the protrusion. Thus, upon energising the

SMA wire **40**, the frictional forces at the contacting surface reduce. This allows the first force component of the actuating force to drive movement of the moveable part **20** along the Z axis whilst being fully supported by the bearings **50**.

(184) In some embodiment, further contraction in the SMA wire **40** causes the moveable part **20** to disengage from the protrusion **22** of the support structure **10**, thereby eliminating friction therebetween.

(185) In contrast to the prior art example **100**, the contacting surface on protrusion **22** is distinct from a bearing **50** (if present) in the actuator assembly **1**, yet allowing the moveable part **20** to be fully supported and guided over the range of movement. In addition, the contacting surface on protrusion **22** is provided on a different surface/side of actuator assembly **1** to the bearing **50** (if present). Thus, the generated frictional forces at the contacting surface are decoupled from the bearing surface. So, the two surfaces can be individually tailored to suit their needs.

Advantageously, in comparison to the prior art embodiment, the present invention provides a more precise position control when holding the second part in place. Furthermore, because the contacting surface does not require the incorporation of bearings, a wider range of surface profiles may be used for generating the frictional forces.

(186) FIGS. **10A**, **10B** and **10C** are respectively an exploded perspective view, an enlarged side cross-sectional view and a side schematic diagram of an actuator assembly **200** according to an embodiment of the present invention. The actuator assembly **200** is suitable for providing optical image stabilisation (OIS) when incorporated in a camera apparatus or other optical apparatus. The actuator assembly **200** is arranged as described below, but in general terms has a similar arrangement and function to the actuator arrangement described in WO 2017/755788, except for some differences described below. Accordingly, reference is made to WO 2017/755788.

(187) The actuator assembly **200** includes a support plate **250** and a movable part **260**, which are the first part and the second part, respectively, in this example. The movable part **260** is movable with respect to the support structure **260**.

(188) The support structure **250** and the movable part **260** are integral sheets made of metal, for example steel such as stainless steel. The support structure **250** is fixed to a support sheet **270**.

(189) The movable part **260** supports a lens assembly **301**. The support sheet **270** is fixed to a base **302** on which an image sensor **303** is mounted, although in other types of optical apparatus the image sensor **303** may be omitted. In general, the movable part **260** may support the image sensor **303** and the lens assembly **301** may be mounted on the base **302**. Each of the support structure **250** and the movable part **260** is provided with a central aperture aligned with an optical axis O allowing the passage of light from the lens assembly **301** to the image sensor **303** to allow the image sensor **303** to capture an image formed by the lens assembly **301**.

(190) The actuator assembly **200** includes four plain bearings **210** spaced around the optical axis O and each having a structure shown in more detail in FIG. **10D**. Each plain bearing **210** comprises a bearing element **211** mounted on the support structure **250**, for example by adhesive, and a bearing surface **212** which is a surface of the movable part **260**. The bearing element **211** bears on the bearing surface **212**. In particular, an outer surface **213** of the bearing element **211** contacts the bearing surface **212**, the outer surface **213** of the bearing element **211** and the bearing surface **212** conforming with each other. The plain bearings **210** may be arranged as described in further detail in WO 2017/755788.

(191) Thus, the movable part **260** is capable of movement relative to the static plate **260** across the bearing surfaces **212** of the plain bearings **210** in any direction in two dimensions orthogonal to the optical axis O.

(192) As an alternative, the plain bearings **210** may be reversed to comprise a bearing element mounted on the movable part **260** and a bearing surface which is a surface of the support structure **250**. In that case, the support structure **250** would form the first part and the movable part **260** would form the second part. In that sense, the lens assembly **301** may be mounted on either one of

the first and second parts.

(193) The actuator assembly **200** includes comprises two flexures **267** connected between the support structure **250** and the movable part **260**. In this example, the flexures **267** are formed integrally with the movable part **260** at one end thereof and are mounted to the support structure **250** at the other end thereof, although the flexures **267** could be formed integrally with the support structure **250** and mounted to the movable part **260**, or else could be separate elements mounted to each of the support structure **250** and the movable part **260**.

(194) The flexures **267** are resilient and are therefore resilient biasing elements. The flexures **267** are arranged to act as a resilient biasing arrangement biasing the support structure **250** into contact with bearing surfaces **212** of the movable part **260**. This may be achieved by configuring the flexures **267** so that they are deflected from their relaxed state to provide a pre-loading force that provides the biasing. This generates a reaction between the movable part **260** and the bearing surfaces **212**, as well as generating frictional forces between the movable part **260** and the bearing surfaces **212**.

(195) Simultaneously, the flexures **267** permit movement of the movable part **260** relative to the support structure **250** orthogonal to the optical axis O.

(196) The flexures **267** are made of a suitable material that provides the desired mechanical properties and is electrically conductive so that the flexures **267** may electrically connect SMA wires **280** that are connected thereto, for carrying the drive current supplied to the SMA wires **280**. Typically, the material is a metal having a relatively high yield, for example steel such as stainless steel.

(197) The second actuator assembly **200** also includes four SMA wires **280** connected between the support structure **250** and the movable part **260**. Specifically, the support structure **250** is formed with crimps **251** and the movable part **260** is formed with crimps **261**, wherein the crimps **251** and **261** crimp the four SMA wires **280** so as to connect them to the support structure **250** and the moving plate **260**. In contrast to arrangement disclosed in WO 2017/755788 of the SMA wires **280** extending perpendicular to the optical axis O, each SMA actuator wire **280** is inclined at an acute angle α of greater than 0° with respect to the bearing surfaces **212** so as to apply a force (“upforce”), on contraction of the SMA actuator wire **280**, with a component normal to the bearing surfaces **212** that biases the support structure **250** away from the bearing surfaces **212** and with a component parallel to the bearing surfaces **212**.

(198) The SMA wires **280** have an arrangement around the optical axis O which is the same as that described in WO 2017/755788 so that each SMA wires **80** applies a component of force parallel to the bearing surfaces **212** in different directions and the SMA wires **280** are capable of driving movement of the movable part **260** relative to the support structure **250** in two dimensions across the bearing surfaces **212**.

(199) As the SMA wires **280** are opposed, their average tension and hence the upforce can be controlled at least substantially independently of the movement.

(200) The SMA wires **280** are each connected to a control circuit which may be implemented in an integrated circuit chip. The control circuit in use applies drive signals to the SMA wires **280** which resistively heat the SMA wires **280** causing them to contract. In operation, the SMA wires **280** are selectively driven to move the movable part **260** relative to the support structure **250** along a movement axis in any direction orthogonal to the optical axis O. Such control may be used to move the lens assembly relative to image sensor orthogonally to the optical axis O so as to provide OIS as described in WO 2017/755788.

(201) In the absence of drive signals being applied, the SMA wires **280** do not contract, and so the flexures **267** bias the movable part **260** onto the bearing surfaces **212** generating frictional forces that are sufficient to retain the movable part **260** in position on the bearing surfaces **212**. In this state, the movable part **260** is retained in position with zero power consumption by the second actuator assembly **200**.

(202) The flexures **267** may be designed to provide sufficient frictional forces to reduce motion and thereby improve stability of the second actuator assembly **200** and/or reduce the risk of audible noise when the SMA wires **280** are in an unpowered state. This is important as being able to turn off OIS in situations where it is not effective (e.g. very high light levels) will reduce power consumption. In such a state, the frictional forces should retain the movable part **260** in position on the bearing surfaces **212** in the event of typical forces acting on the second actuator assembly **200**, including gravitational forces which can lead to movement that is dependent on the orientation (posture dependence) and inertial impact forces. Otherwise, there is a risk that the second actuator assembly **200** is insufficiently stable and/or that audible noise is generated (e.g. between the movable part **260** and the bearing surfaces **212** or between the lens assembly **301** and an enclosure of the camera apparatus) when the second actuator assembly **200** vibrates, for example due to a haptic effect of a device such as a mobile telephone in which the second actuator assembly **200** is incorporated. When the second actuator assembly **200** is unpowered the SMA wires **280** will slacken off and not exert much force. The position of the lens assembly **301** will therefore be determined by the interaction of the following forces: the combined weight of the lens assembly **301** and the movable part **260**; the stiffness of the flexures **267** (in the movement plane); the frictional forces; and inertia (when accelerating)

(203) For example, when the camera apparatus is held with the optical axis O horizontal the lens position will “sag” until the restoring force of the flexures **267** and frictional forces counterbalance the weight.

(204) Generally, the frictional forces and hence the strength of the biasing force from the flexures **267** need to be increased with increasing mass of the camera lens assembly that is to be mounted on the movable part **260**.

(205) Additionally, when the camera is accelerated hard inertia may move the lens assembly **301** relative to the image sensor **303**. Both effects are undesirable, leading to blur from the motion and potential interference with OIS. A rigid stable system is desired for optimal OIS performance. The frictional forces generated between the movable part **260** and the bearing surfaces **212** in the absence of contraction of the SMA wires **280** may be less than the combined weight of the lens assembly **301** and the movable part **260**. In that case, the movable part **260** is maintained in position on the bearing surfaces **212** under the effect of gravitational forces when the camera apparatus is held with the optical axis horizontal and ignoring the other forces in the system.

(206) If frictional forces of a suitable level to achieve these effects were encountered when the SMA wires **280** were driven, then this may hinder OIS performance. However, due to the inclination of the SMA wires **280**, the force applied by the SMA wires **280** on the support structure **250** has a component normal to the bearing surfaces **212** that biases the support structure **250** away from the bearing surfaces **212**, thereby reducing the frictional forces therebetween so as to reduce the impact on OIS performance.

(207) In order to provide an appropriate degree of reduction, the ratio between (i) the frictional forces generated when the SMA wires **280** drive the maximum degree of relative movement of the movable part **260**, and (ii) the frictional forces generated in the absence of contraction of the SMA wires **280** may be less than 0.9 and more preferably less than 0.7. The inventors have found that this can be achieved with practical sets of design parameters, which includes, amongst other things, an angle α of greater than 0.5° . In smaller actuators, angles of 0.5° or less are generally associated with unpractically small height differences between the ends of the SMA wires **280** whereas, in larger actuators, such small angles generally do not provide sufficient upforce. Larger angles may be used but generally lead to taller actuators.

(208) In order to constraint free movement in the moveable part **20** when the wire are not energised, the plain bearings **210** may be provided with, amongst others, a surface coating or a material. The coefficient of friction of the plain bearings **210**, e.g. by surface roughness, is in the range of 0.05 to 0.6, or in the range of 0.1 to 0.4, or preferably in the range of 0.05 to 0.4. Such an

arrangement may allow the biasing arrangement to generate sufficient frictional forces to keep the second part in position when the SMA wires **280** are not energised, yet not presenting a significant resistance to the movement in the second part.

(209) FIGS. **11** and **12** show further embodiments of an actuator assembly according to the present invention. The mechanics of these actuator assemblies **1** are described, for example, in WO 2013 175197 A1 or WO 2017 072525 A1, which are herein incorporated by reference.

(210) The actuator assemblies **1** comprise a support structure **10** and a movable part **20**. The movable part **20** is movable in a movement plane within a range of movement. In particular, the movable part **20** may be movable both translationally and rotationally in the movement plane, i.e. with three DOFs in the movement plane. The actuator assembly **1** comprises a total of four SMA wires **40** connected between the movable part **20** and the support structure **10** in an arrangement wherein none of the SMA wires **40** are collinear, and wherein the SMA wires **40** are capable of being selectively driven to move the movable part **10** relative to the support structure to any position in said range of movement without applying any net torque to the movable part **20** around a primary axis perpendicular to the movement plane.

(211) For example, two of the SMA wires **40** may be connected between the movable part **20** and the support structure **10** to each apply a torque to the movable part **20** in said movement plane around the primary axis in a first sense around the primary axis and the other two SMA wires **40** are connected between the movable part **20** and the support structure **10** to each apply a torque to the movable part in said movement plane around the primary axis in a second, opposite sense around the primary axis. The four SMA wires **40** may be arranged in a loop at different angular positions around the primary axis, successive SMA wires around the primary axis being connected to apply a force to the movable element in alternate senses around the primary axis.

(212) In general, fewer than four SMA wires **40** may be provided, for example two SMA wires **40** for driving movement of the movable part translationally in the plane (and opposed by resilient elements, such as springs) or three SMA wires **40** for driving movement of the movable part translationally in the plane.

(213) A lens assembly may be fixed relative to the movable part and an image sensor may be fixed relative to the support structure, as described in WO 2013 175197 A1. Alternatively, an image sensor may be fixed relative to the movable part and a lens assembly may be fixed relative to the support structure, as described in WO 2017 072525 A1. In either case, movement of the lens relative to the image sensor may effect OIS.

(214) FIG. **11A** shows a side view and FIG. **11B** shows a plan view of an actuator assembly **1**. The biasing arrangement **30** is comprised by the support structure **10**. So, the biasing arrangement **30** remains static with the support structure **10** upon movement of the movable part **20**. Put another way, the support structure **10** comprises two portions that are coupled via a resilient element of the biasing arrangement **30**.

(215) In particular, the biasing arrangement **30** comprises four resilient elements in the form of four flexures. A first end of each of the flexures is fixed relative to the support structure **10**. An SMA wire **40** is connected to the second end of each flexure. The second end of each flexure comprises the first friction surface **10f** that engages the second friction surface **20f** on the movable part **20**. The flexure is preloaded so as to bias the friction surfaces **10f**, **20f** together. The flexures additionally provide a biasing force to urge the bearing arrangement **50**, which in the depicted embodiment is in the form of a ball bearing.

(216) In the embodiment of FIG. **11**, the flexures are angled relative to the SMA wires. As a result, the flexures may be deformed (e.g. upward in FIG. **12B**) on contraction of the SMA wire **40**. The frictional force F between the friction surfaces **10f**, **20f** may thereby be reduced. In particular, in the opposing wire configuration of FIG. **11**, equal contraction of the SMA wires **40** may reduce the frictional force F without movement of the movable part **20**, whereas differing contraction of the SMA wires **40** may result in movement of the movable part **20**.

(217) FIG. 12A shows a plan view and FIG. 12B shows a side view of an actuator assembly 1. The biasing arrangement 30 is comprised partly by the support structure 10 and partly by the movable part 20.

(218) So, part of the biasing arrangement 30 remains static with the support structure 10 upon movement of the movable part 20, and part of the biasing arrangement 30 moves with the movable part 20 upon movement of the movable part 20. In particular, the biasing arrangement 30 comprises four pairs of resilient elements, in the form of four pairs of flexures, each pair comprising a first flexure and a second flexure.

(219) A first end of each of the first flexures is fixed relative to the support structure 10. A first end of each of the second flexures is fixed relative to the movable part 20. An SMA wire 40 is connected between the second end of each pair of flexures. The second end of each flexure comprises a first friction surface 10f that engages a respective second friction surface 20f on the movable part 20. The flexures are preloaded so as to bias the friction surfaces 10f, 20f together. The flexures may additionally provide a biasing force to load the bearing arrangement 50.

(220) In the embodiment of FIG. 12, the SMA wires 40 are parallel to the flexures. However, the SMA wires are offset from the pair of flexures (i.e. spaced above the flexures in FIG. 12B), i.e. the SMA wire 40 is not arranged in the same plane as the respective flexures. As a result, the flexures may be biased (e.g. upward in FIG. 12B) on contraction of the SMA wire 40. The frictional force F between the friction surfaces 10f, 20f may thereby be reduced.

(221) There is thus provided an actuator assembly comprising a support structure comprising a first friction surface and a movable part comprising a second friction surface engaging the first friction surface, one or more SMA wires arranged, on contraction, to move the movable part relative to the support structure to any position within a range of movement, a biasing arrangement arranged to bias the first and second friction surfaces against each other with a normal force, thereby generating a static frictional force that constrains the movement of the movable part relative to the support structure at any position within the range of movement when the one or more SMA wires are not contracted. The biasing arrangement may be comprised by the movable part or by the support structure. This includes being comprised partly by the movable part and partly by the support structure. So, the biasing arrangement may move with the movable part or remain static relative to the support structure. The biasing arrangement is arranged to apply the normal force only in a direction perpendicular to the range of movement at any position within the range of movement. The one or more SMA wires are arranged, on contraction, to reduce the normal force between first and second friction surfaces.

(222) The actuator assembly 1 may comprise a total of four SMA wires 40. The SMA wires 40 may be arranged so as to drive movement of the movable part 20 in three degrees of freedom in a movement plane. The friction surfaces 10f, 20f may be parallel to the movement plane. The biasing arrangement comprises a resilient element that is comprised by the movable part and/or a resilient element that is comprised by the support structure. Each resilient element is connected at one end to one of the movable element or to the support structure, and at the other end to a respective SMA wire. The other end of the respective SMA wire is connected to the other of the movable element or to the support structure, or to another resilient element that is connected to the other of the movable element or to the support structure. Each resilient element may bias friction surfaces 10f, 20f against each other. Each resilient element may load a bearing arrangement comprised by the actuator assembly 1. The resilient element may be angled relative to the SMA wire. Alternatively, the resilient element may be parallel to the SMA wire, but the SMA wire may not be co-planar with the resilient element.

(223) The term 'shape memory alloy (SMA) wire' may refer to any element comprising SMA. The SMA wire may be described generally as an SMA element. The SMA element may have any shape that is suitable for the purposes described herein. The SMA element may be elongate and may have a round cross section or any other shape cross section. The cross section may vary along the length

of the SMA element. The SMA element might have a relatively complex shape such as a helical spring. It is also possible that the length of the SMA element (however defined) may be similar to one or more of its other dimensions. The SMA element may be sheet-like, and such a sheet may be planar or non-planar. The SMA element may be pliant or, in other words, flexible. In some examples, when connected in a straight line between two components, the SMA element can apply only a tensile force which urges the two components together. In other examples, the SMA element may be bent around a component and can apply a force to the component as the SMA element tends to straighten under tension. The SMA element may be beam-like or rigid and may be able to apply different (e.g. non-tensile) forces to elements. The SMA element may or may not include material(s) and/or component(s) that are not SMA. For example, the SMA element may comprise a core of SMA and a coating of non-SMA material. Unless the context requires otherwise, the term 'SMA element' may refer to any configuration of SMA material acting as a single actuating element which, for example, can be individually controlled to produce a force on an element. For example, the SMA element may comprise two or more portions of SMA material that are arranged mechanically in parallel and/or in series. In some arrangements, the SMA element may be part of a larger SMA element. Such a larger SMA element might comprise two or more parts that are individually controllable, thereby forming two or more SMA elements. The SMA element may comprise an SMA wire, SMA foil, SMA film or any other configuration of SMA material. The SMA element may be manufactured using any suitable method, for example by a method involving drawing, rolling or deposition and/or other forming process(es). The SMA element may exhibit any shape memory effect, e.g. a thermal shape memory effect or a magnetic shape memory effect, and may be controlled in any suitable way, e.g. by Joule heating, another heating technique or by applying a magnetic field.

(224) In general, although the present invention has been described in relation to an SMA wire, actuator components other than SMA wires may be used. For example, a voice coil motor (VCM), piezoelectric element or other actuator may be used in place of the SMA wire in any of the above-described embodiments. As such, any reference to SMA wire in the above may be replaced with actuator component, and any reference to contraction of an SMA wire with actuation of the actuator component.

(225) Aspects of the present invention are set out in the following clauses. The claims of the present application are provided further below under the heading "claims". 1. An actuator assembly comprising: a support structure comprising a first friction surface; a movable part comprising a second friction surface engaging the first friction surface; one or more SMA wires arranged, on contraction, to move the movable part relative to the support structure to any position within a range of movement; a biasing arrangement arranged to bias the first and second friction surfaces against each other with a normal force, thereby generating a static frictional force that constrains the movement of the movable part relative to the support structure at any position within the range of movement when the one or more SMA wires are not contracted, wherein the biasing arrangement is comprised by the movable part or by the support structure so as to move with the movable part or remain static relative to the support structure, and is arranged to apply the normal force only in a direction perpendicular to the range of movement at any position within the range of movement; wherein the one or more SMA wires are arranged, on contraction, to reduce the normal force between first and second friction surfaces. 2. An actuator assembly according to clause 1, wherein the movable part comprises two portions that are coupled via the biasing arrangement or wherein the support structure comprises two portions that are coupled via the biasing arrangement. 3. An actuator assembly according to clause 1 or 2, wherein the biasing arrangement comprises a resilient element. 4. An actuator assembly according to clause 3, wherein the biasing arrangement comprises one or more flexures. 5. An actuator assembly according to any preceding clause, wherein the actuator assembly comprises a bearing arrangement for bearing movement of the movable part relative to the support structure.

Optionally, wherein the biasing arrangement is arranged to load the bearing arrangement. 6. An actuator assembly according to clause 2 and clause 5, wherein the bearing arrangement is provided on one portion of the support structure or movable part, and wherein the first or second friction surface is provided on the other portion of the support structure or movable part. 7. An actuator assembly according to clause 6, wherein the one or more SMA wires are coupled to the other portion of the support structure or movable part. 8. An actuator assembly according to clause 6 or 7, wherein the other portion of the support structure or movable part is formed integrally with the biasing arrangement. 9. An actuator assembly according to any one of clauses 5 to 8, wherein the one or more SMA wires are arranged, on contraction, to load the bearing arrangement. 10. An actuator assembly according to any one of clauses 5 to 9, wherein the bearing arrangement comprises a rolling bearing, the rolling bearing comprising a support bearing surface on the support structure, a movable bearing surface on the movable part and a rolling bearing element arranged between the support bearing surface and the movable bearing surface. 11. An actuator assembly according to clause 10, wherein the support bearing surface and movable bearing surface are parallel to the first and second friction surfaces. 12. An actuator assembly according to any one of clauses 5 to 9, wherein the bearing arrangement comprises a plain bearing formed between an engaging surface on the support structure in engagement with a corresponding engaging surface on the movable part. 13. An actuator assembly according to any one of clauses 5 to 12, wherein the bearing arrangement is separate from the first and second friction surfaces. 14. An actuator assembly according to any one of clauses 5 to 13, wherein the bearing arrangement constrains movement of the movable part relative to the support structure to movement in three degrees of freedom. 15. An actuator assembly according to clause 14, wherein the bearing arrangement constrains movement of the movable part relative to the support structure to movement in a movement plane. 16. An actuator assembly according to any one of clauses 5 to 13, wherein the bearing arrangement constrains movement of the movable part relative to the support structure to movement in one degree of freedom. 17. An actuator assembly according to clause 16, wherein the bearing arrangement constrains movement of the movable part relative to the support structure to helical movement about a helical axis. 18. An actuator assembly according to clause 16, wherein the bearing arrangement constrains movement of the movable part relative to the support structure to translational movement along a movement axis or rotational movement about a rotation axis. 19. An actuator assembly according to any preceding clause, wherein the one or more SMA wires are arranged, on contraction, to reduce the normal force between first and second friction surfaces by at least 10%, preferably at least 20%, most preferably by at least 50%. 20. An actuator assembly according to any preceding clause, wherein the one or more SMA wires are arranged, on contraction, to disengage the first and second frictional surfaces. 21. An actuator assembly according to any preceding clause, wherein the one or more SMA wires are arranged, on contraction, to lift at least a portion of the movable part into engagement with an endstop. 22. An actuator assembly according to clause 21, wherein the endstop is arranged on another portion of the movable part. 23. An actuator assembly according to any preceding clause, wherein the ratio of the static frictional force to weight of the movable part is greater than 1, preferably greater than 3, further preferably greater than 5. 24. An actuator assembly according to any preceding clauses, wherein the coefficient of static friction between the first and second friction surfaces is in the range between 0.05 and 0.6, preferably in the range between 0.1 and 0.4. 25. An actuator assembly according to any one of the preceding clauses, wherein the one or more SMA wires apply forces to the movable part that are angled relative to the first and second friction surfaces. 26. An actuator assembly according to any one of the preceding clauses, wherein the one or more SMA wires are angled relative to the first and second friction surfaces. 27. An actuator assembly according to any one of the preceding clauses, wherein the one or more SMA wires are angled with respect to one or more directions of movement of the movable part relative to the support structure. 28. An actuator assembly according to any one of the preceding clauses, wherein the one or more SMA wires

comprise at least two opposing SMA wires arranged, on contraction, to both reduce the normal force between first and second friction surfaces, and to move the movable part in opposite directions within the range of movement. 1a. An actuator assembly comprising: a support structure comprising a first friction surface; a movable part comprising a second friction surface engaging the first friction surface; a bearing arrangement for bearing movement of the movable part relative to the support structure within a range of movement; one or more SMA wires arranged, on contraction, to move the movable part relative to the support structure to any position within the range of movement; a biasing arrangement arranged to bias the first and second friction surfaces against each other with a normal force, thereby generating a static frictional force that constrains the movement of the movable part relative to the support structure at any position within the range of movement when the one or more SMA wires are not contracted, wherein the one or more SMA wires are arranged, on contraction, to lift the movable part off the first friction surface such that the movable part bears on the bearing arrangement.

Optionally, wherein the biasing arrangement is arranged to load the bearing arrangement. 2a. An actuator assembly according to clause 1a, wherein the biasing arrangement is connected between the movable part and the support structure. 3a. An actuator assembly according to clause 2a, wherein the one or more SMA wires are configured, on contraction, to lift the movable part off the first friction surface and onto the bearing arrangement. 4a. An actuator assembly according to clause 1a, wherein the biasing arrangement is comprised by the movable part or by the support structure so as to move with the movable part or remain static relative to the support structure, and is arranged to apply the normal force only in a direction perpendicular to the range of movement at any position within the range of movement. 5a. An actuator assembly according to clause 1a or 4a, wherein the movable part comprises two portions that are coupled via the biasing arrangement or wherein the support structure comprises two portions that are coupled via the biasing arrangement. 6a. An actuator assembly according to clause 5a, wherein the bearing arrangement bears movement of one portion of the support structure or movable part, and wherein the first or second friction surface is provided on the other portion of the support structure or movable part. 7a. An actuator assembly according to clause 5a or 6a, comprising an endstop formed between the two portions of the movable part or between the two portions of the support structure. 8a. An actuator assembly according to clause 7a, wherein the one or more SMA wires are configured, on contraction, to disengage the friction surfaces and to engage the endstop. 9a. An actuator assembly according to any one of clauses 5a to 8a, wherein the one or more SMA wires are connected to the other portion of the support structure or movable part. 10a. An actuator assembly according to any one of clauses 5a to 9a, wherein the other portion of the movable part is formed integrally with the biasing arrangement. 11a. An actuator assembly according to any one of clauses 1a to 10a, wherein the biasing arrangement comprises a resilient element. 12a. An actuator assembly according to clause 11, wherein the biasing arrangement comprises one or more flexures. 13a. An actuator assembly according to any one of clauses 1a to 12a, wherein the one or more SMA wires are arranged, on contraction, to load the bearing arrangement. 14a. An actuator assembly according to any one of clauses 1a to 13a, wherein the bearing arrangement comprises a rolling bearing, the rolling bearing comprising a support bearing surface on the support structure, a movable bearing surface on the movable part and a rolling bearing element arranged between the support bearing surface and the movable bearing surface. 15a. An actuator assembly according to clause 14a, wherein the support bearing surface and movable bearing surface are parallel to the first and second friction surfaces. 16a. An actuator assembly according to any one of clauses 1a to 13a, wherein the bearing arrangement comprises a plain bearing formed between an engaging surface on the support structure in engagement with a corresponding engaging surface on the movable part. 17a. An actuator assembly according to any one of clauses 1a to 17a, wherein the bearing arrangement is separate from the first and second friction surfaces. 18a. An actuator assembly according to any one of clauses 1a to 17a, wherein the ratio of the static frictional force to weight of the movable part is

greater than 1, preferably greater than 3, further preferably greater than 5. 19a. An actuator assembly according to any one of clauses 1a to 18a, wherein the coefficient of static friction between the first and second friction surfaces is in the range between 0.05 and 0.6, preferably in the range between 0.1 and 0.4. 20a. An actuator assembly according to any one of clauses 1a to 19a, wherein the one or more SMA wires apply forces to the movable part that are angled relative to the first and second friction surfaces. 21a. An actuator assembly according to any one of clauses 1a to 20a, wherein the one or more SMA wires are angled relative to the first and second friction surfaces. 22a. An actuator assembly according to any one of clauses 1a to 21a, wherein the one or more SMA wires are angled with respect to one or more directions of movement of the movable part relative to the support structure. 23a. An actuator assembly according to any one of clauses 1a to 22a, wherein the one or more SMA wires comprise at least two opposing SMA wires arranged, on contraction, to both reduce the normal force between first and second friction surfaces, and to move the movable part in opposite directions within the range of movement. 24a. An actuator assembly according to any one of clauses 1a to 23a, wherein the bearing arrangement constrains movement of the movable part relative to the support structure to movement in three degrees of freedom. 25a. An actuator assembly according to clause 24a, wherein the bearing arrangement constrains movement of the movable part relative to the support structure to movement in a movement plane. 26a. An actuator assembly according to any one of clauses 1a to 23a, wherein the bearing arrangement constrains movement of the movable part relative to the support structure to movement in one degree of freedom. 27a. An actuator assembly according to clause 26a, wherein the bearing arrangement constrains movement of the movable part relative to the support structure to helical movement about a helical axis. 28a. An actuator assembly according to clause 26a, wherein the bearing arrangement constrains movement of the movable part relative to the support structure to translational movement along a movement axis or rotational movement about a rotation axis.

Claims

1. An actuator assembly comprising: a support structure comprising a first friction surface; a movable part comprising a second friction surface engaging the first friction surface; one or more shape memory alloy (SMA) wires arranged, on contraction, to move the movable part relative to the support structure to any position within a range of movement; and a biasing arrangement arranged to bias the first and second friction surfaces against each other with a normal force, thereby generating a static frictional force that constrains the movement of the movable part relative to the support structure at any position within the range of movement when the one or more SMA wires are not contracted, wherein the one or more SMA wires are arranged, on contraction, to reduce the normal force between the first and the second friction surfaces.
2. The actuator assembly according to claim 1, wherein: the movable part comprises two portions that are coupled via the biasing arrangement; or the support structure comprises two portions that are coupled via the biasing arrangement.
3. The actuator assembly according to claim 1, wherein the biasing arrangement is connected between the movable part and the support structure.
4. The actuator assembly according to claim 1, wherein the biasing arrangement comprises a resilient element.
5. The actuator assembly according to claim 1, wherein the actuator assembly comprises a bearing arrangement for bearing movement of the movable part relative to the support structure, optionally wherein the biasing arrangement is arranged to load the bearing arrangement.
6. The actuator assembly according to claim 5, wherein the one or more SMA wires are arranged, on contraction, to lift the movable part off the first friction surface such that the movable part bears on the bearing arrangement.

7. The actuator assembly according to claim 6, wherein the one or more SMA wires are configured, on contraction, to lift the movable part off the first friction surface and onto the bearing arrangement.
 8. The actuator assembly according to claim 2, wherein: the actuator assembly comprises a bearing arrangement for bearing movement of the movable part relative to the support structure, optionally wherein the biasing arrangement is arranged to load the bearing arrangement; the bearing arrangement is provided on one portion of the support structure or movable part; and the first or second friction surface is provided on the other portion of the support structure or movable part.
 9. The actuator assembly according to claim 8, wherein the one or more SMA wires are coupled to the other portion of the support structure or movable part.
 10. The actuator assembly according to claim 5, wherein the one or more SMA wires are arranged, on contraction, to load the bearing arrangement.
 11. The actuator assembly according to claim 5, wherein the bearing arrangement comprises a rolling bearing, the rolling bearing comprising; a support bearing surface on the support structure; a movable bearing surface on the movable part; and a rolling bearing element arranged between the support bearing surface and the movable bearing surface.
 12. The actuator assembly according to claim 5, wherein the bearing arrangement comprises the first and second friction surfaces.
 13. The actuator assembly according to claim 5, wherein the bearing arrangement constrains movement of the movable part relative to the support structure to movement in three degrees of freedom.
 14. The actuator assembly according to claim 5, wherein the bearing arrangement constrains movement of the movable part relative to the support structure to movement in one degree of freedom.
 15. The actuator assembly according to claim 1, wherein the one or more SMA wires are arranged, on contraction, to reduce the normal force between first and second friction surfaces by at least 10%.
 16. The actuator assembly according to claim 1, wherein the one or more SMA wires are arranged, on contraction, to disengage the first and second frictional surfaces.
 17. The actuator assembly according to claim 1, wherein the one or more SMA wires are arranged, on contraction, to lift at least a portion of the movable part into engagement with an endstop.
 18. The actuator assembly according to claim 17, wherein the endstop is arranged on another portion of the movable part.
 19. The actuator assembly according to claim 1, wherein the ratio of the static frictional force to weight of the movable part is greater than 1.
 20. The actuator assembly according to claim 1, wherein the one or more SMA wires apply forces to the movable part that are angled relative to the first and second friction surfaces.
-