

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410824
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Zhan; Yongyong et al.

Hydraulic oil-circuit system and hydraulic jack

Abstract

A hydraulic oil-circuit system and a hydraulic jack are proposed. The hydraulic oil-circuit system includes a hydraulic cylinder, an oil loading chamber, a storage oil chamber and an oil unloading pipeline; a piston is arranged in the hydraulic cylinder and divides the hydraulic cylinder into a first hydraulic oil chamber and a second hydraulic oil chamber; the first hydraulic oil chamber has a first oil port, and the second hydraulic oil chamber has a second oil port; the first oil port and the second oil port are both in unidirectional communication with the oil loading chamber and are both in unidirectional communication with the storage oil chamber; and the oil unloading pipeline connects the oil loading chamber and the storage oil chamber.

Inventors: Zhan; Yongyong (Zhejiang, CN), Du; Xinfu (Zhejiang, CN), Wang; Songfeng (Zhejiang, CN), Ruan; Binhao (Zhejiang, CN)

Applicant: T-MAX (HANGZHOU) TECHNOLOGY CO., LTD. (Zhejiang, CN)

Family ID: 84193855

Assignee: T-MAX (HANGZHOU) TECHNOLOGY CO., LTD. (Zhejiang, CN)

Appl. No.: 17/731409

Filed: April 28, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220381265 A1	Dec. 01, 2022

Foreign Application Priority Data

CN	202110573888.8	May. 25, 2021
CN	202110573889.2	May. 25, 2021
CN	202121137294.4	May. 25, 2021
CN	202121140078.5	May. 25, 2021

Publication Classification

Int. Cl.: F15B15/14 (20060101); B66F3/28 (20060101); B66F3/38 (20060101); B66F3/42 (20060101); F15B1/26 (20060101)

U.S. Cl.:

CPC F15B15/149 (20130101); B66F3/28 (20130101); B66F3/38 (20130101); B66F3/42 (20130101); F15B1/26 (20130101);

Field of Classification Search

CPC: B66F (3/28); B66F (3/38); B66F (3/42); F15B (15/149); F15B (1/26)

USPC: 254/93R

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5524868	12/1995	Decker	254/93H	B66F 3/42
6042085	12/1999	Tang	254/93H	B66F 3/42
6199379	12/2000	Hung	60/482	F15B 7/04
6247307	12/2000	Hung	60/479	B66F 3/42
6347786	12/2001	Lai	254/93H	B66F 3/42
7421841	12/2007	Yueh	254/93H	B66F 5/04
2009/0057633	12/2008	Beck et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1182047	12/1997	CN	N/A
2294340	12/1997	CN	N/A
202508822	12/2011	CN	N/A
104228784	12/2013	CN	N/A
205133020	12/2015	CN	N/A
111017786	12/2019	CN	N/A
3000766	12/2015	EP	N/A

OTHER PUBLICATIONS

Qin Baojun, "ISR for PCT Application PCT/CN2021/095858", Feb. 25, 2022, CNIPA, China. cited by applicant

Xu Changhong, "ISR for PCT Application PCT/CN2021/095857", Mar. 2, 2022, CNIPA, China. cited by applicant

Examiner, "Office Action for CN Application No. 202110573888.8", Jul. 5, 2022, CNIPA, China. cited by applicant

Ong Guoqin, "Office Action for CN Application No. 202110573889.2", Jul. 15, 2023, CNIPA, China. cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is based on and claims priority to Chinese Application No. 202110573889.2, No. 202110573888.8, No. 202121137294.4, and No. 202121140078.5, all filed on May 25, 2021, the entire contents of which are incorporated herein by reference for all purposes.

FIELD

(2) This application relates to the field of mechanical equipment and, more particularly, to a hydraulic oil-circuit system and a hydraulic jack.

BACKGROUND

(3) In hydraulic jacks of the related art, telescopic rods are driven to reciprocate through mutual transfer of liquid oil in two areas of the jacks, and a jacking function can be realized by a one-way valve and a cross-section difference. The hydraulic jacks generally lift weights simply by pressing a single piston downward, but due to the structural limitation, the weights can have a lifting stroke only when the piston is pressed downward. That is, there is no lifting stroke when the piston is pulled upward. At the same time, support blocks of the existing jacks are fixed, and if the weights are too far away from the support blocks, the jacks cannot support the weights, or most of the lifting stroke is wasted as an idle stroke.

(4) Therefore, the existing hydraulic jacks have defects in terms of the structure and hydraulic oil-circuit system.

SUMMARY

(5) A hydraulic oil-circuit system of a hydraulic jack includes: a hydraulic cylinder, a piston being arranged in the hydraulic cylinder and dividing an interior of the hydraulic cylinder into a first hydraulic oil chamber and a second hydraulic oil chamber, in which the first hydraulic oil chamber has a first oil port, and the second hydraulic oil chamber has a second oil port; an oil loading chamber in unidirectional communication with the first oil port and the second oil port, to allow unidirectional flow from the first oil port and the second oil port to the oil loading chamber; a storage oil chamber in unidirectional communication with the first oil port and the second oil port are both in unidirectional communication, to allow unidirectional flow from the storage oil chamber to the first oil port and the second oil port; an oil unloading pipeline connecting the oil loading chamber with the storage oil chamber. The hydraulic cylinder is a double-acting hydraulic cylinder, reciprocating motion of the piston changes volumes of the first hydraulic oil chamber and the second hydraulic oil chamber, and one of the first oil port and the second oil port delivers hydraulic oil to the oil loading chamber, while the other of the first oil port and the second oil port sucks oil from the storage oil chamber.

(6) A hydraulic jack includes: an outer oil barrel, a handle being arranged on the outer oil barrel; an inner oil barrel, the outer oil barrel being fitted over the inner oil barrel and movable relative to the inner oil barrel, and the outer oil barrel and the inner oil barrel forming a storage oil chamber; a hydraulic cylinder arranged in the inner oil barrel and movable along an axial direction of the inner oil barrel in a sealing manner, in which an oil loading chamber and the storage oil chamber are formed at two ends of the hydraulic cylinder; a piston is arranged in the hydraulic cylinder and divides an interior of the hydraulic cylinder into a first hydraulic oil chamber and a second hydraulic oil chamber; the first hydraulic oil chamber has a first oil port, and the second hydraulic oil chamber has a second oil port; the first oil port and the second oil port are both in unidirectional communication with the oil loading chamber, to allow unidirectional flow from the first oil port and the second oil port to the oil loading chamber; the first oil port and the second oil port are both

in unidirectional communication with the storage oil chamber, to allow unidirectional flow from the storage oil chamber to the first oil port and the second oil port; the hydraulic cylinder has an oil unloading pipeline connecting the oil loading chamber with the storage oil chamber; a piston rod having a first end connected to the piston and a second end connected to the handle, in which the handle drives the piston to reciprocate through the piston rod, to change volumes of the first hydraulic oil chamber and the second hydraulic oil chamber, and one of the first oil port and the second oil port delivers hydraulic oil to the oil loading chamber, while the other of the first oil port and the second oil port sucks oil from the storage oil chamber.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic diagram of a hydraulic oil-circuit system according to embodiments of the present disclosure;
- (2) FIG. 2 is a sectional view of a hydraulic jack in a first section plane according to embodiments of the present disclosure;
- (3) FIG. 3 is a partially enlarged view of part A in FIG. 2;
- (4) FIG. 4 is a partial sectional view of a hydraulic jack in a second section plane according to embodiments of the present disclosure;
- (5) FIG. 5 is a partially enlarged view of part B in FIG. 4;
- (6) FIG. 6 is a top view illustrating the assembly of a hydraulic cylinder, a piston rod and other components according to embodiments of the present disclosure;
- (7) FIG. 7 is a sectional view along A-A of FIG. 6;
- (8) FIG. 8 is a sectional view along B-B of FIG. 6;
- (9) FIG. 9 and FIG. 10 are perspective views of an oil-circuit main body arranged at different angles according to embodiments of the present disclosure;
- (10) FIG. 11 is an exploded view of a bearing assembly mounted on an outer oil barrel according to embodiments of the present disclosure;
- (11) FIG. 12 and FIG. 13 are sectional views of a bearing assembly mounted on an outer oil barrel according to embodiments of the present disclosure;
- (12) FIG. 14 and FIG. 15 are sectional views of a bearing assembly mounted on an outer oil barrel according to embodiments of the present disclosure, in which pins are located in different positions;
- (13) FIG. 16 is a perspective view of a sliding block and a jacking block according to embodiments of the present disclosure;
- (14) FIG. 17 is a schematic diagram of a hydraulic jack used as a manual winch according to embodiments of the present disclosure.

DETAILED DESCRIPTION OF EMBODIMENTS

(15) Embodiments of the present disclosure are described in detail below, and examples of the described embodiments are shown in accompanying drawings. The following embodiments described with reference to the accompanying drawings are exemplary and are intended to explain the present disclosure rather than limit the present disclosure.

(16) FIG. 1 shows a hydraulic oil-circuit system of a hydraulic jack according to some embodiments of the present disclosure. Depending on purposes and methods of use, the hydraulic jack can lift or pull a weight. The hydraulic oil-circuit system mainly includes: a hydraulic cylinder 10, an oil loading chamber 20, a storage oil chamber 30 and an oil unloading pipeline 21.

(17) Specifically, a piston 13 is arranged in the hydraulic cylinder 10 and divides an interior of hydraulic cylinder 10 into a first hydraulic oil chamber 11 and a second hydraulic oil chamber 12. The first hydraulic oil chamber 11 has a first oil port, and the second hydraulic oil chamber 12 has a

second oil port; the first oil port and the second oil port are both in unidirectional communication with the oil loading chamber **20**, to allow unidirectional flow from the first oil port and the second oil port to the oil loading chamber **20**; the first oil port and the second oil port are both in unidirectional communication with the storage oil chamber **30**, to allow unidirectional flow from the storage oil chamber **30** to the first oil port and the second oil port.

(18) In some embodiments, the hydraulic cylinder **10** is a double-acting hydraulic cylinder, that is, the first hydraulic oil chamber **11** and the second hydraulic oil chamber **12** are both working chambers. Thus, reciprocating motion of the piston **13** can change volumes of the first hydraulic oil chamber **11** and the second hydraulic oil chamber **12**, so that one of the first oil port and the second oil port delivers hydraulic oil to the oil loading chamber **20**, and the other thereof sucks oil from the storage oil chamber **30**.

(19) As shown in FIG. **1**, when a handle **41** is pressed down, the second hydraulic oil chamber **12** is compressed, and the hydraulic oil is pressed into the oil loading chamber **20** through a fourth one-way valve **124**, and a liquid level in the oil loading chamber **20** is raised. During this process, the volume of the first hydraulic oil chamber **11** increases, thus sucking the hydraulic oil from the storage oil chamber **30** through a first one-way valve **113**. When the handle **41** is lifted up, the first hydraulic oil chamber **11** is compressed, so that the hydraulic oil in the first hydraulic oil chamber **11** is pressed into the oil loading chamber **20** through a second one-way valve **114**, and the liquid level in the oil loading chamber **20** is raised. During this process, the volume of the second hydraulic oil chamber **12** increases, thus sucking the hydraulic oil from the storage oil chamber **30** through a third one-way valve **123**.

(20) Due to the design of the hydraulic cylinder **10** as the double-acting hydraulic cylinder and in combination with the control over the unidirectional flow of oil circuit, the liquid level in the oil loading chamber **20** can be raised regardless of pressing down or lifting up the handle **41**, thus improving the working efficiency.

(21) In some embodiments, a bearing assembly **80** for supporting the weight can be arranged outside the storage oil chamber **30** and fixed relative to the storage oil chamber **30**. The bearing assembly **80** can be omitted, and an effect of supporting the weight can be realized directly by using an external structure of the storage oil chamber **30**.

(22) In the above embodiments, an oil unloading pipeline **21** is provided, and the oil unloading pipeline **21** connects the oil loading chamber **20** and the storage oil chamber **30**. After the hydraulic oil-circuit system completes a lifting or pulling operation, the hydraulic oil in the oil loading chamber **20** can flow into the storage oil chamber **30** through the oil unloading pipeline **21**. An unloading switch **211** is arranged at the oil unloading pipeline **21** and can control opening and closing of the oil unloading pipeline **21**.

(23) In some embodiments, the first oil port is in communication with the storage oil chamber **30** through a first oil inlet line **111** and is in communication with the oil loading chamber **20** through a first oil outlet line **112**; the first one-way valve **113** is arranged at the first oil inlet line **111**; and the second one-way valve **114** is arranged at the first oil outlet line **112**. The second oil port is in communication with the storage oil chamber **30** through a second oil inlet line **121** and is in communication with the oil loading chamber **20** through a second oil outlet line **122**; the third one-way valve **123** is arranged at the second oil inlet line **121**; and the fourth one-way valve **124** is arranged at the second oil outlet line **122**.

(24) Thus, the unidirectional communication of the first oil port and the second oil port with the oil loading chamber **20** can be realized, and the unidirectional communication of the first oil port and the second oil port with the storage oil chamber **30** can be realized. Besides the embodiments, other embodiments can also realize the unidirectional communication of the first oil port and the second oil port with the oil loading chamber **20**, and the unidirectional communication of the first oil port and the second oil port with the storage oil chamber **30**.

(25) In some embodiments, a first overload protection oil circuit **115** is connected between the first

hydraulic oil chamber **11** and the storage oil chamber **30**, and a second overload protection oil circuit **125** is connected between the second hydraulic oil chamber **12** and the storage oil chamber **30**. When a pressure in the first hydraulic oil chamber **11** is greater than a first preset value, the first overload protection oil circuit **115** is opened to release the pressure to the storage oil chamber **30**, avoiding damage to the hydraulic cylinder **10**. Similarly, when a pressure in the second hydraulic oil chamber **12** is greater than a second preset value, the second overload protection oil circuit **125** is opened to release the pressure to the storage oil chamber **30**, avoiding damage to the hydraulic cylinder **10**.

(26) Specifically, a first pressure one-way valve **1151** can be arranged at the first overload protection oil circuit **115**, and a second pressure one-way valve **1251** can be arranged at the second overload protection oil circuit **125**. The first pressure one-way valve **1151** and the second pressure one-way valve **1251** each can only be opened at a preset pressure, and the first preset value and the second preset value can be the same or different.

(27) Referring to FIGS. 2-5, embodiments of the present disclosure provide a hydraulic jack that includes: an outer oil barrel **40**, an inner oil barrel **50**, a hydraulic cylinder **10**, and a piston rod **60**.

(28) Specifically, a handle **41** is arranged on the outer oil barrel **40**; the outer oil barrel **40** is fitted over the inner oil barrel **50** and can move relative to the inner oil barrel **50**; the outer oil barrel **40** and the inner oil barrel **50** form a storage oil chamber **30**; the storage oil chamber **30** may be located inside the inner oil barrel **50**, or may be located between the outer oil barrel **40** and the inner oil barrel **50**, or may be located inside the inner oil barrel **50** and between the outer oil barrel **40** and the inner oil barrel **50**.

(29) The hydraulic cylinder **10** is arranged in the inner oil barrel **50** and can move along an axial direction of the inner oil barrel **50** in a sealing manner. An oil loading chamber **20** and a storage oil chamber **30** are located at two ends of the hydraulic cylinder **10**. A piston **13** is arranged within hydraulic cylinder **10** and divides an interior of the hydraulic cylinder **10** into a first hydraulic oil chamber **11** and a second hydraulic oil chamber **12**. The first hydraulic oil chamber **11** has a first oil port, and the second hydraulic oil chamber **12** has a second oil port. The first oil port and the second oil port are both in unidirectional communication with the oil loading chamber **20**, to allow unidirectional flow from the first oil port and the second oil port to the oil loading chamber **20**. The first oil port and the second oil port are both in unidirectional communication with the storage oil chamber **30**, to allow unidirectional flow from the storage oil chamber **30** to the first oil port and the second oil port. The hydraulic cylinder **10** has an oil unloading pipeline **21** that connects the oil loading chamber **20** and the storage oil chamber **30**.

(30) A first end of the piston rod **60** is connected to the piston **13** and a second end of the piston rod **60** is connected to the handle **41**, so that the handle **41** can drive the piston **13** to reciprocate through the piston rod **60**, to change volumes of the first hydraulic oil chamber **11** and the second hydraulic oil chamber **12**. As a result, one of the first oil port and the second oil port delivers hydraulic oil to the oil loading chamber **20**, and the other thereof sucks oil from the storage oil chamber **30**.

(31) In the above embodiments, the piston rod **60** also plays a supporting role. When the hydraulic oil in the oil loading chamber **20** increases, the hydraulic cylinder **10** is pushed to move upward, and a support force is transmitted to the handle **41** through the piston rod **60** and further to the outer oil barrel **40**, so that the hydraulic cylinder **10**, the outer oil barrel **40** and the piston rod **60** move upward synchronously relative to the inner oil barrel **50**, realizing a jacking or pulling function.

(32) In some embodiments, the outer oil barrel **40** is provided with an oil barrel cover **42**, and the oil barrel cover **42** is arranged in a sealing manner at a top of the outer oil barrel **40**. The handle **41** is hinged to the oil barrel cover **42**, and the piston rod **60** passes through the oil barrel cover **42** and is hinged with the handle **41**. That is, the top of the outer oil barrel **40** in the embodiments is sealed by the oil barrel cover **42**, and meanwhile the oil barrel cover **42** is also used to mount the handle **41**.

(33) Referring to FIG. 3 and FIG. 5, the outer oil barrel **40** is provided with a sleeve **43**, and the sleeve **43** is fixedly connected to a bottom of the outer oil barrel **40**. The sleeve **43** is fitted over the inner oil barrel **50** and can slide along an outer wall of the inner oil barrel **50** in a sealing manner. In some embodiments, the sleeve **43** can play a sealing role at the bottom of the outer oil barrel **40**, and play a guiding role to ensure coaxiality of the outer oil barrel **40** and the inner oil barrel **50** and avoid skew during a rising process of the outer oil barrel **40**.

(34) In some embodiments, a shaft sleeve **431** is arranged on at least part of an inner wall of the sleeve **43**. The shaft sleeve **431** is arranged coaxially with the sleeve **43** and fixed relative to the sleeve **43**. The sleeve **43** is fitted over the outer wall of the inner oil barrel **50**, and can move axially relative to the inner oil barrel **50**. In some embodiments, the shaft sleeve **431** also plays a guiding role, and a plurality of shaft sleeves **431** can be arranged. As shown in FIG. 3, one shaft sleeve **431** is arranged at each of an upper end and a lower end of the sleeve **43**.

(35) In some embodiments, a base sealing body **51** is arranged at a bottom of the inner oil barrel **50** and the base sealing body **51** seals the bottom of the inner oil barrel **50**; a top of the inner oil barrel **50** is located below the oil barrel cover **42** and is open in an inner chamber of the outer oil barrel **40**. As a result, an inner chamber of the inner oil barrel **50** is in communication with the inner chamber of the outer oil barrel **40**, and the storage oil chamber **30** is formed in the inner chamber of the inner oil barrel **50** and the inner chamber of the outer oil barrel **40**. Instead of the arrangement of the base sealing body **51** at the bottom of the inner oil barrel **50**, the bottom of the inner oil barrel **50** can be directly designed as a sealed structure, that is, the inner oil barrel **50** can be a barrel with only one upper opening. When the inner oil barrel **50** is designed to have upper and lower openings, the base sealing body **51** is arranged at the bottom of the inner oil barrel **50** to seal it.

(36) In some embodiments, the base sealing body **51** can also be used as a support foundation of the hydraulic jack, and designed with a larger support surface. A base **52** can also be specially designed. For example, the base sealing body **51** is connected to the base **52**, and the base **52** is detachably connected to the base sealing body **51**. The base **52** can also be removed when necessary.

(37) In some embodiments, referring to FIG. 2, a limiting member **53** is arranged on the outer wall of the inner oil barrel **50** and used to limit a motion range of the outer oil barrel **40**; the limiting member **53** is located at a position above a middle part of the inner oil barrel **50** and fixed relative to the inner oil barrel **50**.

(38) Referring to FIG. 3 and FIGS. 5-8, in some embodiments, the hydraulic cylinder **10** mainly includes: an oil-circuit main body **101**, an oil-circuit upper cover **102**, and an oil-circuit lower cover **103**. An outer wall of the oil-circuit main body **101** is in sealing contact with an inner wall of the inner oil barrel **50**, and the oil-circuit main body **101** can move axially relative to the inner oil barrel **50**. A hydraulic oil chamber running through the oil-circuit main body **101** is formed in the oil-circuit main body **101**, and the piston **13** is arranged in the hydraulic oil chamber and divides the hydraulic oil chamber into the first hydraulic oil chamber **11** and the second hydraulic oil chamber **12**. The oil-circuit upper cover **102** seals an upper end of the hydraulic oil chamber, and the oil-circuit lower cover **103** seals a lower end of the hydraulic oil chamber. The piston rod **60** passes through the oil-circuit upper cover **102** and is connected to the piston **13**. The oil unloading pipeline **21** is formed in the oil-circuit main body **101**. A hydraulic principle of the hydraulic jack according to the embodiments can refer to FIG. 1 and the description about the hydraulic oil-circuit system in the above embodiments.

(39) In some embodiments, referring to FIGS. 7-8, the first oil port is in communication with the storage oil chamber **30** through the first oil inlet line **111** and is in communication with the oil loading chamber **20** through the first oil outlet line **112**, the first one-way valve **113** is arranged at the first oil inlet line **111**, and the second one-way valve **114** is arranged at the first oil outlet line **112**; the second oil port is in communication with the storage oil chamber **30** through the second oil

inlet line **121** and is in communication with the oil loading chamber **20** through the second oil outlet line **122**, the third one-way valve **123** is arranged at the second oil inlet line **121**, and the fourth one-way valve **124** is arranged at the second oil outlet line **122**.

(40) In some embodiments, the first oil inlet line **111** is formed in the oil-circuit upper cover **102**, the first oil outlet line **112** and the second oil inlet line **121** are both formed in the oil-circuit main body **101**, and the second oil outlet line **122** is formed in the oil-circuit lower cover **103**.

(41) In some embodiments, referring to FIG. 9 and FIG. 10, a first sink **1011** is formed at an upper end of the oil-circuit main body **101**, and a second sink **1012** is formed at a lower end of the oil-circuit main body **101**. At least a partial structure of the oil-circuit upper cover **102** is arranged in the first sink **1011**, and at least a partial structure of the oil-circuit lower cover **103** is arranged in the second sink **1012**. An inlet of the first oil outlet line **112** is located in the first sink **1011**, and an outlet of the second oil inlet line **121** is located in the second sink **1012**.

(42) Referring to FIG. 7 and FIG. 8, a certain gap can be formed between a top of the oil-circuit lower cover **103** and a bottom of the second sink **1012**, so that the hydraulic oil at the outlet of the second oil inlet line **121** can flow into the second hydraulic oil chamber **12** quickly. If there is no gap, a channel groove can be arranged at the top of the oil-circuit lower cover **103**. Similarly, a certain gap can be formed between a bottom of the oil-circuit upper cover **102** and a bottom of the first sink **1011**, so that the hydraulic oil in the first hydraulic oil chamber **11** can enter the inlet of the first oil outlet line **112**. If there is no gap, a channel groove can be arranged at the bottom of the oil-circuit upper cover **102**.

(43) In some embodiments, referring to FIG. 2 and FIG. 8, an oil unloading rod **70** is arranged in the inner oil barrel **50**. A first end of the oil unloading rod **70** is arranged at the oil unloading pipeline **21**, and a second end of the oil unloading rod **70** passes through the oil barrel cover **42** and is connected to an oil unloading handle **71**. The oil unloading handle **71** is hinged to the oil barrel cover **42**, and the communication and closing of the oil unloading pipeline **21** can be controlled by the oil unloading rod **70**. Specifically, the oil unloading rod **70** can be provided with a reset spring (not shown in the drawings). When the oil unloading rod **70** is pressed down, a bottom of the oil unloading pipeline **21** is opened, thus connecting the storage oil chamber **30** and the oil loading chamber **20**, and realizing oil unloading and pressure release of the oil loading chamber **20**. When a pressing action on the oil unloading rod **70** is stopped, the oil unloading rod **70** automatically closes the oil unloading pipeline **21** under the action of the reset spring.

(44) In some embodiments, a first overload protection oil circuit **115** is connected between the first hydraulic oil chamber **11** and the storage oil chamber **30**, and a second overload protection oil circuit **125** is connected between the second hydraulic oil chamber **12** and the storage oil chamber **30**. When a pressure in the first hydraulic oil chamber **11** is greater than a first preset value, the first overload protection oil circuit **115** is opened to release the pressure to the storage oil chamber **30**, avoiding damage to the hydraulic cylinder **10**.

(45) Similarly, when a pressure in the second hydraulic oil chamber **12** is greater than a second preset value, the second overload protection oil circuit **125** is opened to release the pressure to the storage oil chamber **30**, avoiding damage to the hydraulic cylinder **10**. Specifically, a first pressure one-way valve **1151** can be arranged at the first overload protection oil circuit **115**, and a second pressure one-way valve **1251** can be arranged at the second overload protection oil circuit **125**. The first pressure one-way valve **1151** and the second pressure one-way valve **1251** each can only be opened at a preset pressure, and the first preset value and the second preset value can be the same or different.

(46) In some embodiments, the first overload protection oil circuit **115** is arranged at the oil-circuit upper cover **102**, and the second overload protection oil circuit **125** is arranged at the piston rod **60**. At least part of the piston rod **60** has a hollow structure, and a bottom end of the piston **13** has an opening, so that the hydraulic oil in the second hydraulic oil chamber **12** can flow into the hollow piston rod **60** through the opening, and then flow to a position of the second pressure one-way

valve **1251**. An outlet of the second pressure one-way valve **1251** is arranged to be communicated with the storage oil chamber **30**.

(47) In some embodiments, the first pressure one-way valve **1151** is arranged at the first overload protection oil circuit **115**, and the second pressure one-way valve **1251** is arranged at the second overload protection oil circuit **125**. The first pressure one-way valve **1151** is opened when a pressure difference on both sides of the first pressure one-way valve **1151** is greater than a first preset value, and the second pressure one-way valve **1251** is opened when a pressure difference on both sides of the second pressure one-way valve **1251** is greater than a second preset value. An opening pressure value for the first pressure one-way valve **1151** and an opening pressure value for the second pressure one-way valve **1251** can be the same or different.

(48) In some embodiments, a piston barrel **61** is fitted over the piston rod **60**, one end of the piston barrel **61** is connected to the oil barrel cover **42**, and the other end of the piston barrel **61** is connected to the hydraulic cylinder **10**. The piston barrel **61** plays a supporting role between the hydraulic cylinder **10** and the oil barrel cover **42**. The hydraulic cylinder **10** moving upward transmits a support force to the oil barrel cover **42** through the piston barrel **61**. When the piston barrel **61** supports the oil barrel cover **42**, the support force of the piston rod **60** on the oil barrel cover **42** decreases or the piston rod **60** has no support force on the oil barrel cover **42**. This arrangement can reduce damage to the piston rod **60** and improve the service life of the hydraulic jack.

(49) In some embodiments, the piston rod **60** includes an upper piston rod **62** and a lower piston rod **63** connected with each other, the upper piston rod **62** is connected to the handle **41**, and the lower piston rod **63** is connected to the piston **13**. The lower piston rod **63** has a hollow structure, and the second pressure one-way valve **1251** is arranged in the lower piston rod **63**. One or more through holes can be arranged in the piston barrel **61** to connect the hydraulic oil in the piston barrel **61** with the storage oil chamber **30**.

(50) In some embodiments, referring to FIGS. **11-15**, a bearing assembly **80** is arranged on an outer wall of the outer oil barrel **40**, the outer wall of the outer oil barrel **40** has a plurality of fixing positions, and the bearing assembly **80** can be fixed at any fixing position and can move between any two fixing positions. During use of the hydraulic jack, if the position of the bearing assembly **80** is far from a lifting surface, the fixing position of the bearing assembly **80** can be first adjusted, and hence the bearing assembly **80** is fixed at a nearest position from the lifting surface. Then, a lifting operation is carried out, and the invalid stroke can be reduced.

(51) Specifically, a snap groove **44** is arranged in each of the fixing positions. The bearing assembly **80** includes: a sliding block **81**, a pin **82** and a jacking block **83**; the sliding block **81** is fitted over the outer wall of the outer oil barrel **40** and can move relative to the outer oil barrel **40**. A pin mounting groove **811** is arranged in the sliding block **81**, and one end of the pin **82** is hinged to the pin mounting groove **811** through a hinge shaft **84**. The pin **82** has an opening state (as shown in FIG. **15**) and a locking state (as shown in FIG. **14**), and can switch between the opening state and the locking state; in the opening state, the sliding block **81** can move relative to the outer oil barrel **40**.

(52) In the locking state, the pin **82** has a partial structure located in the pin mounting groove **811** and a partial structure located in the snap groove **44**, so that the sliding block **81** is fixed relative to the outer oil barrel **40**.

(53) In some embodiments, in the locking state, the pin **82** pivots into the pin mounting groove **811**; in the opening state, the one end of the pin **82** pivots out of the pin mounting groove **811**.

(54) In some embodiments, the jacking block **83** is mounted on the sliding block **81** and can move synchronously with the sliding block **81**. The jacking block **83** is detachably connected to the sliding block **81**. The specific connection mode can be insertion, snap connection, mortise-tenon connection, or threaded connection.

(55) Referring to FIG. **16**, an insertion groove **813** is arranged in the sliding block **81**, and the

insertion groove **813** includes a first guide portion **8131** and a limiting portion **8132**. The jacking block **83** has an insertion portion **831**, and the insertion portion **831** includes a second guide portion **8311** and a limiting block **8312**. The insertion portion **831** can be inserted in the insertion groove **813**, the second guide portion **8311** cooperates with the first guide portion **8131**, and the limiting block **8312** cooperates with the limiting portion **8132**. This insertion structure enables quick connection and quick detachment of the sliding block **81** and the jacking block **83**, and enjoys high stability of connection. Cooperating surfaces of the first guide portion **8131** and the second guide portion **8311** are curved surfaces.

(56) In some embodiments, an elastic pushing assembly **812** is arranged on the sliding block **81**, and a groove **821** is arranged on the pin **82**. When the pin **82** is in the locking state, the elastic pushing assembly **812** abuts against the groove **821**. As shown in FIG. 12 and FIG. 13, the elastic pushing assembly **812** is pushed into the groove **821** to limit rotation of the pin **82**. The limitation of the elastic pushing assembly **812** on the pin **82** can prevent the pin **82** from rotating arbitrarily. By applying a certain external force to the pin **82**, the groove **821** can get rid of the limitation of the elastic pushing assembly **812**, and thus the locking state is switched to the opening state.

(57) In some embodiments, the elastic pushing assembly **812** includes a screw **8121**, a spring **8122** and a push bead **8123**. The sliding block **81** is provided with a mounting through hole; and the screw **8121**, the spring **8122**, and the push bead **8123** are arranged in the mounting through hole. The spring **8122** is compressed between the screw **8121** and the push bead **8123**, and a part of the push bead **8123** can be exposed from an end of the mounting through hole to abut against the groove **821**. As shown in FIG. 14, the pin **82** is located in the pin mounting groove **811**, and the position of the sliding block **81** is fixed. As shown in FIG. 15, the one end of the pin **82** pivots out of the pin mounting groove **811**, and the position of the sliding block **81** can be adjusted up and down.

(58) As shown in FIG. 13, the jacking block **83** is detachably connected with the sliding block **81**. The structure of the jacking block **83** can be in many forms. Anti-skid stripes are arranged on a lifting surface of the jacking block **83**. The lifting surface of the jacking block **83** may be perpendicular to a lifting direction of the outer oil barrel **40** (i.e., a horizontal arrangement shown in FIG. 13) or may be arranged as an inclined surface for use in a special working environment. Therefore, the detachable connection between the jacking block **83** and the sliding block **81** can facilitate replacement of different types of jacking blocks **83**.

(59) In some embodiments, two pins **82** are provided, two pin mounting grooves **811** are arranged in the sliding block **81**, and one pin **82** is hinged to each of the pin mounting grooves **811**; the two pins **82** are symmetrical about a center axis of the outer oil barrel **40**. This arrangement can make the connection between the sliding block **81** and the outer oil barrel **40** firmer and more stable.

(60) In some embodiments, the hydraulic jack also functions as a manual winch, and the specific use method is as follows. Referring to FIG. 17, a fiber rope **5** passes through a base attachment **3**, a base **52**, and a towing attachment **4** (which prevents overturning under force); one end of the fiber rope **5** is connected to a fixed object, and the other end of the fiber rope **5** is connected to the base **52** of the hydraulic jack; one end of a tow chain **2** is connected to an object **1** to be towed, and the other end of the tow chain **2** is fixed to the towing attachment **4** of the hydraulic jack; the handle **41** is pushed and pulled to realize the towing of the object **1**; the tow chain **2** is hooked alternately by a hook on the base attachment **3** and a hook on the towing attachment **4**, so that the object **1** will not slide towards an initial position during reciprocating motion of the hydraulic jack, thus realizing a function of the manual winch.

(61) Referring to FIG. 3, FIG. 5, and FIGS. 7-10, embodiments of the present disclosure provide a hydraulic cylinder **10** that is used to be mounted in an oil barrel. Spaces at two ends of the hydraulic cylinder **10** are an oil loading chamber **20** and a storage oil chamber **30** respectively. The oil loading chamber **20** and the storage oil chamber **30** are sealed relative to each other, and the relative seal of the oil loading chamber **20** and the storage oil chamber **30** is realized by the

hydraulic cylinder **10**.

(62) In some embodiments, the hydraulic cylinder **10** includes: an oil-circuit main body **101**, an oil-circuit upper cover **102**, and an oil-circuit lower cover **103**. The hydraulic oil chamber running through the oil-circuit main body **101** is formed in the oil-circuit main body **101**. A piston **13** is arranged in the hydraulic oil chamber, and the piston **13** divides the hydraulic oil chamber into a first hydraulic oil chamber **11** and a second hydraulic oil chamber **12**. The piston **13** is connected to a piston rod **60**.

(63) The oil-circuit upper cover **102** seals an upper end of the hydraulic oil chamber, and the oil-circuit lower cover **103** seals a lower end of the hydraulic oil chamber. The piston rod **60** passes through the oil-circuit upper cover **102** and is connected to the piston **13**. The first hydraulic oil chamber **11** has a first oil port, and the second hydraulic oil chamber **12** has a second oil port. The first oil port and the second oil port are both in unidirectional communication with the oil loading chamber **20**, to allow unidirectional flow from the first oil port and the second oil port to the oil loading chamber **20**. The first oil port and the second oil port are both in unidirectional communication with the storage oil chamber **30**, to allow unidirectional flow from the storage oil chamber **30** to the first oil port and the second oil port.

(64) Reciprocating motion of the piston **13** can change volumes of the first hydraulic oil chamber **11** and the second hydraulic oil chamber **12**, so that one of the first oil port and the second oil port delivers hydraulic oil to the oil loading chamber **20**, and the other thereof sucks the oil from the storage oil chamber **30**.

(65) Referring to FIGS. **11-16**, embodiments of the present disclosure provide a bearing assembly **80** used for a hydraulic jack having an outer oil barrel **40**, and the outer oil barrel **40** is provided with a snap groove **44**.

(66) The bearing assembly **80** includes a sliding block **81** and a pin **82**; a bearing surface of the bearing assembly **80** can be arranged on the sliding block **81**, and the sliding block **81** has a bore which can be fitted over a periphery of the outer oil barrel **40**; the sliding block **81** is provided with a pin mounting groove **811**, and the pin mounting groove **811** is in communication with the bore; the pin **82** is hinged in the pin mounting groove **811**, and the pin **82** has an opening state and a locking state and can switch between the opening state and the locking state. In the opening state, the pin **82** is located outside the snap groove **44**; in the locking state, the pin **82** has a partial structure located in the pin mounting groove **811** and a partial structure located in the snap groove **44**, so that the sliding block **81** is fixed relative to the outer oil barrel **40**.

(67) In some embodiments, the bearing assembly **80** also includes a jacking block **83**, and the jacking block **83** is mounted on the sliding block **81** and can move synchronously with the sliding block **81**. The bearing surface of the bearing assembly **80** is arranged on the jacking block **83**, and anti-skid stripes or anti-skid pads may be arranged on the bearing surface of the bearing assembly **80**. Other structures and arrangement methods of the bearing assembly **80** can refer to the description about the hydraulic jack in the above embodiments, and will not be repeated here.

(68) The technical features described in the above specific examples can be implemented in various configurations. Some examples of the configurations are provided below.

(69) In some configurations, a hydraulic jack includes an outer oil barrel, a bearing assembly for bearing or pulling a weight is arranged on an outer wall of the outer oil barrel, the outer wall of the outer oil barrel has a plurality of fixing positions, and the bearing assembly can be fixed at any of the fixing positions and can move between any two of the fixing positions.

(70) In some configurations, a snap groove is arranged in each of the fixing positions, and the bearing assembly includes: a sliding block, a pin and a jacking block. The sliding block is fitted over the outer wall of the outer oil barrel and can move relative to the outer oil barrel. The sliding block is provided with a pin mounting groove, and the pin is hinged to the pin mounting groove. The pin has an opening state and a locking state, and can switch between the opening state and the locking state. In the opening state, the sliding block can move relative to the outer oil barrel; in the

locking state, the pin has a partial structure located in the pin mounting groove and has a partial structure located in the snap groove, so that the sliding block is fixed relative to the outer oil barrel. The jacking block is mounted on the sliding block and can move along with the sliding block.

(71) In some configurations, an elastic pushing assembly is arranged on the sliding block, a groove is arranged on the pin, and the elastic pushing assembly abuts against the groove when the pin is in the locking state.

(72) In some configurations, the elastic pushing assembly includes a screw, a spring and a push bead. The sliding block is provided with a mounting through hole; the screw, the spring and the push bead are arranged in the mounting through hole. The spring is compressed between the screw and the push bead, and a part of the push bead can be exposed from an end of the mounting through hole to abut against the groove.

(73) In some configurations, the jacking block is detachably connected to the sliding block, or the jacking block and the sliding block are formed integrally.

(74) In some configurations, an insertion groove is arranged in the sliding block, and the insertion groove includes a first guide portion and a limiting member. The jacking block has an insertion portion, and the insertion portion includes a second guide portion and a limiting block. The insertion portion can be inserted in the insertion groove, the second guide portion cooperates with the first guide portion, and the limiting block cooperates with the limiting member.

(75) In some configurations, two pins are provided, two pin mounting grooves are arranged in the sliding block, and one pin is hinged to each pin mounting groove. The two pins are symmetrical about a center axis of the outer oil barrel.

(76) In some configurations, the hydraulic jack also includes an inner oil barrel, a hydraulic cylinder and a piston rod; the outer oil barrel is fitted over the inner oil barrel and can move relative to the inner oil barrel; the outer oil barrel and the inner oil barrel form a storage oil chamber. The hydraulic cylinder is arranged in the inner oil barrel and can move along an axial direction of the inner oil barrel in a sealing manner. An oil loading chamber and the storage oil chamber are located at two ends of the hydraulic cylinder. A piston is arranged in the hydraulic cylinder and divides an interior of the hydraulic cylinder into a first hydraulic oil chamber and a second hydraulic oil chamber. The first hydraulic oil chamber has a first oil port, and the second hydraulic oil chamber has a second oil port. The first oil port and the second oil port are both in unidirectional communication with the oil loading chamber, to allow unidirectional flow from the first oil port and the second oil port to the oil loading chamber. The first oil port and the second oil port are both in unidirectional communication with the storage oil chamber, to allow unidirectional flow from the storage oil chamber to the first oil port and the second oil port. The hydraulic cylinder has an oil unloading pipeline that connects the oil loading chamber and the storage oil chamber, and an unloading switch is arranged at the oil unloading pipeline. A handle is hinged to the outer oil barrel. A first end of the piston rod is connected to the piston and a second end of the piston rod is connected to the handle, so that the handle can drive the piston to reciprocate through the piston rod, to change volumes of the first hydraulic oil chamber and the second hydraulic oil chamber. Thus, one of the first oil port and the second oil port delivers hydraulic oil to the oil loading chamber, and the other thereof sucks the oil from the storage oil chamber.

(77) In some configurations, the outer oil barrel is provided with an oil barrel cover, and the oil barrel cover is arranged in a sealing manner at a top of the outer oil barrel. The handle is hinged to the oil barrel cover, and the piston rod passes through the oil barrel cover and is hinged with the handle.

(78) In some configurations, the outer oil barrel is provided with a sleeve; the sleeve is fixedly connected to a bottom of the outer oil barrel; and the sleeve is fitted over the inner oil barrel and can slide along an outer wall of the inner oil barrel in a sealing manner.

(79) In some configurations, a shaft sleeve is arranged on at least part of an inner wall of the sleeve; the shaft sleeve is arranged coaxially with the sleeve and fixed relative to the sleeve; and the sleeve

is fitted over the outer wall of the inner oil barrel, and can move axially relative to the inner oil barrel.

(80) In some configurations, a base sealing body is arranged at a bottom of the inner oil barrel, and the base sealing body seals the bottom of the inner oil barrel; a top of the inner oil barrel is located below the oil barrel cover and is open in an inner chamber of the outer oil barrel.

(81) In some configurations, the base sealing body is connected to the base; a limiting member is arranged on the outer wall of the inner oil barrel and used to limit a motion range of the outer oil barrel; the limiting member is located at a position above a middle part of the inner oil barrel.

(82) In some configurations, the hydraulic cylinder includes: an oil-circuit main body, an oil-circuit upper cover, and an oil-circuit lower cover. An outer wall of the oil-circuit main body is in sealing contact with an inner wall of the inner oil barrel, and the oil-circuit main body can move axially relative to the inner oil barrel. A hydraulic oil chamber running through the oil-circuit main body is formed in the oil-circuit main body, and the piston is arranged in the hydraulic oil chamber and divides the hydraulic oil chamber into the first hydraulic oil chamber and the second hydraulic oil chamber. The oil unloading pipeline is formed in the oil-circuit main body. The oil-circuit upper cover seals an upper end of the hydraulic oil chamber, and the oil-circuit lower cover seals a lower end of the hydraulic oil chamber. The piston rod passes through the oil-circuit upper cover and is connected to the piston.

(83) In some configurations, the first oil port is in communication with the storage oil chamber through a first oil inlet line and is in communication with the oil loading chamber through a first oil outlet line; a first one-way valve is arranged at the first oil inlet line; and a second one-way valve is arranged at the first oil outlet line. The second oil port is in communication with the storage oil chamber through a second oil inlet line and is in communication with the oil loading chamber through a second oil outlet line; a third one-way valve is arranged at the second oil inlet line; and a fourth one-way valve is arranged at the second oil outlet line.

(84) In some configurations, the first oil inlet line is formed in the oil-circuit upper cover, the first oil outlet line and the second oil inlet line are both formed in the oil-circuit main body, and the second oil outlet line is formed in the oil-circuit lower cover.

(85) In some configurations, a first sink is formed at an upper end of the oil-circuit main body, and a second sink is formed at a lower end of the oil-circuit main body. At least a partial structure of the oil-circuit upper cover is arranged in the first sink, and at least a partial structure of the oil-circuit lower cover is arranged in the second sink. An inlet of the first oil outlet line is located in the first sink, and an outlet of the second oil inlet line is located in the second sink.

(86) In some configurations, an oil unloading rod is arranged in the inner oil barrel, one end of the oil unloading rod is arranged at the oil unloading pipeline, and the other end of the oil unloading rod passes through the oil barrel cover and is connected to the oil unloading handle. The oil unloading handle is hinged to the oil barrel cover, and the communication and closing of the oil unloading pipeline can be controlled by the oil unloading rod.

(87) In some configurations, a first overload protection oil circuit is connected between the first hydraulic oil chamber and the storage oil chamber, and a second overload protection oil circuit is connected between the second hydraulic oil chamber and the storage oil chamber.

(88) In some configurations, the hydraulic cylinder includes: an oil-circuit main body, an oil-circuit upper cover, and an oil-circuit lower cover. An outer wall of the oil-circuit main body is in sealing contact with the inner wall of the inner oil barrel, and the oil-circuit main body can move axially relative to the inner oil barrel. A hydraulic oil chamber running through the oil-circuit main body is formed in the oil-circuit main body, and the piston is arranged in the hydraulic oil chamber and divides the hydraulic oil chamber into the first hydraulic oil chamber and the second hydraulic oil chamber. The oil-circuit upper cover seals an upper end of the hydraulic oil chamber, and the oil-circuit lower cover seals a lower end of the hydraulic oil chamber. The first overload protection oil circuit is arranged at the oil-circuit upper cover, and the second overload protection oil circuit is

arranged at the piston rod.

(89) In some configurations, a first pressure one-way valve is arranged at the first overload protection oil circuit, and a second pressure one-way valve is arranged at the second overload protection oil circuit. The first pressure one-way valve is opened when a pressure difference on both sides of the first pressure one-way valve is greater than a first preset value, and the second pressure one-way valve is opened when a pressure difference on both sides of the second pressure one-way valve is greater than a second preset value.

(90) In some configurations, a piston barrel is fitted over the piston rod, one end of the piston barrel is connected to the oil barrel cover, and the other end of the piston barrel is connected to the hydraulic cylinder.

(91) In some configurations, the piston rod includes an upper piston rod and a lower piston rod connected to each other, the upper piston rod is connected to the handle, and the lower piston rod is connected to the piston.

(92) In some configurations, a bearing assembly is used for a hydraulic jack having an outer oil barrel, and the outer oil barrel is provided with a snap groove. The bearing assembly includes a sliding block and a pin. The sliding block has a bore which can be fitted over a periphery of the outer oil barrel. The sliding block is provided with a pin mounting groove, and the pin mounting groove is in communication with the bore. The pin is hinged to the pin mounting groove, and the pin has an opening state and a locking state and can switch between the opening state and the locking state. In the opening state, the pin is located outside the snap groove; in the locking state, the pin has a partial structure located in the pin mounting groove and a partial structure located in the snap groove, so that the sliding block is fixed relative to the outer oil barrel.

(93) In some configurations, the bearing assembly also includes a jacking block, and the jacking block is mounted on the sliding block and can move synchronously with the sliding block.

(94) In some configurations, an elastic pushing assembly is arranged on the sliding block, a groove is arranged on the pin, and the elastic pushing assembly abuts against the groove when the pin is in the locking state.

(95) In some configurations, the elastic pushing assembly includes a screw, a spring, and a push bead. The sliding block is provided with a mounting through hole; and the screw, the spring, and the push bead are arranged in the mounting through hole. The spring is compressed between the screw and the push bead, and a part of the push bead can be exposed from an end of the mounting through hole to abut against the groove.

(96) In some configurations, the jacking block is detachably connected to the sliding block, or the jacking block is formed integrally with the sliding block.

(97) In some configurations, an insertion groove is arranged in the sliding block, and the insertion groove includes a first guide portion and a limiting member. The jacking block has an insertion portion, and the insertion portion includes a second guide portion and a limiting block. The insertion portion can be inserted in the insertion groove, the second guide portion cooperates with the first guide portion, and the limiting block cooperates with the limiting member.

(98) In some configurations, two pins are provided, two pin mounting grooves are arranged in the sliding block, and one pin is hinged to each pin mounting groove. The two pins are symmetrical about a center axis of the outer oil barrel.

(99) In some configurations, the hydraulic jack includes an outer oil barrel, and the bearing assembly according to any one of the above configurations is arranged on an outer wall of the outer oil barrel. The outer wall of the outer oil barrel has a plurality of fixing positions, and a snap groove is arranged in each of the fixing positions. The bearing assembly can move to any of the fixing positions and be fixed to the outer oil barrel by the snap groove. The bearing assembly can move between any two fixing positions.

(100) In some configurations, the hydraulic jack also includes an inner oil barrel, a hydraulic cylinder and a piston rod; the outer oil barrel is fitted over the inner oil barrel and can move relative

to the inner oil barrel; the outer oil barrel and the inner oil barrel form a storage oil chamber. The hydraulic cylinder is arranged in the inner oil barrel and can move along an axial direction of the inner oil barrel in a sealing manner. An oil loading chamber and the storage oil chamber are located at two ends of the hydraulic cylinder. A piston is arranged in the hydraulic cylinder and divides an interior of the hydraulic cylinder into a first hydraulic oil chamber and a second hydraulic oil chamber. The first hydraulic oil chamber has a first oil port, and the second hydraulic oil chamber has a second oil port. The first oil port and the second oil port are both in unidirectional communication with the oil loading chamber, to allow unidirectional flow from the first oil port and the second oil port to the oil loading chamber. The first oil port and the second oil port are both in unidirectional communication with the storage oil chamber, to allow unidirectional flow from the storage oil chamber to the first oil port and the second oil port. The hydraulic cylinder has an oil unloading pipeline that connects the oil loading chamber and the storage oil chamber, and an unloading switch is arranged at the oil unloading pipeline. A handle is hinged to the outer oil barrel. A first end of the piston rod is connected to the piston and a second end of the piston rod is connected to the handle, so that the handle can drive the piston to reciprocate through the piston rod, to change volumes of the first hydraulic oil chamber and the second hydraulic oil chamber. Thus, one of the first oil port and the second oil port delivers hydraulic oil to the oil loading chamber, and the other thereof sucks the oil from the storage oil chamber.

(101) In some configurations, the hydraulic cylinder includes: an oil-circuit main body, an oil-circuit upper cover, and an oil-circuit lower cover. An outer wall of the oil-circuit main body is in sealing contact with an inner wall of the inner oil barrel, and the oil-circuit main body can move axially relative to the inner oil barrel. A hydraulic oil chamber running through the oil-circuit main body is formed in the oil-circuit main body, and the piston is arranged in the hydraulic oil chamber and divides the hydraulic oil chamber into the first hydraulic oil chamber and the second hydraulic oil chamber. The oil unloading pipeline is formed in the oil-circuit main body. The oil-circuit upper cover seals an upper end of the hydraulic oil chamber, and the oil-circuit lower cover seals a lower end of the hydraulic oil chamber. The piston rod passes through the oil-circuit upper cover and is connected to the piston.

(102) In some configurations, a hydraulic cylinder is used to be mounted in an oil barrel. Spaces at two ends of the hydraulic cylinder are an oil loading chamber and a storage oil chamber respectively. The oil loading chamber and the storage oil chamber are sealed relative to each other. The hydraulic cylinder includes: an oil-circuit main body, an oil-circuit upper cover, and an oil-circuit lower cover. A hydraulic oil chamber running through the oil-circuit main body is formed in the oil-circuit main body, and a piston is arranged in the hydraulic oil chamber. The piston divides the hydraulic oil chamber into a first hydraulic oil chamber and a second hydraulic oil chamber, and the piston is connected to a piston rod. The oil-circuit upper cover seals an upper end of the hydraulic oil chamber, and the oil-circuit lower cover seals a lower end of the hydraulic oil chamber. The piston rod passes through the oil-circuit upper cover and is connected to the piston. The first hydraulic oil chamber has a first oil port, and the second hydraulic oil chamber has a second oil port. The first oil port and the second oil port are both in unidirectional communication with the oil loading chamber, to allow unidirectional flow from the first oil port and the second oil port to the oil loading chamber. The first oil port and the second oil port are both in unidirectional communication with the storage oil chamber, to allow unidirectional flow from the storage oil chamber to the first oil port and the second oil port. Reciprocating motion of the piston can change volumes of the first hydraulic oil chamber and the second hydraulic oil chamber, so that one of the first oil port and the second oil port delivers hydraulic oil to the oil loading chamber, and the other thereof sucks the oil from the storage oil chamber.

(103) In some configurations, the hydraulic cylinder has an oil unloading pipeline that connects the oil loading chamber and the storage oil chamber. An unloading switch is arranged at the oil unloading pipeline, and the unloading switch can control opening and closing of the oil unloading

pipeline.

(104) In some configurations, the first oil port is in communication with the storage oil chamber through a first oil inlet line and is in communication with the oil loading chamber through a first oil outlet line; a first one-way valve is arranged at the first oil inlet line; and a second one-way valve is arranged at the first oil outlet line. The second oil port is in communication with the storage oil chamber through a second oil inlet line and is in communication with the oil loading chamber through a second oil outlet line; a third one-way valve is arranged at the second oil inlet line; and a fourth one-way valve is arranged at the second oil outlet line.

(105) In some configurations, the first oil inlet line is formed in the oil-circuit upper cover, the first oil outlet line and the second oil inlet line are formed in the oil-circuit main body, and the second oil outlet line is formed in the oil-circuit lower cover; the oil unloading pipeline is formed in the oil-circuit main body.

(106) In some configurations, a first sink is formed at an upper end of the oil-circuit main body, and a second sink is formed at a lower end of the oil-circuit main body. At least a partial structure of the oil-circuit upper cover is arranged in the first sink, and at least a partial structure of the oil-circuit lower cover is arranged in the second sink. An inlet of the first oil outlet line is located in the first sink, and an outlet of the second oil inlet line is located in the second sink.

(107) In some configurations, a hydraulic jack includes: an outer oil barrel provided with a handle; an inner oil barrel, the outer oil barrel being fitted over the inner oil barrel and movable relative to the inner oil barrel, and the outer oil barrel and the inner oil barrel together forming a storage oil chamber; the hydraulic cylinder according to any one of the above configurations, arranged in the inner oil barrel and movable along an axial direction of the inner oil barrel in a sealing manner, an oil loading chamber and a storage oil chamber being located at two ends of the hydraulic cylinder. A first end of the piston rod is connected to the piston and a second end of the piston rod is connected to the handle, so that the handle can drive the piston to reciprocate through the piston rod, to change the volumes of the first hydraulic oil chamber and the second hydraulic oil chamber. Thus, one of the first oil port and the second oil port delivers the hydraulic oil to the oil loading chamber, and the other thereof sucks the oil from the storage oil chamber.

(108) In some configurations, the outer oil barrel is provided with an oil barrel cover, and the oil barrel cover is arranged in a sealing manner at a top of the outer oil barrel. The handle is hinged to the oil barrel cover, and the piston rod passes through the oil barrel cover and is hinged with the handle.

(109) In some configurations, the outer oil barrel is provided with a sleeve; the sleeve is fixedly connected to a bottom of the outer oil barrel; and the sleeve is fitted over the inner oil barrel and can slide along an outer wall of the inner oil barrel in a sealing manner.

(110) In some configurations, a shaft sleeve is arranged on at least part of an inner wall of the sleeve; the shaft sleeve is arranged coaxially with the sleeve and fixed relative to the sleeve; and the sleeve is fitted over the outer wall of the inner oil barrel, and can move axially relative to the inner oil barrel.

(111) In some configurations, a base sealing body is arranged at a bottom of the inner oil barrel, and the base sealing body seals the bottom of the inner oil barrel; a top of the inner oil barrel is located below the oil barrel cover and is open in an inner chamber of the outer oil barrel.

(112) In the description of the present disclosure, it shall be understood that terms such as “central,” “longitudinal,” “transverse,” “length,” “width,” “thickness,” “upper,” “lower,” “front,” “rear,” “left,” “right,” “vertical,” “horizontal,” “top,” “bottom,” “inner,” “outer,” “clockwise,” “counterclockwise,” “axial,” “radial” and “circumferential” should be construed to refer to the orientation as then described or as shown in the drawings under discussion. These relative terms are for convenience of description and do not indicate or imply that the device or element referred to must have a particular orientation, or be constructed and operated in a particular orientation. Thus, these terms shall not be construed as limitation on the present disclosure.

(113) In addition, terms such as “first” and “second” are merely used for descriptive purposes and cannot be understood as indicating or implying relative importance or the number of technical features indicated. Thus, the features associated with “first” and “second” may explicitly or implicitly include at least one of the features. In the description of the present disclosure, unless otherwise specifically defined, “a plurality of” means at least two, such as two, three, etc.

(114) In the present disclosure, unless otherwise explicitly specified and defined, the terms “mounted,” “connected,” “coupled,” “fixed” and the like are used broadly, and may be, for example, fixed connections, detachable connections, or integral connections; may also be mechanical or electrical connections; may also be direct connections or indirect connections via intervening structures; may also be inner communications of two elements, which can be understood by those skilled in the art according to specific situations.

(115) In the present disclosure, unless otherwise explicitly specified and defined, a structure in which a first feature is “on” or “below” a second feature may include an embodiment in which the first feature is in direct contact with the second feature, and may also include an embodiment in which the first feature and the second feature are not in direct contact with each other, but are contacted via an additional feature formed therebetween. Furthermore, a first feature “on,” “above,” or “on top of” a second feature may include an embodiment in which the first feature is right or obliquely “on,” “above,” or “on top of” the second feature, or just means that the first feature is at a height higher than that of the second feature; while a first feature “below,” “under,” or “on bottom of” a second feature may include an embodiment in which the first feature is right or obliquely “below,” “under,” or “on bottom of” the second feature, or just means that the first feature is at a height lower than that of the second feature.

(116) In the present disclosure, terms such as “an embodiment,” “some embodiments,” “an example,” “a specific example,” or “some examples,” means that a particular feature, structure, material, or characteristic described in connection with the embodiment or example is included in at least one embodiment or example of the present disclosure. Thus, the appearances of these terms in various places throughout this specification are not necessarily referring to the same embodiment or example of the present disclosure. Furthermore, the particular features, structures, materials, or characteristics may be combined in any suitable manner in one or more embodiments or examples. In addition, without contradiction, those skilled in the art may combine and unite different embodiments or examples or features of the different embodiments or examples described in this specification.

(117) Although the embodiments of the present disclosure have been shown and described above, it can be understood that the above embodiments are exemplary and shall not be understood as limitation on the present disclosure, and changes, modifications, alternatives and variations can be made in the above embodiments within the scope of the present disclosure.

Claims

1. A hydraulic jack, comprising: an outer oil barrel, a handle being arranged on the outer oil barrel; an inner oil barrel, the outer oil barrel being fitted over the inner oil barrel and movable relative to the inner oil barrel, the outer oil barrel and the inner oil barrel forming a storage oil chamber; a hydraulic cylinder arranged in the inner oil barrel and movable along an axial direction of the inner oil barrel in a sealing manner, wherein an oil loading chamber and the storage oil chamber are disposed at two ends of the hydraulic cylinder, respectively, a piston is arranged in the hydraulic cylinder and divides an interior of the hydraulic cylinder into a first hydraulic oil chamber and a second hydraulic oil chamber, the first hydraulic oil chamber has a first oil port, the second hydraulic oil chamber has a second oil port, the first oil port and the second oil port are both configured to be in unidirectional communication with the oil loading chamber to allow unidirectional flow from the first oil port and the second oil port to the oil loading chamber, the

first oil port and the second oil port are both configured to be in unidirectional communication with the storage oil chamber to allow unidirectional flow from the storage oil chamber to the first oil port and the second oil port, and the hydraulic cylinder has an oil unloading pipeline connecting the oil loading chamber with the storage oil chamber; and a piston rod having a first end connected to the piston and a second end connected to the handle, wherein the handle drives the piston to reciprocate through the piston rod to change volumes of the first hydraulic oil chamber and the second hydraulic oil chamber, and one of the first oil port and the second oil port is configured to deliver hydraulic oil to the oil loading chamber, while the other of the first oil port and the second oil port sucks oil from the storage oil chamber.

2. The hydraulic jack according to claim 1, wherein the outer oil barrel includes an oil barrel cover, the oil barrel cover is arranged in a sealing manner at a top of the outer oil barrel, the handle is hinged to the oil barrel cover, and the piston rod passes through the oil barrel cover and is hinged with the handle.

3. The hydraulic jack according to claim 2, wherein the outer oil barrel includes a sleeve, the sleeve is fixedly connected to a bottom of the outer oil barrel, and the sleeve is fitted over the inner oil barrel and slidable along an outer wall of the inner oil barrel in a sealing manner.

4. The hydraulic jack according to claim 3, wherein a shaft sleeve is arranged on at least part of an inner wall of the sleeve, the shaft sleeve is arranged coaxially with the sleeve and fixed relative to the sleeve, and the sleeve is fitted over the outer wall of the inner oil barrel and is axially movable relative to the inner oil barrel.

5. The hydraulic jack according to claim 2, wherein a base sealing body is arranged on a bottom of the inner oil barrel, the base sealing body sealing the bottom of the inner oil barrel, a top of the inner oil barrel is positioned below the oil barrel cover and is open in an inner chamber of the outer oil barrel.

6. The hydraulic jack according to claim 1, wherein the hydraulic cylinder comprises: an oil-circuit main body; an oil-circuit upper cover; and an oil-circuit lower cover, wherein an outer wall of the oil-circuit main body is in sealing contact with an inner wall of the inner oil barrel, and the oil-circuit main body is axially movable relative to the inner oil barrel, wherein a hydraulic oil chamber running through the oil-circuit main body is disposed in the oil-circuit main body, and the piston is arranged in the hydraulic oil chamber and divides the hydraulic oil chamber into the first hydraulic oil chamber and the second hydraulic oil chamber, wherein the oil unloading pipeline is disposed in the oil-circuit main body, and wherein the oil-circuit upper cover seals an upper end of the hydraulic oil chamber, the oil-circuit lower cover seals a lower end of the hydraulic oil chamber, and the piston rod passes through the oil-circuit upper cover and is connected to the piston.

7. The hydraulic jack according to claim 6, wherein the first oil port is configured to be in communication with the storage oil chamber through a first oil inlet line and is configured to be in communication with the oil loading chamber through a first oil outlet line, a first one-way valve is arranged at the first oil inlet line, and a second one-way valve is arranged at the first oil outlet line, wherein the second oil port is configured to be in communication with the storage oil chamber through a second oil inlet line and is configured to be in communication with the oil loading chamber through a second oil outlet line, a third one-way valve is arranged at the second oil inlet line, and a fourth one-way valve is arranged at the second oil outlet line.

8. The hydraulic jack according to claim 7, wherein the first oil inlet line is disposed in the oil-circuit upper cover, the first oil outlet line and the second oil inlet line are both disposed in the oil-circuit main body, and the second oil outlet line is disposed in the oil-circuit lower cover.

9. The hydraulic jack according to claim 8, wherein a first sink is disposed in an upper end of the oil-circuit main body, a second sink is disposed in a lower end of the oil-circuit main body, at least a partial structure of the oil-circuit upper cover is arranged in the first sink, and at least a partial structure of the oil-circuit lower cover is arranged in the second sink, wherein an inlet of the first

oil outlet line is positioned in the first sink, and an outlet of the second oil inlet line is positioned in the second sink.

10. The hydraulic jack according to claim 2, wherein an oil unloading rod is arranged in the inner oil barrel, a first end of the oil unloading rod is arranged at the oil unloading pipeline, a second end of the oil unloading rod passes through the oil barrel cover and is connected to an oil unloading handle, and the oil unloading handle is hinged to the oil barrel cover and is configured to control communication and closing of the oil unloading pipeline by the oil unloading rod.

11. The hydraulic jack according to claim 1, wherein a first overload protection oil circuit is connected between the first hydraulic oil chamber and the storage oil chamber, and a second overload protection oil circuit is connected between the second hydraulic oil chamber and the storage oil chamber.

12. The hydraulic jack according to claim 11, wherein the hydraulic cylinder comprises: an oil-circuit main body; an oil-circuit upper cover; and an oil-circuit lower cover, wherein an outer wall of the oil-circuit main body is in sealing contact with an inner wall of the inner oil barrel, and the oil-circuit main body is axially movable relative to the inner oil barrel, wherein a hydraulic oil chamber running through the oil-circuit main body is disposed in the oil-circuit main body, and the piston is arranged in the hydraulic oil chamber and divides the hydraulic oil chamber into the first hydraulic oil chamber and the second hydraulic oil chamber, wherein the oil-circuit upper cover seals an upper end of the hydraulic oil chamber, and the oil-circuit lower cover seals a lower end of the hydraulic oil chamber, wherein the first overload protection oil circuit is arranged at the oil-circuit upper cover, and the second overload protection oil circuit is arranged at the piston rod.

13. The hydraulic jack according to claim 2, wherein a piston barrel is fitted over the piston rod, a first end of the piston barrel is connected to the oil barrel cover, and a second end of the piston barrel is connected to the hydraulic cylinder.

14. The hydraulic jack according to claim 1, wherein the piston rod comprises an upper piston rod and a lower piston rod connected with each other, the upper piston rod is connected to the handle, and the lower piston rod is connected to the piston.

15. The hydraulic jack according to claim 1, wherein a bearing assembly is arranged on an outer wall of the outer oil barrel, the outer wall of the outer oil barrel has a plurality of fixing positions, and the bearing assembly is configured to be fixed at any of the plurality of fixing positions and movable between any two of the plurality of fixing positions.

16. The hydraulic jack according to claim 15, wherein a snap groove is arranged in each of the plurality of fixing positions, and wherein the bearing assembly comprises: a sliding block fitted over the outer wall of the outer oil barrel and being movable relative to the outer oil barrel, a pin mounting groove being arranged in the sliding block, a pin hinged to the pin mounting groove, having an opening state and a locking state, and being switchable between the opening state and the locking state, wherein in the opening state, the sliding block is movable relative to the outer oil barrel, and in the locking state, one part of the pin is disposed in the pin mounting groove and another part of the pin is disposed in the snap groove, such that the sliding block is fixed relative to the outer oil barrel; a jacking block mounted on the sliding block and being movable along with the sliding block.

17. The hydraulic jack according to claim 16, wherein an elastic pushing assembly is arranged on the sliding block, a groove is arranged in the pin, and the elastic pushing assembly abuts against the groove when the pin is in the locking state.

18. The hydraulic jack according to claim 17, wherein the elastic pushing assembly comprises: a screw; a spring; and a push bead, wherein the sliding block includes an mounting through hole, and the screw, the spring and the push bead are arranged in the mounting through hole, wherein the spring is compressed between the screw and the push bead, and a part of the push bead is exposed from an end of the mounting through hole and abuts against the groove.
