

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412689
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Morton; David H.

Magnetic coupling device

Abstract

Magnetic coupling devices are disclosed. The magnetic coupling devices may include sensors, retractable pins, stationary pins, probes, and/or additional tools. The magnetic coupling devices may include multiple sets of pole portions, a first set may be received in an opening in a first magnet of the magnetic coupling device and a second set may be outside of an envelope of the first magnet.

Inventors:	Morton; David H. (Boulder, CO)
Applicant:	Magswitch Technology, Inc. (Superior, CO)
Family ID:	84230388
Assignee:	Magswitch Automation Company (Superior, CO)
Appl. No.:	18/823658
Filed:	September 03, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240428971 A1	Dec. 26, 2024

Related U.S. Application Data

continuation parent-doc US 18288140 US 12112889 WO PCT/US2022/031286 20220527 child-doc US 18823658
us-provisional-application US 63194692 20210528

Publication Classification

Int. Cl.: H01F7/02 (20060101)

U.S. Cl.:

CPC **H01F7/0252** (20130101);

Field of Classification Search

CPC: H01F (7/0252); H01F (7/04); B23Q (3/154); B23Q (3/1546); B25J (15/0608); B66C (1/04)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3017545	12/1961	Meier	N/A	N/A
4401960	12/1982	Uchikune et al.	N/A	N/A
6331810	12/2000	Jung	N/A	N/A
6636153	12/2002	Barton et al.	N/A	N/A
7012495	12/2005	Underwood et al.	N/A	N/A
7049919	12/2005	Yamaki	N/A	N/A
7161451	12/2006	Shen	N/A	N/A
8031038	12/2010	Kimura	N/A	N/A
8183965	12/2011	Michael	N/A	N/A
8256098	12/2011	Michael	N/A	N/A
8350663	12/2012	Michael	N/A	N/A
8604900	12/2012	Kocijan	N/A	N/A
8641105	12/2013	Goodman et al.	N/A	N/A
8878639	12/2013	Kocijan	N/A	N/A
9514904	12/2015	Dai et al.	N/A	N/A
10903030	12/2020	Morton et al.	N/A	N/A
10971292	12/2020	Arnold et al.	N/A	N/A
11097401	12/2020	Morton et al.	N/A	N/A
2007/0013468	12/2006	Heard	N/A	N/A
2009/0027149	12/2008	Kocijan	N/A	N/A
2011/0037547	12/2010	Cardone et al.	N/A	N/A
2013/0320686	12/2012	Morton	N/A	N/A
2016/0289046	12/2015	Norton et al.	N/A	N/A
2017/0103839	12/2016	Choi	N/A	N/A
2018/0311795	12/2017	Morton et al.	N/A	N/A
2018/0315563	12/2017	Morton	N/A	H01F 7/04
2021/0031317	12/2020	Morton et al.	N/A	N/A
2021/0122011	12/2020	Kitaura et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201882760	12/2010	CN	N/A
104209892	12/2013	CN	N/A
2476509	12/2011	EP	N/A
0531946	12/1940	GB	N/A
2211356	12/1988	GB	N/A
2009/000008	12/2007	WO	N/A

OTHER PUBLICATIONS

Gupta et al.; Simulation and Prototyping of Saturable Magnetic Switch for Current Pulse Compression; 2019 IEEE 4th International Conference on Condition Assessment Techniques in Electrical Systems (CATCON); IEEE; 2019. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2022/031286, mailed on Nov. 3, 2022, 14 pages. cited by applicant

Kim et al.; Design and Analysis Method for a DC Magnetic Contactor with a Permanent Magnet; 2014 17th International Conference on Electrical Machines and Systems (ICEMS); IEEE; 2014. cited by applicant

Sanati et al.; Optimization of Geometry and Dimensions of Magnetic Switch Core with Approach of Flux Density Uniformity; 2019 International Power System Conference (PSC); IEEE; Oct. 2019. cited by applicant

Primary Examiner: Musleh; Mohamad A

Attorney, Agent or Firm: Faegre Drinker Biddle & Reath LLP

Background/Summary

RELATED APPLICATION (1) This application is a continuation application of U.S. patent application Ser. No. 18/288,140, filed Oct. 24, 2023 which is a national stage application of PCT International Application No. PCT/US2022/031286, filed May 27, 2022, titled MAGNETIC COUPLING DEVICE, which claims the benefit of U.S. Provisional Application No. 63/194,692, filed May 28, 2021, titled MAGNETIC COUPLING DEVICE, the entire disclosures of which are hereby expressly incorporated by reference herein in their entirety.

TECHNICAL FIELD

(1) The present disclosure is related to magnetic coupling devices and in particular to magnetic coupling devices having multiple workpiece contact interfaces for each pole of the magnetic coupling device.

BACKGROUND

(2) Magnetic coupling devices are known. Exemplary coupling devices are disclosed in U.S. Pat. Nos. 7,012,495, 8,878,639, and US Published Patent Application No. 20180311795.

SUMMARY

(3) In an exemplary embodiment of the present disclosure, a magnetic coupling device for magnetically coupling to a ferromagnetic workpiece is provided. The magnetic coupling device comprising a housing; a switchable magnetic flux source supported by the housing, the switchable magnetic flux source being switchable between at least an OFF state and an ON state; and a plurality of pole portions, each having at least one workpiece engagement surface, the switchable magnetic flux source being positioned between the plurality of pole portions. The plurality of pole portions including a first north pole portion having a first workpiece engagement surface, a second north pole portion having a second workpiece engagement surface, a first south pole portion having a third workpiece engagement surface, and a second south pole portion having a fourth workpiece engagement surface, wherein the second north pole portion and the second south pole portion are each positioned between the first north pole portion and the first south pole portion and the switchable magnetic flux source in an ON state is magnetically coupled to each of the first workpiece engagement surface of the first north pole portion, the second workpiece engagement

surface of the second north pole portion, the third workpiece engagement surface of the first south pole portion, and the fourth workpiece engagement surface of the second south pole portion.

(4) In an example thereof, a channel is located between the first north pole portion and the first south pole portion. In a variation thereof, the magnetic coupling device further comprises a sensor positioned in the channel. In another variation thereof, the magnetic coupling device further comprises a tool positioned in the channel. In a further variation thereof, the magnetic coupling device further comprises one of a tool and a sensor positioned in the channel.

(5) In another example variation thereof, the channel extends from a first position above a top side of the switchable magnetic flux source to a second position below the top side of the switchable magnetic flux source.

(6) In a further example thereof, the channel is positioned between the second north pole portion and the second south pole portion.

(7) In yet another example thereof, the second north pole portion is positioned between the second south pole portion and the first north pole portion.

(8) In still another example thereof, the switchable magnetic flux source includes a plurality of permanent magnets. In a variation thereof, at least first one of the plurality of permanent magnets is an electro-permanent magnet. In another variation thereof, at least a second one of the plurality of permanent magnets is a rare earth magnet. In yet another variation thereof, the plurality of permanent magnets including a first permanent magnet and a second permanent magnet movable relative to the first permanent magnet. In a further variation thereof, the second permanent magnet is rotatable relative to the first permanent magnet. In still another variation thereof, each of the first permanent magnet and the second permanent magnet are positioned between the first north pole portion and the first south pole portion. In yet another variation thereof, in the ON state of the magnetic flux source a north pole of the second permanent magnet is generally aligned with a north pole of the first permanent magnet and in the OFF state of the magnetic flux source a south pole of the second permanent magnet is generally aligned with the north pole of the first permanent magnet.

(9) In another exemplary embodiment of the present disclosure, a magnetic coupling device for magnetically coupling to a ferromagnetic workpiece is provided. The magnetic coupling device comprising: a housing; a switchable magnetic flux source supported by the housing including a plurality of permanent magnets, the plurality of permanent magnets including a first permanent magnet and a second permanent magnet movable relative to the first permanent magnet about a first axis of rotation; and a plurality of workpiece engagement surfaces supported by the housing and magnetically coupled to the switchable magnetic flux source, the plurality of workpiece engagement surfaces adapted to contact the ferromagnetic workpiece, a first workpiece engagement surface of the plurality of workpiece engagement surfaces corresponding to a north pole of the magnetic coupling device and a second workpiece engagement surface of the plurality of workpiece engagement surfaces corresponding to a south pole of the magnetic coupling device, both the first workpiece engagement surface and the second workpiece engagement surface being closer to the first axis of rotation than the second permanent magnet.

(10) In an example thereof, the plurality of workpiece engagement surfaces further includes a third workpiece engagement surface corresponding to the north pole of the magnetic coupling device and a fourth workpiece engagement surface corresponding to the south pole of the magnetic coupling device, each of the third workpiece engagement surface and the fourth workpiece engagement surface being further away from the first axis of rotation than the second permanent magnet.

(11) In another example thereof, the first permanent magnet surrounds the first workpiece engagement surface and the second workpiece engagement surface.

(12) In yet another example thereof, each of the first permanent magnet and the second permanent magnet surrounds the first workpiece engagement surface and the second workpiece engagement

surface.

(13) In a further example thereof, the magnetic coupling device further comprising: a first pole member including the first workpiece engagement surface; a second pole member including the second workpiece engagement surface, the first pole member and the second pole member defining a channel; and at least one sensor positioned in the channel. In a variation thereof, the second permanent magnet includes a top face and a bottom face, the bottom face facing the first permanent magnet, the at least one sensor is positioned lower than the top face of the second permanent magnet. In another variation thereof, the at least one sensor is positioned lower than the bottom face of the second permanent magnet. In a further variation thereof, the at least one sensor includes a first magnetic field sensor positioned to monitor a first magnetic flux associated with at least one of the first workpiece engagement surface and the second workpiece engagement surface. In yet another variation thereof, the magnetic coupling device further comprising a logic control circuit operatively coupled to the at least one sensor, the logic control circuit configured to determine at least one operating state of the magnetic coupling device based on an output from the at least one sensor. In a further variation thereof, the magnetic coupling device further comprises an output device which provides an indication of the operating state of the magnetic coupling device.

(14) In yet a further example thereof, the magnetic coupling device further comprises at least one of a stationary pin, a retractable pin, and a probe moveable within the channel. In a variation thereof, wherein the probe supports the at least one sensor.

(15) In still yet a further example thereof, the magnetic coupling device further comprises an actuator operatively coupled to the second permanent magnet to move the second permanent magnet relative to the first permanent magnet. In a variation thereof, the actuator is one of a user input having an operator actuatable portion, an electric motor, at least one conductive coil, a hydraulic system, and a pneumatic system. In a further variation thereof, the actuator is a user input having an operator actuatable portion which is moveable between a first position corresponding to the second permanent magnet being in a first orientation relative to the first permanent magnet and a second position corresponding to the second permanent magnet being in a second orientation relative to the first permanent magnet and further comprising a lock to hold the second permanent magnet in at least one of the first orientation and the second orientation.

(16) In a further exemplary embodiment of the present disclosure, a magnetic coupling device for magnetically coupling to a ferromagnetic workpiece is provided. The magnetic coupling device comprising: a housing; a switchable magnetic flux source supported by the housing including a plurality of permanent magnets, the plurality of permanent magnets including a first permanent magnet and a second permanent magnet movable relative to the first permanent magnet about a first axis of rotation; a plurality of workpiece engagement surfaces supported by the housing and magnetically coupled to the switchable magnetic flux source, the plurality of workpiece engagement surfaces adapted to contact the ferromagnetic workpiece, a first workpiece engagement surface of the plurality of workpiece engagement surfaces corresponding to a north pole of the magnetic coupling device and a second workpiece engagement surface of the plurality of workpiece engagement surfaces corresponding to a south pole of the magnetic coupling device; and at least one sensor positioned in a channel between the first workpiece engagement surface and the second workpiece engagement surface and between a lower surface of the first permanent magnet and the upper surface of the second permanent magnet.

(17) In yet a further exemplary embodiment of the present disclosure, a magnetic coupling device for magnetically coupling to a ferromagnetic workpiece is provided. The magnetic coupling device comprising: a housing; a switchable magnetic flux source supported by the housing including a plurality of permanent magnets, the plurality of permanent magnets including a first permanent magnet and a second permanent magnet movable relative to the first permanent magnet about a first axis of rotation; a plurality of workpiece engagement surfaces supported by the housing and magnetically coupled to the switchable magnetic flux source, the plurality of workpiece

engagement surfaces adapted to contact the ferromagnetic workpiece, a first workpiece engagement surface of the plurality of workpiece engagement surfaces corresponding to a north pole of the magnetic coupling device and a second workpiece engagement surface of the plurality of workpiece engagement surfaces corresponding to a south pole of the magnetic coupling device; and at least one tool positioned in a channel between the first workpiece engagement surface and the second workpiece engagement surface and between a lower surface of the first permanent magnet and the upper surface of the second permanent magnet.

(18) In still a further exemplary embodiment of the present disclosure, a magnetic coupling device for magnetically coupling to a ferromagnetic workpiece is provided. The magnetic coupling device comprising: a housing; a switchable magnetic flux source supported by the housing including a plurality of permanent magnets, the plurality of permanent magnets including a first permanent magnet and a second permanent magnet movable relative to the first permanent magnet, the first permanent magnet having a first end surface and a second end surface; a plurality of workpiece engagement surfaces supported by the housing and magnetically coupled to the switchable magnetic flux source, the plurality of workpiece engagement surfaces adapted to contact the ferromagnetic workpiece. The plurality of workpiece engagement surfaces comprising: a first workpiece engagement surface positioned adjacent the first end surface of the first permanent magnet, a second workpiece engagement surface positioned adjacent the second end surface of the first permanent magnet, each of the first workpiece engagement surface and the second workpiece engagement surface corresponding to a north pole of the magnetic coupling device; a third workpiece engagement surface; and a fourth workpiece engagement surface spaced apart from the third workpiece engagement surface, each of the third workpiece engagement surface and the fourth workpiece engagement surface corresponding to a south pole of the magnetic coupling device.

(19) In an example thereof, the third workpiece engagement surface is positioned adjacent the first end surface of the first permanent magnet and the fourth workpiece engagement surface is positioned adjacent the second end surface of the first permanent magnet.

(20) In another example thereof, the second permanent magnet is rotatable relative to the first permanent magnet. In a variation thereof, a strength level of a magnetic field of the north pole of the magnetic coupling device is varied based on a rotational position of the second permanent magnet relative to the first permanent magnet. In a further variation thereof, the strength level of the magnetic field of the north pole of the magnetic coupling device is strongest when a north pole of the second permanent magnet is aligned with a north pole of the first permanent magnet and is weakest when the north pole of the second permanent magnet is aligned with a south pole of the first permanent magnet.

(21) In a further example thereof, the first permanent magnet surrounds the first workpiece engagement surface and the third workpiece engagement surface.

(22) In yet another example thereof, each of the first permanent magnet and the second permanent magnet surrounds the first workpiece engagement surface and the third workpiece engagement surface.

(23) In still another example thereof, the magnetic coupling device further comprises a first pole member including the first workpiece engagement surface; a second pole member including the third workpiece engagement surface, the first pole member and the second pole member defining a channel; and at least one sensor positioned in the channel. In a variation thereof, the second permanent magnet includes a top face and a bottom face, the bottom face facing the first permanent magnet, the at least one sensor is positioned lower than the top face of the second permanent magnet. In another variation thereof, the at least one sensor is positioned lower than the bottom face of the second permanent magnet. In still another variation thereof, the at least one sensor includes a first magnetic field sensor positioned to monitor a first magnetic flux associated with at least one of the first workpiece engagement surface and the third workpiece engagement surface. In a further

variation thereof, the magnetic coupling device further comprises a logic control circuit operatively coupled to the at least one sensor, the logic control circuit configured to determine at least one operating state of the magnetic coupling device based on an output from the at least one sensor. In yet a further variation thereof, the magnetic coupling device further comprises an output device which provides an indication of the operating state of the magnetic coupling device. In still another variation thereof, the magnetic coupling device further comprises a probe moveable within the channel. In a further still variation thereof, the probe supports the at least one sensor.

(24) In a further still example thereof, the magnetic coupling device further comprises an actuator operatively coupled to the second permanent magnet to move the second permanent magnet relative to the first permanent magnet. In a variation thereof, the actuator is one of a user input having an operator actuatable portion, an electric motor, at least one conductive coil, a hydraulic system, and a pneumatic system.

(25) In still another exemplary embodiment of the present disclosure, a magnetic coupling device for magnetically coupling to a ferromagnetic workpiece is provided. The magnetic coupling device comprising: a housing; a switchable magnetic flux source supported by the housing including at least one electro-permanent magnet; and a plurality of workpiece engagement surfaces supported by the housing and magnetically coupled to the switchable magnetic flux source. The plurality of workpiece engagement surfaces adapted to contact the ferromagnetic workpiece, a first pole portion including a first workpiece engagement surface of the plurality of workpiece engagement surfaces, a second pole portion including a second workpiece engagement surface of the plurality of workpiece engagement surfaces, the first workpiece engagement surface and the second workpiece engagement surface corresponding to a north pole of the magnetic coupling device, a third pole portion including a third workpiece engagement surface of the plurality of workpiece engagement surfaces, and a fourth pole portion including a fourth workpiece engagement surface of the plurality of workpiece engagement surfaces, the third workpiece engagement surface and the fourth workpiece engagement surface corresponding to a south pole of the magnetic coupling device, both the first pole portion and the third pole portion being received in an opening in the switchable magnetic flux source.

(26) In an example thereof, the second pole portion and the fourth pole portion are outside of an envelope of the switchable magnetic flux source.

(27) In another example thereof, the switchable magnetic flux source includes at least one rare earth permanent magnet.

(28) In a further example thereof, the magnetic coupling device further comprises at least one sensor, wherein the first pole member and the second pole member define a channel, the at least one sensor positioned in the channel.

(29) In yet a further example thereof, a proximity sensor is positioned in the channel.

(30) In yet still another exemplary embodiment of the present disclosure, a magnetic coupling device for magnetically coupling to a ferromagnetic workpiece is provided. The magnet coupling device comprising: a housing; a switchable magnetic flux source supported by the housing including a plurality of magnets, the plurality of magnets including a first magnet and a second magnet, the switchable magnetic flux having a first configuration wherein a north pole of the second magnet is aligned relative to the first magnet and a second configuration wherein a south pole of the second magnet is aligned relative to the north pole of the first magnet; and a plurality of workpiece engagement surfaces supported by the housing and magnetically coupled to the switchable magnetic flux source. The plurality of workpiece engagement surfaces adapted to contact the ferromagnetic workpiece, a first pole portion including a first workpiece engagement surface of the plurality of workpiece engagement surfaces, a second pole portion including a second workpiece engagement surface of the plurality of workpiece engagement surfaces, the first workpiece engagement surface and the second workpiece engagement surface corresponding to a north pole of the magnetic coupling device, a third pole portion including a third workpiece

engagement surface of the plurality of workpiece engagement surfaces, and a fourth pole portion including a fourth workpiece engagement surface of the plurality of workpiece engagement surfaces, the third workpiece engagement surface and the fourth workpiece engagement surface corresponding to a south pole of the magnetic coupling device, both the first pole portion and the third pole portion being received in an opening in the switchable magnetic flux source.

(31) In an example thereof, the second pole portion and the fourth pole portion are outside of an envelope of the first magnet.

(32) In another example thereof, the second magnet is movable relative to the first permanent magnet. In a variation thereof, the second magnet is rotatable relative to the first magnet. In another variation thereof, a strength level of a magnetic field of the north pole of the magnetic coupling device is varied based on a rotational position of the second magnet relative to the first magnet.

(33) In a further example thereof, the strength level of the magnetic field of the north pole of the magnetic coupling device is strongest when a north pole of the second magnet is aligned with a north pole of the first magnet and is weakest when the north pole of the second magnet is aligned with a south pole of the first magnet.

(34) In yet a further example thereof, the magnetic coupling device further comprises at least one sensor, wherein the first pole member and the second pole member define a channel, the at least one sensor positioned in the channel. In a variation thereof, the second magnet includes a top face and a bottom face, the bottom face facing the first magnet, the at least one sensor is positioned lower than the top face of the second magnet. In a further variation thereof, the at least one sensor is positioned lower than the bottom face of the second magnet.

(35) In still a further example thereof, the at least one sensor includes a first magnetic field sensor positioned to monitor a first magnetic flux associated with at least one of the first workpiece engagement surface and the third workpiece engagement surface.

(36) In another still example thereof, the magnetic coupling device further comprises a logic control circuit operatively coupled to the at least one sensor, the logic control circuit configured to determine at least one operating state of the magnetic coupling device based on an output from the at least one sensor. In a variation thereof, the magnetic coupling device further comprises an output device which provides an indication of the operating state of the magnetic coupling device.

(37) In a further still example thereof, the magnetic coupling device further comprises at least one of a pin, a probe, and tool positioned within the channel. In a variation thereof, the probe supports the at least one sensor.

(38) In another yet still example thereof, the magnetic coupling device further comprises an actuator operatively coupled to the second magnet to move the second magnet relative to the first magnet. In a variation thereof, the actuator is one of a user input having an operator actuatable portion, an electric motor, at least one conductive coil, a hydraulic system, and a pneumatic system.

(39) In another example thereof, the first magnet is a permanent magnet.

(40) In yet another example thereof, each of the first magnet and the second magnet is a permanent magnet.

(41) In yet still another exemplary embodiment, a magnetic coupling device for magnetically coupling to a ferromagnetic workpiece is provided. The magnetic coupling device comprising: a housing and a switchable magnetic flux source supported by the housing including a plurality of magnets and a plurality of ferromagnetic inserts. The plurality of magnets including a first permanent ring magnet having a first outer circumferential surface and a first inner circumferential surface and a second permanent ring magnet having a second outer circumferential surface and a second inner circumferential surface. The plurality of ferromagnetic inserts including a first ferromagnetic insert having a first outer arcuate surface positioned adjacent the first inner circumferential surface of the first permanent ring magnet and a second ferromagnetic insert having a second outer arcuate surface positioned adjacent the second inner circumferential surface of the second permanent magnet. The switchable magnetic flux having a first configuration wherein a

north pole of the second permanent ring magnet is aligned relative to a north pole of the first permanent ring magnet and a second configuration wherein a south pole of the second permanent ring magnet is aligned relative to the north pole of the first permanent magnet. A plurality of workpiece engagement surfaces magnetically coupled to the switchable magnetic flux source. The plurality of workpiece engagement surfaces adapted to contact the ferromagnetic workpiece. A first pole portion including a first workpiece engagement surface of the plurality of workpiece engagement surfaces. A second pole portion including a second workpiece engagement surface of the plurality of workpiece engagement surfaces.

(42) In an example thereof, the second permanent ring magnet is moveable relative to the first permanent ring magnet. In a variation thereof, the second permanent ring magnet is rotatable relative to the first permanent ring magnet about a first axis. In another variation thereof, the first ferromagnetic insert remains stationary relative to the first permanent ring magnet as the second permanent ring magnet rotates relative to the first permanent ring magnet. In a further variation thereof, the second ferromagnetic insert remains stationary relative to the first permanent ring magnet as the second permanent ring magnet rotates relative to the first permanent ring magnet.

(43) In a further example thereof, each of the first outer arcuate surface of the first ferromagnetic insert and the second outer arcuate surface of the second ferromagnetic insert are positioned closer to the first axis than the first permanent ring magnet and the second permanent ring magnet.

(44) In still a further example thereof, the first outer arcuate surface of the first ferromagnetic insert contacts the first inner circumferential surface of the first permanent ring magnet.

(45) In yet still a further example thereof, the first outer arcuate surface of the first ferromagnetic insert contacts the second inner circumferential surface of the second permanent ring magnet.

(46) Other aspects and optional and/or preferred embodiments will become apparent from the following description provided below with reference to the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above-mentioned and other features and advantages of this disclosure, and the manner of attaining them, will become more apparent and will be better understood by reference to the following description of exemplary embodiments taken in conjunction with the accompanying drawings, wherein:

(2) FIG. 1 illustrates a representative view of an exemplary magnetic coupling device having multiple workpiece contact interfaces for each pole of the magnetic coupling device and the magnetic coupling device in an OFF state;

(3) FIG. 2 illustrates the magnetic coupling device of FIG. 1 with the magnetic coupling device in an ON state;

(4) FIG. 3 illustrates the magnetic coupling device of FIG. 1 with a sensing system;

(5) FIG. 4 illustrates a representative view of an exemplary magnetic coupling device having multiple workpiece contact interfaces for each pole of the magnetic coupling device, the magnetic coupling device including a stack of permanent magnets with a first permanent magnet moveable relative to a second permanent magnet with an actuator;

(6) FIG. 5 illustrates the magnetic coupling device of FIG. 4 including an electronic controller operatively coupled to the actuator;

(7) FIG. 6 illustrates a representative view of an exemplary magnetic coupling device having multiple workpiece contact interfaces for each pole of the magnetic coupling device, the magnetic coupling device including a stack of permanent magnets with a first electro-permanent magnet and a second permanent magnet;

(8) FIG. 7 illustrates a first upper perspective view of an exemplary magnetic coupling device in

accordance with the magnetic coupling device of FIG. 4 having a manual actuator;

(9) FIG. 8 illustrates a second upper perspective view of the magnetic coupling device of FIG. 7;

(10) FIG. 9 illustrates a first lower perspective view of the magnetic coupling device of FIG. 7;

(11) FIG. 10 illustrates an exploded assembly view of the magnetic coupling device of FIG. 7;

(12) FIG. 11 illustrates a third upper perspective view of the magnetic coupling device of FIG. 7 with a portion of a housing removed to illustrate an actuation assembly of the magnetic coupling device of FIG. 7;

(13) FIG. 12 illustrates an exploded view of a magnet and pole piece assembly of the magnetic coupling device of FIG. 7;

(14) FIG. 13 illustrates a lower perspective view of the magnet and pole piece assembly of FIG. 12 including a plurality of workpiece contact interfaces;

(15) FIG. 14 illustrates an upper perspective view of magnet and pole piece assembly of FIG. 12;

(16) FIG. 15 illustrates a first sectional view of a portion of the magnetic coupling device of FIG. 7;

(17) FIG. 16 illustrates a second sectional view of the magnet and pole piece assembly of FIG. 12 of the magnetic coupling device of FIG. 7;

(18) FIG. 17 illustrates the sectional view of FIG. 16 with the magnet and pole piece assembly of FIG. 12 of the magnetic coupling device of FIG. 7 supported on a ferromagnetic workpiece;

(19) FIG. 18 illustrates the arrangement of FIG. 17 with the magnetic coupling device in an OFF state;

(20) FIG. 19 illustrates the arrangement of FIG. 17 with the magnetic coupling device in an ON state;

(21) FIG. 20 illustrates the magnetic coupling device of FIG. 1 spaced apart from a ferromagnetic workpiece and having a locator positioned in a channel of the magnetic coupling device;

(22) FIG. 21 illustrates the magnetic coupling device of FIG. 20 with the locator received in a locator feature of the ferromagnetic workpiece;

(23) FIG. 22 illustrates the magnetic coupling device of FIG. 1 having a retractable locator positioned in a channel of the magnetic coupling device;

(24) FIG. 23 illustrates another exemplary magnetic coupling device in a first configuration; and

(25) FIG. 24 illustrates the magnetic coupling device of FIG. 23 in a second configuration.

DETAILED DESCRIPTION OF THE DRAWINGS

(26) For the purposes of promoting an understanding of the principles of the present disclosure, reference is now made to the embodiments illustrated in the drawings, which are described below. The embodiments disclosed herein are not intended to be exhaustive or limit the present disclosure to the precise form disclosed in the following detailed description. Rather, the embodiments are chosen and described so that others skilled in the art may utilize their teachings. Therefore, no limitation of the scope of the present disclosure is thereby intended. Corresponding reference characters indicate corresponding parts throughout the several views.

(27) The terms “couples”, “coupled”, “coupler” and variations thereof are used to include both arrangements wherein the two or more components are in direct physical contact and arrangements wherein the two or more components are not in direct contact with each other (e.g., the components are “coupled” via at least a third component), but yet still cooperate or interact with each other.

(28) In some instances throughout this disclosure and in the claims, numeric terminology, such as first, second, third, and fourth, is used in reference to various components or features. Such use is not intended to denote an ordering of the components or features. Rather, numeric terminology is used to assist the reader in identifying the component or features being referenced and should not be narrowly interpreted as providing a specific order of components or features.

(29) Referring to FIG. 1, an exemplary magnetic coupling tool 10 is shown. Magnetic coupling device 10 is configured to magnetically couple a ferromagnetic workpiece 12. Magnetic coupling device 10 includes a housing 14, a switchable magnetic flux source 16, a first north pole portion

18, a second north pole portion **20**, a first south pole portion **22**, and a second south pole portion **24**. First north pole portion **18** includes a workpiece interface **28**, second north pole portion **20** includes a workpiece interface **30**, first south pole portion **22** includes a workpiece interface **32**, and second south pole portion **24** includes a workpiece interface **34**, each of which contacts a respective part of ferromagnetic workpiece **12**, illustratively a surface **26** of ferromagnetic workpiece **12**. Each of workpiece interface **28**, workpiece interface **30**, workpiece interface **32**, and workpiece interface **34** include at least one workpiece engagement surface. Workpiece interface **28**, workpiece interface **30**, workpiece interface **32**, and workpiece interface **34** may each be planar, curved, contoured, have a plurality of spaced apart projections, or any other suitable shape for contacting ferromagnetic workpiece **12**. Each of first north pole portion **18**, second north pole portion **20**, first south pole portion **22**, and second south pole portion **24** are made of a ferromagnetic material and may be a part of housing **14** or separate components coupled to housing **14**.

(30) Switchable magnetic flux source **16** of magnetic coupling tool **10** is switchable between an OFF state wherein a magnetic circuit is formed within housing **14** and an ON state wherein a magnetic circuit is formed from switchable magnetic flux source **16** through workpiece interface **28** and workpiece interface **30** of magnetic coupling tool **10**, through ferromagnetic workpiece **12**, through workpiece interface **32** and workpiece interface **34** of magnetic coupling tool **10**, and back to switchable magnetic flux source **16** (as represented by the arrows shown in FIG. 2). In embodiments, switchable magnetic flux source **16** may be placed in at least one partial ON state wherein the strength of the magnetic circuit formed through ferromagnetic workpiece **12** is more than the OFF state and less than the ON state.

(31) Switchable magnetic flux source **16** may include multiple permanent magnets and is configurable to have an overall north pole portion **44** and an overall south pole portion **46**. As shown in FIG. 2, overall north pole portion **44** of switchable magnetic flux source **16** is positioned between first north pole portion **18** and second north pole portion **20** and overall south pole portion **46** of switchable magnetic flux source **16** is positioned between first south pole portion **22** and second south pole portion **24**. Overall north pole portion **44** of switchable magnetic flux source **16** is magnetically coupled with first north pole portion **18** and second north pole portion **20** resulting in workpiece interface **28** of first north pole portion **18** and workpiece interface **30** of second north pole portion **20** forming an overall north pole **40** of magnetic coupling tool **10**. Overall south pole portion **46** is magnetically coupled with first south pole portion **22** and second south pole portion **24** resulting in workpiece interface **32** of first south pole portion **22** and workpiece interface **34** of second south pole portion **24** forming an overall south pole **42** of magnetic coupling tool **10**.

(32) Switchable magnetic flux source **16** may include one or more permanent magnets and is configurable to have an overall north pole portion **44** and an overall south pole portion **46**. In embodiments, switchable magnetic flux source **16** includes at least one electro-permanent magnet which is switchable between an ON state (having a north pole and a south pole) and an OFF state (not magnetized relative to external objects). Further, the at least one electro-permanent magnet may be configured to have varying magnetic strengths which allow the device to be configured in a partial ON state having a magnetic strength at workpiece interfaces **28**, **30**, **32**, and **34** less than the ON state and greater than an OFF state. In embodiments, switchable magnetic flux source **16** includes at least one rare earth permanent magnet and at least one electro-permanent magnet, the combination of which is switchable between an ON state having a magnetic strength at workpiece interfaces **28**, **30**, **32**, and **34** and an OFF state wherein a magnetic circuit is formed internally to housing **14**. Further, the combination may be configured to have varying magnetic strengths which allow the device to be configured in a partial ON state having a magnetic strength at workpiece interfaces **28**, **30**, **32**, and **34** less than the ON state and greater than an OFF state. In embodiments, switchable magnetic flux source **16** includes a plurality of rare earth permanent magnets, the combination of which is switchable between an ON state having a magnetic strength at workpiece

interfaces **28**, **30**, **32**, and **34** and an OFF state wherein a magnetic circuit is formed internally to housing **14**. Further, the combination may be configured to have varying magnetic strengths which allow the device to be configured in a partial ON state having a magnetic strength at workpiece interfaces **28**, **30**, **32**, and **34** less than the ON state and greater than an OFF state. In embodiments, switchable magnetic flux source **16** includes at least one rare earth permanent magnet which is moveable relative to the housing **14** to thus be switchable between an ON state having a magnetic strength at workpiece interfaces **28**, **30**, **32**, and **34** and an OFF state wherein a magnetic circuit is formed internally to housing **14**.

(33) As shown in FIGS. **1** and **2**, a channel **50** is provided between pole portions **20** and **24**.

Channel **50**, as discussed herein, may receive one or more sensors, stationary pins, retractable pins, probes, and/or additional tools.

(34) Referring to FIG. **3**, in embodiments, magnetic coupling tool **10** further includes a monitoring system **48** including one or more sensors which monitor a characteristic of magnetic coupling tool **10** and/or a characteristic of a magnetic circuit formed between magnetic coupling tool **10** and ferromagnetic workpiece **12**. As shown in FIG. **3**, a first sensor **60** may be positioned proximate first north pole portion **18**, a second sensor **62** may be positioned proximate first south pole portion **22**, and a third sensor **64** may be positioned proximate ferromagnetic workpiece **12** in a channel **50** provided between second north pole portion **20** and second south pole portion **24**. Each of first sensor **60**, second sensor **62**, and third sensor **64** may be a magnetic flux sensor. Additional types of sensors include temperature sensors which are used to compensate for temperature dependent drift in the magnetic flux sensors. Additionally, the positions of sensors **60**, **62**, and **64** are exemplary and one or sensors may be positioned at different locations. In embodiments, sensor **64** may be a proximity sensor. Exemplary proximity sensors include inductive sensors, ultrasound sensors, photonic sensors, and other suitable sensors.

(35) Each of sensors **60**, **62**, and **64** are operatively coupled to an electronic controller **70**.

Electronic controller **70** includes at least one processor **72** and associated memory **74**. Memory **74** includes magnetic coupling state logic **76**, logic control circuit, which monitors the output of sensors **60**, **62**, **64** to determine one or more characteristics of magnetic coupling tool **10** and/or one or more characteristics of a magnetic circuit formed between magnetic coupling tool **10** and ferromagnetic workpiece **12**. The term “logic” as used herein includes software and/or firmware executing on one or more programmable processors, application-specific integrated circuits, field-programmable gate arrays, digital signal processors, hardwired logic, or combinations thereof. Therefore, in accordance with the embodiments, various logic may be implemented in any appropriate fashion and would remain in accordance with the embodiments herein disclosed. A non-transitory machine-readable medium comprising logic can additionally be considered to be embodied within any tangible form of a computer-readable carrier, such as solid-state memory, magnetic disk, and optical disk containing an appropriate set of computer instructions and data structures that would cause a processor to carry out the techniques described herein. This disclosure contemplates other embodiments in which electronic controller **70** is not microprocessor-based, but rather is configured to control operation of magnetic coupling device **100** based on one or more sets of hardwired instructions. Further, electronic controller **70** may be contained within a single device or be a plurality of devices networked together or otherwise electrically connected to provide the functionality described herein.

(36) Electronic controller **70** may further receive input through one or more input devices **80**.

Exemplary input devices include buttons, switches, levers, dials, touch displays, soft keys, and a communication module. Electronic controller **70** may further provide output through one or more output devices **82**. Exemplary output devices include visual indicators, audio indicators, and a communication module. Exemplary visual indicators include displays, lights, and other visual systems. Exemplary audio indicators include speakers and other suitable audio systems.

(37) Referring to FIG. **4**, each of workpiece interface **30** and workpiece interface **34** are closer to

rotational axis **110** than either of first permanent magnet **102** and second permanent magnet **104**. Between workpiece interface **30** and workpiece interface **34** is channel **50** which as mentioned herein may receive one or more sensors, stationary pins, retractable pins, retractable pin clamps, cameras, probes, and/or additional tools. Workpiece interface **30** of second north pole portion **20** and workpiece interface **34** of second south pole portion **24** provide an external north pole of magnetic coupling device **100** and an external south pole of magnetic coupling device **100**, respectively, of a magnetic circuit formed with rare earth permanent magnets without any of the rare earth permanent magnets forming the magnetic circuit being positioned between second north pole portion **20** and second south pole portion **24**. Further, in embodiments, each of first permanent magnet **102** and second permanent magnet **104** surround rotational axis **110** and each of first permanent magnet **102** and second permanent magnet **104** include a respective aperture to form part of channel **50**.

(38) Referring to FIG. 4, an exemplary embodiment of magnetic coupling device **10** is shown, illustratively magnetic coupling device **100**. Magnetic coupling device **100** includes a switchable magnetic flux source **16** having a first permanent magnet **102** and a second permanent magnet **104**. Second permanent magnet **104** is spaced apart from first permanent magnet **102**. In embodiments, a spacer (not shown) is positioned between first permanent magnet **102** and second permanent magnet **104**. In embodiments, each of first permanent magnet **102** and second permanent magnet **104** are rare earth permanent magnets.

(39) Second permanent magnet **104** is moveable relative to first permanent magnet **102**. Magnetic coupling device **100** includes an actuator **106** which positions second permanent magnet **104** relative to first permanent magnet **102**. Exemplary actuators **106** include manual actuators, hydraulic actuators, pneumatic actuators, mechanical actuators, electrically controlled actuators, and combinations thereof. Referring to FIG. 5, actuator **106** is an electrically controlled actuator and includes a motor (not shown) which is controlled by electronic controller **70** to position second permanent magnet **104** relative to first permanent magnet **102**. Exemplary actuators are disclosed in U.S. Pat. No. 10,903,030, the entire disclosure of which is expressly incorporated by reference herein.

(40) In embodiments, actuator **106** rotates second permanent magnet **104** relative to first permanent magnet **102** about a rotational axis **110**. First permanent magnet **102** is held fixed relative to housing **14**. Workpiece interface **28** of first north pole portion **18**, workpiece interface **30** of second north pole portion **20**, workpiece interface **32** of first south pole portion **22**, and workpiece interface **34** of second south pole portion **24** are magnetically coupled to first permanent magnet **102** and second permanent magnet **104**. In embodiments, one or both of first permanent magnet **102** and second permanent magnet **104** are comprised of a single rare earth magnet. In embodiments, one or both of first permanent magnet **102** and second permanent magnet **104** are comprised of a multiple rare earth magnets that collectively form the respective first permanent magnet **102** or second permanent magnet **104**.

(41) In one position of second permanent magnet **104** relative to first permanent magnet **102**, a north pole of second permanent magnet **104** is generally aligned with a north pole of first permanent magnet **102** and a south pole of second permanent magnet **104** is generally aligned with a south pole of first permanent magnet **102**, as shown in FIG. 4. This configuration corresponds to magnetic coupling device **100** being in an ON state with workpiece interface **28** of first north pole portion **18** and workpiece interface **30** of second north pole portion **20** corresponding to an external north pole of magnetic coupling device **100** and workpiece interface **32** of first south pole portion **22** and workpiece interface **34** of second south pole portion **24** corresponding to an external south pole of magnetic coupling device **100**. In the ON state, when magnetic coupling device **100** is in contact with ferromagnetic workpiece **12**, a magnetic circuit is formed to magnetically couple ferromagnetic workpiece **12** to magnetic coupling device **100**.

(42) In another position of second permanent magnet **104** relative to first permanent magnet **102**, a

north pole of second permanent magnet **104** is generally aligned with a south pole of first permanent magnet **102** and a south pole of second permanent magnet **104** is generally aligned with a north pole of first permanent magnet **102**, as shown in FIG. 5. This configuration corresponds to magnetic coupling device **100** being in an OFF state and a magnetic circuit is formed generally within housing **14**; magnetic coupling device **100** lacks an external north pole at workpiece interface **28** of first north pole portion **18** and workpiece interface **30** of second north pole portion **20** and an external south pole at workpiece interface **32** of first south pole portion **22** and workpiece interface **34** of second south pole portion **24**. In the OFF state, ferromagnetic workpiece **12** is not magnetically coupled to magnetic coupling device **100**.

(43) Actuator **106** rotates second permanent magnet **104** about rotational axis **110** to move second permanent magnet **104** between the positions shown in FIG. 4 and FIG. 5. In embodiments, actuator **106** is able to position second permanent magnet **104** at rotational positions between those shown in FIGS. 4 and 5. These intermediate rotational positions correspond to partial ON states of magnetic coupling device **100** with workpiece interface **28** of first north pole portion **18** and workpiece interface **30** of second north pole portion **20** corresponding to an external north pole of magnetic coupling device **100** and workpiece interface **32** of first south pole portion **22** and workpiece interface **34** of second south pole portion **24** corresponding to an external south pole of magnetic coupling device **100**, but having a lower level of magnetic flux available at each of the external north pole and the external south pole. As such, magnetic coupling device **100** is able to be configured to provide a variable strength magnetic flux level to perform various operations, such as the operations disclosed in U.S. Pat. No. 10,903,030, the entire disclosure of which is expressly incorporated by reference herein.

(44) Referring to FIG. 4, each of workpiece interface **30** and workpiece interface **34** are closer to rotational axis **110** than either of first permanent magnet **102** and second permanent magnet **104**. Between workpiece interface **30** and workpiece interface **34** is channel **50** which as mentioned herein may receive one or more sensors and/or tools, such as probes. Workpiece interface **30** of second north pole portion **20** and workpiece interface **34** of second south pole portion **24** provide an external north pole of magnetic coupling device **100** and an external south pole of magnetic coupling device **100**, respectively, of a magnetic circuit formed with rare earth permanent magnets without any of the rare earth permanent magnets forming the magnetic circuit being positioned between second north pole portion **20** and second south pole portion **24**. Further, in embodiments, each of first permanent magnet **102** and second permanent magnet **104** surround rotational axis **110** and each of first permanent magnet **102** and second permanent magnet **104** include a respective aperture to form part of channel **50**.

(45) Referring to FIG. 6, an exemplary embodiment of magnetic coupling device **10** is shown, illustratively magnetic coupling device **200**. Magnetic coupling device **200** includes a switchable magnetic flux source **16** having a first permanent magnet **202** and a second permanent magnet **204**. Second permanent magnet **204** is spaced apart from first permanent magnet **202**. In embodiments, a spacer (not shown) is positioned between first permanent magnet **202** and second permanent magnet **204** or an air gap is maintained between first permanent magnet **202** and second permanent magnet **204**. In embodiments, first permanent magnet **202** is a rare earth permanent magnet and second permanent magnet **204** is an electro-permanent magnet. First permanent magnet **202** and second permanent magnet **204** are held fixed relative to housing **14**. Workpiece interface **28** of first north pole portion **18**, workpiece interface **30** of second north pole portion **20**, workpiece interface **32** of first south pole portion **22**, and workpiece interface **34** of second south pole portion **24** are magnetically coupled to first permanent magnet **202** and second permanent magnet **204**.

(46) At least a portion of second permanent magnet **204** is surrounded by a coil **210** which is coupled to a current source **212**. A direction and strength of a current provided through coil **210** is controlled by electronic controller **70**. The current is used to alter the pole positions for second permanent magnet **204**. In embodiments, the current may be used to position a north pole of second

permanent magnet **204** in general alignment with a north pole of first permanent magnet **202** and a south pole of second permanent magnet **204** is general alignment with a south pole of first permanent magnet **202**, as shown in FIG. **6**. The current does not need to be persistent to maintain second permanent magnet **204** in this configuration. This configuration corresponds to magnetic coupling device **200** being in an ON state with workpiece interface **28** of first north pole portion **18** and workpiece interface **30** of second north pole portion **20** corresponding to an external north pole of magnetic coupling device **200** and workpiece interface **32** of first south pole portion **22** and workpiece interface **34** of second south pole portion **24** corresponding to an external south pole of magnetic coupling device **200**. In the ON state, when magnetic coupling device **200** is in contact with ferromagnetic workpiece **12**, a magnetic circuit is formed to magnetically couple ferromagnetic workpiece **12** to magnetic coupling device **200**. In embodiments, the magnetic mass of first permanent magnet **202** and second permanent magnet **204** may be different or the same. In embodiments, one or both of first permanent magnet **202** and second permanent magnet **204** are comprised of a permanent magnet. In embodiments, one or both of first permanent magnet **102** and second permanent magnet **104** are comprised of multiple permanent magnets that collectively form the respective first permanent magnet **102** or second permanent magnet **104**.

(47) In embodiments, the current may be used to position a north pole of second permanent magnet **204** in general alignment with a south pole of first permanent magnet **202** and a south pole of second permanent magnet **204** in general alignment with a north pole of first permanent magnet **202**. This configuration corresponds to magnetic coupling device **200** being in an OFF state and a magnetic circuit is formed generally within housing **14**; magnetic coupling device **200** lacks an external north pole at workpiece interface **28** of first north pole portion **18** and workpiece interface **30** of second north pole portion **20** and an external south pole at workpiece interface **32** of first south pole portion **22** and workpiece interface **34** of second south pole portion **24**. In the OFF state, ferromagnetic workpiece **12** is not magnetically coupled to magnetic coupling device **100**.

(48) In embodiments, the electro permanent magnet of the second permanent magnet **204** may be charged to different levels to provide a variable magnetic strength at the workpiece interfaces **28**, **30**, **32**, **34**. Thus, at least one partial ON state may be configured having a magnetic strength at the workpiece interfaces **28**, **30**, **32**, **34** being less than the ON state and greater than the OFF state. Exemplary electro-permanent magnets include AlNiCo electro-permanent magnets.

(49) Referring to FIG. **6**, between workpiece interface **30** and workpiece interface **34** is channel **50** which as mentioned herein may receive one or more sensors and/or tools, such as probes. In embodiments, each of first permanent magnet **102** and second permanent magnet **104** surround rotational axis **110** and each of first permanent magnet **102** and second permanent magnet **104** include a respective aperture to form part of channel **50**.

(50) Referring to FIGS. **7-21**, an exemplary magnetic coupling device **300** is shown. Magnetic coupling device **300** is similar in structure to magnetic coupling device **100**. Magnetic coupling device **300** includes a housing **302**. Housing **302** is a multi-piece housing. Magnetic coupling device **300** includes an actuator assembly **304** and a magnet and pole piece assembly **306**.

(51) Referring to FIG. **12**, magnet and pole piece assembly **306** includes a first permanent magnet **320** and a second permanent magnet **322**. In the illustrated embodiment, each of first permanent magnet **320** and second permanent magnet **322** are rare earth permanent magnets.

(52) Magnet and pole piece assembly **306** includes a housing **318** having an opening **324** therethrough. Housing **318** is made of a ferromagnetic material. An exemplary ferromagnetic material is steel. An inwardly extending lip **326** (see FIG. **16**) is provided at a lower portion of housing **318**. Housing **318** is dimensioned such that only thin wall webs **328** and **330** connect a first thick walled housing portion **332** and a second thick walled housing portion **334**. Each of first thick walled housing portion **332** and second thick walled housing portion **334** provide integral pole extension pieces of magnetic coupling device **300**. Referring to FIG. **13**, first thick walled housing portion **332** includes a workpiece engagement surface **342** and second thick walled housing portion

334 includes a workpiece engagement surface **344**. First permanent magnet **320** is secured in housing **318** with a N-S pole separation plane **336** extending (bridging) between thin wall webs **328**, **330** resulting in a north pole portion **346** of first permanent magnet **320** being positioned adjacent second thick walled housing portion **334** of housing **318** and a south pole portion **348** of first permanent magnet **320** being positioned adjacent first thick walled housing portion **332** of housing **318**.

(53) Referring to FIG. 12, during assembly, a spacer **350** is received in opening **324** of housing **318** and is supported by lip **326** of housing **318**. First permanent magnet **320** is supported by a spacer **350** and secured to housing **318**. In embodiments, spacer **350** is non-ferromagnetic. In embodiments, spacer **350** is ferromagnetic. In embodiments, first permanent magnet **320** is secured to housing **318** with an adhesive, a mechanical interference, and/or a fastener. A second non-ferromagnetic spacer **352** is placed on top of first permanent magnet **320** and separates second permanent magnet **322** from first permanent magnet **320**. Second permanent magnet **322** is also received in opening **324** of housing **318** and is rotatable relative to housing **318** and first permanent magnet **320** about an axis **356**. Second permanent magnet **322** has a N-S pole separation plane **358** dividing a north pole portion **360** of second permanent magnet **322** and a south pole portion **362** of second permanent magnet **322**.

(54) Magnet and pole piece assembly **306** further includes a first pole member **370** and a second pole member **372**. Referring to FIG. 13, first pole member **370** includes a workpiece engagement surface **374** and second pole member **372** includes a workpiece engagement surface **376**. Each of first pole member **370** and second pole member **372** are received in an opening **378** in spacer **350**, an opening **380** in first permanent magnet **320**, an opening **382** in second non-ferromagnetic spacer **352**, and an opening **384** in second permanent magnet **322**. As shown in FIG. 16, each of workpiece engagement surface **342** of first thick walled housing portion **332**, workpiece engagement surface **344** of second thick walled housing portion **334**, workpiece engagement surface **374** of first pole member **370**, and workpiece engagement surface **376** of second pole member **372** are positioned lower than spacer **350**. Further, each of first pole member **370** and second pole member **372** have an arcuate outer shape to generally match the shape of opening **380** in first permanent magnet **320** and the shape of opening **384** in second permanent magnet **322** and provide good magnetic transfer therebetween. Opening **378** of spacer **350**, Opening **380** of first permanent magnet **320**, opening **382** of second non-ferromagnetic spacer **352**, and opening **384** of second permanent magnet **322**, collectively form a channel **390** (see FIGS. 13 and 14) which receives first pole member **370** and second pole member **372**.

(55) Referring to FIG. 13, N-S pole separation plane **336** of first permanent magnet **320** is represented. As shown, first pole member **370** is spaced apart from second pole member **372**. First pole member **370** is positioned on the same side of N-S pole separation plane **336** as first thick walled housing portion **332**. Thus, each of workpiece engagement surface **342** of first thick walled housing portion **332** and workpiece engagement surface **374** of first pole member **370** are south pole extension portions of first permanent magnet **320** and second permanent magnet **322** when first permanent magnet **320** and second permanent magnet **322** are aligned and collectively form an external south pole for magnetic coupling device **300**. Second pole member **372** is positioned on the same side of N-S pole separation plane **336** as second thick walled housing portion **334**. Thus, each of workpiece engagement surface **344** of second thick walled housing portion **334** and workpiece engagement surface **376** of second pole member **372** are north pole extension portions of first permanent magnet **320** and second permanent magnet **322** when first permanent magnet **320** and second permanent magnet **322** are aligned and collectively form an external north pole for magnetic coupling device **300**.

(56) Referring to FIGS. 13 and 17, workpiece engagement surface **342** of first thick walled housing portion **332**, workpiece engagement surface **344** of second thick walled housing portion **334**, workpiece engagement surface **374** of first pole member **370**, and workpiece engagement surface

376 of second pole member **372** are planar, parallel, and positioned in a common plane. In embodiments, the shape of each of workpiece engagement surface **342** of first thick walled housing portion **332**, workpiece engagement surface **344** of second thick walled housing portion **334**, workpiece engagement surface **374** of first pole member **370**, and workpiece engagement surface **376** of second pole member **372** is contoured to a shape of ferromagnetic workpiece **12**. Further, in embodiments, one or more of workpiece engagement surface **342** of first thick walled housing portion **332**, workpiece engagement surface **344** of second thick walled housing portion **334**, workpiece engagement surface **374** of first pole member **370**, and workpiece engagement surface **376** of second pole member **372** include spaced apart projections, such as the projections disclosed in US Published Patent Application No. 20/210031317, the entire disclosure of which is expressly incorporated by reference herein.

(57) In one position of second permanent magnet **322** relative to first permanent magnet **320**, north pole portion **360** of second permanent magnet **322** is generally aligned with north pole portion **346** of first permanent magnet **320** and south pole portion **362** of second permanent magnet **322** is generally aligned with south pole portion **348** of first permanent magnet **320**, as shown in FIG. **19**. This configuration corresponds to magnetic coupling device **300** being in an ON state with workpiece engagement surface **344** of workpiece engagement surface **342** and workpiece engagement surface **376** of second pole member **372** corresponding to an external north pole of magnetic coupling device **300** and workpiece engagement surface **342** of first thick walled housing portion **332** and workpiece engagement surface **374** of first pole member **370** corresponding to an external south pole of magnetic coupling device **300**. In the ON state, when magnetic coupling device **300** is in contact with ferromagnetic workpiece **12**, a magnetic circuit is formed to magnetically couple ferromagnetic workpiece **12** to magnetic coupling device **300**.

(58) In another position of second permanent magnet **322** relative to first permanent magnet **320**, north pole portion **360** of second permanent magnet **322** is generally aligned with south pole portion **348** of first permanent magnet **320** and south pole portion **362** of second permanent magnet **322** is generally aligned with north pole portion **346** of first permanent magnet **320**, as shown in FIG. **18**. This configuration corresponds to magnetic coupling device **300** being in an OFF state and a magnetic circuit is formed generally within housing **318**; magnetic coupling device **300** lacks an external north pole at workpiece engagement surface **344** of workpiece engagement surface **342** and workpiece engagement surface **376** of second pole member **372** and an external south pole at workpiece engagement surface **342** of first thick walled housing portion **332** and workpiece engagement surface **374** of first pole member **370**. In the OFF state, ferromagnetic workpiece **12** is not magnetically coupled to magnetic coupling device **300**.

(59) As described in more detail herein, an actuator assembly **500** (see FIG. **11**) rotates second permanent magnet **322** about axis **356** to move second permanent magnet **322** between the positions shown in FIG. **18** and FIG. **19**. In embodiments, actuator assembly **500** is able to position second permanent magnet **322** at rotational positions between those shown in FIGS. **18** and **19**. These intermediate rotational positions correspond to partial ON states of magnetic coupling device **300** with workpiece engagement surface **344** of workpiece engagement surface **342** and workpiece engagement surface **376** of second pole member **372** corresponding to an external north pole of magnetic coupling device **300** and workpiece engagement surface **342** of first thick walled housing portion **332** and workpiece engagement surface **374** of first pole member **370** corresponding to an external south pole of magnetic coupling device **300**, but having a lower level of magnetic flux available at each of the external north pole and the external south pole. As such, magnetic coupling device **300** is able to be configured to provide a variable strength magnetic flux level to perform various operations, such as the operations disclosed in U.S. Pat. No. 10,903,030, issued Jan. 26, 2021, titled VARIABLE FIELD MAGNETIC COUPLERS AND METHODS FOR ENGAGING A FERROMAGNETIC WORKPIECE, the entire disclosures of which are expressly incorporated by reference herein.

(60) Referring to FIG. 15, first pole member 370 and second pole member 372 are carried by a support 400. In embodiments, first pole member 370 and second pole member 372 are secured to support 400 with adhesive. Support 400 is non-ferromagnetic which is received in channel 390 of magnet and pole piece assembly 306. Support 400 includes a central channel 402. One or more of sensors, stationary pins, retractable pins, probes, and/or additional tools may be moved through central channel 402 of support 400 or wires coupled to sensors carried by support 400 may be routed through central channel 402 of support 400. As described herein, support 400 is secured to actuator assembly 304 of magnetic coupling device 300.

(61) Referring to FIG. 10, components of actuator assembly 304 are shown. Housing 302 includes an upper housing 510 and a lower housing 512. Upper housing 510, lower housing 512, and housing 318 are secured together through fasteners 514 which are received in openings in upper housing 510 and lower housing 512 and threaded into respective apertures 516 in housing 318. A top portion 410 of support 400 is press fit in opening 518 of upper housing 510 (see FIG. 7) or otherwise secured to housing 302 of magnetic coupling device 300.

(62) An engagement member 530 is coupled to second permanent magnet 322 which couplers 532 which are received in corresponding recesses 534 in second permanent magnet 322. An inner opening 540 of engagement member 530 is profiled to mesh with the teeth of a gear wheel 542 (see FIG. 11). As such, second permanent magnet 322 and gear wheel 542 rotate about axis 356 as a unit due to the coupling of engagement member 530.

(63) An actuator 550 is operatively coupled to gear wheel 542 to rotate gear wheel 542 about axis 356 and thus second permanent magnet 322 about axis 356. Actuator 550 includes a gear tooth portion which intermeshes with the teeth of gear wheel 542. Actuator 550 further includes a pin 554 which extends from both a lower side and an upper side of actuator 550. Pin 554 is received in recess 560 in lower housing 512 and a corresponding recess (not shown) in upper housing 510. Bushings 556 and 558 are provided between pin 554 and upper housing 510 and pin 554 and lower housing 512, respectively.

(64) Actuator 550 further includes an operator actuatable handle 570. Actuator 550 also includes a lock operator 572. Lock operator 572 is rotatably coupled to operator actuatable handle 570 about pin 574 which is received in apertures 578 of operator actuatable handle 570. A distal end of lock operator 572 is biased away from operator actuatable handle 570 with a spring 576.

(65) Referring to FIG. 8, lock operator 572 may be rotated upward by an operator in direction 580 into a recess in operator actuatable handle 570 to permit movement of operator actuatable handle 570 in one of direction 582 and 584. When released, lock operator 572 may be received in one of ON lock recess 586 and OFF lock recess 588 (see FIG. 10). Housing 302 includes a first indicia 590 indicating an ON state of magnetic coupling device 300 and a second indicia 592 indicating an OFF state of magnetic coupling device 300.

(66) When actuator 550 is in the position shown in FIG. 8 with lock operator 572 in OFF lock recess 588, magnetic coupling device 300 is in the OFF state with second permanent magnet 322 in the position shown in FIG. 18 relative to first permanent magnet 320. An operator may depress lock operator 572 to move lock operator 572 in direction 580 and out of OFF lock recess 588. The operator may then move operator actuatable handle 570 in direction 582 till lock operator 572 is above ON lock recess 586. The operator then releases lock operator 572 which is received in ON lock recess 586. The rotation of operator actuatable handle 570 causes a corresponding rotation of gear wheel 542 and in turn second permanent magnet 322 relative to first permanent magnet 320. When lock operator 572 is in ON lock recess 586, magnetic coupling device 300 is in the ON state with second permanent magnet 322 in the position shown in FIG. 19 relative to first permanent magnet 320. The process is reversed to transition magnetic coupling device 300 from the ON state to the OFF state.

(67) Each of first pole member 370 and second pole member 372 is an exemplary ferromagnetic insert. The magnets 320, 322 of magnetic coupling device 300 form an exemplary switchable

magnetic flux source. As illustrated in FIG. 12, first permanent magnet 320 and second permanent magnet 322 are each ring magnets. Each of first permanent magnet 320 and second permanent magnet 322 are permanent magnets and in embodiments are both rare earth permanent magnets. First permanent magnet 320 includes a first outer circumferential surface 420 and a first inner circumferential surface 422 which defines opening 380. Second permanent magnet 322 includes a second outer circumferential surface 424 and a second inner circumferential surface 426 which defines opening 384. Ferromagnetic insert 370 includes an outer arcuate surface 428 positioned adjacent the first inner circumferential surface 422 of the first permanent ring magnet 320 (see FIG. 15). Ferromagnetic insert 372 includes an outer arcuate surface 430 positioned adjacent the second inner circumferential surface 426 of the second permanent magnet 322 (see FIG. 15).

Ferromagnetic insert 370 remains stationary relative to the first permanent ring magnet 320 as the second permanent ring magnet 322 rotates relative to the first permanent ring magnet 320.

Ferromagnetic insert 372 remains stationary relative to the first permanent ring magnet 320 as the second permanent ring magnet 322 rotates relative to the first permanent ring magnet 320. Each of the first outer arcuate surface 428 of the first ferromagnetic insert 370 and the second outer arcuate surface 430 of the second ferromagnetic insert 372 are positioned closer to the axis 356 than the first permanent ring magnet 320 and the second permanent ring magnet 322. The first outer arcuate surface 428 of the first ferromagnetic insert 370 contacts the first inner circumferential surface 422 of the first permanent ring magnet 320. The first outer arcuate surface 430 of the first ferromagnetic insert 372 contacts the second inner circumferential surface 426 of the second permanent ring magnet 322.

(68) The switchable magnetic flux has a first configuration wherein a north pole of the second permanent ring magnet 322 is aligned relative to a north pole of the first permanent ring magnet 320 and a second configuration wherein a south pole of the second permanent ring magnet 322 is aligned relative to the north pole of the first permanent magnet 320. Workpiece engagement surfaces 342 and 344 of first thick walled housing portion 332 and second thick walled housing portion 334 are adapted to contact a ferromagnetic workpiece.

(69) Referring to FIG. 20, an embodiment of magnetic coupling tool 10 is shown which includes at least one locator 86. Locator 86 illustratively is a stationary pin which is carried by housing 14. Locator 86 includes a lowermost extent 88 which extends away from housing 14. As shown in FIG. 21, the lowermost extent 88 of at least one locator 86 extends into a locating feature 15, illustratively a hole, in ferromagnetic workpiece 12. The lowermost extent 88 of at least one locator 86 is lower than workpiece interface 30 of second north pole portion 20 and workpiece interface 34 of second south pole portion 24 which contact surface 26 of ferromagnetic workpiece 12. In embodiments, the relative position of the lowermost extent 88 of at least one locator 86 is lower than workpiece interface 30 of second north pole portion 20 and workpiece interface 34 of second south pole portion 24 remains constant when magnetic coupling tool 10 is spaced apart from ferromagnetic workpiece 12 and when magnetic coupling tool 10 is coupled to ferromagnetic workpiece 12. In other embodiments, at least one locator 86 is positioned completely within housing 14 and receives a protrusion of ferromagnetic workpiece 12 to locate magnetic coupling tool 10 relative to ferromagnetic workpiece 12.

(70) In embodiments, ferromagnetic workpiece 12 does not include a locating feature and at least one locator 86 is retractable from an extended position wherein the lowermost extent 88 of 86 extends lower than workpiece interface 30 of second north pole portion 20 and workpiece interface 34 of second south pole portion 24 to a retracted position wherein the lowermost extent 88 of at least one locator 86 is one of aligned with one or both lower than workpiece interface 30 of second north pole portion 20 and workpiece interface 34 of second south pole portion 24 or the lowermost extent 88 of at least one locator 86 is retracted relative to housing 14 so that the lowermost extent 88 of at least one locator 86 remains spaced apart from ferromagnetic workpiece 12 when workpiece interface 30 of second north pole portion 20 and workpiece interface 34 of second south

pole portion **24** contact ferromagnetic workpiece **12**. Exemplary retracting locators include retractable pins.

(71) The position of retractable locator **86** in FIG. **22** is controlled by a locator actuator **90** which is supported by housing **14**. Locator actuator **90** may be mechanical, electric, pneumatic, hydraulic, or magnetic and is capable of moving the lowermost extent **88** of at least one locator **86** between an extended position, such as in FIG. **21**, and a retracted position, such as FIG. **22**. In the illustrated embodiment, electronic controller **70** includes locator position logic **92** which is executed by at least one processor **72** to control the position of at least one locator **86**. An advantage, among others, of incorporating a retractable locator is that magnetic coupling tool **10** may be used in a larger variety of applications and with different types of ferromagnetic workpiece **12**.

(72) Referring to FIGS. **23** and **24**, another arrangement of magnetic coupling device **300** is shown. In this arrangement, only permanent magnet **320** is included and permanent magnet **320** is rotatable relative to housing **318**. Permanent magnet **320** forms the switchable magnetic flux source. In alternative embodiments, both first permanent magnet **320** and second permanent magnet **322** are included and rotate relative to housing **318** as a group to form the switchable magnetic flux source. In other embodiments, additional permanent magnets may be included in the group including first permanent magnet **320** and second permanent magnet **322** and rotate as a group to form the switchable magnetic flux source.

(73) Referring to FIG. **23**, first permanent magnet **320** is arranged relative to housing **318** such that each of the north pole portion (N) and the south pole portion(S) of first permanent magnet **320** are exposed to both first thick walled housing portion **332** and second thick walled housing portion **334**. This is the OFF state for the device and the magnetic circuit is completed internally to housing **318**. Referring to FIG. **24**, first permanent magnet **320** has been rotated 90 degrees relative to FIG. **23** such that the north pole portion (N) of first permanent magnet **320** is exposed to second thick walled housing portion **334** and the south pole portion(S) of first permanent magnet **320** is exposed to first thick walled housing portion **332**. This results in the magnetic circuit being completed through workpiece engagement surface **344** of second thick walled housing portion **334**, workpiece engagement surface **376** of second pole member **372**, ferromagnetic workpiece **12**, workpiece engagement surface **342** of first thick walled housing portion **332**, workpiece engagement surface **374** of first pole member **370**, and is the ON state for the device.

(74) In embodiments, the magnetic coupling devices disclosed herein have an elongated housing to hold multiple instances of the respective magnetic flux sources and pole portions in a linear array. An exemplary device having multiple instances of magnetic flux sources is the LAY Series unit as manufactured and sold by Magswitch Technology Inc.

(75) In embodiments, the magnetic coupling devices disclosed herein have an elongated housing to hold multiple instances of the respective magnetic flux sources and pole portions in a circular array. An exemplary device having multiple instances of magnetic flux source **15** is the AY Series unit as manufactured and sold by Magswitch Technology Inc.

(76) In embodiments, the magnetic coupling devices disclosed herein may be used as part of a fixture to hold a ferromagnetic part or an end-of-arm-tool for a robot which is able to couple and move a ferromagnetic part.

EXAMPLES

(77) Example 1. A magnetic coupling device for magnetically coupling to a ferromagnetic workpiece is provided. The magnetic coupling device may comprise a housing; a switchable magnetic flux source supported by the housing; and a plurality of pole portions, each having at least one workpiece engagement surface. The switchable magnetic flux source may be switchable between at least an OFF state and an ON state. The switchable magnetic flux source may be positioned between the plurality of pole portions. The plurality of pole portions may include a first north pole portion having a first workpiece engagement surface, a second north pole portion having a second workpiece engagement surface, a first south pole portion having a third workpiece

engagement surface, and a second south pole portion having a fourth workpiece engagement surface. The second north pole portion and the second south pole portion may each be positioned between the first north pole portion and the first south pole portion and the switchable magnetic flux source in an ON state may be magnetically coupled to each of the first workpiece engagement surface of the first north pole portion, the second workpiece engagement surface of the second north pole portion, the third workpiece engagement surface of the first south pole portion, and the fourth workpiece engagement surface of the second south pole portion.

(78) Example 2. The magnetic coupling device of Example 1, wherein a channel may be located between the first north pole portion and the first south pole portion.

(79) Example 3. The magnetic coupling device of Example 2, further comprising a sensor positioned in the channel.

(80) Example 4. The magnetic coupling device of Example 2, further comprising a tool positioned in the channel.

(81) Example 5. The magnetic coupling device of Example 2, further comprising one of a tool and a sensor positioned in the channel.

(82) Example 6. The magnetic coupling device of any of Examples 2-5, wherein the channel may extend from a first position above a top side of the switchable magnetic flux source to a second position below the top side of the switchable magnetic flux source.

(83) Example 7. The magnetic coupling device of any of Examples 2-6, wherein the channel may be positioned between the second north pole portion and the second south pole portion.

(84) Example 8. The magnetic coupling device of any of the preceding Examples, wherein the second north pole portion may be positioned between the second south pole portion and the first north pole portion.

(85) Example 9. The magnetic coupling device of any of the preceding Examples, wherein the switchable magnetic flux source includes a plurality of permanent magnets.

(86) Example 10. The magnetic coupling device of Example 9, wherein at least first one of the plurality of permanent magnets may be an electro-permanent magnet.

(87) Example 11. The magnetic coupling device of Example 9, wherein at least a second one of the plurality of permanent magnets may be a rare earth magnet.

(88) Example 12. The magnetic coupling device of Example 9, wherein the plurality of permanent magnets including a first permanent magnet and a second permanent magnet movable relative to the first permanent magnet.

(89) Example 13. The magnetic coupling device of Example 12, wherein the second permanent magnet may be rotatable relative to the first permanent magnet.

(90) Example 14. The magnetic coupling device of Example 13, wherein each of the first permanent magnet and the second permanent magnet are positioned between the first north pole portion and the first south pole portion.

(91) Example 15. The magnetic coupling device of any one of Examples 12-14, wherein in the ON state of the magnetic flux source a north pole of the second permanent magnet may be generally aligned with a north pole of the first permanent magnet and in the OFF state of the magnetic flux source a south pole of the second permanent magnet may be generally aligned with the north pole of the first permanent magnet.

(92) Example 16. A magnetic coupling device for magnetically coupling to a ferromagnetic workpiece is provided. The magnetic coupling device may comprise a housing; a switchable magnetic flux source supported by the housing including a plurality of permanent magnets; and a plurality of workpiece engagement surfaces supported by the housing and magnetically coupled to the switchable magnetic flux source. The plurality of permanent magnets may include a first permanent magnet and a second permanent magnet movable relative to the first permanent magnet about a first axis of rotation. The plurality of workpiece engagement surfaces may be adapted to contact the ferromagnetic workpiece. A first workpiece engagement surface of the plurality of

workpiece engagement surfaces may correspond to a north pole of the magnetic coupling device and a second workpiece engagement surface of the plurality of workpiece engagement surfaces may correspond to a south pole of the magnetic coupling device. Both the first workpiece engagement surface and the second workpiece engagement surface may be closer to the first axis of rotation than the second permanent magnet.

(93) Example 17. The magnetic coupling device of Example 16, wherein the plurality of workpiece engagement surfaces may further include a third workpiece engagement surface corresponding to the north pole of the magnetic coupling device and a fourth workpiece engagement surface corresponding to the south pole of the magnetic coupling device, each of the third workpiece engagement surface and the fourth workpiece engagement surface may be further away from the first axis of rotation than the second permanent magnet.

(94) Example 18. The magnetic coupling device of Example 16, wherein the first permanent magnet may surround the first workpiece engagement surface and the second workpiece engagement surface.

(95) Example 19. The magnetic coupling device of Example 16, wherein each of the first permanent magnet and the second permanent magnet may surround the first workpiece engagement surface and the second workpiece engagement surface.

(96) Example 20. The magnetic coupling device of any of the preceding Examples, further comprising: a first pole member including the first workpiece engagement surface; a second pole member including the second workpiece engagement surface, the first pole member and the second pole member defining a channel; and at least one sensor positioned in the channel.

(97) Example 21. The magnetic coupling device of Example 20, wherein the second permanent magnet includes a top face and a bottom face, the bottom face facing the first permanent magnet, the at least one sensor may be positioned lower than the top face of the second permanent magnet.

(98) Example 22. The magnetic coupling device of Example 21, wherein the at least one sensor may be positioned lower than the bottom face of the second permanent magnet.

(99) Example 23. The magnetic coupling device of any one of Examples 20-22, wherein the at least one sensor includes a first magnetic field sensor positioned to monitor a first magnetic flux associated with at least one of the first workpiece engagement surface and the second workpiece engagement surface.

(100) Example 24. The magnetic coupling device of any one of Examples 20-23, further comprising a logic control circuit operatively coupled to the at least one sensor, the logic control circuit may be configured to determine at least one operating state of the magnetic coupling device based on an output from the at least one sensor.

(101) Example 25. The magnetic coupling device of Example 24 further comprising an output device which provides an indication of the operating state of the magnetic coupling device.

(102) Example 26. The magnetic coupling device of any of Examples 20-25,

(103) further comprising at least one of a stationary pin, a retractable pin, and a probe moveable within the channel.

(104) Example 27. The magnetic coupling device of Example 26, wherein the probe supports the at least one sensor.

(105) Example 28. The magnetic coupling device of any of the preceding Examples further comprising an actuator operatively coupled to the second permanent magnet to move the second permanent magnet relative to the first permanent magnet.

(106) Example 29. The magnetic coupling device of Example 28, wherein the actuator may be one of a user input having an operator actuatable portion, an electric motor, at least one conductive coil, a hydraulic system, and a pneumatic system.

(107) Example 30. The magnetic coupling device of Example 28, wherein the actuator may be a user input having an operator actuatable portion which may be moveable between a first position corresponding to the second permanent magnet may be in a first orientation relative to the first

permanent magnet and a second position corresponding to the second permanent magnet may be in a second orientation relative to the first permanent magnet and further comprising a lock to hold the second permanent magnet in at least one of the first orientation and the second orientation.

(108) Example 31. A magnetic coupling device for magnetically coupling to a ferromagnetic workpiece is provided. The magnetic coupling device may comprise a housing; a switchable magnetic flux source supported by the housing including a plurality of permanent magnets; and a plurality of workpiece engagement surfaces supported by the housing and magnetically coupled to the switchable magnetic flux source. The plurality of permanent magnets may include a first permanent magnet and a second permanent magnet movable relative to the first permanent magnet about a first axis of rotation. The plurality of workpiece engagement surfaces may be adapted to contact the ferromagnetic workpiece. A first workpiece engagement surface of the plurality of workpiece engagement surfaces may correspond to a north pole of the magnetic coupling device and a second workpiece engagement surface of the plurality of workpiece engagement surfaces may correspond to a south pole of the magnetic coupling device. The magnetic coupling device may further comprise at least one sensor positioned in a channel between the first workpiece engagement surface and the second workpiece engagement surface. The at least one sensor may further be positioned between a lower surface of the first permanent magnet and the upper surface of the second permanent magnet.

(109) Example 32. A magnetic coupling device for magnetically coupling to a ferromagnetic workpiece is provided. The magnetic coupling device may comprise a housing; a switchable magnetic flux source supported by the housing including a plurality of permanent magnets; and a plurality of workpiece engagement surfaces supported by the housing and magnetically coupled to the switchable magnetic flux source. The plurality of permanent magnets may include a first permanent magnet and a second permanent magnet movable relative to the first permanent magnet about a first axis of rotation. The plurality of workpiece engagement surfaces may be adapted to contact the ferromagnetic workpiece. A first workpiece engagement surface of the plurality of workpiece engagement surfaces may correspond to a north pole of the magnetic coupling device and a second workpiece engagement surface of the plurality of workpiece engagement surfaces may correspond to a south pole of the magnetic coupling device. The magnetic coupling device may further comprise at least one tool positioned in a channel between the first workpiece engagement surface and the second workpiece engagement surface and between a lower surface of the first permanent magnet and the upper surface of the second permanent magnet.

(110) Example 33. A magnetic coupling device for magnetically coupling to a ferromagnetic workpiece is provided. The magnetic coupling device may comprise a housing; a switchable magnetic flux source supported by the housing including a plurality of permanent magnets; and a plurality of workpiece engagement surfaces supported by the housing and magnetically coupled to the switchable magnetic flux source. The plurality of permanent magnets may include a first permanent magnet and a second permanent magnet movable relative to the first permanent magnet. The first permanent magnet may have a first end surface and a second end surface. The plurality of workpiece engagement surfaces may be adapted to contact the ferromagnetic workpiece. The plurality of workpiece engagement surfaces may comprise a first workpiece engagement surface positioned adjacent the first end surface of the first permanent magnet, a second workpiece engagement surface positioned adjacent the second end surface of the first permanent magnet, each of the first workpiece engagement surface and the second workpiece engagement surface corresponding to a north pole of the magnetic coupling device; a third workpiece engagement surface; and a fourth workpiece engagement surface spaced apart from the third workpiece engagement surface, each of the third workpiece engagement surface and the fourth workpiece engagement surface corresponding to a south pole of the magnetic coupling device.

(111) Example 34. The magnetic coupling device of Example 33, wherein the third workpiece engagement surface may be positioned adjacent the first end surface of the first permanent magnet

and the fourth workpiece engagement surface may be positioned adjacent the second end surface of the first permanent magnet.

(112) Example 35. The magnetic coupling device of Example 33, wherein the second permanent magnet may be rotatable relative to the first permanent magnet.

(113) Example 36. The magnetic coupling device of Example 35, wherein a strength level of a magnetic field of the north pole of the magnetic coupling device may be varied based on a rotational position of the second permanent magnet relative to the first permanent magnet.

(114) Example 37. The magnetic coupling device of Example 36, wherein the strength level of the magnetic field of the north pole of the magnetic coupling device may be strongest when a north pole of the second permanent magnet is aligned with a north pole of the first permanent magnet and may be weakest when the north pole of the second permanent magnet is aligned with a south pole of the first permanent magnet.

(115) Example 38. The magnetic coupling device of Example 33, wherein the first permanent magnet surrounds the first workpiece engagement surface and the third workpiece engagement surface.

(116) Example 39. The magnetic coupling device of Example 33, wherein each of the first permanent magnet and the second permanent magnet may surround the first workpiece engagement surface and the third workpiece engagement surface.

(117) Example 40. The magnetic coupling device of any of Examples 33-39, may further comprise a first pole member including the first workpiece engagement surface; a second pole member including the third workpiece engagement surface, the first pole member and the second pole member defining a channel; and at least one sensor positioned in the channel.

(118) Example 41. The magnetic coupling device of Example 40, wherein the

(119) second permanent magnet includes a top face and a bottom face, the bottom face facing the first permanent magnet, the at least one sensor may be positioned lower than the top face of the second permanent magnet.

(120) Example 42. The magnetic coupling device of Example 41, wherein the at least one sensor may be positioned lower than the bottom face of the second permanent magnet.

(121) Example 43. The magnetic coupling device of any one of Examples 40-42, wherein the at least one sensor includes a first magnetic field sensor positioned to monitor a first magnetic flux associated with at least one of the first workpiece engagement surface and the third workpiece engagement surface.

(122) Example 44. The magnetic coupling device of any one of Examples 40-42, further comprising a logic control circuit operatively coupled to the at least one sensor, the logic control circuit may be configured to determine at least one operating state of the magnetic coupling device based on an output from the at least one sensor.

(123) Example 45. The magnetic coupling device of Example 44 further comprising an output device which may provide an indication of the operating state of the magnetic coupling device.

(124) Example 46. The magnetic coupling device of any of Examples 40-45, further comprising a probe moveable within the channel.

(125) Example 47. The magnetic coupling device of Example 46, wherein the probe supports the at least one sensor.

(126) Example 48. The magnetic coupling device of any of Examples 33-47, further comprising an actuator operatively coupled to the second permanent magnet to move the second permanent magnet relative to the first permanent magnet.

(127) Example 49. The magnetic coupling device of Example 48, wherein the actuator may be one of a user input having an operator actuatable portion, an electric motor, at least one conductive coil, a hydraulic system, and a pneumatic system.

(128) Example 50. The magnetic coupling device of any one of Examples 32, 33, and 40, wherein a proximity sensor may be positioned in the channel.

(129) Example 51. A magnetic coupling device for magnetically coupling to a ferromagnetic workpiece is provided. The magnetic coupling device may comprise a housing; a switchable magnetic flux source supported by the housing including at least one electro-permanent magnet; and a plurality of workpiece engagement surfaces supported by the housing and magnetically coupled to the switchable magnetic flux source. The plurality of workpiece engagement surfaces may be adapted to contact the ferromagnetic workpiece. A first pole portion may include a first workpiece engagement surface of the plurality of workpiece engagement surfaces. A second pole portion may include a second workpiece engagement surface of the plurality of workpiece engagement surfaces. The first workpiece engagement surface and the second workpiece engagement surface may correspond to a north pole of the magnetic coupling device. A third pole portion may include a third workpiece engagement surface of the plurality of workpiece engagement surfaces. A fourth pole portion may include a fourth workpiece engagement surface of the plurality of workpiece engagement surfaces. The third workpiece engagement surface and the fourth workpiece engagement surface may correspond to a south pole of the magnetic coupling device. Both the first pole portion and the third pole portion may be received in an opening in the switchable magnetic flux source.

(130) Example 52. The magnetic coupling device of Example 51, wherein the second pole portion and the fourth pole portion are outside of an envelope of the switchable magnetic flux source.

(131) Example 53. The magnetic coupling device of Example 51, wherein the switchable magnetic flux source includes at least one rare earth permanent magnet.

(132) Example 54. The magnetic coupling device of any of Examples 51-53, further comprising at least one sensor, wherein the first pole member and the second pole member define a channel, the at least one sensor positioned in the channel.

(133) Example 55. A magnetic coupling device for magnetically coupling to a ferromagnetic workpiece is provided. The magnetic coupling device may comprise a housing; a switchable magnetic flux source supported by the housing including a plurality of magnets. The plurality of magnets may include a first magnet and a second magnet. The switchable magnetic flux may have a first configuration wherein a north pole of the second magnet may be aligned relative to a north pole of the first magnet and a second configuration wherein a south pole of the second magnet may be aligned relative to the north pole of the first magnet. The magnetic coupling device may further comprise a plurality of workpiece engagement surfaces supported by the housing and magnetically coupled to the switchable magnetic flux source. The plurality of workpiece engagement surfaces may be adapted to contact the ferromagnetic workpiece. A first pole portion may include a first workpiece engagement surface of the plurality of workpiece engagement surfaces. A second pole portion may include a second workpiece engagement surface of the plurality of workpiece engagement surfaces. The first workpiece engagement surface and the second workpiece engagement surface may correspond to a north pole of the magnetic coupling device. A third pole portion may include a third workpiece engagement surface of the plurality of workpiece engagement surfaces. A fourth pole portion may include a fourth workpiece engagement surface of the plurality of workpiece engagement surfaces. The third workpiece engagement surface and the fourth workpiece engagement surface may correspond to a south pole of the magnetic coupling device. Both the first pole portion and the third pole portion may be received in an opening in the switchable magnetic flux source.

(134) Example 56. The magnetic coupling device of Example 55, wherein the second pole portion and the fourth pole portion are outside of an envelope of the first magnet.

(135) Example 57. The magnetic coupling device of Example 55, wherein the second magnet may be movable relative to the first permanent magnet.

(136) Example 58. The magnetic coupling device of Example 57, wherein the second magnet may be rotatable relative to the first magnet.

(137) Example 59. The magnetic coupling device of Example 58, wherein a strength level of a

magnetic field of the north pole of the magnetic coupling device may be varied based on a rotational position of the second magnet relative to the first magnet.

(138) Example 60. The magnetic coupling device of Example 59, wherein the strength level of the magnetic field of the north pole of the magnetic coupling device may be strongest when a north pole of the second magnet is aligned with a north pole of the first magnet and may be weakest when the north pole of the second magnet is aligned with a south pole of the first magnet.

(139) Example 61. The magnetic coupling device of any of Examples 55-60, further comprising at least one sensor, wherein the first pole member and the second pole member may define a channel, the at least one sensor may be positioned in the channel.

(140) Example 62. The magnetic coupling device of Example 61, wherein the second magnet includes a top face and a bottom face, the bottom face facing the first magnet, the at least one sensor may be positioned lower than the top face of the second magnet.

(141) Example 63. The magnetic coupling device of Example 62, wherein the at least one sensor may be positioned lower than the bottom face of the second magnet.

(142) Example 64. The magnetic coupling device of any one of Examples 61-63, wherein the at least one sensor includes a first magnetic field sensor positioned to monitor a first magnetic flux associated with at least one of the first workpiece engagement surface and the third workpiece engagement surface.

(143) Example 65. The magnetic coupling device of any one of Examples 61-64, further comprising a logic control circuit operatively coupled to the at least one sensor, the logic control circuit may be configured to determine at least one operating state of the magnetic coupling device based on an output from the at least one sensor.

(144) Example 66. The magnetic coupling device of Example 65 further comprising an output device which provides an indication of the operating state of the magnetic coupling device.

(145) Example 67. The magnetic coupling device of any of Examples 61-66,

(146) further comprising at least one of a pin, a probe, and tool positioned within the channel.

(147) Example 68. The magnetic coupling device of Example 67, wherein the

(148) probe supports the at least one sensor.

(149) Example 69. The magnetic coupling device of Example 57, further comprising an actuator operatively coupled to the second magnet to move the second magnet relative to the first magnet.

(150) Example 70. The magnetic coupling device of Example 69, wherein the

(151) actuator may be one of a user input having an operator actuatable portion, an electric motor, at least one conductive coil, a hydraulic system, and a pneumatic system.

(152) Example 71. The magnetic coupling device of any one of Examples 55-70, wherein the first magnet may be a permanent magnet.

(153) Example 72. The magnetic coupling device of any one of Examples 55-71, wherein each of the first magnet and the second magnet may be a permanent magnet.

(154) Example 73. A magnetic coupling device for magnetically coupling to a ferromagnetic workpiece is provided. The magnetic coupling device may comprise a housing and a switchable magnetic flux source supported by the housing including a plurality of magnets and a plurality of ferromagnetic inserts. The plurality of magnets may include a first permanent ring magnet having a first outer circumferential surface and a first inner circumferential surface and a second permanent ring magnet having a second outer circumferential surface and a second inner circumferential surface. The plurality of ferromagnetic inserts may include a first ferromagnetic insert having a first outer arcuate surface positioned adjacent the first inner circumferential surface of the first permanent ring magnet and a second ferromagnetic insert having a second outer arcuate surface positioned adjacent the second inner circumferential surface of the second permanent magnet. The switchable magnetic flux may have a first configuration wherein a north pole of the second permanent ring magnet may be aligned relative to a north pole of the first permanent ring magnet and a second configuration wherein a south pole of the second permanent ring magnet may be

aligned relative to the north pole of the first permanent magnet. The magnetic coupling device may further comprise a plurality of workpiece engagement surfaces magnetically coupled to the switchable magnetic flux source. The plurality of workpiece engagement surfaces may be adapted to contact the ferromagnetic workpiece. A first pole portion may include a first workpiece engagement surface of the plurality of workpiece engagement surfaces. A second pole portion may include a second workpiece engagement surface of the plurality of workpiece engagement surfaces.

(155) Example 74. The magnetic coupling device of Example 73, wherein the second permanent ring magnet may be moveable relative to the first permanent ring magnet.

(156) Example 75. The magnetic coupling device of Example 74, wherein the second permanent ring magnet may be rotatable relative to the first permanent ring magnet about a first axis.

(157) Example 76. The magnetic coupling device of Example 75, wherein the first ferromagnetic insert remains stationary relative to the first permanent ring magnet as the second permanent ring magnet rotates relative to the first permanent ring magnet.

(158) Example 77. The magnetic coupling device of Example 75, wherein the second ferromagnetic insert remains stationary relative to the first permanent ring magnet as the second permanent ring magnet rotates relative to the first permanent ring magnet.

(159) Example 78. The magnetic coupling device of any of Examples 73-77, wherein each of the first outer arcuate surface of the first ferromagnetic insert and the second outer arcuate surface of the second ferromagnetic insert are positioned closer to the first axis than the first permanent ring magnet and the second permanent ring magnet.

(160) Example 79. The magnetic coupling device of any of Examples 73-77, wherein the first outer arcuate surface of the first ferromagnetic insert contacts the first inner circumferential surface of the first permanent ring magnet.

(161) Example 80. The magnetic coupling device of any of Examples 73-77, wherein the first outer arcuate surface of the first ferromagnetic insert contacts the second inner circumferential surface of the second permanent ring magnet.

(162) Various modifications and additions can be made to the exemplary embodiments discussed without departing from the scope of the present invention. For example, while the embodiments described above refer to particular features, the scope of this invention also includes embodiments having different combinations of features and embodiments that do not include all of the described features. Accordingly, the scope of the present invention is intended to embrace all such alternatives, modifications, and variations as fall within the scope of the claims, together with all equivalents thereof.

Claims

1. A magnetic coupling device for magnetically coupling to a ferromagnetic workpiece, comprising: a housing; a switchable magnetic flux source supported by the housing including a plurality of permanent magnets, the plurality of permanent magnets including a first permanent magnet and a second permanent magnet movable relative to the first permanent magnet about a first axis of rotation; a plurality of workpiece engagement surfaces supported by the housing and magnetically coupled to the switchable magnetic flux source, the plurality of workpiece engagement surfaces adapted to contact the ferromagnetic workpiece, a first workpiece engagement surface of the plurality of workpiece engagement surfaces corresponding to a north pole of the magnetic coupling device and a second workpiece engagement surface of the plurality of workpiece engagement surfaces corresponding to a south pole of the magnetic coupling device, both the first workpiece engagement surface and the second workpiece engagement surface being closer to the first axis of rotation than the second permanent magnet.

2. The magnetic coupling device of claim 1, wherein the plurality of workpiece engagement

surfaces further includes a third workpiece engagement surface corresponding to the north pole of the magnetic coupling device and a fourth workpiece engagement surface corresponding to the south pole of the magnetic coupling device, each of the third workpiece engagement surface and the fourth workpiece engagement surface being further away from the first axis of rotation than the second permanent magnet.

3. The magnetic coupling device of claim 1, wherein the first permanent magnet surrounds the first workpiece engagement surface and the second workpiece engagement surface.

4. The magnetic coupling device of claim 1, wherein each of the first permanent magnet and the second permanent magnet surrounds the first workpiece engagement surface and the second workpiece engagement surface.

5. The magnetic coupling device of claim 1, further comprising: a first pole member including the first workpiece engagement surface; a second pole member including the second workpiece engagement surface, the first pole member and the second pole member defining a channel; and at least one sensor positioned in the channel.

6. The magnetic coupling device of claim 5, wherein the second permanent magnet includes a top face and a bottom face, the bottom face facing the first permanent magnet, the at least one sensor is positioned lower than the top face of the second permanent magnet.

7. The magnetic coupling device of claim 6, wherein the at least one sensor is positioned lower than the bottom face of the second permanent magnet.

8. The magnetic coupling device of claim 5, wherein the at least one sensor includes a first magnetic field sensor positioned to monitor a first magnetic flux associated with at least one of the first workpiece engagement surface and the second workpiece engagement surface.

9. The magnetic coupling device of claim 5, further comprising a logic control circuit operatively coupled to the at least one sensor, the logic control circuit configured to determine at least one operating state of the magnetic coupling device based on an output from the at least one sensor.

10. The magnetic coupling device of claim 9 further comprising an output device which provides an indication of the operating state of the magnetic coupling device.

11. The magnetic coupling device of claim 5, further comprising at least one of a stationary pin, a retractable pin, and a probe moveable within the channel.

12. The magnetic coupling device of claim 11, wherein the probe supports the at least one sensor.

13. The magnetic coupling device of claim 1, further comprising an actuator operatively coupled to the second permanent magnet to move the second permanent magnet relative to the first permanent magnet.

14. The magnetic coupling device of claim 13, wherein the actuator is one of a user input having an operator actuatable portion, an electric motor, at least one conductive coil, a hydraulic system, and a pneumatic system.

15. The magnetic coupling device of claim 13, wherein the actuator is a user input having an operator actuatable portion which is moveable between a first position corresponding to the second permanent magnet being in a first orientation relative to the first permanent magnet and a second position corresponding to the second permanent magnet being in a second orientation relative to the first permanent magnet and further comprising a lock to hold the second permanent magnet in at least one of the first orientation and the second orientation.

16. A magnetic coupling device for magnetically coupling to a ferromagnetic workpiece, comprising: a housing; a switchable magnetic flux source supported by the housing including a plurality of permanent magnets, the plurality of permanent magnets including a first permanent magnet and a second permanent magnet movable relative to the first permanent magnet about a first axis of rotation; a plurality of workpiece engagement surfaces supported by the housing and magnetically coupled to the switchable magnetic flux source, the plurality of workpiece engagement surfaces adapted to contact the ferromagnetic workpiece, a first workpiece engagement surface of the plurality of workpiece engagement surfaces corresponding to a north pole of the

magnetic coupling device and a second workpiece engagement surface of the plurality of workpiece engagement surfaces corresponding to a south pole of the magnetic coupling device; and at least one sensor positioned in a channel between the first workpiece engagement surface and the second workpiece engagement surface and between a lower surface of the first permanent magnet and the upper surface of the second permanent magnet.

17. A magnetic coupling device for magnetically coupling to a ferromagnetic workpiece, comprising: a housing; a switchable magnetic flux source supported by the housing including a plurality of permanent magnets, the plurality of permanent magnets including a first permanent magnet and a second permanent magnet movable relative to the first permanent magnet about a first axis of rotation; a plurality of workpiece engagement surfaces supported by the housing and magnetically coupled to the switchable magnetic flux source, the plurality of workpiece engagement surfaces adapted to contact the ferromagnetic workpiece, a first workpiece engagement surface of the plurality of workpiece engagement surfaces corresponding to a north pole of the magnetic coupling device and a second workpiece engagement surface of the plurality of workpiece engagement surfaces corresponding to a south pole of the magnetic coupling device; and at least one tool positioned in a channel between the first workpiece engagement surface and the second workpiece engagement surface and between a lower surface of the first permanent magnet and the upper surface of the second permanent magnet.

18. A magnetic coupling device for magnetically coupling to a ferromagnetic workpiece, comprising: a housing; a switchable magnetic flux source supported by the housing including a plurality of magnets and a plurality of ferromagnetic inserts, the plurality of magnets including a first permanent ring magnet having a first outer circumferential surface and a first inner circumferential surface and a second permanent ring magnet having a second outer circumferential surface and a second inner circumferential surface, the plurality of ferromagnetic inserts including a first ferromagnetic insert having a first outer arcuate surface positioned adjacent the first inner circumferential surface of the first permanent ring magnet and a second ferromagnetic insert having a second outer arcuate surface positioned adjacent the second inner circumferential surface of the second permanent magnet, the switchable magnetic flux having a first configuration wherein a north pole of the second permanent ring magnet is aligned relative to a north pole of the first permanent ring magnet and a second configuration wherein a south pole of the second permanent ring magnet is aligned relative to the north pole of the first permanent magnet; and a plurality of workpiece engagement surfaces magnetically coupled to the switchable magnetic flux source, the plurality of workpiece engagement surfaces adapted to contact the ferromagnetic workpiece, a first pole portion including a first workpiece engagement surface of the plurality of workpiece engagement surfaces, and a second pole portion including a second workpiece engagement surface of the plurality of workpiece engagement surfaces.

19. The magnetic coupling device of claim 18, wherein the second permanent ring magnet is moveable relative to the first permanent ring magnet.

20. The magnetic coupling device of claim 19, wherein the second permanent ring magnet is rotatable relative to the first permanent ring magnet about a first axis.

21. The magnetic coupling device of claim 20, wherein the first ferromagnetic insert remains stationary relative to the first permanent ring magnet as the second permanent ring magnet rotates relative to the first permanent ring magnet.

22. The magnetic coupling device of claim 20, wherein the second ferromagnetic insert remains stationary relative to the first permanent ring magnet as the second permanent ring magnet rotates relative to the first permanent ring magnet.

23. The magnetic coupling device of any of claim 18, wherein each of the first outer arcuate surface of the first ferromagnetic insert and the second outer arcuate surface of the second ferromagnetic insert are positioned closer to the first axis than the first permanent ring magnet and the second permanent ring magnet.

24. The magnetic coupling device of any of claim 18, wherein the first outer arcuate surface of the first ferromagnetic insert contacts the first inner circumferential surface of the first permanent ring magnet.

25. The magnetic coupling device of any of claim 18, wherein the first outer arcuate surface of the first ferromagnetic insert contacts the second inner circumferential surface of the second permanent ring magnet.
