

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413565
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Nomani; Muhammad Salman et al.

Systems and methods for group messaging using blockchain-based secure key exchange

Abstract

A system described herein provide for the secure maintaining and providing of information, such as public keys used in Public Key Infrastructure (“PKI”) techniques or other techniques, using a secure distributed ledger (e.g., “blockchain”) system. A first entity may generate an asymmetric key pair that includes a public key and a private key, and may provide the public key, along with a key identifier, to a blockchain system for retrieval by multiple other entities. For example, the entities may be engaged in a secure group communication session, in which communications are encrypted and may be decrypted using one or more keys, including the public key. The other entities may identify the public key, as recorded to the blockchain system, based on the key identifier. Participants may be added to or removed from the secure group communication session.

Inventors: Nomani; Muhammad Salman (Hillsborough, NJ), Stokes; John M. (Yorba Linda, CA)

Applicant: Verizon Patent and Licensing Inc. (Basking Ridge, NJ)

Family ID: 83999168

Assignee: Verizon Patent and Licensing Inc. (Basking Ridge, NJ)

Appl. No.: 17/808330

Filed: June 23, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220368681 A1	Nov. 17, 2022

Related U.S. Application Data

continuation-in-part parent-doc US 17321378 20210514 US 11849032 child-doc US 17808330

Publication Classification

Int. Cl.: H04L9/40 (20220101); H04L9/00 (20220101); H04L9/08 (20060101); H04L9/14 (20060101)

U.S. Cl.:

CPC H04L63/0442 (20130101); H04L9/50 (20220501); H04L63/061 (20130101);

Field of Classification Search

CPC: H04L (63/0442); H04L (9/50); H04L (63/061); H04L (9/006); H04L (9/0861); H04L (9/14); H04L (63/12)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10686594	12/2019	Hamel	N/A	H04L 9/088
10735193	12/2019	Knas	N/A	H04L 9/3239
10999260	12/2020	Silvestri	N/A	H04L 9/0894
11423474	12/2021	Ribeiro	N/A	N/A
2014/0355757	12/2013	Shrivastava	380/46	H04L 9/0822
2019/0245681	12/2018	Alwen	N/A	H04L 9/085
2019/0268312	12/2018	Ma et al.	N/A	N/A
2019/0280855	12/2018	Tong	N/A	H04L 9/0637
2020/0052880	12/2019	Bathen	N/A	H04L 63/102
2020/0145229	12/2019	Li	N/A	H04L 9/3247
2021/0160058	12/2020	Zhang	N/A	H04L 63/12
2021/0176075	12/2020	Chu	N/A	H04L 9/3247
2022/0107994	12/2021	Bernardi	N/A	N/A
2022/0294611	12/2021	Katsumata et al.	N/A	N/A
2023/0021047	12/2022	Ammar et al.	N/A	N/A
2023/0121852	12/2022	Yan	713/153	H04L 9/3268

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
112602289	12/2020	CN	H04L 63/0428

OTHER PUBLICATIONS

“Key escrow”, Wikipedia, Nov. 20, 2020 (available at https://en.wikipedia.org/w/index.php?title=Key_escrow&oldid=989705940, visited Apr. 23, 2021). cited by applicant

Maheshwari, “Learn step-by-step how to set up a basic blockchain network”, Think 2021: The premier hybrid cloud and AI event, Jul. 10, 2020 (available at <https://developer.ibm.com/technologies/blockchain/tutorials/quick-start-guide-for-ibm-blockchain-platform/>, visited May 7, 2021). cited by applicant

Perrin, et al., “The Double Ratchet Algorithm”, Signal, Nov. 20, 2016 (available at <https://signal.org/docs/specifications/doubleratchet/>, visited Apr. 23, 2021). cited by applicant

Primary Examiner: Colin; Carl G

Assistant Examiner: Suh; Andrew

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This Application is a Continuation-in-Part of U.S. patent application Ser. No. 17/321,378 filed on May 14, 2021, titled “SYSTEMS AND METHODS FOR BLOCKCHAIN-BASED SECURE KEY EXCHANGE,” the contents of which are herein incorporated by reference in their entirety.

BACKGROUND

(1) Some encryption techniques, such as Public Key Infrastructure (“PKI”) techniques, may make use of public keys, which may be used to encrypt messages that may be decrypted using an associated private key, and/or may be used in other techniques. Public keys may be distributed or stored by key escrow systems, which may provide a single point of failure and/or an opportunity for a “man-in-the-middle” attack, via which public key may be obtained, modified, and/or otherwise compromised.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 illustrates an example overview of one or more embodiments described herein;
- (2) FIG. 2 illustrates an example of using a shared public key via a private blockchain system, in accordance with some embodiments, in a communication that utilizes double ratchet techniques to secure communications;
- (3) FIG. 3 illustrates an example of establishing a private blockchain system, in accordance with one or more embodiments;
- (4) FIG. 4 illustrates an example of using a shared public key via a private blockchain system, in accordance with some embodiments, in a communication that utilizes double ratchet techniques to secure communications;
- (5) FIGS. 5 and 6 illustrate example processes for using a shared public key via a private blockchain system, in accordance with some embodiments, in a communication that utilizes double ratchet techniques to secure communications;
- (6) FIG. 7 illustrates an example initiation of a group communication session, in accordance with some embodiments;
- (7) FIG. 8 illustrates an example sharing of public keys, along with associated key identifiers, to a blockchain system, in accordance with some embodiments;
- (8) FIG. 9 illustrates an example of obtaining and/or cross-validating public keys associated with

- active participants of a group communication session, in accordance with some embodiments;
- (9) FIG. **10** illustrates an example of outputting an encrypted message package to multiple participants of a group communication session, in accordance with some embodiments;
- (10) FIG. **11** illustrates an example of recipients of an encrypted message package obtaining and/or cross-validating a public key of a sender of the encrypted message from a blockchain system, in accordance with some embodiments;
- (11) FIGS. **12-16** illustrate further examples of blockchain-based secure group communications, in accordance with some embodiments;
- (12) FIGS. **17** and **18** illustrate an example automatic retrieval and/or cross-validation of public keys associated with participants of group communication session from a blockchain system, in accordance with some embodiments;
- (13) FIGS. **19** and **20** illustrate an example of adding a participant to an existing group communication session, in accordance with some embodiments;
- (14) FIG. **21** illustrates an example of removing a participant from a group communication session, in accordance with some embodiments;
- (15) FIG. **22** illustrates an example environment in which one or more embodiments, described herein, may be implemented;
- (16) FIG. **23** illustrates an example arrangement of a radio access network (“RAN”), in accordance with some embodiments; and
- (17) FIG. **24** illustrates example components of one or more devices, in accordance with one or more embodiments described herein.

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS

- (18) The following detailed description refers to the accompanying drawings. The same reference numbers in different drawings may identify the same or similar elements.
- (19) Embodiments described herein provide for the secure maintaining and providing of information, such as public keys used in PKI techniques or other techniques, using a secure distributed ledger (e.g., “blockchain”) system. For example, embodiments described herein may utilize a blockchain system in lieu of a key escrow system in the exchange and/or providing of public keys in a Diffie-Hellman key exchange technique or other type of technique in which public keys are provided from one entity to another. For example, as discussed herein, a first entity may generate an asymmetric key pair that includes a public key and a private key, and may provide the public key to a blockchain system for retrieval by one or more other entities. For example, the entities may be engaged in a secure messaging session, in which messages are encrypted and may be decrypted using one or more keys, including the public key. For example, the messaging session may be associated with multiple key derivation functions, in which a first key or set of keys (e.g., “root” keys) are used in the generation of one or more other keys (e.g., “send” keys and/or “receive” keys). A root key derivation function, for example, may be performed by first and second entities engaged in the communication session to generate respective send and/or receive keys for each entity. The entities may make use of different private keys in their respective root derivation functions, but may utilize one or more shared public keys for their respective root derivation functions. Examples of techniques that make use of multiple key derivation functions, including a root derivation function utilizing one or more shared public keys, include a “double ratchet” encryption technique, a “Signal Protocol,” and/or other types of techniques.
- (20) In some embodiments, the contents of the secured ledger system (e.g., blockchain) may be publicly available or accessible, but the information stored therein may have no meaning or use to an attacker or other malicious user, in the context of obtaining public keys associated with PKI techniques or other techniques. In some embodiments, a private blockchain may be used, in which only authorized entities are able to access the information stored in the private blockchain. Further, as records stored in a blockchain system are immutable, an attacker may be prevented from modifying public keys and thereby potentially having access to information encrypted based on

such keys. For simplicity, embodiments described herein are described in the context of the secured ledger system being a blockchain system. However, similar concepts may apply to another type of secured ledger system other than a blockchain system.

(21) As shown in FIG. 1, a first entity, such as User Equipment (“UE”) **101-1**, may generate (at **102**) a set of keys. The set of keys may be, and/or may include, asymmetric key pair **103**, which may include private key **105** and public key **107**. Private key **105** may be used to decrypt information encrypted by public key **107**, may be used in a double ratchet and/or Signal Protocol technique, and/or may be used for other suitable purposes. UE **101-1** may securely store private key **105**, such as in a local storage device associated with UE **101-1**, in a private key store, in a Universal Integrated Circuit Card (“UICC”), and/or in some other secure location.

(22) As further shown, UE **101-1** may record (at **104**) the public key to a blockchain system, such as private blockchain system **109**. As noted above, private blockchain system **109** may be “private,” in that only authorized entities (e.g., authorized UEs, authorized users, etc.) may have access to the information stored in private blockchain system **109**. The information stored in private blockchain system **109** may be organized as “blocks,” where one particular record corresponds to one particular block, and/or where one block includes multiple records. A block may also include a reference to one or more other blocks (e.g., a “previous” block and/or a “next” block), such that a group of blocks and their associated references may form a “chain” of blocks. Further, private blockchain system **109** may include a set of nodes **111** that form a consensus regarding the blocks of which the blockchain is comprised, thus preventing unauthorized changes to the information stored in the blockchain, as well as resiliency in case any particular node **111** is compromised or otherwise becomes unavailable. In some embodiments, nodes **111** may each be implemented by a respective UE **101**, such as a mobile telephone, a workstation computer, a tablet, an Internet of Things (“IoT”) device, and/or other suitable type of device. While shown in the figure as being “external” to private blockchain system **109**, in practice, UE **101-1** may be, and/or may implement, a particular node **111** associated with private blockchain system **109**.

(23) When recording the public key to private blockchain system **109**, UE **101-1** may provide an identifier associated with UE **101-1** and/or other identifying information based on which the public key may be retrieved by an entity that may use the public key. For example, the record may include an Internet Protocol (“IP”) address associated with UE **101-1**, a device name, a user name, a Session Initiation Protocol (“SIP”) address, and/or some other suitable information associated with UE **101-1**.

(24) Additionally, or alternatively, the record may include a session identifier, which may identify a communication session between UE **101-1** and another UE, such as UE **101-2**. For example, UE **101-1** and UE **101-2** may be engaged in a secure messaging session, in which UE **101-1** and UE **101-2** exchange encrypted messages. The messaging session may be associated with a double ratchet technique, a Signal Protocol technique, and/or other type of technique in which UE **101-1** and UE **101-2** provide public keys to each other.

(25) Briefly, for example, for each message sent between UE **101-1** and UE **101-2**, a new public key may be generated (e.g., in an alternating fashion, where UE **101-1** generates a public key for a first message, UE **101-2** generates a public key for a second message, UE **101-1** generates a public key for a third message, and so on). As described below, these alternating shared public keys may serve as a first “ratchet” in a double ratchet technique to ensure security of the encrypted communications. For example, as discussed below, the public keys may be used to generate symmetric send and/or receive keys, which may be used to encrypt and/or decrypt communications between UE **101-1** and UE **101-2** without transmitting the send and/or receive keys between each other.

(26) Private blockchain system **109** is illustrated as including four nodes **111-1**, **111-2**, **111-3**, and **111-4**. In practice, private blockchain system **109** may include fewer nodes and/or additional nodes. Private blockchain system **109** may, in some embodiments, be associated with one or more suitable

authentication mechanisms whereby only authorized devices or systems are able to participate as nodes **111** of private blockchain system **109**. For example, as discussed herein, particular users or UEs **101** may be specified or automatically identified (e.g., based on an address book or contact list associated with a particular UE **101** that is authorized to access private blockchain system **109** and/or some other suitable technique). As such, unauthorized devices, such as UE **101-N**, may not be able to access information stored in private blockchain system **109** and/or may not be able to participate as a node **111** of private blockchain system **109**. Further, as the nodes **111** of private blockchain system **109** may only include trusted devices, the integrity of the information stored by private blockchain system **109** may be enhanced, as the likelihood of a compromise or attack of private blockchain system **109** may be reduced or eliminated. Further, the recording and/or accessing of private blockchain system **109** may be private with respect to external devices that do not have access to private blockchain system **109**.

(27) In some embodiments, separate private blockchain systems **109** may be established for discrete groups, such as messaging or conversation groups (e.g., where a first communication session includes a first set of participants and is associated with a first private blockchain system **109**, and where a second communication session includes a second set of participants and is associated with a second private blockchain system **109**). In some embodiments, a single private blockchain system **109** may be associated with multiple communication sessions, where keys associated with a given communication session may be protected by a set of smart contracts or other security mechanisms that are accessible only to participants in the communication session.

(28) Once recorded to private blockchain system **109**, public key **107** may be obtained (at **106**) by UE **101-2** and/or another device or system to which the information stored in private blockchain system **109** is available. For example, as noted above, UE **101-2** may be a UE with which UE **101-1** is engaged in a communication session via which UE **101-1** and UE **101-2** exchange encrypted communications. UE **101-2** may identify a record stored in private blockchain system **109** that includes the identifier associated with UE **101-1**, a communication session associated with UE **101-1** and UE **101-2**, and/or some other suitable identifier. In some embodiments, UE **101-2** may be a node **111** of private blockchain system **109**, and may maintain a full copy of the blockchain stored by private blockchain system **109**. In some embodiments, private blockchain system **109** may implement or be communicatively coupled to a search system, which may provide records that match a query. For example, UE **101-2** may query private blockchain system **109** for the identifier associated with UE **101-1** and/or a communication session with UE **101-1**, and private blockchain system **109** may return one or more blocks that include the identifier associated with UE **101-1** and/or the communication session. In some embodiments, private blockchain system **109** may return, and/or UE **101-2** may otherwise identify, the latest (e.g., most current) block matching the query. In this manner, in situations where UE **101-1** has provided multiple public keys to private blockchain system **109** over time, UE **101-2** may be able to retrieve and/or otherwise identify the newest public key. Identifying the newest public key may be useful in a double ratchet technique, a Signal Protocol technique, and/or some other technique in which an updated public key is used for each message between UE **101-1** and UE **101-2**. In some embodiments, public keys may be provided with sequence numbers or other information, based on which public keys associated with communications received in a non-sequential manner (e.g., out of order) may be identified.

(29) In some embodiments, the public key may be provided as part of a Diffie-Hellman exchange or some other suitable technique in which public keys associated with multiple UEs **101** are exchanged amongst each other. UE **101-2** may accordingly maintain and/or use (at **108**) the received public key for a double ratchet technique, a Signal Protocol technique, and/or in some other technique that involves a Diffie-Hellman key exchange or other type of key exchange procedure.

(30) FIG. 2 illustrates an example of using a shared public key (e.g., shared via private blockchain system **109**, in accordance with some embodiments) in a communication technique that utilizes

double ratchet techniques to secure communications between UE **101-1** and UE **101-2**. As shown, UE **101-1** and UE **101-2** may each include a respective messaging client **201**, which may send and/or receive encrypted communications. For example, messaging client **201-1**, associated with UE **101-1**, may encrypt communications based on techniques described herein, and may send the encrypted communications to messaging client **201-2** associated with UE **101-2**. Messaging client **201-2** may receive encrypted communications from UE **101-1** (e.g., from messaging client **201-1**), may decrypt the communications based on techniques described herein, and may present the decrypted communications (e.g., via a graphical user interface (“GUI”) or other suitable manner of presentation). Similarly, messaging client **201-2**, associated with UE **101-2**, may encrypt communications based on techniques described herein, and may send the encrypted communications to messaging client **201-1** associated with UE **101-1**. Messaging client **201-1** may receive encrypted communications from UE **101-2** (e.g., from messaging client **201-2**), may decrypt the communications based on techniques described herein, and may present the decrypted communications (e.g., via a GUI or other suitable manner of presentation).

(31) The encryption and/or decryption by messaging client **201-1** and/or messaging client **201-2** may be performed using a symmetric key that is generated based on a double ratchet technique, a Signal Protocol technique, and/or other suitable technique. For example, as discussed herein, the symmetric key may be used by a sender (e.g., UE **101-1**, in this example) to encrypt a communication, and may be used by a recipient (e.g., UE **101-2**, in this example) to decrypt the communication. The symmetric keys may be generated by respective Send Key Derivation Function (“KDF”) **205** and/or Receive KDF **207** associated with the sender and/or recipient. The symmetric keys may be generated based on one or more root keys provided by Root KDF **203** to Send KDF **205** and/or Receive KDF **207**. For example, Root KDF **203-1** may provide a root key output based on a public key and a private key to Send KDF **205-1**, which may generate a send key (e.g., based on the root key output and one or more private keys) which may be used to encrypt communications to be sent by messaging client **201-1**. The private key based on which the root key output is generated may be privately maintained by UE **101-1** (e.g., not sent to UE **101-2**), while the public key may be shared with UE **101-2** via private blockchain system **109**, in accordance with embodiments described herein. Root KDF **203-1** may provide a different root key output for each message sent and/or received by messaging client **201-1**, based on a public key exchange (e.g., via a Diffie-Hellman key exchange or other suitable procedure) with UE **101-2**, which may be performed each time a message is sent by UE **101-1** and/or UE **101-2**.

(32) For example, when UE **101-1** sends a message, Root KDF **203-1** may generate a root key output, and may further output a public key based on which the root key output was generated, to private blockchain system **109**. As discussed above, the public key may be provided with a session identifier (e.g., to identify a communication session between messaging client **201-1** and messaging client **201-2**), an identifier associated with UE **101-1**, an identifier associated with UE **101-2**, and/or other suitable information based on which UE **101-2** may identify that the public key recorded to private blockchain system **109** is associated with the communication session between UE **101-1** and UE **101-2**.

(33) UE **101-2** (e.g., Root KDF **203-2**) may obtain the root public key from private blockchain system **109** based on the session identifier or other suitable identifier, and may generate a root key output based on the obtained public key and a private key (e.g., a different private key than the private key used by Root KDF **203-1** to encrypt the communication). As noted above, using private blockchain system **109** to exchange public keys may maintain the integrity of the keys, such as by preventing malicious actors from modifying or “spoofing” keys. Further, using private blockchain system **109** may aid in situations where a given UE **101** (e.g., UE **101-2**, in this example) is “offline” or is otherwise unavailable to receive public keys from another UE **101** (e.g., UE **101-1**, in this example) at the time that the other UE **101** outputs the public keys.

(34) Root KDF **203-2** may provide the root key output to Receive KDF **207-2**, which may generate

a receive key based on the root key output and one or more private keys. In accordance with the double ratchet techniques, Signal Protocol techniques, etc., the receive key generated by Receive KDF **207-2** may be the same as the send key output generated by Send KDF **205-1**. In this manner, these respective send and receive keys may be an identical symmetric key that may be used to encrypt and decrypt communications, such as the encrypted communication sent by messaging client **201-1** to messaging client **201-2** in this example.

(35) While an example is provided here in the context of UE **101-1** encrypting a communication, sending the encrypted communication to UE **101-2**, and UE **101-2** decrypting the communication, similar techniques may be performed (e.g., iteratively) for communications encrypted and sent by UE **101-2** to UE **101-1**, as denoted by the dashed lines in FIG. 2. For example, Root KDF **203-2** may generate a root key pair, output a public key of the root key pair to private blockchain system **109** for retrieval by UE **101-1**, generate a root key output based on the root key pair, and provide the root key output to Send KDF **205-2**. Send KDF **205-2** may generate a send key based on the root key output and one or more private keys, and messaging client **201-2** may encrypt a communication based on the send key. Further, Root KDF **203-1** may retrieve the public key from private blockchain system **109**, generate a root key output based on the retrieved public key and one or more private keys, and provide the root key output to Receive KDF **207-1**. Receive KDF **207-1** may generate a receive key based on the root key output and one or more private keys, and messaging client **201-1** may decrypt a communication received from messaging client **201-2**, as encrypted based on a matching send key.

(36) As noted above, private blockchain system **109** may be a “private” blockchain, in that only approved UEs **101** (or other suitable devices or systems) may participate in private blockchain system **109** as nodes **111** of private blockchain system **109**. In some embodiments, eligible participants may be identified based on an automated determination of contacts associated with one or more participant nodes **111** of private blockchain system **109**, and/or some other suitable technique. For example, as shown in FIG. 3, UE **101-1** may establish (at **301**) and/or join private blockchain system **109**. For example, UE **101-1** may establish a new private blockchain system **109** by generating a “genesis” block, and/or may join an existing private blockchain system **109**. In some embodiments, UE **101-1** may communicate with one or more devices or systems that facilitate the establishment of private blockchain system **109**.

(37) UE **101-1** may further automatically identify (at **303**) candidate participants (e.g., nodes **111** for private blockchain system **109**, devices or systems that are authorized to access information stored in private blockchain system **109**, or the like). For example, UE **101-1** may identify contacts in an address book, call history, and/or other type of contact list associated with UE **101-1**. Additionally, or alternatively, UE **101-1** and/or some other device or system may utilize artificial intelligence/machine learning (“AI/ML”) techniques or other suitable techniques to identify UEs **101** with which UE **101-1** has communicated.

(38) UE **101-1** may output (at **305**) an invitation to join (e.g., as a node **111** and/or as an authorized viewer of information stored in private blockchain system **109**) to identified UEs **101-2**, **101-3**, and **101-4**. In some embodiments, UE **101-1** (e.g., an application or application programming interface (“API”) associated with UE **101-1**) may communicate with contacts in a contact list associated with UE **101-1** (e.g., where the contacts include UEs **101-2**, **101-3**, and **101-4** in this example) via one or more suitable messaging or other types of communication applications, and may identify particular ones of the contacts participate in a key escrow or other type of key exchange. UE **101-1** may output an invitation to private blockchain system **109** to the identified contacts via the messaging or other communication applications and/or some other suitable communication pathway. In some embodiments, the invitation may include identifying information associated with UE **101-1**, such as an IP address associated with UE **101-1**, a Mobile Directory Number (“MDN”) associated with UE **101-1**, an International Mobile Station Equipment Identity (“IMEI”) associated with UE **101-1**, an International Mobile Subscriber Identity (“IMSI”) associated with UE **101-1**,

and/or some other suitable identifier.

(39) UEs **101-2**, **101-3**, and **101-4** may accordingly join (at **307**, **309**, and **311**, respectively) private blockchain system **109**. For example, such UEs **101-2**, **101-3**, and **101-4** may register as nodes **111** using information provided (at **305**) by UE **101-1**, and/or may access information stored in private blockchain system **109** using such information. In this manner, private blockchain system **109** may be “private” inasmuch as UEs **101** which were not invited (at **305**) to private blockchain system **109** may not access the information stored in private blockchain system **109**.

(40) FIG. 4 illustrates an example of the use of private blockchain system **109** to exchange public keys in the encryption and/or decryption of secure communications between UEs **101** participating in a secure communication session. In this example, UEs **101-1**, **101-2**, **101-3**, and **101-4** may be nodes **111** of private blockchain system **109**. Further, UEs **101-1** and **101-3** may be participants in a communication session (e.g., via respective messaging clients **201** associated with UEs **101-1** and **101-3**). For example, UE **101-1** and UE **101-3** may establish (at **401**) a secure communication session using any suitable session establishment technique or protocol. The communication session may be associated with a session identifier or other suitable mechanism by which UEs **101-1** and/or **101-3** may identify the communication session. For example, an initiator of the communication session may generate or otherwise determine an identifier for the communication session, and/or UEs **101-1** and **101-3** may otherwise negotiate or determine an identifier for the communication session.

(41) UE **101-1** may further generate (at **403**) an asymmetric key pair, which may be used as part of a double ratchet technique, a Signal Protocol technique, and/or some other encryption technique used to secure communications between UEs **101-1** and **101-3**. For example, the asymmetric key pair generated (at **403**) by UE **101-1** may include a public key used in the generation of a send key used to encrypt communications sent to UE **101-3**. While not explicitly shown in FIG. 4, UE **101-3** may also generate one or more keys that may be used in the encryption and/or decryption of messages between UEs **101-1** and **101-3**, in accordance with the double ratchet technique, Signal Protocol technique, and/or other suitable encryption technique.

(42) UE **101-1** may further provide (at **405**) the public key of the generated asymmetric key pair to private blockchain system **109**. As noted above, UEs **101-1**, **101-2**, **101-3**, and **101-4** may be nodes **111** of private blockchain system **109**. In other examples, UE **101-3** (e.g., a participant in the secure communication session) may not be a node **111** of private blockchain system **109**, and thus UE **101-1** may not directly provide (at **405**) the public key to UE **101-3**. When providing (at **405**) the public key to private blockchain system **109**, UE **101-1** may include the session identifier of the communication session between UEs **101-1** and **101-3**, and/or some other suitable identifier based on which UE **101-3** may identify (at **407**) the public key provided by UE **101-1**.

(43) For example, as discussed above, UE **101-3** may retrieve (at **407**) the public key from private blockchain system **109** based on identifying a record in private blockchain system **109** that includes the session identifier or other suitable identifier associated with UEs **101-1** and/or **101-3**. In situations where multiple blocks exist with the session identifier, UE **101-3** may identify a latest (e.g., newest) block. For example, in accordance with the double ratchet and/or Signal Protocol techniques, a new public key may be provided each time a message is sent and/or received by UE **101-1** and/or UE **101-3**. As such, identifying a latest public key associated with the communication session between UEs **101-1** and **101-3** may facilitate the secure communications according to the double ratchet and/or Signal Protocol techniques.

(44) UE **101-1** may further encrypt (at **409**) a message for UE **101-3** using a symmetric key (e.g., a send key, as similarly discussed above) that UE **101-1** generates based on the public key, one or more private keys, and/or one or more KDFs (e.g., Send KDF **205**). UE **101-1** may proceed to output (at **411**) the encrypted message to UE **101-3**. UE **101-3** may decrypt (at **413**) the message using a symmetric key (e.g., the same symmetric key as UE **101-1** used to encrypt (at **409**) the message), which may be generated by one or more KDFs (e.g., Receive KDF **207**) based on the

retrieved (at **407**) public key.

(45) While FIG. 4 shows an example of one message being sent from UE **101-1** to UE **101-3**, similar techniques may be employed when UE **101-1** sends additional messages to UE **101-3**, and/or when UE **101-3** sends messages to UE **101-1**. For example, UE **101-3** may generate a subsequent asymmetric key pair that is derived from and/or is otherwise based on the retrieved (at **407**) public key, and may output a public key of the subsequent asymmetric key pair to private blockchain system **109**. UE **101-3** may utilize this subsequently generated public key to generate a send key, and UE **101-1** may utilize this subsequently generated public key, retrieved from private blockchain system **109**, to generate a receive key, as described above.

(46) FIGS. 5 and 6 illustrate example processes **500** and **600**, respectively, for utilizing blockchain techniques to share and/or exchange public keys. In the examples provided herein, the key exchange may be part of a Diffie-Hellman key exchange, a key exchange portion of a Signal Protocol technique, a key exchange portion of a double ratchet technique, and/or some other suitable secure exchange of public keys. In some embodiments, some or all of process **500** and/or **600** may be performed by one or more UEs **101** (e.g., UEs **101** engaged in a communication session with each other and/or one or more other UEs **101**). In some embodiments, one or more other devices may perform some or all of processes **500** and/or **600** in concert with, and/or in lieu of, UE **101**.

(47) As shown, process **500** may include establishing (at **502**) a communication session with one or more UEs **101**. The communication session may be associated with a session identifier or other identifier based on which participant UEs **101** of the communication session may identify messages exchanged with one another and/or public keys, associated with the communication session, recorded to private blockchain system **109** in accordance with embodiments described herein.

(48) Process **500** may further include generating (at **504**) a set of root keys, which may include an asymmetric key pair. For example, as discussed above, the root keys may include a private key which may be maintained securely by UE **101**, and a public key which may ultimately be shared with one or more other UEs **101** (e.g., another participant in the communication session).

(49) Process **500** may additionally include recording (at **506**) the public root key (e.g., the public key of the asymmetric key pair generated at **504**) to private blockchain system **109**. For example, UE **101** may output the public key to private blockchain system **109**, and private blockchain system **109** may propagate the information to one or more nodes **111** of private blockchain system **109**. Nodes **111** may form a consensus regarding the addition of the provided public key to one or more records of private blockchain system **109**, and may maintain an immutable record of the provided public key. In some embodiments, the record may include a timestamp, a block identifier, and/or other mechanism by which a recency or age of the record may be determined. As similarly described above, the record may further include a communication session identifier, an identifier of UE **101** from which the information was received, and/or other suitable information.

(50) Process **500** may also include utilizing (at **508**) the root keys to generate a send key. For example, as discussed above, Root KDF **203** may utilize the root keys (e.g., including the root public key, as well as the root private key and/or one or more other keys) to generate a root key output, and may provide the root key output to another KDF, such as Send KDF **205**. Send KDF **205** may generate a send key based on the root key output from Root KDF **203** and/or based on one or more other keys or functions. As discussed above, the generated send key may be a symmetric key that may be identical to a receive key generated by a recipient of the public key, based on a Signal Protocol technique, a double ratchet technique, etc.

(51) Process **500** may further include encrypting (at **510**) a communication using the send key. Process **500** may additionally include outputting (at **512**) the encrypted communication via the communication session, such as to a UE **101** with which the communication session was established (at **502**).

(52) As shown in FIG. 6, process **600** may include establishing (at **602**) a communication session.

For example, as similarly discussed above, UE **101** may establish a communication session with one or more other UEs **101**. The communication session may be associated with a suitable identifier, based on which the UEs **101** participating in the communication session may identify communications associated with the communication session, including encrypted messages, public keys, and/or other information.

(53) Process **600** may further include receiving (at **604**) an encrypted communication via the communication session. For example, the communication may have been encrypted using one or more KDFs, where the input to the one or more KDFs include the public root key and one or more other keys (e.g., one or more private keys, one or more KDF outputs, etc.).

(54) Process **600** may further include retrieving (at **606**) a public root key from private blockchain system **109**. In some embodiments, private blockchain system **109** and/or one or more devices or systems communicatively coupled to private blockchain system **109** may “push” the public root key to private blockchain system **109**. For example, the one or more devices or systems may identify a particular block that includes an identifier of UE **101** (e.g., where the particular block includes the identifier of UE **101** and a public root key), may identify a particular block that includes an identifier of the communication session (e.g., where the particular block includes the identifier of the communication session and a public root key), etc. Additionally, or alternatively, UE **101** may “pull” the information from private blockchain system **109** based on a suitable identifier (e.g., an identifier of UE **101**, an identifier of the communication session, etc.).

(55) Process **600** may additionally include utilizing (at **608**) the public root key to generate a receive key. For example, as discussed above, UE **101** may utilize one or more KDFs, such as Root KDF **203** and/or Receive KDF **207**, to generate a receive key. The receive key may be a symmetric key with respect to a key used to encrypt a communication received by UE **101** via the communication session. For example, as discussed above, the receive key may be identical to a send key used by a sender of the communication, where the send key was also generated based on one or more KDFs and at least the public root key. For example, the sender and UE **101** may perform double ratchet techniques, Signal Protocol techniques, or the like, to respectively encrypt and decrypt the communication, without transmitting or sharing the symmetric key itself.

(56) Process **600** may further include decrypting (at **610**) the communication, received via the communication session, using the generated receive key. For example, UE **101** may apply one or more functions to decrypt the receive message using the receive key, which, as discussed above, may be the same as a send key used to encrypt the communication.

(57) Process **600** may additionally include generating (at **612**) a new set of root keys based on the previously retrieved public root key and one or more other root keys. For example, once UE **101** generates the receive key, the public root key (retrieved at **606**) may be discarded and/or not used for sending messages from UE **101**. In some situations, UE **101** may maintain the public root key and apply techniques described above to decrypt subsequent communications from the sender in situations where the sender sends multiple communications in a row without any intervening messages from UE **101**. The new set of root keys may be generated based on the receive key (generated at **608**), the public root key (retrieved at **606**), and/or one or more other suitable keys. UE **101** may then proceed to output the newly generated public root key to private blockchain system **109**, as similarly described above with respect to operation **506** of process **500**, may generate (e.g., similar to operation **508**) a new send key based on the newly generated public root key, etc.

(58) Embodiments described above are presented in the context of communication sessions between two UEs **101**. Embodiments described herein may further provide for secure blockchain-based key exchange mechanisms for group communication sessions that include more than two participants (e.g., between three or more UEs **101**). For example, techniques described below provide for a blockchain-based key exchange such that group messages may be encrypted such that only participants in the group are able to access (e.g., decrypt) the messages. Further, as discussed

below, situations may arise in which a participant in a communication session receives an encrypted message from another participant, but does not possess one or more keys needed to decrypt the message (e.g., a public key associated with the sender), and/or has not received confirmation from the blockchain that the participant is in possession of such keys. Techniques described below provide for the recipient to securely obtain the one or more keys from blockchain system **109** in order to decrypt the message. Further, embodiments described below provide for the adding and removing of participants from a secure group communication session.

(59) FIG. 7 illustrates an example establishment of a group communication session that uses blockchain-based secure key exchange techniques. In this example, assume that the group communication session is between UEs **101-1**, **101-2**, and **101-3** (also referred to as “Participant_A,” “Participant_B,” and “Participant_C”). As shown, UE **101-1** may initiate (at **702**) a group communication session (also referred to as a “group chat”), such as by sending (at **702**) one or more messages to UEs **101-2** and **101-3**. For example, a messaging application (e.g., a particular messaging client **201**) of UE **101-1** may communicate with the same or a different messaging application (e.g., respective messaging clients **201**) of UEs **101-2** and **101-3**. The message(s) sent (at **702**) by UE **101-1** may include one or more Rich Communication Suite (“RCS”) messages or messages of another type or protocol. In some embodiments, the message(s) may include a session identifier associated with the group communication session, may include identifiers associated with UEs **101-1**, **101-2**, and/or **101-3** (e.g., IP addresses, SIP addresses, MDNs, etc.), and/or one or more other suitable identifiers. In some embodiments, the message(s) may include one or more instructions, indications, requests, etc. to implement blockchain-based key exchange for the communication session. In this example, assume that UEs **101-1**, **101-2**, and **101-3** support and/or have accepted the instruction, request, etc. to utilize blockchain-based key exchange.

(60) UEs **101-1**, **101-2**, and **101-3** may further select (at **704**) passive participants, or nodes **111**, for blockchain system **109** to securely maintain keys associated with the group communication session. For example, as similarly discussed above, UEs **101-1**, **101-2**, and **101-3** may automatically select contacts from respective address books, contacts lists, etc. In this example, UE **101-1** may select UE **101-4** as a node **111** for blockchain system **109**, UE **101-2** may select UE **101-5** as a node **111** for blockchain system **109**, and UE **101-3** may select UE **101-6** as a node **111** for blockchain system **109**.

(61) UEs **101-2** and **101-3** may indicate (at **706**) their respective selections of nodes **111** to UE **101-1**. For example, UE **101-2** may provide an identifier (e.g., MDN, IP address, etc.) of UE **101-5**, and UE **101-3** may provide an identifier of UE **101-6**. In some embodiments, UE **101-1** may have also provided (at **702**) a public key to UEs **101-2** and **101-3**. In such embodiments, UEs **101-2** and **101-3** may each encrypt the messages sent (at **706**) to UE **101-1**, including the identifiers of UEs **101-5** and **101-6**.

(62) UE **101-1** may generate (at **708**) a full list of blockchain participants, including active participant UEs **101-1**, **101-2**, and **101-3**, as well as passive participant UEs **101-4**, **101-5**, and **101-6**. UE **101-1** may provide (at **710**) the full list of blockchain participants to UEs **101-2** and **101-3**, thus providing for UEs **101-2** and **101-3** to be aware of, and therefore able to communicate with, blockchain system **109** once established. In some embodiments, UE **101-1** may encrypt the message (sent at **710**) with a private key, which may be associated with the public key provided at **702**. For example, the public and private keys may be associated with the same asymmetric key pair. UEs **101-2** and **101-3** may be able to use the public key (received at **702**) of UE **101-1** to decrypt the provided list of blockchain participants. UE **101-1** may proceed to establish (at **712**) blockchain system **109**, which may include generating a genesis block, providing the genesis block to nodes **111** of blockchain system **109** (e.g., UEs **101-2** through **101-6**), and/or other operations to establish blockchain system **109**. In some embodiments, the genesis block or other data included in or associated with blockchain system **109** may include or may be based on the session identifier associated with the group communication session. In this manner, different blockchain systems **109**

may be associated with different communication sessions and may have different session identifiers.

(63) As shown in FIGS. 8-18, UEs **101-1**, **101-2**, and **101-3** may utilize blockchain-based key exchange techniques to securely communicate via the established group communication session. As shown in FIG. 8, UE **101-1** may generate asymmetric key pair **103-1**, including private key **105-1** and public key **107-1**. In embodiments where UE **101-1** generated a key pair and provided a public key (e.g., at **702**) to UEs **101-1** and **101-2**, asymmetric key pair **103-1** (shown in FIG. 8) may be a different key pair. UE **101-1** may further record public key **107-1** to blockchain system **109**. Similarly, UE **101-2** may generate asymmetric key pair **103-2** (which may include private key **105-2** and public key **107-2**) and may record public key **107-2** to blockchain system **109**. Additionally, UE **101-3** may generate asymmetric key pair **103-3** (which may include private key **105-3** and public key **107-3**) and may record public key **107-3** to blockchain system **109**.

(64) In some embodiments, when recording keys (e.g., public keys **107**) to blockchain system **109**, respective UEs **101** may provide a key identifier. For example, UE **101-1** may provide key identifier **801-1** with public key **107-1**, UE **101-2** may provide key identifier **801-2** with public key **107-2**, and UE **101-3** may provide key identifier **801-3** with public key **107-3**. In some embodiments, key identifiers **801** may be unique to each respective public key **107**, such that particular public keys **107** may be retrieved from blockchain system **109** based on associated key identifiers **801**. For example, in situations where a double ratchet encryption technique and/or other type of protocol in which keys are iteratively generated and used to encrypt messages associated with the group communication session, up-to-date public keys **107** may be retrieved from blockchain system **109** based on respective key identifiers **801**, as discussed below.

(65) In some embodiments, key identifiers **801** may include, and/or may be based on, identifiers of respective UEs **101** with which public keys **107** are associated. For example, key identifier **801-1** may include, may be derived from, and/or may otherwise be based on an identifier (e.g., MDN, IP address, etc.) associated with UE **101-1**. Additionally, or alternatively, key identifier **801-1** may include, may be derived from, and/or may otherwise be based on a session identifier associated with the group communication session between UEs **101-1**, **101-2**, and **101-3**. In some embodiments, key identifier **801-1** may be independent of, and/or may not be based on, a respective UE identifier and/or session identifier. In some embodiments, public keys **107** may be provided to blockchain system **109** with an indication of a respective UE identifier and/or session identifier (e.g., independent of key identifier **801**).

(66) As shown in FIG. 9, UE **101-1** may generate message **901**, which may be associated with the group communication session between UEs **101-1**, **101-2**, and **101-3**. For example, a user of UE **101-1** may have provided input such as text, audio, an image, etc. to be sent to UEs **101-2** and **101-3** associated with the group communication session. Such input may be provided, for example, via a suitable messaging application executing at UE **101-1**. Based on receiving the input specifying outgoing message **901**, UE **101-1** may determine that UE **101-1** does not have possession of public keys associated with the other active participants of the group communication session, namely public keys **107-2** and **107-3** associated with UEs **101-2** and **101-3**. Additionally, or alternatively, UE **101-1** may determine that UE **101-1** is in possession of public keys **107-2** and **107-3** (e.g., may have received such public keys **107** by virtue of being a node **111** of blockchain system **109**, as discussed above with respect to FIG. 8), but may determine that such public keys **107** have not been confirmed by blockchain system **109**.

(67) Accordingly, as shown, UE **101-1** may obtain public keys **107-2** and **107-3** from blockchain system **109**. As discussed above, for example, public keys **107-2** and **107-3** may have previously been recorded to blockchain system **109** by UEs **101-2** and **101-3**. In some embodiments, UE **101-1** may identify public keys **107-2** and **107-3** by identifying a session identifier recorded with keys **107-2** and **107-3** and/or UE identifiers of UE **101-2** and **101-3** recorded with public keys **107-2** and **107-3**, as discussed above. In some embodiments, UE **101-1** may identify public keys **107-2** and

107-3 based on key identifiers **801-2** and **801-3** associated with public keys **107-2** and **107-3**. For example, based on detecting that UE **101-1** does not have possession of such keys, and/or based on detecting that UE **101-1** has received input specifying outgoing message **901**, UE **101-1** may output requests to UEs **101-2** and **101-3** for key identifiers **801-2** and **801-3** associated with public keys **107-2** and **107-3** of UEs **101-2** and **101-3**. In such embodiments, UEs **101-2** and **101-3** may provide key identifiers **801-2** and **801-3**, based on which UE **101-1** may search blockchain system **109** and/or otherwise identify corresponding public keys **107-2** and **107-3**.

(68) In some embodiments, when obtaining keys (e.g., public keys **107-2** and **107-3**, in this example) from blockchain system **109**, a particular UE **101** obtaining such keys (e.g., UE **101-1**, in this example) may perform one or more cross-validation techniques in order to verify that the keys are accurate and/or have not been compromised in some way (e.g., a “man-in-the-middle” attack or some other type of malicious action). For example, in this example, UE **101-1** may compute a hash of one or more blocks of blockchain system **109** from which public keys **107-2** and/or **107-3** were obtained, and/or may otherwise identify or generate information based on information recorded to blockchain system **109** that corresponds to public keys **107-2** and **107-3**.

(69) UE **101-1** may further communicate with one or more other nodes **111** of blockchain system **109** (e.g., UEs **101-2**, **101-3**, **101-4**, **101-5**, and/or **101-6**) in order to verify the information (e.g., the hash of the one or more blocks from which public keys **107-2** and/or **107-3** were obtained). When quorum is reached (e.g., UE **101-1** has received at least a threshold quantity of confirmations from other nodes **111**) with respect to the hash or other suitable information, UE **101-1** may identify that the obtained public keys **107-2** and **107-3** are valid, accurate, etc., thus enhancing the security of the group communication session. Similar concepts may apply in situations where UE **101-1** already has possession of public keys **107-2** and **107-3** (e.g., in situations where UE **101-1** is a node **111** of blockchain system **109** and has therefore received public keys **107-2** and **107-3** when UEs **101-2** and **101-3** provided such public keys **107** to blockchain system **109**). For example, UE **101-1** may identify a local copy of blockchain system **109** and may obtain public keys **107-2** and **107-3** from the local copy of blockchain system **109**, and may perform a cross-validation process (e.g., may communicate with other nodes **111** of blockchain system **109**) to verify that public keys **107-2** and **107-3** from the local copy of blockchain system **109** is accurate, valid, etc.

(70) In other figures that discuss the obtaining of information (e.g., respective public keys **107**) from blockchain system **109**, a given UE **101** obtaining such information may perform similar operations in order to verify the authenticity, accuracy, etc. of the obtained information. Similarly, in other examples that discuss whether a given UE **101** is in possession of particular information (e.g., respective public keys **107**), such examples may also refer to whether the given UE **101** has received confirmations from other nodes **111** (e.g., at least a threshold quantity of nodes **111**, such that a quorum is reached) that such information is valid, even in instances where the given UE **101** already has possession of the information. That is, the given UE **101** may store a copy of one or more public keys **107** (e.g., within a local copy of blockchain system **109**), but may not be considered in “possession” of such public keys **107**, in accordance with some embodiments, if UE **101** has not received confirmation, validation, etc. from at least a threshold quantity of nodes **111** of blockchain system **109** that such copies of public keys **107** are valid, accurate, etc.

(71) As shown in FIG. **10**, after retrieving public keys **107-2** and **107-3** from blockchain system **109** (and/or after receiving confirmation from at least a threshold quantity of nodes **111** of blockchain system **109** that such public keys **107-2** and **107-3** are valid), UE **101-1** may have possession of validated copies of public keys **107-2** and **107-3** (also referred to in the figures as “Public key B” and “Public key C”), as well as its own private key **105-1** (also referred to in the figures as “Private key A”) and public key **107-1**. As further shown, at this point, UEs **101-2** and **101-3** may have possession of their own respective private keys **105** and public keys **107**, but may not yet have possession of private keys **105** or public keys **107** associated with other UEs **101** (and/or may not have confirmation that locally stored copies of private keys **105** or public keys

107, stored by UEs **101-2** and **101-3** in respective local copies of blockchain system **109**, are valid). (72) UE **101-1** may generate encrypted message package **1001** based on message **901**, and send encrypted message package **1001** to UEs **101-2** and **101-3**. As shown, encrypted message package **1001** may include first portion **1003-1** and second portion **1003-2**, as well as key identifier **801-1**, associated with public key **107-1**. Portion **1003-1** may include a first encrypted version of message **901**, while portion **1003-2** may include a second encrypted version of message **901**. The first encrypted version of message **901** (e.g., as included in portion **1003-1**) may, in some embodiments, be encrypted based on private key **105-1** (e.g., Private key A) and public key **107-2** (e.g., Public key B). For example, the first encrypted version of message **901** may be encrypted based on a symmetric key derived from private key **105-1** and public key **107-2**. Similarly, the second encrypted version of message **901** (e.g., as included in portion **1003-2**) may be encrypted based on private key **105-1** and public key **107-3** (e.g., a symmetric key derived from Private key A and Public key C).

(73) In some embodiments, portion **1003-1** may include an identifier of UE **101-2** and/or key identifier **801-2** associated with public key **107-2**, such that UE **101-2** is able to identify that UE **101-2** is the recipient of portion **1003-1** and/or that public key **107-2** has been used in the encryption of message **901** included in portion **1003-1**. Similarly, portion **1003-2** may include an identifier of UE **101-3** and/or key identifier **801-3**, such that UE **101-3** is able to identify that UE **101-3** is the recipient of portion **1003-2**.

(74) As shown in FIG. 11, UEs **101-2** and **101-3** may retrieve public key **107-1** (e.g., Public key A) from blockchain system **109**, based on receiving encrypted message package **1001**. For example, UE **101-2** may identify that portion **1003-1** includes an encrypted message from UE **101-1** associated with the group communication session, and UE **101-3** may identify that portion **1003-2** includes an encrypted message from UE **101-1** associated with the group communication session. For example, as discussed above, encrypted message package **1001** and/or respective portions **1003** may include a session identifier associated with the group communication session, key identifier **801-1**, and/or identifiers of UEs **101-2** and/or **101-3**. As discussed above, retrieving public key **107-1** from blockchain system **109** may further include cross-validating the retrieved public key **107-1** with at least a threshold quantity of nodes **111** of blockchain system **109** (e.g., including some or all of UEs **101-1** through **101-6**).

(75) UEs **101-2** and **101-3** may accordingly use key identifier **801-1**, a session identifier, and/or other suitable information to identify public key **107-1**, as previously recorded to blockchain system **109**. Once UEs **101-2** and **101-3** have obtained public key **107-1**, UE **101-2** may be in possession of public key **107-1** as well as its own private key **105-2** and public key **107-2**, and UE **101-3** may also be in possession of public key **107-1** as well as its own private key **105-3** and public key **107-3**. UEs **101-2** and **101-3** may accordingly decrypt their own respective portions **1003-1** and **1003-2** in order to extract original message **901**. For example, as similarly discussed above, UE **101-2** may derive a symmetric key based on private key **105-2** (e.g., Private key B) and public key **107-1** (e.g., Public key A), and may use the symmetric key to decrypt portion **1003-1** in order to extract message **901**. Similarly, UE **101-3** may derive a symmetric key based on private key **105-3** (e.g., Private key C) and public key **107-1** (e.g., Public key A), and may use the symmetric key to decrypt portion **1003-2** in order to extract message **901**.

(76) As shown in FIG. 12, UE **101-3** may receive input specifying outgoing message **1201**, associated with the same group communication session. Based on operations described above, UE **101-1** may be in possession of keys **105-1**, **107-1**, **107-2**, and **107-3**; UE **101-2** may be in possession of keys **105-2**, **107-1**, and **107-2**; and UE **101-3** may be in possession of keys **105-3**, **107-1**, and **107-3**. Based on receiving the input specifying message **1201**, UE **101-3** may identify that UE **101-3** is not in possession of a public key associated with UE **101-2**. Accordingly, as similarly discussed above, UE **101-3** may obtain public key **107-2**, associated with UE **101-2**, from blockchain system **109**. For example, UE **101-3** may identify public key **107-2**, as recorded to

blockchain system **109**, based on a session identifier recorded with public key **107-2** and/or a UE identifier of UE **101-2** recorded with public key **107-2**. Additionally, or alternatively, as discussed above, UE **101-3** may communicate with UE **101-2** in order to obtain a respective key identifier **801-2** associated with public key **107-2**, and may obtain public key **107-2** from blockchain system **109** based on key identifier **801-2**.

(77) In some embodiments, UE **101-3** may attempt to obtain a respective public key **107** associated with each group participant based on receiving the input specifying message **1201**. That is, in some embodiments, each time a respective UE **101** receives input specifying an outgoing message, such UE **101** may attempt to obtain public keys **107** associated with other group participants, in implementations where new public keys **107** (e.g., associated with new key pairs **103**) are generated by UEs **101**. For example, as discussed above, such implementations may include a double ratchet technique, in which updated key pairs **103** are generated for different outgoing messages. In the examples shown in the figures, it is assumed that the same respective key pairs **103** are used by UEs **101**, for the sake of simplicity.

(78) As shown in FIG. **13**, UE **101-3** may output encrypted message package **1301** to UEs **101-1** and **101-2**. Encrypted message package **1301** may include, for example, encrypted portions **1303-1** and **1303-2**, where portion **1303-1** includes a first encrypted version of message **1201** and portion **1303-2** includes a second encrypted version of message **1201**. For example, the first encrypted version of message **1201** may be encrypted based on a symmetric key associated with UEs **101-1** and **101-3** (e.g., Public key A and Private key C), and the second encrypted version of message **1201** may be encrypted based on a symmetric key associated with UEs **101-2** and **101-3** (e.g., Public key B and Private key C).

(79) As shown in FIG. **14**, based on receiving encrypted message package **1301**, UE **101-1** may decrypt portion **1303-1** using previously obtained public key **107-3** (e.g., as obtained when outputting a group message, as shown in FIG. **9**). For example, UE **101-1** may derive a symmetric key based on private key **105-1** (e.g., Private key A) and public key **107-3** (e.g., Public key C).

(80) Additionally, or alternatively, in some embodiments, UE **101-3** may have generated a new public key **107** (e.g., associated with a new private key **105**), and recorded the new public key **107** to blockchain system **109**. In such embodiments, UE **101-1** may request, and/or UE **101-3** may otherwise provide, a key identifier **801** associated with the new public key **107** to UE **101-1**, such that UE **101-1** is able to obtain the new public key **107** from blockchain system **109**. As further shown, UE **101-2** may obtain public key **107-3** from blockchain system **109** based on receiving encrypted message package **1301** (e.g., based on identifying portion **1303-2**). Once obtained, UE **101-2** may use public key **107-3** (e.g., along with private key **105-2**) to decrypt portion **1303-2** in order to extract message **1201**, as sent by UE **101-3**.

(81) At this point, UEs **101-1**, **101-2**, and **101-3** may all be in possession of each other's public keys **107**, as well as their own respective private keys **105**. Thus, when sending and receiving messages via the group communication session, UEs **101-1**, **101-2**, and **101-3** may not need to access blockchain system **109** any more. Thus, even in situations where other nodes **111** of blockchain system **109** go offline or become unreachable, the security and decentralization provided by techniques described above may be maintained. For example, as shown in FIG. **15**, UE **101-2** may generate encrypted message package **1501**, including portions **1503-1** and **1503-2**, which may each include a respective encrypted version of outgoing message **1551**. UE **101-2** may, in some embodiments, generate encrypted message package **1501** without attempting to access blockchain system **109** (e.g., communicating with nodes **111** of blockchain system **109**), as UE **101-2** is already in possession of the respective public keys **107** needed to encrypt message **1551** in accordance with example embodiments described above. Similarly, as shown in FIG. **16**, UEs **101-1** and **101-3** may receive encrypted message package **1501** and decrypt respective portions **1503-1** and **1503-2** using previously obtained public key **107-2** (e.g., Public key B) and their respective private keys **105-1** and **105-3**, in order to extract message **1551**.

(82) In some embodiments, participants in a group communication session may retrieve and/or cross-validate public keys **107** of other participants prior to receiving encrypted messages via the group communication session. For example, as shown in FIG. **17**, when initiating a group communication session, UE **101-1** may provide session identifier **1701** to other participants of the group communication session (e.g., UEs **101-2** and **101-3**). As similarly discussed above, UEs **101-1**, **101-2**, and **101-3** may generate respective asymmetric key pairs **103**, including a respective private key **105** and public key **107**. UEs **101-1**, **101-2**, and **101-3** may record respective public keys **107** to blockchain system **109**, along with session identifier **1701**. In some embodiments, session identifier **1701** may be provided with public keys **107** along with other suitable information, such as key identifiers **801**, UE identifiers, etc.

(83) As shown in FIG. **18**, UEs **101-1**, **101-2**, and **101-3** may automatically retrieve and/or cross-validate public keys **107** of the other group communication session participants (e.g., independently of receiving any encrypted messages or encrypted message packages via the group communication session). For example, UEs **101-1**, **101-2**, and **101-3** may implement and/or communicate with a “listener” or “explorer” of blockchain system **109**, based on which UEs **101-1**, **101-2**, and/or **101-3** may identify that public keys **107** of other group communication session participants have been recorded to blockchain system **109** (e.g., as discussed above with respect to FIG. **17**). Whenever such public keys **107** are recorded to blockchain system **109** (e.g., along with session identifier **1701** associated with the group communication session), UEs **101-1**, **101-2**, and/or **101-3** may automatically retrieve such public keys **107**. Additionally, or alternatively, UEs **101-1**, **101-2**, and/or **101-3** may perform a cross-validation of public keys **107**, including communicating with other nodes **111** of blockchain system **109** (e.g., at least a threshold quantity of UEs **101** from the set of UEs **101-1** through **101-6** that serve as nodes **111** of blockchain system **109**), to verify that the retrieved public keys **107** are valid.

(84) In some embodiments, participants may be added or removed from a group communication session secured by blockchain-based key exchange techniques. For example, as shown in FIG. **19**, UE **101-1** may add (at **1902**) a participant to an existing group communication session. For example, UE **101-1** may add UE **101-4** to a group communication session that already includes UEs **101-1**, **101-2**, and **101-3**. As such, UE **101-1** may provide a session identifier, associated with the existing group communication session, to UE **101-4**. UE **101-1** may additionally provide information regarding blockchain system **109**, such as identifiers of one or more nodes **111** of blockchain system **109** (e.g., MDNs, IP addresses, etc. of UEs **101** that are serving as nodes **111** of blockchain system **109**). In situations where UE **101-4** is already an existing node **111** of blockchain system **109** (e.g., where UE **101-4** is “promoted” from a passive participant to an active participant of the group communication session), UE **101-1** may forgo providing (at **1902**) information regarding blockchain system **109** to UE **101-4**, as UE **101-4** may already be aware of blockchain system **109** associated with the group communication session.

(85) In some embodiments, UE **101-1** may provide (at **1902**) the above-described information and/or other group communication session information to UE **101-4** via an RCS message or via some other suitable protocol or type of message. In some embodiments, UE **101-1** may generate an asymmetric key pair (e.g., including a public key and a private key), provide the public key to UE **101-4**, and encrypt some or all of the information (provided at **1902**) using the private key. In such embodiments, UE **101-4** may decrypt the information (provided at **1902**) using the public key.

(86) As further shown, UE **101-4** may, based on being added (or promoted) to the group communication session, generate asymmetric key pair **103** (e.g., including a respective private key **105** and public key **107**), and may share public key **107** of the generated asymmetric key pair **103**. For example, UE **101-4** may record the generated (at **1904**) public key **107** to blockchain system **109** and/or to some other suitable device or system from which the other UEs **101-1**, **101-2**, and **101-3** of the group communication session may retrieve and/or validate the generated public key **107** associated with UE **101-4**.

(87) UE **101-1** may also notify (at **1906**) the other participants of the group communication session (e.g., UEs **101-2** and **101-3**) that UE **101-4** has been added to the group communication session. The notification may include an identifier of UE **101-4**, such that UEs **101-2** and **101-3** may include UE **101-4** when sending encrypted messages via the group communication session.

(88) Once UE **101-4** has been added to the group communication session, UE **101-4** may send encrypted messages to other participants of the group communication session (e.g., UEs **101-1**, **101-2**, and **101-3**) in a similar manner as discussed above. For example, as shown in FIG. **20**, UE **101-4** may obtain and/or cross-validate public keys **107-1**, **107-2**, and **107-3** in order to encrypt outgoing message **2001**. As discussed above, encrypting message **2001** based on the obtained public keys **107-1**, **107-2**, and **107-3** may include generating an encrypted message package that includes multiple encrypted copies of message **2001**, where each encrypted copy may be encrypted based on a respective public key **107** of a given recipient UE **101** and/or private key **105-4** of UE **101-4**. UEs **101-1**, **101-2**, and **101-3** may obtain and/or cross-validate public key **107-4**, associated with UE **101-4**, in a manner similarly discussed above in order to decrypt such encrypted messages provided by UE **101-4**.

(89) FIG. **21** illustrates an example removal of a participant from a group communication session. As shown, UE **101-1** may output (at **2102**) an indication to some or all of the other UEs **101** of the group communication session (e.g., UEs **101-2**, **101-3**, and **101-4**, in this example) that UE **101-4** is being removed from the group communication session. The indication may include a session identifier associated with the group communication session and/or other suitable information based on which UEs **101-2**, **101-3**, and/or **101-4** may identify the group communication session from which UE **101-4** is being removed.

(90) Based on receiving such indication, UE **101-4** may remove (at **2104**) all keys associated with the group communication session. For example, UE **101-4** may remove, delete, mark for garbage collection, etc. private key **105-4**, public key **107-4**, and/or one or more public keys **107** associated with UEs **101-1**, **101-2**, and **101-3**. In some embodiments, UE **101-4** may retain (at **2104**) a chat history associated with the group communication session. For example, a messaging application of UE **101-4** may retain copies of messages (e.g., decrypted copies of such messages) received by UE **101-4** via the group communication session. UE **101-4** may retain such copies along with a session identifier of the group communication session. In this manner, a user of UE **101-4** may refer back to the previously received messages, even if UE **101-4** does not receive new messages via the group communication session after UE **101-4** is removed. Further, in instances where UE **101-4** is added back to the group communication session (e.g., associated with the same session identifier), a user interface, messaging application, etc. of UE **101-4** may seamlessly present newly received messages (e.g., after UE **101-4** is added back to the group communication session) along with previously received messages (e.g., received before UE **101-4** was removed from the group communication session).

(91) UEs **101-2** and **101-3** may further remove (at **2106** and **2108**, respectively) keys associated with UE **101-4**, such as public key **107-4**, based on receiving (at **2102**) the indication that UE **101-4** has been removed. Additionally, UE **101-1** may remove (at **2110**) keys associated with UE **101-4**, such as public key **107-4**, based on the removal of UE **101-4**.

(92) In situations where the removed UE **101-4** is serving as a node **111** of blockchain system **109**, UE **101-4** may be “demoted” from an active participant of the group communication session to a passive participant. For example, UE **101-4** may continue serving as a node **111** of blockchain system **109**, but may no longer receive encrypted messages via the group communication session from other UEs **101** of the group communication session. In such examples, UE **101-4** may retain some or all public keys **107** associated with UEs **101-1**, **101-2**, and **101-3**, at least inasmuch as these retained public keys **107** may be stored within a local copy of blockchain system **109** maintained by UE **101-4**.

(93) FIG. **22** illustrates an example environment **2200**, in which one or more embodiments may be

implemented. In some embodiments, environment **2200** may correspond to a Fifth Generation (“5G”) network, and/or may include elements of a 5G network. In some embodiments, environment **2200** may correspond to a 5G Non-Standalone (“NSA”) architecture, in which a 5G radio access technology (“RAT”) may be used in conjunction with one or more other RATs (e.g., a Long-Term Evolution (“LTE”) RAT), and/or in which elements of a 5G core network may be implemented by, may be communicatively coupled with, and/or may include elements of another type of core network (e.g., an evolved packet core (“EPC”)). As shown, environment **2200** may include UE **101**, RAN **2210** (which may include one or more Next Generation Node Bs (“gNBs”) **2211**), RAN **2212** (which may include one or more evolved Node Bs (“eNBs”) **2213**), and various network functions such as Access and Mobility Management Function (“AMF”) **2215**, Mobility Management Entity (“MME”) **2216**, Serving Gateway (“SGW”) **2217**, Session Management Function (“SMF”)/Packet Data Network (“PDN”) Gateway (“PGW”)-Control plane function (“PGW-C”) **2220**, Policy Control Function (“PCF”)/Policy Charging and Rules Function (“PCRF”) **2225**, Application Function (“AF”) **2230**, User Plane Function (“UPF”)/PGW-User plane function (“PGW-U”) **2235**, Unified Data Management function (“UDM”)/Home Subscriber Server (“HSS”) **2240**, and Authentication Server Function (“AUSF”) **2245**. Environment **2200** may also include one or more networks, such as Data Network (“DN”) **2250**.

(94) The example shown in FIG. **22** illustrates one instance of each network component or function (e.g., one instance of SMF/PGW-C **2220**, PCF/PCRF **2225**, UPF/PGW-U **2235**, UDM/HSS **2240**, and/or AUSF **2245**). In practice, environment **2200** may include multiple instances of such components or functions. For example, in some embodiments, environment **2200** may include multiple “slices” of a core network, where each slice includes a discrete set of network functions (e.g., one slice may include a first instance of SMF/PGW-C **2220**, PCF/PCRF **2225**, UPF/PGW-U **2235**, UDM/HSS **2240**, and/or AUSF **2245**, while another slice may include a second instance of SMF/PGW-C **2220**, PCF/PCRF **2225**, UPF/PGW-U **2235**, UDM/HSS **2240**, and/or AUSF **2245**). The different slices may provide differentiated levels of service, such as service in accordance with different Quality of Service (“QoS”) parameters.

(95) The quantity of devices and/or networks, illustrated in FIG. **22**, is provided for explanatory purposes only. In practice, environment **2200** may include additional devices and/or networks, fewer devices and/or networks, different devices and/or networks, or differently arranged devices and/or networks than illustrated in FIG. **22**. For example, while not shown, environment **2200** may include devices that facilitate or enable communication between various components shown in environment **2200**, such as routers, modems, gateways, switches, hubs, etc. Alternatively, or additionally, one or more of the devices of environment **2200** may perform one or more network functions described as being performed by another one or more of the devices of environment **2200**. Devices of environment **2200** may interconnect with each other and/or other devices via wired connections, wireless connections, or a combination of wired and wireless connections. In some implementations, one or more devices of environment **2200** may be physically integrated in, and/or may be physically attached to, one or more other devices of environment **2200**.

(96) UE **101** may include a computation and communication device, such as a wireless mobile communication device that is capable of communicating with RAN **2210**, RAN **2212**, and/or DN **2250**. UE **101** may be, or may include, a radiotelephone, a personal communications system (“PCS”) terminal (e.g., a device that combines a cellular radiotelephone with data processing and data communications capabilities), a personal digital assistant (“PDA”) (e.g., a device that may include a radiotelephone, a pager, Internet/intranet access, etc.), a smart phone, a laptop computer, a tablet computer, a camera, a personal gaming system, an IoT device (e.g., a sensor, a smart home appliance, or the like), a wearable device, an Internet of Things (“IoT”) device, a Machine-to-Machine (“M2M”) device, or another type of mobile computation and communication device. UE **101** may send traffic to and/or receive traffic (e.g., user plane traffic) from DN **2250** via RAN **2210**, RAN **2212**, and/or UPF/PGW-U **2235**. In some embodiments, UE **101** may include,

implement, etc. one or more nodes **111** of blockchain system **109**.

(97) RAN **2210** may be, or may include, a 5G RAN that includes one or more base stations (e.g., one or more gNBs **2211**), via which UE **101** may communicate with one or more other elements of environment **2200**. UE **101** may communicate with RAN **2210** via an air interface (e.g., as provided by gNB **2211**). For instance, RAN **2210** may receive traffic (e.g., voice call traffic, data traffic, messaging traffic, signaling traffic, etc.) from UE **101** via the air interface, and may communicate the traffic to UPF/PGW-U **2235**, and/or one or more other devices or networks. Similarly, RAN **2210** may receive traffic intended for UE **101** (e.g., from UPF/PGW-U **2235**, AMF **2215**, and/or one or more other devices or networks) and may communicate the traffic to UE **101** via the air interface.

(98) RAN **2212** may be, or may include, a LTE RAN that includes one or more base stations (e.g., one or more eNBs **2213**), via which UE **101** may communicate with one or more other elements of environment **2200**. UE **101** may communicate with RAN **2212** via an air interface (e.g., as provided by eNB **2213**). For instance, RAN **2210** may receive traffic (e.g., voice call traffic, data traffic, messaging traffic, signaling traffic, etc.) from UE **101** via the air interface, and may communicate the traffic to UPF/PGW-U **2235**, and/or one or more other devices or networks. Similarly, RAN **2210** may receive traffic intended for UE **101** (e.g., from UPF/PGW-U **2235**, SGW **2217**, and/or one or more other devices or networks) and may communicate the traffic to UE **101** via the air interface.

(99) AMF **2215** may include one or more devices, systems, Virtualized Network Functions (“VNFs”), etc., that perform operations to register UE **101** with the 5G network, to establish bearer channels associated with a session with UE **101**, to hand off UE **101** from the 5G network to another network, to hand off UE **101** from the other network to the 5G network, manage mobility of UE **101** between RANs **2210** and/or gNBs **2211**, and/or to perform other operations. In some embodiments, the 5G network may include multiple AMFs **2215**, which communicate with each other via the N14 interface (denoted in FIG. 22 by the line marked “N14” originating and terminating at AMF **2215**).

(100) MME **2216** may include one or more devices, systems, VNFs, etc., that perform operations to register UE **101** with the EPC, to establish bearer channels associated with a session with UE **101**, to hand off UE **101** from the EPC to another network, to hand off UE **101** from another network to the EPC, manage mobility of UE **101** between RANs **2212** and/or eNBs **2213**, and/or to perform other operations.

(101) SGW **2217** may include one or more devices, systems, VNFs, etc., that aggregate traffic received from one or more eNBs **2213** and send the aggregated traffic to an external network or device via UPF/PGW-U **2235**. Additionally, SGW **2217** may aggregate traffic received from one or more UPF/PGW-U **2235** and may send the aggregated traffic to one or more eNBs **2213**. SGW **2217** may operate as an anchor for the user plane during inter-eNB handovers and as an anchor for mobility between different telecommunication networks or RANs (e.g., RANs **2210** and **2212**).

(102) SMF/PGW-C **2220** may include one or more devices, systems, VNFs, etc., that gather, process, store, and/or provide information in a manner described herein. SMF/PGW-C **2220** may, for example, facilitate the establishment of communication sessions on behalf of UE **101**. In some embodiments, the establishment of communications sessions may be performed in accordance with one or more policies provided by PCF/PCRF **2225**.

(103) PCF/PCRF **2225** may include one or more devices, systems, VNFs, etc., that aggregate information to and from the 5G network and/or other sources. PCF/PCRF **2225** may receive information regarding policies and/or subscriptions from one or more sources, such as subscriber databases and/or from one or more users (such as, for example, an administrator associated with PCF/PCRF **2225**).

(104) AF **2230** may include one or more devices, systems, VNFs, etc., that receive, store, and/or provide information that may be used in determining parameters (e.g., quality of service

parameters, charging parameters, or the like) for certain applications.

(105) UPF/PGW-U **2235** may include one or more devices, systems, VNFs, etc., that receive, store, and/or provide data (e.g., user plane data). For example, UPF/PGW-U **2235** may receive user plane data (e.g., voice call traffic, data traffic, etc.), destined for UE **101**, from DN **2250**, and may forward the user plane data toward UE **101** (e.g., via RAN **2210**, SMF/PGW-C **2220**, and/or one or more other devices). In some embodiments, multiple UPFs **2235** may be deployed (e.g., in different geographical locations), and the delivery of content to UE **101** may be coordinated via the N9 interface (e.g., as denoted in FIG. **22** by the line marked “N9” originating and terminating at UPF/PGW-U **2235**). Similarly, UPF/PGW-U **2235** may receive traffic from UE **101** (e.g., via RAN **2210**, SMF/PGW-C **2220**, and/or one or more other devices), and may forward the traffic toward DN **2250**. In some embodiments, UPF/PGW-U **2235** may communicate (e.g., via the N4 interface) with SMF/PGW-C **2220**, regarding user plane data processed by UPF/PGW-U **2235**.

(106) UDM/HSS **2240** and AUSF **2245** may include one or more devices, systems, VNFs, etc., that manage, update, and/or store, in one or more memory devices associated with AUSF **2245** and/or UDM/HSS **2240**, profile information associated with a subscriber. AUSF **2245** and/or UDM/HSS **2240** may perform authentication, authorization, and/or accounting operations associated with the subscriber and/or a communication session with UE **101**.

(107) DN **2250** may include one or more wired and/or wireless networks. For example, DN **2250** may include an Internet Protocol (“IP”)-based PDN, a wide area network (“WAN”) such as the Internet, a private enterprise network, and/or one or more other networks. UE **101** may communicate, through DN **2250**, with data servers, other UEs **101**, and/or to other servers or applications that are coupled to DN **2250**. DN **2250** may be connected to one or more other networks, such as a public switched telephone network (“PSTN”), a public land mobile network (“PLMN”), and/or another network. DN **2250** may be connected to one or more devices, such as content providers, applications, web servers, and/or other devices, with which UE **101** may communicate.

(108) FIG. **23** illustrates an example Distributed Unit (“DU”) network **2300**, which may be included in and/or implemented by one or more RANs (e.g., RAN **2210**, RAN **2212**, or some other RAN). In some embodiments, a particular RAN may include one DU network **2300**. In some embodiments, a particular RAN may include multiple DU networks **2300**. In some embodiments, DU network **2300** may correspond to a particular gNB **2211** of a 5G RAN (e.g., RAN **2210**). In some embodiments, DU network **2300** may correspond to multiple gNBs **2211**. In some embodiments, DU network **2300** may correspond to one or more other types of base stations of one or more other types of RANs. As shown, DU network **2300** may include Centralized Unit (“CU”) **2305**, one or more Distributed Units (“DUs”) **2303-1** through **2303-N** (referred to individually as “DU **2303**,” or collectively as “DUs **2303**”), and one or more Radio Units (“RUs”) **2301-1** through **2301-M** (referred to individually as “RU **2301**,” or collectively as “RUs **2301**”).

(109) CU **2305** may communicate with a core of a wireless network (e.g., may communicate with one or more of the devices or systems described above with respect to FIG. **22**, such as AMF **2215** and/or UPF/PGW-U **2235**). In the uplink direction (e.g., for traffic from UEs **101** to a core network), CU **2305** may aggregate traffic from DUs **2303**, and forward the aggregated traffic to the core network. In some embodiments, CU **2305** may receive traffic according to a given protocol (e.g., Radio Link Control (“RLC”)) from DUs **2303**, and may perform higher-layer processing (e.g., may aggregate/process RLC packets and generate Packet Data Convergence Protocol (“PDCP”) packets based on the RLC packets) on the traffic received from DUs **2303**.

(110) In accordance with some embodiments, CU **2305** may receive downlink traffic (e.g., traffic from the core network) for a particular UE **101**, and may determine which DU(s) **2303** should receive the downlink traffic. DU **2303** may include one or more devices that transmit traffic between a core network (e.g., via CU **2305**) and UE **101** (e.g., via a respective RU **2301**). DU **2303** may, for example, receive traffic from RU **2301** at a first layer (e.g., physical (“PHY”) layer traffic,

or lower PHY layer traffic), and may process/aggregate the traffic to a second layer (e.g., upper PHY and/or RLC). DU **2303** may receive traffic from CU **2305** at the second layer, may process the traffic to the first layer, and provide the processed traffic to a respective RU **2301** for transmission to UE **101**.

(111) RU **2301** may include hardware circuitry (e.g., one or more RF transceivers, antennas, radios, and/or other suitable hardware) to communicate wirelessly (e.g., via an RF interface) with one or more UEs **101**, one or more other DUs **2303** (e.g., via RUs **2301** associated with DUs **2303**), and/or any other suitable type of device. In the uplink direction, RU **2301** may receive traffic from UE **101** and/or another DU **2303** via the RF interface and may provide the traffic to DU **2303**. In the downlink direction, RU **2301** may receive traffic from DU **2303**, and may provide the traffic to UE **101** and/or another DU **2303**.

(112) RUs **2301** may, in some embodiments, be communicatively coupled to one or more Multi-Access/Mobile Edge Computing (“MEC”) devices, referred to sometimes herein simply as “MECs” **2307**. For example, RU **2301-1** may be communicatively coupled to MEC **2307-1**, RU **2301-M** may be communicatively coupled to MEC **2307-M**, DU **2303-1** may be communicatively coupled to MEC **2307-2**, DU **2303-N** may be communicatively coupled to MEC **2307-N**, CU **2305** may be communicatively coupled to MEC **2307-3**, and so on. MECs **2307** may include hardware resources (e.g., configurable or provisionable hardware resources) that may be configured to provide services and/or otherwise process traffic to and/or from UE **101**, via a respective RU **2301**.

(113) For example, RU **2301-1** may route some traffic, from UE **101**, to MEC **2307-1** instead of to a core network (e.g., via DU **2303** and CU **2305**). MEC **2307-1** may process the traffic, perform one or more computations based on the received traffic, and may provide traffic to UE **101** via RU **2301-1**. In this manner, ultra-low latency services may be provided to UE **101**, as traffic does not need to traverse DU **2303**, CU **2305**, and an intervening backhaul network between DU network **2300** and the core network. In some embodiments, MEC **2307** may include, and/or may implement, some or all of the functionality described above with respect to one or more nodes **111**.

(114) FIG. **24** illustrates example components of device **2400**. One or more of the devices described above may include one or more devices **2400**. Device **2400** may include bus **2410**, processor **2420**, memory **2430**, input component **2440**, output component **2450**, and communication interface **2460**. In another implementation, device **2400** may include additional, fewer, different, or differently arranged components.

(115) Bus **2410** may include one or more communication paths that permit communication among the components of device **2400**. Processor **2420** may include a processor, microprocessor, or processing logic that may interpret and execute instructions. In some embodiments, processor **2420** may be or may include one or more hardware processors. Memory **2430** may include any type of dynamic storage device that may store information and instructions for execution by processor **2420**, and/or any type of non-volatile storage device that may store information for use by processor **2420**.

(116) Input component **2440** may include a mechanism that permits an operator to input information to device **2400** and/or other receives or detects input from a source external to **2440**, such as a touchpad, a touchscreen, a keyboard, a keypad, a button, a switch, a microphone or other audio input component, etc. In some embodiments, input component **2440** may include, or may be communicatively coupled to, one or more sensors, such as a motion sensor (e.g., which may be or may include a gyroscope, accelerometer, or the like), a location sensor (e.g., a Global Positioning System (“GPS”)-based location sensor or some other suitable type of location sensor or location determination component), a thermometer, a barometer, and/or some other type of sensor. Output component **2450** may include a mechanism that outputs information to the operator, such as a display, a speaker, one or more light emitting diodes (“LEDs”), etc.

(117) Communication interface **2460** may include any transceiver-like mechanism that enables device **2400** to communicate with other devices and/or systems. For example, communication

interface **2460** may include an Ethernet interface, an optical interface, a coaxial interface, or the like. Communication interface **2460** may include a wireless communication device, such as an infrared (“IR”) receiver, a Bluetooth® radio, or the like. The wireless communication device may be coupled to an external device, such as a remote control, a wireless keyboard, a mobile telephone, etc. In some embodiments, device **2400** may include more than one communication interface **2460**. For instance, device **2400** may include an optical interface and an Ethernet interface.

(118) Device **2400** may perform certain operations relating to one or more processes described above. Device **2400** may perform these operations in response to processor **2420** executing software instructions stored in a computer-readable medium, such as memory **2430**. A computer-readable medium may be defined as a non-transitory memory device. A memory device may include space within a single physical memory device or spread across multiple physical memory devices. The software instructions may be read into memory **2430** from another computer-readable medium or from another device. The software instructions stored in memory **2430** may cause processor **2420** to perform processes described herein. Alternatively, hardwired circuitry may be used in place of or in combination with software instructions to implement processes described herein. Thus, implementations described herein are not limited to any specific combination of hardware circuitry and software.

(119) The foregoing description of implementations provides illustration and description, but is not intended to be exhaustive or to limit the possible implementations to the precise form disclosed. Modifications and variations are possible in light of the above disclosure or may be acquired from practice of the implementations.

(120) For example, while series of blocks and/or signals have been described above (e.g., with regard to FIGS. **1-21**), the order of the blocks and/or signals may be modified in other implementations. Further, non-dependent blocks and/or signals may be performed in parallel. Additionally, while the figures have been described in the context of particular devices performing particular acts, in practice, one or more other devices may perform some or all of these acts in lieu of, or in addition to, the above-mentioned devices.

(121) The actual software code or specialized control hardware used to implement an embodiment is not limiting of the embodiment. Thus, the operation and behavior of the embodiment has been described without reference to the specific software code, it being understood that software and control hardware may be designed based on the description herein.

(122) In the preceding specification, various example embodiments have been described with reference to the accompanying drawings. It will, however, be evident that various modifications and changes may be made thereto, and additional embodiments may be implemented, without departing from the broader scope of the invention as set forth in the claims that follow. The specification and drawings are accordingly to be regarded in an illustrative rather than restrictive sense.

(123) Even though particular combinations of features are recited in the claims and/or disclosed in the specification, these combinations are not intended to limit the disclosure of the possible implementations. In fact, many of these features may be combined in ways not specifically recited in the claims and/or disclosed in the specification. Although each dependent claim listed below may directly depend on only one other claim, the disclosure of the possible implementations includes each dependent claim in combination with every other claim in the claim set.

(124) Further, while certain connections or devices are shown, in practice, additional, fewer, or different, connections or devices may be used. Furthermore, while various devices and networks are shown separately, in practice, the functionality of multiple devices may be performed by a single device, or the functionality of one device may be performed by multiple devices. Further, multiple ones of the illustrated networks may be included in a single network, or a particular network may include multiple networks. Further, while some devices are shown as communicating with a network, some such devices may be incorporated, in whole or in part, as a part of the

network.

(125) To the extent the aforementioned implementations collect, store, or employ personal information of individuals, groups or other entities, it should be understood that such information shall be used in accordance with all applicable laws concerning protection of personal information. Additionally, the collection, storage, and use of such information can be subject to consent of the individual to such activity, for example, through well known “opt-in” or “opt-out” processes as can be appropriate for the situation and type of information. Storage and use of personal information can be in an appropriately secure manner reflective of the type of information, for example, through various access control, encryption and anonymization techniques for particularly sensitive information.

(126) No element, act, or instruction used in the present application should be construed as critical or essential unless explicitly described as such. An instance of the use of the term “and,” as used herein, does not necessarily preclude the interpretation that the phrase “and/or” was intended in that instance. Similarly, an instance of the use of the term “or,” as used herein, does not necessarily preclude the interpretation that the phrase “and/or” was intended in that instance. Also, as used herein, the article “a” is intended to include one or more items, and may be used interchangeably with the phrase “one or more.” Where only one item is intended, the terms “one,” “single,” “only,” or similar language is used. Further, the phrase “based on” is intended to mean “based, at least in part, on” unless explicitly stated otherwise.

Claims

1. A first device, comprising: one or more hardware processors configured to: maintain an asymmetric key pair that includes a first key and a second key, wherein the asymmetric key pair is associated with a particular key identifier; receive a message to be sent to a second device and a third device; receive a first public key associated with the second device; receive a second public key associated with the third device; generate an encrypted communication based on the message, wherein generating the encrypted communication includes: generating a first encrypted version of the message by encrypting the message using the first key of the asymmetric key pair and the first public key associated with the second device, and generating a second encrypted version of the message by encrypting the message using the first key of the asymmetric key pair and the second public key associated with the third device, wherein the encrypted communication includes the particular key identifier, the first encrypted version of the message, and the second encrypted version of the message; output the encrypted communication to the second device and the third device; and output, to a blockchain system, the second key and the particular key identifier associated with the asymmetric key pair, wherein the second device: obtains the second key from the blockchain system based on the particular key identifier included in the encrypted communication, and decrypts the first encrypted version of the message using the second key obtained from the blockchain system based on the particular key identifier and a first private key that is associated with the first public key, and wherein the third device: obtains the second key from the blockchain system based on the particular key identifier included in the encrypted communication, and decrypts the second encrypted version of the message using the second key obtained from the blockchain system based on the particular key identifier and a second private key that is associated with the second public key.
2. The first device of claim 1, wherein receiving the first and second public keys includes obtaining the first and second public keys from the blockchain system.
3. The first device of claim 1, wherein the one or more hardware processors are further configured to: add a fourth device to a group communication session with which the first, second, and third devices are associated, wherein adding the fourth device includes providing a session identifier associated with the group communication session to the fourth device, wherein the fourth device

obtains at least of the first or second public keys from the blockchain system based on the session identifier.

4. The first device of claim 1, wherein the one or more hardware processors are further configured to: remove the third device from a group communication session with which the first, second, and third devices are associated, wherein removing the third device from the group communication session includes outputting an indication to the second and third devices that the third device is being removed from the group communication session, wherein the third device retains a chat history associated with the group communication session after receiving the indication that the third device is being removed from the group communication session.

5. The first device of claim 1, wherein the second device is a node of the blockchain system, wherein obtaining the second key from the blockchain system includes cross-validating the second key with at least a threshold quantity of other nodes of the blockchain system.

6. The first device of claim 1, wherein the one or more hardware processors are further configured to: remove the third device from a group communication session with which the first, second, and third devices are associated, wherein removing the third device from the group communication session includes outputting an indication to the second device that the third device is being removed from the group communication session, wherein the second device deletes the second public key associated with the third device.

7. The first device of claim 1, wherein the third device is a node of the blockchain system, wherein the one or more hardware processors are further configured to: remove the third device from a group communication session with which the first, second, and third devices are associated, wherein the third device continues to serve as a node of the blockchain system after being removed from the group communication session.

8. A non-transitory computer-readable medium storing a plurality of processor-executable instructions, wherein execution of the processor-executable instructions by a first device causes the first device to: maintain an asymmetric key pair that includes a first key and a second key, wherein the asymmetric key pair is associated with a particular key identifier; receive a message to be sent to a second device and a third device; receive a first public key associated with the second device; receive a second public key associated with the third device; generate an encrypted communication based on the message, wherein generating the encrypted communication includes: encrypting the message using the first key of the asymmetric key pair and the first public key associated with the second device, and generating a second encrypted version of the message by encrypting the message using the first key of the asymmetric key pair and the second public key associated with the third device, wherein the encrypted communication includes the particular key identifier, the first encrypted version of the message, and the second encrypted version of the message; output the encrypted communication to the second device and the third device; and output, to a blockchain system, the second key and the particular key identifier associated with the asymmetric key pair, wherein the second device: obtains the second key from the blockchain system based on the particular key identifier included in the encrypted communication, and decrypts the first encrypted version of the message using the second key obtained from the blockchain system based on the particular key identifier and a first private key that is associated with the first public key, and wherein the third device: obtains the second key from the blockchain system based on the particular key identifier included in the encrypted communication, and decrypts the second encrypted version of the message using the second key obtained from the blockchain system based on the particular key identifier and a second private key that is associated with the second public key.

9. The non-transitory computer-readable medium of claim 8, wherein receiving the first and second public keys includes obtaining the first and second public keys from the blockchain system.

10. The non-transitory computer-readable medium of claim 8, wherein the plurality of processor-executable instructions further include processor-executable instructions to: add a fourth device to a

group communication session with which the first, second, and third devices are associated, wherein adding the fourth device includes providing a session identifier associated with the group communication session to the fourth device, wherein the fourth device obtains at least of the first or second public keys from the blockchain system based on the session identifier.

11. The non-transitory computer-readable medium of claim 8, wherein the plurality of processor-executable instructions further include processor-executable instructions to: remove the third device from a group communication session with which the first, second, and third devices are associated, wherein removing the third device from the group communication session includes outputting an indication to the second and third devices that the third device is being removed from the group communication session, wherein the third device retains a chat history associated with the group communication session after receiving the indication that the third device is being removed from the group communication session.

12. The non-transitory computer-readable medium of claim 8, wherein the second device is a node of the blockchain system, wherein obtaining the second key from the blockchain system includes cross-validating the second key with at least a threshold quantity of other nodes of the blockchain system.

13. The non-transitory computer-readable medium of claim 8, wherein the plurality of processor-executable instructions further include processor-executable instructions to: remove the third device from a group communication session with which the first, second, and third devices are associated, wherein the third device continues to serve as a node of the blockchain system after being removed from the group communication session.

14. A method, comprising: maintaining, by a first device, an asymmetric key pair that includes a first key and a second key, wherein the asymmetric key pair is associated with a particular key identifier; receiving a message to be sent to a second device and a third device; receiving a first public key associated with the second device; receiving a second public key associated with the third device; generating an encrypted communication based on the message, wherein generating the encrypted communication includes: encrypting the message using the first key of the asymmetric key pair and the first public key associated with the second device, and generating a second encrypted version of the message by encrypting the message using the first key of the asymmetric key pair and the second public key associated with the third device, wherein the encrypted communication includes the particular key identifier, the first encrypted version of the message, and the second encrypted version of the message; outputting the encrypted communication to the second device and the third device; and outputting, to a blockchain system, the second key and the particular key identifier associated with the asymmetric key pair, wherein the second device: obtains the second key from the blockchain system based on the particular key identifier included in the encrypted communication, and decrypts the first encrypted version of the message using the second key obtained from the blockchain system based on the particular key identifier and a first private key that is associated with the first public key, and wherein the third device: obtains the second key from the blockchain system based on the particular key identifier included in the encrypted communication, and decrypts the second encrypted version of the message using the second key obtained from the blockchain system based on the particular key identifier and a second private key that is associated with the second public key.

15. The method of claim 14, wherein receiving the first and second public keys includes obtaining the first and second public keys from the blockchain system.

16. The method of claim 14, further comprising: adding a fourth device to a group communication session with which the first, second, and third devices are associated, wherein adding the fourth device includes providing a session identifier associated with the group communication session to the fourth device, wherein the fourth device obtains at least of the first or second public keys from the blockchain system based on the session identifier.

17. The method of claim 14, further comprising: removing the third device from a group

communication session with which the first, second, and third devices are associated, wherein removing the third device from the group communication session includes outputting an indication to the second and third devices that the third device is being removed from the group communication session, wherein the third device retains a chat history associated with the group communication session after receiving the indication that the third device is being removed from the group communication session.

18. The method of claim 14, wherein the second device is a node of the blockchain system, wherein obtaining the second key from the blockchain system includes cross-validating the second key with at least a threshold quantity of other nodes of the blockchain system.

19. The method of claim 14, further comprising: removing the third device from a group communication session with which the first, second, and third devices are associated, wherein removing the third device from the group communication session includes outputting an indication to the second device that the third device is being removed from the group communication session, wherein the second device deletes the second public key associated with the third device.

20. The method of claim 14, wherein the third device is a node of the blockchain system, the method further comprising: removing the third device from a group communication session with which the first, second, and third devices are associated, wherein the third device continues to serve as a node of the blockchain system after being removed from the group communication session.
