

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403349
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Li; Jianjun

Adjustable dumbbell

Abstract

The present disclosure discloses an adjustable dumbbell including a base, a grip, and dumbbell plates on the grip. The base is provided with a dumbbell plate fix groove, a bottom of the dumbbell plate fix groove is provided with several locking pieces; a through hole is provided on the grip, an interior of the through hole is provided with a connection mechanism. Each dumbbell plate includes a shell and a weight stack arranged in the shell. The shell is fixedly connected with a positioning mechanism, a connection rod in the connection mechanism is moved towards both ends of the grip by rotating the grip. A movement length of the connection rod and the number of dumbbell plates of the grip are controlled to control a weight of the dumbbell. The dumbbell plates are easy to disassemble and assemble and the positioning mechanism prevents the dumbbell plates from falling off.

Inventors:	Li; Jianjun (Luzhou, CN)
Applicant:	Yongkang Zuojian Industry and Trade Co., Ltd. (Yongkang, CN)
Family ID:	90167314
Assignee:	Yongkang Zuojian Industry and Trade Co., Ltd. (Yongkang, CN)
Appl. No.:	18/400295
Filed:	December 29, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250065180 A1	Feb. 27, 2025

Foreign Application Priority Data

CN	202322245566.8	Aug. 21, 2023
----	----------------	---------------

Publication Classification

Int. Cl.: A63B21/072 (20060101); A63B21/075 (20060101)

U.S. Cl.:

CPC A63B21/0726 (20130101); A63B21/0728 (20130101); A63B21/075 (20130101);

Field of Classification Search

CPC: A63B (21/0726); A63B (21/0728); A63B (21/075)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11198031	12/2020	Chen	N/A	A63B 21/072
11717714	12/2022	Hong	482/107	A63B 21/0726
2007/0184945	12/2006	Lin	482/107	A63B 21/075
2018/0353794	12/2017	Wang	N/A	A63B 71/0036
2022/0096890	12/2021	Lu	N/A	A63B 21/0728
2022/0249898	12/2021	Jiang	N/A	A63B 71/0036
2023/0001258	12/2022	Svenberg	N/A	A63B 21/0724

Primary Examiner: Dzierzynski; Evan P

Attorney, Agent or Firm: Birchwood IP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims priority to Chinese Patent Application No. 202322245566.8, filed on Aug. 21, 2023, which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

(2) The present disclosure relates to the field of fitness equipment technologies, and in particular, to an adjustable dumbbell.

BACKGROUND

(3) Dumbbells are widely used fitness equipment. Its middle part is a grip, and two ends are spherical or cylindrical bell bodies, which are convenient to use. However, the weight of a single dumbbell is fixed and cannot meet the needs of trainers with different strengths or usage habits. Due to the widespread use of dumbbells, users often need many dumbbell plates of different weights, and changing the weight can only be done through frequent disassembly and replacement of dumbbell plates. This frequent and cumbersome procedure brings certain troubles to users.

SUMMARY

(4) The technical solution adopted by the present disclosure to solve the above problems is as follows.

(5) The present disclosure provides a dumbbell that is easy to adjust, including: a dumbbell plate

fix seat, which is provided with a dumbbell plate fix groove on the dumbbell plate fix seat, a bottom of the dumbbell plate fix groove is provided with several locking pieces; a grip, which is provided with a through hole, an interior of the through hole is provided with a connection mechanism, the connection mechanism includes a lead screw and a moving rod slidably connected to the lead screw, the moving rod is provided with a second positioning hole, the moving rod is fixedly connected to a connection rod, the connection rod is provided with several first position holes, the grip is connected to the several dumbbell plates; where each dumbbell plate includes a shell and a weight stack arranged in the shell, the shell is provided with a positioning mechanism, the positioning mechanism is provided with a dumbbell plate connection hole, the positioning mechanism includes a base and a cover plate, and a moving piece provided between the base and the cover plate; the base is provided with a third pin hole, and the moving piece is provided with a third pin above the third pin hole, an elastic member is provided between an upper of the moving piece and the base; the elastic member ensures that the moving piece is not subjected to an external force, and the third pin is located in the third pin hole; a conflict block is provided below the moving piece, the conflict block is connected to an outside through a lower of the base.

(6) In an embodiment of the present disclosure, a side wall of the dumbbell plate fix groove is provided with a dumbbell fix block, the dumbbell plate is provided with a clamp slot, the dumbbell plate is fixed to the dumbbell fix block through the clamp slot.

(7) In an embodiment of the present disclosure, a bottom of the dumbbell plate fix groove is provided with several dumbbell plate positioning grooves with a width consistent with that of the dumbbell plate.

(8) In an embodiment of the present disclosure, the dumbbell plate fix seat is provided with a groove below the grip.

(9) In an embodiment of the present disclosure, the lead screw is fixedly connected to a connection sleeve, the connection sleeve is provided with a second pin, the lead screw is fixedly connected to the grip through the second pin.

(10) In an embodiment of the present disclosure, the grip is provided with an anti-slip sleeve and an anti-slip pattern.

(11) In an embodiment of the present disclosure, the connection rod is provided with a first pin hole, the moving rod is provided with a first pin, and the connection rod is fixedly connected to the moving rod through the first pin.

(12) In an embodiment of the present disclosure, the moving piece is provided with an elastic member connection block, and the elastic member is positioned through the elastic member connection block and abuts against the base.

(13) The beneficial effects of the present disclosure are that a dumbbell that is easy to adjust is provided, which includes a dumbbell plate fix seat, a grip, and dumbbell plates on the grip. The dumbbell plate fix seat is provided with a dumbbell plate fix groove, and the bottom of the dumbbell plate fix groove is provided with several locking pieces; a through hole is provided on the grip, and the interior of the through hole is provided with a connection mechanism. The dumbbell plate includes a shell and a weight stack arranged in the shell. The shell is fixedly connected with a positioning mechanism, and the connection rod in the connection mechanism is moved towards both ends of the grip by rotating the grip. The movement length of the connection rod is controlled to control the number of pieces of dumbbell plates connected to the grip, thereby controlling the weight of the dumbbell plate. The dumbbell plates with the above structure are easy to disassemble and assemble, besides, the positioning mechanism prevents the dumbbell plates from falling off during use and has high safety.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) In order to provide a clearer explanation of the embodiments of the present disclosure or the technical solutions in the prior art, a brief introduction will be given below to the drawings required in description of the embodiments or prior art. It is obvious that the drawings in the following description are only some embodiments of the present disclosure. For ordinary technical personnel in this field, without creative work, other drawings can also be obtained based on the structures shown in these drawings.

(2) FIG. 1 is a perspective diagram of an adjustable dumbbell in the present disclosure.

(3) FIG. 2 is an exploded diagram of the adjustable dumbbell in the present disclosure.

(4) FIG. 3 is an enlarged diagram of position A in FIG. 2.

(5) FIG. 4 is an exploded diagram of a grip in the adjustable dumbbell of the present disclosure.

(6) FIG. 5 is a perspective diagram of a dumbbell plate in the adjustable dumbbell in the present disclosure.

(7) FIG. 6 is an exploded diagram of FIG. 5.

(8) FIG. 7 is an enlarged diagram of position B in FIG. 6.

(9) Numeral reference: **1**—grip, **101**—anti-slip sleeve, **102**—through hole, **103**—connection rod, **1031**—first positioning hole, **1032**—first pin hole, **104**—lead screw, **105**—moving rod, **1051**—second positioning hole, **1052**—first pin, **106**—second pin, **107**—connection sleeve, **2**—dumbbell plate fix seat, **201**—dumbbell plate fix groove, **202**—groove, **203**—dumbbell fix block, **204**—dumbbell plate positioning groove, **205**—locking piece, **3**—dumbbell plate, **301**—shell, **301**—positioning mechanism installation groove, **302**—dumbbell plate connection hole, **303**—clamp slot, **304**—cover plate, **305**—weight stack, **306**—moving piece, **3061**—conflict block, **3062**—third pin, **3063**—elastic member connection block, **307**—base, **3071**—third pin hole.

DESCRIPTION OF EMBODIMENTS

(10) In order to enable those skilled in the art to better understand the technical solution of the present application, the following will provide a clear and complete description of the technical solution in the embodiments of the present application in combination with the drawings.

Obviously, the described embodiments are only a part of the embodiments of the present application, not all of them. Based on the embodiments in the present disclosure, all other embodiments obtained by those skilled in the art without creative work fall within the protection scope of the present application.

(11) A dumbbell that is easy to adjust, as shown in FIGS. 1-7, including: a dumbbell plate fix seat **2**, which is provided with a dumbbell plate fix groove **201** thereon, a bottom of the dumbbell plate fix groove **101** is provided with several locking pieces **205**; a grip **1**, which is provided with a through hole **102** thereon, an interior of the through hole **102** is provided with a connection mechanism, the connection mechanism includes a lead screw **104** and a moving rod **105** slidably connected to the lead screw **104**, the moving rod **105** is provided with a second positioning hole **1051**, the moving rod **105** is fixedly connected to a connection rod **103**, and the connection rod **103** is provided with several first positioning holes **1031** thereon, the grip **1** is connected to the several dumbbell plates **3**; the lead screw **104** is driven to rotate by rotating the grip **1**, and then the moving rod **105** and connection rod **103** on the lead screw **104** are moved, the connection rod **103** extends into the dumbbell plate connection hole **302** on the dumbbell plate **3**; each dumbbell plate **3** includes a shell **301** and a weight stack **305** arranged in the shell **301**, the shell **301** is fixedly connected to a positioning mechanism, the positioning mechanism is provided with a dumbbell plate connection hole **302**; the positioning mechanism includes a base **307** and a cover plate **304**, and a moving piece **306** provided between the base **307** and the cover plate **304**; the base **307** is provided with a third pin hole **3071**, and the moving piece **306** is provided with a third pin **3062** above the third pin hole **3071**; an elastic member is provided between an upper of the moving piece **306** and the base **307**, the elastic member is used to ensure that the moving piece **306** is not

subjected to an external force, and the third pin **3062** is located in the third pin hole **3071**, a conflict block **3061** is provided below the moving piece **306**, the conflict block **3061** is connected to an outside through the lower of the base **307**. In addition, there is a positioning mechanism installation groove **3011** on the shell **301**, and the positioning mechanism is fixedly connected to the positioning mechanism installation groove **3011**.

(12) When the dumbbell is placed on the dumbbell plate fix seat **2**, the conflict block **3061** abuts against the locking piece **205** on the dumbbell plate fix seat **2**, and thus, the moving piece **306** is moved upwards. The third pin **3062** separates from the third pin hole **3071**, the first positioning hole and second positioning hole, which allows the connection rod **103** to move. By rotating the grip **1**, a length of the connection rod **103** extending into the dumbbell plate connection hole **302** is controlled to control the number of dumbbell plates.

(13) When lifting the dumbbell, the conflict block **3061** detaches from the locking piece **205**. Due to the elastic member between the moving piece **306** and the base **307**, the moving piece **306** is pressed down and reset. The third pin **3062** extends into the third pin hole **3071**, the first positioning hole and second positioning hole, and thus, the dumbbell plate **3** is fixed on the connection rod **103**.

(14) Specifically, a side wall of the dumbbell plate fix groove **201** is provided with a dumbbell fix block **203**, the dumbbell plate **3** is provided with a clamp slot **303**, the dumbbell plate **3** is fixed to the dumbbell fix block **203** through the clamp slot **303** to prevent the dumbbell plate from shaking.

(15) Specifically, a bottom of the dumbbell plate fix groove **201** is provided with several dumbbell plate positioning grooves **204** with a width consistent with that of the dumbbell plate **3**.

(16) Specifically, the dumbbell plate fix seat **2** is provided with a groove **202** below the grip **1**, thereby providing a space for a user to grip the grip conveniently.

(17) As another preferred implementation mode of this embodiment, the lead screw **104** is fixedly connected to a connection sleeve **107**, the connection sleeve **107** is provided with a second pin **106**, the lead screw **104** is fixedly connected to the grip **1** through the second pin **106**, thereby ensuring a stable connection and convenient assembly of spare parts.

(18) Specifically, the grip **1** is provided with an anti-slip sleeve **101** and an anti-slip pattern. When holding the grip **1**, it is necessary to avoid sliding between the palm and the grip **1**.

(19) Specifically, the connection rod **103** is provided with a first pin hole **1032**, the moving rod **105** is provided with a first pin **1052**, and the connection rod **103** is fixedly connected to the moving rod **105** through the first pin **1052**.

(20) In addition, the moving piece **306** is provided with an elastic member connection block **3063**, which is positioned through the elastic member connection block **3063** and abuts against the base **307** to avoid displacement of the elastic member.

(21) From the above description, it can be seen that the embodiments of the present disclosure achieve the following technical effects: the present disclosure provides a dumbbell that is easy to adjust, which includes a base, a grip, and dumbbell plates on the grip. The base is provided with a dumbbell plate fix groove, and the bottom of the dumbbell plate fix groove is provided with several locking pieces; there is a through hole on the grip, and the interior of the through hole is provided with a connection mechanism. Each dumbbell plate includes a shell and a weight stack arranged in the shell. The shell is fixedly connected with a positioning mechanism, and the connection rod in the connection mechanism is moved towards both ends of the grip by rotating the grip. The movement length of the connection rod is controlled to control the number of pieces of dumbbell plates connected to the grip, thereby controlling the weight of the dumbbell plate. The dumbbell plates with the above structure are easy to disassemble and assemble, in addition, the positioning mechanism prevents the dumbbell plates from falling off during use and has high safety.

(22) It should be noted that terms used here are only for describing specific embodiments and are not intended to limit exemplary embodiments according to the present application. As used here, unless otherwise explicitly stated in the context, the singular form is also intended to include the

plural form. In addition, it should be understood that when terms “including” and/or “comprising” are used in this specification, they indicate the existence of features, steps, operations, devices, components, and/or their combinations.

(23) Unless otherwise specified, the relative arrangement, numerical expressions, and numerical values of the components and steps described in these embodiments do not limit the scope of the present application. At the same time, it should be understood that for ease of description, the dimensions of each part shown in the drawings are not drawn according to the actual proportional relationship. The technology, methods, and equipment known to ordinary technical personnel in the relevant field may not be discussed in detail, but in appropriate cases, such technology, methods, and equipment should be considered as part of the authorization manual. In all embodiments shown and discussed here, any specific value should be interpreted as merely illustrative and not as a limitation. Therefore, other examples of exemplary embodiments may have different values. It should be noted that similar labels and letters represent similar terms in the following drawings, so once a term is defined in one drawing it does not need to be further discussed in subsequent drawings.

(24) In the description of the present application, it should be understood that the orientation or position relationships indicated by directional words such as “front”, “back”, “up”, “down”, “left”, “right”, “horizontal”, “longitudinal”, “upright”, “vertical”, “plane”, and “top”, “bottom” are usually based on the orientation or position relationships shown in the drawings, only for the convenience of describing the present application and simplifying the description. Unless otherwise specified, these directional words do not indicate or imply that the device or component referred to must have a specific orientation or be constructed and operated in a specific orientation, and therefore cannot be understood as a limitation on the protection scope of the present application; in addition, directional words “inner” and “outer” refer to the inner and outer contours relative to each component itself.

(25) It should be understood that when a component is referred to as “on” or “connected to” another component, it can be directly connected to or on that other component, or indirectly connected with an inserted component between the two. On the contrary, when a component is referred to as “directly” on another component or “directly connected” to another component, there is no inserted component between the two.

(26) Furthermore, it should be noted that in the description of the present disclosure, the use of words such as “first” and “second” to define the components is only for the purpose of distinguishing the corresponding components. If not otherwise stated, the above words do not have special meanings and cannot be understood as limiting the protection scope of the present application. In the description of the present disclosure, unless otherwise specified, the meaning of “multiple” refers to two or more.

(27) The above is the preferred embodiments of the present disclosure. It should be pointed out that for ordinary technical personnel in this field, several improvements and embellishments can be made without departing from the principles of the present disclosure. These improvements and embellishments are also considered as the protection scope of the present disclosure.

Claims

1. An adjustable dumbbell, comprising: a dumbbell plate fix seat, which is provided with a dumbbell plate fix groove on the dumbbell plate fix seat, a bottom of the dumbbell plate fix groove is provided with several locking pieces; a grip, which is provided with a through hole, an interior of the through hole is provided with a connection mechanism, the connection mechanism comprises a lead screw and a moving rod slidably connected to the lead screw, the moving rod is provided with a second positioning hole, the moving rod is fixedly connected to a connection rod, the connection rod is provided with several first position holes, the grip is connected to the several dumbbell

plates; wherein each dumbbell plate comprises a shell and a weight stack arranged in the shell, the shell is provided with a positioning mechanism, the positioning mechanism is provided with a dumbbell plate connection hole, the positioning mechanism comprises a base and a cover plate, and a moving piece provided between the base and the cover plate; the base is provided with a third pin hole, and the moving piece is provided with a third pin above the third pin hole, an elastic member is provided between an upper of the moving piece and the base; the elastic member ensures that the moving piece is not subjected to an external force, and the third pin is located in the third pin hole; a conflict block is provided below the moving piece, the conflict block is connected to an outside through a lower of the base.

2. The adjustable dumbbell according to claim 1, wherein a side wall of the dumbbell plate fix groove is provided with a dumbbell fix block, the dumbbell plate is provided with a clamp slot, the dumbbell plate is fixed to the dumbbell fix block through the clamp slot.

3. The adjustable dumbbell according to claim 2, wherein a bottom of the dumbbell plate fix groove is provided with several dumbbell plate positioning grooves with a width consistent with that of the dumbbell plate.

4. The adjustable dumbbell according to claim 3, wherein the dumbbell plate fix seat is provided with a groove below the grip.

5. The adjustable dumbbell according to claim 4, wherein the lead screw is fixedly connected to a connection sleeve, the connection sleeve is provided with a second pin, the lead screw is fixedly connected to the grip through the second pin.

6. The adjustable dumbbell according to claim 2, wherein the lead screw is fixedly connected to a connection sleeve, the connection sleeve is provided with a second pin, the lead screw is fixedly connected to the grip through the second pin.

7. The adjustable dumbbell according to claim 3, wherein the lead screw is fixedly connected to a connection sleeve, the connection sleeve is provided with a second pin, the lead screw is fixedly connected to the grip through the second pin.

8. The adjustable dumbbell according to claim 1, wherein the lead screw is fixedly connected to a connection sleeve, the connection sleeve is provided with a second pin, the lead screw is fixedly connected to the grip through the second pin.

9. The adjustable dumbbell according to claim 8, wherein the grip is provided with an anti-slip sleeve and an anti-slip pattern.

10. The adjustable dumbbell according to claim 9, wherein the connection rod is provided with a first pin hole, the moving rod is provided with a first pin, and the connection rod is fixedly connected to the moving rod through the first pin.

11. The adjustable dumbbell according to claim 10, wherein the moving piece is provided with an elastic member connection block, and the elastic member is positioned through the elastic member connection block and abuts against the base.
