

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12405658

Kind Code

B2

Date of Patent

September 02, 2025

Inventor(s)

Zhang; Lei et al.

Virtual AR interfaces for controlling IoT devices using mobile device orientation sensors

Abstract

Described are virtual AR interfaces for generating a virtual rotational interface for the purpose of controlling connected IoT devices using the inertial measurement unit (IMU) of a portable electronic device. The IMU control application enables a user of a portable electronic device to activate a virtual rotational interface overlay on a display and adjust a feature of a connected IoT product by rotating a portable electronic device. The device IMU moves a slider on the virtual rotational interface. The IMU control application sends a control signal to the IoT product which executes an action in accordance with the slider position. The virtual rotational interface is presented on the display as a virtual object in an AR environment. The IMU control application detects the device orientation (in the physical environment) and in response presents a corresponding slider element on the virtual rotational interface (in the AR environment).

Inventors: Zhang; Lei (Ann Arbor, MI), Cho; Youjean (New York, NY), Kim; Daekun (Santa Monica, CA), Robinson; Ava (Solana Beach, CA), Tham; Yu Jiang (Seattle, WA), Vaish; Rajan (Beverly Hills, CA), Monroy-Hernández; Andrés (Seattle, WA)

Applicant: Snap Inc. (Santa Monica, CA)

Family ID: 90060764

Appl. No.: 18/748987

Filed: June 20, 2024

Prior Publication Data

Document Identifier

US 20240338071 A1

Publication Date

Oct. 10, 2024

Related U.S. Application Data

Publication Classification

Int. Cl.: **G06F3/01** (20060101); **G06F1/16** (20060101); **G06T19/00** (20110101)

U.S. Cl.:

CPC **G06F3/011** (20130101); **G06F1/163** (20130101); **G06T19/006** (20130101);

Field of Classification Search

CPC: G06F (15/16); G06F (3/011); G06F (3/048); G06F (3/04815); G06F (3/04847); G06F (3/0482); G06F (9/451); G06F (9/54); H04L (67/12)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10031581	12/2017	Raman et al.	N/A	N/A
10110678	12/2017	Hebsur et al.	N/A	N/A
10496253	12/2018	Keller	N/A	N/A
10551993	12/2019	Sanocki et al.	N/A	N/A
10739861	12/2019	Kin	N/A	G06V 40/18
10831267	12/2019	Golard et al.	N/A	N/A
10921764	12/2020	Mao et al.	N/A	N/A
10936280	12/2020	Lin	N/A	N/A
11406896	12/2021	Cheung et al.	N/A	N/A
12045383	12/2023	Zhang et al.	N/A	N/A
2004/0091848	12/2003	Nemitz	N/A	N/A
2006/0003824	12/2005	Kobayashi et al.	N/A	N/A
2006/0041546	12/2005	Ahn	N/A	N/A
2007/0124507	12/2006	Gurram et al.	N/A	N/A
2009/0300676	12/2008	Harter, Jr.	N/A	N/A
2010/0092930	12/2009	Fletcher et al.	N/A	N/A
2011/0165939	12/2010	Borst et al.	N/A	N/A
2011/0314381	12/2010	Fuller et al.	N/A	N/A
2012/0284426	12/2011	Smith et al.	N/A	N/A
2013/0307855	12/2012	Lamb et al.	N/A	N/A
2013/0307856	12/2012	Keane et al.	N/A	N/A
2014/0080109	12/2013	Haseltine et al.	N/A	N/A
2014/0282013	12/2013	Amijee	N/A	N/A
2014/0368533	12/2013	Salter et al.	N/A	N/A
2015/0072330	12/2014	Rosenberg	N/A	N/A
2015/0165310	12/2014	Rebh et al.	N/A	N/A
2015/0347114	12/2014	Yoon	N/A	N/A
2016/0005207	12/2015	Jeon	N/A	N/A
2016/0136524	12/2015	Leites et al.	N/A	N/A

2016/0225187	12/2015	Knipp et al.	N/A	N/A
2016/0274705	12/2015	Kapadia et al.	N/A	N/A
2017/0142324	12/2016	Jost et al.	N/A	N/A
2017/0220134	12/2016	Burns et al.	N/A	N/A
2017/0337164	12/2016	Longdale et al.	N/A	N/A
2018/0047396	12/2017	Forutanpour et al.	N/A	N/A
2018/0053351	12/2017	Anderson	N/A	N/A
2018/0276185	12/2017	Kaldma et al.	N/A	N/A
2019/0066387	12/2018	Grossmann et al.	N/A	N/A
2019/0107927	12/2018	Schriber et al.	N/A	N/A
2019/0114061	12/2018	Daniels et al.	N/A	N/A
2019/0188917	12/2018	Cho et al.	N/A	N/A
2019/0244427	12/2018	Sun et al.	N/A	N/A
2019/0361575	12/2018	Ni et al.	N/A	N/A
2019/0371002	12/2018	Hwang et al.	N/A	N/A
2019/0371071	12/2018	Lyons	N/A	N/A
2020/0026362	12/2019	Kim	N/A	G06F 3/013
2020/0042286	12/2019	Bui et al.	N/A	N/A
2020/0051302	12/2019	Subramonyam et al.	N/A	N/A
2020/0118343	12/2019	Koblin et al.	N/A	N/A
2020/0326831	12/2019	Marr	N/A	N/A
2020/0326837	12/2019	Ni	N/A	N/A
2020/0334463	12/2019	Shapira	N/A	N/A
2020/0338451	12/2019	Wang	N/A	N/A
2020/0387289	12/2019	Dunn et al.	N/A	N/A
2021/0052976	12/2020	Anderson et al.	N/A	N/A
2021/0084233	12/2020	Faaborg et al.	N/A	N/A
2021/0183158	12/2020	Korngold et al.	N/A	N/A
2021/0196174	12/2020	Tarnanas et al.	N/A	N/A
2021/0216145	12/2020	Monge Nunez et al.	N/A	N/A
2021/0256865	12/2020	Koshiba et al.	N/A	N/A
2021/0342047	12/2020	Badr et al.	N/A	N/A
2022/0083198	12/2021	Kaehler et al.	N/A	N/A
2022/0253808	12/2021	Ferguson et al.	N/A	N/A
2022/0258056	12/2021	Jiang	N/A	N/A
2022/0398798	12/2021	Baradaran	N/A	N/A
2023/0120437	12/2022	Simic et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
20170108285	12/2016	KR	N/A
2018102615	12/2017	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion for International Application No. PCT/US2023/028720, dated Nov. 7, 2023 (Nov. 7, 2023)—10 pages. cited by applicant

International Search Report and Written Opinion for International Application No. PCT/US2023/028776, dated Nov. 15, 2023 (Nov. 15, 2023)—10 pages. cited by applicant

International Search Report and Written Opinion for International Application No. PCT/US2023/028788, dated Nov. 8, 2023 (Nov. 8, 2023)—10 pages. cited by applicant

Primary Examiner: Rosario; Nelson M

Attorney, Agent or Firm: CM Law

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a Continuation of U.S. patent application Ser. No. 17/901,568 filed on Sep. 1, 2022, the contents of which are incorporated fully herein by reference.

TECHNICAL FIELD

(1) Examples set forth in the present disclosure relate to the field of augmented reality (AR) experiences for electronic devices, including portable electronic devices and wearable devices such as eyewear. More particularly, but not by way of limitation, the present disclosure describes AR applications for displaying virtual rotational interfaces that enable users to interact with and control connected IoT devices using the inertial measurement unit (IMU) of a mobile device.

BACKGROUND

(2) Many types of computers and electronic devices available today, such as mobile devices (e.g., smartphones, tablets, and laptops), handheld devices, and wearable devices (e.g., smart glasses, digital eyewear, headwear, headgear, and head-mounted displays), include a variety of cameras, sensors, wireless transceivers, input systems, and displays. Users sometimes refer to information on these devices during physical activities such as exercise.

(3) The so-called “Internet of Things” (IoT) refers to and includes physical products that are embedded with sensors, software, and other technologies for enabling connection and exchange of data with other devices, in a network, often over the Internet. For example, IoT products are used in home automation to control lighting, heating and air conditioning, media and security systems, and camera systems. A number of IoT-enabled devices have been provided that function as smart home hubs to connect different smart home products. IoT devices have been used in a number of other applications as well. Application layer protocols and supporting frameworks have been provided for implementing such IoT applications. For example, some IoT products include an application programming interface (API) that allows the IoT product to pair with and otherwise communicate with other products and electronic devices, such as portable computers. Artificial intelligence has also been combined with the Internet of Things infrastructure to achieve more efficient IoT network operations, improve human-machine interactions, and enhance data management and analytics.

(4) Virtual reality (VR) technology generates a complete virtual environment including realistic images, sometimes presented on a VR headset or other head-mounted display. VR experiences allow a user to move through the virtual environment and interact with virtual objects. AR is a type of VR technology that combines real objects in a physical environment with virtual objects and displays the combination to a user. The combined display gives the impression that the virtual objects are authentically present in the environment, especially when the virtual objects appear and behave like the real objects. Cross reality (XR) is generally understood as an umbrella term referring to systems that include or combine elements from AR, VR, and MR (mixed reality) environments.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Features of the various examples described will be readily understood from the following detailed description, in which reference is made to the figures. A reference numeral is used with each element in the description and throughout the several views of the drawing. When a plurality of similar elements is present, a single reference numeral may be assigned to like elements, with an added upper or lower-case letter referring to a specific element.
- (2) The various elements shown in the figures are not drawn to scale unless otherwise indicated. The dimensions of the various elements may be enlarged or reduced in the interest of clarity. The several figures depict one or more implementations and are presented by way of example only and should not be construed as limiting. Included in the drawing are the following figures:
- (3) FIG. 1A is a side view (right) of an eyewear device suitable for use in an example IMU control system;
- (4) FIG. 1B is a perspective, partly sectional view of optical components and electronics in a portion of the eyewear device illustrated in FIG. 1A;
- (5) FIG. 1C is a side view (left) of the eyewear device of FIG. 1A;
- (6) FIG. 1D is a perspective, partly sectional view of optical components and electronics in a portion of the eyewear device illustrated in FIG. 1C;
- (7) FIGS. 2A and 2B are rear views of an eyewear device utilized in an example IMU control system;
- (8) FIG. 3 is a block diagram illustrating an example of capturing visible light using an example eyewear device illustrated in any of the proceeding figures;
- (9) FIG. 4 is a functional block diagram of an example IMU control system including an eyewear device and a server system connected via various networks;
- (10) FIG. 5 is a diagrammatic representation of an example hardware configuration for a mobile device configured for use in the example IMU control system of FIG. 4;
- (11) FIG. 6 is a perspective view of a user in an example environment, including physical objects and virtual objects, for reference in describing an example process known as simultaneous localization and mapping (SLAM);
- (12) FIG. 7 is a flow chart listing the steps in an example method of presenting a virtual rotational interface on a display;
- (13) FIG. 8A is an illustration of an example virtual rotational interface presented on the display of a portable electronic device;
- (14) FIG. 8B is an illustration of an example interaction between the portable electronic device and the virtual rotational interface of FIG. 8A, resulting in a corresponding IoT action; and
- (15) FIG. 9 is an illustration of an example interaction between a portable electronic device and an example virtual rotational interface presented on the display of an electronic eyewear device.

DETAILED DESCRIPTION

- (16) A IMU control system for use with AR applications on portable electronic devices, including mobile phones and wearable devices such as electronic eyewear devices. The IMU control system enables the user of a portable electronic device to view a virtual rotational interface that is presented on the display near an IoT product. The user can tilt the electronic device in order to interact with the virtual rotational interface, thereby adjusting one or more controllable features (e.g., on, off, volume, brightness) of the IoT product.
- (17) Various implementations and details are described with reference to examples for presenting a virtual rotational interface in an augmented reality environment to control an IoT product using the IMU of a portable electronic device that has a camera and a display. In an example implementation, a method involves capturing frames of video data with the camera and detecting the IoT product at

an IoT product location in a physical environment using the captured frames of video data. This example method also includes determining a portable electronic device location relative to the IoT product location, and then presenting on the display a virtual rotational interface according to the IoT product location and the portable electronic device location. An example virtual rotational interface includes a slider that is virtually presented at a slider position according to the detected device orientation. The slider position corresponds to an IoT action (e.g., adjusting a variable feature, such as volume, brightness, or color hue). The example method includes sending a control signal to the IoT product, wherein the control signal includes instructions for use by the IoT product to perform the IoT action.

(18) Although the various systems and methods are described herein with reference to an IMU controlling a slider in a curved viewport that is generally coplanar relative to the display, the technology described herein may be applied to any of a variety of orientation sensors in a portable electronic device controlling a slider or another kind of movable virtual element, with or without a viewport or track. Moreover, the technology described herein may be applied to control one or more variable features of a connected IoT product using movements of a portable electronic device along or near any plane of rotation (e.g., roll, pitch, yaw). For example, a variable feature (e.g., volume) may be controlled by moving the portable electronic device about or nearly about the z-axis (e.g., yaw). Another feature (e.g., channel selection) may be controlled by moving the portable electronic device about or nearly about the y-axis (e.g., roll). Yet another feature (e.g., brightness) may be controlled by moving the portable electronic device about an arbitrary axis (e.g., in an arbitrary non-orthogonal plane). In this aspect, the virtual rotational interface described herein is useful for controlling a variety of features associated with IoT consumer products, such as lamps, speakers, and fans, as well as IoT products used for commercial, medical, and industrial applications of all kinds.

(19) The following detailed description includes systems, methods, techniques, instruction sequences, and computer program products illustrative of examples set forth in the disclosure. Numerous details and examples are included for the purpose of providing a thorough understanding of the disclosed subject matter and its relevant teachings. Those skilled in the relevant art, however, may understand how to apply the relevant teachings without such details. Aspects of the disclosed subject matter are not limited to the specific devices, systems, and methods described because the relevant teachings can be applied or practiced in a variety of ways. The terminology and nomenclature used herein is for the purpose of describing particular aspects only and is not intended to be limiting. In general, well-known instruction instances, protocols, structures, and techniques are not necessarily shown in detail.

(20) The term “connect,” “connected,” “couple,” and “coupled” as used herein refers to any logical, optical, physical, or electrical connection, including a link or the like by which the electrical or magnetic signals produced or supplied by one system element are imparted to another coupled or connected system element. Unless described otherwise, coupled, or connected elements or devices are not necessarily directly connected to one another and may be separated by intermediate components, elements, or communication media, one or more of which may modify, manipulate, or carry the electrical signals. The term “on” means directly supported by an element or indirectly supported by the element through another element integrated into or supported by the element.

(21) The term “proximal” is used to describe an item or part of an item that is situated near, adjacent, or next to an object or person; or that is closer relative to other parts of the item, which may be described as “distal.” For example, the end of an item nearest an object may be referred to as the proximal end, whereas the generally opposing end may be referred to as the distal end.

(22) The orientations of the eyewear device, associated components and any complete devices incorporating an eye scanner and camera such as shown in any of the drawings, are given by way of example only, for illustration and discussion purposes. In operation for a particular variable optical processing application, the eyewear device may be oriented in any other direction suitable

to the particular application of the eyewear device for example up, down, sideways, or any other orientation. Also, to the extent used herein, any directional term, such as front, rear, inwards, outwards, towards, left, right, lateral, longitudinal, up, down, upper, lower, top, bottom and side, are used by way of example only, and are not limiting as to direction or orientation of any optic or component of an optic constructed as otherwise described herein.

(23) Advanced AR technologies, such as computer vision and object tracking, may be used to produce a perceptually enriched and immersive experience. Computer vision algorithms extract three-dimensional data about the physical world from the data captured in digital images or video. Object recognition and tracking algorithms are used to detect an object in a digital image or video, estimate its orientation or pose, and track its movement over time. The recognition and tracking in real time of body parts, such as hands and fingers, arms and legs, and feet is one of the most challenging and processing-intensive tasks in the field of computer vision.

(24) Additional objects, advantages and novel features of the examples will be set forth in part in the following description, and in part will become apparent to those skilled in the art upon examination of the following and the accompanying drawings or may be learned by production or operation of the examples. The objects and advantages of the present subject matter may be realized and attained by means of the methodologies, instrumentalities and combinations particularly pointed out in the appended claims.

(25) In sample configurations, eyewear devices with augmented reality (AR) capability are used in the systems described herein. Eyewear devices are desirable to use in the system described herein as such devices are scalable, customizable to enable personalized experiences, enable effects to be applied anytime, anywhere, and ensure user privacy by enabling only the user to see the transmitted information. An eyewear device such as SPECTACLES™ available from Snap, Inc. of Santa Monica, California, may be used without any specialized hardware in a sample configuration.

(26) As shown in FIGS. 1A-1D, the eyewear device **100** includes a first camera **114A** and a second camera **114B**. The cameras **114** capture image information for a scene from separate viewpoints. The captured images may be used to project a three-dimensional display onto an image display for three dimensional (3D) viewing.

(27) The cameras **114** are sensitive to the visible-light range wavelength. Each of the cameras **114** define a different frontward facing field of view, which are overlapping to enable generation of 3D depth images; for example, a first camera **114A** defines a first field of view **111A** and a second camera **114B** defines a second field of view **111B**. Generally, a “field of view” is the part of the scene that is visible through the camera at a particular position and orientation in space. The fields of view **111** have an overlapping field of view **304** (FIG. 3). Objects or object features outside the field of view **111** when the camera captures the image are not recorded in a raw image (e.g., photograph or picture). The field of view describes an angle range or extent, which the image sensor of the camera **114** picks up electromagnetic radiation of a given scene in a captured image of the given scene. Field of view can be expressed as the angular size of the view cone; i.e., an angle of view. The angle of view can be measured horizontally, vertically, or diagonally.

(28) In an example configuration, one or both cameras **114** has a field of view of 100° and a resolution of 480×480 pixels. The “angle of coverage” describes the angle range that a lens of the cameras **114** can effectively image. Typically, the camera lens produces an image circle that is large enough to cover the film or sensor of the camera completely, possibly including some vignetting (e.g., a darkening of the image toward the edges when compared to the center). If the angle of coverage of the camera lens does not fill the sensor, the image circle will be visible, typically with strong vignetting toward the edge, and the effective angle of view will be limited to the angle of coverage.

(29) Examples of suitable cameras **114** include a high-resolution complementary metal-oxide-semiconductor (CMOS) image sensor and a digital VGA camera (video graphics array) capable of resolutions of 480p (e.g., 640×480 pixels), 720p, 1080p, or greater. Other examples include

cameras **114** that can capture high-definition (HD) video at a high frame rate (e.g., thirty to sixty frames per second, or more) and store the recording at a resolution of 1216 by 1216 pixels (or greater).

(30) The eyewear device **100** may capture image sensor data from the cameras **114** along with geolocation data, digitized by an image processor, for storage in a memory. The cameras **114** capture respective raw images (e.g., left and right raw images) in the two-dimensional space domain that comprise a matrix of pixels on a two-dimensional coordinate system that includes an X-axis for horizontal position and a Y-axis for vertical position. Each pixel includes a color attribute value (e.g., a red pixel light value, a green pixel light value, or a blue pixel light value); and a position attribute (e.g., an X-axis coordinate and a Y-axis coordinate).

(31) In order to capture stereo images for later display as a 3D projection, the image processor **412** (FIG. 4) may be coupled to the cameras **114** to receive and store the visual image information. The image processor **412**, or another processor, controls operation of the cameras **114** to act as a stereo camera simulating human binocular vision and may add a timestamp to each image. The timestamp on each pair of images allows display of the images together as part of a 3D projection. 3D projections produce an immersive, life-like experience that is desirable in a variety of contexts, including virtual reality (VR) and video gaming.

(32) FIG. 1B is a perspective, cross-sectional view of a right corner **110A** of the eyewear device **100** of FIG. 1A depicting the first camera **114A**, additional optical components, and electronics. FIG. 1C is a side view (left) of an example hardware configuration of an eyewear device **100** of FIG. 1A, which shows the second camera **114B** of the camera system. FIG. 1D is a perspective, cross-sectional view of a left corner **110B** of the eyewear device **100** of FIG. 1C depicting the second camera **114B** of the camera system, additional optical components, and electronics.

(33) As shown in the example of FIG. 1B, the eyewear device **100** includes the first camera **114A** and a circuit board **140A**, which may be a flexible printed circuit board (PCB). A first hinge **126A** connects the right corner **110A** to a first temple **125A** of the eyewear device **100**. In some examples, components of the first camera **114A**, the flexible PCB **140A**, or other electrical connectors or contacts may be located on the first temple **125A** or the first hinge **126A**.

(34) The right corner **110A** includes corner body **190** and a corner cap, with the corner cap omitted in the cross-section of FIG. 1B. Disposed inside the right corner **110A** are various interconnected circuit boards **109**, such as the flexible PCB **140A**, that include controller circuits for the first camera **114A**, microphone(s) **139**, speaker(s) **191**, low-power wireless circuitry (e.g., for wireless short range network communication via Bluetooth™), high-speed wireless circuitry (e.g., for wireless local area network communication via Wi-Fi).

(35) The first camera **114A** is coupled to or disposed on the flexible PCB **140A** and is covered by a camera cover lens, which is aimed through opening(s) formed in the frame **105**. For example, the right rim **107A** of the frame **105**, shown in FIG. 2A, is connected to the right corner **110A** and includes the opening(s) for the camera cover lens. The frame **105** includes a front side configured to face outward and away from the eye of the user. The opening for the camera cover lens is formed on and through the front or outward-facing side of the frame **105**. In the example, the first camera **114A** has an outward-facing field of view **111A** (shown in FIG. 3) with a line of sight or perspective that is correlated with the right eye of the user of the eyewear device **100**. The camera cover lens can also be adhered to a front side or outward-facing surface of the right corner **110A** in which an opening is formed with an outward-facing angle of coverage, but in a different outwardly direction. The coupling can also be indirect via intervening components.

(36) As shown in the example of FIG. 1D, the eyewear device **100** includes the second camera **114B** and a circuit board **140B**, which may be a flexible printed circuit board (PCB). A second hinge **126B** connects the left corner **110B** to a second temple **125B** of the eyewear device **100**. In some examples, components of the second camera **114B**, the flexible PCB **140B**, or other electrical connectors or contacts may be located on the second temple **125B** or the second hinge **126B**.

(37) The left corner **110B** includes corner body **190** and a corner cap, with the corner cap omitted in the cross-section of FIG. **1D**. Disposed inside the right corner **110A** are various interconnected circuit boards, such as the flexible PCB **140B**, that include controller circuits for the second camera **114B**.

(38) The camera **114** are coupled to or disposed on respective flexible PCBs **140** and are covered by a camera cover lens, which is aimed through opening(s) formed in the frame **105**. For example, as shown in FIG. **2A**, the right rim **107A** of the frame **105** is connected to the right corner **110A** and includes the opening(s) for the camera cover lens and the left rim **107B** of the frame **105** is connected to the left corner **110B** and includes the opening(s) for the camera cover lens. The frame **105** includes a front side configured to face outward and away from the eye of the user. The opening for the camera cover lens is formed on and through the front or outward-facing side of the frame **105**. In the example, the cameras **114** have respective outward-facing fields of view **111** (shown in FIG. **3**) with a line of sight or perspective that is correlated with a respective eye of the user of the eyewear device **100**. The camera cover lenses can also be adhered to a front side or outward-facing surface of the respective corners **110** in which an opening is formed with an outward-facing angle of coverage, but in a different outwardly direction. The coupling can also be indirect via intervening components.

(39) FIGS. **2A** and **2B** depict example hardware configurations of the eyewear device **100**, including two different types of image displays. The eyewear device **100** is sized and shaped in a form configured for wearing by a user. The form of eyeglasses is shown in the illustrated examples. The eyewear device **100** can take other forms and may incorporate other types of frameworks; for example, a headgear, a headset, or a helmet.

(40) In the eyeglasses example, eyewear device **100** includes a frame **105** including a right rim **107A** connected to a left rim **107B** via a bridge **106** configured to receive a nose of the user to support the eyewear device **100** on the user's head. The right rim **107A** includes a first aperture **175A**, which holds a first optical element **180A**. The left rim **107B** includes a second aperture **175B**, which holds a second optical element **180B**. As shown in FIG. **2B**, each optical element **180A**, **180B** in some implementations includes an integrated image display (e.g., a first display **182A** and a second display **182B**). As used herein, the term "lens" is meant to include transparent or translucent pieces of glass or plastic having curved or flat surfaces that cause light to converge or diverge or that cause little or no convergence or divergence.

(41) A touch-sensitive input device, such as a touchpad **181** is positioned on the first temple **125A**. As shown, the touchpad **181** may have a boundary that is plainly visible or includes a raised or otherwise tactile edge that provides feedback to the user about the location and boundary of the touchpad **181**; alternatively, the boundary may be subtle and not easily seen or felt. The eyewear device **100** may include a touchpad on the other side that operates independently or in conjunction with the touchpad **181**.

(42) The surface of the touchpad **181** is configured to detect finger touches, taps, and gestures (e.g., moving touches) for use with a graphical user interface (GUI) displayed by the eyewear device, on an image display, to allow the user to navigate through and select menu options in an intuitive manner, which enhances and simplifies the user experience.

(43) Detection of finger inputs on the touchpad **181** can enable several functions. For example, touching anywhere on the touchpad **181** may cause the GUI to display or highlight an item on the image display, which may be projected onto at least one of the optical assemblies **180**. Tapping or double tapping on the touchpad **181** may select an item or icon. Sliding or swiping a finger in a particular direction (e.g., from front to back, back to front, up to down, or down to) may cause the items or icons to slide or scroll in a particular direction; for example, to move to a next item, icon, video, image, page, or slide. Sliding the finger in another direction may slide or scroll in the opposite direction; for example, to move to a previous item, icon, video, image, page, or slide. The touchpad **181** can be positioned essentially anywhere on the eyewear device **100**.

(44) In one example, an identified finger gesture of a single tap on the touchpad **181**, initiates selection or pressing of a GUI element in the image presented on the image display of the optical assembly **180**. An adjustment to the image presented on the image display of the optical assembly **180** based on the identified finger gesture can be a primary action which selects or submits the GUI element on the image display of the optical assembly **180** for further display or execution.

(45) FIG. 2A is an example hardware configuration for the eyewear device **100** in which the right corner **110A** supports a microphone **139** and a speaker **191**. The microphone **139** includes a transducer that converts sound into a corresponding electrical audio signal. The microphone **139** in the illustrated example is positioned with an opening that faces inward toward the wearer, to facilitate reception of the sound waves, such as human speech including verbal commands and questions. Additional or differently oriented openings may be implemented. In other example configurations, the eyewear device **100** is coupled to one or more microphones **139**, configured to operate together or independently, and positioned at various locations on the eyewear device **100**.

(46) The speaker **191** includes an electro-acoustic transducer that converts an electrical audio signal into a corresponding sound. The speaker **191** is controlled by one of the processors **422**, **432** or by an audio processor **413** (FIG. 4). The speaker **191** in this example includes a series of oblong apertures, as shown, that face inward to direct the sound toward the wearer. Additional or differently oriented apertures may be implemented. In other example configurations, the eyewear device **100** is coupled to one or more speakers **191**, configured to operate together (e.g., in stereo, in zones to generate surround sound) or independently, and positioned at various locations on the eyewear device **100**. For example, one or more speakers **191** may be incorporated into the frame **105**, temples **125**, or corners **110** of the eyewear device **100**.

(47) Although shown in FIG. 2A and FIG. 2B as having two optical elements **180**, the eyewear device **100** can include other arrangements, such as a single optical element (or it may not include any optical element **180**), depending on the application or the intended user of the eyewear device **100**. As further shown, eyewear device **100** includes a right corner **110A** adjacent the right lateral side **170A** of the frame **105** and a left corner **110B** adjacent the left lateral side **170B** of the frame **105**. The corners **110** may be integrated into the frame **105** on the respective sides **170** (as illustrated) or implemented as separate components attached to the frame **105** on the respective sides **170**. Alternatively, the corners **110A**, **110B** may be integrated into temples (not shown) attached to the frame **105**.

(48) In one example, each image display of optical assembly **180** includes an integrated image display (e.g., a first display **182A** and a second display **182B**). As shown in FIG. 2A, each optical assembly **180** has a display **182** that includes a suitable display matrix **177**, such as a liquid crystal display (LCD), an organic light-emitting diode (OLED) display, or other such display. Each optical assembly **180** also includes an optical layer or layers **176**, which can include lenses, optical coatings, prisms, mirrors, waveguides, optical strips, and other optical components in any combination. The optical layers (shown as **176A-N** in FIG. 2A) can include a prism having a suitable size and configuration and including a first surface for receiving light from a display matrix and a second surface for emitting light to the eye of the user. The prism of the optical layers **176A-N** extends over all or at least a portion of the respective apertures **175** formed in the left and right rims **107** to permit the user to see the second surface of the prism when the eye of the user is viewing through the corresponding rims **107**. The first surface of the prism of the optical layers **176A-N** faces upwardly from the frame **105** and the display matrix **177** overlies the prism so that photons and light emitted by the display matrix **177** impinge the first surface. The prism is sized and shaped so that the light is refracted within the prism and is directed toward the eye of the user by the second surface of the prism of the optical layers **176A-N**. In this regard, the second surface of the prism of the optical layers **176A-N** can be convex to direct the light toward the center of the eye. The prism can optionally be sized and shaped to magnify the image projected by the display matrix **177**, and the light travels through the prism so that the image viewed from the second

surface is larger in one or more dimensions than the image emitted from the display matrix **177**.

(49) In one example, the optical layers **176A-N** may include an LCD layer that is transparent (keeping the lens open) unless and until a voltage is applied which makes the layer opaque (closing or blocking the lens). The image processor **412** on the eyewear device **100** may execute programming to apply the voltage to the LCD layer in order to produce an active shutter system, making the eyewear device **100** suitable for viewing visual content when displayed as a 3D projection. Technologies other than LCD may be used for the active shutter mode, including other types of reactive layers that are responsive to a voltage or another type of input.

(50) In another example, the image display device of optical assembly **180** has a display **182** that includes a projection image display as shown in FIG. 2B. Each optical assembly **180** includes a respective laser projector **150**, such as a three-color laser projector using a scanning mirror or galvanometer. Each laser projector **150** is disposed in or on a respective temples **125** of the eyewear device **100**. Each optical assembly **180**, in this example, includes one or more optical strips (shown as **155A-N** in FIG. 2B), which are spaced apart and across the width of the lens of each optical assembly **180** or across a depth of the lens between the front surface and the rear surface of the lens.

(51) As the photons projected by the laser projector **150** travel across the lens of each optical assembly **180**, the photons encounter the optical strips **155A-N**. When a particular photon encounters a particular optical strip, the photon is either redirected toward the user's eye, or it passes to the next optical strip. A combination of modulation of laser projector **150**, and modulation of optical strips, control specific photons or beams of light. In an example, a processor controls optical strips **155A-N** by initiating mechanical, acoustic, or electromagnetic signals. Although shown as having two optical assemblies **180**, the eyewear device **100** can include other arrangements, such as a single or three optical assemblies, or each optical assembly **180** may have different arrangements depending on the application or intended user of the eyewear device **100**.

(52) FIG. 3 is a diagrammatic depiction of a 3D scene **306**, a first raw image **302A** captured using a first camera **114A**, and a second raw image **302B** captured using a second camera **114B**. The first field of view **111A** may overlap, as shown, with the second field of view **111B**. The overlapping fields of view **304** represents that portion of the image captured using both cameras **114**. The term 'overlapping' when referring to field of view means the matrix of pixels in the generated raw images overlap by thirty percent (30%) or more. 'Substantially overlapping' means the matrix of pixels in the generated raw images—or in the infrared image of scene—overlap by fifty percent (50%) or more. As described herein, the two raw images **302** may be processed to include a timestamp, which allows the images to be displayed together as part of a three-dimensional projection.

(53) For the capture of stereo images, as illustrated in FIG. 3, a pair of raw red, green, and blue (RGB) images are captured of a 3D scene **306** at a given moment in time—a first raw image **302A** captured using the first camera **114A** and second raw image **302B** captured using the second camera **114B**. When the pair of raw images **302** are processed (e.g., by the image processor **412**), depth images are generated. The generated depth images may be viewed on the optical assemblies **180** of an eyewear device, on another display (e.g., the image display **580** on a mobile device **401**), or on a screen.

(54) The generated depth images are in the three-dimensional space domain and can comprise a matrix of vertices on a three-dimensional location coordinate system that includes an X axis for horizontal position (e.g., length), a Y axis for vertical position (e.g., height), and a Z axis for depth (e.g., distance). Each vertex may include a color attribute (e.g., a red pixel light value, a green pixel light value, or a blue pixel light value); a position attribute (e.g., an X location coordinate, a Y location coordinate, and a Z location coordinate); a texture attribute; a reflectance attribute; or a combination thereof. The texture attribute quantifies the perceived texture of the depth image, such as the spatial arrangement of color or intensities in a region of vertices of the depth image.

(55) FIG. 4 is a functional block diagram of an example IMU control system **400** that includes an eyewear device **100**, a mobile device **401**, and a server system **498** connected via various networks **495** such as the Internet. As shown, the IMU control system **400** includes a low-power wireless connection **425** and a high-speed wireless connection **437** between the eyewear device **100** and the mobile device **401**.

(56) The eyewear device **100** includes one or more cameras **114** that capture still images, video images, or both still and video images, as described herein. The cameras **114** may have a direct memory access (DMA) to high-speed circuitry **430** and function as a stereo camera. The cameras **114** may be used to capture initial-depth images that may be rendered into three-dimensional (3D) models that are texture-mapped images of a red, green, and blue (RGB) imaged scene. The device **100** may also include a depth sensor that uses infrared signals to estimate the position of objects relative to the device **100**. The depth sensor in some examples includes one or more infrared emitter(s) and infrared camera(s) **410**.

(57) The eyewear device **100** further includes two image displays of optical assemblies **180** (one associated with the right side **170A** and one associated with the left side **170B**). The eyewear device **100** also includes an image display driver **442**, an image processor **412**, low-power circuitry **420**, and high-speed circuitry **430**. The image displays of optical assemblies **180** are for presenting images, including still images, video images, or still and video images. The image display driver **442** is coupled to the image displays of optical assemblies **180** in order to control the display of images.

(58) The components shown in FIG. 4 for the eyewear device **100** are located on one or more circuit boards, for example a printed circuit board (PCB) or flexible printed circuit (FPC), located in the rims or temples. Alternatively, or additionally, the depicted components can be located in the corners, frames, hinges, or bridge of the eyewear device **100**. The cameras **114** include digital camera elements such as a complementary metal-oxide-semiconductor (CMOS) image sensor, a charge-coupled device, a lens, or any other respective visible or light capturing elements that may be used to capture data, including still images or video of scenes with unknown objects.

(59) As shown in FIG. 4, high-speed circuitry **430** includes a high-speed processor **432**, a memory **434**, and high-speed wireless circuitry **436**. In the example, the image display driver **442** is coupled to the high-speed circuitry **430** and operated by the high-speed processor **432** in order to drive the image displays of optical assemblies **180**. High-speed processor **432** may be essentially any processor capable of managing high-speed communications and operation of any general computing system. High-speed processor **432** includes processing resources needed for managing high-speed data transfers on high-speed wireless connection **437** to a wireless local area network (WLAN) using high-speed wireless circuitry **436**.

(60) In some examples, the high-speed processor **432** executes an operating system such as a LINUX operating system or other such operating system of the eyewear device **100** and the operating system is stored in memory **434** for execution. In addition to any other responsibilities, the high-speed processor **432** executes a software architecture for the eyewear device **100** that is used to manage data transfers with high-speed wireless circuitry **436**. In some examples, high-speed wireless circuitry **436** is configured to implement Institute of Electrical and Electronic Engineers (IEEE) 802.11 communication standards, also referred to herein as Wi-Fi. In other examples, other high-speed communications standards may be implemented by high-speed wireless circuitry **436**.

(61) The low-power circuitry **420** includes a low-power processor **422** and low-power wireless circuitry **424**. The low-power wireless circuitry **424** and the high-speed wireless circuitry **436** of the eyewear device **100** can include short-range transceivers (Bluetooth™ or Bluetooth Low-Energy (BLE)) and wireless wide, local, or wide-area network transceivers (e.g., cellular or Wi-Fi). Mobile device **401**, including the transceivers communicating via the low-power wireless connection **425** and the high-speed wireless connection **437**, may be implemented using details of

the architecture of the eyewear device **100**, as can other elements of the network **495**.

(62) Memory **434** includes any storage device capable of storing various data and applications, including, among other things, camera data generated by the cameras **114A**, **114B**, the infrared camera(s) **410**, the image processor **412**, and images generated for display by the image display driver **442** on the image display of each optical assembly **180**. Although the memory **434** is shown as integrated with high-speed circuitry **430**, the memory **434** in other examples may be an independent, standalone element of the eyewear device **100**. In some such examples, electrical routing lines may provide a connection through a chip that includes the high-speed processor **432** from the image processor **412** or low-power processor **422** to the memory **434**. In other examples, the high-speed processor **432** may manage addressing of memory **434** such that the low-power processor **422** will boot the high-speed processor **432** any time that a read or write operation involving memory **434** is to be performed.

(63) As shown in FIG. 4, various elements of the eyewear device **100** can be coupled to the low-power circuitry **420**, high-speed circuitry **430**, or both. For example, the infrared camera **410** (including in some implementations an infrared emitter), the user input elements **491** (e.g., a button switch, a touchpad **181**, a microphone **139**), and the inertial measurement unit (IMU) **472** may be coupled to the low-power circuitry **420**, high-speed circuitry **430**, or both.

(64) As shown in FIG. 5, which is discussed in further detail below, the CPU **540** of the mobile device **401** may be coupled to a camera system **570**, a mobile display driver **582**, a user input layer **591**, and a memory **540A**.

(65) The server system **498** may be one or more computing devices as part of a service or network computing system, for example, that include a processor, a memory, and network communication interface to communicate over the network **495** with an eyewear device **100** and a mobile device **401**.

(66) The output components of the eyewear device **100** include visual elements, such as the image displays associated with each lens or optical assembly **180** as described with reference to FIGS. 2A and 2B (e.g., a display such as a liquid crystal display (LCD), a plasma display panel (PDP), a light emitting diode (LED) display, a projector, or a waveguide). The eyewear device **100** may include a user-facing indicator (e.g., an LED, a speaker **191**, or a vibrating actuator), or an outward-facing signal (e.g., an LED, a speaker **191**). The image displays of each optical assembly **180** are driven by the image display driver **442**. In some example configurations, the output components of the eyewear device **100** further include additional indicators such as audible elements (e.g., speakers **191**), tactile components (e.g., an actuator such as a vibratory motor to generate haptic feedback), and other signal generators. For example, the device **100** may include a user-facing set of indicators, and an outward-facing set of signals. The user-facing set of indicators are configured to be seen or otherwise sensed by the user of the device **100**. For example, the device **100** may include an LED display positioned so the user can see it, one or more speakers **191** positioned to generate a sound the user can hear, or an actuator to provide haptic feedback the user can feel. The outward-facing set of signals are configured to be seen or otherwise sensed by an observer near the device **100**. Similarly, the device **100** may include an LED, a speaker **191**, or an actuator that is configured and positioned to be sensed by an observer.

(67) The user input elements **491** of the eyewear device **100** may include alphanumeric input components (e.g., a touch screen or touchpad **181** configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric-configured elements), pointer-based input components (e.g., a mouse, a touchpad **181**, a trackball, a joystick, a motion sensor, or other pointing instruments), tactile input components (e.g., a button switch, a touch screen or touchpad **181** that senses the location, force or location and force of touches or touch gestures, or other tactile-configured elements), and audio input components (e.g., a microphone **139**), and the like. The mobile device **401** and the server system **498** may include alphanumeric, pointer-based, tactile, audio, and other input components.

(68) In some examples, the eyewear device **100** includes a collection of motion-sensing components referred to as an IMU **472**. The motion-sensing components may be micro-electro-mechanical systems (MEMS) with microscopic moving parts, often small enough to be part of a microchip. The IMU **472** in some example configurations includes an accelerometer, a gyroscope, and a magnetometer. The accelerometer senses the linear acceleration of the device **100** (including the acceleration due to gravity) relative to three orthogonal axes (x, y, z). The gyroscope senses the angular velocity of the device **100** about three axes of rotation (pitch, roll, yaw). Together, the accelerometer and gyroscope can provide position, orientation, and motion data about the device relative to six axes (x, y, z, pitch, roll, yaw). The magnetometer, if present, senses the heading of the device **100** relative to magnetic north. The position of the device **100** may be determined by location sensors, such as a GPS unit **473**, one or more transceivers to generate relative position coordinates, altitude sensors or barometers, and other orientation sensors. Such positioning system coordinates can also be received over the wireless connections **425**, **437** from the mobile device **401** via the low-power wireless circuitry **424** or the high-speed wireless circuitry **436**.

(69) The IMU **472** may include or cooperate with a digital motion processor or programming that gathers the raw data from the components and compute a number of useful values about the position, orientation, and motion of the device **100**. For example, the acceleration data gathered from the accelerometer can be integrated to obtain the velocity relative to each axis (x, y, z); and integrated again to obtain the position of the device **100** (in linear coordinates, x, y, and z). The angular velocity data from the gyroscope can be integrated to obtain the position of the device **100** (in spherical coordinates). The programming for computing these useful values may be stored in memory **434** and executed by the high-speed processor **432** of the eyewear device **100**.

(70) The eyewear device **100** may optionally include additional peripheral sensors, such as biometric sensors, specialty sensors, or display elements integrated with eyewear device **100**. For example, peripheral device elements may include any I/O components including output components, motion components, position components, or any other such elements described herein. For example, the biometric sensors may include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye tracking), to measure bio signals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), or to identify a person (e.g., identification based on voice, retina, facial characteristics, fingerprints, or electrical bio signals such as electroencephalogram data), and the like.

(71) The mobile device **401** may be a smartphone, tablet, laptop computer, access point, or any other such device capable of connecting with eyewear device **100** using both a low-power wireless connection **425** and a high-speed wireless connection **437**. Mobile device **401** is connected to server system **498** and network **495**. The network **495** may include any combination of wired and wireless connections.

(72) The IMU control system **400**, as shown in FIG. 4, includes a computing device, such as a portable electronic device **401** (e.g., a mobile device), coupled to an eyewear device **100** over a network **495**. The IMU control system **400** includes a memory (e.g., a non-transitory computer readable media) for storing instructions and a processor for executing the instructions. In some implementations, the memory and processing functions of the IMU control system **400** can be shared or distributed across the processors and memories of an eyewear device **100**, a portable electronic device **401** (e.g., a mobile device), and/or a server system **498**.

(73) In some implementations, the IMU control system **400** includes one or more elements or modules, referred to herein as a IMU control application **910**, a localization system **915**, an image processing system **920**, and a voice recognition module **925**.

(74) The IMU control application **910** in some implementations renders and presents a virtual rotational interface **800** on a display, as described herein.

(75) The localization system **915** in some implementations obtains localization data for use in determining the current position of a portable electronic device **401** (e.g., a mobile phone) or an

electronic eyewear device **100** relative to a physical environment **600**. For example, the localization system **915** may access the frames of video data **900** captured using the camera **114B** to determine the current eyewear device location **840** in three-dimensional coordinates relative to the physical environment **600** (with or without reference to data from other sources, such as an inertial measurement unit or IMU **472**). As used herein, the term ‘frames of video data’ refers to the video motion data captured using the one or more cameras **114A**, **114B** coupled to the eyewear device **100**, including images, spatial data, and related information captured using essentially any sensor component of a camera in any form and at any sample rate. In some implementations, the localization data may be derived from the frames of motion data captured using the IMU **472**, from data gathered by a GPS unit **473**, or from a combination thereof.

(76) The image processing system **920** in some implementations generates and presents a virtual rotational interface **800**, as described herein, on the display of a portable electronic device **401** (e.g., a mobile phone) or an electronic eyewear device **100**, in cooperation with the image display driver **442** and the image processor **412**. The virtual rotational interface **800** in some implementations includes one or more virtual surfaces each of which is virtually presented at a surface position **810** in the physical environment **600** relative to the display.

(77) The voice recognition module **925** in some implementations receives human speech, converts the received speech into frames of audio data, identifies an inquiry or a request based on the audio data, and executes an action that is correlated with and responsive to the identified inquiry or request.

(78) FIG. 5 is a high-level functional block diagram of an example mobile device **401**. Mobile device **401** includes a flash memory **540A** which stores programming to be executed by the CPU **540** to perform all or a subset of the functions described herein.

(79) The mobile device **401** may include a camera **570** that comprises at least two cameras (e.g., first and second visible-light cameras with overlapping fields of view) or at least one camera and a depth sensor with substantially overlapping fields of view. Flash memory **540A** may further include multiple images or video, which are generated via the camera **570**.

(80) As shown, the mobile device **401** includes an image display **580**, a mobile display driver **582** to control the image display **580**, and a display controller **584**. In the example of FIG. 5, the image display **580** includes a user input layer **591** (e.g., a touchscreen) that is layered on top of or otherwise integrated into the screen used by the image display **580**.

(81) Examples of touchscreen-type mobile devices that may be used include (but are not limited to) a smart phone, a personal digital assistant (PDA), a tablet computer, a laptop computer, or other portable device. However, the structure and operation of the touchscreen-type devices is provided by way of example; the subject technology as described herein is not intended to be limited thereto. For purposes of this discussion, FIG. 5 therefore provides a block diagram illustration of the example mobile device **401** with a user interface that includes a touchscreen input layer **591** for receiving input (by touch, multi-touch, or gesture, and the like, by hand, stylus, or other tool) and an image display **580** for displaying content.

(82) As shown in FIG. 5, the mobile device **401** includes at least one digital transceiver (XCVR) **510**, shown as WWAN XCVRs, for digital wireless communications via a wide-area wireless mobile communication network. The mobile device **401** also includes additional digital or analog transceivers, such as short-range transceivers (XCVRs) **520** for short-range network communication, such as via NFC, VLC, DECT, ZigBee, Bluetooth™, or Wi-Fi. For example, short range XCVRs **520** may take the form of any available two-way wireless local area network (WLAN) transceiver of a type that is compatible with one or more standard protocols of communication implemented in wireless local area networks, such as one of the Wi-Fi standards under IEEE 802.11.

(83) To generate location coordinates for positioning of the mobile device **401**, the mobile device **401** can include a global positioning system (GPS) receiver. Alternatively, or additionally the

mobile device **401** can utilize either or both the short range XCVRs **520** and WWAN XCVRs **510** for generating location coordinates for positioning. For example, cellular network, Wi-Fi, or Bluetooth™ based positioning systems can generate accurate location coordinates, particularly when used in combination. Such location coordinates can be transmitted to the eyewear device over one or more network connections via XCVRs **510**, **520**.

(84) The mobile device **401** in some examples includes a collection of motion-sensing components referred to as an inertial measurement unit (IMU) **572** for sensing the position, orientation, and motion of the mobile device **401**. The motion-sensing components may be micro-electro-mechanical systems (MEMS) with microscopic moving parts, often small enough to be part of a microchip. The inertial measurement unit (IMU) **572** in some example configurations includes an accelerometer, a gyroscope, and a magnetometer. The accelerometer senses the linear acceleration of the mobile device **401** (including the acceleration due to gravity) relative to three orthogonal axes (x, y, z). The gyroscope senses the angular velocity of the mobile device **401** about three axes of rotation (pitch, roll, yaw). Together, the accelerometer and gyroscope can provide position, orientation, and motion data about the device relative to six degrees of freedom (x, y, z, pitch, roll, yaw) sometimes referred to as 6DOF. The magnetometer, if present, senses the heading of the mobile device **401** relative to magnetic north.

(85) The IMU **572** may include or cooperate with a digital motion processor or programming that gathers the raw data from the components and compute a number of useful values about the position, orientation, and motion of the mobile device **401**. For example, the acceleration data gathered from the accelerometer can be integrated to obtain the velocity relative to each axis (x, y, z); and integrated again to obtain the position of the mobile device **401** (in linear coordinates, x, y, and z). The angular velocity data from the gyroscope can be integrated to obtain the position of the mobile device **401** (in spherical coordinates). The programming for computing these useful values may be stored in on or more memory elements **540A**, **540B**, **540C** and executed by the CPU **540** of the mobile device **401**.

(86) The transceivers **510**, **520** (i.e., the network communication interface) conforms to one or more of the various digital wireless communication standards utilized by modern mobile networks. Examples of WWAN transceivers **510** include (but are not limited to) transceivers configured to operate in accordance with Code Division Multiple Access (CDMA) and 3rd Generation Partnership Project (3GPP) network technologies including, for example and without limitation, 3GPP type 2 (or 3GPP2) and LTE, at times referred to as “4G.” For example, the transceivers **510**, **520** provide two-way wireless communication of information including digitized audio signals, still image and video signals, web page information for display as well as web-related inputs, and various types of mobile message communications to/from the mobile device **401**.

(87) The mobile device **401** further includes a microprocessor that functions as a central processing unit (CPU); shown as CPU **540** in FIG. 4. A processor is a circuit having elements structured and arranged to perform one or more processing functions, typically various data processing functions. Although discrete logic components could be used, the examples utilize components forming a programmable CPU. A microprocessor for example includes one or more integrated circuit (IC) chips incorporating the electronic elements to perform the functions of the CPU. The CPU **540**, for example, may be based on any known or available microprocessor architecture, such as a Reduced Instruction Set Computing (RISC) using an ARM architecture, as commonly used today in mobile devices and other portable electronic devices. Of course, other arrangements of processor circuitry may be used to form the CPU **540** or processor hardware in smartphone, laptop computer, and tablet.

(88) The CPU **540** serves as a programmable host controller for the mobile device **401** by configuring the mobile device **401** to perform various operations, for example, in accordance with instructions or programming executable by CPU **540**. For example, such operations may include various general operations of the mobile device, as well as operations related to the programming

for applications on the mobile device. Although a processor may be configured by use of hardwired logic, typical processors in mobile devices are general processing circuits configured by execution of programming.

(89) The mobile device **401** includes a memory or storage system, for storing programming and data. In the example, the memory system may include a flash memory **540A**, a random-access memory (RAM) **540B**, and other memory components **540C**, as needed. The RAM **540B** serves as short-term storage for instructions and data being handled by the CPU **540**, e.g., as a working data processing memory. The flash memory **540A** typically provides longer-term storage.

(90) Hence, in the example of mobile device **401**, the flash memory **540A** is used to store programming or instructions for execution by the CPU **540**. Depending on the type of device, the mobile device **401** stores and runs a mobile operating system through which specific applications are executed. Examples of mobile operating systems include Google Android, Apple IOS (for iPhone or iPad devices), Windows Mobile, Amazon Fire OS, RIM BlackBerry OS, or the like.

(91) The processor **432** within the eyewear device **100** may construct a map of the environment surrounding the eyewear device **100**, determine a location of the eyewear device within the map of the environment, and determine a relative position of the eyewear device to one or more objects in the mapped environment. The processor **432** may construct the map and determine location and position information using a simultaneous localization and mapping (SLAM) algorithm applied to data received from one or more sensors. Sensor data includes images received from one or both of the cameras **114A**, **114B**, distance(s) received from a laser range finder, position information received from a GPS unit **473**, motion and acceleration data received from an IMU **572**, or a combination of data from such sensors, or from other sensors that provide data useful in determining positional information. In the context of augmented reality, a SLAM algorithm is used to construct and update a map of an environment, while simultaneously tracking and updating the location of a device (or a user) within the mapped environment. The mathematical solution can be approximated using various statistical methods, such as particle filters, Kalman filters, extended Kalman filters, and covariance intersection. In a system that includes a high-definition (HD) video camera that captures video at a high frame rate (e.g., thirty frames per second), the SLAM algorithm updates the map and the location of objects at least as frequently as the frame rate; in other words, calculating and updating the mapping and localization thirty times per second.

(92) Sensor data includes image(s) received from one or both cameras **114A**, **114B**, distance(s) received from a laser range finder, position information received from a GPS unit **473**, motion and acceleration data received from an IMU **472**, or a combination of data from such sensors, or from other sensors that provide data useful in determining positional information.

(93) FIG. 6 depicts an example physical environment **600** along with elements that are useful when using a SLAM algorithm (Simultaneous Localization and Mapping) and other types of tracking applications (e.g., natural feature tracking (NFT), hand tracking, foot tracking, etc.). A user **602** of a portable electronic device **401** (e.g., a mobile phone) and an electronic eyewear device **100** is present in an example physical environment **600** (which, in FIG. 6, is an interior room). The processor **432** of the eyewear device **100** (or the processor of the mobile phone **401**) determines the position of the electronic device **100**, **401** with respect to one or more physical objects **604** (e.g., including IoT objects **50**) within the environment **600** using captured image data, constructs a map of the environment **600** using a coordinate system (e.g., a Cartesian coordinate system (x, y, z)) for the environment **600**, and determines the position of the device **100**, **401** relative to the coordinate system. Additionally, the processor in some implementations determines a precise orientation and location (x-prime, y-prime, z-prime, roll, pitch, and yaw) of the portable electronic device **401** or the eyewear device **100** within the environment by using two or more location points (e.g., three location points **606a**, **606b**, and **606c**) associated with a single object **604a**, or by using one or more location points **606** associated with two or more objects **604a**, **604b**, **604c**. An application on the portable electronic device **401** or the eyewear device **100** may present a virtual object **608** (such as

the key shown in FIG. 6) within the environment 600 for viewing on a display during an augmented reality experience.

(94) The localization system 915 in some examples includes a virtual marker 610a associated with a virtual object 608 in the physical environment 600. In an augmented reality environment, in some implementations, markers are registered at locations in the physical environment 600 to assist electronic devices with the task of tracking and updating the location of users, devices, and objects (virtual and physical) relative to the physical environment. Markers are sometimes registered to a high-contrast physical object, such as the relatively dark object, such as the framed picture 604a, mounted on a lighter-colored wall, to assist cameras and other sensors with the task of detecting the marker. The markers may be assigned and registered in a memory by the eyewear device 100 operating within the environment. In some implementations, the markers are assigned and registered in the memory of other devices in the network.

(95) The localization system 915 tracks physical objects and virtual objects within the physical environment 600 relative to the eyewear device 100. For a physical object 604 (e.g., the example floor safe 604c, the example IoT object 50) the localization system 915 continuously analyzes captured images of the physical environment 600 to identify the object 604 and to determine its location relative to the eyewear device 100 (e.g., by applying a SLAM algorithm). The localization system 915 maintains and updates the determined location information for the physical object 604 in memory, thereby tracking the physical object 604 as the eyewear device 100 if and when it moves through the physical environment 600. For a virtual object 608 (e.g., key) the localization system 915 establishes or designates an initial location for the virtual object 608 corresponding to a location or a physical object 604 in the environment 600 (or, in some implementations, at a location relative to the eyewear device 100). The localization system 915 maintains and updates the virtual object 608 location information, for example, in accordance with a movement algorithm associated with the virtual object 608, in response to movement of the eyewear device 100 through the environment, or a combination thereof, thereby tracking the virtual object 608 as the eyewear device 100 moves through the environment.

(96) Markers can be encoded with or otherwise linked to information. A marker might include position information, a physical code (such as a bar code or a QR code; either visible to the user or hidden), or a combination thereof. A set of data associated with the marker is stored in the memory 434 of the eyewear device 100. The set of data includes information about the marker 610a, the marker's position (location and orientation), one or more virtual objects, or a combination thereof. The marker position may include three-dimensional coordinates for one or more marker landmarks 616a, such as the corner of the generally rectangular marker 610a shown in FIG. 6. The marker location may be expressed relative to real-world geographic coordinates, a system of marker coordinates, a position of the eyewear device 100, or other coordinate system. The one or more virtual objects associated with the marker 610a may include any of a variety of materials, including still images, video, audio, tactile feedback, executable applications, interactive user interfaces and experiences, and combinations or sequences of such material. Any type of content capable of being stored in a memory and retrieved when the marker 610a is encountered or associated with an assigned marker may be classified as a virtual object in this context. The virtual key 608 shown in FIG. 6, for example, is a virtual object displayed as a still image, either 2D or 3D, at a marker location.

(97) In one example, the marker 610a may be registered in memory as being located near and associated with a physical object 604a (e.g., the framed work of art shown in FIG. 6). In another example, the marker may be registered in memory as being a particular position with respect to the eyewear device 100.

(98) FIG. 7 is a flow chart 700 of an example method of controlling an IoT product 50 using a portable electronic device 401. Although the steps are described with reference to the portable electronic device 401 (e.g., a mobile phone) or the eyewear device 100 described herein, other

implementations of the steps described, for other types of devices, will be understood by one of skill in the art from the description herein. One or more of the steps shown and described may be performed simultaneously, in a series, in an order other than shown and described, or in conjunction with additional steps. Some steps may be omitted or, in some applications, repeated. (99) The IMU control application **910** described herein, in some implementations, launches in response to receiving a selection through a user interface (e.g., selecting from a menu, pressing a button, using a touchpad) or through some other input means (e.g., a hand gesture detected in captured images, a finger touch **681** on the touchpad **181**, a voice command).

(100) In some implementations, an IoT product **50** (e.g., a lamp, a speaker, a fan) is paired with a portable electronic device **401** or an electronic eyewear device **100**. Some IoT products **50** include an application programming interface (API) (e.g., a product API) that allows the IoT product **50** to pair with and otherwise communicate with other products and electronic devices, such as portable electronic devices **401** and electronic eyewear devices **100**. In some implementations, the product API includes information such as a product type (e.g., lamp, speaker, fan) and, in some implementations, a list of the one or more controllable features **56** (e.g., on, off, brightness, color temperature, hue, volume, speed) associated with the IoT product **50**.

(101) FIG. **8A** is an illustration of an example virtual rotational interface **800** presented on the display **580** of a portable electronic device **401**. In this example, the IoT product **50** is a lamp, as shown. The IoT product **50** is present and observable, of course, in the physical environment **600**. The virtual rotational interface **800** is observable when presented on the display **580** by the IMU control application **910** described herein.

(102) The IMU control application **910** in some implementations controls the process of pairing the IoT product **50** with the portable electronic device **410**. The process of pairing in some implementations uses the product API. In some implementations, the IoT product **50** includes an associated product API which includes a product type (e.g., “lamp”) and a list of the one or more controllable features **56** (e.g., brightness, color temperature, hue).

(103) FIG. **8B** is an illustration of an example interaction between the portable electronic device **401** and the virtual rotational interface **800** of FIG. **8A**, resulting in a corresponding IoT action **60** (e.g., decreasing the brightness of the lamp).

(104) FIG. **9** is an illustration of an example interaction between a portable electronic device **401** and an example virtual rotational interface **800** presented on the display **182B** of an electronic eyewear device **100**. The eyewear device **100** in some implementations includes a voice recognition module **925**, as described herein, and a microphone **139** coupled to a speaker **191**. The voice recognition module **925** in some implementations configures the processor **432** to perceive human speech, convert the received speech into frames of audio data, identify a first inquiry based on converted frames of audio data, and then perform an action in response to and in accordance with the identified first inquiry. For example, the human speech may include a verbal command (e.g., “show virtual rotational interface”) and, in response, the identified first inquiry causes the IMU control application **910** to present a virtual rotational interface **800** on the display.

(105) In some implementations, an IoT product **50** does not include an API. An IoT product **50** is typically connected to the internet or to other products in a network. Because of this connectivity, the communications between and among IoT products **50** generally includes data or information indicating the product type (e.g., lamp, speaker, fan). In this aspect, the product type is generally known, even when the IoT product **50** does not include a product API. In some implementations, the IMU control application **910** described herein includes an inference engine that is configured to infer a set of probable controllable features **56** associated with an IoT product **50** based on the product type alone. For example, an IoT product **50** may be sharing data that indicates the product type is “speaker.” The inference engine, in some implementations, will infer a set of probable controllable features **56** (e.g., on, off, variable volume, list of available nature sounds) because such features are generally associated with a particular product type (e.g., a speaker or sound system).

For another example, when the product type is a “fan,” the inference engine, in some implementations, will infer a set of probable controllable features **56** (e.g., an on-off toggle switch for power, a variable fan speed (from a minimum to a maximum), a set of predefined fan speeds (low, medium, high), an on-off toggle switch for oscillating (still or moving), and the like). When the product type is an “LED lamp,” the inference engine, in some implementations, will infer a set of probable controllable features **56** (e.g., an on-off toggle switch for power, a variable brightness (from a minimum to a maximum value), a variable color selection (in a continuous cycle of hues or colors), and the like).

(106) Block **702** in FIG. **7** recites an example step of capturing frames of video data **900** with the camera **570** of a portable electronic device **401**. In some implementations, the process of capturing frames of video data **900** is ongoing during active use of the portable device **401**. In other examples, the process of capturing starts in response to receiving a selection through a user interface or through some other input means. The example method step, at block **702**, in some implementations, includes storing the captured frames of video data **900** in memory on the portable electronic device **401**, at least temporarily, such that the frames of video data **900** are available for uses including processing and analysis.

(107) Block **704** in FIG. **7** recites an example step of detecting an IoT product **50** at an IoT product location **790** in a physical environment **600** based on the captured frames of video data **900**. As described herein, the IoT product **50** in some implementations is already paired with or otherwise in wireless communication with the portable electronic device **401**. In this aspect, the process of detecting occurs when (and for as long as) the IoT product **50** is within a threshold proximity of the portable electronic device **401**.

(108) FIG. **8A** illustrates an example IoT product **50** located in the physical environment **600** at an IoT product location **790**.

(109) In some implementations the process of detecting an IoT product **50** includes determining or estimating an IoT product location **790** relative to the physical environment **600**. The current IoT product location **790** in some implementations is estimated using the localization system **915** as described herein.

(110) The localization system **915** in some implementations configures the IMU control application **910** to obtain localization data based on the captured frames of video data **900** and, in some implementations, based on the motion data gathered by an inertial measurement unit (IMU). In some implementations, the localization system **915** constructs a virtual map of one or more objects within the camera field of view **904** using a SLAM algorithm, as described herein, updating the map and the location of objects at least as frequently as the camera captures video data **900**.

(111) The process of determining or estimating the IoT product location **790** relative to the physical environment **600** in some implementations includes calculating a correlation between the IoT product location **790** and the current portable electronic device location **440** (as shown in FIG. **8A**). The term correlation refers to and includes one or more vectors, matrices, formulas, or other mathematical expressions sufficient to define the three-dimensional distance between the IoT product location **790** and the current portable electronic device location **440**. Because the localization process occurs frequently, the process of correlation between the IoT product location **790** and the portable electronic device location **440** produces accurate and near real-time tracking of the IoT product location **790** relative to the portable electronic device location **440**.

(112) Block **706** recites an example step of determining the portable electronic device location **440** relative to the IoT product location **790** using the captured frames of video data **900**. As the portable electronic device **401** moves through the physical environment **600** its location changes relative to the IoT product location **790**.

(113) FIG. **8A** illustrates an example portable electronic device **410** located in the physical environment **600** at a portable electronic device location **440**.

(114) The portable electronic device location **440** in some implementations is estimated using the

localization system **915** as described herein.

(115) The process of determining or estimating portable electronic device location **440** relative to the IoT product location **790** in some implementations includes calculating a correlation between the two locations. The term correlation refers to and includes one or more vectors, matrices, formulas, or other mathematical expressions sufficient to define the three-dimensional distance between the current portable electronic device location **440** and the current IoT product location **790**. Because the localization process occurs frequently, the process of correlation produces accurate and near real-time tracking of the portable electronic device location **440** relative to the IoT product location **790**. In some implementations, the process of estimating the current portable electronic device location **440** is based on the frames of motion data captured using an IMU, or on the frames of video data **900** captured using a camera, or a combination of both.

(116) Block **708** in FIG. **7** recites an example step of detecting a device orientation **80** relative to the physical environment **600** using the IMU **572**. FIG. **8A** shows an example portable electronic device **401** having a device orientation **80a** relative to the physical environment **600**. FIG. **8B** shows the device **401** at a new device orientation **80b** relative to the physical environment **600**. FIG. **9** shows an example eyewear device **100** having a device orientation **80c** relative to the physical environment **600**.

(117) In some implementations the IMU **572** alone is used in the process of detecting the device orientation **80**. By contrast, the captured frames of video data **900** are used in the process at block **706** of determining the portable electronic device location **440**. In some instances, the device orientation **80** and the portable electronic device location **440** are nearly identical. Both values **80**, **440** include coordinates in three dimensions.

(118) In some instances (e.g., when the device orientation **80** or the IMU data is not available) the process of detecting the device orientation **80** includes selecting and using the portable electronic device location **440** as the device orientation **80**. Similarly, the device orientation **80** may be used as the portable electronic device location **440** in some instances (e.g., when the portable electronic device location **440** or the video data **900** are not available).

(119) As described herein, the IMU **572** on the portable electronic device **401** (and the IMU **572** of the eyewear device **100**) in some implementations includes a collection of motion-sensing components. The motion-sensing components may be micro-electro-mechanical systems (MEMS) with microscopic moving parts, often small enough to be part of a microchip. The IMU **472**, **572** in some example configurations includes an accelerometer, a gyroscope, and a magnetometer. The accelerometer senses the linear acceleration of the device **401**, **100** (including the acceleration due to gravity) relative to three orthogonal axes (x, y, z). The gyroscope senses the angular velocity of the device **401**, **100** about three axes of rotation (pitch, roll, yaw). Together, the accelerometer and gyroscope can provide position, orientation, and motion data about the device **401**, **100** relative to six degrees of freedom (x, y, z, pitch, roll, yaw). The magnetometer, if present, senses the heading of the device relative to magnetic north.

(120) In some implementations the process of detecting the device orientation **80** includes detecting a starting device orientation **81** (e.g., generally vertical, as shown in FIG. **8A**) and associating the starting device orientation **81** with a current value of one of the controllable features **56** (e.g., the brightness). In the example shown in FIG. **8A**, the example current value happens to be 100%; however, this is not always the case. In some implementations, the process of detecting the device orientation **80** includes presenting a highlight or other indicia near the slider **802** when the starting device orientation **81** associated with the current value of a feature. In this example, the user is alerted that the portable device **401** is engaged with the slider **802**. The process of detecting a starting device orientation **81** in some implementations occurs when the electronic device location **440** is first detected within a threshold proximity of the IoT product location **790**.

(121) The process of detecting the device orientation **80** in this example also includes detecting a final device orientation **89** (e.g., tilted clockwise, as shown in FIG. **8B**) and associating the final

device orientation **89** with the IoT action **60**. The process of detecting a final device orientation **89** in some implementations occurs when the electronic device location **440** is no longer detected within a threshold proximity of the IoT product location **790**. In other implementations the process of detecting a final device orientation **89** takes place in response to a user input.

(122) Block **810** in FIG. **7** recites an example step of presenting on the display **580** a virtual rotational interface **800** according to the IoT product location **790** and the portable electronic device location **440**. In this example, the virtual rotational interface **800** is presented on the display **580** at a consistent position relative to the IoT product location **790**, even as the portable electronic device **401** moves through the physical environment **600**. For example, as shown in FIG. **8A**, the virtual rotational interface **800** is presented on the display **580** at a viewport position **812** (e.g., near the top or upper section of the IoT lamp **50**).

(123) The process of presenting the virtual rotational interface **800** in some implementations includes moving or otherwise adjusting the viewport position **812** relative to the IoT product **50**. In some implementations, the IMU control application **910** moves or otherwise adjusts the viewport position **812** so the virtual rotational interface **800** will be presented in the foreground relative to the IoT product **50**. In some implementations, the IMU control application **910** moves or otherwise adjusts the viewport position **812** automatically, without user input. The viewport position **812** in some implementations is configurable, such that the process of presenting the virtual rotational interface **800** includes providing the user with one or more tools to adjust or otherwise configure the viewport position **812**.

(124) The process of presenting the virtual rotational interface **800** in some implementations includes providing the user with one or more tools to adjust or otherwise configure the virtual rotational interface **800**, as described herein, or to start and stop the presentation selectively. For example, the user may pause or stop (or re-start) the process of presenting the virtual rotational interface **800** by speaking a voice command, pressing a push button on the eyewear device **100**, executing a hand gesture, or tapping a finger touch **681** on the touchpad **181**.

(125) The virtual rotational interface **800** in some implementations includes a slider **802** virtually presented at a slider position **804**, as shown in FIG. **8B**, according to the detected device orientation **80**. For example, in FIG. **8B**, the slider position **804** (e.g., in position along the viewport **806** at a clockwise distance from the starting position shown in FIG. **8A**) which corresponds to the detected device orientation **80** (e.g., the mobile device **401** has been rotated clockwise relative to its starting orientation).

(126) In some implementations, as shown in FIG. **8A**, the virtual rotational interface **800** includes a plurality of sliders **802** (e.g., slider **802** located on the right viewport **806**, and slider **802b** located on the left viewport). The arched viewports in this example are presented in a semi-circle around the top of the IoT lamp **50**.

(127) The process of presenting a virtual rotational interface **800** in some implementations includes presenting the slider **802** (and the viewport **806** if present) as an overlay relative to the physical environment **600**, such that the virtual rotational interface **800** is persistently viewable in the foreground relative to the real objects in the physical environment **600**. For example, as shown in FIG. **8A**, the virtual rotational interface **800** is presented as an overlay (e.g., in the foreground, in front of the lamp **50**) relative to the physical environment **600** (e.g., the lamp **50** and the walls behind it), such that the virtual rotational interface **800** is persistently viewable relative to other objects in the physical environment **600**.

(128) In some implementations, the process of presenting a virtual rotational interface **800** includes rendering or otherwise graphically generating the slider **802** (and the viewport **806** if present) at a predefined and configurable size and shape. For example, as shown in FIG. **8A**, the virtual rotational interface **800** is presented at a size that nearly fills the available space on the display **580**. In some implementations, the relative size of the virtual rotational interface **800** changes automatically, based on the IoT product location **790**, the portable electronic device location **440**,

and the available space on the display **580**.

(129) The process of presenting a virtual rotational interface **800** in some implementations includes presenting indicia at a position on the display **580** near the slider **802**. In some implementations the indicia are associated with one or more of the controllable features **56**. For example, in FIG. **8A**, the indicia include a window displaying a value of 100%. After the slider **802** has moved, as shown in FIG. **8B**, the indicia include a window displaying a value of 59%.

(130) The process of presenting a virtual rotational interface **800** in some implementations includes presenting the interface **800** when the electronic device location **440** is within a threshold proximity of the IoT product **50** (e.g., mathematically evaluating the distance between the electronic device location **440** and the IoT product location **790**). In this example, the virtual rotational interface **800** appears when the electronic device **401** is near the IoT product **50**.

(131) The process of presenting the virtual rotational interface **800** in some implementations includes estimating a plane of device rotation **820** using the IMU **572**. The plane of device rotation **820** generally corresponds to the plane of rotation as detected by the IMU **572** inside the portable device **401**. The device rotation plane **820** in some implementations is an average or median of a series of values gathered by the IMU **572** over time. The device rotation plane **820** is represented graphically in FIG. **8B** by a circular arrow near the top edge of the device **401**. The process at block **710** in some implementations includes presenting the virtual rotational interface **800** in accordance with the estimated device rotation plane **820**, such that the interface **800** appears to be aligned on the display **580** with the plane of device rotation **820** (e.g., as the portable device **410** rotates over time).

(132) Block **712** in FIG. **7** recites an example step of sending a control signal **55** to the IoT product **50** in accordance with the device orientation **80**. The process of sending the control signal **55** in some implementations includes sending the control signal **55** using a wireless transceiver to the IoT product **50**, sending the control signal **55** to a cloud-based service which in turn transmits the control signal **55** to the IoT product **50**, or otherwise broadcasting the control signal **55** using a method and manner to facilitate delivery of the control signal **55** to the IoT product **50**.

(133) The control signal **55** in some implementations includes instructions configured for use by the IoT product **50** to facilitate the execution or performance of the associated IoT action **60**. For example, when a device orientation **80** (e.g., rotated clockwise relative to vertical) corresponds to a particular IoT action **60** (e.g., reducing the brightness), the control signal **55** includes instructions for the IoT product **50** to execute the IoT action **60** (e.g., reducing the brightness accordingly).

(134) Block **714** in FIG. **7** recites an example step of the IoT product **50** executing or otherwise performing the IoT action **60** according to the device orientation **80**. The control signal **55** in some implementations includes instructions for use by the IoT product **50** for performing or otherwise executing the IoT action **60**.

(135) Block **716** in FIG. **7** recites an example step of establishing and calibrating a virtual scale **810**. The IoT product **50** in some implementations includes or is associated with a product API as described herein. The product API in some implementations includes a controllable feature **56** (e.g., brightness) and a range of variable values (e.g., from zero to one hundred percent, from one to eleven, and the like).

(136) The virtual scale **810** in some implementations extends from a low end **811** to a high end **819**. For example, FIG. **8B** shows a viewport **806** extending from a low end **811** in a clockwise direction toward a high end **819**. In this example the low end **811** represents a maximum brightness of 100% and the high end **819** represents a minimum brightness.

(137) The process of calibrating a virtual scale **810** (e.g., low end **811** to high end **819**) includes in some implementations comparing the virtual scale **810** with the range of values **59** (e.g., one hundred to zero) and mathematically correlating the length of the virtual scale **810** (e.g., ninety degrees) to the range of values **59** (e.g., one hundred to zero). In this example, mathematically, each nine-degree increment along the virtual scale **810** correlates with a ten-percent increment in the

brightness values **59**.

(138) The steps are described with reference to the portable electronic device **401** (e.g., a mobile phone). The methods and systems described herein, in some implementations, may be executed and operated on an eyewear device **100**, a mobile phone **401**, or another electronic device. For example, in some implementations, the portable electronic device **401** is an electronic eyewear device **100** as described herein. In this example, the camera **570** is an eyewear camera **114B**, the display **580** is an eyewear display **182B**, the IMU **572** is the eyewear IMU **472**, the memory elements **540A**, **540B**, **540C** are the eyewear memory **434**, and so forth.

(139) In some implementations the methods and systems described herein are processed and executed using a portable electronic device **401** (e.g., a mobile phone) and the virtual rotational interface **800** is presented on the display **580** of the mobile phone **401**, or on the display **182B** of the eyewear device **100**, or both. In this example, the IMU of the mobile phone **401** controls the device orientation **80** and the slider **802**, while the virtual rotational interface **800** is observable by someone wearing an electronic eyewear device **100**.

(140) Any of the functionality described herein for the eyewear device **100**, the mobile device **401**, and the server system **498** can be embodied in one or more computer software applications or sets of programming instructions, as described herein. According to some examples, “function,” “functions,” “application,” “applications,” “instruction,” “instructions,” or “programming” are program(s) that execute functions defined in the programs. Various programming languages can be employed to develop one or more of the applications, structured in a variety of manners, such as object-oriented programming languages (e.g., Objective-C, Java, or C++) or procedural programming languages (e.g., C or assembly language). In a specific example, a third-party application (e.g., an application developed using the ANDROID™ or IOS™ software development kit (SDK) by an entity other than the vendor of the particular platform) may include mobile software running on a mobile operating system such as IOS™, ANDROID™, WINDOWS® Phone, or another mobile operating system. In this example, the third-party application can invoke API calls provided by the operating system to facilitate functionality described herein.

(141) Hence, a machine-readable medium may take many forms of tangible/non-transitory storage medium. Non-volatile storage media include, for example, optical or magnetic disks, such as any of the storage devices in any computer devices or the like, such as may be used to implement the client device, media gateway, transcoder, etc. shown in the drawings. Volatile storage media include dynamic memory, such as main memory of such a computer platform. Tangible transmission media include coaxial cables; copper wire and fiber optics, including the wires that comprise a bus within a computer system. Carrier-wave transmission media may take the form of electric or electromagnetic signals, or acoustic or light waves such as those generated during radio frequency (RF) and infrared (IR) data communications. Common forms of computer-readable media therefore include for example: a floppy disk, a flexible disk, hard disk, magnetic tape, any other magnetic medium, a CD-ROM, DVD or DVD-ROM, any other optical medium, punch cards paper tape, any other physical storage medium with patterns of holes, a RAM, a PROM and EPROM, a FLASH-EPROM, any other memory chip or cartridge, a carrier wave transporting data or instructions, cables or links transporting such a carrier wave, or any other medium from which a computer may read programming code or data. Many of these forms of computer readable media may be involved in carrying one or more sequences of one or more instructions/program code to a processor for execution.

(142) Except as stated immediately above, nothing that has been stated or illustrated is intended or should be interpreted to cause a dedication of any component, step, feature, object, benefit, advantage, or equivalent to the public, regardless of whether it is or is not recited in the claims.

(143) It will be understood that the terms and expressions used herein have the ordinary meaning as is accorded to such terms and expressions with respect to their corresponding respective areas of inquiry and study except where specific meanings have otherwise been set forth herein. Relational

terms such as first and second and the like may be used solely to distinguish one entity or action from another without necessarily requiring or implying any actual such relationship or order between such entities or actions. The terms “comprises,” “comprising,” “includes,” “including,” or any other variation thereof, are intended to cover a non-exclusive inclusion, such that a process, method, article, or apparatus that comprises or includes a list of elements or steps does not include only those elements or steps but may include other elements or steps not expressly listed or inherent to such process, method, article, or apparatus. An element preceded by “a” or “an” does not, without further constraints, preclude the existence of additional identical elements in the process, method, article, or apparatus that comprises the element.

(144) Unless otherwise stated, any and all measurements, values, ratings, positions, magnitudes, sizes, and other specifications that are set forth in this specification, including in the claims that follow, are approximate, not exact. Such amounts are intended to have a reasonable range that is consistent with the functions to which they relate and with what is customary in the art to which they pertain. For example, unless expressly stated otherwise, a parameter value or the like may vary by as much as plus or minus ten percent from the stated amount or range.

(145) In addition, in the foregoing Detailed Description, it can be seen that various features are grouped together in various examples for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the claimed examples require more features than are expressly recited in each claim. Rather, as the following claims reflect, the subject matter to be protected lies in less than all features of any single disclosed example. Thus, the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separately claimed subject matter.

(146) While the foregoing has described what are considered to be the best mode and other examples, it is understood that various modifications may be made therein and that the subject matter disclosed herein may be implemented in various forms and examples, and that they may be applied in numerous applications, only some of which have been described herein. It is intended by the following claims to claim any and all modifications and variations that fall within the true scope of the present concepts.

Claims

1. A method of controlling an Internet of Things (IoT) product using a portable electronic device comprising an inertial measurement unit (IMU), a camera, and a display, wherein the IoT product is associated with a product API comprising a product type and a controllable feature associated with a range of variable values, the method comprising: capturing frames of video data with the camera; detecting the IoT product at an IoT product location relative to a physical environment using the captured frames of video data; determining a portable electronic device location relative to the IoT product location using the captured frames of video data; detecting a device orientation relative to the physical environment using the IMU; presenting on the display, when the IoT product location is within a threshold proximity of the portable electronic device location, a virtual rotational interface at a viewport position according to at least one of the IoT product location or the portable electronic device location, persistently and without regard to the device orientation; associating the device orientation with the controllable feature; presenting relative to the virtual rotational interface a slider at a slider position according to the device orientation; and sending a control signal to the IoT product in accordance with the device orientation, the control signal comprising instructions for use by the IoT product to perform an IoT action relative to the controllable feature.

2. The method of claim 1, wherein the virtual rotational interface comprises a virtual scale extending angularly from a low end to a high end, the method comprising: calibrating the virtual scale according to the range of variable values to produce a calibrated virtual scale; associating the device orientation with the calibrated virtual scale; and presenting the slider according to the device

orientation and the calibrated virtual scale.

3. The method of claim 2, comprising: presenting on the display one or more indicia associated with the slider position relative at least one of the virtual rotational interface, the range of variable values, or the calibrated virtual scale.

4. The method of claim 1, wherein the IoT product comprises a controllable feature characterized by a current value, wherein detecting the device orientation further comprises: detecting a starting device orientation when the portable electronic device location is detected within the threshold proximity; associating the starting device orientation with the current value; detecting a current device orientation; and sending the control signal in accordance with the current device orientation.

5. The method of claim 1, wherein detecting the device orientation further comprises: detecting a final device orientation when the portable electronic device location is no longer detected within the threshold proximity; and sending the control signal in accordance with at least one of the final device orientation or a user input.

6. The method of claim 1, wherein sending the control signal comprises: detecting a selection based on the device orientation; and sending the control signal in accordance with the selection.

7. The method of claim 1, wherein the display is characterized by a display plane, and wherein detecting the device orientation further comprises: estimating a plane of rotation relative to the display plane using the IMU; generating an adjusted device orientation based on the plane of rotation; presenting the slider according to the adjusted device orientation; and sending the control signal in accordance with the adjusted device orientation.

8. The method of claim 1, wherein the virtual rotational interface comprises the slider and an additional slider, the method comprising: selectively presenting at least one of the slider or the additional slider according to the device orientation.

9. A portable electronic device for controlling an Internet of Things (IoT) product, wherein the IoT product is associated with a product API comprising a product type and a controllable feature associated with a range of variable values, the portable electronic device comprising: a processor; a memory; an inertial measurement unit (IMU); a camera; a display; and programming in the memory, wherein execution of the programming by the processor configures the portable electronic device to perform functions, including functions to: capture frames of video data with the camera; detect the IoT product at an IoT product location relative to a physical environment using the captured frames of video data; determine a portable electronic device location relative to the IoT product location using the captured frames of video data; detect a device orientation relative to the physical environment using the IMU; present on the display, when the IoT product location is within a threshold proximity of the portable electronic device location, a virtual rotational interface at a viewport position according to at least one of the IoT product location or the portable electronic device location, persistently and without regard to the device orientation; associate the device orientation with the controllable feature; present relative to the virtual rotational interface a slider at a slider position according to the device orientation; and send a control signal to the IoT product in accordance with the device orientation, the control signal comprising instructions for use by the IoT product to perform an IoT action relative to the controllable feature.

10. The portable electronic device of claim 9, wherein the virtual rotational interface comprises a virtual scale extending angularly from a low end to a high end, and wherein the execution of the programming further configures portable electronic device to perform functions to: calibrate the virtual scale according to the range of variable values to produce a calibrated virtual scale; associate the device orientation with the calibrated virtual scale; and present the slider according to the device orientation and the calibrated virtual scale.

11. The portable electronic device of claim 10, wherein the execution of the programming further configures portable electronic device to perform functions to: present on the display one or more indicia associated with the slider position relative at least one of the virtual rotational interface, the range of variable values, or the calibrated virtual scale.

12. The portable electronic device of claim 9, wherein the IoT product comprises a controllable feature characterized by a current value, and wherein the execution of the programming further configures portable electronic device to perform functions to: detect a starting device orientation when the portable electronic device location is detected within the threshold proximity; associate the starting device orientation with the current value; detect a current device orientation; detect a final device orientation when the portable electronic device location is no longer detected within the threshold proximity; and send the control signal in accordance with at least one of the current device orientation, the final device orientation, or a user input.

13. The portable electronic device of claim 9, wherein the display is characterized by a display plane, and wherein the execution of the programming further configures portable electronic device to perform functions to: estimate a plane of rotation relative to the display plane using the IMU; generate an adjusted device orientation based on the plane of rotation; present the slider according to the adjusted device orientation; and send the control signal in accordance with the adjusted device orientation.

14. The portable electronic device of claim 9, wherein the virtual rotational interface comprises the slider and an additional slider, and wherein the execution of the programming further configures portable electronic device to perform functions to: selectively present at least one of the slider or the additional slider according to the device orientation.

15. A non-transitory computer-readable medium storing program code that, when executed, is operative to cause a processor of a portable electronic device to perform the steps of: capturing frames of video data with a camera coupled to the portable electronic device; detecting an Internet of Things (IoT) product at an IoT product location relative to a physical environment using the captured frames of video data, wherein the IoT product is associated with a product API comprising a product type and a controllable feature associated with a range of variable values; determining a portable electronic device location relative to the IoT product location using the captured frames of video data; detecting a device orientation relative to the physical environment using an inertial measurement unit (IMU) coupled to the portable electronic device; presenting on a display, when the IoT product location is within a threshold proximity of the portable electronic device location, a virtual rotational interface at a viewport position according to at least one of the IoT product location or the portable electronic device location, persistently and without regard to the device orientation; associating the device orientation with the controllable feature; presenting relative to the virtual rotational interface a slider at a slider position according to the device orientation; and sending a control signal to the IoT product in accordance with the device orientation, the control signal comprising instructions for use by the IoT product to perform an IoT action relative to the controllable feature.

16. The non-transitory computer-readable medium storing program code of claim 15, wherein the virtual rotational interface comprises a virtual scale extending angularly from a low end to a high end, and wherein the program code when executed is operative to cause the processor to perform the further steps of: calibrating the virtual scale according to the range of variable values to produce a calibrated virtual scale; associating the device orientation with the calibrated virtual scale; and presenting the slider according to the device orientation and the calibrated virtual scale.

17. The non-transitory computer-readable medium storing program code of claim 15, wherein the display is characterized by a display plane, and wherein the program code when executed is operative to cause the processor to perform the further steps of: estimating a plane of rotation relative to the display plane using the IMU; generating an adjusted device orientation based on the plane of rotation; presenting the slider according to the adjusted device orientation; and sending the control signal in accordance with the adjusted device orientation.
