

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12406600

Kind Code

B2

Date of Patent

September 02, 2025

Inventor(s)

Passero; Abbigael et al.

Appliance model display system

Abstract

A product advertisement system includes (A) a plurality of miniature three-dimensional product models, wherein each product model (i) has a bottom surface, a top surface, and a side surface extending between the top and bottom surfaces; (ii) is a scaled replica of a full-size residential or commercial appliance; and (iii) has a hollow interior configuration with an opening in the bottom surface; and (B) a base configured to retain each product model in a single position thereon. Each product model is manually removable from and replaceable onto the base. The opening in the bottom surface of each product model has a unique shape, and the base includes projections that correspond to each of the openings, with each projection being sized and shaped to matingly engage with a single one of the openings of the product models to retain each product model in its single position on the base.

Inventors: Passero; Abbigael (Thousand Oaks, CA), Duarte Rodriguez; Sergio Fabricio (Oxnard, CA), Gohil; Augusta (Oxnard, CA), Reyes; Justin (Santa Paula, CA), Monfared; Amin (Oxnard, CA)

Applicant: Rheem Manufacturing Company (Atlanta, GA)

Family ID: 90060883

Assignee: Rheem Manufacturing Company (Atlanta, GA)

Appl. No.: 18/240616

Filed: August 31, 2023

Prior Publication Data

Document Identifier

US 20240078938 A1

Publication Date

Mar. 07, 2024

Related U.S. Application Data

Publication Classification

Int. Cl.: **G09F19/00** (20060101); **G09F3/00** (20060101); **G09F9/30** (20060101); **G09F19/12** (20060101)

U.S. Cl.:

CPC **G09F19/125** (20210501); **G09F3/0297** (20130101); **G09F9/30** (20130101);

Field of Classification Search

CPC: G09F (19/125); G09F (3/0297); G09F (9/30); A47F (5/0062); A47F (7/286); A47B (81/00); A63H (33/30); G09B (25/00); G09B (25/02)

USPC: 446/479

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2321339	12/1942	Wadsworth	N/A	N/A
2801754	12/1956	Dorfman	N/A	N/A
3133376	12/1963	Orenstein	446/481	A63H 33/30
3579862	12/1970	Ballen	273/156	G09B 1/10
D296630	12/1987	Renold et al.	N/A	N/A
5239491	12/1992	Mucciacciaro	700/242	G04B 37/127
D507431	12/2004	Goth	N/A	N/A
D543383	12/2006	Edison et al.	N/A	N/A
D555936	12/2006	King	N/A	N/A
D637016	12/2010	Pohl	N/A	N/A
D813575	12/2017	Kraemer	N/A	N/A
D909100	12/2020	Joseph	N/A	N/A
D962681	12/2021	Lou	N/A	N/A
D977308	12/2022	Chen	N/A	N/A
D990206	12/2022	Cheng	N/A	N/A
D996098	12/2022	Goldstein et al.	N/A	N/A

Primary Examiner: Davis; Cassandra

Attorney, Agent or Firm: Eversheds Sutherland (US) LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims priority to and benefit of U.S. Provisional Patent Application No. 63/403,142, filed Sep. 1, 2022, which is incorporated herein by reference.

FIELD OF THE INVENTION

(1) This disclosure is generally in the field of display models used in product advertising, and more particularly to display systems for small-scale replicas of products, such as appliances.

BACKGROUND

(2) The use of conventional advertising brochures and displays for products in retail and distribution stores may be limited by insufficient space available in these locations. Such space challenges may be more acute for relatively larger products and/or extensive product lines. In addition, there is a continual need for innovative approaches to attract potential customers and distinguish advertising displays from those of competitors.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The detailed description is set forth with reference to the accompanying drawings. In some instances, the use of the same reference numerals may indicate similar or identical items. Various embodiments may utilize elements and/or components other than those illustrated in the drawings, and some elements and/or components may not be present in various embodiments. Throughout this disclosure, depending on the context, singular and plural terminology may be used interchangeably.

(2) FIG. 1A is a perspective view of a product advertisement system according to one embodiment of the present disclosure.

(3) FIG. 1B is an exploded, perspective view of a product advertisement system according to the embodiment of the present disclosure shown in FIG. 1A.

(4) FIG. 2 is a perspective view of a base of a product advertisement system according to one embodiment of the present disclosure.

(5) FIG. 3A is a top, perspective view of a miniature three-dimensional product model of one appliance according to one embodiment of the present disclosure.

(6) FIG. 3B is a side view of the miniature three-dimensional product model shown in FIG. 3A.

(7) FIG. 3C is a bottom view of the miniature three-dimensional product model shown in FIG. 3A.

(8) FIG. 4 is a bottom, perspective view of another miniature three-dimensional product model of an appliance according to another embodiment of the present disclosure.

(9) FIG. 5 is a perspective view of a product advertisement system according to another embodiment of the present disclosure, which includes a video display and a product model sensor.

DETAILED DESCRIPTION

(10) A product advertisement system has been developed. In some embodiments, the system includes (A) a plurality of miniature three-dimensional product models, wherein each of the plurality of miniature three-dimensional product models (i) has a bottom surface, a top surface, and at least one side surface extending between the bottom surface and the top surface; (ii) is a scaled replica of a full-size residential or commercial appliance; and (iii) has a hollow interior configuration with an opening in the bottom surface; and (B) a base configured to retain each of the plurality of miniature three-dimensional product models in a single position thereon, each of the plurality of miniature three-dimensional product models being manually removable from and replaceable onto the base, wherein the opening in the bottom surface of each of the plurality of miniature three-dimensional product models has a unique shape, and the base comprises a plurality of projections that correspond to each of the openings, with each of the plurality of projections being sized and shaped to matingly engage with a single one of the openings of the plurality of miniature three-dimensional product models to retain each miniature three-dimensional product model in its single position on the base.

(11) In some other embodiments, the product advertisement system includes (A) a plurality of

miniature three-dimensional product models, wherein each of the plurality of miniature three-dimensional product models (i) has a bottom surface, a top surface, and at least one side surface extending between the bottom surface and the top surface; and (ii) is a scaled replica of a full-size residential or commercial appliance; and (iii) has at least one projection extending from the bottom surface; and (B) a base configured to retain each of the plurality of miniature three-dimensional product models in a single position thereon, each of the plurality of miniature three-dimensional product models being manually removable from and replaceable onto the base, wherein the base has a recess corresponding to the at least one projection of each of the plurality of miniature three-dimensional product models, each recess having a unique shape and/or size, the at least one projection of each of the plurality of miniature three-dimensional product models being sized and shaped to matingly engage with a single one of the recesses in the base to retain each miniature three-dimensional product model in its single position on the base.

(12) In some embodiments, the full-size residential or commercial appliance is selected from pool and spa heaters, heat pumps, filter pumps, water pumps, indirect heat exchangers, boilers, and water heaters (including but not limited to residential or commercial waters, as well as both tanked and tankless water heaters). The miniature three-dimensional product model can be a replica scaled down to any size suitable for display and manual handling by a person. The product models in a particular product advertisement system may be the same scale as one another or a different scale from that of other products in the system.

(13) An example of product advertisement system in accordance with the present disclosure is described in greater detail with reference to FIG. 1A to FIG. 4.

(14) FIGS. 1A-1B show a product advertisement system **100** that includes a base **102**, six miniature three-dimensional product models **104a**, **104b**, **104c**, **104d**, **104e**, and **104f**, and a background wall **106**. The base **102** has an upper tier and a lower tier, wherein the upper tier displays product models **104a**, **104b**, **104c**, and the lower tier displays product models **104d**, **104e**, and **104f**. In FIG. 1A, each product model is retained in its single nested position on the base **102**. In FIG. 1B, each product model is shown removed from its single nested position on the base **102**. The models are configured to be easily manually lifted from and replaced onto their nested positions on the base.

(15) The miniature three-dimensional product models **104a**, **104b**, **104c**, **104d**, **104e**, and **104f**, are scaled replicas of a full-size pool or spa appliance, including heat pumps, variable speed water pumps, cartridge filters, residential pool and spa heater, and commercial pool heaters. In other embodiments, the product models are other types of residential and commercial appliances, including HVAC equipment and household (e.g., kitchen) appliances. In some embodiments, the miniature three-dimensional product models are replicas that are scaled from 2% to 10% of the sizes of the actual products. In some preferred embodiments, the model scales range from 3% to 6% of the sizes of the actual products.

(16) The background wall **106** is configured for placement adjacent to the base **102** and is sized to extend above the plurality of miniature three-dimensional product models on the base. The background wall may be removably attached to the base and may include various product images and/or description.

(17) In certain embodiments, the base **102** includes a QR code **108** proximate to the nesting position of each of the miniature three-dimensional product models on the base, which is visible when the models are in the nested position. In other embodiments, a barcode or other machine-readable code may be used in place of, or in combination with, the QR code. In some embodiments, each QR code **108** is unique and provides a link to a website page with further information about the product of which the model is a replica. Such information may include product specifications, pricing, availability, etc.

(18) FIG. 2 shows base **102** in further detail. The base **102** include upper tier surface **220** from which projections **208a**, **208b**, and **208c** extend. The base **102** also include lower tier surface **222** from which projections **208d** and **208f** extend. Each of projections **208a**, **208b**, **208c**, **208d**, and

208f has unique size and/or shape that corresponds to an opening in the bottom surface of one of the product models, to matingly engage with a single one of the openings of the miniature three-dimensional product models. In this way, the base **102** is configured to retain each of product models **104a**, **104b**, **104c**, **104d**, and **104f** in a single position in the base **102**, with each of these product models being manually removable from and replaceable onto the base **102**.

(19) FIG. 2 also shows that the lower tier surface **222** includes a pair of slots **209**. These slots correspond to a pair of projections extending from a bottom surface of one of the product models, in this case product model **104e**. In various embodiments, the base may include only openings, only projections, or a combination of openings and projections.

(20) FIG. 2 also shows a plurality of sensors **210** located in the base **102**. The sensors **210** are configured to detect removal of each of the miniature three-dimensional product models from its position on the base. The sensors also may be further configured to detect replacement of each of the miniature three-dimensional product models onto its position on the base. Each sensor **210** may be associated with each of the product models, for example, in a location on a surface of the base in an area about, e.g., under, each of the product models, or on/in one of the projections. Alternatively, the sensor may be located in each of the plurality of miniature three-dimensional product models. Any suitable sensor known in the art may be adapted for use in the advertising system. For example, the sensor may detect a change in pressure, light, electrical or magnetic field, that occurs when as a product model is moved into and out of its nesting position on the base. Upon detecting removal of a product model from its nesting position on the base, the sensor may send a signal to trigger actuation of another feature of the advertising system. For example, the advertising system may further include a video display and/or a speaker; memory configured to store computer-executable instructions; and a computer processor configured to access the memory and execute the computer-executable instructions to: determine, based a signal from a sensor, that one of the miniature three-dimensional product models has been removed from its nesting position on the base; and then to display motion or still images, on the video display, and/or to play an audio recording through the speaker, providing information, for example, related to the product corresponding to the particular product model removed.

(21) FIG. 5 illustrates one embodiment of an advertising system **500**, which has a base **502** and a sensor **508** located on projection **510**. The product models are omitted from this image. Sensor **508** is operatively connected to controller and memory electronics **540**, which in turn are operatively connected to video display **550** and speaker **555**, which are mounted on a background wall **570**. Additional advertising images and/or text can be provided on background walls **570** and **572**. With a product model removed from its nesting position on projection **510**, the sensor **508** triggers, via the controller and memory electronics **540**, the video display **550** and speaker to play one or more pre-recorded audiovisual messages. The sensor, controller, video display, and speaker components and modules are those known in the art, and can be operably connected with wired and/or wireless connections known in the art, and powered with appropriate electrical power sources, for example rechargeable batteries and/or power cables connectable to conventional power outlets.

(22) FIGS. 3A-3C show one embodiment of a miniature three-dimensional product model **104a**. The product model **104a** has a bottom surface **502**, a top surface **504**, and a side surface **506** extending between the bottom surface and the top surface. The product model **104a** has an opening **512** in the bottom surface **502**. The product model **104a** has a body **508** having hollow interior configuration that is accessible via the opening **512**. As used herein, the term “hollow” refers to the model having an interior configuration in which an open volume is defined within the side surface of the model. In some embodiments, the open volume may define the opening in the bottom surface. For example, in certain embodiments, the hollow interior configuration includes the opening and additional volume extending between the bottom surface and the top surface of the model. In some embodiments, the product model consists of a single monolithic structure. In some other embodiments, the product model may include two or more components. For example,

product model **104a** may be constructed by (i) making the body **508**, e.g., by 3D printing; (ii) making fan grill **510**, and then (iii) using an adhesive to attach fan grill **510** to body **508**.

(23) FIG. 4 shows another embodiment of a miniature three-dimensional product model **400**. The bottom surface **402** includes an opening **412** which is configured to matingly engage with a single projection on a base of product advertising system as described herein. In this case, the opening **412** has a keyhole design.

(24) In other embodiments, the projections and recesses of the base and the respective openings and projections may have a variety of other peripheral shapes, such as square, rectangular, or circular, and may have a keyhole notches, chamfered or beveled corners, and the like. Essentially any suitable geometry may be used, so long as the openings/projections in of each of the miniature three-dimensional product models has unique shape and/or size to provide a single nesting location and nesting orientation for each product model on the base.

(25) The miniature three-dimensional product models may be produced by any suitable method. In some embodiments, the models are produced by a process comprising molding and/or additive manufacturing, such as 3D printing, e.g., polymeric materials known in the art of 3D printing. In some embodiments, the product model has at least one sidewall that defines the at least one side surface. In some embodiments, the at least one sidewall has a thickness of at least 0.05 inches (1.3 mm) which was found to provide the product models with sufficient rigidity and good features resolution. In some embodiments, the side walls have a thickness from about 0.05 inches (1.3 mm) to about 0.5 inches (13 mm). The walls of the product models may be driven by the size of the boss, or projection, on which the product model nests.

(26) In some embodiments, the top surface and the at least one side surface of each miniature three-dimensional product models is finished by a vapor smoothing process, as known in the art.

(27) It should be apparent that the foregoing relates only to certain embodiments of the present disclosure and that numerous changes and modifications may be made herein by one of ordinary skill in the art without departing from the general spirit and scope of the disclosure.

(28) Although specific embodiments of the disclosure have been described, numerous other modifications and alternative embodiments are within the scope of the disclosure. For example, any of the functionality described with respect to a particular device or component may be performed by another device or component. Further, while specific device characteristics have been described, embodiments of the disclosure may relate to numerous other device characteristics. Further, although embodiments have been described in language specific to structural features and/or methodological acts, it is to be understood that the disclosure is not necessarily limited to the specific features or acts described. Rather, the specific features and acts are disclosed as illustrative forms of implementing the embodiments. Conditional language, such as, among others, “can,” “could,” “might,” or “may,” unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments could include, while other embodiments may not include, certain features, elements, and/or steps. Thus, such conditional language is not generally intended to imply that features, elements, and/or steps are in any way required for one or more embodiments.

Claims

1. A product advertisement system comprising: a plurality of miniature three-dimensional product models, wherein each of the plurality of miniature three-dimensional product models (i) has a bottom surface, a top surface, and at least one side surface extending between the bottom surface and the top surface; (ii) is a scaled replica of a full-size residential or commercial appliance; and (iii) has a hollow interior configuration with an opening in the bottom surface; and a base configured to retain each of the plurality of miniature three-dimensional product models in a single position thereon, each of the plurality of miniature three-dimensional product models being

manually removable from and replaceable onto the base, wherein the opening in the bottom surface of each of the plurality of miniature three-dimensional product models has a unique shape, and the base comprises a plurality of projections that correspond to each of the openings, with each of the plurality of projections being sized and shaped to matingly engage with a single one of the openings of the plurality of miniature three-dimensional product models to retain each miniature three-dimensional product model in its single position on the base, wherein the system further comprises one or more sensors located in the base and/or in the plurality of miniature three-dimensional product models, wherein the one or more sensors are configured to detect removal of each of the plurality of miniature three-dimensional product models from its position on the base.

2. The product advertisement system of claim 1, wherein the base comprises an upper tier and a lower tier, and a first portion of the plurality of projections is located on the upper tier and the remainder of the plurality of projections is located on the lower tier.
3. The product advertisement system of claim 2, wherein the upper tier is configured to display a single row of three or more of the plurality of miniature three-dimensional product models.
4. The product advertisement system of claim 2, wherein the lower tier is configured to display a single row of three or more of the plurality of miniature three-dimensional product models.
5. The product advertisement system of claim 1, wherein the plurality of miniature three-dimensional product models are produced by a process comprising molding and/or additive manufacturing.
6. The product advertisement system of claim 5, wherein the plurality of miniature three-dimensional product models are produced by a process comprising 3D printing.
7. The product advertisement system of claim 5, wherein each of the plurality of miniature three-dimensional product models is a monolithic structure or consists of only two components secured to one another.
8. The product advertisement system of claim 5, wherein the top surface and the at least one side surface of each of the plurality of miniature three-dimensional product models has been finished by a vapor smoothing process.
9. The product advertisement system of claim 1, wherein the one or more sensors are further configured to detect replacement of each of the plurality of miniature three-dimensional product models onto its position on the base.
10. The product advertisement system of claim 1, further comprising: a video display; memory configured to store computer-executable instructions; and at least one computer processor configured to access the memory and execute the computer-executable instructions to: determine, based a signal from the one or more sensors, that one of the plurality of miniature three-dimensional product models has been removed from its position on the base; and display motion or still images, on the video display, corresponding to the miniature three-dimensional product models that has been determined to have been removed from its position on the base.
11. The product advertisement system of claim 1, wherein the base further comprises a barcode, a QR code, or other machine-readable code disposed proximate to the position of each of the plurality of miniature three-dimensional product models on the base.
12. The product advertisement system of claim 1, further comprising a background wall configured for placement adjacent to the base and sized to extend above the plurality of miniature three-dimensional product models on the base.
13. The product advertisement system of claim 1, wherein the full-size residential or commercial appliance is selected from pool and spa heaters, heat pumps, filter pumps, water pumps, indirect heat exchangers, boilers, and water heaters.
14. A product advertisement system comprising: a plurality of miniature three-dimensional product models, wherein each of the plurality of miniature three-dimensional product models (i) has a bottom surface, a top surface, and at least one side surface extending between the bottom surface and the top surface; and (ii) is a scaled replica of a full-size residential or commercial appliance;

and (iii) has at least one projection extending from the bottom surface; and a base configured to retain each of the plurality of miniature three-dimensional product models in a single position thereon, each of the plurality of miniature three-dimensional product models being manually removable from and replaceable onto the base, wherein the base has a recess corresponding to the at least one projection of each of the plurality of miniature three-dimensional product models, each recess having a unique shape and/or size, the at least one projection of each of the plurality of miniature three-dimensional product models being sized and shaped to matingly engage with a single one of the recesses in the base to retain each miniature three-dimensional product model in its single position on the base, wherein the system further comprises one or more sensors located in the base and/or in the plurality of miniature three-dimensional product models, wherein the one or more sensors are configured to detect removal of each of the plurality of miniature three-dimensional product models from its position on the base.

15. The product advertisement system of claim 14, wherein the base comprises an upper tier and a lower tier, and a first portion of the plurality of projections is located on the upper tier and the remainder of the plurality of projections is located on the lower tier.

16. The product advertisement system of claim 14, wherein the one or more sensors are further configured to detect replacement of each of the plurality of miniature three-dimensional product models onto its position on the base.

17. The product advertisement system of claim 14, wherein the base further comprises a barcode, a QR code, or other machine-readable code disposed proximate to the position of each of the plurality of miniature three-dimensional product models on the base.

18. The product advertisement system of claim 14, wherein the full-size residential or commercial appliance is selected from pool and spa heaters, heat pumps, filter pumps, water pumps, indirect heat exchangers, boilers, and water heaters.

19. A model display system comprising: a plurality of miniature three-dimensional product models, wherein each of the plurality of miniature three-dimensional product models (i) has a bottom surface, a top surface, and at least one side surface extending between the bottom surface and the top surface; (ii) is a scaled replica of a full-size residential or commercial appliance; and (iii) has a hollow interior configuration with an opening in the bottom surface; a base comprising an upper tier and a lower tier, each of the upper and lower tiers being configured to retain half of the plurality of miniature three-dimensional product models in a single position thereon, each of the plurality of miniature three-dimensional product models being manually removable from and replaceable onto the base; and one or more sensors configured to detect removal of each of the plurality of miniature three-dimensional product models from its position on the base, wherein the opening in the bottom surface of each of the plurality of miniature three-dimensional product models has a unique shape, and the base comprises a plurality of projections that correspond to each of the openings, with each of the plurality of projections being sized and shaped to matingly engage with a single one of the openings of the plurality of miniature three-dimensional product models to retain each miniature three-dimensional product model in its single position on the base.

20. The model display system of claim 19, further comprising: a video display; memory configured to store computer-executable instructions; and at least one computer processor configured to access the memory and execute the computer-executable instructions to: determine, based a signal from the one or more sensors, that one of the plurality of miniature three-dimensional product models has been removed from its position on the base; and display motion or still images, on the video display, corresponding to the miniature three-dimensional product models that has been determined to have been removed from its position on the base.
