

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408293
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Sun; Hui-Ping et al.

Foldable electronic device

Abstract

A foldable electronic device, including a first body, a second body, an air valve movably disposed in the first body, at least one triggering member, and a hinge connecting the first body and the second body, is provided. The first body has multiple openings respectively located at two opposite surfaces. The triggering member is movably disposed in the first body and has a part exposed outside the first body. The air valve and the triggering member are mutually on moving paths of each other. The first body and the second body are rotated to be folded or unfolded relative to each other by the hinge. A part of the triggering member is suitable for bearing a force such that the triggering member drives the air valve, so that the air valve opens or closes the openings.

Inventors: Sun; Hui-Ping (New Taipei, TW), Yu; Jui-Yi (New Taipei, TW), Wen; Chun-Hung (New Taipei, TW), Chueh; Yen-Chou (New Taipei, TW), Lin; Yu-Ming (New Taipei, TW), Chen; Chun-Hsien (New Taipei, TW)

Applicant: Acer Incorporated (New Taipei, TW)

Family ID: 89857886

Assignee: Acer Incorporated (New Taipei, TW)

Appl. No.: 18/354676

Filed: July 19, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240098932 A1	Mar. 21, 2024

Foreign Application Priority Data

TW	111135238	Sep. 16, 2022
----	-----------	---------------

Publication Classification

Int. Cl.: H05K7/20 (20060101); G06F1/16 (20060101); G06F1/20 (20060101)

U.S. Cl.:

CPC H05K7/20154 (20130101); G06F1/1616 (20130101); G06F1/1681 (20130101); G06F1/203 (20130101); H05K7/2039 (20130101); G06F2200/202 (20130101)

Field of Classification Search

CPC: G06F (1/1616); G06F (1/1681); G06F (2200/202); G06F (1/166); G06F (1/1637); G06F (1/1679); G06F (1/183); G06F (1/206); G06F (2200/203); G06F (1/203); H05K (7/20145); H05K (7/20136); H05K (7/20154); H05K (7/2039); F28D (15/0233); H04M (1/022)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2004/0042176	12/2003	Niwatsukino	165/80.4	F28D 15/0266
2005/0111183	12/2004	Pokharna	361/679.48	G06F 1/206
2009/0147469	12/2008	Chen	361/679.55	G06F 1/166
2018/0173282	12/2017	Huang	N/A	H01L 23/427
2021/0356999	12/2020	Chao	N/A	H05K 7/20145

Primary Examiner: Matey; Michael A

Attorney, Agent or Firm: JCIPRNET

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims the priority benefit of Taiwan application serial no. 111135238, filed on Sep. 16, 2022. The entirety of the above-mentioned patent application is hereby incorporated by reference herein and made a part of this specification.

BACKGROUND

Technical Field

(2) The disclosure relates to a foldable electronic device.

Description of Related Art

(3) A notebook computer includes a keyboard and a screen. Generally speaking, the keyboard is equipped with a central processing unit. The central processing unit generates a large amount of heat, which will cause the electronic elements inside the keyboard to fail. Therefore, how to effectively dissipate the heat of the central processing unit to the outside is one of the goals of industries in the art.

(4) At the same time, in order to comply with the ergonomics during operation, most of the conventional notebook computers support the screen on the desktop and partially lift the host after

unfolding the screen relative to the host, so that the inclined host and the keyboard and the touchpad on the inclined surface can facilitate the tapping action of the user, which will not cause fatigue in a short time in addition to maintaining the input feel. Furthermore, the elevated host can be used as a source of cool air from the bottom when the fan therein is operating, thereby helping to improve the heat dissipation efficiency of heat dissipation components such as the fan.

(5) However, after supporting and elevating the host with the screen, a part of the screen is covered by the host (from the viewing angle of the user), and the rear side of the host originally as the airflow outlet of the fan also directly faces the screen, which are factors not conducive to vision (the screen-to-body ratio of the screen) and heat dissipation.

SUMMARY

(6) The disclosure provides a foldable electronic device, which provides a movable air valve in one of the bodies thereof to provide an additional escape path for an airflow discharged by another body.

(7) The foldable electronic device of the disclosure includes a first body, a second body, an air valve, at least one triggering member, and a hinge. The first body has multiple openings, which are respectively located at two opposite surfaces of the first body. The air valve is movably disposed in the first body. The triggering member is movably disposed in the first body and has a part exposed outside the first body, and the triggering member and the air valve are mutually on moving paths of each other. The hinge connects the first body and the second body, so that the first body and the second body are rotated to be folded or unfolded relative to each other by the hinge. A part of the triggering member is suitable for bearing a force such that the triggering member drives the air valve, so that the air valve opens or closes the openings.

(8) Based on the above, the body of the foldable electronic device is further provided with the movable triggering member and air valve, the triggering member has a part exposed outside the body to bear the force, and the triggering member and the air valve are mutually on the moving paths of each other. Therefore, the air valve can provide the functions of opening and closing the openings of the body, that is, the user can change the position of the air valve in the body by driving the triggering member, thereby operating the air valve to open and close the openings. The changes of the above mechanism are adapted to the specific functions required by the foldable electronic device.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1A is a schematic view of a foldable electronic device according to an embodiment of the disclosure.

(2) FIG. 1B illustrates the foldable electronic device of FIG. 1A from another viewing angle.

(3) FIG. 2A is a disassembled schematic view of some components of the foldable electronic device of FIG. 1A.

(4) FIG. 2B further illustrates a disassembly situation of some components of FIG. 2A.

(5) FIG. 2C illustrates related components of FIG. 2B from another viewing angle.

(6) FIG. 2D is a schematic view of an air valve according to an embodiment of the disclosure.

(7) FIG. 3A and FIG. 3B partially illustrate a state of a foldable electronic device with an air valve opening openings from different viewing angles.

(8) FIG. 4 partially illustrates different states of a foldable electronic device from a side viewing angle.

(9) FIG. 5A and FIG. 5B are partial cross-sectional views of an air valve closing openings.

(10) FIG. 5C and FIG. 5D are partial cross-sectional views of an air valve opening openings.

(11) FIG. 6A and FIG. 6B are schematic views of some components of a foldable electronic device.

(12) FIG. 7A and FIG. 7B illustrate an air valve according to another embodiment from different viewing angles.

(13) FIG. 8A and FIG. 8B are partial cross-sectional views of an air valve opening openings from different viewing angles.

DETAILED DESCRIPTION OF DISCLOSED EMBODIMENTS

(14) FIG. 1A is a schematic view of a foldable electronic device according to an embodiment of the disclosure. FIG. 1B illustrates the foldable electronic device of FIG. 1A from another viewing angle. Taking a notebook computer as an example, a foldable electronic device **100** includes a first body **110**, a second body **120**, and a hinge **150**, wherein the hinge **150** connects the first body **110** and the second body **120**, so that the first body **110** and the second body **120** are rotated to be folded or unfolded relative to each other by the hinge **150**. Here, FIG. 1A and FIG. 1B show the foldable electronic device **100** in an unfolded state.

(15) FIG. 2A is a disassembled schematic view of some components of the foldable electronic device of FIG. 1A. FIG. 2B further illustrates a disassembly situation of some components of FIG. 2A. FIG. 2C illustrates related components of FIG. 2B from another viewing angle. FIG. 2D is a schematic view of an air valve according to an embodiment of the disclosure. Please refer to FIG. 2A to FIG. 2C first. In the embodiment, the foldable electronic device **100** further includes an air valve **130** and at least one triggering member **140**. Here, the triggering member **140** including two parts A1 and A2 is taken as an example. The air valve **130** is movably disposed in the first body **110**. The triggering member **140** is movably disposed in the first body **110** and has a part exposed outside the first body **110**, and the triggering member **140** and the air valve **130** are mutually on moving paths of each other. Furthermore, the first body **110** of the embodiment includes a display module **111**, a front cover **113**, and a back cover **112**, which are assembled with each other. Please refer to FIG. 1A and FIG. 1B, it can be seen that the display module **111** is stacked on a part of the back cover **112**, the display module **111** and a front surface S1 of the front cover **113** are substantially on the same plane, and the front cover **113** is stacked on another part of the back cover **112**. In other words, when the first body **110** is folded to the second body **120**, the display module **111** and the front cover **113** face the second body **120**, and the back cover **112** faces away from the second body **120**. Multiple openings being respectively located at two opposite surfaces of the first body **110** refers to the front surface S1 and a rear surface S2 of the back cover **112**.

(16) In addition, please refer to FIG. 1A and FIG. 1B again. The first body **110** of the embodiment also has multiple openings, which are respectively located at the front cover **113** and the back cover **112**. Here, the opening located at the front cover **113** is defined as a first opening **113a**, and the opening located at the back cover **112** is defined as a second opening **112a**. Meanwhile, the embodiment takes three first openings **113a** and one second opening **112a** as an example, but not limited thereto. Meanwhile, it can be clearly seen from the correspondence between the front cover **113** and the back cover **112** that the first opening **113a** and the second opening **112a** are communicated with each other through an inner space of the first body **110**. More importantly, the movable air valve **130** is a component that can open or close the first openings **113a** and the second openings **112a**, and the triggering member **140** is disposed at a junction between the front cover **113** and the back cover **112** and is exposed from the first body **110**, so as to bear a force to drive the air valve **130**, which will be further described later.

(17) Please refer to FIG. 2B to FIG. 2D first, and compare with FIG. 2A or FIG. 1B to facilitate understanding of the configuration relationship of the related components. In the embodiment, the back cover **112** also has a guide post **112d**, a guide post **112c**, and a limiting portion **112e** located on an inner surface S2a. The second opening **112a** connects the inner surface S2a and the rear surface S2 (labelled in FIG. 1B) of the back cover **112**, and the back cover **112** also has a notch **112b** for the triggering member **140** to pass through. The notch **112b** is adjacently connected between the inner surface S2a and the rear surface S2.

(18) As shown in FIG. 2D, the air valve **130** has a plate body **131**, multiple stopping portions, and

two side wings **133**, wherein the plate body **131** has openings **131a** and **131b**, the stopping portions are located at two opposite surfaces of the plate body **131** and are distinguished as multiple first stopping portions **132** and one second stopping portion **134** here, and the first stopping portion **132** and the second stopping portion **134** are respectively spaced apart relative to the plate body **131** to form multiple (lattice or grid) channels **132a** and **134a**. The first stopping portion **132**, the second stopping portion **134**, and the opening **131b** are side by side, and the channels **132a** and **134a** are located between the two side wings **133** or are located between the two openings **131a**.

(19) Next, please refer to FIG. 2B and FIG. 2C again. The foldable electronic device **100** of the embodiment further includes springs R1 and R2 and multiple locking members C1, C2, C3, and C4, wherein the air valve **130** is sleeved onto the guide post **112c** to be movable up and down (for example, from the viewing angle shown in FIG. 2B) through the opening **131a**. The springs R1 and R2 are respectively sleeved onto the guide post **112c** and thus abut between the inner surface S2a of the back cover **112** and the air valve **130**. Finally, the locking members C2 and C4 are respectively locked to the guide post **112c** to stop the up and down movements of the air valve **130**. Furthermore, the triggering member **140** of the embodiment includes two parts A1 and A2, which respectively have an expanded hole **142** to be movably sleeved onto the guide post **112d**. For FIG. 2B, the triggering member **140** is in a state of being movable along the lower left and the upper right. Similarly, the locking members C1 and C3 are locked to the guide post **112d** to stop and limit the triggering member **140**, so as to facilitate the movable state of the triggering member **140** on the inner surface S2a.

(20) In addition, as shown in FIG. 2A and FIG. 2B, the limiting member **112e** (labeled in FIG. 2B) limits the air valve **130** to smoothly move up and down along the guide post **112c** through a rib structure thereof, so as to move closer to or away from the inner surface S2a of the back cover **112**.

(21) The assembled air valve **130**, triggering member **140**, and first body **110** are as shown in FIG. 1A and FIG. 1B. The first stopping portion **132** corresponds to the first opening **113a** to open and close the first opening **113a**, and the second stopping portion **134** corresponds to the second opening **112a** to open and close the second opening **112a**.

(22) FIG. 3A and FIG. 3B partially illustrate a state of a foldable electronic device with an air valve opening openings from different viewing angles. FIG. 4 partially illustrates different states of a foldable electronic device from a side viewing angle. FIG. 5A and FIG. 5B are partial cross-sectional views of an air valve closing openings. FIG. 5C and FIG. 5D are partial cross-sectional views of an air valve opening openings. Please refer to FIG. 3A and FIG. 3B first, and compare FIG. 1A and FIG. 1B. Because of the configuration of the related components, the triggering member **140** can smoothly generate a linkage relationship with the air valve **130** to open or close the first opening **113a** and the second opening **112a**, so that the first body **110** generates a linkage relationship from the first opening **113a**, the inner space of the first body **110**, and the second opening **112a**. As shown in FIG. 3A and FIG. 3B, the first stopping portion **132** of the air valve **130** is embedded into the first body **110** from the first opening **113a**, and the second stopping portion **134** protrudes from the rear surface S2 of the back cover **112** from the second opening **112a**, so that the channel **134a** is exposed outside the first body **110**.

(23) Next, please refer to FIG. 4. Here, one of the manners for driving the triggering member **140** is provided, but not limited thereto. As shown in FIG. 4, the foldable electronic device **100** is suitable for being placed on a platform **200** (for example, a desktop), and when the user unfolds the first body **110** (for example, a screen) relative to the second body **120** (for example, a host), the triggering member **140** can abut against the platform **200**.

(24) Please refer to FIG. 1B and FIG. 4 at the same time. In the embodiment, the first body **110** also has at least one supporting portion (here, two supporting portions **114** are taken as an example, which may be regarded as two of the foot pads of the foldable electronic device **100**, but not limited thereto), the supporting portion **114** and the triggering member **140** are both located and both protrude from the edge of the first body **110**, so that when the first body **110** is unfolded

relative to the second body **120** as shown in the center drawing of FIG. **4**, the supporting portion **114** and the triggering member **140** are both located at the bottom of the first body **110** to successively rely on the platform **200**. Here, the height of a part of the triggering member **140** protruding from the edge is greater than the height of the supporting portion **114** protruding from the edge, wherein the height of the supporting portion **114** protruding from the edge is a fixed value, so at this time, the first body **110** abuts against the platform **200** with an abutment surface **141** of the triggering member **140**. Next, as shown in the right drawing of FIG. **4**, in order to open the openings (the first opening **113a** and the second opening **112a**), the user may apply a force to the first body **110** to push the first body **110** down toward the direction of the platform **200**, so as to drive (trigger) the triggering member **140** to move toward the inner space of the first body **110** until the height of the part of the triggering member **140** protruding from the edge is equal to the height of the supporting portion **114** protruding from the edge. In other words, when the triggering member **140** has driven the air valve **130** to open the first opening **113a** and the second opening **112a**, the heights of the supporting portion **114** and the triggering member **140** protruding relative to the first body **110** are the same, that is at this time, the first body **110** is supported on the platform **200** by the supporting portion **114** and the triggering member **140**.

(25) Please refer to FIG. **5A** to FIG. **5D** at the same time. Here, cross-sectional views at different places are used to illustrate the linkage relationship between the triggering member **140** and the air valve **130** of the embodiment, wherein FIG. **5A** and FIG. **5B** correspond to FIG. **1A** and FIG. **1B**, that is, the state of the air valve **130** closing the openings, while FIG. **5C** and FIG. **5D** illustrate the state of the air valve **130** opening the openings. As shown in FIG. **5A** and FIG. **5C** (or may also refer to FIG. **2B** and FIG. **2C** at the same time), the air valve **130** and the triggering member **140** achieve the required movements by corresponding structures of wedge surfaces. Here, the triggering member **140** has a wedge surface **143**, the two side wings **133** of the air valve **130** also have a corresponding wedge surface **133a**, and the wedge surfaces **143** and **133a** are movably abutted together.

(26) Accordingly, as shown in FIG. **5C**, when the triggering member **140** moves toward the inner space of the first body **110** due to a force **F1** on the abutment surface **141**, during the process from FIG. **5C** to FIG. **5A**, the air valve **130** can be driven by the wedge surfaces **143** and **133a** to move along the direction **D1**, which is equivalent to moving the air valve **130** from the front cover **113** toward the back cover **112**.

(27) In this way, the first stopping portion **132** can be further embedded into the first body **110** (the first stopping portion **132** being embedded into the first opening **113a** of the front cover **113** is also equivalent to moving the first stopping portion **132** from the first opening **113a** toward the back cover **112**). The second stopping portion **134** protrudes from the first body **110** (the second stopping portion **134** protruding from the second opening **112a** of the back cover **112** is also equivalent to moving the second stopping portion **134** away from the front cover **113** from the second opening **112a** and is also equivalent to moving away from the rear surface **S2** of the back cover **112**), so that the first body **110** transitions from the opening closed state shown in FIG. **5B** to the opening open state shown in FIG. **5D**.

(28) FIG. **6A** and FIG. **6B** are schematic views of some components of a foldable electronic device. Please refer to FIG. **6A** and FIG. **6B** at the same time. In the embodiment, the foldable electronic device **100** further includes a centrifugal fan **161** and a heat dissipation fin **162**. The centrifugal fan **161** is suitable for introducing cool air from the external environment into the centrifugal fan **161** from an axial direction **161a** thereof to generate an airflow, which passes through the heat dissipation fin **162** to absorb heat (for example, through a bottom opening **121** of the second body **120**), and is then discharged through a lateral opening **122** of the second body **120**. However, as described above or as shown in FIG. **4**, since the first body **110** partially blocks the second body **120** after being unfolded relative to the second body **120** to open the openings by the linkage relationship between the triggering member **140** and the air valve **130** of the embodiment, as shown

in FIG. 6A and FIG. 6B, the airflow discharged from the lateral opening **122** can at least partially pass through the first body **110** due to the opening of the openings.

(29) For example, when the openings need to be further opened, as shown in the center drawing and the right drawing of FIG. 4, the user pushes the first body **110** down to drive the triggering member **140**, so that at least part of the airflow discharged from the second body **120** can be discharged from the rear surface **S2** of the back cover **112** from the first opening **113a**, the opening **131b**, the second opening **112a**, and the channels **132a** and **134a** as shown in FIG. 6A and FIG. 6B, so as to provide an additional escape path for the airflow discharged from the second body **120**.

(30) Please refer to FIG. 4 again. In actual use, whether the triggering member **140** is triggered may be based on the self-weight of the first body **110**, that is, as shown in the center drawing of FIG. 4. When the user unfolds the first body **110** such that the triggering member **140** abuts against the platform **200**, the above triggering action can be successively activated. Of course, in other unshown embodiments, a tenon structure or a latch structure may also be used to activate, maintain, or deactivate the triggering state of the triggering member **140**.

(31) FIG. 7A and FIG. 7B illustrate an air valve according to another embodiment from different viewing angles. FIG. 8A and FIG. 8B are partial cross-sectional views of an air valve opening openings from different viewing angles. Please refer to FIG. 7A, FIG. 7B, FIG. 8A, and FIG. 8B at the same time. In the embodiment, only an air valve **230** is different from the air valve **130** of the foregoing embodiments, and other features such as peripheral components and driving relationships are the same as the foregoing embodiments, so the same content will not be repeated.

(32) Please refer to FIG. 7A and FIG. 7B, and compare with FIG. 2D of the foregoing embodiment. The air valve **230** of the embodiment includes a plate body **231**, multiple first stopping portions **232**, a pair of wing portions **233**, and multiple second stopping portions **234**, wherein the plate body **231** has multiple openings **231a** and **231b**, the first stopping portions **232** bulge from the plate body **231**, and the first stopping portions **232** and the openings **231b** are located in the same row and staggered. Here, the wing portion **233** and a wedge surface **233a** thereof are the same as the foregoing embodiments and are driven by the triggering member **140**, so the triggering member **140** will not be illustrated and described here. Similarly, the opening **231a** is also the same as the opening **131a** of the foregoing embodiments and is used for screws **C2** and **C4** to pass through to lock the air valve **230** to the structure, so there will also be no repetition. In short, the driving manner and related components of the air valve **230** of the embodiment are still the same as the air valve **130** of the foregoing embodiments.

(33) Furthermore, the second stopping portion portions **234** and the first stopping portions **232** are opposite to each other across the plate body **231**. Further, each second stopping portion **234** also bulges relative to the plate body **231**, and a channel **234a** is further formed, so as to be communicated with the opening **231b**.

(34) Accordingly, when the triggering member **140** is triggered to drive the first stopping portion **232** and the second stopping portion **234** of the air valve **230** to respectively move away from a corresponding first opening **213a** of a front cover **213** and second opening **212a** of a back cover **212**, that is, a channel for an airflow to pass through can be generated as in the foregoing embodiments. Here, in order to facilitate identification, the airflow is shown in FIG. 7A with arrows. Please refer to FIG. 7A and FIG. 8A at the same time. The uppermost arrow represents the airflow flowing from the first opening **213a** into the first body **110**. It can be clearly seen that the airflow is separated by the first stopping portion **232** and flows from the adjacent opening **231b** to the channel **234a**, and the same opening **231b** corresponds to two branched channels **234a** (of the same second stopping portion **234**), so as to increase the number of airflow outlets to be beneficial to heat dissipation.

(35) In summary, in the foregoing embodiments of the disclosure, the body of the foldable electronic device is further provided with the movable triggering member and air valve, the triggering member has a part exposed outside the body to facilitate bearing of a force, and the

triggering member and the air valve are mutually on the moving paths of each other. Therefore, the air valve can provide the functions of opening and closing the openings of the body, that is, the user can change the position of the air valve in the body by driving the triggering member, thereby operating the air valve to open and close the openings. The changes of the above mechanism are adapted to the specific functions required by the foldable electronic device.

(36) Further, the foldable electronic device is provided with the centrifugal fan and the heat dissipation fin in the second body therein, and the airflow after absorbing heat is discharged through the lateral opening of the second body. However, as mentioned above, the first body is directly located on the discharge path of the airflow, so the opening of the openings generated by the air valve can allow at least part of the airflow discharged by the second body to pass through the first body through the openings, and to be smoothly discharged from the rear surface of the first body, so as to provide the additional escape path for the airflow. At the same time, the openings are located at the front cover of the first body and are substantially located at the bottom of the display module (in the unfolded state), so the foldable electronic device can take into account the maximum visual screen-to-body ratio and the required heat dissipation efficacy.

Claims

1. A foldable electronic device, comprising: a first body, having a plurality of openings, respectively located at two opposite surfaces of the first body; a second body; an air valve, movably disposed in the first body; at least one triggering member, movably disposed in the first body and having a part exposed outside the first body, wherein the triggering member and the air valve are mutually on moving paths of each other; and a hinge, connecting the first body and the second body, so that the first body and the second body are rotated to be folded or unfolded relative to each other by the hinge, and the part of the triggering member is suitable for bearing a force such that the triggering member drives the air valve, so that the air valve opens or closes the openings.
2. The foldable electronic device according to claim 1, wherein each of the triggering member and the air valve has a wedge surface, and the wedge surfaces correspond to each other and are movably abutted together.
3. The foldable electronic device according to claim 1, further comprising: a spring, disposed in the first body and abutting between the air valve and the first body, wherein the spring constantly drives the air valve to close the openings to reset the triggering member, the triggering member is suitable for bearing an external force to open the openings and deform the spring, and when the external force is removed, an elastic force of the spring drives the air valve to close the openings.
4. The foldable electronic device according to claim 1, wherein the first body has a back cover and a front cover assembled with each other, the openings are respectively located at the front cover and the back cover, the openings are communicated with each other through an interior of the first body, and the part of the triggering member is exposed from an edge of the first body from a junction between the front cover and the back cover.
5. The foldable electronic device according to claim 4, further comprising: a display module, assembled at the front cover and the back cover, wherein the display module is stacked on a part of the back cover, the display module and the front cover are located on a same plane, and the front cover is stacked on another part of the back cover.
6. The foldable electronic device according to claim 4, wherein the air valve has a plate body and at least one first stopping portion and at least one second stopping portion located at two opposite surfaces of the plate body, a part of the stopping portions correspond to a part of the openings located at the front cover, the openings comprise at least one first opening located at the front cover and at least one second opening located at the back cover, the first stopping portion corresponds to the first opening, the second stopping portion corresponds to the second opening, when the triggering member bears an external force and moves toward the interior of the first body to drive

the air valve to move from the front cover to the back cover, the first stopping portion is embedded into the first body from the first opening to open the first opening, and the second stopping portion protrudes from the first body from the second opening to open the second opening.

7. The foldable electronic device according to claim 6, further comprising: a spring, disposed in the first body and abutting between the plate body and the back cover, wherein the spring constantly drives the plate body to move from the back cover toward the front cover, the triggering member bears the external force to deform the spring, and after the external force is removed, an elastic force of the spring drives the air valve to reset the triggering member, the first stopping portion closes the first opening, and the second stop closes the second opening.

8. The foldable electronic device according to claim 6, wherein the air valve also has two wing portions located at two opposite sides of the plate body, each of the first stopping portion and the second stopping portion is located between the two wing portions, the foldable electronic device comprises a pair of triggering members, and the pair of triggering members and the two wing portions are mutually driven by wedge surfaces abutting against each other.

9. The foldable electronic device according to claim 6, wherein the first stopping portion and the plate body are spaced apart to form at least one first channel, the second stopping portion and the plate body are spaced apart to form at least one second channel, the plate body has at least one third channel, and when the first opening and the second opening are opened, the first opening is communicated with the second opening sequentially through the first channel, the third channel, and the second channel.

10. The foldable electronic device according to claim 4, wherein the triggering member has an expanded hole slidably coupled to a guide post of the back cover.

11. The foldable electronic device according to claim 4, wherein the first body has at least one supporting portion, the supporting portion and the triggering member are both located and both protrude from the edge of the first body, when the air valve closes the openings, a height of the part of the triggering member protruding from the edge is greater than a height of the supporting portion protruding from the edge, and when the air valve opens the openings, a height of the part of the triggering member protruding from the edge is equal to the height of the supporting portion protruding from the edge.

12. The foldable electronic device according to claim 11, wherein the height of the supporting portion protruding from the edge is a fixed value.

13. The foldable electronic device according to claim 4, further comprising: a fan and a heat dissipation fin, disposed in the second body, wherein an airflow generated by the fan passes through the heat dissipation fin and is then discharged out of the second body from at least one lateral outlet of the second body, when the first body is unfolded relative to the second body by the hinge, the first body supports and elevates a part of the second body, and the lateral outlet corresponds to the openings located at the front cover, and when the air valve opens the openings, at least part of the airflow sequentially passes through the openings of the front cover, the air valve, and the openings of the back cover to pass through the first body.

14. The foldable electronic device according to claim 1, wherein when the first body is unfolded relative to the second body by the hinge, the first body supports and elevates a part of the second body, and the triggering member is located at a bottom of the first body.

15. The foldable electronic device according to claim 1, further comprising: a fan and a heat dissipation fin, disposed in the second body, wherein an airflow generated by the fan passes through the heat dissipation fin and is then discharged out of the second body from at least one lateral outlet of the second body, when the first body is unfolded relative to the second body by the hinge, the first body supports and elevates a part of the second body, and the lateral outlet corresponds to a part of the openings, and when the air valve opens the openings, at least part of the airflow passes through the openings to pass through the first body.

16. The foldable electronic device according to claim 1, wherein the part of the triggering member

is suitable for bearing a force, so that the triggering member moves toward an interior of the first body to drive different parts of the air valve to respectively protrude and be embedded into the first body to open the openings.
