

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281256

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Hendrix; Heidi Frances et al.

SURGICAL DRAPE FOR THERMAL TREATMENT BASIN

Abstract

A drape for a piece of equipment used during a medical procedure may be formed of a flexible sheet of polymeric material. The flexible sheet can have a basin portion shape-indexed to a basin or reservoir of the piece of equipment over which the drape is intended to be draped. The flexible sheet can also have a side sheet portion connected to the basin portion. The side sheet portion can drape down the basin or reservoir of the piece of equipment over which the drape is draped. The basin portion of the flexible sheet can be collapsible. As a result, the drape can be collapsed into planar package for storage. Upon being removed from the package, the basin portion of the drape can be expanded to conform to the walls of the basin of the piece of equipment over which the drape is deployed.

Inventors: Hendrix; Heidi Frances (Atlanta, GA), Rawlings; David Richard (Cumming, GA), Wilson; Michelle (Caledonia, GA)

Applicant: Medline Industries, LP (Northfield, IL)

Family ID: 63896648

Appl. No.: 19/218037

Filed: May 23, 2025

Related U.S. Application Data

parent US continuation 18453302 20230821 parent-grant-document US 12310692 child US 19218037

parent US continuation 16144706 20180927 parent-grant-document US 11730555 child US 18453302

us-provisional-application US 62564229 20170927

Publication Classification

Int. Cl.: A61B46/10 (20160101); **A61B46/00** (20160101); **A61F7/00** (20060101); **A61F7/02** (20060101)

U.S. Cl.:

CPC A61B46/10 (20160201); **A61B46/40** (20160201); **A61F7/0085** (20130101); **A61F7/0241** (20130101)

Background/Summary

CROSS-REFERENCE [0001] This application is a continuation of U.S. patent application Ser. No. 18/453,302, filed Aug. 21, 2023 and issued as U.S. Pat. No. 12,310,692 on May 27, 2025, which application is a continuation of U.S. patent application Ser. No. 16/144,706, filed Sep. 27, 2018 and issued as U.S. Pat. No. 11,730,555 on Aug. 22, 2023, which application claims priority to U.S. Provisional Patent Application No. 62/564,229, filed Sep. 27, 2017, the entire contents of each of which are incorporated herein by reference.

TECHNICAL FIELD

[0002] This disclosure relates to surgical drapes and, more particularly, surgical drapes used to cover medical equipment during a procedure.

BACKGROUND

[0003] Disposable surgical drapes are used to help establish or maintain a sterile field during a medical procedure, reducing the likelihood that a patient undergoing the procedure will be infected from contaminated surfaces or objects. For example, a sterile surgical drape may be deployed over a piece of equipment used in the surgical suite or other medical environment prior to the start of the procedure. The sterile surgical drape can provide a barrier between materials introduced into and/or removed from the patient during the procedure and the equipment being used during the procedure. Even though the equipment itself may be sterilized before use, the addition of a sterile surgical drape can reduce the likelihood of patient contamination and hospital-acquired infection during the procedure.

[0004] In practice, a sterile surgical drape may be provided as a pre-packaged, disposable item. The sterile surgical drape may be packed sufficiently small so as to be conveniently transported and stored. However, the sterile surgical drape may have an unpackaged size adequate to cover the intended medical equipment. To help avoid contact contamination during deployment of the sterile surgical drape, the drape may be folded and packaged so as to minimize contact of sterile surfaces by a user deploying the drape.

SUMMARY

[0005] In general, this disclosure is directed to surgical drapes as well as techniques for folding surgical drapes for convenient packaging and unfolding surgical drapes for sterile deployment. In some examples, a surgical drape is designed to cover a basin of a surgical system, such as a system for thermally treating surgical fluid before utilizing the fluid during a medical procedure. The surgical fluid may be temperature adjusted within the system to raise the temperature above ambient temperature or reduce the temperature below ambient temperature. The system can also maintain the surgical fluid at an elevated or reduced temperature relative to ambient temperature until the surgical fluid is ready to be used during a procedure. In use, the surgical fluid may be withdrawn from the basin and dispensed over a surgical site on or in a patient to irrigate the site and flush away bodily matter.

[0006] In some example, a drape according to the disclosure includes a thermoformed basin and side sheet bonded to the thermoformed basin. The thermoformed basin can be shape-indexed to the

shape of a basin of a surgical system. The thermoformed basin may be formed of a polymeric material and may be sufficiently thin so as to be collapsible. In some configurations, for example, the drape may be defined by a bottom wall and collapsible sidewall. To facilitate compact packaging, the sidewall and/or bottom wall of the drape can collapse into a substantially flat package. After being removed from the package, however, the sidewall and/or bottom can expand to define the shape-indexed basin portion of the drape, which is insertable into the basin of the thermal treatment system. In this way, the drape can define a compact package for transport and/or storage yet expand to include a basin portion that would occupy more space if not collapsible. [0007] Although a drape according to the disclosure can have a variety of different features as described herein, in some configurations, the drape includes a flexible window portion. The flexible window portion may be thermally bonded between a thermoformed basin portion and flexible side sheet portion of the drape. The window portion can be positionable over a user input device (e.g., display screen) of the thermal treatment system over which the drape is deployed. The window portion may be formed of a polymer that is visually transparent to the user. Depending on the type of polymer used, the polymer may contain a tackifying agent to increase the tackiness and/or friction of the window (e.g., as compared to other portions of the drape). This can help prevent the window from sliding relative to the user interface over which the window is positioned when the user interacts with the user interface through the window.

[0008] As another example feature, the drape may include an electronically readable tag embedded in the drape. For example, the electronically readable tag may be positioned in a pocket formed by bonding two sheets of material together. The electronically readable tag may be oriented relative to the basin portion such that, when the drape is placed over the thermal treatment system, the electronically readable tag is positioned over a non-contact reader. This arrangement can provide a securely attached electronically readable tag that is appropriately positioned relative to the thermal treatment system by inserting the basin portion of the drape into the basin of the thermal treatment system without requiring special positioning by the operator.

[0009] In one example, a drape for a surgical fluid thermal treatment system is described. The drape includes a flexible sheet having a basin portion and a side sheet portion connected to the basin portion. The basin portion defines a bottom wall and a collapsible sidewall. The collapsible sidewall is configured to transform from a first configuration in which the basin portion is expanded such that the basin portion is configured to conform to a basin of the surgical fluid thermal treatment system to a second configuration in which the basin portion is collapsed and the flexible sheet is planar.

[0010] In another example, a drape is described that includes a thermoformed basin that is shape-indexed to a shape of a basin of a surgical system into which the thermoformed basin is configured to be inserted. The example specifies that the thermoformed basin is collapsible. In addition, the example specifies that the drape includes flexible side sheet bonded to and extending about an entire perimeter of the thermoformed basin.

[0011] In another example, a method is described that includes removing a drape that is folded and flat from a sealed package. The method includes inserting a basin portion of the drape into a basin of a surgical fluid thermal treatment system and expanding the basin portion of the drape from a collapsed configuration to an expanded configuration.

[0012] In another example, a method of folding a drape is described. The method includes providing a drape that includes a collapsible basin and a flexible side sheet extending about a perimeter of the collapsible basin, the flexible side sheet having a first edge and a second edge on an opposite side of the flexible side sheet from the first edge. The method involves arranging the drape so the collapsible basin is collapsed and substantially planar and folding the first edge of the drape toward the second edge of the drape to form a first fold line transecting the collapsible basin. The method further involves folding the first edge of the drape back away from the second edge of the drape to form a second fold line offset from the first fold line, thereby providing a first drape

panel positioned over the collapsible basin. In addition, the method includes folding the first edge of the drape toward the second edge of the drape to form a third fold line offset from the second fold line, and folding the first edge of the drape back away from the second edge of the drape to form a fourth fold line offset from the third fold line, thereby providing a second drape panel positioned over the collapsible basin.

[0013] The details of one or more examples are set forth in the accompanying drawings and the description below. Other features, objects, and advantages will be apparent from the description and drawings, and from the claims.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0014] FIG. 1 is a perspective view of an example surgical system that may be draped with a drape according to the disclosure.

[0015] FIGS. 2 and 3 are perspective illustrations of an example drape.

[0016] FIGS. 4 and 5 are a side view and perspective view, respectively, showing an example layout of a basin portion that can be used for the drape of FIGS. 2 and 3.

[0017] FIG. 6 is a perspective view showing an example arrangement of window portions relative to a basin portion that can be used for the drape of FIGS. 2 and 3.

[0018] FIG. 7 is a sectional view illustrating an example configuration of a basin portion where the thickness of the basin portion varies.

[0019] FIG. 8 is a perspective view showing an example collapsed configuration for the drape of FIGS. 2 and 3.

[0020] FIG. 9 is a perspective view of an example portion of a drape showing how an electronically readable tag may be arranged in the drape.

[0021] FIGS. 10-26 illustrate example folding and packaging steps that may be utilized for a drape according to the disclosure.

DETAILED DESCRIPTION

[0022] This disclosure is generally directed to drapes used to protect medical equipment. In some examples, a drape according to the disclosure is individually pre-packaged and is sterilized so as to be free from bacteria or other living organisms. The drape may be subject to thermal treatment and/or chemical treatment (e.g., exposed to ethylene oxide) to provide a sterilized drape that can be arranged over medical equipment within an operating environment to establish a sterile field over the medical equipment so draped. The drape can be disposed after use and a new drape used during a subsequent medical procedure or, in the case of a long procedure, during a latter portion of the same medical procedure.

[0023] In some examples, a drape is configured with a basin portion and a side sheet portion. The side sheet portion can be operatively connected to the basin portion and, in some configurations, extend outwardly away from the basin portion. The entire drape may be formed of flexible sheet material(s) that can be deformed under human hand pressure. For example, the drape may be folded into a compact, substantially flat package with the basin portion collapsed in on itself and the side sheet portion folded over the collapsed basin. In use, an operator can remove the drape from the package and insert the collapsed basin portion over a corresponding piece of medical equipment to be draped. The operator can expand the collapsed basin portion into its expanded shape, substantially conforming the walls of the basin portion to the corresponding piece of medical equipment to be draped. The side sheet portion may drape downwardly over the piece of medical equipment. By configuring the drape with a collapsible basin, among other features, a more compact package may be provided for transport and storage than if a drape structure was fabricated by attaching a flexible plastic drape around a rigid basin.

[0024] While a drape according to the disclosure can be used to drape any type of equipment that is desirably covered during use, the drape may be particularly useful to drape equipment used within a medical environment to provide a sterile draped surface over the equipment. Reference to a medical, surgical, or operating environment includes any hospital, clinic, facility or location where illness or injuries are diagnosed or treated using interventional or non-interventional techniques. Example pieces of medical equipment that may be draped using a drape with a basin portion according to the disclosure include, but are not limited to, a sink basin, a weighing trough to weight materials introduced into or removed from a patient, a basin to hold material used during a surgical procedure (e.g., tools, swabs), and the like.

[0025] As one specific example, a drape may be deployed over a system for thermally treating surgical fluid before utilizing the fluid during a medical procedure. The surgical fluid may be temperature adjusted within the system to raise the temperature above ambient temperature or reduce the temperature below ambient temperature. The system can also maintain the surgical fluid at an elevated or reduced temperature relative to ambient temperature until the surgical fluid is ready to be used during a procedure.

[0026] FIG. 1 is a perspective view of one example of a system **10** for thermally treating surgical fluids that may be draped with a drape according to the disclosure. In the example, of FIG. 1, system **10** includes a base **12** and a basin **14**. Basin **14** is supported by and vertically elevated above base **12**. Basin **14** can provide an open reservoir into which surgical fluid can be dispensed or other material being processed introduced. Once added to basin **14**, the surgical fluid can be temperature adjusted within the basin. For example, basin **14** may be thermally coupled to a thermal treatment device that can raise or lower the temperature of thermal fluid. Basin **14** can also maintain surgical fluid at a target temperature until the fluid is removed from the basin and used in a procedure. In some configurations, system **10** can heat surgical fluid in basin **14** to a temperature near a patient's normal body temperature, such as a temperature within the range of 90 degrees Fahrenheit (32.2 Celsius) to 120 degrees Fahrenheit (48.9 Celsius), such as from 95 degrees Fahrenheit (35 Celsius) to 105 degrees Fahrenheit (40.6 Celsius).

[0027] To allow an operator to interact with system **10** and control different settings, system **10** may include a user interface. In the example of FIG. 1, system **10** includes at least one user interface **16**. User interface **16** can include a user input through which a clinician inputs information to system **10** and a user output from which the clinician receives information from the system. For example, user interface **16** may include one or more manipulable inputs that the clinician can interact with to adjust settings of system **10**, provide an indication that fresh fluid is being added to basin **14**, provide an indication that non-surgical components are being added or removed from system **10**, change a temperature to which fluid in basin **14** is heated, or the like. The manipulable user input may be implemented as physically depressible buttons (e.g., switches), portions of a touch screen that a clinician can interact with, or other features that a clinician can interact with to convey information to system **10**. The user output of user interface **16** may be a display that provides graphical and/or textual information concerning the operation of system **10**.

[0028] In applications where system **10** includes a display, the system can be configured with a single display or multiple displays. In FIG. 1, system **10** is illustrated as having a first display that forms part of user interface **16** and a second display **18**. The first display is positioned on an exterior surface of one side of basin **14** while the second display is positioned on an exterior surface on a substantially opposite side of the basin. This arrangement can be useful to allow clinicians working on different sides of basin **14** to see information regarding the operation of system **10**. In some examples, second display **18** is part of a user interface that includes the same features and functionalities (e.g., user input(s) and/or user output(s)) as first user interface **16**. This can allow the clinician to present information to and receive information from system **10** when working on either side of the system. In other examples, second display **18** may be a display that provide a user output but does not have user input controls. In these applications, the clinician may

enter information or commands through user input(s) on user interface **16** but be able to view output information on both displays.

[0029] Any type of material may be introduced into and removed from basin **14** during a procedure, including any type of surgical fluid during a medical procedure. Example types of medical fluid that may be used during a medical procedure include water, saline, or the like. The surgical fluid may or may not include medicament, such as compounds imparting antibacterial properties, anticoagulation/coagulation properties, anesthesia properties, or the like. Alternative materials that may be introduced into basin **14** can include a medical specimen extracted from a patient for weighing (e.g., in embodiments in which basin is configured to measure weight), blood, platelets, or materials for thermal adjustment before being introduced into a patient, or non-medical related materials (e.g., in applications in which system **10** is not used in a medical environment). Additionally or alternatively, medical tools may be added and removed from basin **14** during use, such as an asepto bulb syringe and/or a graduated measuring container.

[0030] In the configuration of FIG. **1**, basin **14** is supported by and vertically elevated above base **12**. In particular, basin **14** is mounted on an elongated housing **20** that extends vertically upwardly from base **12**. Base **12** and housing **20** can elevate basin **14** to a position where it is convenient for a clinician to interact with the basin. Additional details on example thermal treatment systems can be found in U.S. patent application Ser. No. 15/469,476, filed Mar. 24, 2017, the entire contents of which are incorporated herein by reference.

[0031] Independent of the configuration of the equipment to be draped, a drape according to disclosure can have a variety of different features and configurations as discussed herein. FIGS. **2** and **3** are perspective illustrations of an example drape **30** that may be used to drape system **10** in FIG. **1** or any other desired piece of equipment. FIG. **2** is an exploded perspective view of drape **30**, while FIG. **3** illustrates the drape in assembled form. As shown, drape **30** can be formed from a flexible sheet of material **32** that has a basin portion **34** and side sheet portion **36**. Side sheet portion **36** can at least partially, and in the illustrated example entirely, surround the perimeter of basin portion **34**. Side sheet portion **36** can be physically connected to basin portion **34** to define a unitary, unbroken sheeting surface. In some configurations such as that illustrated in FIGS. **2** and **3**, drape **30** includes one or more window portions **38**, **40**. The window portions **38**, **40** of drape **30** may be arranged and designed to be positioned over viewable and/or interactable features of the equipment being draped, such as user interface **16** and/or display **18** in system **10** of FIG. **1**.

[0032] Basin portion **34** of drape **30** can be collapsible to facilitate flat folding and packing of drape **30** and expandable to facilitate insertion of the basin portion into a basin to be draped during use. Basin portion **34** in FIGS. **2** and **3** is illustrated in an expanded configuration where the basin portion defines its maximum volume, e.g., such as the configuration when the drape is in use and basin portion **34** of drape **30** is inserted into basin **14** of system **10**. Basin portion **34** of drape **30** can be collapsible so that the basin portion folds down into a more compact shape and is substantially planar (e.g., FIG. **7**).

[0033] Basin portion **34** of drape **30** may define a reservoir that receives and holds surgical fluid or other materials inserted into the equipment being draped with the drape positioned therebetween. Basin portion **34** of drape **30** can define any polygonal (e.g., rectangle, square, hexagonal) or arcuate (e.g., circular, elliptical) shape, or even combinations of polygonal and arcuate shapes. In the illustrated example, basin portion **34** is shown as a general oval shape and includes a bottom wall **42** and at least one sidewall **44** extending vertically upwardly away from the base (e.g., when basin portion is expanded and not collapsed). Bottom wall **42** and sidewall **44** can collectively form a bounded cavity with an open top surface that receives and holds materials inserted into the covered equipment with the drape positioned between the equipment and the material.

[0034] Side sheet portion **36** of drape **30** can be connected to basin portion **34** and extend outwardly and/or downwardly away from the basin portion. For example, basin portion **34** may define a perimeter **46** that delimits the basin portion. The perimeter **46** of basin portion **34** may be

where the basin portion transitions from a vertical-orientated sidewall defining a reservoir depth or height (e.g., when in the expanded configuration) to a horizontally-oriented sidewall. In either case, side sheet portion **36** can be physically connected to perimeter **46** of basin portion, e.g., either directly or indirectly with a window **38**, **40** positioned between the perimeter and the side sheet. Side sheet portion **36** can be flexible and fall or drape downwardly under the force of gravity over the equipment which the drape is installed. For example, when drape **30** is deployed over system **10** in FIG. 1, basin portion **34** can be inserted into basin **14** of the system with side sheet portion **36** draping downwardly over at least a portion of the exterior surface of basin **14** and/or housing **24**. [0035] In general, basin portion **34** of drape **30** may be shape-indexed to the shape of the basin or reservoir into which basin portion **34** is intended to be inserted. Basin portion **34** may be shape-indexed in that it may have a complementary size and/or shape to the reservoir or basin of the equipment to be draped and into which basin portion **34** is intended to be inserted. For example, basin portion **34** may be shape-indexed so that bottom wall **42** and sidewall **44** are in physical contact with and/or conform to corresponding wall surfaces of the structure into which the draped basin portion is inserted (e.g., basin **14** of system **10** in FIG. 1). Conforming the shape of basin portion **34** to the structure into which it is intended to be inserted can be useful, e.g., to facilitate efficient thermal transfer between the heated or cooled wall surfaces of the structure and the material contained within basin portion **34** whose temperature is being adjusted.

[0036] The shape of basin portion **34** can be established by the configuration of bottom wall **42** and the at least one sidewall **44**. In general, sidewall **44** extends upwardly from bottom wall **42**. The number of sidewalls interconnected together to form the side structure of basin portion **34** can vary depending on the shape of the reservoir. For example, a basin portion with a circular cross-sectional shape (e.g., in the horizontal plane) may be formed of a single sidewall whereas a basin portion with a square or rectangular cross-sectional shape may be defined by four interconnected sidewalls.

[0037] In some examples, the at least one sidewall **44** defining basin portion **34** is sloped such that the sidewall extends vertically upwardly and outwardly away from bottom wall **42**. For example, sidewall **44** may be curved and define a radius of curvature where the sidewall intersects and joins bottom wall **42**. Bottom wall **42** may be flat, curved, or have other suitable shape profile.

Configuring sidewall **44** with a curved or sloped profile instead of a straight sidewall may help prevent materials from accumulating in corners where sidewall **44** intersects bottom wall **42**. For example, basin portion **34** may define an arcuate shape devoid of 90 degree angles to help prevent materials from accumulating in such angular regions. That being said, in other examples, sidewall **44** may not be curved but may instead be straight (e.g., perpendicular with respect to ground).

[0038] FIGS. 4 and 5 are a side view and perspective view, respectively, of basin portion **34** showing an example layout of the basin portion. As shown in this example, sidewall **44** defines a radius of curvature **45** where the sidewall extends outwardly from and joins to bottom wall **42**.

When so configured, basin portion **34** may define an open top surface **48** that has a greater cross-sectional area **50** than the cross-sectional area **52** defined by bottom wall **42**. Configuring basin portion **34** so the open top surface **48** defined by the basin portion is larger than bottom wall **42** may be useful to provide space for the basin portion to collapse into a compact profile. For example, basin portion **34** may collapse telescopically such that bottom wall **42** is arranged substantially coplanar with perimeter **46** and sidewall **44** is nested or folded in rings of collapsed/gathered material between the bottom wall and upper end of the sidewall.

[0039] In some configurations, such as the configuration illustrated in FIGS. 4 and 5, sidewall **44** extends vertically upwardly from bottom wall **42** and defines a curved perimeter lip **54**. The curve perimeter lip **54** may be a transition region of sidewall **44** that transitions from a generally vertical orientation to a generally horizontal orientation. In some examples, curved perimeter lip **54** of basin portion **34** may transition sidewall **44** from a generally upward vertical orientation, to a generally horizontal orientation, and then to a generally downward vertical orientation. For example, sidewall **44** may extend upwardly from bottom wall **42** to an inflection point **56** and then extend

downwardly from the inflection point toward ground (e.g., when installed over the object being draped). The weight of side sheet portion **36** hanging down toward ground under a force of gravity may help impart this curvature to the perimeter lip of basin portion **34**. Configuring basin portion **34** with a curved perimeter lip may be useful to help the basin portion wrap over the top surface of the basin or reservoir of the equipment being draped with drape **30**.

[0040] Although drape **30** is illustrated as having a single basin portion **34** for being inserted into a corresponding basin of equipment being draped, the drape may be formed with multiple basin portions separated from each other by a wall of material. For example, basin portion **34** may be a single cavity with internal partition(s) or divider(s) separating one or more reservoir cavities from fluid communication with one or more other reservoir cavities. Alternatively, drape **30** may include multiple basin portions **34** separated from each other but physically joined together.

[0041] As mentioned above, drape **30** may include at least one window portion which, in the example of FIGS. **2** and **3**, is illustrated as two window portions **38**, **40**. Each window portion may be a transparent region that is configured to be positioned over user interface features of the equipment being draped. For example, drape **30** may include a first window portion **38** configured to be positioned over user interface **16** of system **10** (FIG. **1**) and a second window portion **40** configured to be positioned over display **18** of system **10**. By configuring drape **30** with transparent window portions **38**, **40**, a user can better visualize and/or interact with equipment features located under the respective window portion.

[0042] When drape **30** includes a window portion, the location of the window portion relative to basin portion **34** may vary depending on the configuration of the equipment intended to be draped. In some examples, drape **30** includes at least one window portion positioned between basin portion **34** and side sheet portion **36**. The window portion can be connected to basin portion **34** and side sheet portion **36**, collectively forming an unbroken drape surface.

[0043] FIG. **6** is a perspective view of basin portion **34** showing an example arrangement of window portions **38** and **40** relative to the basin portion. As shown, basin portion **34** defines a perimeter **46** having a length **58** and a width **60**. In the illustrated configuration, first window portion **38** projects away from one lengthwise perimeter section of basin portion **34**. Second window portion **40** projects away from the opposite lengthwise perimeter section of basin portion **34**. In this arrangement, no window portion projects away from the widthwise perimeter sections of the basin portion, although other window arrangements can be used without departing from the scope of disclosure.

[0044] In the arrangement of FIG. **6**, basin portion **34** is illustrated as defining an oval-shaped cavity formed, collectively, by bottom wall **42** and sidewall **44**. The oval-shaped cavity transitions to a generally rectangular shape about perimeter **46**. For example, perimeter lip **54** of sidewall **44** is illustrated as transitioning from the oval cross-sectional shape to the generally rectangular cross-sectional shape. The corners of the generally rectangular perimeter shape for basin portion **34** are illustrated as being chamfered or rounded, although may intersect at sharp (e.g., 90°) angles in other configurations.

[0045] Although drape **30** can be fabricated from any suitable materials, the drape may typically be fabricated from one or more polymeric materials. Example polymers that may be used to fabricate drape **30** include, but are not limited to, polyethylene, polypropylene, polyvinyl chloride, polystyrene, polyamide, polytetrafluoroethylene (PTFE), polyethylene terephthalate (PET), polyurethane, and combinations thereof.

[0046] The specific material or materials used to form drape **30** may be selected based on the desired performance characteristics of the drape, such as its chemical and/or thermal resistance, its puncture resistance, its flexibility, or yet further performance characteristic. For example, where drape **30** is intended to cover a piece of equipment that adjust the temperature of the contents placed in basin portion **34** relative to ambient temperature, at least basin portion **34** may be selected for temperature compatibility with the equipment being draped. In some examples, drape **30** and/or

basin portion **34** of the drape may be formed of a polymer having a melt temperature rather than 100° F., such as greater than 120° F., greater than 130° F., or greater than 150° F. This may be useful for draping over a thermal warmer, such as the example thermal warmer illustrated in FIG. **1**, in applications where the contents placed in basin portion **34** are heated around the temperature of the human body or slightly above that temperature.

[0047] In some examples, each portion of drape **30** (e.g., basin portion **34**, side sheet portion **36**, and windows **38**, **40**) are formed of the same polymer. In other examples, at least one portion of drape **30** may be formed of a different polymer composition than at least one (and optionally all) of the other portions forming the drape. For example, basin portion **34** may be formed of a first polymer composition, windows **38**, **40** may be formed of a second polymer composition, and side sheet portion **36** may be formed of a third polymer composition. The first, second, and third polymer compositions may each be different from each other. For example, each polymer composition may be formed from different types of monomers, or multiple (e.g., all) of the polymer compositions may be formed from the same type of monomer with different constituent ingredients included in the formulation to provide a different resulting composition.

[0048] As one example, the first, second, and third polymer compositions may each be formed from a polyurethane monomer but may have different formulations to provide compositions different from each other. The pre-polymerization resins used to fabricate the first, second, and third polymer compositions may contain a common polyurethane monomer but may include different additives and/or constituent ingredients. Additionally or alternatively, the type and/or degree of polymerization may vary between the different polymer compositions used to fabricate the different portions of drape **30**.

[0049] In some examples, the second polymer composition used to fabricate window portions **38**, **40** is selected to have tackier surface properties than the first polymer composition used to fabricate basin portion **34** and the third polymer composition used to fabricate side sheet portion **36**. For example, the second polymer composition may have a tackifying agent (e.g., in different amounts and/or a different composition than in the first and third polymer compositions) that impacts the tackiness of window portions **38**, **40**. Example tackifying agents that may be used include, but are not limited to, aliphatic hydrocarbon resins; rosin esters and rosin acids; mixed aliphatic/aromatic tackifying resins; polyterpene tackifiers; and hydrogenated tackifying resins, such as those produced from the polymerization and subsequent hydrogenation of aromatic feedstocks such as styrene, alpha-methyl styrene, and vinyl toluene.

[0050] Fabricating window portions **38**, **40** from a polymeric composition that imparts tackiness and/or resistance to sliding friction may be useful to facilitate user interaction with the portion of the draped equipment underlying window portions **38**, **40**. The comparatively greater tackiness of window portions **38**, **40** than basin portion **34** and/or side sheet portion **36** may be useful to help prevent the window portions from moving if a user presses against one of the window portions to interact with equipment features under the window portion. For example, where a window portion overlies a user interface of a draped piece of equipment, a user may press against the window portion to engage the user interface covered by the window portion. In some examples, the material(s) used to fabricate the window portions of drape **30** exhibits a coefficient of friction according to ASTM D1894 greater than 1 and/or may be too tacky to test according to the standard.

[0051] Depending on the type of material(s) selected to fabricate the different portions of drape **30**, the different portions may have any degree of optical transparency ranging from transparent to opaque, in each case within the visible light spectrum. For example, drape **30** or any portion thereof may be transparent, translucent, or opaque. In some examples, window portions **38**, **40** are transparent, and side sheet portion **36** is transparent or translucent. This configuration can help a user see features and/or components of the equipment draped under the window portions and/or side sheet portion. Additionally, any portion of drape **30** may or may not be colored, e.g., by incorporating a dye or pigment in a polymeric composition forming the drape. Drape **30** or a

portion thereof, such as side sheet portion **36**, may be blue to help visually designate that the drape is defining a sterile area.

[0052] When drape **30** is formed from one or more polymeric materials, polymeric processing techniques may be used to fabricate the drape or any portion thereof. For example, drape **30** may be formed using casting, extrusion, calendaring, and/or other polymeric processing technique. In some examples, drape **30** or any portion thereof is formed from an extruded polymeric film, which may be a single layer film or multilayer film of the same or different chemical constituents.

[0053] Additionally or alternatively, basin portion **34** of drape **30** may be formed using a thermoforming technique to produce a thermoformed basin. Thermoforming generally involves heating a plastic sheet until it is pliable (e.g., optionally above the glass transition temperature) and stretching it over a mold having the inverse shape of the shape desired to be imparted into the sheet being thermoformed. The polymeric sheet can have the shape of the mold imparted into it upon cooling, e.g., resulting in a thermoformed basin portion **34**. The thermoforming process may occur under vacuum pressure or positive pressure. When performing vacuum thermoforming, a plastic sheet may be heated until it is pliable (e.g., optionally above the glass transition temperature) and then vacuum drawn down into a mold having the same shape as the shape desired to be imparted into the sheet being thermoformed.

[0054] While basin portion **34** of drape **30** may be formed using other polymer shaping techniques, such as injection molding, blow molding, or rotational molding, thermoforming may be useful to produce a basin portion that has a thinner thickness than would result if using other polymer shaping techniques. Basin portion **34** of drape **30** may collapse more readily to facilitate packing and storage when it is formed of a thinner gauge material than if it is formed of a thicker gauge material that does not collapse into a planar shape.

[0055] While drape **30** and each portion thereof may be formed of any suitable thickness material, in some examples, basin portion **34** is fabricated from a thicker material than the side sheet portion **36**. Fabricating basin portion **34** from a thicker material may be helpful to prevent surgical tools or other potentially sharp objects placed in basin portion **34** during use from puncturing the drape. By contrast, fabricating side sheet portion **36** from a comparatively thinner material may increase the flexibility of the side sheet portion, helping the side sheet portion drape downwardly over the object covered by drape **30**.

[0056] In some configurations, basin portion **34** has a thickness ranging from 0.05 mm to 1 mm, such as from 0.1 mm to 0.5 mm. Side sheet portion **36** may have a thickness less than 0.2 mm, such as less than 0.15 mm, or less than 0.05 mm. For example, side sheet portion **36** may have a thickness ranging from 0.025 mm to 0.15 mm, such as from 0.05 mm to 0.08 mm. A window portion of drape **30** (such as window portions **38**, **40**, when included) can have a thickness substantially equal to that of side sheet portion **36**, basin portion **34**, or yet a different thickness. For example, the window portion(s) of drape **30** may have a thickness that is thinner than that of the side sheet portion **36** and/or basin portion **34**. The window portion(s) may have a thickness and be constructed of a material that allows a screen and/or buttons under the window to be tactile and feelable to a user pressing the screen and/or buttons through the window. In some examples, window portion(s) of drape **30** may have a thickness ranging from 0.05 mm to 0.1 mm. The thickness of each portion of drape **30** may be constant across the drape or may vary across the drape.

[0057] FIG. 7 is a sectional view of basin portion **34** illustrating an example configuration of the basin where the thickness of the basin varies. In this example, basin portion **34** defines a maximum thickness **62** at its perimeter edge **46**. The thickness of the material forming basin portion **34** tapers to a minimum thickness **64** at bottom wall **42**. Although FIG. 7 illustrates the thickness of material progressively and continuously decreasing in thickness along sidewall **44** between perimeter edge **46** and bottom wall **42**, in other configurations, the taper may be discontinuous or may be to a different extent than illustrated in the example figure. The material forming basin portion **34** may

be tapered during the thermoforming process as the polymeric sheet used to form the basin portion is stretched to assume the basin shape. This can result in a thinning of material over the region in which the basin depression is defined as compared to the substantially horizontal/planar perimeter edge of the basin portion, which may be substantially un-deformed through the thermoforming process.

[0058] In some examples, the thickness of sidewall **44** varies from a maximum thickness **62** equal to or greater than 0.4 mm to a minimum thickness **64** where the sidewall joins bottom wall **42** less than 0.4 mm. For example, the maximum thickness **62** of sidewall **44** may range from 0.4 mm to 0.7 mm. The minimum thickness **64** of sidewall **44** may range from 0.1 mm to 0.2 mm.

Accordingly, a ratio of a maximum thickness divided by a minimum thickness of the basin portion **34** may range from 2 to 10, such as from 3 to 5, although other thickness ratios may be used.

[0059] Independent of whether the thickness of sidewall **44** of basin portion **34** is constant or varies, the thickness may be sufficiently small so as to allow the sidewall of the basin portion to collapse. Sidewall **44** may collapse by deforming the sidewall under human hand pressure, causing the sidewall to lose structural rigidity and fold or crumple upon itself. The sidewall **44** may be reversibly expanded by applying an expansion force under human hand pressure opposite the deformation force, causing the folded or crumpled sidewall to elongate and/or stretch out to assume its stretched, wall-like structure. In different examples, bottom wall **42** of basin portion **34** may be rigid or may be as flexible and collapsible (or even more so) than sidewall **44**.

[0060] In practice, drape **30** may be fabricated from a single sheet of material (which may itself be a single layer of material or multiple layers of material integrally bonded together, such as through co-extrusion) or may be fabricated from different sections of material joined together. For example, each portion of drape **30** (e.g., side sheet portion **36**, basin portion **34**, windows **38**, **40**) may be formed separately (e.g., from separate sections of material) and joined together to form drape **30**. Alternatively, drape **30** may be formed from a single, unitary sheet of material in which basin portion **34** is formed to define the drape. Accordingly, while the different portions of drape **30** are described as being connected together herein, it should be appreciated that the portions may be physically connected by being part of a common sheet of material or may be physically connected by bonding different sheets or sections of material together to form drape **30**.

[0061] In some examples, each portion of drape **30** (e.g., side sheet portion **36**, basin portion **34**, windows **38**, **40**) are formed from separate sections or sheets of material, e.g., each of which has a different polymeric composition. Each portion of drape **30** may be cut to a size suitable for incorporation into the resulting drape, e.g., with the edge of the cut portion overlapping an adjacent portion to form a bond therebetween. Any suitable bonding technique can be used to join different portions of drape **30** together to form the resultant drape structure. For example, different portions of drape **30** may be bonded together using an adhesive and/or thermal bonding, such as ultrasonic bonding, RF bonding, laser bonding, or other bonding technique which uses heat to melt and integrally join overlapping sections of polymeric material to form a bond there between.

[0062] In general, the specific dimensions of drape **30** and each portion thereof may vary depending on the configuration of the equipment intended to be covered by the drape. Basin portion **34** of drape **30** can define a height **66** (FIG. 7) that varies depending on whether the basin is in its fully expanded form (deployed use state) or whether it is in its fully collapsed form (packaged state). In some examples, the height **66** of basin portion **34** ranges from 75 mm to 150 mm when the basin is fully expanded. By contrast, when basin portion **34** is fully collapsed, the height of the basin portion may be less than 50 mm, such as less than 25 mm.

[0063] To collapse basin portion **34**, bottom wall **42** and sidewall **44** may be folded up into the void space defined by the basin portion in its otherwise expanded state, as indicated by arrows **68** on FIG. 7. For example, bottom wall **42** of basin portion **34** may be pushed upward and/or side sheet portion **32** pushed downward relative to the basin portion until the bottom wall is substantially coplanar with the side sheet portion. In the process of moving bottom wall **42** to be substantially

coplanar with side sheet portion **36**, sidewall **44** may collapse inwardly to also be substantially coplanar with the bottom wall and side sheet portion. As a result, the cavity defined by basin portion **34** in its expanded state can be eliminated to provide a substantially flat or planar drape. This can facilitate further folding and/or packaging of the drape to provide a compact structure for storage.

[0064] FIG. **8** is a perspective view of drape **30** shown with basin portion **34** collapsed to provide a planar flexible sheet. Depending on factors such as the thickness of the material(s) used to form drape **30** and the configuration of basin portion **34**, drape **30** may define a height **70** less than 25 mm when basin portion **34** is collapsed, such as less than 10 mm, less than 5 mm, or less than 1 mm. In some examples, height **70** ranges from 1 mm to 50 mm when basin portion **34** is collapsed, such as from 5 mm to 25 mm. The height **70** can be measured when basin portion **34** is collapsed and side sheet portion **36** is unfolded (e.g., as opposed to being stacked on top of the collapsed basin portion).

[0065] Drape **30** may include a variety of features to enhance the performance and/or functionality of the drape. As one example, drape **30** may include an electronically readable tag embedded in the drape. For example, the electronically readable tag may be positioned in a pocket formed by bonding two sheets of material together. The electronically readable tag may be positioned within any portion(s) of drape **30**, e.g., to appropriately align the tag relative to the location of a corresponding non-contact electronic tag reader associated with the equipment being covered by drape **30**.

[0066] FIG. **9** is a perspective view of an example portion of drape **30** showing how an electronically readable tag **80** may be arranged in the drape portion. The illustrated example, tag **80** is positioned within a first window portion **38** of drape **30**, although the tag may be positioned at other locations and/or in other portions of the drape without departing from the disclosure.

[0067] To secure and position electronically readable tag **80** in drape **30**, the electronically readable tag **80** may be bonded between multiple layers of multiple. In the example of FIG. **9**, for example, electronically readable tag **80** is illustrated as being positioned between a first layer of material **82** and a second layer of material **84**. Each layer of material **82**, **84** may itself be a single layer of material or multiple layers of material integrally bonded together, such as through co-extrusion, to form a composite layer having an inner face and an outer face. In either case, the first layer of material **82** and the second layer of material **84** can be bonded together, e.g., using any of the bonding techniques discussed above, to seal the electronically readable tag **80** in the space between the layers of material. The layers of material may be sealed and/or joined together directly up to the perimeter of the electronically readable tag **80** or may be joined together to form a pocket surrounding and separated from the perimeter edge of electronically readable tag **80**.

[0068] In some examples, a small slit **86** (e.g., having a length less than the length of electronically readable tag **80**) is formed through one of the layers of material between which the electronically readable tag **80** is positioned. Slit **86** can help during subsequent sterilization of drape **80**, e.g., allowing a chemical sterilization gas such as ethylene oxide to flow into the space between the layers of material **82**, **84** for sterilization.

[0069] Electronically readable tag **80** may be any type of non-transitory electronically readable medium and may be readable using a non-contact reader. In different examples, electronically readable tag **80** may be implemented using as a bar code, a radio frequency identification (RFID) tag, or a near field communication (NFC) tag. The electronically readable tag **80** may or may not be covered with a manufacturer or distributor logo or trademark, such as by placing a sticker bearing the trademark over the electronically readable tag **80**.

[0070] As noted above, drape **30** may be sterilized to provide a sterile covering over the equipment draped for medical procedure. Drape **30** may be sterilized after fabrication, and optionally, after being packaged. To help ensure that drape **30** does not inadvertently become contaminated by an operator during the process of removing the drape from its packaging and deploying it over the

equipment to be draped, drape **30** may be packaged so as to promote sterile and aseptic removal and deployment of the drape. For example, drape **30** may be folded and packaged in such a way that the user can remove the drape from its packaging and employ it over the equipment to be draped while minimizing or eliminating the extent to which the user touches the sterile, outward facing, surfaces of the drape defining the sterile field.

[0071] FIGS. **8** and **10-26** illustrate example folding and packaging steps that may be utilized to produce a folded drape that facilitates subsequent sterile removal and deployment. With reference to FIG. **8**, drape **30** is illustrated as being arranged in a substantially planar or flat layout, which may be achieved by laying the drape out on a table surface for folding. Basin portion **34** is collapsed to be substantially planar with side sheet portion **36**. As illustrated, drape **30** defines a first perimeter edge **100** and a second perimeter edge **102** on an opposite side of the drape from the first perimeter edge. In FIG. **8**, the first perimeter edge **100** and the second perimeter edge **102** are lengthwise edges of a generally rectangular-shaped drape perimeter. In other examples, however, the perimeter edges used for folding may be width-wise edges of a drape having a rectangular-shaped perimeter, opposite side edges of a circular-shaped drape perimeter, or other edges defining the outward extent of the drape to be folded.

[0072] In the folding technique illustrated in FIG. **8**, first edge **100** of drape **30** is folded towards second edge **102** of the drape to form a first fold line **104**. The first fold line **104** may extend parallel to the basin portion **34**. In some examples, first fold line **104** is offset from the basin portion **34** in a direction away from second edge **102**. Additionally or alternatively, first fold line **104** may transect (e.g., cut across) basin portion **34**. The first fold line may bisect basin portion **34** or, in the illustrated example, be offset from a bisecting centerline through basin portion **34** such that first edge **100** is not folded all the way to second edge **102**.

[0073] With reference to FIG. **10**, the first edge **100** of drape **30** can be folded back away from second edge **102**, for example in a direction opposite to the direction the first edge was initially folded toward the second edge. The first edge **100** may be folded back away from second edge **102** a lesser distance than the first edge **100** was previously folded toward the second edge **102**. As a result, this can establish a second fold line **106** offset from the first fold line **104**. The distance and/or drape material between the first fold line **104** and second fold line **106** can define a first drape panel **108**, which may be a folded section of drape material. Depending on the position of first fold line **104** relative to basin portion **36**, first drape panel **108** may be positioned at least partially, and in some examples fully, over the collapsed basin portion **36**.

[0074] Continuing with FIG. **11**, the first edge **100** of drape **30** may again be folded toward the second edge **102** of the drape. The first edge **100** may be folded toward second edge **102** a lesser distance than the first edge **100** was previously folded toward the second edge **102** to define a third fold line **110** offset from the second fold line **106**. The distance and/or drape material between the second fold line **106** and third fold line **110** can define a second drape panel **112**, which may be a second section of folded drape material. Again, depending on the position of second fold line **106** and third fold line **110**, second drape panel **112** may or may not be positioned at least partially, and in some examples fully, over the collapsible basin portion **36**. In different configurations, first panel **108** may have the same width as second panel **112** or may have a different width.

[0075] The process of folding the first edge **100** of drape **30** toward the second edge **102** and back away from the second edge to define additional fold lines, and correspondingly folded panels of material between the fold lines, can be repeated one or more (e.g., multiple) additional times. The number of folds and fold panels created during the folding process may vary, e.g., based on the size of the drape and the size of each panel created during the folding process. FIGS. **12-16** illustrate additional example folding steps that can be performed on drape **30** to define additional fold lines **114** and additional fold panels **116** between adjacent fold lines.

[0076] Once drape **30** has been folded a suitable number of times, the free edge of the drape (e.g., first perimeter edge **100**) may be positioned for grasping by a user during subsequent deployment

of the drape. In some examples, such as the example illustrated in FIG. 17, first edge **100** is folded toward second edge **102** to define a final fold line **118** and to position the first edge **100** over the collapsible basin portion **36**. For example, first edge **100** may be folded toward second edge **102** so the edge is positioned on an axis bisecting basin portion **36**.

[0077] FIG. **18** is a side view illustration of drape **30** showing an example arrangement of fold lines and drape panel portions that may be formed through the process of folding the drape. The resultant folded drape section may have multiple drape panels stacked vertically on top of each other to define a stacked fold arrangement. In some examples, the cumulative number of drape panels in the vertical stack may range from 2 panels to 20 panels, such as from 5 drape panels to 15 drape panels. The drape panels may or may not be positioned over the collapsed basin portion **36**. While the size of each panel may vary, in some examples, each panel ranges from 25 mm to 200 mm, such as from 50 mm to 100 mm.

[0078] Drape **30** in the illustrated example is shown as being symmetrical, such that side sheet portion **34** extends the same distance from basin portion **36** to first edge **100** as the side sheet portion extends from basin portion **36** to second edge **102**. Accordingly, the folding process illustrated and described with respect to FIGS. **8** and **10-18** with respect to one half of the side sheet portion between basin portion **36** and first edge **100** may be replicated on the second half of side sheet portion **34**, either concurrently with, prior to, or after folding the first half of the side sheet portion. In other configurations of drape **30**, side sheet portion **34** may only extend from one side of basin portion **36**, or may extend a different distance from the basin portion to the first edge **100** than the second edge **102**. Accordingly, the number of folds and/or size of drape panels formed during folding may be the same on each side of basin portion **36** or may be different on different sides of the basin portion.

[0079] FIG. **19** is a side view illustration of drape **30** showing an example arrangement of fold lines and drape panel portions that may be formed through the process of folding both sides of the drape. As shown, both sides of drape **30** have been folded to define two vertically stacked sections of panel portions arranged side-by-side next to each other. The first stack of panel sections includes first fold line **104**, second fold line **106**, third fold line **110**, etc. to form first drape panel **108**, second drape panel **112**, etc. The second stack of panel sections includes a fourth fold line **120**, a fifth fold line **122**, a sixth fold line **124**, etc. to form a third drape panel **126**, a fourth drape panel **128**, etc.

[0080] In some examples, the first edge **100** of drape **30** and the second edge **102** of the drape are folded towards each other to create the outermost fold of the full drape. For example, the first edge **100** of drape **30** and second edge **102** of the drape may be brought into adjacent alignment, and in some examples abutting contact. The edges may be substantially centered over the collapsed basin portion **34**, such as in alignment with an axis bisecting the basin portion. In some configurations, a tag, label, or tab is fixed to the first edge **100** and/or the second edge **102**. The respective labels may be co-linearly aligned when the two edges are brought into adjacent alignment and may provide grasping surfaces and/or markers that a user is intended to grasp when opening drape **30**. The respective labels may be positioned so that a user's hands are positioned at the inner-most surface of the drape when grasping at the labels, which can help minimize the risk of the user touching non-sterile equipment when opening the drape.

[0081] In some examples, drape **30** may be folded further beyond the vertically stacked arrangement illustrated in FIG. **19**. For example, FIGS. **20-22** illustrate additional example folds that may be made to drape **30** to provide a compact folded drape structure. As illustrated in the example configuration of FIG. **20**, for instance, opposed folded edges of drape **30** may be folded toward each other to reduce the overall size profile of the folded drape. For example, drape **30** may include a third perimeter edge **130** substantially perpendicular to the first edge **100** and the second edge **102**. The drape may also include a fourth perimeter edge **132** on an opposite side of the drape from the third edge **130**. Drape **30** may be folded by folding a corner **134** formed by an intersection

of the third edge **130** with the first fold line **104** toward the second edge **102** and/or fourth fold line **120**. It should be appreciated that the designation of a particular fold line number is used for purposes of discussion, and the fold line need not be in any particular numeric sequence or representative of any particular number of folds imparted to the drape. Drape **30** may also be folded by folding a corner **136** formed by an intersection of the fourth edge **132** with the first fold line **104** toward second edge **102** and/or fourth fold line **120**.

[0082] As shown in FIG. **21**, a corner **138** formed by the intersection of the third edge **130** with the fourth fold line **120** may be folded toward first edge **100** and/or first fold line **104**, overlapping corner **134**. Additionally, a corner **140** formed by the intersection of the fourth edge **132** with the fourth fold line **120** may be folded toward the first edge **100** and/or first fold line **104**, overlapping corner **136**. The overlapping regions of corners **138** and **140** extending beyond the folded body of drape **30** may be tucked back under the folded body, as shown in FIG. **22**. The ends of the resulting folded body may be folded, for example perpendicular to the basin portion **36**, to define a resulting folded drape as illustrated in FIGS. **23** and **24**.

[0083] After folding, the folded drape may be inserted into a container **150**, as shown in FIG. **25**. Drape **30** and/or container **150** may then be subject to a sterilization treatment to sterilize drape **30** and/or the contents of container **150**. Container **150** may be sealed (e.g., hermetically) to close drape **30** in the container before or after sterilization. In some examples, container **150** is formed of a polymeric material.

[0084] In use, an operator may open container **150** and remove drape **30** from the container. The operator may unfold the ends of the folded drape, e.g., reversing the folding process described above. The operator may place drape **30** and, more particularly, basin portion **36** of the drape over a corresponding basin of the equipment to be draped before fully unfolding the drape. For example, before the operator unfurls the vertically stacked folds imparted to drape **30**, the operator may place the basin portion of the drape in/or over the basin of the equipment being draped. The operator may grasp first edge **100** and second edge **102**, e.g., by grasping respective tabs or labels placed on each edge. The operator may then pull the edges outwardly and away from each other, unfolding the vertically folded drape sections, e.g., as illustrated in FIG. **26**. In some examples, the operator may push the collapsed basin portion **36** downwardly into the basin of the equipment being draped, thereby expanding the collapsed basin portion of the drape and causing the basin portion to conform to the walls of the basin of equipment being draped. In either case, by folding drape **30** so that an operator can deploy the drape while minimizing the extent to which the outward facing surface of the drape is contacted during deployment, the likelihood that the sterile surfaces the drape may be contaminated during deployment are reduced.

[0085] Various examples have been described. These and other examples are within the scope of the following claims.

Claims

1. A drape for a surgical fluid thermal treatment system comprising: a flexible sheet comprising: a basin portion having a basin perimeter and fabricated from a basin polymer composition; a window portion fabricated from a window polymer composition different than the basin polymer composition; and a side sheet portion extending from the basin portion along at least a part of the basin perimeter; wherein the basin portion is configured to be positioned in an open basin of a surgical fluid thermal treatment system, and the side sheet portion is configured to cover at least a part of the surgical fluid thermal treatment system.
2. The drape of claim 1, wherein the side sheet portion is fabricated from a side sheet polymer composition different than the basin polymer composition.
3. The drape of claim 1, wherein the side sheet portion is fabricated from a side sheet polymer composition different than the window polymer composition.

4. The drape of claim 1, wherein the side sheet portion is fabricated from a side sheet polymer composition different than the basin polymer composition and the window polymer composition.
 5. The drape of claim 4, wherein the side sheet polymer composition comprises polyurethane.
 6. The drape of claim 1, wherein the basin portion has a width and a length that is greater than the width, and the window portion projects away from a lengthwise perimeter section of the basin portion.
 7. The drape of claim 6, wherein the side sheet portion extends from the basin perimeter at a widthwise perimeter section of the basin portion and from an edge of the window portion in at least a part of the basin lengthwise perimeter section.
 8. The drape of claim 1, wherein the window portion is positioned between the basin portion and the side sheet portion along at least a part of the basin perimeter.
 9. The drape of claim 1, wherein the side sheet portion extends from the basin portion in a first basin perimeter section.
 10. The drape of claim 9, wherein the window portion extends from the basin perimeter in a second basin perimeter section.
 11. The drape of claim 10, wherein a first edge of the window portion is connected with the basin portion and a second edge of the window portion is connected with the side sheet portion.
 12. A drape for a surgical fluid thermal treatment system comprising: a flexible sheet comprising: a basin portion having a basin perimeter and fabricated from a basin polymer composition; a window portion fabricated from a window polymer composition, the window polymer composition comprising a tackifying agent; and a side sheet portion fabricated from a side sheet polymer composition and extending from the basin along at least a part of the basin perimeter; wherein the basin portion is configured to be positioned in an open basin of a surgical fluid thermal treatment system, and the side sheet portion is configured to cover at least a part of the surgical fluid thermal treatment system.
 13. The drape of claim 12, wherein the window portion overlays a user interface of the surgical fluid thermal treatment system when the drape is positioned over the surgical fluid thermal treatment system.
 14. The drape of claim 13, wherein the tackifying agent increases friction between the window portion and the user interface.
 15. The drape of claim 14, wherein the increased friction between the window portion and the user interface resists movement of the window portion relative to the user interface.
 16. The drape of claim 12, wherein the window polymer composition differs from the basin polymer composition.
 17. A drape for a surgical fluid thermal treatment system comprising: a flexible sheet comprising: a basin portion having a perimeter and comprising a basin material having a basin thickness; a window portion comprising a window material having a window thickness different from the basin thickness; and a side sheet portion comprising a side sheet material having a side sheet thickness different from the window thickness, the side sheet extending from the basin portion along at least a portion of the basin portion perimeter; wherein the basin portion is configured to be positioned in an open basin of a surgical fluid thermal treatment system, and the side sheet portion is configured to cover at least a part of the surgical fluid thermal treatment system.
 18. The drape of claim 17, wherein the window thickness is less than a thickness of the basin portion.
 19. The drape of claim 17, wherein the window thickness is less than a thickness of the side sheet portion.
 20. The drape of claim 17, wherein the window thickness is less than basin thickness and less than the side sheet thickness.
-