

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250286035

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Hu; Shun-Yuan et al.

ELECTRONIC DEVICE

Abstract

Disclosed are an electronic device. The electronic device includes a substrate, a metal layer, a transistor, a first chip, and a second chip. The metal layer is disposed on the substrate. The transistor is disposed on the substrate and overlaps with the metal layer. The first chip is disposed on the substrate, and is electrically connected to the metal layer and the transistor. The second chip is disposed on the substrate and is adjacent to the first chip. A first angle is between a first extension direction of a first side of the first chip and an extension direction of a first boundary of the second substrate. A second angle is between a second extension direction of a second side of the second chip and the extension direction of the first boundary of the second substrate. The first angle is different from the second angle.

Inventors: Hu; Shun-Yuan (Miaoli County, TW), Ho; Chia-Chi (Miaoli County, TW)

Applicant: Innolux Corporation (Miaoli County, TW)

Family ID: 83232762

Assignee: Innolux Corporation (Miaoli County, TW)

Appl. No.: 19/218654

Filed: May 27, 2025

Foreign Application Priority Data

CN 202210513602.1

May. 12, 2022

Related U.S. Application Data

parent US continuation 17876508 20220728 parent-grant-document US 12341142 child US 19218654

us-provisional-application US 63233334 20210816

Publication Classification

Int. Cl.: H01L25/16 (20230101); H01L21/683 (20060101); H01L23/00 (20060101)

U.S. Cl.:

CPC H01L25/167 (20130101); H01L21/6835 (20130101); H01L24/08 (20130101); H01L24/16 (20130101); H01L2221/68368 (20130101); H01L2224/08145 (20130101); H01L2224/16227 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application is a continuation application of and claims the priority benefit of a prior application Ser. No. 17/876,508, filed on Jul. 28, 2022, which claims the priority benefits of U.S. provisional application Ser. No. 63/233,334, filed on Aug. 16, 2021 and China application no. 202210513602.1, filed on May 12, 2022. The entirety of each of the above-mentioned patent applications is hereby incorporated by reference herein and made a part of this specification.

BACKGROUND

Technical Field

[0002] The disclosure relates to an electronic device. In particular, the disclosure relates to an electronic device that can meet diverse requirements of users.

Description of Related Art

[0003] Currently, since a transfer machine can only move in an X-Y plane, a temporary substrate with a release film (e.g., a blue film) and chips mounted thereon moves at a fixed angle. Thus, during transfer of the chips from the temporary substrate to a target substrate, the chips are only at a single angle on the target substrate. Accordingly, if users need to change the angle of the chips on the target substrate for appearance reliability or electrical requirements, major operation of first suspending the production line is required to change settings of the machine or the like, which is relatively costly.

SUMMARY

[0004] The disclosure is directed to an electronic device, in which extension directions of sides of a plurality of transferred chips can respectively form a plurality of different angles with an extension direction of a boundary of a substrate.

[0005] According to an embodiment of the disclosure, an electronic device includes a substrate, a metal layer, a transistor, a first chip, and a second chip. The metal layer is disposed on the substrate. The transistor is disposed on the substrate and overlaps with the metal layer. The first chip is disposed on the substrate, and is electrically connected to the metal layer and the transistor. The second chip is disposed on the substrate and is adjacent to the first chip. A first angle is between a first extension direction of a first side of the first chip and an extension direction of a first boundary of the second substrate. A second angle is between a second extension direction of a second side of the second chip and the extension direction of the first boundary of the second substrate. The first angle is different from the second angle.

[0006] Based on the foregoing, in the embodiments of the disclosure, different angles are between the extension directions of the sides of the first chip and the second chip and the extension direction of the boundary of the second substrate after the first chip and the second chip are sequentially transferred to the second substrate. Compared with the existing technology, in which only a single angle is between the transferred chips and the substrate, the electronic device of the disclosure can

meet the diverse requirements of users.

[0007] To make the aforementioned more comprehensible, several embodiments accompanied with drawings are described in detail as follows.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The accompanying drawings are included to provide a further understanding of the disclosure, and are incorporated in and constitute a part of this specification. The drawings illustrate exemplary embodiments of the disclosure and, together with the description, serve to explain the principles of the disclosure.

[0009] FIG. 1A is a schematic diagram of a manufacturing method of an electronic device according to an embodiment of the disclosure.

[0010] FIG. 1B is a schematic diagram of a first chip, a second chip, and a third chip on a second substrate in FIG. 1A.

[0011] FIG. 2 is a schematic diagram of a manufacturing method of an electronic device according to another embodiment of the disclosure.

[0012] FIG. 3 is a schematic diagram of a manufacturing method of an electronic device according to another embodiment of the disclosure.

[0013] FIG. 4 is a schematic diagram of a manufacturing method of an electronic device according to another embodiment of the disclosure.

[0014] FIG. 5 is a schematic diagram of a manufacturing method of an electronic device according to another embodiment of the disclosure.

[0015] FIG. 6 is a schematic diagram of a manufacturing method of an electronic device according to another embodiment of the disclosure.

[0016] FIG. 7 is a schematic diagram of a manufacturing method of an electronic device according to another embodiment of the disclosure.

[0017] FIG. 8 is a schematic diagram of a manufacturing method of an electronic device according to another embodiment of the disclosure.

DESCRIPTION OF THE EMBODIMENTS

[0018] Reference will now be made in detail to exemplary embodiments of the disclosure, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numerals are used in the drawings and description to refer to the same or like parts.

[0019] The disclosure may be understood with reference to the following detailed description together with the accompanying drawings. It should be noted that, for ease of understanding by readers and conciseness of the drawings, a plurality of drawings in the disclosure merely show a part of an electronic device, and specific elements in the drawings are not drawn to scale. In addition, the number and size of the elements in the drawings only serve for exemplifying instead of limiting the scope of the disclosure.

[0020] Certain terms are used throughout the description and the appended claims to refer to specific elements. Those skilled in the art should understand that electronic device manufacturers may refer to the same element by different names. Herein, it is not intended to distinguish between elements that have the same function but have different names.

[0021] In the following description and claims, terms such as “include”, “comprise”, and “have” are open-ended terms, and thus should be interpreted as “including, but not limited to”.

[0022] In addition, relative terms, such as “below” or “bottom” and “above” or “top,” may be used in the embodiments to describe the relative relationship of one element to another element of the drawings. It will be understandable that if the device in the drawings is turned upside down, elements described on the “lower” side will become elements described on the “upper” side.

[0023] In some embodiments of the disclosure, terms related to bonding and connection such as “connection”, “interconnection”, etc., unless specifically defined, may indicate the case where two structures are in direct contact, or where two structures are not in direct contact and other structures are disposed in between. Moreover, such terms related to bonding and connection may also cover the case where two structures are both movable or where two structures are both fixed. Furthermore, the term “coupling” includes transfer of energy between two structures by means of direct or indirect electrical connection, or transfer of energy between two separate structures by means of mutual induction.

[0024] It should be understood that when an element or film layer is referred to as being “on”, or “connected to” another element or film layer, the element or film layer may be directly on or connected to the another element or film layer, or intervening elements or film layers may also be present in between (non-direct circumstances). In contrast, when an element or film layer is referred to as being “directly on” or “directly connected to” another element or film layer, no intervening elements or film layers are present in between.

[0025] The term “about”, “equal to”, “equivalent” or “same”, “substantially”, or “essentially” is typically interpreted so that a value is within 20% of a given value or range, or within 10%, 5%, 3%, 2%, 1%, or 0.5% of a given value or range.

[0026] As used herein, the term(s) “film” and/or “layer” may refer to any continuous or discontinuous structure and material (e.g., materials deposited by the methods disclosed herein). For example, films and/or layers may include two-dimensional materials, three-dimensional materials, nanoparticles, or even partial or complete molecular layers, or partial or complete atomic layers, or atomic and/or molecular clusters. The films or layers may include materials or layers having pinholes and may be at least partially continuous.

[0027] Although the terms first, second, third, and so on may be used to describe diverse constituent elements, such constituent elements are not limited by the terms. The terms are used only to discriminate one constituent element from other constituent elements in the description. In the claims, the terms first, second, third, etc. may be used in accordance with the order of claiming elements instead of using the same terms. Accordingly, a first constituent element in the following description may be a second constituent element in the claims.

[0028] Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art. It is understandable that these terms, such as those defined in commonly used dictionaries, should be interpreted to have a meaning consistent with the background or context of the related art and the disclosure, and not interpreted in an idealized or overly formal manner, unless specifically defined herein.

[0029] It should be noted that features in several different embodiments below may be replaced, recombined, mixed with each other to achieve other embodiments without departing from the spirit of the disclosure.

[0030] The electronic device of the disclosure may include, but is not limited to, a display device, an antenna device, a sensing device, a light-emitting device, or a tiled device. The electronic device may include a bendable or flexible electronic device. The electronic device may include electronic components. The electronic components may include passive elements, active elements, or a combination thereof, for example, a capacitor, a resistor, an inductor, a variable capacitor, a filter, a diode, a transistor, a sensor, MEMS, a liquid crystal chip, but not limited thereto. The diode may include a light-emitting diode (LED) or a non-light-emitting diode. The diode include a P-N junction diode, a PIN diode, or a constant current diode. The light-emitting diode may include an organic light-emitting diode (OLED), a mini LED, a micro LED, a quantum dot LED, fluorescence, phosphor, or other suitable materials or a combination thereof, for example but not limited thereto. The sensor may include a capacitive sensor, an optical sensor, an electromagnetic sensor, a fingerprint sensor (FPS), a touch sensor, an antenna, or a pen sensor, for example but not

limited thereto. Hereinafter, a display device will be taken as the electronic device to describe the disclosure, but the disclosure is not limited thereto.

[0031] Reference will now be made in detail to exemplary embodiments of the disclosure, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numerals are used in the drawings and description to refer to the same or like parts.

[0032] FIG. 1A is a schematic diagram of a manufacturing method of an electronic device according to an embodiment of the disclosure. FIG. 1B is a schematic diagram of a first chip, a second chip, and a third chip on a second substrate in FIG. 1A.

[0033] First, reference may be made to FIG. 1A for the manufacturing method of an electronic device of this embodiment. First, a first substrate **10** including a plurality of chips **110** is provided. The first substrate **10** may be a wafer, a glass substrate, or a polyimide substrate (PI), for example but not limited thereto. In an embodiment, the first substrate **10** may be provided with a release film (e.g., a blue film) thereon. The release film is located between the first substrate **10** and the chips **110** to facilitate separation of the chips from the first substrate **10**. Therefore, the first substrate **10** may be regarded as a temporary substrate. In an embodiment, the first substrate **10** may have a chamfer, an arc, or any other shape. The chips **110** may be packaged or bare, and may also be a capacitor, a resistor, an inductor, a variable capacitor, a filter, a diode, a transistor, a sensor, MEMS, a liquid crystal chip, for example but not limited thereto. The diode may include a light-emitting diode or a non-light-emitting diode. The diode include a P-N junction diode, a PIN diode, or a constant current diode. The light-emitting diode may include an organic light-emitting diode (OLED), a mini LED, a micro LED, a quantum dot LED, fluorescence, phosphor, or other suitable materials or a combination thereof, for example but not limited thereto. The sensor may include a capacitive sensor, an optical sensor, an electromagnetic sensor, a fingerprint sensor (FPS), a touch sensor, an antenna, or a pen sensor, for example but not limited thereto.

[0034] Next, with continued reference to FIG. 1A, a second substrate **20** and a pick-and-place device **30** are provided. The first substrate **10** and the second substrate **20** may be respectively located on opposite sides of the pick-and-place device **30**, but not limited thereto. Here, for example, the first substrate **10** and the second substrate **20** are disposed on the X-Y plane, and the pick-and-place device **30** may move on the X-Y plane. The second substrate **20** may be a wafer, a glass substrate, or a polyimide substrate, for example but not limited thereto. In an embodiment, the second substrate **20** may have a chamfer, an arc, or any other shape.

[0035] After that, a transfer process is performed to sequentially transfer a first chip **112** and a second chip **114** among the chips **110** to the second substrate **20**. The second chip **114** is adjacent to the first chip **112** on the second substrate **20**. Therefore, the second substrate **20** may be regarded as a target substrate. The first chip **112** and the second chip **114** may be in the same shape or in different shapes. Here, the shape of the first chip **112** is a rectangle with rounded corners, and the shape of the second chip **114** is a rhombus, for example but not limited thereto. Here, the transfer process is rotating the first substrate **10**, for example. In other words, the first substrate **10** is rotated relative to the X-axis, while the second substrate **20** remains stationary.

[0036] Further, with reference to FIG. 1A and FIG. 1B together, after the first substrate **10** including the chips **110** is rotated by an angle relative to the X-axis, the pick-and-place device **30** picks up the first chip **112** from the first substrate **10** and places the first chip **112** on the second substrate **20**. Next, after the first substrate **10** is rotated by another angle relative to the X-axis, the pick-and-place device **30** picks up the second chip **114** from the first substrate **10** and places the second chip **114** adjacent to the first chip **112** on the second substrate **20**. At this time, a first angle **A1** is between a first extension direction **D1** of a first side **S1** (i.e., a long side) of the first chip **112** and an extension direction **D** of a first boundary **B** of the second substrate **20**. In addition, a second angle **A2** is between a second extension direction **D2** of a second side **S2** of the second chip **114** and the extension direction **D** of the first boundary **B** of the second substrate **20**. In particular, the first angle **A1** is different from the second angle **A2**. Here, for example, the first angle **A1** is greater

than 0 and less than or equal to 90 degrees, and the second angle A2 is greater than 0 and less than or equal to 90 degrees. A difference between the first angle A1 and the second angle A2 is less than 90 degrees, for example. In an embodiment, the difference between the first angle A1 and the second angle A2 is less than 45 degrees, for example. In another embodiment, the difference between the first angle A1 and the second angle A2 is less than 20 degrees, for example. Here, for example, the boundary B may be the long side of the substrate, and the sides may be the long sides of the chips. Alternatively, when side lengths of the chip are the same, the side adjacent to the long side of the substrate is taken as the reference, but not limited thereto.

[0037] Next, with reference to FIG. 1A and FIG. 1B together, the above-mentioned steps may also be repeated to further transfer a third chip 116 among the chips 110 to the second substrate 20. The third chip 116 is adjacent to the second chip 114, and the second chip 114 is located between the first chip 112 and the third chip 116, but not limited thereto. The shape of the third chip 116 is a triangle, for example but not limited thereto. A third angle A3 is between a third extension direction D3 of a third side S3 of the third chip 116 and the extension direction D of the first boundary B of the second substrate 20. In addition, the third angle A3 is different from the first angle A1 and the second angle A2. Here, the third angle A3 is greater than 0 and less than or equal to 90 degrees, for example. A difference between the first angle A1, the second angle A2, and the third angle A3 is less than 90 degrees, for example. In an embodiment, the difference between the first angle A1, the second angle A2, and the third angle A3 is less than 45 degrees, for example. In another embodiment, the difference between the first angle A1, the second angle A2, and the third angle A3 is less than 20 degrees, for example.

[0038] In brief, in this embodiment, the first chip 112, after the second chip 114, and the third chip 116 are sequentially transferred to the second substrate 20, the first angle A1, the second angle A2, and the third angle A3 of different angles are respectively between the extension direction D of the first boundary B of the second substrate 20 and the first extension direction D1 of the first side S1, the second extension direction D2 of the second side S2, and the third extension direction D3 of the third side S3. Compared with the existing technology, in which only a single angle is between the transferred chips and the substrate, the manufacturing method of an electronic device of the disclosure can meet the diverse requirements of users who need to change the angle of the chips on the target substrate for appearance reliability or electrical requirements.

[0039] It should be noted here that reference numerals and partial contents of the embodiments above remain to be used in the following embodiments, and the same reference numerals are used to refer to the same or like elements, and the description of the same technical content is omitted. Reference may be made to the embodiments above for the description of the omitted part, which will not be repeated in the following embodiments.

[0040] FIG. 2 is a schematic diagram of a manufacturing method of an electronic device according to another embodiment of the disclosure. With reference to FIG. 1A and FIG. 2 together, the manufacturing method of an electronic device of this embodiment is similar to the manufacturing method of an electronic device of FIG. 1A. The difference between them is that this embodiment also includes forming a metal layer 120 and an opening hole H after providing the second substrate 20 and before performing the transfer process. The metal layer 120 is located between the second substrate 20 and the first chip 112. An orthogonal projection of the first chip 112 on the second substrate 20 is overlapped with the opening hole H. Further, the metal layer 120 may be formed on the second substrate 20 and covered by a dielectric layer 125 having the opening hole H. The first chip 112 may be disposed in the opening hole H of the dielectric layer 125 and electrically connected to the metal layer 120 through a solder T1. Next, a pad 130 may be further between the second chip 114 and the metal layer 120. The first chip 112 may be electrically connected to the pad 130 through a solder T2, and the second chip 114 is directly disposed on the pad 130. Here, the first chip 112 is a light-emitting diode, and the second chip 114 is an active element, such as a thin film transistor, for example but not limited thereto. In addition, the metal layer 120 includes copper

(Cu), titanium (Ti), or aluminum (Al), for example but not limited thereto.

[0041] Furthermore, a spacer **140** is formed on the dielectric layer **125**. Next, a protective layer **150** is formed on the first chip **112** and the second chip **114** to protect the first chip **112** and the second chip **114**. Disposing the spacer **140** maintains the distance between the protective layer **150** and the first chip **112** and the second chip **114**. Finally, a sealing member **160** is between a periphery of the second substrate **20** and a periphery of the protective layer **150** to prevent moisture and oxygen from eroding the first chip **112**, the second chip **114**, the metal layer **120**, and the pad **130**. For example, the sealing member **160** is formed adjacent to the boundary of the second substrate **20**. So far, an electronic device **100** is completed. Here, the electronic device **100** may include a display device, an antenna device, a sensing device, a light-emitting device, a packaging device, or a tiled device, but not limited thereto. According to another embodiment, it is also possible to first form the sealing member **160** on the periphery of the second substrate **20**, and then form the protective layer **150** on the second substrate **20** and the spacer **140**, but not limited thereto.

[0042] FIG. **3** is a schematic diagram of a manufacturing method of an electronic device according to another embodiment of the disclosure. With reference to FIG. **1A** and FIG. **3** together, the manufacturing method of an electronic device of this embodiment is similar to the manufacturing method of an electronic device of FIG. **1A**. The difference between them is that in this embodiment, the first substrate **10** and the second substrate **20** are disposed on the X-Z plane. In addition, the pick-and-place device **30** may move in the X-Z plane, and the transfer process is rotating the first substrate **10**, for example. In other words, the first substrate **10** is rotated relative to the Z-axis, while the second substrate **20** remains stationary.

[0043] FIG. **4** is a schematic diagram of a manufacturing method of an electronic device according to another embodiment of the disclosure. With reference to FIG. **1A** and FIG. **4** together, the manufacturing method of an electronic device of this embodiment is similar to the manufacturing method of an electronic device of FIG. **1A**. The difference between them is that in this embodiment, the first substrate **10** and the second substrate **20** are disposed on the X-Y plane. In addition, the pick-and-place device **30** may move in the X-Y plane, and the transfer process is rotating the second substrate **20**, for example. In other words, the second substrate **20** is rotated relative to the X-axis, while the first substrate **10** remains stationary.

[0044] FIG. **5** is a schematic diagram of a manufacturing method of an electronic device according to another embodiment of the disclosure. With reference to FIG. **1A** and FIG. **5** together, the manufacturing method of an electronic device of this embodiment is similar to the manufacturing method of an electronic device of FIG. **1A**. The difference between them is that in this embodiment, the first substrate **10** and the second substrate **20** are disposed on the X-Z plane. In addition, the pick-and-place device **30** may move in the X-Z plane, and the transfer process is rotating the second substrate **20**, for example. In other words, the second substrate **20** is rotated relative to the Z-axis, while the first substrate **10** remains stationary.

[0045] FIG. **6** is a schematic diagram of a manufacturing method of an electronic device according to another embodiment of the disclosure. With reference to FIG. **1A** and FIG. **6** together, the manufacturing method of an electronic device of this embodiment is similar to the manufacturing method of an electronic device of FIG. **1A**. The difference between them is that in this embodiment, the first substrate **10** and the second substrate **20** are disposed on the X-Y plane. In addition, the pick-and-place device **30** may be moved in the X-Y plane, and the transfer process includes rotating a rotary disk **40** disposed on the pick-and-place device **30**, for example. In other words, the arrangement angles of the first chip **112**, the second chip **114**, and the third chip **116** after transferred to the second substrate **20** may be changed by rotating the rotary disk **40**. In other words, the first substrate **10** and the second substrate **20** remain stationary during the transfer process.

[0046] FIG. **7** is a schematic diagram of a manufacturing method of an electronic device according to another embodiment of the disclosure. With reference to FIG. **6** and FIG. **7** together, the

manufacturing method of an electronic device of this embodiment is similar to the manufacturing method of an electronic device of FIG. 6. The difference between them is that a first substrate **10'** of this embodiment and the first substrate **10** in FIG. 6 are in different structural forms. The first substrate **10'** is embodied as a flexible substrate, such as a tape, but not limited thereto.

[0047] FIG. 8 is a schematic diagram of a manufacturing method of an electronic device according to another embodiment of the disclosure. With reference to FIG. 1A and FIG. 8 together, the manufacturing method of an electronic device of this embodiment is similar to the manufacturing method of an electronic device of FIG. 1A. The difference between them is that in this embodiment, the pick-and-place device **30** includes a plurality of robot arms **50** each having a rotary disk **52** at the front end. In addition, the transfer process includes rotating the rotary disk **52** of the robot arm **50**. In an embodiment, for example, the arrangement angles of the first chip **112**, the second chip **114**, and the third chip **116** after transferred to the second substrate **20** may be changed by independently controlling the rotary disk **52** of each of the robot arms **50** to rotate the rotary disks **52** by different angles, which accelerates the pick-and-place process to reduce the manufacturing time.

[0048] In summary of the foregoing, in the embodiments of the disclosure, different angles are between the extension directions of the sides of the first chip and the second chip and the extension direction of the boundary of the second substrate after the first chip and the second chip are sequentially transferred to the second substrate. Compared with the existing technology, in which only a single angle is between the transferred chips and the substrate, the manufacturing method of an electronic device of the disclosure can meet the diverse requirements of users.

[0049] It will be apparent to those skilled in the art that various modifications and variations can be made to the disclosed embodiments without departing from the scope or spirit of the disclosure. In view of the foregoing, it is intended that the disclosure covers modifications and variations provided that they fall within the scope of the following claims and their equivalents.

Claims

1. An electronic device, comprising: a substrate; a metal layer, disposed on the substrate; a transistor, disposed on the substrate and overlapping with the metal layer; a first chip, disposed on the substrate and electrically connected to the metal layer and the transistor; and a second chip, disposed on the substrate and adjacent to the first chip, wherein a first angle is between a first extension direction of a first side of the first chip and an extension direction of a first boundary of the second substrate, a second angle is between a second extension direction of a second side of the second chip and the extension direction of the first boundary of the second substrate, and the first angle is different from the second angle.
2. The electronic device according to claim 1, further comprising an antenna device.
3. The electronic device according to claim 1, wherein the metal layer includes copper.
4. The electronic device according to claim 1, wherein the metal layer includes a gap, and the first chip overlaps the gap.
5. The electronic device according to claim 1, wherein the first chip has three contact points, two of the three contact points are electrically connected to the metal layer, and the other of the three contact points is electrically connected to the transistor.
6. The electronic device according to claim 5, further comprising: a pad, overlapping the metal layer, and the first chip is electrically connected to the transistor through the pad.
7. The electronic device according to claim 1, wherein a difference between the first angle and the second angle is less than 45 degrees.
8. The electronic device according to claim 1, further comprising: a third chip, disposed on the substrate and adjacent to the second chip, wherein a third angle is between a third extension

direction of a third side of the third chip and an extension direction of the first boundary of the second substrate, and the third angle is different from the first angle and the second angle.
