

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396527
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Heinz; Martin

Jewelry piece

Abstract

An item of jewelry has a main body with a first and second end, which, in the closed state, is located opposite the first end. The main body defines a through-opening and the two ends of the main body can be moved away from one another to form a through-opening. The main body has a channel, in which at least one resiliently elastic element is movably arranged. The first end of at least one connecting element is fastened directly or indirectly on the first end of the main body, and which extends over a free space between the first and the second ends of the main body in the open state. When the first and second ends of the main body are moved apart the resulting activation of the resiliently elastic element generates a restoring force which moves the two ends of the main body towards one another.

Inventors:	Heinz; Martin (Neulingen, DE)
Applicant:	Joerg Heinz GmbH & Co. KG (Neulingen, DE)
Family ID:	1000008778895
Assignee:	Joerg Heinz GmbH & Co. KG (Neulingen, DE)
Appl. No.:	18/460685
Filed:	September 04, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230404223 A1	Dec. 21, 2023

Foreign Application Priority Data

DE	10 2021 001 206.2	Mar. 08, 2021
----	-------------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: A44C5/00 (20060101)

U.S. Cl.:

CPC A44C5/0069 (20130101);

Field of Classification Search

CPC: A44C (5/0076); A44C (5/0069); A44C (5/0061); A44C (5/0053); A44C (5/0084); A44C (5/0092)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
237344	12/1880	Vester	63/8	A44C 5/12
407566	12/1888	Ballou	59/79.2	A44C 5/0076
1069254	12/1912	Henning	63/29.1	A44C 17/0208
1140445	12/1914	Collingwood et al.	63/5.1	A44C 5/0061
1526702	12/1924	Feid	63/3	A44C 5/0069
1744206	12/1929	Bopp	63/11	A44C 5/0076
1807440	12/1930	Schraysshuen	63/3	A44C 5/0076
2270216	12/1941	Marwil	224/175	A44C 5/0069
2554629	12/1950	Meyer	63/3	A44C 11/002
2600232	12/1951	Feid	D11/4	A44C 5/0069
2639067	12/1952	Hirsch	224/174	A44C 5/0069
2695740	12/1953	Kolbe	224/175	A44C 5/0069
2751132	12/1955	Myerson	224/175	A44C 5/0069
3136139	12/1963	Sinner	224/175	A44C 5/0076
3580438	12/1970	Raval	63/11	A44C 5/04
3693375	12/1971	Paulsen	224/175	A44C 5/0069
5823409	12/1997	Kennedy	24/301	A44C 5/22
2005/0083788	12/2004	Ogletree	368/282	A44C 5/0069
2009/0120130	12/2008	Mabra	63/3.1	A44C 5/22
2014/0113095	12/2013	Xu	428/37	A44C 5/0069
2015/0335108	12/2014	Chiarini	29/896.41	A44C 15/005
2016/0345690	12/2015	Scandolaro	N/A	A44C 5/0076
2020/0329831	12/2019	Kubiak	N/A	A44C 5/20
2021/0298432	12/2020	Picchiotti	N/A	A44C 5/0084
2024/0156217	12/2023	Aivaz	N/A	A44C 5/22

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
7412877	12/1973	DE	N/A
1154138	12/1957	FR	N/A

Primary Examiner: San; Jason W

Assistant Examiner: Rashid; Anna S

Attorney, Agent or Firm: Orbit IP, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This continuation application claims priority to PCT/EP2022/025090 filed on Mar. 8, 2022, which has published as WO 2022/189037 A1 and also the German application number 10 2021 001 206.2 filed on Mar. 8, 2021, the entire contents of which are fully incorporated herein with these references.

FIELD OF THE INVENTION

(1) The invention relates to a piece of jewelry with a base body having a first end and a second end arranged oppositely to the first end in a close state of the piece of jewelry, the base body defining a passage opening and the two ends of the base body can be moved away from each other to form a widened passage opening which is wider than the passage opening, the base body having a channel in which at least one resilient element is movably arranged.

BACKGROUND OF THE INVENTION

(2) Such a piece of jewelry is known and is used as a wrist band or arm hoop, foot band or foot hoop or neck band or neck hoop, in order just to name a few examples. Such pieces of jewelry surround the corresponding body part of the carrier more or less tightly when worn, so that for a removal or for an application of the piece of jewelry a clasp has got to be opened and the two ends of the piece of jewelry being arranged oppositely to each other in the closed stated must be moved away from one another, thereby creating a passage opening which is large enough for the respective body part, e.g., arm, foot or neck of the carrier, to move through it. The known piece of jewelry has, on its first end, a closing element of a clasp and on its second end a closing element formed complementary to the first closing element. After the piece of jewelry has been applied, this clasp has got to be closed in order to enable a secure wearing of the piece of jewelry. This is not simple, in particular, in the case of filigree jewelry pieces with a tiny clasp, since, in order to close the piece of jewelry, the first closing element must be inserted into the second closing element complementary to the first closing element.

(3) The German patent document DE 74 12 877 U discloses a stretchable watch strap which has two rigid brackets which are mounted pivotably on a watch housing and which are hollow in order to create a receiving space for accommodating a connecting member forming a connecting bridge between the brackets, wherein a spring-like retraction device is arranged in the receiving space of the brackets between one of the ends of the receiving space and one of the ends of the connecting member. The connecting element consists of a cord or a pliable band, has a stop at each of its ends and is slidable in the interior of the two brackets. It extends over the entire length of the brackets. Each of these brackets has a compression spring which is arranged coaxially to the flexible cord and which, in its closed position, loads the two brackets. One end of each spring supports on a traverse wall of the respective rigid bracket, which has an opening the cross section of which corresponds to the form and dimension of the pliable band. With its other end, each compression spring rests on a stop of the pliable cord. A first end of each bracket is attached to one side of the watch case via a hinge and each of the two compression springs provided in one bracket each therefore extends from the end of the respective bracket facing the watch case to the other end of

the bracket and is connected there to one end of the connecting member. By pulling apart the two second ends of the two brackets articulatedly connected to the watch case a passage opening defined by the watch strap can be enlarged.

SUMMARY OF THE INVENTION

(4) It is the object of the present invention to further develop a piece of jewelry of the type mentioned at the beginning in such a way that a closing of the piece of jewelry is facilitated.

(5) This object is solved by a piece of jewelry characterized in that the channel of the base body extends from the first end to the second end of the base body, and that the piece of jewelry comprises at least one connecting element, the first end of which is attached directly or indirectly to the first end of the base body, extends across a space being present between the first end and the second end of the base body in its opened state and engages with its second end one end of the resilient element in such a way that, when the first and the second ends of the base body are moved apart from each other to form a widened passage opening, by the therefrom resulting loading of the resilient element a restoring force causing the two ends of the base body to move towards each other can be generated.

(6) By means of the measures according to the invention in an advantageous way a piece of jewelry is created allowing a closing of the piece of jewelry without a clasp. Since it is provided according to the invention that by means of the resilient element a restoring force is created, which causes the two ends of the base body to move towards each other, the closing, i.e., the bringing together of the two ends of the base body, is achieved “automatically”, and a separate clasp, which is up to now required in the case of known pieces of jewelry is in an advantageous way manner no longer necessary.

(7) Advantageous developments of the invention are the subject matter of the dependent claims.

(8) Further details and advantages of the invention can be gathered from the exemplary embodiments, which are described below with reference to the figures. They show:

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates a section through a first embodiment of a piece of jewelry in its closed state,

(2) FIG. 2 illustrates a section through the embodiment according to FIG. 1 in its opened state,

(3) FIG. 3 illustrates a section through a second embodiment of a piece of jewelry in its closed state,

(4) FIG. 4 illustrates a section through the embodiment according to FIG. 3 in its opened state,

(5) FIG. 5 illustrates a section through a third embodiment of a piece of jewelry in its closed state,

(6) FIG. 6 illustrates a section through the embodiment according to FIG. 5 in its opened state,

(7) FIG. 7 illustrates a section through a fourth embodiment of a piece of jewelry in its closed state,

(8) FIG. 8 illustrates a section through the embodiment according to FIG. 7 in its opened state, and

(9) FIG. 9 illustrates a section through the fourth embodiment in its opened state.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

(10) FIGS. 1 and 2 show a first exemplary embodiment of a piece of jewelry, which has a base body 1 having a first end 1a and a second end 1b being arranged opposite to the first end 1a in a closed state of the piece of jewelry. The base body 1 defines a passage opening D of the piece of jewelry, through which its wearer can lead through a respective body part, e.g., an arm, a foot or its neck, in order to apply or remove the piece of jewelry. For opening, i.e., enlarging the passage opening D to an widened passage opening D', the two ends 1a and 1b of the base body 1, which are preferably designed flexible, are moved away from each other, so that the widened passage opening D' is formed, which allows that the wearer of the described piece of jewelry to apply it or to take it off by moving the body part of the carrier, i.e., an arm of the wearer, through said widened passage

opening D'. In the following description it is assumed that the piece of jewelry is designed as a piece of jewelry designated to be worn on an arm of the wearer. However, it is apparent to a person skilled in the art from the following description that the piece of jewelry described is not limited to this application. Rather, the measures explained below are also applicable to a foot hoop or a foot band or a neck band, just to name a few examples, in which, for the application of the piece of jewelry a body part of the wearer is to be moved through the ends **1a**, **1b** of the base body **1** into the interior of the piece of jewelry, and for taking off the piece of jewelry is moved in a reverse direction from the inside to the outside. Such a piece of jewelry is known and therefore needs not to be described in more detail.

(11) In order to enable a simplified and therefore more comfortable application or removal of the piece of jewelry, the following measures are proposed:

(12) The base body **1** of the piece of jewelry has a channel **3** in which a resilient element **4**, which is designed here as a tension spring, is arranged movably. In the exemplary embodiment described here, the channel **3** extends over the entire length of the base body **1**, i.e., from the first end **1a** to the second end **1b**. The resilient element **4** is fixedly connected with its first end **4a** to a stop **5** arranged in a stationery manner in the piece of jewelry or bears against this stationery stop **5**.

(13) The base body **1** is preferably designed as a sheath or a hose. It is apparent to the person skilled in the art that the afore-mentioned embodiments for the base body **1** only have an exemplary character. Rather, it is, e.g., possible to provide the base body **1** as a stocking braid. Essential is only that the base body **1** of the piece of jewelry is designed in such a way that the two ends **1a**, **1b** can be moved away from each other for forming the afore described passage openings D and D' respectively and, for closing the piece of jewelry, can be moved towards one another.

(14) The piece of jewelry has a connecting element **6** which extends between the two ends **1a**, **1b** of the base body **1**, which is with its first end **6a** connected to the first end **1a** of the base body **1** directly or indirectly. The connecting element **6** is preferably non-stretchable. However, it is possible that the connecting element **6** is designed stretchable. Preferably, it is provided that the connecting element **6** is designed as a cable or a strand.

(15) In the exemplary embodiment described here the first end **6a** of the connecting element **6** is connected indirectly to the base body **1**. It is connected to a decorative element **2a** surrounding the first end **1a** of the base body **1**. The decorative element **2a** serves to cover the end **1a** of the base body **1**. Said decorative element **2a** is not essential for the subsequently described moving together of the ends **1a**, **1b**.

(16) But it has got to be noted that this is not mandatory; it is also possible to connect the first end **6a** of the connecting element **6** to the base body **1** directly or indirectly. Essential is only that the connecting element **6** is connected with its first end **6a** directly or indirectly, (e.g., via the first decorative element **2a**) to the or at the first end **1a** of the base body **1**.

(17) A second element **6b** of the connecting element **6** is connected to the second end **4b** of the resilient element **4**. In the exemplary embodiment described, a second decorative element **2b** is provided which surrounds the second end **1b** of the base body **1** and comprises a passage **2b'** through which the connecting element **6** can be led through. It is preferred that the passage **2b'** is configured in such a way that a stop **8** for the second end **4b** of the resilient element **4** is provided, so that in the case of the opening movement of the piece of jewelry described below the second end **4b** is not moved out of the base body **1**.

(18) A comparison of FIGS. **1** and **2** now shows the adjustment of the length of the connecting element **6** and the resilient element **4**: FIG. **2** shows the piece of jewelry in its opened position. In the latter, the second end **4b** of the resilient element **4** abuts at the stop **8**. In the case of a non-stretchable connecting element **6**, which is preferably used, the ends **1a**, **1b** of the base body **2** now cannot be moved further away from each other, since the non-stretchable connecting element **6** prevents this. The length of the connecting element **6** is thus preferably selected in such a way that the maximum distance between the two ends **1a**, **1b** of the base body **1** is defined in this way. In the

closed state, as it is shown in FIG. 1, the two ends **1a**, **1b** are adjacent to one another, that is, to say in this state they have their smallest structurally predetermined distance from one another. Since it is preferred that in this state the resilient element **4** is in its relaxed state, it follows therefrom that the length of the resilient element **4** is adjusted to the length of the connecting element **6** as well as the design of the clasp **2** so that in the closed state of the piece of jewelry the resilient element **4** is in its relaxed state or slightly preloaded.

(19) In the exemplary embodiment described it is also provided that the resilient element **4** essentially extends over the entire length of the base body **1**, i.e., from the stop **5** at the first end **1a** of the base body **1** to the position described above. But this is not mandatory, for example it is possible that the stop **5** is not provided at the first end **1a**, but distant therefrom in the direction of the channel **3**, e.g., in the middle of the base body **1**. This has got the advantage that a correspondingly shorter resilient element **4** can be used.

(20) FIG. 1 now shows the piece of jewelry in its closed state. The two ends **1a**, **1b** of the base body **1** are adjacent to one another, the piece of jewelry surrounds the respective body part of the wearer more or less tightly. In order to open the piece of jewelry and bring it in its position shown in FIG. 2, the piece of jewelry is opened by its wearer by moving away from each other the two ends **1a**, **1b**. Since—as described before—the first end **1a** of the piece of jewelry and the second end **4b** of the resilient element **4** are connected via the connecting element **6**, which is preferably non-stretchable, the moving apart of the ends **1a** and **1b** of the base body **1** causes the resilient element **4**—as it is shown by a comparison of FIGS. 1 and 2—to expand. As a result, a restoring force is built up.

(21) FIG. 2 now shows the piece of jewelry in its opened position, the two ends **1a** and **1b** of the base body **1** are spaced apart so far from each other that through the widened passage opening **D'** formed in that way the corresponding body part of the wearer can be led through. The piece of jewelry therefore can be applied or removed in said position. When the wearer releases one or both ends **1a**, **1b** of the base body **1** of the piece of jewelry, the restoring force created by the resilient element **4** causes that tension spring to contract with the effect that the second end **1b** of the base body **1** is moved towards the first end **1a** by the connecting element **6**, so that the ends **1a** and **1b** of the base body **1** move towards one another. At the end of this closing movement the two ends **1a**, **1b** of the base body **1** are adjacent again, so that the piece of jewelry has been closed “automatically”. By means of the described measures, in an advantageous way a simplified opening and closing of the piece of jewelry is achieved.

(22) If the piece of jewelry is closed as described above, the second decorative element **2b** dips into the sleeve-shaped first decorative element **2a**. Such a measure has got the advantage that in this way an optically high-quality design of the ends **1a**, **1b** of the base body **1** of the piece of jewelry is achieved, since now no longer—as it would be technically sufficient—the two ends **1a**, **1b** lie “naked” next to one another.

(23) FIGS. 3 and 4 now shows a second exemplary embodiment, which corresponds in its basic structure to the one of the first exemplary embodiment, so that corresponding components are provided with the same reference numerals and are not explained with regard to their structural design and their modes of operation once more. The main difference between the two embodiments is the attachment of the connecting element **6** to the first end **1a** of the base body **1**. While in the first exemplary embodiment it is provided that the first end **6a** of the connecting element **6** is firmly attached, i.e., non-detachable, to the first end **1a** of the base body **1** directly or indirectly, it is provided in the second embodiment that the first end **6a** of the connecting element **6** can be detached from the base body **1**. For that purpose, an exchangeable decorative element **12** is provided, which is arranged adjacent to the first end **1a** of the base body **1**. In the example shown here the exchangeable decorative element **12** is provided as a spherical body. The exchangeable decorative element **12** comprises a first closing element **7a** which interacts with the first decorative element **2a** and allows a releasable connection between the first decorative element **2a** and the

exchangeable decorative element **12**. In a corresponding manner, on the opposite side a second closing element **7b** is provided, which cooperates with the second decorative element **2b**, which is arranged at the second end **1b** of the base body **1**.

(24) In FIGS. **5** and **6** a third exemplary embodiment is shown, whose basic structure in turn corresponds to the one of the first two exemplary embodiments, so that corresponding components are provided with the same reference numerals and are no longer described with regard to their structural design and their mode of operation. The main difference between the second exemplary embodiment and this embodiment is that in the third exemplary embodiment, instead of the resilient element **4** acting as a tension spring, a resilient element **14** acting as a compression spring is provided. The resilient element **14** once more extends in channel **3** of the base body **1** from its first end **1a** to its second end **1b**. In the region of the first end **1a** a stop **15** corresponding to the stop **5** for a first end **14a** of the resilient element **14** is provided. In the third exemplary embodiment the stop **15** is not—as the stop **5** of the first two exemplary embodiments—arranged stationery in the base body **1**, but—as a comparison of FIGS. **5** and **6** shows—arranged movably in the base body **1** and, in particular, in channel **3**. The stop **15** is connected with a second end **16b** of a connecting element **16** corresponding to the connecting element **6**, whereby a first end **16a** is connected to a first end **1a** of the base body **1** directly or—as in the present embodiment—indirectly via the exchange decorative element **12**, so that by pulling on the connecting element **16**—as described below—the stop **15** can be displaced in the channel **3** of the base body **1**. Such a measure has the design advantage that in the case of a compression spring the respective end therefore needs not to be—as in the case of the first exemplary embodiment—necessarily fixed to the stop **15** firmly. A further difference between the second and third embodiment following from the afore-mentioned measures is that the connecting **16** does not—like in the first and second embodiment—extend from the first end **1a** of the base body **1** to the second end **4b** of the resilient element **4**, but it is provided that the connecting element **16** of the third exemplary embodiment extends to the stop **15**, wherein it is preferred that the connecting element **16** and the resilient element **14** are guided coaxially, that is to say that the connecting element **16** here preferably runs in the interior of the resilient element **14**.

(25) FIG. **5** now shows the closed state and FIG. **6** shows the opened state of the piece of jewelry. In the closed state the resilient element **14** is unloaded or has a slight preloading. In order to now open the piece of jewelry, the wearer moves the two ends **1a** and **1b** of the base body **1** of the piece of jewelry apart from each other. Since the second end **16b** of the connecting element **16** is connected to the stop **15**, the moving apart of the ends **1a** and **1b** of the base body **1** has got the effect that the connecting element **16** is moved out of the second end **16b** of the base body **1**. This causes the stop **15** connected to the second end **16b** of the connecting element **16** to move in an axial direction and thus acts on the first end **14a** of the resilient element **14** and, in the event of a further displacement, compresses the resilient element **14**. As a result, a restoring force which drives the ends **14a** and **14b** of the resilient element **14** away from each other is generated.

(26) After the piece of jewelry has been moved into its position shown in FIG. **6** and the wearer has moved its arm out of the ring-shaped or bracelet-shaped piece of jewelry and has released one or both ends of the piece of jewelry, the resilient element **14** designed as a compression spring expands, as a result of which the two ends **1a**, **1b** are moved towards one another again. The piece of jewelry is thus closed again and the two ends **1a**, **1b** of the base body **1** are arranged adjacently.

(27) In the third exemplary embodiment shown in FIGS. **5** and **6** once more an exchange decorative element **12** is used. However, it is apparent to a person skilled in the art from the description above that this is not mandatory here either.

(28) In the three exemplary embodiments described above, it is provided that in each case the second end **1b** of the base body **1** moves towards the first end **1a** during the closing process. The first end **6a** and **16a** respectively of the connecting element **6** and **16** respectively is—as described—connected to the first end **1a** directly or indirectly, while the second end **6b** or **16b** respectively is

in engagement with the resilient element **4** and **14** respectively. In the exemplary embodiments described before, the first end **1a** of the base body **1** of the piece of jewelry participates in the process of moving together the ends **1a**, **1b** by means of the restoring force created by the resilient element **4** and **14** respectively only passively, while the second end **1b** constitutes the active part of this closing movement. However, it is possible to design the piece of jewelry in such a way that both ends **1a** and **1b** are active, that is, to say that not only—like in the first exemplary embodiment—the second end **1b** approaches the first end **1a**, but that both ends **1a** and **1b** move towards each other when closing the piece of jewelry.

(29) A piece of jewelry designed in such a way is now shown in FIGS. **7** and **8** showing a fourth exemplary embodiment. Corresponding components are provided with the same reference numerals and are no longer described in terms of their construction and mode of operation. The design features of the fourth exemplary embodiment can be characterized in that this embodiment the design described for the second end **1b** in the third exemplary embodiment is also realized in a corresponding manner at the first end **1a**, that is to say—to put it into a nutshell—the design features as described before for the second end **1b** are “mirrored” onto the first end **1a**. The lower part of the piece of jewelry shown in FIGS. **7** and **8** therefore corresponds to the one of the third embodiment, it is therefore not described here once more. FIGS. **7** and **8** show resilient elements **24a** and **24b** which now do not extend over the entire length of channel **3**, that is to say substantially from the first end **1a** to the second end **1b**, but that the resilient element **14** of the third exemplary embodiment is divided into two parts, namely the afore-mentioned resilient elements **24a** and **24b**, so that two resilient elements **24a** and **24b** are thus arranged in the channel **3** of the base body **1**. In a corresponding manner, the connecting element **16** of the third exemplary embodiment is split into two parts, namely connecting elements **26a** and **26b**. In channel **3** thus two resilient elements **24a** and **24b** and connecting elements **26a** and **26b** are provided. The first connecting element **26a** and the first resilient element **24a** correspond in their function and design to the one of the connecting element **16** and the resilient element **14** of the third exemplary embodiment. The first connecting element **26a** extends from its first end **26a'**, which is directly or via the decorative element **2b** connected to the second end **1b** of the base body **1**, up to a stop **25a** corresponding to the stop **15** and is attached to it. The second connecting element **26b** extends from its first end **26b'**, which is directly or indirectly connected to the first end **1a** of the base body **1**, to a stop **25b** and its end **26b''** is connected to the stop **25b**. If the two ends **1a**, **1b** are now moved away from each other during the opening process of the piece of jewelry, this causes—like in the third exemplary embodiment—the connecting element **26a**, **26b** to be moved out of the base body **1**, so that the stops **25a** and **25b** act upon the ends **24a'** and **24b'** of the resilient elements **24a** and **24b**, causing them to be compressed and each generating a restoring force. If the ends **1a** and **1b** are now released, the resilient elements **24a** and **24b** expand and thus move the ends **1a** and **1b** of the piece of jewelry towards each other.

(30) In the exemplary embodiment described before it has been assumed again that an exchangeable decorative element **12** is provided between the ends **1a** and **1b**, like in the third embodiment. This is not mandatory, it is also possible to provide the design described before—two resilient elements **24a**, **24b**, two connecting elements **26a**, **26b**—in a piece of jewelry according to the first embodiment, that is to say in a piece of jewelry not having such an exchangeable decorative element **12**. Such a piece of jewelry is shown in FIG. **9** showing a fourth embodiment. In the closed state the first end **1a** is provided in a first receiving opening **2a'** of the decorative element **2a** and the second end **1b** is provided in a second receiving opening **2a''** of the decorative element **2a**.

(31) In summary, it has got to be noted that a piece of jewelry is formed by the described measures which is distinguished by an “automatic closing” of the piece of jewelry. In an advantageous manner, no clasp or a similar closure mechanism is required, since both ends **1a**, **1b** are moved via the force of the resilient element **4**, **14** and **24a**, **24b** respectively in their closed position. Such a

measure has got the advantage that the removal and in particular the application of such a piece of jewelry is simplified.

Claims

1. A piece of jewelry, comprising: a base body having a first end and a second end arranged oppositely to the first end in a closed state of the piece of jewelry, the base body defining a passage opening in said closed state; wherein the two ends of the base body can be moved away from one another to enlarge said passage opening to form a widened passage opening; the base body having a channel in which at least one resilient element is moveably arranged, wherein the channel of the base body extends continuously from the first end to the second end of the base body; and the piece of jewelry having at least one connecting element, a first end of which is non-movably connected directly or indirectly to the first end of the base body; wherein the at least one connecting element extends across a space being present between the first end and the second end of the base body in an opened state and wherein a second end of the at least one connecting element engages with one end of the resilient element; wherein, when the first and the second ends of the base body are moved apart from each other to form the said widened passage opening, from the resulting loading of the resilient element a restoring force causing the two ends of the base body to move towards each other is generated.
2. The piece of jewelry according to claim 1, wherein the resilient element is designed as a tension spring, that a first end of the at least one resilient element has a stop arranged stationarily in the piece of jewelry, and that a second end is moveably guided in the channel of the base body and is connected to the moveably guided second end of the at least one resilient element.
3. The piece of jewelry according to claim 1, wherein the at least one resilient element is designed as a compression spring, and that a first end of the at least one resilient element is acting upon a stop being arranged moveably in the base body, that the second end of the at least one connecting element is connected with said stop, and that the first end of the at least one connecting element is connected directly or indirectly with the or on the first end of the base body.
4. The piece of jewelry according to claim 1, wherein in the channel of the base body two resilient elements and two connecting elements are provided, and that the two resilient elements are each designed as a compression spring, that a first end of each of the two resilient elements is acted upon by a stop being arranged moveably in the base body, and that a second end of the corresponding connecting element is connected with an associated stop, and that the first end of the respective connecting element is connected directly or indirectly to or at the first end of the base body.
5. The piece of jewelry according to claim 1, wherein the first end of the at least one connecting element is connected directly to the first end of the base body.
6. The piece of jewelry according to claim 1, wherein the second end of the at least one connecting element is connected to the second end of the base body.
7. The piece of jewelry according to claim 1, wherein the first end of the at least one connecting element is detachably connected directly or indirectly to the first end of the base body.
8. The piece of jewelry according to claim 1, wherein the second end of the at least one connecting element is connected detachably to the second end of the base body.
9. The piece of jewelry according to claim 1, wherein the at least one connecting element is designed non-stretchable.
10. The piece of jewelry according to claim 1, wherein the at least one connecting element is arranged coaxially with the resilient element in the channel of the piece of jewelry.
11. The piece of jewelry according to claim 1, wherein the piece of jewelry comprises a decorative element arranged at the first end of the base body and/or a second decorative element arranged at the second end of the base body.
12. The piece of jewelry according to claim 11, wherein the first decorative element works together

with the second decorative element.

13. The piece of jewelry according to claim 1, wherein the piece of jewelry has an interchangeable decorative element.

14. The piece of jewelry according to claim 13, wherein the interchangeable decorative element comprises at least one closing element which interacts with a decorative element arranged on the base body.

15. A piece of jewelry, comprising: a base body having a first end and a second end arranged oppositely to the first end in a closed state of the piece of jewelry, the base body defining a passage opening in said closed state, wherein the base body extends in a first arcuate direction starting from the first end and extending arcuately to the second end; wherein the two ends of the base body can be moved away from one another to enlarge said passage opening to form a widened passage opening; the base body having a channel in which at least one resilient element is arranged, wherein the channel of the base body extends continuously from the first end to the second end of the base body; and the piece of jewelry having at least one connecting element, a first end of which is non-movably connected directly or indirectly to the first end of the base body, and wherein the at least one connecting element extends from the first end of the at least one connecting element in a second arcuate direction that is opposite of the first arcuate direction of the base body; wherein the at least one connecting element extends across a space being present between the first end and the second end of the base body in an opened state and wherein a second end of the at least one connecting element engages with one end of the resilient element; and wherein, when the first and the second ends of the base body are moved apart from each other to form the said widened passage opening, from the resulting loading of the resilient element a restoring force causing the two ends of the base body to move towards each other is generated.
