

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396862
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Deransart; Pierric et al.

Glenoid baseplate and implant assemblies

Abstract

A glenoid baseplate is provided that has a transverse body and an elongate body. The transverse body has a first side configured to engage scapula bone of a patient, a second side configured to face away from the first side, and a plurality of anchor apertures. The anchor apertures are formed between the first side and the second side. The transverse body also can have an arcuate or circular periphery that has an anterior portion configured to be oriented toward an anterior side of a scapula and a posterior portion that is configured to be oriented toward a posterior side of the scapula. The elongate body is disposed along a longitudinal axis between an end coupled with the first side of the transverse body. The longitudinal axis of the elongate body is off-set from the center of the circular periphery.

Inventors:	Deransart; Pierric (Saint Martin d'uriage, FR), Boileau; Pascal (Bloomington, MN), Walch; Gilles (Bloomington, MN), Penninger; Charles L. (Bloomington, MN)
Applicant:	HOWMEDICA OSTEONICS CORP. (Mahwah, NJ)
Family ID:	1000008778878
Assignee:	HOWMEDICA OSTEONICS CORP. (Mahwah, NJ)
Appl. No.:	17/432228
Filed (or PCT Filed):	May 01, 2020
PCT No.:	PCT/US2020/031134
PCT Pub. No.:	WO2020/231657
PCT Pub. Date:	November 19, 2020

Prior Publication Data

Document Identifier	Publication Date
----------------------------	-------------------------

Related U.S. Application Data

us-provisional-application US 62847077 20190513

Publication Classification

Int. Cl.: **A61F2/40** (20060101); **A61F2/30** (20060101)

U.S. Cl.:

CPC **A61F2/4081** (20130101); **A61F2/30749** (20130101); A61F2002/30433 (20130101); A61F2002/30797 (20130101); A61F2002/30813 (20130101)

Field of Classification Search

CPC: A61F (2/4081); A61F (2/30749); A61F (2002/30433); A61F (2002/30797); A61F (2002/30813); A61F (2002/30774); A61F (2002/3079); A61F (2002/30795); A61F (2/40); A61F (2002/4022); A61F (2002/4085); A61F (2002/4629)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4550450	12/1984	Kinnett	N/A	N/A
4725280	12/1987	Laure	N/A	N/A
4986833	12/1990	Worland	N/A	N/A
4990161	12/1990	Kampner	N/A	N/A
5032132	12/1990	Matsen, III et al.	N/A	N/A
5033036	12/1990	Ohmori et al.	N/A	N/A
5080673	12/1991	Burkhead et al.	N/A	N/A
5108446	12/1991	Wagner et al.	N/A	N/A
5458637	12/1994	Hayes	N/A	N/A
5489309	12/1995	Lackey et al.	N/A	N/A
5489311	12/1995	Cipolletti	N/A	N/A
5531973	12/1995	Sarv	N/A	N/A
5662657	12/1996	Carn	N/A	N/A
5702447	12/1996	Walch et al.	N/A	N/A
5800551	12/1997	Williamson et al.	N/A	N/A
5954722	12/1998	Bono	N/A	N/A
6102951	12/1999	Sutter et al.	N/A	N/A
6102954	12/1999	Albrektsson et al.	N/A	N/A
6139550	12/1999	Michelson	N/A	N/A
6171342	12/2000	O'Neil et al.	N/A	N/A
6228119	12/2000	Ondrla et al.	N/A	N/A
6228120	12/2000	Leonard et al.	N/A	N/A
6406495	12/2001	Schoch	N/A	N/A

6508841	12/2002	Martin et al.	N/A	N/A
6514287	12/2002	Ondrla et al.	N/A	N/A
6673115	12/2003	Resch et al.	N/A	N/A
6679916	12/2003	Frankle et al.	N/A	N/A
6699289	12/2003	Iannotti et al.	N/A	N/A
6761740	12/2003	Tornier	N/A	N/A
6783549	12/2003	Stone et al.	N/A	N/A
6790234	12/2003	Frankle	N/A	N/A
6860903	12/2004	Mears et al.	N/A	N/A
6911047	12/2004	Rockwood, Jr. et al.	N/A	N/A
6942699	12/2004	Stone et al.	N/A	N/A
6953478	12/2004	Bouttens et al.	N/A	N/A
6969406	12/2004	Tornier	N/A	N/A
7160328	12/2006	Rockwood, Jr. et al.	N/A	N/A
7169184	12/2006	Pria	N/A	N/A
7175663	12/2006	Stone	N/A	N/A
7175665	12/2006	German et al.	N/A	N/A
7204854	12/2006	Guederian et al.	N/A	N/A
7316715	12/2007	Plaskon	N/A	N/A
7431736	12/2007	Maroney et al.	N/A	N/A
7462197	12/2007	Tornier	N/A	N/A
7462199	12/2007	Justin et al.	N/A	N/A
7527631	12/2008	Maroney et al.	N/A	N/A
7604665	12/2008	Iannotti et al.	N/A	N/A
7608109	12/2008	Dalla Pria	N/A	N/A
7611539	12/2008	Bouttens et al.	N/A	N/A
7621961	12/2008	Stone	N/A	N/A
7637928	12/2008	Fernandez	N/A	N/A
7648530	12/2009	Habermeyer et al.	N/A	N/A
7666522	12/2009	Justin et al.	N/A	N/A
7753959	12/2009	Berelsman et al.	N/A	N/A
7766969	12/2009	Justin et al.	N/A	N/A
7854768	12/2009	Wiley et al.	N/A	N/A
7883653	12/2010	Smith et al.	N/A	N/A
7892287	12/2010	Deffenbaugh	N/A	N/A
7922769	12/2010	Deffenbaugh et al.	N/A	N/A
7927335	12/2010	Deffenbaugh et al.	N/A	N/A
7993408	12/2010	Meridew et al.	N/A	N/A
8007523	12/2010	Wagner et al.	N/A	N/A
8048161	12/2010	Guederian et al.	N/A	N/A
8062376	12/2010	Shultz et al.	N/A	N/A
8070820	12/2010	Winslow et al.	N/A	N/A
8092545	12/2011	Coon et al.	N/A	N/A
8206453	12/2011	Cooney, III et al.	N/A	N/A
8231683	12/2011	Lappin et al.	N/A	N/A
8241365	12/2011	Williams, Jr. et al.	N/A	N/A
8287600	12/2011	Angibaud	N/A	N/A
8308807	12/2011	Seebeck et al.	N/A	N/A

8357201	12/2012	Mayer et al.	N/A	N/A
8361157	12/2012	Bouttens et al.	N/A	N/A
8425614	12/2012	Winslow et al.	N/A	N/A
8444680	12/2012	Dooney, Jr. et al.	N/A	N/A
8449617	12/2012	McDaniel et al.	N/A	N/A
8454702	12/2012	Smits et al.	N/A	N/A
8454705	12/2012	Pressacco et al.	N/A	N/A
8465548	12/2012	Long	N/A	N/A
8480750	12/2012	Long	N/A	N/A
8532806	12/2012	Masson	N/A	N/A
8556901	12/2012	Anthony et al.	N/A	N/A
8556902	12/2012	Ek et al.	N/A	N/A
8556980	12/2012	Deffenbaugh	N/A	N/A
8556981	12/2012	Jones et al.	N/A	N/A
8591591	12/2012	Winslow et al.	N/A	N/A
8597334	12/2012	Mocanu	N/A	N/A
8632597	12/2013	Lappin	N/A	N/A
8690951	12/2013	Baum et al.	N/A	N/A
8690952	12/2013	Dallmann	N/A	N/A
8753402	12/2013	Winslow et al.	N/A	N/A
8790402	12/2013	Monaghan et al.	N/A	N/A
8840676	12/2013	Belew	N/A	N/A
8864834	12/2013	Boileau et al.	N/A	N/A
8870886	12/2013	Burgi	N/A	N/A
8961611	12/2014	Long	N/A	N/A
9114017	12/2014	Lappin	N/A	N/A
9233003	12/2015	Roche et al.	N/A	N/A
9498345	12/2015	Burkhead et al.	N/A	N/A
9512445	12/2015	Iannotti	N/A	N/A
9629725	12/2016	Gargac et al.	N/A	N/A
9763682	12/2016	Bettenga	N/A	N/A
9782208	12/2016	Martin	N/A	N/A
9839436	12/2016	Kehres et al.	N/A	N/A
10034757	12/2017	Kovacs et al.	N/A	N/A
10064734	12/2017	Burkhead et al.	N/A	N/A
10251755	12/2018	Boileau et al.	N/A	N/A
10342669	12/2018	Hopkins	N/A	N/A
10357373	12/2018	Gargac et al.	N/A	N/A
10463499	12/2018	Emerick et al.	N/A	N/A
10583012	12/2019	Longobardi	N/A	N/A
10722374	12/2019	Hodorek et al.	N/A	N/A
10779952	12/2019	Gunther et al.	N/A	N/A
10945862	12/2020	Roby et al.	N/A	N/A
2001/0011192	12/2000	Ondrla et al.	N/A	N/A
2001/0037153	12/2000	Rockwood et al.	N/A	N/A
2002/0095214	12/2001	Hyde, Jr.	N/A	N/A
2003/0055507	12/2002	McDevitt et al.	N/A	N/A
2003/0149485	12/2002	Tornier	N/A	N/A
2004/0030394	12/2003	Horber	N/A	N/A
2004/0059424	12/2003	Guederian et al.	N/A	N/A

2004/0106928	12/2003	Ek	N/A	N/A
2004/0220673	12/2003	Pria	N/A	N/A
2004/0220674	12/2003	Pria	N/A	N/A
2005/0049709	12/2004	Tornier	N/A	N/A
2005/0060039	12/2004	Cyprien	N/A	N/A
2005/0085915	12/2004	Steinberg	N/A	N/A
2005/0143831	12/2004	Justin et al.	N/A	N/A
2005/0149044	12/2004	Justin et al.	N/A	N/A
2005/0192673	12/2004	Saltzman et al.	N/A	N/A
2005/0256583	12/2004	Bouttens et al.	N/A	N/A
2005/0261775	12/2004	Baum et al.	N/A	N/A
2005/0278030	12/2004	Tornier	N/A	N/A
2006/0069443	12/2005	Deffenbaugh et al.	N/A	N/A
2006/0069444	12/2005	Deffenbaugh	N/A	N/A
2006/0074353	12/2005	Deffenbaugh et al.	N/A	N/A
2006/0074430	12/2005	Deffenbaugh et al.	N/A	N/A
2006/0100714	12/2005	Ensign	N/A	N/A
2006/0111787	12/2005	Bailie et al.	N/A	N/A
2006/0122705	12/2005	Morgan	N/A	N/A
2006/0142865	12/2005	Hyde	N/A	N/A
2006/0200248	12/2005	Beguín et al.	N/A	N/A
2006/0200249	12/2005	Beguín et al.	N/A	N/A
2007/0016304	12/2006	Chudik	N/A	N/A
2007/0055380	12/2006	Berelsman et al.	N/A	N/A
2007/0100458	12/2006	Dalla Pria	N/A	N/A
2007/0142921	12/2006	Lewis et al.	N/A	N/A
2007/0156246	12/2006	Meswania et al.	N/A	N/A
2007/0179624	12/2006	Stone et al.	N/A	N/A
2007/0219638	12/2006	Jones et al.	N/A	N/A
2007/0244563	12/2006	Roche et al.	N/A	N/A
2007/0244564	12/2006	Ferrand et al.	N/A	N/A
2007/0260321	12/2006	Stchur	N/A	N/A
2008/0140130	12/2007	Chan et al.	N/A	N/A
2008/0183297	12/2007	Boileau et al.	N/A	N/A
2008/0255568	12/2007	Tornier et al.	N/A	N/A
2008/0269906	12/2007	Iannotti et al.	N/A	N/A
2008/0294268	12/2007	Baum et al.	N/A	N/A
2008/0306601	12/2007	Dreyfuss	N/A	N/A
2009/0125113	12/2008	Guederian et al.	N/A	N/A
2009/0149961	12/2008	Dallmann	N/A	N/A
2009/0164021	12/2008	Dallmann	N/A	N/A
2009/0204225	12/2008	Meridew et al.	N/A	N/A
2009/0216332	12/2008	Splieth et al.	N/A	N/A
2009/0281630	12/2008	Delince et al.	N/A	N/A
2009/0281632	12/2008	Naidu	N/A	N/A
2009/0292364	12/2008	Linares	N/A	N/A
2010/0016975	12/2009	Iannotti et al.	N/A	N/A
2010/0023068	12/2009	Bouttens et al.	N/A	N/A
2010/0049327	12/2009	Isch et al.	N/A	N/A
2010/0087927	12/2009	Roche et al.	N/A	N/A

2010/0161066	12/2009	Iannotti et al.	N/A	N/A
2010/0217399	12/2009	Groh	N/A	N/A
2010/0234959	12/2009	Roche et al.	N/A	N/A
2010/0249938	12/2009	Gunther et al.	N/A	N/A
2010/0274359	12/2009	Brunnarius et al.	N/A	N/A
2010/0291401	12/2009	Medina et al.	N/A	N/A
2010/0331990	12/2009	Mroczkowski	N/A	N/A
2011/0029089	12/2010	Giuliani et al.	N/A	N/A
2011/0035013	12/2010	Winslow et al.	N/A	N/A
2011/0106266	12/2010	Schwyzer et al.	N/A	N/A
2011/0118846	12/2010	Katrana et al.	N/A	N/A
2011/0144758	12/2010	Deffenbaugh	N/A	N/A
2011/0144760	12/2010	Wong et al.	N/A	N/A
2011/0152869	12/2010	Ek et al.	N/A	N/A
2011/0190899	12/2010	Pierce et al.	N/A	N/A
2011/0224673	12/2010	Smith	N/A	N/A
2011/0282393	12/2010	Garlach et al.	N/A	N/A
2012/0004733	12/2011	Hodorek et al.	N/A	N/A
2012/0029647	12/2011	Winslow et al.	N/A	N/A
2012/0059383	12/2011	Murphy et al.	N/A	N/A
2012/0078258	12/2011	Lo et al.	N/A	N/A
2012/0109320	12/2011	Walch et al.	N/A	N/A
2012/0123419	12/2011	Purdy et al.	N/A	N/A
2012/0130498	12/2011	Long	N/A	N/A
2012/0165954	12/2011	Nimal	N/A	N/A
2012/0191201	12/2011	Smits et al.	N/A	N/A
2012/0209392	12/2011	Angibaud et al.	N/A	N/A
2012/0221112	12/2011	Lappin	N/A	N/A
2012/0232670	12/2011	Bojarski et al.	N/A	N/A
2012/0239051	12/2011	de Wilde et al.	N/A	N/A
2012/0239156	12/2011	De Wilde et al.	N/A	N/A
2012/0253467	12/2011	Frankle	623/19.11	A61F 2/4014
2012/0277880	12/2011	Winslow et al.	N/A	N/A
2013/0018483	12/2012	Li et al.	N/A	N/A
2013/0053968	12/2012	Nardini et al.	N/A	N/A
2013/0066433	12/2012	Veronesi et al.	N/A	N/A
2013/0096631	12/2012	Leung et al.	N/A	N/A
2013/0110116	12/2012	Kehres et al.	N/A	N/A
2013/0110470	12/2012	Vanasse et al.	N/A	N/A
2013/0144393	12/2012	Mutchler et al.	N/A	N/A
2013/0150972	12/2012	Iannotti et al.	N/A	N/A
2013/0150973	12/2012	Splieth et al.	N/A	N/A
2013/0150975	12/2012	Iannotti et al.	N/A	N/A
2013/0226186	12/2012	Burgi	N/A	N/A
2013/0226309	12/2012	Daigo et al.	N/A	N/A
2013/0231754	12/2012	Daigo et al.	N/A	N/A
2013/0253656	12/2012	Long	N/A	N/A
2013/0261751	12/2012	Lappin	N/A	N/A
2013/0261752	12/2012	Lappin et al.	N/A	N/A

2013/0264749	12/2012	Jones et al.	N/A	N/A
2013/0282135	12/2012	Sun et al.	N/A	N/A
2013/0338675	12/2012	Nelson et al.	N/A	N/A
2014/0005789	12/2013	Chavarria et al.	N/A	N/A
2014/0012266	12/2013	Bonin, Jr. et al.	N/A	N/A
2014/0018927	12/2013	de Wilde et al.	N/A	N/A
2014/0025173	12/2013	Cardon et al.	N/A	N/A
2014/0142711	12/2013	Maroney et al.	N/A	N/A
2014/0163564	12/2013	Bollinger	N/A	N/A
2014/0194995	12/2013	Koka	N/A	N/A
2014/0243986	12/2013	Frankle	N/A	N/A
2014/0257499	12/2013	Winslow et al.	N/A	N/A
2014/0277180	12/2013	Paolino et al.	N/A	N/A
2014/0277517	12/2013	Winslow	N/A	N/A
2014/0277518	12/2013	Iannotti	N/A	N/A
2014/0277520	12/2013	Chavarria et al.	N/A	N/A
2014/0316416	12/2013	Liu et al.	N/A	N/A
2014/0371863	12/2013	Vanasse et al.	N/A	N/A
2015/0073424	12/2014	Couture et al.	N/A	N/A
2015/0094819	12/2014	Iannotti et al.	N/A	N/A
2015/0142122	12/2014	Bickley et al.	N/A	N/A
2015/0150688	12/2014	Vanasse et al.	N/A	N/A
2015/0265292	12/2014	Olson	N/A	N/A
2015/0272741	12/2014	Taylor et al.	N/A	N/A
2016/0045323	12/2015	Kovacs et al.	N/A	N/A
2016/0151164	12/2015	Taylor et al.	N/A	N/A
2016/0166392	12/2015	Vanasse et al.	N/A	N/A
2016/0199074	12/2015	Winslow et al.	N/A	N/A
2016/0206436	12/2015	Chavarria et al.	N/A	N/A
2016/0228262	12/2015	Bailey	N/A	N/A
2016/0256222	12/2015	Walch	N/A	N/A
2016/0270922	12/2015	Pressacco et al.	N/A	N/A
2016/0287266	12/2015	Sikora et al.	N/A	N/A
2016/0287401	12/2015	Muir et al.	N/A	N/A
2016/0310285	12/2015	Kovacs et al.	N/A	N/A
2016/0324649	12/2015	Hodorek et al.	N/A	N/A
2016/0354209	12/2015	Van Kampen et al.	N/A	N/A
2016/0367375	12/2015	Boulris	N/A	N/A
2017/0027709	12/2016	Winslow et al.	N/A	N/A
2017/0042687	12/2016	Boileau et al.	N/A	N/A
2017/0042690	12/2016	Burkhead et al.	N/A	N/A
2017/0049574	12/2016	Hopkins	N/A	N/A
2017/0172764	12/2016	Muir et al.	N/A	N/A
2017/0273795	12/2016	Neichel et al.	N/A	N/A
2017/0273801	12/2016	Hodorek et al.	N/A	N/A
2017/0273806	12/2016	Cardon et al.	N/A	N/A
2017/0367836	12/2016	Cardon et al.	N/A	N/A
2018/0014941	12/2017	Frankle et al.	N/A	N/A
2018/0064537	12/2017	Pressacco et al.	N/A	N/A
2018/0078377	12/2017	Gargac et al.	N/A	N/A

2018/0085226	12/2017	Baumgarten	N/A	N/A
2018/0092747	12/2017	Hopkins	N/A	N/A
2018/0161169	12/2017	Cardon et al.	N/A	N/A
2018/0243102	12/2017	Burkhead, Jr. et al.	N/A	N/A
2018/0303618	12/2017	Kovacs et al.	N/A	N/A
2018/0368982	12/2017	Ball	N/A	N/A
2019/0015116	12/2018	Gargac et al.	N/A	N/A
2019/0015117	12/2018	Neichel et al.	N/A	N/A
2019/0015221	12/2018	Neichel	N/A	A61F 2/4081
2019/0029833	12/2018	Briscoe et al.	N/A	N/A
2019/0076261	12/2018	Mutchler et al.	N/A	N/A
2019/0336293	12/2018	Kehres	N/A	N/A
2020/0030108	12/2019	Orphanos et al.	N/A	N/A
2020/0179126	12/2019	Courtney, Jr. et al.	N/A	N/A
2020/0188121	12/2019	Boux De Casson et al.	N/A	N/A
2020/0188125	12/2019	Hodorek et al.	N/A	N/A
2020/0237519	12/2019	Ball	N/A	A61F 2/4612
2020/0289180	12/2019	Martin et al.	N/A	N/A
2020/0289282	12/2019	Lefebvre et al.	N/A	N/A
2020/0368031	12/2019	Hodorek et al.	N/A	N/A
2020/0405491	12/2019	Cleveland et al.	N/A	N/A
2021/0030552	12/2020	Terrill	N/A	N/A
2021/0030553	12/2020	Terrill	N/A	N/A
2021/0045895	12/2020	Sapio et al.	N/A	N/A
2021/0298910	12/2020	Gargac et al.	N/A	N/A
2021/0307911	12/2020	Metcalfe et al.	N/A	N/A
2021/0338456	12/2020	Wolfe et al.	N/A	N/A
2021/0369465	12/2020	Simoes et al.	N/A	N/A
2022/0151793	12/2021	Deransart et al.	N/A	N/A
2022/0151794	12/2021	Fattori et al.	N/A	N/A
2022/0175543	12/2021	Ball	N/A	N/A
2022/0202580	12/2021	Wilkins et al.	N/A	N/A
2022/0241077	12/2021	Hodorek et al.	N/A	N/A
2022/0280306	12/2021	Metcalfe et al.	N/A	N/A
2022/0296381	12/2021	Ek et al.	N/A	N/A
2022/0313440	12/2021	Metcalfe et al.	N/A	N/A
2022/0395376	12/2021	Poon et al.	N/A	N/A
2023/0000636	12/2022	Dalla Pria et al.	N/A	N/A
2023/0114073	12/2022	Perego	N/A	N/A
2023/0285154	12/2022	Picha et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2012204090	12/2011	AU	N/A
10123517	12/2001	DE	N/A

0581667	12/1993	EP	N/A
0776636	12/1996	EP	N/A
1013246	12/1998	EP	N/A
1064890	12/2000	EP	N/A
1323395	12/2002	EP	N/A
1488764	12/2005	EP	N/A
1762201	12/2006	EP	N/A
1639949	12/2006	EP	N/A
1639967	12/2007	EP	N/A
1515758	12/2008	EP	N/A
2057970	12/2008	EP	N/A
1776935	12/2008	EP	N/A
1639966	12/2008	EP	N/A
2201912	12/2009	EP	N/A
1927328	12/2010	EP	N/A
1902689	12/2010	EP	N/A
2564814	12/2012	EP	N/A
1996125	12/2012	EP	N/A
2335655	12/2012	EP	N/A
1951161	12/2013	EP	N/A
1973498	12/2013	EP	N/A
2481376	12/2013	EP	N/A
2601912	12/2015	EP	N/A
3291768	12/2018	EP	N/A
3412252	12/2019	EP	N/A
3679900	12/2019	EP	N/A
3756625	12/2019	EP	N/A
2567019	12/1985	FR	N/A
2739151	12/1996	FR	N/A
2776506	12/1999	FR	N/A
2790662	12/2000	FR	N/A
2825263	12/2001	FR	N/A
2821545	12/2002	FR	N/A
2955248	12/2011	FR	N/A
2971144	12/2011	FR	N/A
2977791	12/2013	FR	N/A
2297257	12/1995	GB	N/A
2001054561	12/2000	WO	N/A
2011044879	12/2010	WO	N/A
WO 2011/073169	12/2010	WO	N/A
WO 2011/150180	12/2010	WO	N/A
2013064569	12/2012	WO	N/A
2015051476	12/2014	WO	N/A
WO 2015/068035	12/2014	WO	N/A
WO 2015/103090	12/2014	WO	N/A
2015130006	12/2014	WO	N/A
2016025712	12/2015	WO	N/A
WO 2017/007565	12/2016	WO	N/A
2019014278	12/2018	WO	N/A
2019079104	12/2018	WO	N/A

WO 2019/079104	12/2018	WO	N/A
2020033911	12/2019	WO	N/A
2020154611	12/2019	WO	N/A
2020219962	12/2019	WO	N/A
WO 2020/231657	12/2019	WO	N/A
2021030146	12/2020	WO	N/A
2021178418	12/2020	WO	N/A
2021216405	12/2020	WO	N/A
2022147376	12/2021	WO	N/A
2022261508	12/2021	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion issued in connection with International Patent Application No. PCT/US2022/034245, Sep. 23, 2022, 16 pages. cited by applicant

International Search Report and Written Opinion issued in connection with International Patent Application No. PCT/US2023/070118, Mar. 1, 2024, 15 pages. cited by applicant

International Search Report and Written Opinion issued in connection with International Patent Application No. PCT/US2022/080550, Apr. 10, 2023, 16 pages. cited by applicant

International Search Report and Written Opinion issued in connection with International Patent Application No. PCT/US2022/035217, Nov. 1, 2022, 14 pages. cited by applicant

International Search Report and Written Opinion issued in connection with International Patent Application No. PCT/US2023/064983, Sep. 29, 2023, 10 pages. cited by applicant

EP Search Report and Written Opinion issued in European Patent Application No. 12153346.7, dated Mar. 8, 2012, in 6 pages. cited by applicant

French Search Report and Written Opinion issued in Application. No. FR1150994, mailed May 27, 2011, in 7 pages. cited by applicant

Anatomical Shoulder™ Inverse/Reverse System Surgical Technique, Product Brochure, Zimmer, Inc., published 2006, in 32 pages. cited by applicant

Arthrex, “Arthrex Releases Univers Revers™ Shoulder Arthroplasty System in the United States—First Surgery Successfully Performed in Chillicothe, OH”, Jun. 18, 2013. cited by applicant

Biomet, “Comprehensive® Reverse Shoulder System”, 2013. cited by applicant

Boileau et al., “Cemented polyethylene versus uncemented metal-backed glenoid components in total shoulder arthroplasty: A prospective, double-blind, randomized study,” Journal of Shoulder and Elbow Surgery, Jul./Aug. 2002, vol. 11, Issue 4, pp. 351-359. cited by applicant

Boileau et al., “Metal-backed glenoid implant with polyethylene insert is not a viable long-term therapeutic option,” Journal of Shoulder and Elbow Surgery, Feb. 2015, pp. 1-10. cited by applicant

Cementless Fixation Using a Polyethylene Oseo-Integration Peg as Used on the Freeman-Samuelson Knee brochure, produced by Finsbury Instruments Limited London in conjunction with Adrian Tuke Limited, 1982. cited by applicant

Castagna et al., “Mid-term results of a metal-backed glenoid component in total shoulder replacement,” The Journal of Bone and Joint Surgery, Oct. 2010, vol. 92-B, No. 10, pp. 1410-1415. cited by applicant

Clement et al., “An uncemented metal-backed glenoid component in total shoulder arthroplasty for osteoarthritis: factors affecting survival and outcome,” The Japanese Orthopaedic Association, published online Sep. 26, 2012, vol. 18, pp. 22-28. cited by applicant

DJO Surgical, Reverse® shoulder prosthesis Surgical Technique, Feb. 2008. cited by applicant

Eclipse™ Stemless Shoulder Prosthesis, Surgical Technique Guide, Anthrex GmbH, 2014, in 12 pages. cited by applicant

Epoca Shoulder Arthroplasty System, Synthes, Inc., Apr. 2008, in 4 pages. cited by applicant

Epoca Shoulder Arthroplasty System—Stem and Glenoid Technique Guide, Synthes, Inc., Apr.

2008, in 56 pages. cited by applicant

Innovative Design Orthopaedics, “Verso® Shoulder Surgical Technique”, 2013. cited by applicant

Kany et al., “A convertible shoulder system: is it useful in total shoulder arthroplasty revisions?” International Orthopaedics, published online Oct. 16, 2014, vol. 39, pp. 299-304. cited by applicant

Katz et al., “New design of a cementless glenoid component in unconstrained shoulder arthroplasty: a prospective medium-term analysis of 143 cases,” published online Oct. 27, 2012, vol. 23, pp. 27-34. cited by applicant

Montoya et al., “Midterm results of a total shoulder prosthesis fixed with a cementless glenoid component,” Journal of Shoulder and Elbow Surgery, May 2013, vol. 22, Issue 5, pp. 628-635. cited by applicant

SMR Axioma® TT Metal Back Surgical Technique, Product Brochure, Lima Corporate, dated Sep. 2013, in 48 pages. cited by applicant

Taunton et al., “Total Shoulder Arthroplasty with a Metal-Backed, Bone-Ingrowth Glenoid Component,” The Journal of Bone and Joint Surgery, Oct. 2008, vol. 90-A, Issue 10, pp. 2180-2188. cited by applicant

Teissier et al., “The TESS reverse shoulder arthroplasty without a stem in the treatment of cuff-deficient shoulder conditions: clinical and radiographic results,” Journal of Shoulder and Elbow Surgery, Jan. 2015, vol. 24, Issue 1, pp. 45-51. cited by applicant

The Anatomical Shoulder™: A true system approach, Product Brochure, Zimmer UK Ltd, printed 2006, in 6 pages. cited by applicant

Uniers Revers™ Total Shoulder System, Surgical Technique Guide, Anthrex Inc., Version D, revised Jul. 2, 2015, in 28 pages. cited by applicant

International Search Report and Written Opinion for PCT International Application No. PCT/US2020/031134 issued Sep. 30, 2020. cited by applicant

Notice of Allowance issued in connection with U.S. Appl. No. 17/172,789, filed Jul. 20, 2023, 8 pages. cited by applicant

Extended European Search Report issued in connection with European Patent Application No. 22201630.5, Feb. 9, 2023, 8 pages. cited by applicant

Non-Final Office Action issued in connection with U.S. Appl. No. 17/149,308, filed May 23, 2023, 12 pages. cited by applicant

Non-Final Office Action issued in connection with U.S. Appl. No. 16/756,429, filed May 6, 2022, 24 pages. cited by applicant

International Search Report and Written Opinion issued in connection with International Patent Application No. PCT/US2022/011217, May 4, 2022, 15 pages. cited by applicant

International Search Report and Written Opinion issued in connection with International Patent Application No. PCT/US2022/06106, May 11, 2022, 12 pages. cited by applicant

Second Office Action issued in connection with Japanese Patent Application No. 2022-507908, Jun. 20, 2023, 7 pages. cited by applicant

First Office Action issued in connection with Japanese Patent Application No. 2023-532755, Jul. 9, 2024, 4 pages. cited by applicant

Examination Report issued in connection with Australian Patent Application No. 202143348, Jun. 28, 2024, 6 pages. cited by applicant

Non-Final Office Action issued in connection with U.S. Appl. No. 17/597,486, filed Jul. 16, 2024, 8 pages. cited by applicant

First Examination Report issued in connection with Australian Patent Application No. 2022227496, May 16, 2024, 5 pages. cited by applicant

Extended European Search Report issued in connection with European Patent Application No. 21916574.3, Jul. 4, 2024, 8 pages. cited by applicant

Extended European Search Report issued in connection with European Patent Application No. 22753403.9, Jul. 4, 2024, 8 pages. cited by applicant

Extended European Search Report issued in connection with European Patent Application No. 24191670.9, Feb. 20, 2025, 13 pages. cited by applicant
Communication Under Rule 164(2)(b) issued in connection with European Patent Application No. 20758408.7, Feb. 28, 2025, 9 pages. cited by applicant
International Search Report and Written Opinion issued in connection with International Patent Application No. PCT/US2024/050431, Feb. 11, 2025, 7 pages. cited by applicant
Extended European Search Report issued in connection with European Patent Application No. 22760169.7, Oct. 29, 2024, 9 pages. cited by applicant
Partial European Search Report issued in connection with European Patent Application No. 24191670.9, Oct. 18, 2024, 11 pages. cited by applicant
Second Examination Report issued in connection with Australian Patent Application No. 2022227496, Aug. 29, 2024, 7 pages. cited by applicant
Extended European Search Report issued in connection with European Patent Application No. 22846386.5, Mar. 12, 2025, 7 pages. cited by applicant
Extended European Search Report issued in connection with European Patent Application No. 22856384.7, Mar. 18, 2025, 5 pages. cited by applicant
Extended European Search Report issued in connection with European Patent Application No. 24219566.7, Mar. 27, 2025, 8 pages. cited by applicant
International Search Report and Written Opinion issued in connection with International Patent Application No. PCT/US2025/016710, Apr. 8, 2025, 11 pages. cited by applicant

Primary Examiner: Edwards; Jerrah

Assistant Examiner: White; Kia Xiong

Attorney, Agent or Firm: DUANE MORRIS LLP

Background/Summary

INCORPORATION BY REFERENCE TO ANY PRIORITY APPLICATIONS (1) This application is a National Stage Application, filed under 35 U.S.C. 371, of International Patent Application No. PCT/US2020/031134, filed on May 1, 2020, which claims priority to U.S. Provisional Patent Application No. 62/847,077 filed May 13, 2019, the entireties of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

(1) This application is directed to improved glenoid baseplate designs that are capable of being coupled to a scapula at a glenoid surface and that can have an anchor peg disposed medial of the glenoid surface and between anterior and posterior faces of the scapula.

Description of the Related Art

(2) Shoulder joint conditions can sometimes be resolved with shoulder arthroplasty. More and more, efforts are being focused on making total shoulder joint arthroplasty available to patients who would benefit from such treatment. In a total shoulder joint arthroplasty, the glenoid is typically reamed and a glenoid articular component is mounted to scapula following reaming. The articular component provides a smooth surface for movement of a humeral head or humeral articular component.

(3) A glenoid baseplate can be used to support the glenoid articular component on the scapula. The glenoid baseplate can include an anchor peg on the medial side thereof that is configured to be

inserted into scapular bone as part of securing the glenoid baseplate to the scapula.

SUMMARY OF THE INVENTION

(4) While glenoid baseplates are known, one challenge faced in implanting such baseplates is assuring that the anchor peg (or other medial projection) of the baseplate is consistently embedded in, e.g., fully enclosed within, the scapula bone and does not extend through a posterior or anterior wall of the scapula.

(5) In some examples, methods are used to produce a glenoid baseplate that can include an elongate body, e.g., an anchor peg, that can be positioned on a transverse body of the baseplate in a position to extend into a deep part or even a deepest part of the scapula beneath the glenoid surface. The anchor peg position can be matched to the geometry beneath the glenoid (sometimes referred to as vault geometry) to provide a long or even a longest anchor peg that would fit in the portion of the vault selected for the anchor. In some cases the position is chosen such that the anchor peg does not perforate a wall of the scapula.

(6) In one embodiment, a glenoid baseplate is provided that has a transverse body and an elongate body. The transverse body has a first side configured to engage scapula bone of a patient, a second side configured to face away from the first side, and a plurality of anchor apertures. The anchor apertures are formed between the first side and the second side. The transverse body also can have a circular periphery that extends between the first side and the second side. The circular periphery has an anterior portion configured to be oriented toward an anterior side of a scapula and a posterior portion that is configured to be oriented toward a posterior side of the scapula. The circular periphery can have a center. The elongate body is disposed along a longitudinal axis between a first end and a second end. The second end is coupled with the first side of the transverse body. The first end is disposed away from the second end. The longitudinal axis of the elongate body is off-set from the center of the circular periphery toward the anterior portion thereof.

(7) Anchor apertures through the baseplate can be fixed relative to the baseplate such that a surgeon can advance a bone anchor through each anchor aperture without determining an angle or orientation of the anchor member during the time of surgery, eliminating a step of determining the angle or orientation.

(8) Anchor apertures can be configured to enable the surgeon to select the angle of an anchor member relative to the baseplate or through the anchor aperture at the time of the surgery. Segmented threads can allow the angle of the anchor member through the anchor aperture to be selected at the time of surgery. Angling an internal member that is configured to tilt, rotate or swivel can allow for the selection of an orientation of the anchor member relative to the baseplate at the time of surgery.

(9) In another embodiment, a glenoid baseplate is provided that includes a transverse plate and an anchor peg. The transverse plate has a medial side configured to engage scapula bone of a patient, a lateral side configured to face away from the medial side, a plurality of bone screw holes formed between the medial side and the lateral side, and a circular periphery. The circular periphery extends between the medial side and the lateral side. The circular periphery has an anterior portion configured to be oriented toward an anterior side of a scapula, a posterior portion configured to be oriented toward a posterior side of the scapula, and a center. The anchor peg is disposed along a longitudinal axis between a lateral end coupled with the medial side of the transverse plate and a medial end disposed away from the lateral end. The longitudinal axis of the anchor peg is off-set from the center of the circular periphery toward the anterior portion thereof.

(10) In another embodiment, a method is performed or instructed in which a glenoid anchor is provided. The glenoid anchor has a transverse member and a projection. The transverse member has a medial side, a lateral side, an anterior periphery, and a posterior periphery. The projection extends from the medial side. The projection is located closer to the anterior periphery than to the posterior periphery. In the method, a blind hole is formed in a lateral portion of the scapula. The blind hole is formed along a trajectory that is off set from a center of an inferior portion of a

glenoid. The blind hole has an opening at the glenoid and an enclosed end opposite the opening. The enclosed end is spaced apart from an anterior surface of the scapula. The enclosed end is spaced apart from a posterior surface of the scapula. The projection of the glenoid anchor is advanced into the blind hole such that the projection is enclosed within the scapula along the blind hole between the opening and the enclosed end.

(11) In another embodiment, a method is performed in which image data responsive to a scan of a scapula of a patient is received. An anchor trajectory extending medially from a lateral surface of the scapula is identified from the image data. The anchor trajectory is at a selected position relative to, e.g., spaced apart from, an anterior surface of the scapula. The anchor trajectory can be at a selected position relative to, e.g., spaced apart from, a posterior surface of the scapula. The spacing of at least one of the anchor trajectory from the anterior surface or the anchor trajectory from the posterior surface is based on the imaging information. A glenoid anchor that has a transverse member and a projection is formed. The glenoid anchor has a medial side, a periphery bounding the medial side, a lateral side, an anterior portion, and a posterior portion. The projection extends from the medial side. The projection is disposed within the periphery at a location aligned with the identified anchor trajectory when the periphery is aligned with the curvature of the inferior portion of the glenoid rim.

(12) In some cases, the periphery bounding the medial side corresponds to a curvature of portion of a glenoid rim of the patient. For instance, the periphery can correspond to an inferior portion of the glenoid rim of the patient. The periphery can correspond to a curvature of another portion of the glenoid if the inferior portion of the glenoid rim is subject to deformity. The periphery can be independent of the shape or curvature of the rim of the patient in some cases.

(13) In some examples an approach is used in which some perforation of a wall of the scapula beneath the glenoid surface is desired, e.g., to provide for bi-cortical fixation of an anchor peg or other elongate member. This approach can be combined with an approach to select a location for the anchor peg or other elongate anchor member that extends into a relatively deep portion of the area under the glenoid (e.g., the vault).

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Various embodiments are depicted in the accompanying drawings for illustrative purposes, and should in no way be interpreted as limiting the scope of the embodiments. Furthermore, various features of different disclosed embodiments can be combined to form additional embodiments, which are part of this disclosure.

(2) FIG. 1 shows a model of a human humerus and a scapula with a glenoid, the glenoid having an articular assembly coupled thereto, the articular assembly including a glenoid baseplate with a medial end that projects through a posterior wall of the scapula, the humerus having a reverse implant assembly coupled thereto;

(3) FIG. 1A is a schematic view of a glenoid and an imager that can be used to gather imaging information pertaining to the glenoid;

(4) FIG. 1B is a flow chart of a method that can be performed with imaging information;

(5) FIG. 1C is a schematic diagram of a portion of a scapula including a glenoid;

(6) FIG. 1D is a flow chart of a method for providing for bi-cortical fixation while achieving sufficient anchor peg length;

(7) FIG. 1E is a schematic diagram of a portion of a scapula including a glenoid;

(8) FIG. 2 shows two views of a scapula with an articular assembly baseplate coupled thereto, a medial end of the baseplate projecting through posterior and anterior walls of scapulae;

(9) FIG. 3 is a side view of one embodiment of a glenoid baseplate having an anteriorly offset

anchor peg;

(10) FIG. 3A is a lateral side view of the glenoid baseplate of FIG. 3;

(11) FIG. 3B is a cross-section of the glenoid baseplate of FIG. 3;

(12) FIG. 4 is side view of another embodiment of a glenoid baseplate having anteriorly offset anchor peg;

(13) FIG. 4A is a lateral side view of the glenoid baseplate of FIG. 4;

(14) FIG. 5 is a side view of another embodiment of a glenoid baseplate having anteriorly offset anchor peg and a lateral mounting projection with a relatively small diameter taper;

(15) FIG. 5A is a lateral side view of the glenoid baseplate of FIG. 5;

(16) FIG. 5B is a cross-section of the glenoid baseplate of FIG. 5;

(17) FIG. 5C is side view of another embodiment of a glenoid baseplate having a centered anchor peg;

(18) FIG. 6 is a side view of another embodiment of a glenoid baseplate having an anchor peg that is offset anteriorly to a position aligned with an aperture circumference;

(19) FIG. 6A is a lateral side view of the glenoid baseplate of FIG. 6; and

(20) FIGS. 7-7C illustrate various steps of a method of applying a glenoid baseplate to a scapula.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

(21) This application is directed to improving the success in providing sound connection between a glenoid assembly and a human scapula. These improvements are intended to allow for greater success in shoulder arthroplasty surgery. FIGS. 1 and 2 illustrate concerns that can arise in some shoulder procedure. FIG. 1 shows a schematic view of a humerus 50 and a scapula 55 of a shoulder having reverse shoulder implants disposed therein. The humerus 50 has a humeral resection 52. A humeral implant assembly 53 including a humeral anchor (shown beneath the humeral resection 52) and a reverse articular body 54. The reverse articular body 54 can be disposed above the humeral resection 52 or at least partially below the humeral resection 52 in some cases. The scapula 55 has a lateral surface 56 that includes a glenoid 58 (see FIG. 1A). The glenoid 58 is the portion of the scapula 55 on which the head of the humerus 50 normally articulates. Following total shoulder arthroplasty, this function is provided by an articular body 66 that is coupled to the scapula 55. For example, a glenoid assembly 60 can be provided that includes a glenoid baseplate 62 to support the articular body 66. The glenoid baseplate 62 can be coupled with the scapula 55. The glenoid baseplate 62 can have an anchor peg 64 configured to be advanced into the scapula 55. The glenoid baseplate 62 can have an end disposed on bone beneath the glenoid 58 if the glenoid 58 is reamed. In some embodiments described below the glenoid baseplate 62 can be placed on the glenoid 58 without or with minimal reaming.

(22) In a sub-optimal case, the glenoid baseplate 62 is not properly placed on the scapula 55. FIGS. 1 and 2 show that the anchor peg 64 of the glenoid baseplate 62 can be placed into the scapula 55 in a sub-optimal manner in which a medial end of the anchor peg 64 pierces the posterior surface 78 of the scapula 55. The anchor peg 64 can be exposed outside the scapula 55 in that case. FIG. 2 shows that the medial end of the anchor peg 64 can pierce the anterior surface 76 or the posterior surface 78 of the scapula 55. These outcomes are sub-optimal for several reasons. The security of the connection between the anchor peg 64 and the bone of the scapula 55 is a function of the length over which there is direct contact between these structures. The direct contact provides opportunities for bony ingrowth, providing security. No such ingrowth will occur along a length that is completely exposed. Further, an exposed end could cause irritation to soft tissue around the scapula 55. Further, if the anchor peg 64 were to perforate the bone in an undesirable location the perforation could weaken the scapula and increase the risk of fracture.

(23) FIG. 1A shows a schematic of a lateral side of a scapula 55. The glenoid 58 includes an articular surface separated from the rest of the glenoid 58 by a glenoid rim 68. A healthy shoulder joint will generally have within the glenoid rim 68 an elongate articular surface that has a generally circular inferior portion 70. More particularly the inferior portion 70 can be bounded by a circular

segment of the glenoid rim **68**. The circular portion of the glenoid rim **68** can be disposed about a center **72**. More generally, the center **72** can be a central portion, e.g., a geometric center, of the inferior portion **70**. The center **72** can be disposed on or along an infero-superior axis of the glenoid rim **68** that extends from the superior-most portion (located at the top of the graphic in FIG. **1A**) of the glenoid rim **68** to the inferior-most portion (located at the bottom in FIG. **1A**) of the glenoid rim **68**. The center **72** may be located at a central portion, e.g., a mid-point, of a chord extending across the glenoid rim **68** at an infero-superior position disposed inferior of a geometric center of the entire glenoid **58** or glenoid rim **68**. For example, the center **72** can be located about one-half to two-thirds of the distance from the inferior-most point of the glenoid rim **68** to the geometric center of the entire glenoid **58** or glenoid rim **68**.

(24) As will be discussed in greater detail below, an imager **80** can be used to scan the scapula **55** to gather imaging information. That information can be processed in an image processing system **82**. The image processing system **82** can include a memory that can store imaging information corresponding to scanned data from the imager **80**. The image processing system **82** can also include one or more hardware processors that can execute instructions. The image processing system **82** can process the imaging information to identify all the foregoing structures of the scapula **55**. The imaging information can also be processed to locate an anchor trajectory **84** in a direction into the scapula **55** for placement of an anchor peg. The anchor trajectory **84** can be a direction from a blind hole **220** (discussed below in connection with FIG. **7A**) in the lateral surface **56** of the scapula **55**. The blind hole **220** can extend from an opening **224** (shown schematically in FIG. **1A** as the opening **86**) along the anchor trajectory **84**. The anchor trajectory **84** can be offset from the center **72** of an inferior portion **74** of a glenoid **58**. As shown in FIG. **1A** the offset can be in the direction of the anterior surface **76**. The opening **86** can be located between the center **72** and the anterior surface **76**. The opening **86** can be located 10% of the distance from the center **72** to the anterior aspect of the glenoid rim **68** adjacent to the anterior surface **76** of the scapula **55**. The opening **86** can be located 20% of the distance from the center **72** to the anterior aspect of the glenoid rim **68** adjacent to the anterior surface **76** of the scapula **55**. The opening **86** can be located 30% of the distance from the center **72** to the anterior aspect of the glenoid rim **68** adjacent to the anterior surface **76** of the scapula **55**. The opening **86** can be located 40% of the distance from the center **72** to the anterior aspect of the glenoid rim **68** adjacent to the anterior surface **76** of the scapula **55**. The opening **86** can be located 50% of the distance from the center **72** to the anterior aspect of the glenoid rim **68** adjacent to the anterior surface **76** of the scapula **55**. The opening **86** can be located 60% of the distance from the center **72** to the anterior aspect of the glenoid rim **68** adjacent to the anterior surface **76** of the scapula **55**. In some cases, the opening **86** is located in a direction other than toward the anterior surface **76**, e.g., closer to the posterior surface **78** of the scapula **55** by any of these or other percentages. The opening **86** could be in other directions as well, e.g., inferior, superior, or some direction between any of anterior, posterior, inferior, or superior depending on the needs of the patient.

(25) The image processing system **82** can be configured to process imaging information in any suitable manner. FIG. **1B** shows one method that can be performed at least in part by the image processing system **82**. In a step **88** a process can receive the imaging information. For example, the imager **80** can be connected by a network to a computer having a processor configured to receive the imaging information. The network can include an Internet connection, a wireless or wired connection within the same facility where the imager **80** is located. In some applications, a data file including the imaging information can be physically transported to an image processing computer. In some applications, the imager **80** is directly connected to a computer with a processor configured to process the imaging information.

(26) Thereafter in a step **90** a lateral portion or surface **56** of a scapula **55** can be characterized. The characterization of the lateral portion can include segmentation to create a virtual model of all or a portion of the scapula **55**. The step **90** can include forming a virtual model of all or a portion of the

humerus **50**. The step **90** can include forming a virtual model of all or a portion of the glenoid **58**. A virtual model formed in step **90** can include a model of the glenoid rim **68**. The virtual model formed in step **90** can include a model of an inferior portion **70** of the glenoid rim **68**. In step **90**, the center **72** of the inferior portion **70** can be identified in the virtual mode. The glenoid **58** can be characterized to locate the center **72**, e.g., by obtaining a radius of curvature of the inferior portion **70**. The center **72** can be identified as the center for a radius of curvature of the inferior portion **70**. (27) The step **90** can include characterizing a lateral surface **56** of the scapula **55**. The scapula **55** can be disposed in the immediate vicinity of the glenoid **58**, e.g., lateral facing bone disposed around the glenoid **58**. In some cases, the scapula **55** is further characterized medially of the lateral surface **56**, e.g., along an anterior surface **76** and/or along a posterior surface **78** of the scapula **55**. The step **90** can include determining the thickness of the scapula **55** between the anterior surface **76** and the posterior surface **78** at one or more locations of the glenoid **58**. For example, thicknesses can be determined along the line **91** as shown in FIGS. **1A** and **1C**. FIG. **1C** provides a simplified illustration of the line **91** as a straight line. In most examples of the glenoid **58** the line **91** follows the curvature of the glenoid **58**, e.g., having a concavity facing laterally. The line **91** can extend from an anterior side of the glenoid rim **68** to a posterior side of the glenoid rim **68**. A thickness **t1** can be determined as a distance extending medially from the center **72**. The distance can be measured perpendicular to a tangent line of the glenoid **58** at the center **72**.

(28) The step **90** can also include determining a thickness **t2** at a location spaced apart from the center **72** if the thickness **t1** is not sufficient to fully contain the anchor peg **64** of a glenoid baseplate **62**. The location of the opening **86** can be determined as a location where the sum of a thickness **t2** and a thickness **t3** exceed a threshold. In one method, it is preferred to provide the thickness **t2** from the end of a blind hole **220** that can be formed to retain the anchor peg **64** to the exterior wall of the posterior surface **78**. For example, the thickness **t3** can be at least large enough to leave the cortical wall at the posterior surface **78** intact. In one technique, the thickness **t3** is measured from a portion of the blind hole **220** that is closest to the nearest wall of the scapula **55**. For example if the posterior wall of the scapula **55** is sloped anteriorly in the vicinity of the end of the blind hole **220**, the measurement for **t3** would be from the posterior aspect of the blind hole **220** (rather than from the center of the blind hole) to the posterior wall.

(29) FIG. **1C** shows that in some cases, the scapula **55** can have a shape that allows the opening **86** to be placed over a range of positions. A distance from the location of the measurements thickness **t2** and thickness **t3** to the location of a measurement of a thickness **t4** from the anterior surface **76** of the scapula **55** provides a range of possible locations for the opening **86**. Upon identification of the range of positions for the opening **86**, selection of the location of the opening **86** can be based on other factors such as bone quality below the glenoid **58** along the range of positions show in FIG. **1C**. In some methods, the presence and location of any deformity can be considered. For example, the presence and location of a deformity can impact the ability of peripheral screws to be secured to the bone. So, the location of the opening **86** can be adjusted or selected to provide the best overall anchorage including that provided by peripheral screws.

(30) The image processing system **82** can perform the step **92** in which the location of the opening **86** and the anchor trajectory **84** are determined. The image processing system **82** can determine the dimensions **t2** and **t3** as a part of determining the location of the opening **86** and the anchor trajectory **84**. For example, a hardware processor in the image processing system **82** can execute code implementing a method that determines the thicknesses **t2** and **t3** for a given location offset from the center **72**. At a location disposed an incremental distance anteriorly from the center **72**, the image processing system **82** can determine the dimension **t3**. The thickness **t3** can provide an anatomic reference distance, such as the thickness of the cortical wall adjacent to the anterior or posterior wall of the scapula beneath the glenoid (see FIG. **1C**). The thickness **t2** can be determined by the image processing system **82** from glenoid surface and the thickness **t3** (see FIG. **1C**). If the thicknesses **t2** and **t3** are sufficient for a given patient, the anchor trajectory **84** as well as the

location for the opening **86** can be established. If either thickness t_2 or t_3 is not sufficient, a further increment from the center **72** can be evaluated by the image processing system **82**. The condition at the bone corresponding to this further increment, e.g., the thicknesses t_2 and t_3 , can be evaluated by the image processing system **82** to determine if the thicknesses t_2 and t_3 are sufficient. In some embodiments the image processing system **82** performs additional steps of the method of FIG. **1B**, e.g., to generate a configuration for a glenoid baseplate **62**. The configuration of the glenoid baseplate **62** can include an amount of offset between a center of a proximal or distal (or lateral or medial) portion of the glenoid baseplate **62** and the location of the center of the anchor peg **64**. The direction along which the anchor peg **64** extends can be generally perpendicular to a lateral or medial surface of the glenoid baseplate **62** in some embodiments. In some methods, the image processing system **82** concludes the step **92** upon determining the location of the opening **86** and the corresponding position of the anchor peg **64** as well as the anchor trajectory **84** within the scapula **55** and the corresponding configuration (e.g., orientation and length) of the anchor peg **64**. The opening **86** may advantageously be determined to be located anterior of the center **72**, posterior of the center **72**, inferior of the center **72**, superior of the center **72**, or any combination of anterior, posterior, inferior and superior to the center **72** as needed based on the analysis in step **90**.

(31) FIGS. **1** and **1C** shows that the direction of the opening **86** relative to the center **72** is toward the anterior surface **76**. The opening **86** could be located between the center **72** and the posterior surface **78**, as shown in FIG. **2**. A range of positions for the opening **86** between the center **72** and the posterior surface **78** also can be provided if the posterior surface **78** extends more generally medially-laterally and the anterior surface **76** is more curved toward the posterior surface (as in the lower image of FIG. **2**).

(32) In a step **94**, a specification or configuration for a glenoid baseplate **62** can be output. The output can be in the form of drawings. The output can be computer code to be used by a rapid manufacturing facility. The output in step **94** can be sent directly or indirectly to multiple recipients, including a review recipient, a manufacturing recipient, a physician customer and/or a patient customer.

(33) In step **96** the configuration or specifications output in step **94** can be received by a manufacturing facility. The configuration or specification can be received by other parties in the step **96**. The step **96** can involve a 3D printer of any sort to receive instructions output in the step **94**. The instructions can be received and can be implemented by the 3D printer forming the glenoid baseplate **62** in a step **98**. The step **98** generate the glenoid baseplate **62** by forming the glenoid baseplate **62** and thereafter putting the glenoid baseplate **62** through appropriate finishing processes. The step **98** can include transferring the glenoid baseplate **62** to the surgeon immediately upon concluding the method of FIG. **1B** or subsequently.

(34) FIGS. **1D-1E** illustrate further variations of methods and apparatuses herein. The method illustrated in FIG. **1D** is similar to that of FIG. **1B** except that there is an additional step **93** in which the length of an elongate body, e.g., an anchor peg, which may be described as an anchor length, is confirmed. An anchor length can correspond to a thickness t_4 between a glenoid surface. In one technique the determination of the thickness t_4 can include using the image processing system **82** to identify a cortical boundary **79**, e.g., a location where generally cancellous bone transitions to generally cortical bone. The thickness t_4 can be required to be at least the distance from the glenoid surface to the cortical boundary **79**. The thickness t_4 can be required to be greater than this distance, such that the result is that a glenoid baseplate formed with an elongate body defined by the method of FIG. **1D** reaches and in some cases extends through the scapula wall to provide bi-cortical fixation. The rest of the method of FIG. **1D** can be the same as the method of FIG. **1B**.

(35) A patent application filed under U.S. Provisional Application No. 62/847,100 on May 13, 2019 listing inventors Pierric Deransart and Vincent Simoes and bearing to title Patient-Matched Orthopedic Implant is hereby incorporate by reference herein in its entirety for further disclosure of

various methods related to configuring and making various embodiments of glenoid baseplates and other orthopedic implants in a patient specific or patient-matched manner and for further disclosure of such glenoid baseplates and orthopedic implants as well as for all other purposes.

(36) FIGS. 3-3B shows an example glenoid baseplate **100** according to one embodiment. The glenoid baseplate **100** can be used to secure a glenoid articular member to a glenoid as discussed below. The glenoid baseplate **100** is an example of an implementation of the glenoid baseplate **62** discussed above.

(37) The glenoid baseplate **100** includes a transverse body **104** and an elongate body **108**. The elongate body **108** can be configured as an anchor peg, e.g., similar to the anchor peg **64**. The glenoid baseplate **100** includes a first side **120**. The first side **120** can be a medial side configured to engage scapula bone of a patient. The glenoid baseplate **100** includes a second side **124**. The second side **124** can be a lateral side configured to face away from the medial side **120**. The second side **124** can face away from the scapula **55** when the first side **120** is secured against the scapula **55**.

(38) FIG. 3A shows that the glenoid baseplate **100** can include plurality of anchor apertures **132**, which can be a plurality of bone screw holes, formed between the medial side **120** and the lateral side **124**. The anchor apertures **132** can be evenly distributed about the transverse body in some embodiments. In some embodiments, there is an uneven distribution of the anchor apertures **132** about the second side **124**. The anchor apertures **132** can be fixed holes or fixed passages through the baseplate **100**. The anchor apertures can be formed as holes or passages defined in part by or through internal members that are disposed within recesses in the baseplate **100**. In some embodiments, the recesses and/or apertures **132** in the baseplate **100** can include a non-threaded and/or threaded surface. In various examples one or more of two or more apertures **132** can be threaded and another one or more of the two or more apertures **132** can be non-threaded. In an example, two threaded apertures **132** can be disposed through an augmented portion of the first or medial side **120**, e.g., an angled surface thereof, and one or more, e.g., two, non-threaded holes can be disposed adjacent to the threaded holes. The augmented portion can be a pre-defined augment appropriate for the patient or can be a patient-specific augmented portion that is designed specifically for the patient based on imaging of the scapula and/or glenoid region of the patient. In some embodiments, the internal member(s) can include a semi-spherical outer surface and can be disposed in a recess that is semi-spherical, in order to permit movement, e.g., rotation, tilting and/or swiveling, of the internal member with respect to the baseplate **100**. The internal member(s) allow an orientation of bone anchors relative to the baseplate **100** to be selected at the time of a surgery. Further details of internal members that can tilt, rotate or swivel are described in U.S. Pat. No. 9,629,725B2, which is hereby incorporated herein by reference.

(39) The glenoid baseplate **100** can have a circular periphery **136** that can extend between the medial side **120** and the lateral side **124**. The circular periphery **136** can be tapered, e.g., larger toward the first side **120** than toward the second side **124**. The circular periphery **136** can correspond to a curvature of an inferior portion **74** of a glenoid rim **68** of the scapula **55**. The elongate body **108** can be disposed within the circular periphery **136** at a location to be aligned with the anchor trajectory **84** when the periphery is aligned with the curvature of the inferior portion **74** of the glenoid rim **68**. The elongate body **108** can be aligned with the opening **86** by rotationally orienting the glenoid baseplate **100**, e.g., by orienting an indicia of directionality as directed. A notation such as “SUP” can be marked on the transverse body **104** to be aligned with the superior direction. Other indicia of directionality can be provided in other embodiments.

(40) FIG. 3A shows that the circular periphery **136** of the glenoid baseplate **100** can have a center **148** with a feature for securing an articular body to the glenoid baseplate **100** as discussed further below. The circular periphery **136** can have an anterior periphery **137** comprising a portion of the circular periphery **136**. The circular periphery **136** can have a posterior periphery **138**. The posterior periphery **138** comprises a posterior portion of the circular periphery **136**. The elongate

body **108** can be configured as a projection that extends from the medial side **120**. The projection **108** can be located closer to the anterior periphery **137** than to the posterior periphery **138**.

(41) The glenoid baseplate **100** can include an anterior portion **140** configured to be oriented toward an anterior side of a scapula **55**. The glenoid baseplate **100** can include a posterior portion **144** configured to be oriented toward a posterior side of the scapula **55**. The anterior portion **140** and the posterior portion **144** can be disposed around, e.g., can surround the center **148**.

(42) FIG. 3 shows how the transverse body **104** and the elongate body **108** can be secured or coupled to each other. The elongate body **108** can extend along a longitudinal axis **160**. The elongate body **108** can have a first end **164** and a second end **168**. The second end **168** can be coupled with the first side **120** (e.g., with the medial side) of the transverse body **104**. The first end **164** can be disposed away from the second end **168** (e.g., away from the lateral end). The first end **164** can be a medial end **164** of the glenoid baseplate **100**. The longitudinal axis **160** of the anchor peg **108** is off-set from the center **148** of the circular periphery **136** toward the anterior portion **140**. The center **148** is illustrated by a dashed line in FIG. 3. FIGS. 3A and 3B show that a recess is formed at the center **148**. The recess allows a connection feature (e.g., a screw) to be used to secure an articular body (such as the articular body **66**) to the glenoid baseplate **100**. The configuration of the glenoid baseplate **100** allows the connection between the articular body **66** and the glenoid baseplate **100** to be along the center **148** while allowing the location of the elongate body **108** to be spaced apart from the center **148**, e.g., according to the method of FIG. 1B.

(43) FIGS. 3A and 3B show that the glenoid baseplate **100** can have a threaded hole **180** to facilitate connection of an articular body (e.g., the articular body **66**) to the glenoid baseplate **100**. The threaded hole **180** preferably is configured as a blind hole with an open end **184**. The blind hole configuration can include an enclosed end **188**. The enclosed end **188** greatly increases the strength of the glenoid baseplate **100** compared to where the threaded hole **180** would open up on the medial side of the structure. The threaded hole **180** can be formed within a fastener body **192**. The fastener body **192** can be configured as a transverse extension of the elongate body **108** as seen most prominently in FIG. 3. The fastener body **192** can have a width that is less than the diameter of the elongate body **108** at the first end **164** thereof. The fastener body **192** can extend by a distance that is less than the medial-lateral thickness of the transverse body **104**. The fastener body **192** can include a first end **194** and a second end **196**. The second end **196** can be coupled with the first side **120** of the transverse body **104**. The first end **194** can be disposed away from the transverse body **104**. The fastener body **192** enables the fastener to extend by at least a small distance beyond the transverse body **104**. This configuration allows the transverse body **104** to be relatively or completely flat on the second side **124**.

(44) The circular periphery **136** of the transverse body **104** comprises a tapered profile **201** configured to mate with a tapered recess of the articular body **66**. The second side **124** of the glenoid baseplate **100** can have an aperture circumference **204** wherein the anchor apertures **132** are evenly distributed about the lateral face of the transverse body **104**. FIG. 4A shows an embodiment where all of the anchor apertures **132** are evenly spaced about a lateral face of the transverse body **104**. FIG. 3A shows that an anterior portion of an aperture circumference **204** opposite the elongate body being formed without an aperture, e.g., providing a continuous area **205**. The continuous area **205** can include a solid surface at a regular spacing from adjacent anchor apertures **132**. The presence of a continuous area **205** can arise due to the shifting of the position of the elongate body **108** into the area of the anchor apertures **132**. Because the elongate body **108** is solid there is not an opportunity to direct a bone screw through that area. Therefore, the continuous area **205** can be provided. The continuous area **205** can be a solid or unperforated area.

(45) In some embodiments, a medial interface **208** is provided in the first end **164** of the elongate body **108**. The medial interface **208** can include a blind hole that is centered on the distal face of the elongate body **108**. The medial interface **208** could be used to secure patient bone matter or graft matter. A blind hole allows a pin or peg to be inserted into the elongate body **108** during

handling or processing of the glenoid baseplate **100**. During such holding the glenoid baseplate **100** can be further processed to provide appropriate smoothed surfaces. The handling interface **208** is optional and can be replaced with a solid surface at the second end **168** of the elongate body **108**. (46) Handling of the glenoid baseplate **100** can be facilitated by providing a tooling interface **150** on the transverse body **104**, e.g. on the second side **124** thereof. As discussed above, the second side **124** can be a lateral side of the glenoid baseplate **100**. The second side **124** can be accessible by a tool that can extend through the skin to the surgeon in use when the tool has been used to place the glenoid baseplate **100** through the skin toward the glenoid. The tooling interface **150** can include two or more opposed slots, openings or blind holes in the second side **124** of the transverse body **104**. The slots, openings or blind holes can be angled toward each other such that the ends thereof are closer to each other than are the ends of the slots, openings or blind holes at the surface of the second side **124**. As shown, the tooling interface **150** can be disposed just outside of the aperture circumference **204** between two circumferentially adjacent anchor apertures **132**.

(47) FIGS. **4** and **4A** show a glenoid baseplate **100A** that is similar to the glenoid baseplate **100** except as described differently below. The description of the glenoid baseplate **100** supplements the description of the glenoid baseplate **100A**. Any features of the glenoid baseplate **100A** that are compatible with the glenoid baseplate **100** also supplement to the glenoid baseplate **100**. The glenoid baseplate **100A** includes the transverse body **104** and the elongate body **108** as discussed above. The elongate body **108** extends along the longitudinal axis **160**. The transverse body **104** can have a circular periphery **136** with a center **148**. An offset between the center **148** and the elongate body **108** can be provided. The offset can be in the anterior direction, as shown in FIG. **4**. Depending on the nature of the scapula to which the glenoid baseplate **100A** is to be applied the offset between the elongate body **108** and the center **148** can be in another direction, e.g., in the posterior direction. The offset between the elongate body **108** and the center **148** can be in other directions as well, e.g., inferior, superior, or some direction between any of anterior, posterior, inferior, or superior depending on the needs of the patient.

(48) The glenoid baseplate **100** can have a fastener body **192A** that is disposed alongside the elongate body **108**. The fastener body **192A** can be similar to the fastener body **192**. For instance, the fastener body **192A** can have an enclosed end **188** and an open end **184**. The fastener body **192** can have a threaded hole **180** that extends from the open end **184** to the enclosed end **188**. The fastener body **192A** can be provided to allow at least a portion of a fastener coupled to the glenoid baseplate **100A** to be disposed below a bone surface to which the first side **120** is applied. The fastener coupled to the fastener body **192A** can extend out of the open end **184** and into an articular body to additionally secure the reverse articular body **66** to the glenoid baseplate **100A**. Accordingly, a portion of a fastener can be disposed in the reverse articular body **66**, a portion in the thickness of the transverse body **104** and a portion in the fastener body **192A**.

(49) The fastener body **192A** extends away from a side surface of the elongate body **108** by a lesser extent than does the fastener body **192** in the glenoid baseplate **100**. Placement of the glenoid baseplate **100A** requires less preparation of the bone of the glenoid **58** to accommodate the lesser volume of the fastener body **192A** compared to the fastener body **192**. Also, the location of the elongate body **108** closer to the fastener body **192A** allows the periphery of the elongate body **108** to be disposed inward of the anchor apertures **132** in the transverse body **104**. FIG. **4A** shows that the configuration allows the aperture circumference **204** to include anchor apertures **132** that are evenly distributed entirely around the transverse body **104**. For example, the transverse body **104** can have anchor apertures **132** located between the position of the elongate body **108**, e.g., of the longitudinal axis **160**, and the anterior portion **140** of the circular periphery **136**. The glenoid baseplate **100A** advantageously enables the elongate body **108** to be lodged completely in bone medial of the first side **120** of the transverse body **104** and also allows anchors to be disposed through the anchor apertures **132** at an even distribution providing even securement to the scapula.

(50) FIGS. **5-5B** show a glenoid baseplate **100B** that is similar to the glenoid baseplate **100** and the

glenoid baseplate **100A** except as described differently below. The descriptions of the glenoid baseplate **100** and the glenoid baseplate **100A** supplement the description of the glenoid baseplate **100B**. Any description of features of the glenoid baseplate **100B** that are compatible with the glenoid baseplate **100** or the glenoid baseplate **100A** also supplements that of the glenoid baseplate **100** and/or the glenoid baseplate **100A**.

(51) The glenoid baseplate **100B** includes an elongate body **108B** and a transverse body **104B**. The elongate body **108B** is disposed along a longitudinal axis **160**. The transverse body **104B** is symmetrical about a center **148**, which is illustrated as a center axis **148**. The glenoid baseplate **100B** includes a coupling projection **210** disposed a side of the transverse body **104B** opposite the elongate body **108B**. The coupling projection **210** can be symmetrical about the center **148**. The coupling projection **210** can have a tapered outer periphery. The coupling projection **210** can have an outer periphery that reduces in diameter along the length thereof from the transverse body **104B** to a free end of the coupling projection **210**. The coupling projection **210** can include a threaded hole **180B** formed therein to engaged with the articular body **66**. The threaded hole **180B** can be disposed between an open end **184B** and an enclosed end **188B** within the coupling projection **210**. The enclosed end **188B** can be disposed within the thickness of the transverse body **104B**. The enclosed end **188B** can be disposed between the elongate body **108B** and the coupling projection **210**. A tooling interface **212** can be disposed in the threaded hole **180B**. The tooling interface **212** can extend from the open end **184B** toward the enclosed end **188B**.

(52) The tooling interface **212** can be rotationally asymmetric to contribute to visualizing or providing the correct orientation of the glenoid baseplate **100B** relative to the scapula. For example, an arrangement of concavities can be provided about the tooling interface **212**. An enlarged concavity can be provided at a superior portion of the tooling interface **212**. The glenoid baseplate **100B** also can be provided with visual indicia of orientation, e.g., labeled “SUP” for superior and/or “INF” for inferior on the lateral side of the transverse body **104B**. In other embodiments, the transverse body **104B** can be labeled “ANT” for anterior or “POS” for posterior. Other indicia could be used for indicating one or more of these orientations.

(53) The transverse body **104B** can include anchor apertures **132B** that are similar to the anchor apertures **132** and can also include threads for connecting the transverse body **104B** to bone anchor, e.g., screws, that can be advanced therethrough. The threads can be segmented to allow the threads to be secured to bone anchors in a fixed orientation, which orientation can be selected at the time of a surgery.

(54) One advantage of the configuration of the glenoid baseplate **100B** is that the elongate body **108B** can have a cylindrical shape with a circular profile from a first end located at a first, bone-facing or medial side of the transverse body **104B** to a second (medial) end of the elongate body **108B**. The exterior surface of the elongate body **108B** is free of a structure similar to the fastener body **192** or fastener body **192A** because the faster advanced into the threaded hole **180B** does not extend beyond the first, bone-facing or medial side of the transverse body **104B**. This allows the preparation of the scapula bone of a patient to be simpler in that a circular hole can be formed in the recess allowing the glenoid baseplate **100B** to be more easily inserted into the bone. The presence of the fastener body **192** or the fastener body **192A** may require either supplemental preparation of the bone or compaction of the bone during impaction of the glenoid baseplate **100** or the glenoid baseplate **100A** if the baseplate is prepared without a patient specific medial surface configured to be placed on the glenoid. In cases where the medial surface is made patient specific the fastener body **192** or the fastener body **192A** may be located in an expanse of the baseplate that is augmented for the patient on the medial side of the baseplates and may be located laterally of the glenoid surface when applied. Thus, no additional bone preparation would be necessary for the fastener body **192** or the fastener body **192A**.

(55) The coupling projection **210** can provide a connection to the articular body **66** that is similar to the connection provided by the tapered profile **201** of the glenoid baseplate **100** or the glenoid

baseplate **100A**. The coupling projection **210** has a tapered profile that has larger dimensions toward the transverse body **104B** than adjacent to the free end of the coupling projection **210**. The largest dimension of the coupling projection **210** is smaller than the diameter of the side of the transverse body **104B** to which the coupling projection **210** is coupled. Thus, the coupling projection **210** can be smaller than the transverse body **104B**. The coupling projection **210** can have an aspect ratio that is greater than 1:5 (height to diameter of the projection **210**). In various examples, the coupling projection **210** has an aspect ratio that is greater than 1:4, greater than 1:3, greater than 1:2, e.g., about 1:1. In contrast, the transverse body **104**, the periphery of which provides the tapered profile **201** for mating to the articular body **66**, can have an aspect ratio that is smaller than 1:1 (diameter to height of the body **104**). The transverse body **104** can have an aspect ratio smaller than 1:2, smaller than 1:3, smaller than 1:4. In some example, the transverse body **104** has an aspect ratio that is between 1:2 and 1:7, e.g., about 1:5. The insertion and alignment of the articular body **66** with the smaller coupling projection **210** can be easier than the insertion and alignment of the articular body **66** over the generally larger tapered profile **201**. The alignment of the body **66** to the smaller diameter projection **210** is easier in part because of the higher aspect ratio (length over width) of this feature. That is, the projection **210** is narrower and longer and thus has a much higher aspect ratio than the tapered profile **201**, which is shorter and wider. The higher aspect ratio allows the articular body **66** to be placed over the free end of the coupling projection **210** and as it is advanced toward the transverse body **104B**, the projection **210** guides the body **66** into the proper alignment prior to full connection. In the case of the tapered profile **201**, the smaller aspect ratio provides less alignment confirmation by way of the structure of these features before the components are to be fully connected. With the presence of soft tissue and limited visibility the alignment is just more difficult. However, both interfaces provide excellent connection between the articular body **66** and the corresponding glenoid baseplate.

(56) FIG. 5C shows a glenoid baseplate **100C** that is similar to the glenoid baseplate **100B** except as described differently below. The glenoid baseplate **100C** has similarity to some feature of the glenoid baseplate **100** and the glenoid baseplate **100A** as well. The descriptions of the glenoid baseplates **100**, **100A**, **100B** supplement the description of the glenoid baseplate **100C**. Any description of features of the glenoid baseplate **100C** that are compatible with the glenoid baseplates **100**, **100A**, **100B** also supplements that of the glenoid baseplates **100**, **100A**, and/or the glenoid baseplate **100B**.

(57) FIG. 5C shows that the glenoid baseplate **100C** has an elongate body **108C** that is disposed on a medial side of the transverse body **104B**. The transverse body **104B** is disposed on the center **148** as in the glenoid baseplate **100B**. The elongate body **108C** is disposed along a longitudinal axis **160**. The longitudinal axis **160** is aligned with, e.g., intersects or is colinear with the center **148** of the transverse body **104B**. As such, the glenoid baseplate **100C** provide a configuration in which both the coupling projection **210** and the elongate body **108C** are symmetrical about a common axis. The glenoid baseplate **100C** is suitable for patients with more symmetrical anterior surface **76** and posterior surface **78** and/or patients with thicker a scapula. These patients can receive the full length of the elongate body **108C** along a direction perpendicular to a plane of the transverse body **104B** extending away from the first side **120** of the transverse body **104B** when the anchor trajectory **84** is aligned with the center **72** of the glenoid **58**.

(58) The configuration of FIG. 5C can have the coupling projection **210** and the tooling interface **212**. The glenoid baseplate **100** can be formed with a symmetrical configuration similar to the glenoid baseplate **100C**.

(59) FIG. 6 shows a glenoid baseplate **100D** that is similar to the glenoid baseplates **100**, **100B** except as described differently below. The glenoid baseplate **100D** has similarity to some feature of the glenoid baseplates **100A**, **100C** as well. The descriptions of the glenoid baseplates **100**, **100A**, **100B**, **100C** supplement the description of the glenoid baseplate **100D**. Any descriptions of features of the glenoid baseplate **100D** that are compatible with the glenoid baseplates **100**, **100A**, **100B**,

100C also supplements that of the glenoid baseplate **100** and/or the glenoid baseplate **100**, **100A**, **100B**, **100C**.

(60) The glenoid baseplate **100D** has a transverse body **104B** and an elongate body **108D**. The elongate body **108D** is similar to the elongate body **108B**. The elongate body **108D** extends from a first side **120** of the transverse body **104B** to a free end disposed away from the first side **120**. The elongate body **108D** extends along a longitudinal axis **160**. The longitudinal axis **160** can be offset from a center **148** of a coupling projection **210** disposed on a side of the transverse body **104B** opposite to the elongate body **108D**. The offset between the center **148** and the longitudinal axis **160** can be in an anterior direction. Such an offset will accommodate a patient where more bone stock is available toward the anterior surface **76** than toward the posterior surface **78** of the scapula **55**.

(61) The offset between the longitudinal axis **160** and the center **148** of the glenoid baseplate **100D** or the glenoid baseplate **100** can be about 6 mm in one embodiment. The offset between the longitudinal axis **160** and the center **148** of the glenoid baseplate **100D** or the glenoid baseplate **100** can be about 5 mm in one embodiment. The offset between the longitudinal axis **160** and the center **148** of the glenoid baseplate **100D** or the glenoid baseplate **100** can be about 4 mm in one embodiment. The offset between the longitudinal axis **160** and the center **148** of the glenoid baseplate **100B** or the glenoid baseplate **100A** can be about 3 mm in one embodiment. The offset between the longitudinal axis **160** and the center **148** of the glenoid baseplate **100B** or the glenoid baseplate **100A** can be about 2 mm in one embodiment. The offset between the longitudinal axis **160** and the center **148** of the glenoid baseplate **100B** or the glenoid baseplate **100A** can be about 1 mm in one embodiment. The offset between the longitudinal axis **160** and the center **148** of the glenoid baseplate **100B** or the glenoid baseplate **100A** can be about 0.5 mm in one embodiment.

(62) FIG. 6A shows that for some amounts of offset the glenoid baseplate **100D** omits one or more anchor apertures **132**. As in the glenoid baseplate **100**, the aperture circumference **204** provide that anchor apertures **132B** are evenly distributed about the second side **124** of the transverse body **104B**. The anchor apertures **132B** can be spaced apart by even increments. In one or more of the increment positions the transverse body **104B** is made solid with no anchor apertures **132B** formed therein. The anchor apertures **132B** is omitted because the glenoid baseplate **100D** has the elongate body **108D** disposed at least partially within the area of the anchor apertures **132B** that is omitted. Because the elongate body **108D** is positioned at this location a bone anchor, such as a bone screw, cannot be placed though this area.

(63) Shoulder Implant Configured From Surgical Planning

(64) The various glenoid baseplates can be better understood with reference to FIGS. 1A-1C, discussed above. The glenoid baseplate **100** can advantageously be formed following step **88** in which imaging information of a scapula **55** is obtained from the imager **80**. The imager **80** can be a CT scanner, X-ray, MRI or other similar imaging modality or from a tracer that can be obtain bone shape by direct contact with the bone or with tissue over the bone. The scapula **55** can be characterized in the step **90**. This can involve any suitable technique employed by the image processing system **82** for creating a virtual model of the scapula **55**, e.g., by segmenting the imaging information to provide a 3D model that can be stored in memory and/or displayed in a graphical user interface. This information can include identifying a center **72** of an inferior portion **74** of the glenoid rim **68** of the scapula **55**. The center **72** can be identified as a mid-point of a chord of the inferior portion **74** of the glenoid rim **68** of the scapula **55**. The chord can be located a distance equal to the radius from the inferior-most point of the inferior portion **74** of the glenoid rim **68**. The chord can be located at an inferior-superior position along the glenoid rim **68** between an anterior portion thereof adjacent to the anterior surface **76** of the scapula **55** and a posterior portion thereof adjacent to the posterior surface **78** of the scapula **55**. The inferior superior position can be that position where the distance across the glenoid **58** is equal to two times the radius of curvature of the inferior portion **74** of the glenoid rim **68**. The glenoid baseplate **100** can be configured such that the

transverse body **104** has a round periphery with a radius equal to the radius of curvature of the inferior portion **74** of the glenoid rim **68**. The center **148** of the transverse body **104** can be located at the center **72** as determined in the step **90**.

(65) The position of the elongate body **108** can be determined in the step **92**. The step involves finding an appropriate position for preparing the opening **86** in the surface of the glenoid **58** for receiving the elongate body **108**. As noted above, the position may be positioned adjacent to the center **72**. The opening **86** may advantageously be formed anterior of the center **72**, posterior of the center **72**, inferior of the center **72**, superior of the center **72**, or any combination of anterior, posterior, inferior and superior to the center **72** as needed based on the analysis in step **90**. The position of the opening **86** may be selected by finding a location along the line **91** where any combination of the depth, strength, thickness, bone density and bone strength is sufficient to accommodate a minimum length of the elongate body **108**. The position of the opening **86** can be one in which the bone will support formation of a blind hole in the scapula **55** extending from the opening **86** to an enclosed end where the entire length of the elongate body **108** can be accommodated in the blind hole. With reference to FIG. **1C** the elongate body **108** can have a length that equates to the thickness **t2**. The position can be anywhere between the two horizontal lines bounding reference number **86**.

(66) The step **94** can include specifying the diameter of the transverse body **104** and the position of elongate body **108**. The step **94** can also include specifying the length of the elongate body **108**. For patients with larger volume of bone in the scapula **55** the elongate body **108** can be made longer than the minimum length if such additional length is deemed to provide a clinical advantage, e.g., better implants security. The step **94** can also output a baseplate with a threaded hole that extends below the bone surface (as in FIGS. **3-4A**) or that is located laterally of the bone when applied to the patient (as in FIGS. **5-6A**).

(67) The step **98** can include forming the baseplate through a suitable process such as an additive manufacturing process, e.g., three dimensional printing. Examples of three dimensional printing include direct metal laser sintering (DMLS), fused deposition modeling (FDM), fused filament fabrication (FFF), and electron beam melting (EBM). Any one or a combination of these or other additive manufacturing processes can be used in the step **98**. In these processes a three dimensional object is formed by sequentially forming individual layers of the object on top of previously formed individual layers. These processes can closely control the gross dimensions of the object and also can form complex features and shapes such as contours. In certain embodiments, the step **98** can be used to form the first side **120** of any of the glenoid baseplates disclosed herein as complementary surface that can mate with specific anatomy of a specific patient, e.g., with a convex surface that mates with the concave surfaces of the glenoid **58** as show in dash-dot line **99** of FIG. **1**.

(68) As discussed further above, the scapula **55** has a thickness between the anterior surface **76** and the posterior surface **78** the scapula can be small and can rapidly and/or unpredictably decrease beneath the glenoid **58**. Thickness change beneath the glenoid **58** can be due to many factors including the anterior and posterior surfaces of the scapula being irregular or inconsistent from patient to patient. The foregoing method and apparatus provide for consistently sound anchorage of the projection of the elongate bodies of the glenoid baseplates on the medial side of the baseplate within the wall of the scapula. The applicants of this application have found that for many patient this results in an offset medial post where the post is offset to an anterior zone of the baseplate. These configurations can lead to higher likelihood of clinical success.

(69) Surgical Methods For Baseplates Configured Based on Patient Scapula Anatomy

(70) The foregoing disclosure provides for various advantageous surgical methods. FIGS. **7-7C** illustrate some of these methods. FIG. **7** shows that a blind hole **220** can be formed in a lateral surface **56** of the scapula **55**, e.g., within the surface of the glenoid **58**. The blind hole can be formed at location of the opening **86** identified in the method of FIGS. **1A-1C**. The blind hole can

extend from an opening **224** corresponding to the opening **86** to an enclosed end **228** opposite the opening **224**. The enclosed end **228** can be at a depth and at an anterior-posterior position that is spaced apart from the anterior surface **76** and the posterior surface **78** of the scapula **55**. The blind hole can extend along an axis that corresponds to the anchor trajectory **84** determined in the method of FIGS. 1A-1C. FIGS. 7 and 7A show that the blind hole **220** is off set from the center **72** of the inferior portion **70** of a glenoid **58**.

(71) FIG. 7 shows that for some of the baseplate configurations, the blind hole **220** may be enlarged, e.g., providing an expanded opening **226**. The expanded opening **226** can be a portion that extends from the blind hole **220** toward the center **72**. For example, the glenoid baseplate **100A** includes the fastener body **192A** that is aligned with the center **148**. The center **148** is to be aligned with the center **72** when the glenoid baseplate **100A** is applied. Accordingly the surface of the glenoid **58** may be prepared to enlarge the blind hole **220** include the expanded opening **226** to accommodate the fastener body **192A**. The expanded opening **226** is disposed at, over or around the center **72** such that a screw for connecting the articular body **66** to the glenoid baseplate **100A** can be centered on the transverse body **104**. Forming the expanded opening **226** may be accomplished by a surgical drill, by a small reamer, by a tamp, or in the process of placing a trial implant in the glenoid **58**. Or the glenoid baseplate **100A** could be advanced into the blind hole **220** and the expanded opening **226** can be formed by compression of the bone as the glenoid baseplate **100A** is impacted into the bone.

(72) FIG. 7C shows application of the glenoid baseplate **100D** to the glenoid **58**. The elongate body **108D** can be advanced as indicated by an arrow **240** toward the glenoid **58** such that the elongate body **108D** is at the opening **224** to the blind hole **220**. The elongate body **108D** can be advanced into the blind hole **220** until the elongate body **108D** is adjacent to or contacts the enclosed end **228**. The elongate body **108D** can be advanced into the blind hole **220** until the elongate body transverse body **104B** is adjacent to or contacts the glenoid **58**. The elongate body **108D** can be advanced into the blind hole **220** until a patient matched medial side of the glenoid baseplate **100D** as indicated by the dash-dot line **99** in FIG. 1 contacts or nests with the natural or existing concavity of the glenoid **58**. The elongate body **108D** is located adjacent to or contacts the enclosed end **228**.

(73) Prior to advancing the elongate body **108D** into the opening **224** the glenoid baseplate **100D** can be rotationally oriented as indicated by the arrow **241** relative to the glenoid **58**. For example, if there are rotational positioning indicia or features those features can be properly oriented by the surgeon. As noted above, the second side **124** of the transverse body **104B** can be marked with "SUP" to indicate the portion of the transverse body **104B** that should be oriented superiorly. In some embodiments the tooling interface **212** disposed on the coupling projection **210** of the transverse body **104B** can be rotationally asymmetric such that a portion of the instrument that advances or holds the glenoid baseplate **100D** can be easily visually confirmed to be properly oriented instead of or in addition to relying marking such as "SUP" for superior, "INF" for inferior, "ANT" for anterior, "POS" for posterior, etc.

(74) FIG. 7C shows that following rotational positioning (if needed) and advancement of the glenoid baseplate **100D** into the blind hole **220** the glenoid baseplate **100D** can be secured to the scapula **55**. One or more bone anchor **244** can be advanced through the transverse body **104B** and into the bone. The bone anchor **244** can be directed through the transverse body **104B** toward and/or into cortical bone of the scapula **55**. In some techniques, the direction of the bone anchor **244** or the length thereof can be planned or selected prior to or during the surgery to assure a particular outcome. For instance the orientation or length can be planned or selected to assure the end of the bone anchor **244** opposite to the end coupled to the transverse body **104B** is disposed in the cortical bone but not through the anterior surface **76** or the posterior surface **78** of the scapula **55**. The orientation or length can be planned or selected to assure the end of the bone anchor **244** opposite to the end coupled to the transverse body **104B** is disposed in the cortical bone and also

extends through the anterior surface **76** or the posterior surface **78** of the scapula **55**. FIG. 7C shows just one screw placed through the transverse body **104B** into the scapula **55**. Additional screws can be placed out of the section plane shown, e.g., superior to and/or inferior to the coupling projection **210**. As discussed above, the glenoid baseplate **100D** is configured such that two anchor apertures **132B** are provided in superior and inferior positions and one anchor aperture **132B** is provided at a posterior position. An anterior expanse of the transverse body **104B** is provided in which the anchor aperture **132B** is omitted. FIG. 7C shows that the glenoid baseplate **100D** is secured without any bone anchor **244** between the position of the elongate body **108D** and the anterior periphery of the transverse body **104B**.

(75) FIG. 7C shows that following the securing of the glenoid baseplate **100D** to the scapula **55** the articular body **66** can be coupled with the glenoid baseplate **100D**. The articular body **66** can be advanced as indicated by arrow **252** toward the coupling projection **210**. The coupling projection **210** can be received in a corresponding tapered recess formed in the medial side of the articular body **66**. The tapered recess and the coupling projection **210** can be configured to form a Morse taper connection. The Morse taper connection can be sufficient to secure the articular body **66** to the glenoid baseplate **100D**. In some embodiments, additional securement can be provided by a screw advanced through the articular body **66** into the threaded hole **180B** of the coupling projection **210**. The screw can engage threads in the threaded hole **180B** as it is advanced from the open end **184B** toward the enclosed end **188B**. In some embodiments, a screw can provide the sole connection between the articular body **66** and the glenoid baseplate **100D** by being advanced into the threaded hole **180B** of the coupling projection **210**, engaging threads in the threaded hole **180B** as it is advanced from the open end **184B** toward the enclosed end **188B**.

Terminology

(76) As used herein, the relative terms “lateral” and “medial” shall be defined relative to the anatomy. Thus, medial refers to the direction toward the midline and lateral refers to the direction away from the midline.

(77) Although certain embodiments and examples have been described herein, it will be understood by those skilled in the art that many aspects of the delivery systems shown and described in the present disclosure may be differently combined and/or modified to form still further embodiments or acceptable examples. All such modifications and variations are intended to be included herein within the scope of this disclosure. A wide variety of designs and approaches are possible. No feature, structure, or step disclosed herein is essential or indispensable.

(78) For purposes of this disclosure, certain aspects, advantages, and novel features are described herein. It is to be understood that not necessarily all such advantages may be achieved in accordance with any particular embodiment. Thus, for example, those skilled in the art will recognize that the disclosure may be embodied or carried out in a manner that achieves one advantage or a group of advantages as taught herein without necessarily achieving other advantages as may be taught or suggested herein.

(79) Moreover, while illustrative embodiments have been described herein, the scope of any and all embodiments having equivalent elements, modifications, omissions, combinations (e.g., of aspects across various embodiments), adaptations and/or alterations as would be appreciated by those in the art based on the present disclosure. The limitations in the claims are to be interpreted broadly based on the language employed in the claims and not limited to the examples described in the present specification or during the prosecution of the application, which examples are to be construed as non-exclusive. Further, the actions of the disclosed processes and methods may be modified in any manner, including by reordering actions and/or inserting additional actions and/or deleting actions. It is intended, therefore, that the specification and examples be considered as illustrative only, with a true scope and spirit being indicated by the claims and their full scope of equivalents.

(80) Conditional language used herein, such as, among others, “can,” “might,” “may,” “e.g.,” and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is

generally intended to convey that some embodiments include, while other embodiments do not include, certain features, elements, and/or states. Thus, such conditional language is not generally intended to imply that features, elements, blocks, and/or states are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without author input or prompting, whether these features, elements and/or states are included or are to be performed in any particular embodiment.

(81) The ranges disclosed herein also encompass any and all overlap, sub-ranges, and combinations thereof. Language such as “up to,” “at least,” “greater than,” “less than,” “between,” and the like includes the number recited. Numbers preceded by a term such as “about” or “approximately” include the recited numbers and should be interpreted based on the circumstances (e.g., as accurate as reasonably possible under the circumstances, for example $\pm 1\%$, $\pm 5\%$, $\pm 10\%$, $\pm 15\%$, etc.). For example, “about 0.01 inches” includes “0.01 inches.” Phrases preceded by a term such as “substantially” include the recited phrase and should be interpreted based on the circumstances (e.g., as much as reasonably possible under the circumstances). For example, “substantially linear” includes “linear.”

Claims

1. A glenoid baseplate, comprising: a transverse body comprising a first side configured to engage scapula bone of a patient, a second side configured to face away from the first side, a plurality of anchor apertures formed between the first side and the second side, and a circular periphery extending between the first side and the second side, the circular periphery having an anterior portion configured to be oriented toward an anterior side of a scapula, a posterior portion configured to be oriented toward a posterior side of the scapula, and a center; an elongate body disposed along a longitudinal axis between a first end and a second end, the second end being coupled with the first side of the transverse body and the first end being disposed away from the second end; a fastener body having a first end and a second end, wherein the fastener body is configured as a transverse extension of the elongate body, the second end of the fastener body being coupled with the first side of the transverse body and the fastener body extends away from the first side of the transverse body along the elongate body and toward the first end of the elongate body; and a threaded hole provided within the transverse body and extending into the fastener body for facilitating a connection of an articular body to the glenoid baseplate; wherein the longitudinal axis of the elongate body is offset from the center of the circular periphery toward the anterior portion thereof.
2. The glenoid baseplate of claim 1, wherein the threaded hole is disposed at the center of the circular periphery.
3. The glenoid baseplate of claim 1, wherein the threaded hole is a blind hole with an open end on the second side of the transverse body and an enclosed end opposite the open end.
4. The glenoid baseplate of claim 3, wherein the enclosed end of the blind hole is disposed between the first end of the transverse body and the first end of the elongate body.
5. The glenoid baseplate of claim 1, wherein the circular periphery of the transverse body comprises a tapered profile configured to mate with a tapered recess of an articular body.
6. The glenoid baseplate of claim 1, wherein the anchor apertures are evenly distributed about the transverse body.
7. The glenoid baseplate of claim 1, wherein the anchor apertures are evenly distributed about an aperture circumference of the transverse body, an anterior portion of the aperture circumference opposite the elongate body being formed without an aperture.
8. A glenoid baseplate, comprising: a transverse plate having a medial side configured to engage scapula bone of a patient, a lateral side configured to face away from the medial side, a plurality of bone screw holes formed between the medial side and the lateral side, and a circular periphery

extending between the medial side and the lateral side, the circular periphery having an anterior portion configured to be oriented toward an anterior side of a scapula, a posterior portion configured to be oriented toward a posterior side of the scapula, and a center; an anchor peg disposed along a longitudinal axis between a lateral end that is coupled with the medial side of the transverse plate and a medial end that is disposed away from the lateral end; a fastener body having a first end and a second end, wherein the fastener body is configured as a transverse extension of the anchor peg, the second end of the fastener body being coupled with the medial side of the transverse plate and the fastener body extends away from the first side of the transverse plate along the anchor peg and toward the lateral end of the anchor peg; and a threaded hole provided within the transverse plate and extending into the fastener body for facilitating a connection of an articular body to the glenoid baseplate; wherein the longitudinal axis of the anchor peg is offset from the center of the circular periphery toward the anterior portion thereof.

9. The glenoid baseplate of claim 8, wherein the threaded hole is a blind hole with an open end that opens up on the lateral side of the transverse plate.

10. A method, comprising: providing a glenoid anchor having a transverse member having a medial side, a lateral side, an anterior periphery, a posterior periphery, an anchor peg extending from the medial side and disposed along a longitudinal axis between a lateral end and a medial end, the lateral end of the anchor peg being coupled with the medial side of the transverse member and the medial end of the anchor peg being disposed away from the lateral side of the transverse member, the anchor peg being located closer to the anterior periphery than to the posterior periphery, and a fastener body having a first end and a second end, wherein the fastener body is configured as a transverse extension of the anchor peg, the second end of the fastener body being coupled with the medial side of the transverse member and the fastener body extends away from the medial side of the transverse member and toward the medial end of the anchor peg; and a threaded hole provided within the transverse member and extending into the fastener body, wherein the threaded hole is a blind hole with an open end that opens up on the lateral side of the transverse member; forming a blind hole in a lateral portion of the scapula along a trajectory that is off set from a center of an inferior portion of a glenoid, the blind hole having an opening at the glenoid and an enclosed end opposite the opening, the enclosed end being spaced apart from an anterior surface of the scapula, and the enclosed end being spaced apart from a posterior surface of the scapula; and advancing the anchor peg of the glenoid anchor into the blind hole such that the anchor peg is enclosed within the scapula along the blind hole between the opening and the enclosed end.

11. The method of claim 10, further comprising orienting the anchor peg of the glenoid anchor toward an anterior portion of a rim of the glenoid prior to advancing the anchor peg of the glenoid anchor into the blind hole.

12. A method, comprising: receiving image data responsive to a scan of a scapula of a patient; identifying from the image data an anchor trajectory extending medially from a lateral surface of the scapula, the anchor trajectory being at a selected position relative to an anterior surface of the scapula and a posterior surface of the scapula; forming a glenoid anchor having a transverse member having a medial side, a lateral side, an anterior periphery, a posterior periphery, a projection extending from the medial side and disposed along a longitudinal axis between a first end and a second end, the second end being coupled with the medial side of the transverse member and the first end being disposed away from the second end, the projection being located closer to the anterior periphery than to the posterior periphery, and a fastener body having a first end and a second end, wherein the fastener body is configured as a transverse extension of the projection, the second end of the fastener body being coupled with the medial side of the transverse member and the fastener body extends away from the medial side of the transverse member along the projection and toward the first end of the projection; and a threaded hole provided within the transverse member and extending into the fastener body, wherein the threaded hole is a blind hole with an open end that opens up on the lateral side of the transverse member; wherein the projection is

disposed within the periphery at a location aligned with the identified anchor trajectory when the periphery is aligned with the curvature of the inferior portion of the glenoid rim.

13. The method of claim 12, wherein the anchor trajectory is spaced apart from the anterior surface of the scapula.

14. The method of claim 12, wherein the anchor trajectory is spaced apart from the posterior surface of the scapula.

15. The method of claim 14, wherein the anchor trajectory is spaced apart from the anterior surface of the scapula.

16. The method of claim 12, wherein the glenoid anchor is formed such that the projection extending from the medial side is configured to extend through opposing cortical bone of the scapula.
