

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399999
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Cheng; Gong et al.

IoT device risk assessment

Abstract

An Internet of Things (IoT) device profile applicable to an IoT device is determined. Data packets transmitted to and from the IoT device are analyzed. A risk level of the IoT device is determined based at least in part on the data packet analysis. A determination is made that the risk level exceeds a threshold and a remedial action is taken in response.

Inventors: Cheng; Gong (Sunnyvale, CA), Ektare; Mayuresh (Santa Clara, CA), Wang; Mei (Saratoga, CA)

Applicant: Palo Alto Networks, Inc. (Santa Clara, CA)

Family ID: 1000008778845

Assignee: Palo Alto Networks, Inc. (Santa Clara, CA)

Appl. No.: 17/342950

Filed: June 09, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20210303699 A1	Sep. 30, 2021

Related U.S. Application Data

continuation parent-doc US 16538787 20190812 US 11087005 child-doc US 17342950
continuation parent-doc US 15357989 20161121 US 10380348 20190813 child-doc US 16538787

Publication Classification

Int. Cl.: G06F21/57 (20130101); H04L9/40 (20220101)

U.S. Cl.:

CPC **G06F21/577** (20130101); **H04L63/0227** (20130101); **H04L63/1425** (20130101);

Field of Classification Search

CPC: G06F (21/577); H04L (63/0227); H04L (63/1425); H04L (63/1433); H04W (4/70)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6142682	12/1999	Skogby	N/A	N/A
6877146	12/2004	Teig	N/A	N/A
8146133	12/2011	Moon	N/A	N/A
8159966	12/2011	Mabee	N/A	N/A
8331229	12/2011	Hu	N/A	N/A
8671099	12/2013	Kapoor	N/A	N/A
8683598	12/2013	Cashin	N/A	N/A
8850588	12/2013	Kumar	N/A	N/A
8863276	12/2013	Giblin	N/A	N/A
8874550	12/2013	Soubramanien	N/A	N/A
8891528	12/2013	Moriarty	N/A	N/A
8898788	12/2013	Aziz	N/A	N/A
8973088	12/2014	Leung	N/A	N/A
9038178	12/2014	Lin	N/A	N/A
9112895	12/2014	Lin	N/A	N/A
9324119	12/2015	Singh	N/A	N/A
9378361	12/2015	Yen	N/A	N/A
9516053	12/2015	Muddu	N/A	N/A
9548987	12/2016	Poole	N/A	N/A
9584536	12/2016	Nantel	N/A	N/A
9600571	12/2016	Shaashua	N/A	N/A
9609003	12/2016	Chmielewski	N/A	N/A
9614742	12/2016	Zhang	N/A	N/A
9661011	12/2016	Van Horenbeeck	N/A	N/A
9692784	12/2016	Nenov	N/A	N/A
9774604	12/2016	Zou	N/A	N/A
9800603	12/2016	Sidagni	N/A	N/A
9807110	12/2016	Harlacher	N/A	N/A
9824356	12/2016	Kurian	N/A	N/A
9891907	12/2017	Searle	N/A	N/A
9894085	12/2017	Dmitriyev	N/A	N/A
9910874	12/2017	Jamail	N/A	N/A
9961096	12/2017	Pierce	N/A	N/A
9984344	12/2017	Singh	N/A	N/A
9985982	12/2017	Bartos	N/A	N/A
10038700	12/2017	Duchin	N/A	N/A
10043591	12/2017	Laborde	N/A	N/A

10122747	12/2017	Mahaffey	N/A	N/A
10129118	12/2017	Ghare	N/A	N/A
10191794	12/2018	Smith	N/A	N/A
10204312	12/2018	Singh	N/A	N/A
10212176	12/2018	Wang	N/A	N/A
10212178	12/2018	Cheng	N/A	N/A
10229269	12/2018	Patton	N/A	N/A
10237875	12/2018	Romanov	N/A	N/A
10320613	12/2018	Cam-Winget	N/A	N/A
10348739	12/2018	Greenspan	N/A	N/A
10459827	12/2018	Aghdaie	N/A	N/A
10489361	12/2018	Sisk	N/A	N/A
10489714	12/2018	Lee	N/A	N/A
10511620	12/2018	Schwartz	N/A	N/A
10623389	12/2019	Childress	N/A	N/A
10630728	12/2019	Ghosh	N/A	N/A
10764315	12/2019	Carroll	N/A	N/A
10862911	12/2019	Dezent	N/A	N/A
10885393	12/2020	Sirianni	N/A	N/A
10887306	12/2020	Gupta	N/A	N/A
11005839	12/2020	Shahidzadeh	N/A	N/A
11070568	12/2020	Ektare	N/A	N/A
11115799	12/2020	Du	N/A	N/A
11115823	12/2020	Heiland	N/A	N/A
11310247	12/2021	Manadhata	N/A	N/A
11455641	12/2021	Shahidzadeh	N/A	N/A
11477202	12/2021	De Knijf	N/A	N/A
2004/0243835	12/2003	Terzis	N/A	N/A
2005/0044406	12/2004	Stute	N/A	N/A
2005/0281291	12/2004	Stolfo	N/A	N/A
2006/0095970	12/2005	Rajagopal	N/A	N/A
2006/0265397	12/2005	Bryan	N/A	N/A
2007/0094725	12/2006	Borders	N/A	N/A
2008/0059536	12/2007	Brock	N/A	N/A
2009/0180391	12/2008	Petersen	N/A	N/A
2010/0054278	12/2009	Stolfo	N/A	N/A
2010/0284282	12/2009	Golic	N/A	N/A
2011/0022812	12/2010	Van Der Linden	N/A	N/A
2011/0087626	12/2010	Yeleshwarapu	N/A	N/A
2011/0239267	12/2010	Lyne	N/A	N/A
2012/0065749	12/2011	Hunter	N/A	N/A
2012/0102543	12/2011	Kohli	N/A	N/A
2012/0174221	12/2011	Han	N/A	N/A
2012/0240185	12/2011	Kapoor	N/A	N/A
2013/0086261	12/2012	Lim	N/A	N/A
2013/0173621	12/2012	Kapoor	N/A	N/A
2013/0247190	12/2012	Spurlock	N/A	N/A
2013/0305357	12/2012	Ayyagari	N/A	N/A
2013/0305358	12/2012	Gathala	N/A	N/A
2014/0006479	12/2013	Maloo	N/A	N/A

2014/0157405	12/2013	Joll	N/A	N/A
2014/0244834	12/2013	Guedalia	N/A	N/A
2014/0281912	12/2013	Doi	N/A	N/A
2014/0325670	12/2013	Singh	N/A	N/A
2014/0337862	12/2013	Valencia	N/A	N/A
2015/0039513	12/2014	Adjaoute	N/A	N/A
2015/0055623	12/2014	Li	N/A	N/A
2015/0161024	12/2014	Gupta	N/A	N/A
2015/0172303	12/2014	Humble	N/A	N/A
2015/0199610	12/2014	Hershberg	N/A	N/A
2015/0229654	12/2014	Perier	N/A	N/A
2015/0256431	12/2014	Buchanan	N/A	N/A
2015/0262067	12/2014	Sridhara	N/A	N/A
2015/0271192	12/2014	Crowley	N/A	N/A
2015/0293954	12/2014	Hsiao	N/A	N/A
2015/0295945	12/2014	Canzanese, Jr.	N/A	N/A
2015/0324559	12/2014	Boss	N/A	N/A
2015/0356451	12/2014	Gupta	N/A	N/A
2016/0006815	12/2015	Dong	N/A	N/A
2016/0028750	12/2015	Di Pietro	N/A	N/A
2016/0036819	12/2015	Zehavi	N/A	N/A
2016/0048984	12/2015	Frigo	N/A	N/A
2016/0119372	12/2015	Borlick	N/A	N/A
2016/0128043	12/2015	Shuman	N/A	N/A
2016/0164721	12/2015	Zhang	N/A	N/A
2016/0173446	12/2015	Nantel	N/A	N/A
2016/0173495	12/2015	Joo	N/A	N/A
2016/0182497	12/2015	Smith	N/A	N/A
2016/0196558	12/2015	Mercille	N/A	N/A
2016/0210556	12/2015	Ben Simhon	N/A	N/A
2016/0212099	12/2015	Zou	N/A	N/A
2016/0218949	12/2015	Dasgupta	N/A	N/A
2016/0261465	12/2015	Gupta	N/A	N/A
2016/0267406	12/2015	Bodo	N/A	N/A
2016/0267408	12/2015	Singh	N/A	N/A
2016/0277435	12/2015	Salajegheh	N/A	N/A
2016/0301707	12/2015	Cheng	N/A	N/A
2016/0301717	12/2015	Dotan	N/A	N/A
2016/0337127	12/2015	Schultz	N/A	N/A
2016/0352685	12/2015	Park	N/A	N/A
2016/0366141	12/2015	Smith	N/A	N/A
2016/0366181	12/2015	Smith	N/A	N/A
2016/0381030	12/2015	Chillappa	N/A	N/A
2017/0006028	12/2016	Tunnell	N/A	N/A
2017/0006135	12/2016	Siebel	N/A	N/A
2017/0011406	12/2016	Tunnell	N/A	N/A
2017/0013005	12/2016	Galula	N/A	N/A
2017/0055913	12/2016	Bandyopadhyay	N/A	N/A
2017/0063774	12/2016	Chen	N/A	N/A
2017/0063889	12/2016	Muddu	N/A	N/A

2017/0063905	12/2016	Muddu	N/A	N/A
2017/0085580	12/2016	Thanos	N/A	N/A
2017/0093915	12/2016	Ellis	N/A	N/A
2017/0118237	12/2016	Devi Reddy	N/A	N/A
2017/0118240	12/2016	Devi Reddy	N/A	N/A
2017/0124660	12/2016	Srivastava	N/A	N/A
2017/0126704	12/2016	Nandha Premnath	N/A	N/A
2017/0149813	12/2016	Wright	N/A	N/A
2017/0180380	12/2016	Bagasra	N/A	N/A
2017/0180399	12/2016	Sukhomlinov	N/A	N/A
2017/0188242	12/2016	Ghosh	N/A	N/A
2017/0200061	12/2016	Julian	N/A	N/A
2017/0214701	12/2016	Hasan	N/A	N/A
2017/0230402	12/2016	Greenspan	N/A	H04W 12/08
2017/0232300	12/2016	Tran	N/A	N/A
2017/0235585	12/2016	Gupta	N/A	N/A
2017/0235783	12/2016	Chen	N/A	N/A
2017/0242414	12/2016	Coote	N/A	N/A
2017/0244737	12/2016	Kuperman	N/A	N/A
2017/0251007	12/2016	Fujisawa	N/A	N/A
2017/0272554	12/2016	Kwan	N/A	N/A
2017/0279685	12/2016	Mota	N/A	N/A
2017/0289168	12/2016	Bar	N/A	N/A
2017/0289184	12/2016	Subramanian	N/A	N/A
2017/0331671	12/2016	Olsson	N/A	N/A
2017/0331906	12/2016	Choi	N/A	N/A
2017/0339178	12/2016	Mahaffey	N/A	N/A
2017/0344407	12/2016	Jeon	N/A	N/A
2017/0346677	12/2016	Suryanarayana	N/A	N/A
2018/0007055	12/2017	Infante-Lopez	N/A	N/A
2018/0007058	12/2017	Zou	N/A	N/A
2018/0012227	12/2017	Tunnell	N/A	N/A
2018/0018684	12/2017	Orr	N/A	N/A
2018/0027006	12/2017	Zimmermann	N/A	N/A
2018/0027020	12/2017	Pallas	N/A	N/A
2018/0039555	12/2017	Salunke	N/A	N/A
2018/0054449	12/2017	Nandha Premnath	N/A	N/A
2018/0078843	12/2017	Tran	N/A	N/A
2018/0115574	12/2017	Ridley	N/A	N/A
2018/0117446	12/2017	Tran	N/A	N/A
2018/0117447	12/2017	Tran	N/A	N/A
2018/0124096	12/2017	Schwartz	N/A	N/A
2018/0139227	12/2017	Martin	N/A	N/A
2018/0144139	12/2017	Cheng	N/A	N/A
2018/0173881	12/2017	Oberheide	N/A	N/A
2018/0191729	12/2017	Whittle	N/A	N/A
2018/0191746	12/2017	De Knijf	N/A	N/A
2018/0191755	12/2017	Monaco	N/A	N/A
2018/0191848	12/2017	Bhattacharya	N/A	N/A
2018/0205793	12/2017	Loeb	N/A	N/A

2018/0212768	12/2017	Kawashima	N/A	N/A
2018/0234302	12/2017	James	N/A	N/A
2018/0234519	12/2017	Boyapalle	N/A	N/A
2018/0248902	12/2017	Dănilă-Dumitrescu	N/A	N/A
2018/0255084	12/2017	Kotinas	N/A	N/A
2018/0261070	12/2017	Stevens	N/A	N/A
2018/0264347	12/2017	Tran	N/A	N/A
2018/0285234	12/2017	Degaonkar	N/A	N/A
2018/0293387	12/2017	Bar-El	N/A	N/A
2018/0295148	12/2017	Mayorgo	N/A	N/A
2018/0302440	12/2017	Hu	N/A	N/A
2018/0349598	12/2017	Harel	N/A	N/A
2018/0349612	12/2017	Harel	N/A	N/A
2018/0351972	12/2017	Yu	N/A	N/A
2018/0357556	12/2017	Rai	N/A	N/A
2018/0375887	12/2017	Dezent	N/A	N/A
2019/0019249	12/2018	Bhattacharjee	N/A	N/A
2019/0081961	12/2018	Bansal	N/A	N/A
2019/0089747	12/2018	Wang	N/A	N/A
2019/0098028	12/2018	Ektare	N/A	N/A
2019/0098058	12/2018	Ikegami	N/A	N/A
2019/0109717	12/2018	Reddy	N/A	N/A
2019/0121978	12/2018	Kraemer	N/A	N/A
2019/0138512	12/2018	Pourmohammad	N/A	N/A
2019/0182278	12/2018	Das	N/A	N/A
2019/0253319	12/2018	Kampanakis	N/A	N/A
2019/0268267	12/2018	Pignataro	N/A	N/A
2019/0268305	12/2018	Xu	N/A	N/A
2019/0296979	12/2018	Gupta	N/A	N/A
2019/0349426	12/2018	Smith	N/A	N/A
2019/0361917	12/2018	Tran	N/A	N/A
2019/0373007	12/2018	Salunke	N/A	N/A
2019/0373472	12/2018	Smith	N/A	N/A
2019/0387399	12/2018	Weinberg	N/A	N/A
2020/0036603	12/2019	Nieves	N/A	N/A
2020/0074085	12/2019	Cheng	N/A	N/A
2020/0076846	12/2019	Pandian	N/A	N/A
2020/0076853	12/2019	Pandian	N/A	N/A
2020/0117690	12/2019	Tran	N/A	N/A
2020/0156654	12/2019	Boss	N/A	N/A
2020/0162278	12/2019	Delaney	N/A	N/A
2020/0162503	12/2019	Shurtleff	N/A	N/A
2020/0177485	12/2019	Shurtleff	N/A	N/A
2020/0177589	12/2019	Mangalvedkar	N/A	N/A
2020/0195679	12/2019	Du	N/A	N/A
2020/0211721	12/2019	Ochoa	N/A	N/A
2020/0213146	12/2019	Kodam	N/A	N/A
2020/0285457	12/2019	Meriac	N/A	N/A
2020/0285997	12/2019	Bhattacharyya	N/A	N/A
2020/0366717	12/2019	Chaubey	N/A	N/A

2020/0409957	12/2019	Zhang	N/A	N/A
2021/0058430	12/2020	Novak	N/A	N/A
2021/0203615	12/2020	Roy	N/A	N/A
2021/0360406	12/2020	Heiland	N/A	N/A
2022/0060491	12/2021	Achleitner	N/A	N/A
2022/0086071	12/2021	Sivaraman	N/A	N/A
2022/0138634	12/2021	Covell	N/A	N/A
2022/0159020	12/2021	Wang	N/A	N/A
2022/0210065	12/2021	Khanna	N/A	N/A
2022/0210066	12/2021	Khanna	N/A	N/A
2023/0049886	12/2022	Sesha	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2904463	12/2019	CA	N/A
101719899	12/2009	CN	N/A
102025577	12/2011	CN	N/A
102291430	12/2012	CN	N/A
107862468	12/2017	CN	N/A
104837158	12/2017	CN	N/A
108650133	12/2017	CN	N/A
105659633	12/2019	CN	N/A
107135093	12/2019	CN	N/A
108306911	12/2019	CN	N/A
3136297	12/2016	EP	N/A
3576373	12/2018	EP	N/A
2016532957	12/2015	JP	N/A
2018513467	12/2017	JP	N/A
2019536144	12/2018	JP	N/A
2020503784	12/2019	JP	N/A
20170059546	12/2016	KR	N/A
2019218874	12/2018	WO	N/A

OTHER PUBLICATIONS

Author Unknown, Cisco Encrypted Traffic Analytics, Feb. 10, 2021. cited by applicant

Arash Fasihi , Rule Based Inference and Action Selection Based on Monitoring Data in IoT, Dec. 1, 2015. cited by applicant

Cramer et al., Detecting Anomalies in Device Event Data in the IoT, Proceedings of the 3rd International Conference on Internet of Things, Big Data and Security, Mar. 21, 2018, pp. 52-62. cited by applicant

Midi et al., Kalis—A System for Knowledge-driven Adaptable Intrusion Detection for the Internet of Things, 2017 IEEE 37th International Conference on Distributed Computing Systems, pp. 656-666. cited by applicant

Al-Shaer et al., Design and Implementation of Firewall Policy Advisor Tools, 2002. cited by applicant

Al-Shaer et al., Firewall Policy Advisor for Anomaly Discovery and Rule Editing, Integrated Network Management VIII, 2003. cited by applicant

Martin et al., Requirements and Recommendations for CWE Compatibility and CWE Effectiveness, Version 1.0, Jul. 28, 2011. cited by applicant

National Electrical Manufacturers Association, Manufacturer Disclosure Statement for Medical

Device Security, HIMSS/NEMA Standard HN Jan. 2013, 2013. cited by applicant

Blackstock et al., IoT Interoperability: A Hub-based Approach, 2014, IEEE International Conference on the Internet of Things (IoT), pp. 80-84. cited by applicant

Fredj et al., A Scalable IoT Service Search Based on Clustering and Aggregation, 2013 IEEE International Conference on Green Computing and Communication and IEEE Internet of Things and IEEE Cyber, Physical and Social Computing, pp. 1-8. cited by applicant

International Application No. PCT/US2016/025661, International Search Report and Written Opinion mailed Jul. 7, 2016. cited by applicant

Li et al., A Distributed Consensus Algorithm for Decision Making in Service-Oriented Internet of Things, Old Dominion University, ODU Digital Commons, 2014. cited by applicant

Liu et al., A Lightweight Anomaly Mining Algorithm in the Internet of Things, 2014 IEEE 5th International Conference on Software Engineering and Service Science, 2014, pp. 1142-1145. cited by applicant

Miloslavskaya et al., Ensuring Information Security for Internet of Things, 2017, IEEE 5th International Conference of Future Internet of Things and Cloud, pp. 62-69. cited by applicant

Nguyen et al., A Software-Defined Model for IoT Clusters: Enabling Applications on Demand, Faculty of Engineering and IT, University of Technology Sydney, Australia, IEEE Xplore, Apr. 23, 2018. cited by applicant

Sivanathan et al., Classifying IoT Devices in Smart Environments Using Network Traffic Characteristics, IEEE, TMC, No. 8, pp. 1745-1759, Aug. 2018. cited by applicant

Sivanathan et al., Detecting Behavioral Change of IoT Devices Using Clustering-Based Network Traffic Modeling, IEEE LCN 2019, Mar. 30, 2020. cited by applicant

Sivanathan et al., Inferring IoT Device Types from Network Behavior Using Unsupervised Clustering, IEEE ICN 2019, Oct. 2019. cited by applicant

Hirofumi Nakakoji, et al., "Study of the Incident Tendency Detection Method on Frequency Analysis," Technical Report of IEICE, Japan, The Institute of Electronics, Information and Communication Engineers (IEICE), Jul. 14, 2005, vol. 105, No. 193, pp. 83-88. cited by applicant

Charyyev et al., Locality-Sensitive IoT Network Traffic Fingerprinting for Device Identification, IEEE Internet of Things Journal, 2020, vol. 8, No. 3, pp. 1272-1281. cited by applicant

Du et al., A Lightweight Flow Feature-Based IoT Device Identification Scheme, Security and Communication Networks, 2022. cited by applicant

Zhao et al., A Few-Shot Learning Based Approach to IoT Traffic Classification, IEEE Communications Letters, 2021. cited by applicant

Charu C. Aggarwal, Outlier Analysis, Feb. 10, 2013, Retrieved from the Internet, URL:<https://web.archive.brg/web/20130210212057/http://charuaggarwal.net/outlierbook.pdf>. cited by applicant

Chen et al., A Model-Based Validated Autonomic Approach to Self-Protect Computing Systems, IEEE Internet of Things Journal, Oct. 2014, pp. 446-460, vol. 1, No. 5. cited by applicant

Meidan et al., ProfilIoT: A Machine Learning Approach for IoT Device Identification Based on Network Traffic Analysis, In Proceedings of the Symposium on Applied Computing (SAC'17), Apr. 3-7, 2017, pp. 506-509. cited by applicant

Fahim et al., Anomaly detection, analysis and prediction techniques in IoT environment: A systematic literature review, IEEE Access, vol. 7, 2019, pp. 81664-81681. cited by applicant

Nassif et al., Machine learning for anomaly detection: A systematic review, IEEE Access, vol. 9, 2021, pp. 78658-78700. cited by applicant

Liu et al., Noise removal in the presence of significant anomalies for industrial IoT sensor data in manufacturing, IEEE Internet of Things Journal, vol. 7, No. 8, Aug. 2020, pp. 7084-7096. cited by applicant

Liu et al., Deep anomaly detection for time-series data in industrial IoT: A communication-efficient on-device federated learning approach, IEEE Internet of Things Journal, vol. 8, No. 8, Apr. 15,

2021, pp. 6348-6358. cited by applicant

Pahl et al., All eyes on you: Distributed Multi-Dimensional IoT microservice anomaly detection, 14th International Conference on Network and Service Management (CNSM), IEEE, 2018, pp. 72-80. cited by applicant

Miettinen et al., IoT Sentinel Demo: Automated Device-Type Identification for Security Enforcement in IoT, IEEE 37th International Conference on Distributed Computing Systems (ICDCS), Jun. 5-8, 2017, pp. 2177-2184, <https://ieeexplore.ieee.org/document/7980220>. cited by applicant

Primary Examiner: Leung; Robert B

Attorney, Agent or Firm: Van Pelt, Yi & James LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 16/538,787, filed Aug. 12, 2019 and entitled IoT DEVICE RISK ASSESSMENT, which is a continuation of U.S. patent application Ser. No. 15/357,989 filed Nov. 21, 2016 and entitled “IoT Device Risk Assessment,” now U.S. Pat. No. 10,380,348, each of which is hereby incorporated by reference herein.

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 depicts a diagram of an example of a system for performing risk assessment for IoT devices.
- (2) FIG. 2 depicts a diagram of an example packet analysis based access log management system.
- (3) FIG. 3 depicts a diagram of an example packet analysis based system log management system.
- (4) FIG. 4 depicts a diagram of an example packet analysis based event log management system.
- (5) FIG. 5 depicts a diagram of an example of a packet analysis based IoT device vulnerability determination system.
- (6) FIG. 6 depicts a diagram of an example of a packet analysis based IoT device profiling system.
- (7) FIG. 7 depicts a diagram of a packet analysis based IoT device risk assessment system.
- (8) FIG. 8 depicts a diagram of an example of a system for assessing risk levels of IoT devices.
- (9) FIG. 9 depicts a diagram of another example of a system for assessing risk levels of IoT devices.
- (10) FIG. 10 depicts a diagram of an example of another system for assessing risk levels of IoT devices.
- (11) FIG. 11 depicts a diagram of another example of a system for assessing risk levels of IoT devices.
- (12) FIG. 12 depicts a diagram of another example of a system for assessing risk levels of IoT devices.
- (13) FIG. 13 depicts a diagram of another example of a system for assessing risk levels of IoT devices.
- (14) FIG. 14 depicts a flowchart of an example of a method for generating device profiles of IoT devices through packet inspection for use in assessing risk levels of the IoT devices.
- (15) FIG. 15 depicts a flowchart of another example of a method for generating device profiles of IoT devices through packet inspection for use in assessing risk levels of the IoT devices.
- (16) FIG. 16 depicts a flowchart of another example of a method for generating device profiles of IoT devices through packet inspection for use in assessing risk levels of the IoT devices.
- (17) FIG. 17 depicts a flowchart of another example of a method for generating device profiles of

IoT devices through packet inspection for use in assessing risk levels of the IoT devices.

(18) FIG. **18** depicts a flowchart of an example of a method for generating device profiles of IoT devices by determining vulnerabilities of IoT devices for use in assessing risk levels of IoT devices.

(19) FIG. **19** depicts a diagram of an example of a system for providing IoT device risk assessment through a mirror point.

(20) FIG. **20** depicts a diagram of an example of a method of assessing risk levels of IoT devices.

(21) FIG. **21** depicts a screenshot of a presentation of risk assessment data to a user.

(22) FIG. **22** depicts a screenshot of another presentation of risk assessment data to a user.

(23) FIG. **23** depicts a screenshot of another presentation of risk assessment data to a user.

(24) FIG. **24** depicts a screenshot of a device map. In the screenshot, the device map includes hosts and devices an IoT device communicates with in accessing network services.

Description

DETAILED DESCRIPTION

(1) FIG. **1** depicts a diagram **100** of an example of a system for performing risk assessment for Internet of things devices (referred to as “IoT devices”). The system of the example of FIG. **1** includes a computer-readable medium **102**, IoT device **104-1 . . . 104-n** (hereinafter referred to as “IoT devices **104**”) coupled to the computer-readable medium **102**, and an IoT device risk assessment system **106**.

(2) The computer-readable medium **102** and other computer readable mediums discussed in this paper are intended to include all mediums that are statutory (e.g., in the United States, under 35 U.S.C. 101), and to specifically exclude all mediums that are non-statutory in nature to the extent that the exclusion is necessary for a claim that includes the computer-readable medium to be valid. Known statutory computer-readable mediums include hardware (e.g., registers, random access memory (RAM), non-volatile (NV) storage, to name a few), but may or may not be limited to hardware.

(3) The computer-readable medium **102** and other computer readable mediums discussed in this paper are intended to represent a variety of potentially applicable technologies. For example, the computer-readable medium **102** can be used to form a network or part of a network. Where two components are co-located on a device, the computer-readable medium **102** can include a bus or other data conduit or plane. Where a first component is co-located on one device and a second component is located on a different device, the computer-readable medium **102** can include a wireless or wired back-end network or LAN. The computer-readable medium **102** can also encompass a relevant portion of a WAN or other network, if applicable.

(4) The devices, systems, and computer-readable mediums described in this paper can be implemented as a computer system or parts of a computer system or a plurality of computer systems. In general, a computer system will include a processor, memory, non-volatile storage, and an interface. A typical computer system will usually include at least a processor, memory, and a device (e.g., a bus) coupling the memory to the processor. The processor can be, for example, a general-purpose central processing unit (CPU), such as a microprocessor, or a special-purpose processor, such as a microcontroller.

(5) The memory can include, by way of example but not limitation, random access memory (RAM), such as dynamic RAM (DRAM) and static RAM (SRAM). The memory can be local, remote, or distributed. The bus can also couple the processor to non-volatile storage. The non-volatile storage is often a magnetic floppy or hard disk, a magnetic-optical disk, an optical disk, a read-only memory (ROM), such as a CD-ROM, EPROM, or EEPROM, a magnetic or optical card, or another form of storage for large amounts of data. Some of this data is often written, by a direct memory access process, into memory during execution of software on the computer system. The

non-volatile storage can be local, remote, or distributed. The non-volatile storage is optional because systems can be created with all applicable data available in memory.

(6) Software is typically stored in the non-volatile storage. Indeed, for large programs, it may not even be possible to store the entire program in the memory. Nevertheless, it should be understood that for software to run, if necessary, it is moved to a computer-readable location appropriate for processing, and for illustrative purposes, that location is referred to as the memory in this paper. Even when software is moved to the memory for execution, the processor will typically make use of hardware registers to store values associated with the software, and local cache that, ideally, serves to speed up execution. As used herein, a software program is assumed to be stored at an applicable known or convenient location (from non-volatile storage to hardware registers) when the software program is referred to as “implemented in a computer-readable storage medium.” A processor is considered to be “configured to execute a program” when at least one value associated with the program is stored in a register readable by the processor.

(7) In one example of operation, a computer system can be controlled by operating system software, which is a software program that includes a file management system, such as a disk operating system. One example of operating system software with associated file management system software is the family of operating systems known as Windows® from Microsoft Corporation of Redmond, Washington, and their associated file management systems. Another example of operating system software with its associated file management system software is the Linux operating system and its associated file management system. The file management system is typically stored in the non-volatile storage and causes the processor to execute the various acts required by the operating system to input and output data and to store data in the memory, including storing files on the non-volatile storage.

(8) The bus can also couple the processor to the interface. The interface can include one or more input and/or output (I/O) devices. Depending upon implementation-specific or other considerations, the I/O devices can include, by way of example but not limitation, a keyboard, a mouse or other pointing device, disk drives, printers, a scanner, and other I/O devices, including a display device. The display device can include, by way of example but not limitation, a cathode ray tube (CRT), liquid crystal display (LCD), or some other applicable known or convenient display device. The interface can include one or more of a modem or network interface. It will be appreciated that a modem or network interface can be considered to be part of the computer system. The interface can include an analog modem, ISDN modem, cable modem, token ring interface, satellite transmission interface (e.g. “direct PC”), or other interfaces for coupling a computer system to other computer systems. Interfaces enable computer systems and other devices to be coupled together in a network.

(9) The computer systems can be compatible with or implemented as part of or through a cloud-based computing system. As used in this paper, a cloud-based computing system is a system that provides virtualized computing resources, software and/or information to end user devices. The computing resources, software and/or information can be virtualized by maintaining centralized services and resources that the edge devices can access over a communication interface, such as a network. “Cloud” may be a marketing term and for the purposes of this paper can include any of the networks described herein. The cloud-based computing system can involve a subscription for services or use a utility pricing model. Users can access the protocols of the cloud-based computing system through a web browser or other container application located on their end user device.

(10) A computer system can be implemented as an engine, as part of an engine or through multiple engines. As used in this paper, an engine includes one or more processors or a portion thereof. A portion of one or more processors can include some portion of hardware less than all of the hardware comprising any given one or more processors, such as a subset of registers, the portion of the processor dedicated to one or more threads of a multi-threaded processor, a time slice during which the processor is wholly or partially dedicated to carrying out part of the engine's functionality, or the like. As such, a first engine and a second engine can have one or more

dedicated processors or a first engine and a second engine can share one or more processors with one another or other engines. Depending upon implementation-specific or other considerations, an engine can be centralized or its functionality distributed. An engine can include hardware, firmware, or software embodied in a computer-readable medium for execution by the processor. The processor transforms data into new data using implemented data structures and methods, such as is described with reference to the FIGS. in this paper.

(11) The engines described in this paper, or the engines through which the systems and devices described in this paper can be implemented, can be cloud-based engines. As used in this paper, a cloud-based engine is an engine that can run applications and/or functionalities using a cloud-based computing system. All or portions of the applications and/or functionalities can be distributed across multiple computing devices, and need not be restricted to only one computing device. In some embodiments, the cloud-based engines can execute functionalities and/or modules that end users access through a web browser or container application without having the functionalities and/or modules installed locally on the end-users' computing devices.

(12) As used in this paper, datastores are intended to include repositories having any applicable organization of data, including tables, comma-separated values (CSV) files, traditional databases (e.g., SQL), or other applicable known or convenient organizational formats. Datastores can be implemented, for example, as software embodied in a physical computer-readable medium on a specific-purpose machine, in firmware, in hardware, in a combination thereof, or in an applicable known or convenient device or system. Datastore-associated components, such as database interfaces, can be considered “part of” a datastore, part of some other system component, or a combination thereof, though the physical location and other characteristics of datastore-associated components is not critical for an understanding of the techniques described in this paper.

(13) Datastores can include data structures. As used in this paper, a data structure is associated with a particular way of storing and organizing data in a computer so that it can be used efficiently within a given context. Data structures are generally based on the ability of a computer to fetch and store data at any place in its memory, specified by an address, a bit string that can be itself stored in memory and manipulated by the program. Thus, some data structures are based on computing the addresses of data items with arithmetic operations; while other data structures are based on storing addresses of data items within the structure itself. Many data structures use both principles, sometimes combined in non-trivial ways. The implementation of a data structure usually entails writing a set of procedures that create and manipulate instances of that structure. The datastores, described in this paper, can be cloud-based datastores. A cloud-based datastore is a datastore that is compatible with cloud-based computing systems and engines.

(14) Returning to the example of FIG. 1, the IoT devices **104** are intended to represent devices with wired or wireless interfaces through which the IoT devices **104** can send and receive data over wired and wireless connections. Examples of IoT devices include thermostats, mobile devices, biological managers, sensory devices, and functionality performing devices. The IoT devices **104** can include unique identifiers which can be used in the transmission of data through a network. Unique identifiers of the IoT devices **104** can include identifiers created in accordance with Internet Protocol version 4 (hereinafter referred to as “IPv4”), or identifiers created in accordance with Internet Protocol version 6 (hereinafter referred to as “IPv6”), of which both protocol versions are hereby incorporated by reference. Depending upon implementation-specific or other considerations, the IoT devices **104** can include applicable communication interfaces for receiving and sending data according to an applicable wireless device protocol. Examples of applicable wireless device protocols include Wi-Fi, ZigBee®, Bluetooth®, and other applicable low-power communication standards.

(15) In a specific implementation, the IoT devices **104** act as stations. A station, as used in this paper, can be referred to as a device with a media access control (MAC) address and a physical layer (PHY) interface to a wireless medium that complies with the IEEE 802.11 standard. Thus, for

example, the network devices can be referred to as stations, if applicable. IEEE 802.11a-1999, IEEE 802.11b-1999, IEEE 802.11g-2003, IEEE 802.11-2007, and IEEE 802.11n TGN Draft 8.0 (2009) are incorporated by reference. As used in this paper, a system that is 802.11 standards-compatible or 802.11 standards-compliant complies with at least some of one or more of the incorporated documents' requirements and/or recommendations, or requirements and/or recommendations from earlier drafts of the documents, and includes Wi-Fi systems. Wi-Fi is a non-technical description that is generally correlated with the IEEE 802.11 standards, as well as Wi-Fi Protected Access (WPA) and WPA2 security standards, and the Extensible Authentication Protocol (EAP) standard. In alternative embodiments, a station may comply with a different standard than Wi-Fi or IEEE 802.11, may be referred to as something other than a "station," and may have different interfaces to a wireless or other medium.

(16) In a specific implementation, the IoT devices **104** are configured to access network services in compliance with IEEE 802.3. IEEE 802.3 is a working group and a collection of IEEE standards produced by the working group defining the physical layer and data link layer's MAC of wired Ethernet. This is generally a local area network technology with some wide area network applications. Physical connections are typically made between nodes and/or infrastructure devices (hubs, switches, routers) by various types of copper or fiber cable. IEEE 802.3 is a technology that supports the IEEE 802.1 network architecture. As is well-known in the relevant art, IEEE 802.11 is a working group and collection of standards for implementing wireless local area network (WLAN) computer communication in the 2.4, 3.6 and 5 GHz frequency bands. The base version of the standard IEEE 802.11-2007 has had subsequent amendments. These standards provide the basis for wireless network products using the Wi-Fi brand. IEEE 802.1 and 802.3 are incorporated by reference.

(17) In the example of FIG. 1, the IoT device risk assessment system **106** is intended to represent a system that functions to determine risk levels of IoT devices. A risk for an IoT device, as used in this paper, indicates a level or levels of vulnerability in a network an IoT device introduces in accessing network services through the network. For example, a risk for an IoT device can include how likely an IoT device is to be used as part of a denial of service attack for a network. In another example, a risk for an IoT device can include how likely an IoT device is to introducing viruses within a network used by the IoT device to access network services. An IoT device with a high risk level corresponds to the IoT device increasing the vulnerability of a network when it accesses services through the network. A network in which an IoT device introduces vulnerability forming the basis for determining a risk of an IoT device can include all or a portion of a LAN used by the IoT device in accessing network services. For example, a network in which an IoT device introduces vulnerability can include a LAN formed by a plurality of IoT devices including the IoT device. Further in the example, the LAN formed by the plurality of IoT devices including the IoT device can include a portion or all of an enterprise or personal network.

(18) In a specific implementation, at least a portion of the IoT device risk assessment system **106** is implemented remote from IoT devices for which the system determines risk levels. For example, at least a portion of the IoT device risk assessment system **106** can be implemented as cloud based systems. Portions of the IoT device risk assessment system **106** implemented remote from IoT devices can transmit and receive data to and from the IoT devices through virtual private network (hereinafter "VPN") tunnels. For example, the IoT device risk assessment system **106** can receive outbound network traffic sent from IoT devices over a VPN tunnel. Additionally, VPN tunnels through which the IoT device risk assessment system **106** can send and receive data can be maintained using dedicated networking equipment. For example, the IoT device risk assessment system **106** can send and receive data to and from IoT devices using dedicated routers for communicating with the IoT devices.

(19) In a specific implementation, the IoT device risk assessment system **106** is implemented, at least in part, through a local agent. A local agent, as used in this paper, is a physical device locally

coupled to IoT devices for use in transmitting data to and from the IoT devices. Depending upon implementation-specific or other considerations, the IoT device risk assessment system **106** can include either or both a wired and a wireless communication interface for transmitting data to and from IoT devices over either or both a wired communication channel and a wireless communication channel. The IoT device risk assessment system **106** can be, at least in part, a device provided by an Internet service provider directly purchased by a consumer and acting as a conduit between networks. Depending upon implementation or other considerations, the IoT device risk assessment system **106** can be implemented as part of a private cloud. A private cloud implementing the IoT device risk assessment system **106**, at least in part, can be specific to an entity.

(20) In a specific implementation, the IoT device risk assessment system **106** functions to determine risk levels of IoT devices according to IoT device risk factors. IoT device risk factors include applicable characteristics of an IoT device and an IoT device in operation used in determining a risk level of an IoT device. For example, IoT device risk factors can include whether an IoT device is operating according to either or both known and discovered vulnerabilities. IoT device risk factors can include applicable operational characteristics of an IoT device in accessing network services through a network. For example, IoT device risk factors can include a number of open ports used by an IoT device in accessing network services. In another example, IoT device risk factors can include a number of open ports not used by an IoT device accessing network services through other open ports.

(21) In a specific implementation, the IoT device risk assessment system **106** functions to determine risk levels of IoT devices according to IoT device risk factors related to device characteristics of the IoT device. Device characteristics of an IoT device include applicable characteristics of an IoT device itself. For example, device characteristics of an IoT device include a device type of an IoT device, applications, operating systems, and firmware used by an IoT device, a version of applications, operating systems, and firmware used by an IoT device, and security risks associated with a device itself, e.g. based on device type of the device. For example, if an IoT device is utilizing an out of data operating system, then the IoT device risk assessment system **106** can determine the IoT device is at a higher risk level.

(22) In a specific implementation, the IoT device risk assessment system **106** functions to determine risk levels of IoT devices according to IoT device risk factors related to applications used by IoT devices in accessing network services. Applications used by IoT devices in accessing network services can include applications residing, at least in part, at an IoT device and capable of being executed as part of the IoT device accessing network services. For example, an application used by an IoT device in accessing network services can include an application executing at the IoT device using data transmitted to and from the IoT device as part of the IoT device accessing network services. IoT device risk factors related to applications used by IoT devices in accessing network services can include a number of applications used by an IoT device in accessing network services and characteristics of applications used by an IoT device in accessing network services. For example, IoT device risk factors related to applications used by an IoT device in accessing network services can include a number of applications executing at an IoT device at a specific time or during a specific time duration.

(23) In a specific implementation, characteristics of an application forming IoT device risk factors used in determining risk levels of IoT devices include a risk reputation of the application. A risk reputation of an application can include a level or levels of vulnerability an application introduced in one or plurality of networks based on past operation of IoT devices in using the application to access network services through the one or plurality of networks. For example, if an application was used to infect IoT devices within a network with a virus, then a risk reputation of the application can indicate or reflect that the application was used to infect IoT devices within a network.

(24) In a specific implementation, the IoT device risk assessment system **106** functions to determine risk levels of IoT devices according to IoT device risk factors related to protocols used by IoT devices in accessing network services. Protocols can include applicable protocols used in providing IoT devices access to network services. For example, protocols can include infrastructure protocols, identification protocols, transport protocols, discovery protocols, data protocols, device management protocols, semantic protocols, and multi-layer framework protocols. IoT device risk factors related to protocols used by IoT devices in accessing network services can include a number of differed protocols used by an IoT device in accessing network services and characteristics of protocols used by an IoT device in accessing network services. For example, IoT device risk factors related to protocols used by an IoT device in accessing network services can include a number of protocols used by an IoT device in accessing network services at a specific time or during a specific time duration.

(25) In a specific implementation, characteristics of a protocol forming IoT device risk factors used in determining risk levels of IoT devices include a risk reputation of the protocol. A risk reputation of a protocol can include a level or levels of network vulnerability introduced to one or plurality of networks based on past operation of IoT devices in using the protocol to access network services through the one or plurality of networks. For example, if an IoT device accessing network services according to a specific protocol was used to spread a virus within a network, then a risk reputation of the protocol can indicate or reflect that a virus was spread through a network using an IoT device accessing network services according to the protocol.

(26) In a specific implementation, the IoT device risk assessment system **106** functions to determine risk levels of IoT devices according to IoT device risk factors related to network activeness of an IoT device in accessing network services. IoT device risk factors related to network activeness include applicable characteristics of an IoT device indicating how active the IoT device is in accessing network services. Example IoT device risk factors related to network activeness include a number of other IoT devices or hosts, e.g. remote hosts, an IoT device is communicating with in accessing network services, a number of connections an IoT device has established in accessing network services, a frequency at which an IoT device communicates with a specific number of other IoT devices or hosts, a frequency at which an IoT device has established a specific number of connections in accessing network services, an amount of bandwidth an IoT device is consuming in accessing network services, and a frequency at which an IoT device is consuming a specific amount of bandwidth. For example, if the IoT device risk assessment system **106** determines an IoT device is communicating with a number of hosts above a threshold number of hosts in accessing network services, then the IoT device risk assessment system **106** can determine the IoT device is at a high risk level.

(27) In a specific implementation, the IoT device risk assessment system **106** functions to determine risk levels of IoT devices according to IoT device risk factors related to network communication characteristics of the IoT devices in accessing network services. IoT device risk factors related to network communication characteristics of IoT devices in accessing network services include applicable characteristics of IoT devices in communicating through a network to access network services. For example, IoT device risk factors related to network communication characteristics include whether an IoT device is communicating internally, e.g. with hosts or other IoT devices through a LAN, whether an IoT device is communicating externally, e.g. with remote hosts or remote IoT devices through a WAN or the Internet, whether an IoT device is communicating in an outbound communication session, e.g. a communication session in which the IoT device initiates communication, and whether an IoT device is communicating in an inbound communication session, e.g. a communication session in which another IoT device or host initiates communication with an IoT device. For example, the IoT device risk assessment system **106** can set a risk level of a first IoT device communicating internally in an outbound communication session lower than a set risk level of a second IoT device communicating externally in an inbound

communication session.

(28) In a specific implementation, network communication characteristics forming IoT device risk factors used in determining risk levels of IoT devices include a risk reputation of a host or another IoT device communicating with an IoT device as part of accessing network services. A risk reputation of another IoT device is communicating with as part of accessing network services can be a risk level assigned to the another network device based on IoT device risk factors. For example, if an IoT device is communicating internally with another IoT device through a LAN, then a risk reputation of the another IoT device can be a risk level assigned to the another IoT device using IoT device risk factors. Additionally, a risk reputation of a host or another IoT device can include a level or levels of vulnerability a host or another IoT device introduced in one or plurality of networks based on past operation of IoT devices communicating with the host or another IoT device in accessing network services through the one or plurality of networks. For example, if IoT device external communication with a remote host caused a network to undergo an attack, then a risk reputation of the remote host can indicate that external communication with the remote host caused an attack on a network.

(29) In a specific implementation, the IoT device risk assessment system **106** functions to determine risk levels of IoT devices according to IoT device risk factors related to security characteristics of data traffic in providing IoT devices network service access. Security characteristics of data traffic in providing IoT devices network service access include applicable characteristics related to security of data traffic, e.g. whether data traffic transmitted to and from an IoT device is encrypted or sent through network tunnels. For example, if an IoT device is sending and receiving encrypted data in accessing network services, then the IoT device risk assessment system **106** can determine that the IoT device has a low risk level.

(30) In a specific implementation, the IoT device risk assessment system **106** functions to determine risk levels of IoT devices according to IoT device risk factors related to operational performance deviations of IoT devices. Operational performance deviations of IoT devices include ways in which IoT devices, in operation, deviate from regular IoT device behaviors, as indicated by device profiles of IoT devices. Regular IoT device behavior includes typical behavior exhibited by IoT devices in operation. Regular IoT device behavior can include typical IoT device behavior of a specific IoT device, typical IoT device behavior of IoT devices of a specific type, and typical IoT device behavior of a group of IoT devices. For example, regular IoT device behavior can include typical IoT device behavior of a group of IoT devices within an enterprise network. In another example, regular IoT device behavior can include typical IoT device behavior of a group of IoT devices at a physical location. An example of an operational performance deviation of an IoT device is an IoT device communicating with a remote host other IoT devices within the enterprise network of the IoT device refrain from communicating with, as indicated by typical IoT device behavior of the other IoT devices within the enterprise network.

(31) In a specific implementation, the IoT device risk assessment system **106** functions to maintain device profiles for IoT devices. Device profiles can be used to determine risk levels of IoT devices, e.g. by analyzing IoT device risk factors of IoT devices indicated by the device profiles. A device profile for an IoT device includes either or both characteristics of the IoT device and characteristics of how the IoT device functions in operation. For example a device profile can include a type of device of an IoT device, a maker of an IoT device, a module of an IoT device, firmware on an IoT device, an operating system of an IoT device, applications executing at or capable of being executed at an IoT device, an entity or an organization associated with an IoT device, a physical location of an IoT device, a network location of an IoT device, uses of an IoT device, characteristics of an IoT device actually operating, patterns of an IoT device in operating. In maintaining IoT device profiles, the IoT device risk assessment system **106** can cluster IoT devices together, thereby associating IoT device profiles with each other, for use in determining risk levels of IoT devices. For example, the IoT device risk assessment system **106** can group IoT devices of

the same type in an enterprise network together for use in determining a risk level of an IoT device of the type in the enterprise network based on device profiles of the grouped IoT devices.

(32) In a specific implementation, the IoT device risk assessment system **106** functions to maintain an instance of an IoT device as part of an IoT device profile. An instance of an IoT device includes either or both characteristics of an IoT device and characteristics of how a device is operating at a specific time. For example, if an IoT device begins communicating internally with another IoT device, then an instance of the IoT device can indicate that the IoT device is communicating internally with another IoT device. The IoT device risk assessment system **106** can use one or a plurality of instances of IoT devices to determine operational performance deviations of the IoT devices. For example, if a plurality of instances of an IoT device indicate an IoT device is communicating with a host which the IoT device does not normally communicate with, as indicated by regular IoT device behavior, then the IoT device risk assessment system **106** can determine the IoT device is deviating in its operation.

(33) In a specific implementation, the IoT device risk assessment system **106** functions to match an IoT device to a new device profile or otherwise create a new device profile for the IoT device based on instances of the IoT device. In matching an IoT device to a new device profile based on instances of the IoT device, the IoT device risk assessment system **106** can determine whether to actually match the IoT device to a new device profile using the instances of the IoT device. For example, if instances of an IoT device indicate the IoT device is continuing to deviate from regular IoT device behavior of the IoT device, or is otherwise behaving abnormally, then the IoT device risk assessment system **106** can determine to match the IoT device to a new device profile or create a new device profile for the IoT device. Additionally, in matching an IoT device to a new device profile based on instances of the IoT device, the IoT device risk assessment system **106** can determine a new device profile to match to the IoT device or otherwise create for the new IoT device. For example, if an instance of an IoT device indicates an IoT device is of a specific type, then the IoT device risk assessment system **106** can match the IoT device to an IoT device profile of an IoT device of the same type. In another example, the IoT device risk assessment system **106** can generate a new IoT device profile for an IoT device based on characteristics of the IoT device, as indicated by instances, before the IoT device began to deviate from regular IoT device behavior.

(34) In a specific implementation, the IoT device risk assessment system **106** functions to maintain device profiles based on passive observation of IoT devices. In maintaining device profiles based on passive observation of IoT devices, the IoT device risk assessment system **106** can use IoT history data created from one or an applicable combination of event logs, system logs, and access logs. Event logs, system logs, and access logs used in creating IoT history data can be maintained by analyzing data packets transmitted to and from IoT devices. For example, event logs, system logs, and access logs used in creating IoT history data can be maintained by performing deep packet inspection on data packets transmitted to and from IoT devices.

(35) In a specific implementation, the IoT device risk assessment system **106** functions to maintain device profile based on active probing of IoT devices. In maintaining device profiles based on active probing of IoT devices, the IoT device risk assessment system **106** can use IoT history data created by analyzing data traffic sent from an IoT device in response to probing of the IoT device. For example, if data sent from an IoT device in response to probing indicates an IoT device is susceptible to malware, as indicated by IoT history data, then the IoT device risk assessment system **106** can update a device profile of the IoT device to indicate the device is susceptible to malware. The IoT device risk assessment system **106** can maintain a device profile of an IoT device based on a vulnerability score assigned to the IoT device in response to proving of the vulnerability device. Specifically, the IoT device risk assessment system **106** can update a device profile of an IoT device to include a vulnerability score assigned to the IoT device and the vulnerability factors and IoT device performance resulting from probing that led to assignment of the vulnerability score to the IoT device.

(36) In a specific implementation, the IoT device risk assessment system **106** functions to determine risk levels of IoT devices according to IoT device risk factors based on assessment weights. Assessment weights specify weights to give to different risk factors in determining a risk level for an IoT device. Additionally, assessment weights are specific to one or a plurality of IoT device risk factors. For example, an assessment weight can specify to weigh IoT risk factors related to applications used by an IoT device in accessing network services 20% in determining an overall risk level, e.g. a risk score, of the IoT device. A risk score determined for an IoT device can be used to assess IoT devices into different risk levels. For example, if a first IoT device is assigned a risk score of twenty and a second IoT device is assigned a risk score of eighty, then the first IoT device can be assessed into a low risk level, while the second IoT device can be assessed into a high risk level.

(37) In a specific implementation, assessment weights applied to IoT device risk factors for use in determining risk levels of IoT devices, are dependent on characteristics of a network. Characteristics of a network include applicable features for describing a network in providing IoT devices access to network services. Examples of characteristics of a network include characteristics of other IoT devices within a network, as indicated by device profiles of the other IoT devices, physical locations of IoT devices within a network, and a network type of a network. In depending on characteristics of a network, assessment weights can vary between different IoT devices accessing network services through different networks. For example, if a first IoT device accesses network services through a first LAN serving a large amount of IoT devices, while a second IoT device accessed network services through a second LAN is serving a small amount of IoT device, then an assessment weight related to network activeness can be lower for the first IoT device than it is for the second IoT device.

(38) In a specific implementation, in depending on characteristics of IoT devices as part of characteristics of a network, assessment weights vary between different IoT devices accessing network services through the same network. For example, a first IoT device of a first device type accessing network services through a LAN can have different assessment weights than a second IoT device of a different device type accessing network services through the same LAN. In another example, if a first IoT device in accessing network services through a LAN is communicating externally with a remote host while a second IoT device in accessing network services through the LAN is communicating internally, then an assessment weight for IoT device risk factors related to network communication characteristics can be greater for the first IoT device than it is for the second IoT device.

(39) In a specific implementation, assessment weights applied to IoT device risk factors related to operational performance deviations of IoT devices are dependent on either or both specific behaviors an IoT device exhibited in deviating from regular IoT device behaviors or a degree to which an IoT device deviates from regular IoT device behaviors. For example, if in communicating with other IoT devices or hosts as part of accessing network services, an IoT device only deviates slightly from regular IoT device behaviors, then an assessment weight to apply IoT device risk factors related to operation performance deviations of IoT devices for the IoT can only be modified slightly for the IoT device. In another example, if in deviating from regular IoT device behavior, an IoT device exhibits vulnerabilities to outside attacks, then an assessment weight applied to IoT device risk factors related to operational performance deviations of IoT devices can be increased significantly.

(40) In a specific implementation, the IoT device risk assessment system **106** functions to present risk assessment data to a user. Risk assessment data includes applicable data related to assessment of IoT devices into risk levels. Example risk assessment data includes determined risk levels of IoT devices, characteristics of IoT devices, identifications of IoT devices, determined risk scores for IoT devices, assessment weights, including values of the weights used to determine risk levels of IoT devices, and IoT device risk factors used to determine risk levels of IoT devices. For example,

the IoT device risk assessment system **106** can present to a user risk levels assigned to IoT devices managed by a user. In another example, the IoT device risk assessment system **106** can present to a user identifications of all IoT devices managed by a user which are assigned to a risk level above a threshold risk level.

(41) In a specific implementation, the IoT device risk assessment system **106** functions to present risk assessment data to a user either or both periodically and in a response to a stimulus. Examples of stimuli triggering presentation of risk assessment data include an IoT device of a user is assigned a risk level greater than a threshold risk level, a threshold number of IoT devices of a user are assigned a risk level greater than a threshold risk level, or a user requests a risk assessment report for their IoT devices. For example, if a threshold for informing a user risk levels assigned to their IoT devices is one hundred devices have been assigned to a high risk level, and one hundred IoT devices managed by a user are assigned to a high risk level, then the IoT device risk assessment system **106** can present identifications of the one hundred IoT devices assigned to the high risk level to the user.

(42) In an example of operation of the example system shown in FIG. **1**, the IoT device risk assessment system **106** generates device profiles for the IoT devices **104** based on characteristics of the IoT devices **104** in accessing network services. In the example of operation of the example system shown in FIG. **1**, the IoT device risk assessment system **106** assigns the IoT devices **104** to risk levels according to IoT device risk factors and assessment weights based on the generated device profiles for the IoT devices **104**. Additionally in the example of operation of the example system shown in FIG. **1**, the IoT device risk assessment system **106** presents risk assessment data indicating the risk levels assigned to the IoT devices **104** to a user associated with the IoT devices **104**.

(43) FIG. **2** depicts a diagram **200** of an example packet analysis based access log management system **202**. The packet analysis based access log management system **202** is intended to represent a system that functions to use packet analysis to manage access logs for IoT devices. The packet analysis based access log management system **202** can be implemented as part of an applicable system for assessing IoT device risk levels, such as the IoT device risk assessment systems described in this paper. An access log managed by the packet analysis based access log management system **202** can be used in assessing IoT device risk levels. For example, an access log maintained by the packet analysis based access log management system **202** can be used to develop device profiles for IoT devices for use in assessing risk levels for the IoT devices. An access log maintained by the packet analysis based access log management system **202** includes applicable information related to users utilizing IoT devices. For example, an access log can include an identification of a user who utilized an IoT device, times when the user accessed the IoT device, locations of the IoT device when it was accessed by a specific user, locations of the user when accessing the IoT device, characteristics of different types of access to the IoT device, e.g. remote access, and ways in which a specific user utilizes the IoT device to access network services, which can also be included as part of or maintained separately as an event log.

(44) In a specific implementation, in maintaining an access log, the packet analysis based access log management system **202** can inspect packets at a location local with respect to IoT devices for which the packet analysis based access log management system **202** manages access logs. For example, the packet analysis based access log management system **202** can be implemented, at least in part, at a local appliance coupled to IoT devices, and subsequently inspect packets sent to and received from the IoT devices at the appliance. Alternatively, the packet analysis based access log management system **202** can inspect packets at a remote location with respect to IoT devices for which the packet analysis based access log management system **202** manages access logs. For example, the packet analysis based access log management system **202** can be implemented at a remote location from IoT devices, e.g. the cloud, and subsequently inspect packets sent to and received from the IoT devices at the remote location, e.g. in-line. When the packet analysis based

access log management system **202** is implemented to inspect packets at a remote location with respect to IoT devices, the packet analysis based access log management system **202** can receive packets for inspection through VPN tunnels.

(45) The packet analysis based access log management system **202** shown in the example of FIG. 2 includes a data flow management engine **204**, a packet inspector engine **206**, an access log management engine **208**, and an access log datastore **210**. The data flow management engine **204** functions to control the flow of data packets to and from IoT devices. In controlling the flow of data packets to and from IoT devices, the data flow management engine **204** can obtain data packets. In various implementations, the data flow management engine **204** can use packet sniffing to obtain data packets. For example, the data flow management engine **204** can analyze headers of data packets to determine which data packets to obtain for subsequent performance of packet inspection. Further, in controlling the flow of data packets to and from IoT devices, the data flow management engine **204** can forward the data packets to an appropriate destination. For example, if a data packet is addressed to a specific IoT device, then the data flow management engine **204** can forward the data packet to the specific IoT device. In various implementations, the data flow management engine **204** can forward data packets after the packets have been inspected. For example, the data flow management engine **204** can forward data packets after deep packet inspection has been performed on the data packets.

(46) In a specific implementation, the data flow management engine **204** functions to manage forwarding of data packets through VPN tunnels. In managing forwarding of data packets through VPN tunnels, the data flow management engine **204** can forward data packets to appropriate destinations using VPN tunnels. For example, the data flow management engine **204** can forward a data packet using a VPN tunnel, by forwarding the data packet to an ultimate destination through dedicated networking equipment, e.g. routers, for VPN tunneling. In managing forwarding of data packets through VPN tunnels, the data flow management engine **204** can select specific data packets to forward using VPN tunnels. The data flow management engine **204** can select data packets to forward through VPN tunneling based, at least in part, on either or both an origin and a destination of the data packet. For example, the data flow management engine **204** can forward data packets sent from a specific IoT device through VPN tunneling. Further, the data flow management engine **204** can select data packets to forward through VPN tunneling based, at least in part, on either or both a packet type and data contained in data packets. For example, if a data packet relates to sensitive information of a user, then the data flow management engine **204** can forward the packet through VPN tunneling. Either or both a packet type and data contained in data packets can be determined by an applicable data packet analysis technique, e.g. deep packet inspection.

(47) In a specific implementation, a portion of the data flow management engine **204** is implemented as a local appliance, with respect to IoT devices, and another portion of the data flow management engine **204** is implemented remote from the IoT devices, e.g. in the cloud. A locally implemented portion of the data flow management engine **204** can obtain data packets transmitted from IoT devices and transmit the data packets to a remotely implemented portion of the data flow management engine **204** for use in assessing IoT device risk levels. Additionally, a locally implemented portion of the data flow management engine **204** can obtain data packets transmitted from IoT devices and transmit the data packets to a remotely implemented portion of the data flow management engine **204** through VPN tunneling. Data packets transmitted from a locally implemented portion of the data flow management engine **204** to a remotely implemented portion of the data flow management engine **204** can be analyzed at the remote location, e.g. in the cloud, for use in assessing IoT device risk levels.

(48) In a specific implementation, a remotely implemented portion of the data flow management engine **204** functions to obtain data packets destined to IoT devices and transmit the data packets to a locally implemented portion of the data flow management engine **204**, for use in assessing risk

levels of IoT devices. A remotely implemented portion of the data flow management engine **204** can obtain data packets destined to IoT devices and transmit the data packets to a remotely implemented portion of the data flow management engine **204** through VPN tunneling. Additionally, data packets transmitted from a remotely implemented portion of the data flow management engine **204** to a locally implemented portion of the data flow management engine **204** can be analyzed at either or both a remote location or a local location, for use in assessing risk levels of IoT devices.

(49) In the example of FIG. 2, the packet inspector engine **206** is intended to represent an engine that functions to sniff packets sent to and from IoT devices for the purposes of assessing risk levels of the IoT devices. For example, the packet inspector engine **206** can analyze packets to determine a user of an IoT device. Depending upon implementation-specific or other considerations, the packet inspector engine **206** can perform deep packet inspection on packets sent to and from IoT devices. In performing deep packet inspection on packets sent to and from IoT devices, the packet inspector engine **206** can determine transaction data from payloads of data packets. Transaction data includes either or both types and subjects of data transmitted as part of a data packet. For example, transaction data of a data packet sent to a thermostat can include an instruction to increase the temperature at the thermostat. Transaction data determined by the packet inspector engine **206** can be used to build, at least in part, historical records for IoT devices. Historical records of IoT devices can be formed from an applicable combination of event logs, system logs, and access logs for IoT devices and used in assessing risk levels of IoT devices.

(50) In a specific implementation, the packet inspector engine **206** functions to identify either or both destinations and sources of analyzed data packets. For example, the packet inspector engine **206** can determine an identification of a destination IoT device by analyzing a data packet destined for the IoT device. In another example, the packet inspector engine **206** can determine a source of a data packet destined to an IoT device. Identifications of either or both destinations and sources of analyzed data packets, as determined by the packet inspector engine **206**, can be used, along with determined transaction data to generate historical records of IoT devices. The packet inspector engine **206** can select data packets to perform deep packet inspection on based on at least one of a source of data packets, a destination of data packets, a data packet type of data packets, and data within data packets. For example, all data packets from a particular source can have deep packet inspection performed on them by the packet inspector engine **206**.

(51) In the example of FIG. 2, the access log management engine **208** is intended to represent an engine that functions to maintain an access log of IoT devices for use in assessing IoT device risk levels. In managing an access log, the access log management engine **208** can create and update an access log to indicate an identification of a specific user interacting with or using an IoT device, when the user interacted with or used the IoT device, whether the user interacted with the IoT device from a remote location or not, and events in interacting with the IoT device, indicating a usage type of the IoT device by the user. An access log can be used to generate a subset of a historical record of an IoT device specific to a user, for use in establishing a regular behavior of a user in interacting with or utilizing a specific IoT device. For example, an access log can be used to establish that a user always interacts with a tablet at 8 o'clock in the evening on weeknights. Regular behavior of a user in interacting with or utilizing a specific IoT device can be used, at least in part, to assess a risk level of the IoT device.

(52) In a specific implementation, the access log management engine **208** functions to maintain an access log for an IoT device based on analysis of data packets transmitted to and from the IoT device. For example, the access log management engine **208** can maintain an access log for an IoT device based on analysis of data packets transmitted to and from the IoT device as a user interacts with or utilizes an IoT device. Depending upon implementation-specific or other considerations, the access log management engine **208** can maintain an access log based on deep packet inspection of packets transmitted to and from an IoT device. For example, the access log management engine

208 can use transaction data identified through deep packet inspection of data packets to determine how a user is interacting with an IoT device, e.g. events in interacting with the IoT device. Further in the example, the access log management engine **208** can update an access log to indicate how the user interacted with the IoT device. In another example, the access log management engine **208** can use transaction data identified through deep packet inspection of data packets to determine how a user remotely interacts with an IoT device, e.g. events in interacting with the IoT device remotely. (53) In a specific implementation, the access log management engine **208** functions to maintain an access log for IoT devices using at least in part, event logs for the IoT devices. In various implementations, the access log management engine **208** can use transaction data identified through deep packet inspection of data packets to determine how a user is interacting with an IoT device, e.g. events in interacting with the IoT device, and an events log to maintain an access log. For example, the access log management engine **208** can compare events determined from transaction data identified through deep packet inspection with a pattern of events, indicated by an event log, to determine how a user is interacting with an IoT device and subsequently update an access log to indicate how the user is interacting with the IoT device. In another example, the access log management engine **208** can compare events determined from transaction data identified through deep packet inspection with a pattern of events associated with different users, indicated by an event log, to determine an identification of a user interacting with an IoT device.

(54) In the example of FIG. 2, the access log datastore **210** is intended to represent a datastore that functions to store access log data indicating access logs for use in determining risk levels of IoT devices. Access log data stored in the access log datastore **210** can be maintained using packet analysis of data packets transmitted to and from IoT devices. Additionally, access log data stored in the access log datastore **210** can be maintained using events in interactions with IoT devices determined from transaction data identified through deep packet inspection of data packets transmitted to and from the IoT devices. Further, access log data stored in the access log datastore **210** can be maintained using, at least in part, an event logs for IoT devices.

(55) In an example of operation of the system shown in the example of FIG. 2, the data flow management engine **204** obtains data packets destined to or sent from an IoT device. In the example of operation of the example system shown in FIG. 2, the packet inspector engine **206** uses deep packet inspection to identify transaction data describing user interactions with the IoT device from the obtained data packets. Further, in the example of operation of the example of operation of the example system shown in FIG. 2, the access log management engine **208** determines events related to user interaction with the IoT device from the transaction data and subsequently maintains an access log, stored as access log data in the access log datastore **210**, based on the determined events. In the example of operation of the example system shown in FIG. 2, the access log, stored as the access log data in the access log datastore **210** is used in assessing IoT device risk levels.

(56) FIG. 3 depicts a diagram **300** of an example packet analysis based system log management system **302**. The packet analysis based system log management system **302** is intended to represent a system that functions to use packet analysis to manage system logs for IoT devices. Additionally, the packet analysis based system log management system **302** can be implemented as part of an applicable system for assessing IoT device risk levels, such as the IoT device risk assessment systems described in this paper. A system log managed by the packet analysis based system log management system **302** can be used in assessing IoT device risk levels. For example, a system log maintained by the system log management system **302** can be used to develop device profiles for IoT devices for use in assessing risk levels of the IoT devices. A system log maintained by the packet analysis based system log management system **302** can include applicable information relating to systems of managed IoT devices. For example, a system log can include applications and operating systems executed at an IoT device, and capabilities of an IoT device, e.g. whether an IoT device is capable of communicating with a remote source.

(57) In a specific implementation, in maintaining a system log, the packet analysis based system

log management system **302** can inspect packets at a location local with respect to IoT devices for which the packet analysis based system log management system **302** manages system logs. For example, the packet analysis based system log management system **302** can be implemented, at least in part, at a local appliance coupled to IoT devices, and subsequently inspect packets sent to and received from the IoT devices at the appliance. Alternatively, the packet analysis based system log management system **302** can inspect packets at a remote location with respect to IoT devices for which the packet analysis based system log management system **302** manages system logs. For example, the packet analysis based system log management system **302** can be implemented at a remote location from IoT devices, e.g. the cloud, and subsequently inspect packets sent to and received from the IoT devices at the remote location, e.g. in-line. When the packet analysis based system log management system **302** is implemented to inspect packets at a remote location with respect to IoT devices, the packet analysis based system log management system **302** can receive packets for inspection through VPN tunneling.

(58) The packet analysis based system log management system **302** shown in the example of FIG. 3 includes a data flow management engine **304**, a packet inspector engine **306**, a system log management engine **308**, and a system log datastore **310**. The data flow management engine **304** is intended to represent an engine that functions according to an applicable engine for controlling the flow of data packets to and from IoT devices for purposes of determining risk levels of the IoT devices, such as the data flow management engines described in this paper. In controlling the flow of data packets to and from IoT devices, the data flow management engine **304** can obtain data packets. Further, in controlling the flow of data packets to and from IoT devices, the data flow management engine **304** can forward the data packets to an appropriate destination. For example, if a data packet is addressed to a specific IoT device, then the data flow management engine **304** can forward the data packet to the specific IoT device. In various implementations, the data flow management engine **304** can forward data packets after the packets have been inspected. For example, the data flow management engine **304** can forward data packets after deep packet inspection has been performed on the data packets.

(59) In a specific implementation, the data flow management engine **304** functions to manage forwarding of data packets through VPN tunnels. In managing forwarding of data packets through VPN tunnels, the data flow management engine **304** can forward data packets to appropriate destinations using VPN tunnels. For example, the data flow management engine **304** can forward a data packet using a VPN tunnel, by forwarding the data packet to an ultimate destination through dedicated networking equipment, e.g. routers, for VPN tunneling. In managing forwarding of data packets through VPN tunnels, the data flow management engine **304** can select specific data packets to forward using VPN tunnels. The data flow management engine **304** can select data packets to forward through VPN tunneling based, at least in part, on either or both an origin and a destination of the data packet. For example, the data flow management engine **304** can forward data packets sent from a specific IoT device through VPN tunneling. The data flow management engine **304** can select data packets to forward through VPN tunneling based, at least in part, on either or both a packet type and data contained in data packets. For example, if a data packet relates to login information of a user, then the data flow management engine **304** can forward the packet through VPN tunneling. Either or both a packet type and data contained in data packets can be determined by an applicable data packet analysis techniques, e.g. deep packet inspection.

(60) In a specific implementation, a portion of the data flow management engine **304** is implemented as a local appliance, with respect to IoT devices, and another portion of the data flow management engine **304** is implemented remote from the IoT devices, e.g. in the cloud. A locally implemented portion of the data flow management engine **304** can obtain data packets transmitted from IoT devices and transmit the data packets to a remotely implemented portion of the data flow management engine **304**. Additionally, a locally implemented portion of the data flow management engine **304** can obtain data packets transmitted from IoT devices and transmit the data packets to a

remotely implemented portion of the data flow management engine **304** through VPN tunneling. Data packets transmitted from a locally implemented portion of the data flow management engine **304** to a remotely implemented portion of the data flow management engine **304** can be analyzed at the remote location, e.g. in the cloud, for use in assessing IoT device risk levels.

(61) In a specific implementation, a remotely implemented portion of the data flow management engine **304** functions to obtain data packets destined to IoT devices and transmit the data packets to a locally implemented portion of the data flow management engine **304**, for use in assessing risk levels of IoT devices. A remotely implemented portion of the data flow management engine **304** can obtain data packets destined to IoT devices and transmit the data packets to a locally implemented portion of the data flow management engine **304** through VPN tunneling. Additionally, data packets transmitted from a remotely implemented portion of the data flow management engine **304** to a locally implemented portion of the data flow management engine **304** can be analyzed at either or both a remote location or a local location, for use in assessing risk levels of IoT devices.

(62) In the example of FIG. 3, the packet inspector engine **306** is intended to represent an engine that functions according to an applicable engine for sniffing packets sent to and from IoT devices for the purposes of assessing risk levels of the IoT devices, such as the packet inspector engines described in this paper. For example, the packet inspector engine **306** can sniff packets to determine applications being executed at an IoT device which can subsequently be used to determine a risk level of an IoT device. In analyzing data packets, the packet inspector engine **306** can perform deep packet inspection on packets sent to and from IoT devices. In performing deep packet inspection on packets sent to and from IoT devices, the packet inspector engine **306** can determine transaction data of data packets. Transaction data determined by the packet inspector engine **306** can be used to build, at least in part, historical records for IoT devices. Historical records for IoT devices can be formed from an applicable combination of event logs, system logs, and access logs for IoT devices and used in assessing risk levels of IoT devices.

(63) In a specific implementation, the packet inspector engine **306** functions to identify either or both destinations and sources of analyzed data packets. For example, the packet inspector engine **306** can determine an identification of a destination IoT device by analyzing a data packet destined for the IoT device. In another example, the packet inspector engine **306** can determine a source of a data packet destined to an IoT device. Identifications of either or both destinations and sources of analyzed data packets can be used, along with transaction data determined from the analyzed data packets, to generate historical records for IoT devices. The packet inspector engine **306** can select data packets to perform deep packet inspection on based on at least one of a source of data packets, a destination of data packets, a data packet type of data packets, and data within data packets. For example, all data packets from a particular source can have deep packet inspection performed on them by the packet inspector engine **306**.

(64) In the example of FIG. 3, the system log management engine **308** is intended to represent an engine that functions to maintain a system log for IoT devices for use in assessing risk levels of IoT devices. In managing a system log, the system log management engine **308** can create and update a system log to indicate one or an applicable combination of an identification of applications and operating systems executing or capable of being executed at an IoT device, versions of applications and operating systems executing or capable of being executed at an IoT device, applications and operating systems that have been executed at an IoT device, and times and locations of the IoT devices when the applications and operating systems were executed at an IoT device. A system log can be used to generate a historical record specific to an IoT device, for use in determining whether a normal application is being executed at an IoT device as part of regular IoT device behavior. For example, a system log can be used to establish that an IoT device usually executes specific applications which can subsequently be used to assess a risk level of the IoT device.

(65) In a specific implementation, the system log management engine **308** functions to maintain a

system log for an IoT device based on analysis of data packets transmitted to and from the IoT device. In maintaining a system log based on analysis of data packets, the system log management engine **308** can maintain a system log based on deep packet inspection of packets transmitted to and from an IoT device. For example, the system log management engine **308** can use transaction data identified through deep packet inspection of data packets to determine what applications are executing on an IoT device, e.g. through types of data transmitted from an IoT device. Further in the example, the system log management engine **308** can update a system log to indicate what applications are executing at an IoT device and times the applications are executing at the IoT device.

(66) In the example of FIG. **3**, the system log datastore **310** is intended to represent a datastore that functions to store system log data indicating system logs for use in assessing IoT device risk levels. System log data stored in the system log datastore **310** can be maintained using packet analysis of data packets transmitted to and from IoT devices. Additionally, system log data stored in the system log datastore **310** can be maintained using transaction data identified through deep packet inspection of data packets transmitted to and from the IoT devices. For example, system log data can be generated based on a determination of applications executing at an IoT device using transaction data identified through deep packet inspection of data packets transferred to and from the IoT device as part of executing the applications.

(67) In an example of operation of the system shown in the example of FIG. **3**, the data flow management engine **304** obtains data packets destined to or sent from an IoT device. In the example of operation of the example system shown in FIG. **3**, the packet inspector engine **306** uses deep packet inspection to identify transaction data from the obtained data packets. Further, in the example of operation of the example system shown in FIG. **3**, the system log management engine **308** determines applications executing at the IoT device from the transaction data and subsequently maintains a system log, stored as system log data in the system log datastore **310**, indicating the applications executing at the IoT device and when the applications were executing at the IoT device. In the example of operation of the example system shown in FIG. **3**, the system log, stored as the system log data in the system log datastore **310** is used in assessing IoT device risk levels.

(68) FIG. **4** depicts a diagram **400** of an example packet analysis based event log management system **402**. The packet analysis based event log management system **402** is intended to represent a system that functions to use packet analysis to manage event logs for IoT devices. Additionally, the packet analysis based event log management system **402** can be implemented as part of an applicable system for assessing IoT device risk levels, such as the IoT device risk assessment systems described in this paper. An event log managed by the packet analysis based event log management system **402** can be used in assessing risk levels of IoT devices. For example, an event log maintained by the packet analysis based event log management system **402** can be used to develop device profiles for IoT devices for use in assessing risk levels of the IoT devices. An event log includes events associated with IoT devices. Events can include applicable parameters related to operation of an IoT device, such as what data is sent to and from the IoT device, destinations and origins of data sent to and from the IoT device, identifications of the IoT device, geographic information relating to the IoT device, and interaction types corresponding to patterns of events. For example, an event log can include a pattern of events corresponding to a specific way in which an IoT device is being interacted with or otherwise functioning.

(69) In a specific implementation, in maintaining an event log, the packet analysis based event log management system **402** can inspect packets at a location local with respect to IoT devices for which the packet analysis based event log management system **402** manages an event log. For example, the packet analysis based event log management system **402** can be implemented, at least in part, at a local appliance coupled to IoT devices, and subsequently inspect packets sent to and received from the IoT devices at the appliance. Alternatively, the packet analysis based event log management system **402** can inspect packets at a remote location with respect to IoT devices for

which the packet analysis based event log management system **402** manages an event log. For example, the packet analysis based event log management system **402** can be implemented at a remote location from IoT devices, e.g. the cloud, and subsequently inspect packets sent to and received from the IoT devices at the remote location, e.g. in-line. When the packet analysis based event log management system **402** is implemented to inspect packets at a remote location with respect to IoT devices, the packet analysis based event log management system **402** can receive packets for inspection through VPN tunneling.

(70) The packet analysis based event log management system **402** shown in the example of FIG. 4 includes a data flow management engine **404**, a packet inspector engine **406**, an event log management engine **408**, and an event log datastore **410**. The data flow management engine **404** is intended to represent an engine that functions according to an applicable engine for controlling the flow of data packets to and from IoT devices for purposes of determining risk levels of IoT devices, such as the data flow management engines described in this paper. In controlling the flow of data packets to and from IoT devices, the data flow management engine **404** can obtain data packets. Further, in controlling the flow of data packets to and from IoT devices, the data flow management engine **404** can forward the data packets to an appropriate destination. For example, if a data packet is addressed to a specific IoT device, then the data flow management engine **404** can forward the data packet to the specific IoT device. In various implementations, the data flow management engine **404** can forward data packets after the packets have been inspected. For example, the data flow management engine **404** can forward data packets after deep packet inspection has been performed on the data packets.

(71) In a specific implementation, the data flow management engine **404** functions to manage forwarding of data packets through VPN tunnels. In managing forwarding of data packets through VPN tunnels, the data flow management engine **404** can forward data packets to appropriate destinations using VPN tunnels. For example, the data flow management engine **404** can forward a data packet using a VPN tunnel, by forwarding the data packet to an ultimate destination through dedicated networking equipment, e.g. routers, for VPN tunneling. In managing forwarding of data packets through VPN tunnels, the data flow management engine **404** can select specific data packets to forward using VPN tunnels. the data flow management engine **404** can select data packets to forward through VPN tunneling based, at least in part, on an either or both an origin and a destination of the data packet. For example, the data flow management engine **404** can forward data packets sent from a specific IoT device through VPN tunneling. Additionally, the data flow management engine **404** can select data packets to forward through VPN tunneling based, at least in part, on either or both a packet type and data contained in data packets. For example, if a data packet relates to login information of a user, then the data flow management engine **404** can forward the packet through VPN tunneling. Either or both a packet type and data contained in data packets can be determined by an applicable packet analysis technique, e.g. deep packet inspection.

(72) In a specific implementation, a portion of the data flow management engine **404** is implemented as a local appliance, with respect to IoT devices, and another portion of the data flow management engine **404** is implemented remote from the IoT devices, e.g. in the cloud. A locally implemented portion of the data flow management engine **404** can obtain data packets transmitted from IoT devices and transmit the data packets to a remotely implemented portion of the data flow management engine **404**. Additionally, a locally implemented portion of the data flow management engine **404** can obtain data packets transmitted from IoT devices and transmit the data packets to a remotely implemented portion of the data flow management engine **404** through VPN tunneling. Data packets transmitted from a locally implemented portion of the data flow management engine **404** to a remotely implemented portion of the data flow management engine **404** can be analyzed at the remote location, e.g. in the cloud, for use in assessing IoT device risk levels.

(73) In a specific implementation, a remotely implemented portion of the data flow management engine **404** functions to obtain data packets destined to IoT devices and transmit the data packets to

a locally implemented portion of the data flow management engine **404**, for use in assessing risk levels of IoT devices. A remotely implemented portion of the data flow management engine **404** can obtain data packets destined to IoT devices and transmit the data packets to a locally implemented portion of the data flow management engine **404** through VPN tunneling. Additionally, data packets transmitted from a remotely implemented portion of the data flow management engine **404** to a locally implemented portion of the data flow management engine **404** can be analyzed at either or both a remote location or a local location, for use in assessing risk levels of IoT devices.

(74) In the example of FIG. 4, the packet inspector engine **406** is intended to represent an engine that functions according to an applicable engine for sniffing packets sent to and from IoT devices for purposes of assessing risk levels of the IoT devices, such as the packet inspector engines described in this paper. For example, the packet inspector engine **406** can sniff packets to determine events occurring at IoT devices which can subsequently be used to determine a risk level of an IoT device. In analyzing data packets, the packet inspector engine **406** can perform deep packet inspection on packets sent to and from IoT devices. In performing deep packet inspection on packets sent to and from IoT devices, the packet inspector engine **406** can determine transaction data of data packets. Transaction data determined by the packet inspector engine **406** can be used to build, at least in part, historical records for IoT devices. Historical records for IoT devices can be formed from an applicable combination of event logs, system logs, and access logs for IoT devices and used in assessing risk levels of IoT devices.

(75) In a specific implementation, the packet inspector engine **406** functions to identify either or both destinations and sources of analyzed data packets. For example, the packet inspector engine **406** can determine an identification of a destination IoT device by analyzing a data packet destined for the IoT device. In another example, the packet inspector engine **406** can determine a source of a data packet destined to an IoT device. Identifications of either or both destinations and sources of analyzed data packets can be used, along with transaction data determined from the analyzed data packets, to generate historical records for IoT devices. The packet inspector engine **406** can select data packets to perform deep packet inspection on based on at least one of a source of data packets, a destination of data packets, a data packet type of data packets, and data within data packets. For example, all data packets from a particular source can have deep packet inspection performed on them.

(76) In the example of FIG. 4, the event log management engine **408** is intended to represent an engine that functions to maintain an event log for IoT devices for use in assessing risk levels of IoT devices. In managing an event log, the event log management engine **408** can create and update an event log to indicate events occurring at an IoT device, times events occurred at the IoT device, and destinations and sources of data traffic related to events at an IoT device. An event log can be used to form part of a historical record of IoT devices. In various implementations, an event log can be used to generate a historical record specific to an IoT device, for use in determining normal operating behavior, e.g. regular IoT device behavior, of an IoT device. For example, an event log can be used to establish that an IoT device usually performs a specific function at a set time of day which can subsequently be used to assess a risk level of the IoT device.

(77) In a specific implementation, the event log management engine **408** functions to maintain an event log for an IoT device based on analysis of data packets transmitted to and from the IoT device. In maintaining an event log based on analysis of data packets, the event log management engine **408** can maintain an event log based on deep packet inspection of packets transmitted to and from an IoT device. For example, the event log management engine **408** can use transaction data identified through deep packet inspection of data packets to determine what events are occurring at an IoT device, e.g. through types of data transmitted from an IoT device. Further in the example, the event log management engine **408** can update an event log to indicate what events are occurring at an IoT device and times the events are occurring at the IoT device.

(78) In the example of FIG. 4, the event log datastore **410** is intended to represent a datastore that functions to store event log data indicating event logs for use in assessing IoT device risk levels. Event log data stored in the event log datastore **410** can be maintained using packet analysis of data packets transmitted to and from IoT devices. Additionally, event log data stored in the event log datastore **410** can be maintained using transaction data identified through deep packet inspection of data packets transmitted to and from the IoT devices. For example, event log data can be generated based on a determination of events occurring at an IoT device using transaction data identified through deep packet inspection of data packets transferred to and from the IoT device as part of occurrences of the events.

(79) In an example of operation of the system shown in the example of FIG. 4, the data flow management engine **404** obtains data packets destined to or sent from an IoT device. In the example of operation of the example system shown in FIG. 4, the packet inspector engine **406** uses deep packet inspection to identify transaction data from the obtained data packets. Further, in the example of operation of the example system shown in FIG. 4, the event log management engine **408** determines events occurring at the IoT device from the transaction data and subsequently maintains an event log, stored as event log data in the event log datastore **410**, indicating the events occurring at the IoT device and when the events occurred at the IoT device. In the example of operation of the example system shown in FIG. 4, the event log, stored as the event log data in the event log datastore **410** is used in assessing IoT device risk levels.

(80) FIG. 5 depicts a diagram **500** of an example of a packet analysis based IoT device vulnerability determination system **502**. The packet analysis based IoT device vulnerability determination system **502** is intended to represent a system that functions to determine vulnerability of IoT devices based, at least in part, on packet inspection. The packet analysis based IoT device vulnerability determination system **502** can be implemented as part of an applicable system for assessing risk levels of IoT devices, such as the IoT device risk assessment systems described in this paper. Vulnerabilities of IoT devices determined by the packet analysis based IoT device vulnerability determination system **502** can be used in assessing risk levels of IoT devices. For example, if the packet analysis based IoT device vulnerability determination system **502** determines that an IoT device is vulnerable to a specific attack, then a risk level can be assessed to the IoT device based on the determined vulnerability of the IoT device to the specific attack.

(81) In a specific implementation, the packet analysis based IoT device vulnerability determination system **502** functions to be implemented, at least in part, at a location local with respect to IoT devices for which the packet analysis based IoT device vulnerability determination system **502** determines vulnerabilities. For example, the packet based analysis IoT device vulnerability determination system **502** can be implemented, at least in part, at a local appliance coupled to IoT devices.

(82) In a specific implementation, the packet analysis based IoT device vulnerability determination system **502** functions to determine device vulnerabilities at a remote location with respect to IoT devices. For example, the packet based IoT device vulnerability determination system can be implemented at a remote location from IoT devices, e.g. the cloud, and subsequently perform vulnerability analysis at the remote location.

(83) The packet analysis based IoT device vulnerability determination system **502** shown in the example of FIG. 5 includes an IoT device probing engine **504**, an IoT device history datastore **506**, and a vulnerability determination engine **508**. The IoT device probing engine **504** functions to probe an IoT device for purposes of determining vulnerability of the IoT device. Results of probing of an IoT device by the IoT device probing engine **504** can be used to determine a risk level of the IoT device. The IoT device probing engine **504** can probe an IoT device by sending data packets to the IoT device. For example, the IoT device probing engine **504** can send a packet for gaining access to an IoT device to see if either or both a user id and a password for accessing the IoT device has changed. Further in the example, if the IoT device probing engine **504** fails to gain access to an

IoT device with either or both a user id and password that is associated with accessing the IoT device, then it can be determined either or both the user id and password for accessing the IoT device has changed. In another example, the IoT device probing engine **504** can send a packet for gaining access to an IoT device using either or both a default user id and password. Further in the example, if the IoT device probing engine **504** can gain access to the IoT device using either or both the default user id and password, it can be determined the IoT device is vulnerable to attacks and hacks. In various implementations, packets communicated between the IoT device probing engine **504** and an IoT device can be used to update event logs, system logs, and access logs, and subsequently IoT device historic data for the IoT device in real-time, for purposes of assessing a risk level of the IoT device.

(84) In a specific implementation, the IoT device probing engine **504** functions to monitor ports of an IoT device to determine device vulnerability for purposes of assessing a risk level of the IoT device. The IoT device probing engine **504** can send packets to an IoT device and observe ports used by the IoT device to receive and transmit data in response to the packets to determine vulnerability of the IoT device. For example, the IoT device probing engine **504** can communicate with an IoT device over an incorrect or less secure port, signifying that the IoT device is vulnerable to attack. Additionally, the IoT device probing engine **504** can probe an IoT device to determine a number of active or inactive ports at the IoT device.

(85) In a specific implementation, the IoT device probing engine **504** functions to communicate with an IoT device in simulating an attack on the IoT device for purposes of assessing a risk level of the IoT device. Manners in which an IoT device responds to a simulation of an attack can be used to determine a vulnerability of the IoT device. For example, if the IoT device probing engine **504** simulates a ping flood, and the IoT device continues to respond to the ping flood, it can be determined that the IoT device is vulnerable to attacks. Vulnerabilities determined based on the IoT device probing engine **504** simulating an attack on an IoT device can be used to assess a risk to an IoT device.

(86) In a specific implementation, the IoT device probing engine **504** functions to actively monitor an IoT device for purposes of assessing a risk level of the IoT device. In actively monitoring an IoT device for purposes of assessing a risk level of the IoT device, the IoT device probing engine **504** functions to send packets to an IoT device to force the IoT device to respond. Traffic sent from an IoT device in response to forcing by the IoT device probing engine **504** can be studied to determine vulnerability of the IoT device. For example, if an IoT device responds with information relating to accessing the IoT device, as determined by an applicable method, such as deep packet inspection, then it can be determined that the IoT device is vulnerable.

(87) In the example of FIG. 5, the IoT device history datastore **506** is intended to represent a datastore that functions to store IoT history data indicating historical records of IoT device operation, for use in assessing IoT device risk levels. IoT history data can be updated in real-time to include event logs, system logs, and access logs. For example, IoT history data stored in the IoT device history datastore **506** can include event logs for an IoT device that are updated in real-time as the IoT device continues to operate. Additionally, IoT history data stored in the IoT device history datastore **506** can be generated using packet analysis. For example, IoT history data stored in the IoT device history datastore **506** can be generated through analysis of headers of data packets sent to and from IoT devices. In another example, IoT history data stored in the IoT device history datastore **506** can be generated from transaction data identified through deep packet inspection of data packets sent to and from IoT devices. IoT history data stored in the IoT device history datastore **506** can also indicate determined vulnerabilities of IoT devices.

(88) In the example of FIG. 5, the vulnerability determination engine **508** is intended to represent an engine that functions to determine vulnerabilities of IoT devices for use in assessing risk levels of the IoT devices. The vulnerability determination engine **508** determines a vulnerability of IoT devices based on analysis of data packets transmitted to and from IoT devices for use in assessing

risk levels of the IoT devices. For example, if an IoT device is transmitting data packets including access credentials for accessing the IoT device, then the vulnerability determination engine **508** can determine the IoT device is vulnerable. Additionally, the vulnerability determination engine **508** can assign a vulnerability score to an IoT device indicating a vulnerability level of the IoT device for use assessing a risk level of the IoT device. The vulnerability determination engine **508** can assign a vulnerability score to an IoT device based on how well an IoT device performs according to vulnerability factors. Vulnerability factors include applicable operational factors for determining how vulnerable an IoT device actually is, e.g. how a device performs in response to an attack, or whether a device is transmitting sensitive data. For example, if an IoT device performs well against a simulated attack but is still transmitting sensitive data, then the vulnerability determination engine **508** can assign the IoT device a vulnerability score of fifty, which can subsequently be used to assess a risk level to the IoT device.

(89) In a specific implementation, the vulnerability determination engine **508** functions to determine a vulnerability of an IoT device for purposes of assessing a risk level of the IoT device based on a response by the IoT device to a simulated attack. In determining a vulnerability of an IoT device based on a response to a simulated attack, the vulnerability determination engine **508** can determine a vulnerability of an IoT device based on a response to the simulated attack by analyzing either or both data packets sent from the IoT device and traffic flow patterns from the IoT device in response to the attack. For example, if an IoT device is subjected to a simulated ping flood attack, the vulnerability determination engine **508** can determine that the IoT device is failing to handle the attack if the IoT device is continually responding to the ping flood attack.

(90) In a specific implementation, the vulnerability determination engine **508** functions to determine a vulnerability of an IoT device for purposes of assessing a risk level of the IoT device by analyzing data traffic forced from the IoT device. Forced traffic analyzed by the vulnerability determination engine **508** can be forced from an IoT device by sending an active packet to the IoT device, thereby forcing the IoT device to respond. The vulnerability determination engine **508** can analyze headers of forced data packets transmitted by an IoT device to determine vulnerability of the IoT device for use in assessing a risk level of the IoT device. Additionally, the vulnerability determination engine **508** can use deep packet inspection to analyze forced data packets transmitted by an IoT device to determine vulnerability of the IoT device for use in assessing a risk level of the IoT device. For example, the vulnerability determination engine **508** can use deep packet inspection to identify transaction data from forced data packets transmitted by an IoT device, and identify events from the transaction data to determine vulnerability of the IoT device for use in assessing a risk level for the IoT device.

(91) In a specific implementation, the vulnerability determination engine **508** functions to determine a vulnerability of an IoT device for use in assessing a risk level for the IoT device based on historical records of IoT devices. Historical records used by the vulnerability determination engine **508** can be updated in real-time to reflect the real-time operation of IoT devices. The vulnerability determination engine **508** can determine vulnerability of an IoT device based on an identification of IoT devices being targeted, as indicated by historical records. For example, the vulnerability determination engine **508** can determine an IoT device is vulnerable if it is a subject of a random scan, as indicated by historical records. Further in the example, whether the IoT device is the subject of a random scan can be determined by the vulnerability determination engine **508** using event logs of IoT devices, as indicated by historical record of the IoT devices.

(92) In a specific implementation, the vulnerability determination engine **508** functions to determine vulnerability of an IoT device for use in assessing a risk level for the IoT device based on determined access credentials of the IoT device. Access credentials of an IoT device can be determined by probing the IoT device with data packets. For example, it can be determined if an IoT device is using default access credentials, e.g. a default user id and password, for providing access to the IoT device by sending data packets utilizing the default access credentials to the IoT

device to gain access. Further, the vulnerability determination engine **508** can determine that an IoT device is vulnerable for purposes of assessing a risk level of the IoT device if it determines the IoT device is granting access through default access credentials.

(93) In an example of operation of the system shown in the example of FIG. 5, the IoT device probing engine **504** probes an IoT device by sending data packets to the IoT device. In the example of operation the vulnerability determination engine **508** determines a vulnerability of the IoT device based on a response of the IoT device to the probing by the IoT device probing engine **504**. Further, in the example of operation of the example system shown in FIG. 5, the IoT device history datastore **506** stores IoT history data indicating historical records of a plurality of IoT devices including the IoT device. In the example of operation of the example system shown in FIG. 5, the vulnerability determination engine **508** determines vulnerability of the IoT device based on the historical records indicated by IoT history data stored in the IoT device history datastore **506**. In the example of operation of the example system shown in FIG. 5, the vulnerability of the IoT device determined by the vulnerability determination engine is used to assess a risk level of the IoT device.

(94) FIG. 6 depicts a diagram **600** of an example of a packet analysis based IoT device profiling system **602**. The packet analysis based IoT device profiling system **602** is intended to represent a system that functions to profile IoT devices based, at least in part, on packet inspection. Device profiles generated by the packet analysis based IoT device profiling system **602** can be used in assessing IoT device risk levels. The packet analysis based IoT device profiling system **602** can be implemented as part of an applicable system for assessing risk levels of IoT devices, such as the IoT device risk assessment systems described in this paper. Device profiles created by the packet analysis based IoT device profiling system **602** can be used in assessing risk levels of IoT devices. Device profiles of IoT devices created by the packet analysis based IoT device profiling system **602** can be used to assess risk levels of IoT devices by an outside/third party IoT management entity.

(95) In a specific implementation, the packet analysis based IoT device profiling system **602** functions to be implemented, at least in part, at a location local with respect to IoT devices. The packet analysis based IoT device profiling system **602** can be implemented, at least in part, at a local location with respect to IoT devices profiled by the packet analysis based IoT device profiling system **602**. For example, the packet analysis based IoT device profiling system **602** can be implemented, at least in part, at a local appliance coupled to IoT devices. Alternatively, in another implementation, the packet analysis based IoT device profiling system **602** can profile devices at a remote location with respect to IoT devices, e.g. the cloud.

(96) The packet analysis based IoT device profiling system **602** shown in the example of FIG. 6 includes an IoT history datastore **604**, an IoT device clustering engine **606**, an IoT device profiling engine **608**, and a device profile datastore **610**. The IoT history datastore **604** is intended to represent a datastore that functions to store IoT history data, such as the IoT history datastores described in this paper. IoT history data stored in the IoT history datastore **604** can be updated in real-time to include event logs, system logs, and access logs. For example, IoT history data stored in the IoT history datastore **604** can include event logs for an IoT device that are updated in real-time as the IoT device continues to operate. In various implementations, IoT history data stored in the IoT history datastore **604** can be generated using packet analysis. For example, IoT history data stored in the IoT history datastore **604** can be generated through packet analysis, e.g. analyzing headers of data packets sent to and from IoT devices. Additionally, IoT history data stored in the IoT history datastore **604** can be generated through deep packet inspection of data packets sent to and from IoT devices. For example, IoT history data stored in the IoT history datastore **604** can be generated from transaction data identified through deep packet inspection of data packets sent to and from IoT devices. IoT history data stored in the IoT history datastore **604** can be used in assessing risk levels of IoT devices.

(97) In the example of FIG. 6, the IoT device clustering engine **606** is intended to represent an

engine that functions to cluster IoT devices for purposes of profiling the IoT devices for use in assessing risk levels of IoT devices. In clustering IoT devices, the IoT device clustering engine **606** can aid a profiling mechanism in creating a detailed profile for IoT devices. The IoT device clustering engine **606** can cluster IoT devices based on clustering factors. Clustering factors include applicable factors related to characteristics of IoT devices and characteristics of operation of IoT devices for use in grouping IoT devices. Example clustering factors include device types, attributes of IoT devices, functionalities of IoT device, operating systems and applications executing at or capable of being executed at IoT devices, entities associated with IoT devices, users who interact with IoT devices, and hosts and devices with which the IoT devices communicate. For example, the IoT device clustering engine **606** can cluster IoT devices accessing network services through a home LAN into a single cluster.

(98) In a specific implementation, the IoT device clustering engine **606** functions to receive new clustering factors and subsequently cluster the devices according to the new clustering factors for use in assessing risk levels of IoT devices. For example, the IoT device clustering engine **606** can receive information indicating either or both a new IoT device and IoT device type and subsequently cluster IoT devices according to either or both the new IoT device and IoT device type. In clustering IoT devices according to new clustering factors, the IoT device clustering engine **606** can provide an interface through which an applicable entity, e.g. an administrator, can manually input the new clustering factors.

(99) In the example of FIG. **6**, the IoT device profiling engine **608** is intended to represent an engine that functions to generate device profiles for IoT devices for use in assessing risk levels of IoT devices. The IoT device profiling engine **608** can create profiles for a specific IoT device or for a cluster of IoT devices. For example, the IoT device profiling engine **608** can create a profile for a single IoT device accessing services through a specific LAN and for a plurality of IoT devices accessing network services through the LAN. A device profile generated by the IoT device profiling engine **608** can include a device map. A device map includes a map showing systems and devices with which an IoT device communicates. For example, a device map can include other IoT devices with which an IoT device communicates. In another example, a device map can include hosts an IoT device is communicating with through the Internet. Additionally, the IoT device profiling engine **608** can generate profiles for IoT devices that are specific to a time of year. For example, the IoT device profiling engine **608** can model profiles of a thermostat for summer and winter months based on changing operation of the thermostat during summer and winter months. The IoT device profiling engine **608** can use machine learning to improve its models used in profiling devices over time as it continues to profile IoT device.

(100) In a specific implementation, the IoT device profiling engine **608** functions to generate device profiles for IoT devices that include instances of the IoT devices for use in assessing risk levels of IoT devices. For example, if at a specific time an IoT device is communicating externally with a remote host as part of an inbound communication session, then the IoT device profiling engine **608** can create an instance for the IoT device, included as part of a device profile, to indicate the IoT device was communicating externally with the remote host as part of the inbound communication session at the specific time. In another example, if at a specific time an IoT device is utilizing a specific number of ports in accessing network services, then the IoT device profiling engine **608** can create an instance for the IoT device, included as part of a device profile, to indicate the IoT device was utilizing the specific number of ports at the specific time to access network services.

(101) In a specific implementation, the IoT device profiling engine **608** functions to generate IoT device profiles based, at least in part, on IoT historical records for use in assessing risk levels of IoT devices. In generating device profiles based on IoT historical records, the IoT device profiling engine **608** can generate an IoT device profile based, at least in part, on an event log included as part of IoT historical records. For example, the IoT device profiling engine **608** can generate an IoT

device profile, using an event log, to indicate how an IoT device operates. Additionally, in generating device profiles based on IoT historical records, the IoT device profiling engine **608** can generate an IoT device profile based, at least in part, on an access log included as part of IoT historical records. For example, the IoT device profiling engine **608** can generate an IoT device profile, using an access log, to indicate how a specific user interacts with an IoT device as part of operation of the IoT device. Further, in generating device profiles based on IoT historical records, the IoT device profiling engine **608** can generate an IoT device profile based, at least in part, on a system log included as part of IoT historical records. For example, the IoT device profiling engine **608** can generate an IoT device profile, using a system log, to indicate an identification of an IoT device and applications executing at the IoT device.

(102) In a specific implementation, the IoT device profiling engine **608** can generate IoT device profiles based, at least in part, on determined vulnerabilities of IoT devices for use in assessing risk levels of IoT devices. The IoT device profiling engine **608** can generate IoT device profiles based, at least in part, on vulnerabilities of IoT devices determined by an applicable system for determining IoT device vulnerabilities, such as the packet analysis based IoT device vulnerability determination systems described in this paper. In generating device profiles based on determined vulnerabilities of IoT devices, the IoT device profiling engine **608** can generate IoT device profiles based on vulnerabilities determined from active probing of IoT devices. For example, if an IoT device performs poorly in response to a simulated attack, then the IoT device profiling engine **608** can generate a device profile for the IoT device indicating that the IoT device is vulnerable to the attack. Additionally, the IoT device profiling engine **608** can generate IoT device profiles based on determined vulnerabilities of IoT devices using historical records of the IoT devices. For example, if historical records, e.g. event logs, indicate that an IoT device is the subject of a random scanning by a user, then the IoT device profiling engine **608** can generate an IoT device profile for the IoT device indicating that it has been the subject of random scanning, and thus vulnerable.

(103) In a specific implementation, the IoT device profiling engine **608** can model regular IoT device behaviors, as included as part of device profiles of the IoT devices, for use in assessing risk levels of IoT devices. The IoT device profiling engine **608** can model regular IoT device behavior of IoT devices based on historical records of IoT devices. An example of the IoT device profiling engine **608** modeling regular IoT device behavior is if a thermostat raises the temperature at five in the evening every day, as indicated by an events log for the thermostat, then the IoT device profiling engine **608** can model regular IoT device behavior of the IoT device to indicate raising of the temperature at five in the evening every day. The IoT device profiling engine **608** can model regular IoT device behavior of an IoT device specific to a user. For example, if a user interacts with a device in a similar fashion repeatedly, then the IoT device profiling engine **608** can model a regular IoT device behavior specific to the user to indicate the repeated interactions between the user and the IoT device.

(104) In a specific implementation, the IoT device profiling engine **608** functions to provide device profiles to an interface for presentation. The IoT device profiling engine **608** can provide the device profiles to an interface in a format that is readable to a human. For example, the IoT device profiling engine **608** can provide device maps illustrating hosts and devices an IoT device interacts with in a format a human is capable of reading or otherwise perceiving.

(105) In a specific implementation, the IoT device profiling engine **608** functions to map an IoT device to a new device profile or otherwise create a new device profile for an IoT device. The IoT device profiling engine **608** can match an IoT device to a new device profile or otherwise create a new device profile for the IoT device based on deviations from regular device behavior in operation of the IoT device. For example, if an IoT device continues to deviate further away from regular device behavior, then the IoT device profiling engine can map the IoT device to a new device profile or otherwise create a new device profile for the IoT device.

(106) In a specific implementation, the IoT device profiling engine **608** can match an IoT device to

a new device profile or otherwise create a new device profile for the IoT device based on instances of the IoT device. In matching an IoT device to a new device profile based on instances of the IoT device, the IoT device profiling engine **608** can determine whether to actually match the IoT device to a new device profile using the instances of the IoT device. For example, if instances of an IoT device indicate the IoT device is continuing to deviate from regular IoT device behavior of the IoT device, then the IoT device profiling engine **608** can determine to match the IoT device to a new device profile or create a new device profile for the IoT device. Additionally, in matching an IoT device to a new device profile based on instances of the IoT device, the IoT device profiling engine **608** can determine a new device profile to match to the IoT device or otherwise create for the new IoT device. For example, if an instance of an IoT device indicates an IoT device is of a specific type, then the IoT device profiling engine **608** can match the IoT device to an IoT device profile of an IoT device of the same type. In another example, the IoT device profiling engine **608** can generate a new IoT device profile for an IoT device based on characteristics of the IoT device, as indicated by instances, before the IoT device began to deviate from regular IoT device behavior. (107) In the example of FIG. **6**, the device profile datastore **610** is intended to represent a datastore that functions to store device profile data indicating device profiles of IoT devices for use in assessing risk levels of IoT devices. Device profiles indicated by device profile data stored in the device profile datastore **610** can be generated from historical records of IoT devices. Device profile data stored in the device profile datastore **610** can include device profiles indicating one or an applicable combination of instances of IoT devices, vulnerabilities of IoT devices, device maps of IoT devices, and regular IoT device behaviors.

(108) In an example of operation of the system shown in the example of FIG. **6**, the IoT history datastore **604** stores IoT history data indicating historical records of IoT devices. In the example of operation of the example system shown in FIG. **6**, the IoT device clustering engine **606** clusters IoT devices into clusters based on the historical records of the IoT devices indicated by IoT history data stored in the IoT history datastore **604**. Further, in the example of operation of the example system shown in FIG. **6**, the IoT device profiling engine **608** profiles the IoT devices according to the clusters into device profiles using the historical records of the IoT devices indicated by IoT history data stored in the IoT history datastore **604**. In the example of operation of the example system shown in FIG. **6**, the device profile datastore stores device profile data indicating device profiles determined by the IoT device profiling engine **608**. Additionally, in the example of operation of the example system shown in FIG. **6**, device profiles indicated by device profile data stored in the device profile datastore **610** are used in assessing risk levels of IoT devices.

(109) FIG. **7** depicts a diagram **700** of an example of a packet analysis based IoT device risk assessment system **702**. The packet analysis based IoT device risk assessment system **702** can be implemented as part of an applicable system for assessing risk levels of IoT devices, such as the IoT device risk assessment systems described in this paper. The packet analysis based IoT device risk assessment system **702** is intended to represent a system that functions to assess risk levels of IoT devices. The packet analysis based IoT device risk assessment system **702** can determine risk levels of IoT devices based on characteristics of IoT devices, as indicated by IoT device profiles. Specifically, the packet analysis based IoT device risk assessment system **702** can determine risk levels of IoT devices based on characteristics of an IoT device itself and characteristics of an IoT device in operation. For example, the Packet analysis based IoT device risk assessment system **702** can determine a risk level of an IoT device based on a device type of the IoT device. In another example, the packet analysis based IoT device risk assessment system **702** can determine a risk level of an IoT device based on characteristics of the IoT device in accessing network services, as indicated through inspection of data packets transmitted to and from the IoT device as part of the IoT device accessing network services.

(110) In a specific implementation, the packet analysis based IoT device risk assessment system **702** functions to analyze risk factors of IoT devices using device profiles to assess risk levels of IoT

devices. In analyzing risk factors of IoT devices to using device profiles to assess risk levels of IoT devices, the packet analysis based IoT device risk assessment system **702** can apply assessment weights IoT device risk factors of IoT devices, as indicated by corresponding device profiles. For example, if an IoT device is of a specific type and is communicating using a specific number of ports, then the packet analysis based IoT device risk assessment system **702** can apply assessment weights to the factors indicating the IoT device is of a specific type and is communicating using a specific number of ports to determine a risk level of the IoT device. In another example, if an IoT device is communicating externally with a remote host through an inbound communication session, then the packet analysis based IoT device risk assessment system **702**, can apply assessment weights to the factors that the device is communicating externally with a remote host through an inbound communication session to determine a risk level of the IoT device.

(111) The example packet analysis based IoT device risk assessment system **702** shown in the example of FIG. 7 includes an assessment weight variance management engine **704**, an assessment weight datastore **706**, a device profile datastore **708**, an IoT device behavior deviation determination engine **710**, an IoT device risk factor analysis engine **712**, a risk assessment datastore **714**, and an IoT device risk presentation engine **716**. The assessment weight variance management engine **704** is intended to represent an engine that functions to manage assessment weights for application to IoT device risk factors in assessing IoT device risk levels. In managing assessment weights, the assessment weight variance management engine **704** can assign specific assessment weights to specific risk factors. For example, the assessment weight variance management engine **704** can assign an assessment weight of 10% to IoT device risk factors related to protocols used by an IoT device in accessing network services. The assessment weight variance management engine **704** can assign specific assessment weights to specific risk factors at varying levels of granularity. Specifically, the assessment weight variance management engine **704** can assign specific assessment weights to specific risk factors on one or an applicable combination of a per-device basis, a per-device type basis, a per-network basis, or other applicable per-IoT device characteristic basis. For example, the assessment weight variance management engine **704** can assign the same specific assessment weights to specific risk factors for a single IoT device or for all IoT devices of the same type. In another example, the assessment weight variance management engine **704** can assign the same specific assessment weights to IoT devices accessing network services through a specific LAN.

(112) In a specific implementation, the assessment weight variance management engine **704** functions to assign specific assessment weights to IoT device risk factors based on characteristics of a network. In assigning specific assessment weights to IoT device risk factors based on characteristics of a network, assessment weights assigned to specific risk factors can vary between IoT devices. Specifically, assessment weights assigned to specific risk factors by the assessment weight variance management engine **704** can vary between IoT device, IoT devices of different types, IoT devices accessing network services through different networks, and IoT devices distinguished from each other based on an applicable IoT device characteristic, e.g. a characteristic of the IoT device itself or a characteristics of the IoT device in operation. For example, an IoT device communicating externally with a remote host can have a different assessment weight assigned to risk related to network communication characteristics than another IoT device communicating internally with a local IoT device through a LAN.

(113) In a specific implementation, the assessment weight variance management engine **704** functions to set assessment weights based on characteristics of a user associated with IoT devices or input from a user associated with IoT devices. In adjusting assessment weights based on input of a user, the assessment weight variance management engine **704** can set assessment weights according to the input received from the user. For example, a user can specify setting adjustment weights for IoT device risk factors related to network activeness to 50%, and the assessment weight variance management engine **704** can subsequently set adjustment weights applied to IoT device

risk factors related to network activeness at 50%. Further, in adjusting assessment weights based on characteristics of a user, the assessment weight variance management engine **704** can set adjustment weights based on tolerances of a user; such tolerances of the user can be intentional or unintentional.

(114) In the example of FIG. 7, the assessment weight datastore **706** is intended to represent a datastore that functions to store assessment weight data. Assessment weight data stored in the assessment weight datastore **706** includes applicable data used in applying assessment weights to IoT device risk factors of IoT devices for assessing risk levels of the IoT devices. Example assessment weight data stored in the assessment weight datastore **706** can indicate specific assessment weights to apply to specific risk factors of specific IoT devices. For example, assessment weight data stored in the assessment weight datastore **706** can indicate applying an assessment weight of 20% to IoT device risk factors related to network communication characteristics of IoT devices accessing network services through a specific LAN. In another example, assessment weight data stored in the assessment weight datastore **706** can indicate applying an assessment weight of 50% to IoT device risk factors related to operation performance deviations of IoT devices of a specific type.

(115) In the example of FIG. 7, the device profile datastore **708** is intended to represent a datastore that functions to store data associated with device profiles. Device profile data stored in the device profile datastore **708** can be used to assess risk levels of IoT devices. For example, device profiles represented by device profile data stored in the device profile datastore **708** can include or otherwise be used to extract specific risk factors of IoT devices to which assessment weights can be applied for determining risk levels of IoT devices.

(116) In the example of FIG. 7, the IoT device behavior deviation determination engine **710** is intended to represent an engine that functions to determine operational performance deviations of an IoT device with respect to regular IoT device behaviors. In determining operational performance deviations of an IoT device, the IoT device behavior deviation determination engine **710** can determine if an IoT device is deviating in operation with respect to a regular IoT device behaviors and how an IoT device is operating to deviate from the regular IoT device behaviors. For example, the IoT device behavior deviation determination engine **710** can determine an IoT device is actually deviating from regular IoT device behaviors if it begins communicating with a new external host. Further in the example, the IoT device behavior deviation determination engine **710** can determine how the IoT device is deviating from the regular IoT device behaviors by determining the IoT device is communicating with the new external host.

(117) In a specific implementation, the IoT device behavior deviation determination engine **710** can determine operational performance deviations of an IoT device using device profiles. In determining operational performance deviations of an IoT device using device profiles, the IoT device behavior deviation determination engine **710** can determine the operational performance deviations of the IoT device by comparing or tracking instances of an IoT device, included as part of a device profile of the IoT device. For example, if previous instances of an IoT device indicate an IoT device was operating in a specific way, and current instances of the IoT device indicate the IoT device is continuing to operate in a different way, then the IoT device behavior deviation determination engine **710** can determine the IoT device is deviating in operation from regular IoT device behavior. Additionally, in determining operational performance deviations of an IoT device using device profiles, the IoT device behavior deviation determination engine **710** can determine the operational performance deviations based on device profiles of different devices. For example, if a device profiles of IoT devices within a LAN indicate the IoT devices are operating in a specific way, and a device profile of another IoT device within the LAN indicates the another IoT device is operating in a different way, then the IoT device behavior deviation determination engine **710** can determine the another device is deviating in operating according to regular IoT device behaviors.

(118) In the example of FIG. 7, the IoT device risk factor analysis engine **712** is intended to

represent an engine that functions to determine risk levels of IoT devices. In determining risk levels of IoT devices, the IoT device risk factor analysis engine **712** can apply assessment weights to IoT device risk factors. Further, in determining risk levels of IoT devices, the IoT device risk factor analysis engine **712** can apply assessment weights to IoT device risk factors to assess a risk score for the IoT devices and subsequently use the determined risk scores to categorize the IoT devices into different risk levels. For example the IoT device risk factor analysis engine **712** can apply an assessment weight of 20% to IoT device risk factors related to applications used by an IoT device in accessing network services to determine a risk score of 80 the IoT device. Further in the example, the IoT device risk factor analysis engine **712** can assess a risk level of high risk to the IoT device based on the determined risk score of 80.

(119) In a specific implementation, the IoT device risk factor analysis engine **712** functions to select specific assessment weights to apply in determining risk levels of IoT devices. The IoT device risk factor analysis engine **712** can select specific assessment weights to apply using assessment weight data. For example if assessment weight data indicates to apply specific assessment weights to specific IoT device risk factors for use in determining risk levels of specific IoT devices, then the IoT device risk factor analysis engine **712** can specify the specific assessment weights for application to the specific IoT device risk factors.

(120) In a specific implementation, the IoT device risk factor analysis engine **712** functions to extract or otherwise determine IoT device risk factors to apply assessment weights to in assessing risk levels of IoT devices. The IoT device risk factor analysis engine **712** can extract IoT device risk factors to apply assessment weights to using device profiles of IoT devices. For example, if an instance included in a device profile indicates an IoT device is communicating using four ports, then the IoT device risk factor analysis engine **712** can determine that the IoT device is communicating using four ports as part of extracting IoT device risk factors for the IoT device. Additionally, the IoT device risk factor analysis engine **712** can extract IoT device risk factors using determined operational performance deviations. For example, if operational performance deviations indicate an IoT device is greatly deviating from operating according to regular IoT device behavior, then the IoT device risk factor analysis engine **712** can determine that the IoT device is greatly deviating in operation as part of extracting IoT device risk factors related to operation performance deviation of the IoT device. As operational performance deviations can be determined from device profiles, in extracting IoT device risk factors from determined operational performance deviations, the IoT device risk factor analysis engine **712** can function to extract risk factors from device profiles when extracting risk factors from determined operational performance deviations. The IoT device risk factor analysis engine **712** can apply assessment weights to extracted IoT device risk factors for determining a risk score for the IoT device.

(121) In the example of FIG. 7, the risk assessment datastore **714** is intended to represent a datastore that functions to store risk assessment data. Risk assessment data stored in the risk assessment datastore **714** can include one or an applicable combination of extracted IoT device risk factors of IoT devices, assessment weights used in generating risk scores of IoT devices, actual assessed risk scores of IoT devices, and actual assess risk levels of IoT devices. Risk assessment data stored in the risk assessment datastore **714** can be presented to a user associated with IoT devices for use in monitoring security in a network including IoT devices.

(122) In the example of FIG. 7, the IoT device risk presentation engine **716** is intended to represent an engine that functions to present or otherwise facilitate presentation of risk assessment data to a user. In presenting risk assessment data to a user, the IoT device risk presentation engine **716** can determine specific risk assessment data to present to a user and subsequently present the specific risk assessment data to the user. For example, if user preferences indicate a user only wants to see assessed risk levels of their IoT devices, then the IoT device risk presentation engine **716** can only present the assessed risk levels of the IoT devices to the user. Further, in presenting risk assessment data to a user, the IoT device risk presentation engine **716**, can determine when to present risk

assessment data to a user. For example, the IoT device risk presentation engine **716** can determine to present risk assessment data to a user when a number of IoT devices greater than a threshold number have been assessed a high risk level.

(123) In an example of operation of the system shown in the example of FIG. 7, the assessment weight variance management engine **704** updates assessment weight data stored in the assessment weight datastore **706** to indicate specific assessment weights to apply to specific IoT device risk factors based on a network. In the example of operation of the example system shown in FIG. 7, the device profile datastore **708** stores device profile data indicating device profiles of IoT devices. Further, in the example of operation of the example system shown in FIG. 7, the IoT device behavior deviation determination engine **710** determines operational performance deviations of the IoT devices from a regular IoT device behavior based on the device profile data stored in the device profile datastore **708**.

(124) In the example of operation of the system shown in the example of FIG. 7, the IoT device risk factor analysis engine extracts IoT device risk factors based on device profile data stored in the device profile datastore **708** and selects specific assessment weights to apply to the extracted IoT device risk factors using the assessment weight data stored in the assessment weight datastore **706**. Additionally, in the example of operation of the example system shown in FIG. 7 the IoT device risk factor analysis engine **712** assess risk levels of the IoT devices by applying the specific assessment weights to the extracted IoT device risk factors. In the example of operation of the example system shown in FIG. 7, the IoT device risk factor analysis engine **712** updates risk assessment data stored in the risk assessment datastore **714** to indicate the assessed risk levels of the IoT devices. Additionally, in the example of operation of the example system shown in FIG. 7, the IoT device risk presentation engine **716** presents risk assessment data stored in the risk assessment datastore **714**, including the assessed risk levels of the IoT devices to a user associated with the IoT devices.

(125) FIG. 8 depicts a diagram **800** of an example of a system for assessing risk levels of IoT devices. The system shown in the example of FIG. 8 includes a local network **802**, a cloud **804**, and a third party cloud **806**. The local network **802** is intended to represent a network formed by at least one IoT device and a local appliance.

(126) In the example of FIG. 8, the local network **802** includes an IoT device risk assessment system **808**. The IoT device risk assessment system **808** is intended to represent a system that functions to analyze data packets for managing assessment of risk levels of IoT devices, such as the IoT device risk assessment systems described in this paper.

(127) The IoT device risk assessment system **808** includes applicable systems for managing event logs, access logs, and system logs of IoT devices through packet analysis, such as the packet analysis based access log management systems, the packet analysis based system log management systems, and packet analysis based event log management systems described in this paper. In the example system shown in FIG. 8, the applicable systems of the IoT device risk assessment system **808** for managing event logs, access logs, and system logs of IoT devices through packet analysis are implemented at the local network **802** as part of a local appliance. In being implemented as part of a local appliance, the IoT device risk assessment system **808** can analyze packets locally for purposes of maintaining access logs, system logs, and event logs for use in assessing risk levels of IoT devices.

(128) In the example system shown in FIG. 8, the cloud **804** includes a packet analysis based IoT device profiling system **810** and a packet analysis based IoT device risk assessment system **812**. The packet analysis based IoT device profiling system **810** is intended to represent a system that functions to maintain IoT device profiles for use in assessing risk levels of IoT devices, such as the packet analysis based IoT device profiling systems described in this paper. The packet analysis based IoT device risk assessment system **812** is intended to represent a system that functions to apply assessment weights to IoT device risk factors extracted from device profiles for purposes of

assessing risk levels of IoT devices, such as the packet analysis based IoT device risk assessment systems described in this paper. Additionally, the cloud **804** can include an applicable system for determining IoT device vulnerabilities, such as the packet based IoT device vulnerability determination systems described in this paper. The cloud **804** can be specific to a private entity. The packet analysis based IoT device profiling system **810** can receive one or an applicable combination of event logs, access logs, and system logs in real-time as they are updated, through VPN tunnels from the IoT device risk assessment system **808** implemented at the local network **802**. The packet analysis based IoT device profiling system **810** can use one or an applicable combination of received event logs, access logs, and system logs to profile IoT device into device profiles.

(129) In the example system shown in FIG. **8**, the third party cloud **806** is intended to represent a cloud that receives device profile data indicating device profiles of IoT devices through VPN tunnels. The third party cloud **806** receives profile data indicating device profiles of IoT devices through VPN tunnels from the packet analysis based IoT device profiling system **810** implemented at the cloud **804**. Additionally, the third party cloud **806** can receive risk assessment data through VPN tunnels from the packet analysis based IoT device risk assessment system **812**. The third party cloud **806** can be associated with or used by a third party management system for managing IoT devices.

(130) FIG. **9** depicts a diagram **900** of another example of a system for assessing risk levels of IoT devices. The system shown in the example of FIG. **9** includes a local network **902**, a third party cloud **904**, and a cloud **906**. The local network **902** is intended to represent a network formed by at least one IoT device and a local appliance. The local network **902** includes an IoT device risk assessment system **908**. The IoT device risk assessment system **908** is intended to represent a system that functions according to an applicable system for managing assessment of risk levels of IoT devices, such as the IoT device risk assessment systems described in this paper.

(131) In a specific implementation, the IoT device risk assessment system **908** includes applicable systems for managing event logs, access logs, and system logs of IoT devices through packet analysis, such as the packet analysis based access log management systems, the packet analysis based system log management systems, and packet analysis based event log management systems described in this paper. In the example system shown in FIG. **9**, the applicable systems of the IoT device risk assessment system **908** for managing event logs, access logs, and system logs of IoT devices through packet analysis are implemented at the local network **902** as part of a local appliance. In being implemented as part of a local appliance, the IoT device risk assessment system **908** can analyze packets locally for purposes of maintaining access logs, system logs, and event logs for use in assessing risk levels of IoT devices.

(132) In the system shown in the example of FIG. **9**, the third party cloud **904** receives applicable data for profiling IoT devices for use in assessing risk levels of IoT devices, such as one or an applicable combination of event logs, access logs, and system logs through VPN tunnels from the IoT device risk assessment system **908** implemented at the local network **902**. The third party cloud **904** can be associated with or used by a third party management system for managing IoT devices.

(133) In the example system shown in FIG. **9**, the cloud **906** includes a packet analysis based IoT device profiling system **910** and a packet analysis based IoT device risk assessment system **912**. The packet analysis based IoT device profiling system **910** is intended to represent a system that functions to maintain IoT device profiles for use in assessing risk levels of IoT devices, such as the packet analysis based IoT device profiling systems described in this paper. The packet analysis based IoT device risk assessment system **912** is intended to represent a system that functions to apply assessment weights to IoT device risk factors extracted from device profiles for purposes of assessing risk levels of IoT devices, such as the packet analysis based IoT device risk assessment systems described in this paper. Additionally, the cloud **906** can include an applicable system for determining IoT device vulnerabilities, such as the packet based IoT device vulnerability

determination systems described in this paper. The packet analysis based IoT device profiling system **910** can receive one or an applicable combination of event logs, access logs, and system logs in real-time as they are updated, through VPN tunnels from the third party cloud **904**, which are received at the third party cloud **904** from the IoT device risk assessment system **908** implemented at the local network **902**.

(134) In a specific implementation, the packet analysis based IoT device profiling system **910** uses one or an applicable combination of received event logs, access logs, and system logs to profile IoT device into device profiles. The packet analysis based IoT device risk assessment system **912** can use device profiles managed by the packet analysis based IoT device profiling system **910** to assess risk levels of IoT devices. The packet analysis based IoT device profiling system **910** can send generated device profiles back to the third party cloud **904** through VPN tunnels. The packet analysis based IoT device risk assessment system **912** can send generated risk assessment data back to the third party cloud **904** through VPN tunnels. The third party cloud **904** can use either or both device profiles received from the packet analysis based IoT device profiling system **910** and risk assessment data received from the packet analysis based IoT device risk assessment system **912** to manage IoT devices in the local network **902**.

(135) FIG. **10** depicts a diagram **1000** of an example of another system for assessing risk levels of IoT devices. The system shown in the example of FIG. **10** includes a local network **1002**, a cloud **1004**, and a third party cloud **1006**. The local network **1002** is intended to represent a network formed by at least one IoT device and a local appliance. The local network **1002** includes an IoT device risk assessment system **1008**. The IoT device risk assessment system **1008** is intended to represent a system that functions to analyze data packets for managing assessment of risk levels of IoT devices, such as the IoT device risk assessment systems described in this paper.

(136) In a specific implementation, the IoT device risk assessment system **1008** includes applicable systems for managing event logs, access logs, and system logs of IoT devices through packet analysis, such as the packet analysis based access log management systems, the packet analysis based system log management systems, and packet analysis based event log management systems described in this paper. In the example system shown in FIG. **10**, the applicable systems of the IoT device risk assessment system **1008** for managing event logs, access logs, and system logs of IoT devices through packet analysis are implemented at the local network **1002** as part of a local appliance. In being implemented as part of a local appliance, the IoT device risk assessment system **1008** can analyze packets locally for purposes of maintaining access logs, system logs, and event logs for use in assessing risk levels of IoT devices.

(137) In the example system shown in FIG. **10**, the cloud **1004** includes a packet analysis based IoT device profiling system **1010** and a packet analysis based IoT device risk assessment system **1012**. The packet analysis based IoT device profiling system **1010** is intended to represent a system that functions to maintain IoT device profiles for use in assessing risk levels of IoT devices, such as the packet analysis based IoT device profiling systems described in this paper. The packet analysis based IoT device risk assessment system **1012** is intended to represent a system that functions to apply assessment weights to IoT device risk factors extracted from device profiles for purposes of assessing risk levels of IoT devices, such as the packet analysis based IoT device risk assessment systems described in this paper. Additionally, the cloud **1004** can include an applicable system for determining IoT device vulnerabilities, such as the packet based IoT device vulnerability determination systems described in this paper. The cloud **1004** can be specific to a private entity. The packet analysis based IoT device profiling system **1010** can receive one or an applicable combination of event logs, access logs, and system logs in real-time as they are updated, through traditional network channels, e.g. using protocols of a network through which the data is being transmitted without the use of VPN tunneling, from the IoT device risk assessment system **1008** implemented at the local network **1002**. The packet analysis based IoT device profiling system **1010** can use one or an applicable combination of received event logs, access logs, and system logs

to profile IoT device into device profiles.

(138) In the system shown in the example of FIG. **10**, the third party cloud **1006** is intended to represent a network that receives device profile data indicating device profiles of IoT devices without the use of VPN tunnels. The third party cloud **1006** receives profile data indicating device profiles of IoT devices, through traditional network channels, e.g. using protocols of a network through which the data is being transmitted without the use of VPN tunneling, from the packet analysis based IoT device profiling system **1010** implemented at the cloud **1004**. Additionally, the third party cloud **1006** can receive risk assessment data, through traditional network channels, e.g. using protocols of a network through which the data is being transmitted without the use of VPN tunneling, from the packet analysis based IoT device risk assessment system **1012**. The third party cloud **1006** can be associated with or used by a third party management system for managing IoT devices.

(139) FIG. **11** depicts a diagram **1100** of another example of a system for assessing risk levels of IoT devices. The example system shown in FIG. **11** includes a local network **1102**, a third party cloud **1104**, and a cloud **1106**. The local network **1102** is intended to represent a network that is formed by at least one IoT device and a local appliance. The local network **1102** includes an IoT device risk assessment system **1108**.

(140) In the example of FIG. **11**, the IoT device risk assessment system **1108** is intended to represent a system that functions to manage assessment of risk levels of IoT devices. The IoT device risk assessment system **1108** includes applicable systems for managing event logs, access logs, and system logs of IoT devices through packet analysis, such as the packet analysis based access log management systems, the packet analysis based system log management systems, and packet analysis based event log management systems described in this paper. In the example system shown in FIG. **11**, the applicable systems of the IoT device risk assessment system **1108** for managing event logs, access logs, and system logs of IoT devices through packet analysis are implemented at the local network **1102** as part of a local appliance. In being implemented as part of a local appliance, the IoT device risk assessment system **1108** can analyze packets locally for purposes of maintaining access logs, system logs, and event logs for use in assessing risk levels of IoT devices.

(141) In the system shown in the example of FIG. **11**, the third party cloud **1104** is intended to represent a network that receives applicable data for profiling IoT devices for use in assessing risk levels of IoT devices, such as one or an applicable combination of event logs, access logs, and system logs, through traditional network channels, e.g. using protocols of a network through which the data is being transmitted without the use of VPN tunneling, from the IoT device risk assessment system **1108** implemented at the local network **1102**. The third party cloud **1104** can be associated with or used by a third party management system for managing IoT devices.

(142) In the system shown in the example of FIG. **11**, the cloud **1106** includes a packet analysis based IoT device profiling system **1110** and a packet analysis based IoT device risk assessment system **1112**. The packet analysis based IoT device profiling system **1110** is intended to represent a system that functions to maintain IoT device profiles for use in assessing risk levels of IoT devices, such as the packet analysis based IoT device profiling systems described in this paper. The packet analysis based IoT device risk assessment system **1112** is intended to represent a system that functions to apply assessment weights to IoT device risk factors extracted from device profiles for purposes of assessing risk levels of IoT devices, such as the packet analysis based IoT device risk assessment systems described in this paper. Additionally, the cloud **1106** can include an applicable system for determining IoT device vulnerabilities, such as the packet based IoT device vulnerability determination systems described in this paper. The packet analysis based IoT device profiling system **1110** can receive an applicable combination of event logs, access logs, and system logs in real-time as they are updated, through traditional network channels, e.g. using protocols of a network through which the data is being transmitted without the use of VPN tunneling, from the

third party cloud **1104**, which are received at the third party cloud **1104** from the IoT device risk assessment system **1108** implemented at the local network **1102**.

(143) In a specific implementation, the packet analysis based IoT device profiling system **1110** uses one or an applicable combination of received event logs, access logs, and system logs to profile IoT device into device profiles. The packet analysis based IoT device risk assessment system **1112** can use device profiles managed by the packet analysis based IoT device profiling system **1110** to assess risk levels of IoT devices. The packet analysis based IoT device profiling system **1110** can send generated device profiles back to the third party cloud **1104**, through traditional network channels, e.g. using protocols of a network through which the data is being transmitted without the use of VPN tunneling. The packet analysis based IoT device risk assessment system **1112** can send generated risk assessment data back to the third party cloud **1104** through, through traditional network channels, e.g. using protocols of a network through which the data is being transmitted without the use of VPN tunneling. The third party cloud **1104** can use either or both device profiles received from the packet analysis based IoT device profiling system **1110** and risk assessment data received from the packet analysis based IoT device risk assessment system **1112** to manage IoT devices in the local network **1104**.

(144) FIG. **12** depicts a diagram **1200** of another example of a system for assessing risk levels of IoT devices. The system shown in the example of FIG. **12** includes a local network **1202** and a third party cloud **1204**. The local network **1202** includes an IoT device risk assessment system **1206**. The IoT device risk assessment system **1206** is intended to represent a system that functions according to an applicable system for analyzing data packets for managing assessment of risk levels of IoT devices, such as the IoT device risk assessment systems described in this paper.

(145) In a specific implementation, the IoT device risk assessment system **1206** includes applicable systems for managing event logs, access logs, and system logs of IoT devices through packet analysis, such as the packet analysis based access log management systems, the packet analysis based log management systems, and packet analysis based event log management systems described in this paper. In the system shown in the example of FIG. **12**, the applicable systems of the IoT device risk assessment system **1206** for managing event logs, access logs, and system logs of IoT devices through packet analysis are implemented at the local network **1202** as part of a local appliance. In being implemented as part of a local appliance, the IoT device risk assessment system **1206** can analyze packets locally for purposes of maintaining access logs, system logs, and event logs.

(146) In the system shown in the example of FIG. **12**, the third party cloud **1204** includes a packet analysis based IoT device profiling system **1208** and a packet analysis based IoT device risk assessment system **1210**. Depending upon implementation-specific or other considerations, the third party cloud **1204** can include an applicable system for determining IoT device vulnerabilities, such as the packet based IoT device vulnerability determination systems described in this paper. The third party cloud **1204** can be associated with or used by a third party management system for managing IoT devices. The packet analysis based IoT device profiling system **1208** is intended to represent a system that functions to profile IoT devices for purposes of assessing risk levels of the IoT devices, such as the packet analysis based IoT device management systems described in this paper. The packet analysis based IoT device risk assessment system **1210** is intended to represent a system that functions to apply assessment weights to IoT device risk factors extracted from device profiles for purposes of assessing risk levels of IoT devices, such as the packet analysis based IoT device risk assessment systems described in this paper. The packet analysis based IoT device profiling system **1208** can receive event logs, access logs, and/or system logs in real-time as they are updated, through VPN tunnels or traditional network channels from the IoT device risk assessment system **1206** implemented at the local network **1202**. The packet analysis based IoT device profiling system **1208** can use received event logs, access logs, and/or system logs to profile IoT device into device profiles.

(147) FIG. 13 depicts a diagram 1300 of another example of a system for assessing risk levels of IoT devices. The system shown in the example of FIG. 13 includes a local network 1302 and a cloud 1304. The local network 1302 is intended to represent a network that includes at least one IoT device coupled to a local appliance. In the example of FIG. 13, the cloud 1304 is intended to represent a third party cloud, e.g. a cloud of a third party IoT device management entity. The local appliance can transmit data packets from the IoT device through the cloud 1304.

(148) In the example of FIG. 13, the cloud 1304 includes an IoT device risk assessment system 1306, a packet analysis based IoT device profiling system 1308, and a packet analysis based IoT device risk assessment system 1310. The IoT device risk assessment system 1306 is intended to represent a system that obtains packets transmitted to and from IoT devices in the local network 1302 through the local appliance. The IoT device risk assessment system 1306 can use obtained packets to build historical records of IoT devices by building event logs, system logs, and access logs through packet analysis of the obtained packets. The packet analysis based IoT device profiling system 1308 is intended to represent a system that uses historical records of IoT devices to profile the IoT devices into device profiles. The packet analysis based IoT device risk assessment system 1310 is intended to represent a system that uses device profiles of IoT devices to assess risk levels of the IoT devices.

(149) FIG. 14 depicts a flowchart 1400 of an example of a method for generating device profiles of IoT devices through packet inspection for use in assessing risk levels of the IoT devices. The flowchart 1400 begins at module 1402, where data packets transmitted to and from IoT devices are obtained. An applicable engine for controlling the flow of data to and from IoT devices, such as the data flow management engines described in this paper, can obtain data packets transmitted to and from IoT devices. Data packets can be obtained at a local appliance with respect to the IoT devices. Alternatively, data packets can be obtained at a location remote from IoT devices after they have been transmitted to the remote location by a local appliance or before they are transmitted through a local network to the IoT devices. Further depending upon implementation-specific or other considerations, data packets can be obtained based on a source, a destination, a data packet type, and data within a data packet. For example, all data packets from a particular source can be obtained. In various implementations, data packets can be transmitted using VPN tunnels.

(150) The flowchart 1400 continues to module 1404, where the data packets are analyzed to identify transaction data. An applicable engine for analyzing the data packets, such as the packet inspector engines described in this paper, can analyze the data packets to identify transaction data. Data packets can be analyzed using deep packet inspection. For example, deep packet inspection can be used to identify transaction data from payloads of the data packets. Additionally, specific data packets to perform deep packet inspection on can be selected based on at least one of a source of data packets, a destination of data packets, a data packet type of data packets, and data within data packets. For example, all data packets from a particular source can have deep packet inspection performed on them.

(151) The flowchart 1400 continues to module 1406, where historical records of the IoT devices are created or updated. An applicable engine for managing logs, such as one or a combination of the event log, system log, and access log management engines described in this paper, can create/update historical records for the IoT devices using the transaction data. A historical record can include one or a combination of access logs, system logs, and event logs of the IoT devices.

(152) The flowchart 1400 continues to module 1408, where device profiles of the IoT devices are created or updated based on the historical records. An applicable engine for profiling the IoT devices, such as the IoT device profiling engines described in this paper, can function to create/update device profiles of the IoT devices based on the historical records. IoT devices can be clustered before they are profiled into device profiles. Additionally, determined vulnerabilities of IoT devices can be included in device profiles of the IoT devices. In generating device profiles of the IoT devices, regular IoT device behavior of the IoT device can be determined from the

historical records and included as part of the device profiles.

(153) The flowchart **1400** continues to module **1410**, where risk levels of the IoT devices are assessed based on the device profiles. Risk levels of the IoT devices can be assessed by an applicable engine for assessing risk levels of IoT devices, such as the IoT device risk factor analysis engines described in this paper. In assessing risk levels of the IoT device using the device profiles, IoT device risk factors can be extracted from the device profiles. Additionally, in assessing risk levels of the IoT devices, assessment weights can be applied to extracted IoT device risk factors to determine risk scores for the IoT devices. Risk scores of the IoT devices can be used to assess risk levels to the IoT devices based on the risk scores.

(154) FIG. **15** depicts a flowchart **1500** of another example of a method for generating device profiles of IoT devices through packet inspection for use in assessing risk levels of the IoT devices. The flowchart **1500** begins at module **1502**, where data packets transmitted to and from IoT devices are obtained. An applicable engine for controlling the flow of data to and from IoT devices, such as the data flow management engines described in this paper, can obtain data packets transmitted to and from IoT devices. Data packets can be obtained at a local appliance with respect to the IoT devices. Additionally, data packets can be obtained at a location remote from IoT devices after they have been transmitted to the remote location by a local appliance or before they are transmitted through a local network to the IoT devices. Data packets can be obtained based on a source, a destination, a data packet type, and data within a data packet. For example, all data packets from a particular source can be obtained. In various implementations, data packets can be transmitted using VPN tunnels.

(155) The flowchart **1500** continues to module **1504**, where the data packets are analyzed to identify transaction data. An applicable engine for analyzing data packets, such as the packet inspector engines described in this paper, can analyze the data packets to identify transaction data. Data packets can be analyzed using deep packet inspection. For example, deep packet inspection can be used to identify transaction data from payloads of the data packets. Additionally, specific data packets to perform deep packet inspection on can be selected based on at least one of a source of data packets, a destination of data packets, a data packet type of data packets, and data within data packets. For example, all data packets from a particular source can have deep packet inspection performed on them.

(156) The flowchart **1500** continues to module **1506**, where event logs of the IoT devices are created or updated. An applicable engine for managing event logs, such as the event log management engines described in this paper, can create/update event logs for the IoT devices using the transaction data. An event log can be updated in real-time using the transaction data as it is identified in real-time as the IoT devices operate.

(157) The flowchart **1500** continues to module **1508**, where device profiles of the IoT devices are created or updated based on the event logs. An applicable engine for profiling the IoT devices, such as the IoT device profiling engines described in this paper, can function to create/update device profiles of the IoT devices based on the event logs. In profiling the IoT devices, the IoT devices can be clustered before they are profiled into device profiles. Additionally, in profiling the IoT devices, determined vulnerabilities of IoT devices can be included in device profiles of the IoT devices. In generating device profiles of the IoT devices, regular IoT device behavior of the IoT device can be determined from the event logs and included as part of the device profiles.

(158) The flowchart **1500** continues to module **1510**, where risk levels of the IoT devices are assessed based on the device profiles. Risk levels of the IoT devices can be assessed by an applicable engine for assessing risk levels of IoT devices, such as the IoT device risk factor analysis engines described in this paper. In assessing risk levels of the IoT device using the device profiles, IoT device risk factors can be extracted from the device profiles. Additionally, in assessing risk levels of the IoT devices, assessment weights can be applied to extracted IoT device risk factors to determine risk scores for the IoT devices. Risk scores of the IoT devices can be used to

assess risk levels to the IoT devices based on the risk scores.

(159) FIG. **16** depicts a flowchart **1600** of another example of a method for generating device profiles of IoT devices through packet inspection for use in assessing risk levels of the IoT devices. The flowchart **1600** begins at module **1602**, where data packets transmitted to and from IoT devices are obtained. An applicable engine for controlling the flow of data to and from IoT devices, such as the data flow management engines described in this paper, can obtain data packets transmitted to and from IoT devices. Data packets can be obtained at a local appliance with respect to the IoT devices. Additionally, data packets can be obtained at a location remote from IoT devices after they have been transmitted to the remote location by a local appliance or before they are transmitted through a local network to the IoT devices. Data packets can be obtained based on a source, a destination, a data packet type, and data within a data packet. For example, all data packets from a particular source can be obtained. In various implementations, data packets can be transmitted using VPN tunnels.

(160) The flowchart **1600** continues to module **1604**, where the data packets are analyzed to identify transaction data. An applicable engine for analyzing data packets, such as the packet inspector engines described in this paper, can analyze the data packets to identify transaction data. Data packets can be analyzed using deep packet inspection. For example, deep packet inspection can be used to identify transaction data from payloads of the data packets. Specific data packets to perform deep packet inspection on can be selected based on at least one of a source of data packets, a destination of data packets, a data packet type of data packets, and data within data packets. For example, all data packets from a particular source can have deep packet inspection performed on them.

(161) The flowchart **1600** continues to module **1606**, where system logs of the IoT devices are created or updated. An applicable engine for managing system logs, such as the system log management engines described in this paper, can create or update system logs for the IoT devices using the transaction data. A system log can be updated in real-time using the transaction data as it is identified in real-time as the IoT devices operate.

(162) The flowchart **1600** continues to module **1608**, where device profiles of the IoT devices are created or updated based on the system logs. An applicable engine for profiling the IoT devices, such as the IoT device profiling engines described in this paper, can function to create/update device profiles of the IoT devices based on the system logs. In profiling the IoT devices, the IoT devices can be clustered before they are profiled into device profiles. Additionally, in profiling the IoT devices, determined vulnerabilities of IoT devices can be included in device profiles of the IoT devices. In generating device profiles of the IoT devices, regular IoT device behavior of the IoT device can be determined from the system logs and included as part of the device profiles.

(163) The flowchart **1600** continues to module **1610**, where risk levels of the IoT devices are assessed based on the device profiles. Risk levels of the IoT devices can be assessed by an applicable engine for assessing risk levels of IoT devices, such as the IoT device risk factor analysis engines described in this paper. In assessing risk levels of the IoT device using the device profiles, IoT device risk factors can be extracted from the device profiles. Additionally, in assessing risk levels of the IoT devices, assessment weights can be applied to extracted IoT device risk factors to determine risk scores for the IoT devices. Risk scores of the IoT devices can be used to assess risk levels to the IoT devices based on the risk scores.

(164) FIG. **17** depicts a flowchart **1700** of another example of a method for generating device profiles of IoT devices through packet inspection for use in assessing risk levels of the IoT devices. The flowchart **1700** begins at module **1702**, where data packets transmitted to and from IoT devices are obtained. An applicable engine for controlling the flow of data to and from IoT devices, such as the data flow management engines described in this paper, can obtain data packets transmitted to and from IoT devices. Data packets can be obtained at a local appliance with respect to the IoT devices. Additionally, data packets can be obtained at a location remote from IoT devices after they

have been transmitted to the remote location by a local appliance or before they are transmitted through a local network to the IoT devices. Data packets can be obtained based on a source, a destination, a data packet type, and data within a data packet. For example, all data packets from a particular source can be obtained. In various implementations, data packets can be transmitted using VPN tunnels.

(165) The flowchart **1700** continues to module **1704**, where the data packets are analyzed to identify transaction data. An applicable engine for analyzing data packets, such as the packet inspector engines described in this paper, can analyze the data packets to identify transaction data. Data packets can be analyzed using deep packet inspection. For example, deep packet inspection can be used to identify transaction data from payloads of the data packets. Additionally, specific data packets to perform deep packet inspection on can be selected based on at least one of a source of data packets, a destination of data packets, a data packet type of data packets, and data within data packets. For example, all data packets from a particular source can have deep packet inspection performed on them.

(166) The flowchart **1700** continues to module **1706**, where access logs of the IoT devices are created or updated. An applicable engine for managing access logs, such as the access log management engines described in this paper, can create/update access logs for the IoT devices using the transaction data. An access log can be updated in real-time using the transaction data as it is identified in real-time as the IoT devices operate.

(167) The flowchart **1700** continues to module **1708**, where device profiles of the IoT devices are created or updated based on the access logs. An applicable engine for profiling the IoT devices, such as the IoT device profiling engines described in this paper, can function to create/update device profiles of the IoT devices based on the access logs. In profiling the IoT devices, the IoT devices can be clustered before they are profiled into device profiles. Additionally, in profiling the IoT devices, determined vulnerabilities of IoT devices can be included in device profiles of the IoT devices. In generating device profiles of the IoT devices, regular IoT device behavior of the IoT device can be determined from the system logs and included as part of the device profiles.

(168) The flowchart **1700** continues to module **1710**, where risk levels of the IoT devices are assessed based on the device profiles. Risk levels of the IoT devices can be assessed by an applicable engine for assessing risk levels of IoT devices, such as the IoT device risk factor analysis engines described in this paper. In assessing risk levels of the IoT device using the device profiles, IoT device risk factors can be extracted from the device profiles. Additionally, in assessing risk levels of the IoT devices, assessment weights can be applied to extracted IoT device risk factors to determine risk scores for the IoT devices. Risk scores of the IoT devices can be used to assess risk levels to the IoT devices based on the risk scores.

(169) FIG. **18** depicts a flowchart **1800** of an example of a method for generating device profiles of IoT devices by determining vulnerabilities of IoT devices for use in assessing risk levels of IoT devices. The flowchart **1800** begins at module **1802**, where a historical record of an IoT device is created or updated. A historical record of an IoT device can be created from one or an applicable combination of an event log, a system log, and an access log of the IoT device. An event log, a system log, and an access log can be created using packet analysis of data packets transmitted to and from an IoT device. An event log, a system log, and an access log can be created from transaction data identified from deep packet inspection of data packets transmitted to and from an IoT device.

(170) The flowchart **1800** continues to module **1804**, where the IoT device is probed by sending data packets to the IoT device. An applicable engine for probing an IoT device, such as the IoT device probing engines described in this paper, can probe the IoT device by sending data packets to the IoT device. The IoT device can be probed by sending data packets to the IoT device to simulate an attack on the IoT device. Additionally, the IoT device can be probed by sending data packets to the IoT device to force the IoT device to respond.

(171) The flowchart **1800** continues to module **1806**, where vulnerability of the IoT device is determined based on the response by the IoT device to the probe. An applicable engine for determining IoT device vulnerability, such as the vulnerability determination engines described in this paper, can determine a vulnerability of the IoT device based on the response by the IoT device to the probe. Vulnerability of the IoT device can be determined based on an analysis of data packets transmitted from the IoT device in response to the probe. Additionally, vulnerability of the IoT device can be determined based on an analysis of how the IoT device actually responds, e.g. whether it does not respond, to the probe.'

(172) The flowchart **1800** continues to module **1808**, where optionally a vulnerability of the IoT device is determined based on the historical record of the IoT device. An applicable engine for determining IoT device vulnerability, such as the vulnerability determination engines described in this paper, can determine a vulnerability of the IoT device based on the historical record of the IoT device. For example, a historical record can be checked to see if the IoT device is the subject of a random scan by a user and subsequently determined vulnerability of the IoT device.

(173) The flowchart **1800** continues to module **1810**, where a device profile of the IoT device is created or updated to indicate the vulnerability of the IoT device for use in assessing a risk level of the IoT device. An applicable engine for profiling IoT devices, such as the IoT device profiling engines described in this paper, can create/update a device profile of the IoT device to indicate the determined vulnerability of the IoT device. For example, IoT device risk factors related to the IoT device can be extracted from a device profile of the IoT device based on the determined vulnerability and used in assessing a risk level of the IoT device.

(174) FIG. **19** depicts a diagram **1900** of an example of a system for providing IoT device risk assessment through a mirror point. The system shown in the example of FIG. **19** includes a mirror port **1902**, an IoT device **1904**, a source/destination **1906**, and a packet analysis based IoT device risk assessment system **1908**. The mirror port **1902** is intended to represent a device that functions to perform port mirroring on another port. The mirror port **1902** can be used to obtain data packets transmitted to and from IoT devices without disrupting the flow of the data packets. The mirror port **1902** can be implemented as part of switches or other applicable networking devices. Additionally, the mirror port **1902** can be implemented on network devices in a LAN of IoT devices, or on network devices in a WAN of IoT devices. For example, the mirror port **1902** can be implemented as part of a local router in an enterprise network of IoT devices. Further in the example, in being implemented as part of the local router in an enterprise network, the mirror port **1902** can be used to obtain data packets transmitted between IoT devices in the enterprise network, e.g. intranetwork traffic.

(175) In the example of FIG. **19**, the IoT device **1904** is intended to represent a device that includes wired or wireless interfaces through which the IoT device **1904** can send and receive data over wired and wireless connections. The IoT device **1904** can include unique identifiers which can be used in the transmission of data through a network. Unique identifiers of the IoT device **1904** can include identifiers created in accordance with Internet Protocol version 4 (hereinafter referred to as "IPv4"), or identifiers created in accordance with Internet Protocol version 6 (hereinafter referred to as "IPv6"), of which both protocol versions are hereby incorporated by reference.

(176) In the example of FIG. **19**, the source/destination **1906** is intended to represent a system accessible by IoT devices through, e.g., a WAN. For example, the source/destination **1906** can be a system that an IoT device communicates with over the Internet. Alternatively, the source/destination **1906** can be a system or device within a LAN of an IoT device. For example, the source/destination **1906** can be another IoT device in a LAN over which an IoT device communicates.

(177) In the example of FIG. **19**, the IoT device risk assessment system **1908** is intended to represent a system that functions to assess IoT device risks through packet analysis, such as the IoT device risk assessment systems described in this paper. The IoT device risk assessment system

1908 functions to assess risks of IoT devices using packet analysis of data packets transmitted to and from the IoT devices. The IoT device risk assessment system **1908** can obtain data packets through a mirror port, without interrupting the flow of the data packets between sources and destinations.

(178) In an example of operation of the example system shown in FIG. **19**, the IoT device **1904** sends and receives data packets that the mirror port **1902** mirrors for purposes of assess a risk level of the IoT device **1904**. In the example of operation of the example system shown in FIG. **19**, the source/destination **1906** transmits and receives data in response to data received from the IoT device **1904**. In the example of operation of the example system shown in FIG. **19** the packet analysis based IoT device risk assessment system **1908** obtains data packets through the mirror port **1902** for use in assessing a risk level of the IoT device **1904** using packet analysis.

(179) FIG. **20** depicts a flowchart **2000** of an example of a method of assessing risk levels of IoT devices. The flowchart **2000** begins at module **2002**, where an IoT device is profiled into an IoT device profile. An applicable engine for profiling an IoT device into an IoT device profile, such as the IoT device profiling engines described in this paper, can profile an IoT device into an IoT device profile. An IoT device can be profiled based on analysis of data traffic to and from an IoT device as the IoT device accesses network services through a network. In profiling an IoT device based on analysis of data traffic to and from an IoT device, an IoT device can be profiled through passive monitoring by analyzing data packets sent to and from the IoT device. For example, the IoT device can be profiled based on one or a combination of event logs, system logs, and access logs maintained based on an analysis of data packets transmitted to and from the IoT device.

Additionally, in profiling an IoT device based on analysis of data traffic to and from the IoT device, the IoT device can be actively probed to determine vulnerability of the IoT device. Determined vulnerabilities of an IoT device can be included as part of a device profile of the IoT device.

(180) The flowchart **2000** continues to module **2004**, where IoT device risk factors are extracted from the IoT device profile. An applicable engine for analyzing IoT device risk factors, such as the IoT device risk factor analysis engines described in this paper, can extract IoT device risk factors from the IoT device profile. IoT device risk factors extracted from the IoT device profile can include one or an applicable combination of risk factors related to applications used by the IoT device in accessing the network services through the network, protocols used by the IoT device in accessing the network services through the network, network activeness of the IoT device in accessing the network services through the network, network communication characteristics of the IoT device in accessing the network services through the network, security characteristics of data traffic associated with the IoT device in accessing the network services through the network, and operational performance deviations of the IoT device in accessing the network services through the network.

(181) The flowchart **2000** continues to module **2006**, where assessment weights to apply to the IoT device risk factors are selected. An applicable engine for managing assessment weights to apply in assessing risk levels of IoT devices, such as the assessment weight variance management engines described in this paper, can select assessment weights to apply to the IoT device risk factors extracted from the IoT device profile. Assessment weights can be selected for specific IoT device risk factors. Additionally, assessment weights can be selected on one or an applicable combination of a per-device basis, a per-device type basis, a per-network basis, or other applicable per-IoT device characteristic basis. Assessment weights can be selected based on one or an applicable combination of characteristics of a network through which the IoT device is accessing network services, input of a user associated with the IoT device, and characteristics of the user associated with the IoT device.

(182) The flowchart **2000** continues to module **2008**, where a risk score of the IoT device is determined by applying the assessment weights to the IoT device risk factors. An applicable engine for analyzing IoT device risk factors, such as the IoT device risk factor analysis engines described

in this paper, can determine a risk score of the IoT device by applying the assessment weights to the extracted IoT device risk factors. For example, if assessment weights for IoT device risk factors related to operational performance deviations of IoT devices are 20%, then an assessment weight of 20% can be applied to extracted IoT device factors related to operational performance deviations of the IoT device in determining a risk score for the IoT device.

(183) The flowchart **2000** continues to module **2010**, where a risk level of the IoT device is assessed based on the risk score. An applicable engine for analyzing IoT device risk factors, such as the IoT device risk factor analysis engines described in this paper, can assess a risk level of the IoT device based on the risk score. A risk level of the IoT device can be assessed based on where the risk score falls within a range of risk scores. For example, if the risk score is above a threshold risk score for a high risk level, then the IoT device can be assess a risk level of high risk.

(184) FIG. **21** depicts a screenshot **2100** of a presentation of risk assessment data to a user. In the screenshot **2100**, IoT devices assessed high risk levels are shown, along with identifiers of the IoT devices, and a number of applications executing at the IoT devices.

(185) FIG. **22** depicts a screenshot **2200** of another presentation of risk assessment data to a user. In the screenshot **2200**, risk levels of IoT devices along with types of communicating and amount of data actually communicated are shown.

(186) FIG. **23** depicts a screenshot **2300** of another presentation of risk assessment data to a use. In the screenshot **2300**, the number of IoT devices assessed at different risk levels are displayed to a user.

(187) FIG. **24** depicts a screenshot of a device map. In the screenshot **2400**, the device map includes hosts and devices an IoT device communicates with in accessing network services.

(188) These and other examples provided in this paper are intended to illustrate but not necessarily to limit the described implementation. As used herein, the term “implementation” means an implementation that serves to illustrate by way of example but not limitation. The techniques described in the preceding text and figures can be mixed and matched as circumstances demand to produce alternative implementations.

Claims

1. A system, comprising: a processor configured to: perform a match, from a set of previously defined device profiles, of an Internet of Things (IOT) device profile applicable to an IoT device, at least in part by analyzing one or more characteristics of how the IoT device functions in accessing a network service, and in response determine that a new profile should be generated for the IoT device, wherein the IoT device profile applicable to the IOT device is associated with a plurality of individual IoT devices clustered using a plurality of clustering factors related, collectively, to characteristics of the plurality of individual IOT devices and characteristics of operation of the plurality of individual IoT devices; analyze data packets transmitted to or from the IoT device; determine a risk level of the IoT device based at least in part on the data packets analysis and the matched IoT device profile, including by evaluating a set of risk factors; and determine that the risk level of the IoT device exceeds a threshold and take a remedial action in response, including by preventing the IOT device from further transmitting data packets; and a memory coupled to the processor and configured to provide the processor with instructions.

2. The system of claim 1, wherein the IoT device profile includes one or more characteristics of the IoT device.

3. The system of claim 1, wherein the IoT device profile includes one or more characteristics of how the IoT device functions in operation.

4. The system of claim 1, wherein the processor is further configured to cluster a plurality of IoT devices together.

5. The system of claim 4, wherein the processor is further configured to associate a plurality of IoT

device profiles together based at least in part on the cluster.

6. The system of claim 1, wherein the processor is further configured to determine an operational performance deviation of a particular instance of the IoT device at least in part by using a plurality of other instances of the IoT device.

7. The system of claim 1, wherein matching the IoT device profile includes passively observing the IoT device.

8. The system of claim 1, wherein matching the IoT device profile includes actively probing the IoT device.

9. The system of claim 1, wherein the set of risk factors have one or more associated assessment weights.

10. The system of claim 1, wherein at least one risk factor comprises a risk posed by the IoT device using an application in accessing the network service.

11. The system of claim 9, wherein at least one assessment weight is based at least in part on a network characteristic.

12. The system of claim 9, wherein at least one assessment weight is based at least in part on an operational performance deviation of the IoT device.

13. The system of claim 1, wherein taking the remedial action includes generating an alert that a single IoT device has the risk level that exceeds the threshold.

14. The system of claim 1, wherein determining that the risk level exceeds the threshold includes determining that a plurality of IoT devices have respective risk levels above respective thresholds.

15. The system of claim 1, wherein taking the remedial action further includes presenting the risk level of the IoT device to a user.

16. A method, comprising: performing a match, from a set of previously defined device profiles, of an Internet of Things (IOT) device profile applicable to an IoT device, at least in part by analyzing one or more characteristics of how the IoT device functions in accessing a network service, and in response determining that a new profile should be generated for the IoT device, wherein the IoT device profile applicable to the IoT device is associated with a plurality of individual IoT devices clustered using a plurality of clustering factors related, collectively, to characteristics of the plurality of individual IoT devices and characteristics of operation of the plurality of IoT devices; analyzing data packets transmitted to or from the IoT device; determining a risk level of the IoT device based at least in part on the data packets analysis and the matched IoT device profile, including by evaluating a set of risk factors; and determining that the risk level of the IOT device exceeds a threshold and taking a remedial action in response, including by preventing the IoT device from further transmitting data packets.

17. The method of claim 16, wherein the IoT device profile includes one or more characteristics of how the IoT device functions in operation.

18. The method of claim 16, further comprising clustering a plurality of IoT devices together.

19. The method of claim 18, further comprising associating a plurality of IoT device profiles together based at least in part on the cluster.

20. The method of claim 16, further comprising determining an operational performance deviation of a particular instance of the IoT device at least in part by using a plurality of other instances of the IoT device.

21. The method of claim 16, wherein the set of risk factors have one or more associated assessment weights.

22. The method of claim 21, wherein at least one assessment weight is based at least in part on a network characteristic.

23. The method of claim 21, wherein at least one assessment weight is based at least in part on an operational performance deviation of the IoT device.
