

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401873
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Li; Huacong et al.

Camera module and electronic device

Abstract

A camera module is disclosed and includes: a housing, internally provided with an accommodation cavity; a lens assembly, movably arranged in the accommodation cavity; a circuit board, connected to lens assembly; and a gimbal assembly, including: a support plate, where at least part of the support plate is movably arranged in the accommodation cavity, and the lens assembly and the circuit board are arranged on the support plate; a first driving assembly, where the first driving assembly is arranged on the housing, and at least part of the first driving assembly is connected to the support plate to drive the support plate to move in a first direction; and a second driving assembly, where the second driving assembly is arranged on the support plate, and at least part of the second driving assembly is connected to the support plate to drive the support plate to move in a second direction.

Inventors: Li; Huacong (Chang'an Dongguan, CN), He; Yunfa (Chang'an Dongguan, CN), Yang; Ze (Chang'an Dongguan, CN)

Applicant: VIVO MOBILE COMMUNICATION CO., LTD. (Guangdong, CN)

Family ID: 1000008778855

Assignee: VIVO MOBILE COMMUNICATION CO., LTD. (Guangdong, CN)

Appl. No.: 18/340010

Filed: June 22, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230336857 A1	Oct. 19, 2023

Related U.S. Application Data

continuation parent-doc WO PCT/CN2021/138635 20211216 PENDING child-doc US 18340010

Publication Classification

Int. Cl.: H04N23/54 (20230101); H04N23/55 (20230101); H04N23/57 (20230101); H04N23/68 (20230101); H05K1/18 (20060101)

U.S. Cl.:

CPC H04N23/54 (20230101); H04N23/55 (20230101); H04N23/57 (20230101); H04N23/687 (20230101); H05K1/189 (20130101); H05K2201/10121 (20130101)

Field of Classification Search

CPC: H04N (23/54); H04N (23/55); H04N (23/57); H04N (23/687); H04N (23/51); H04N (23/685); H05K (1/189); H05K (2201/10121); H05K (1/0277); G02B (27/646); G02B (7/04-105); H04M (1/0264); G03B (2205/0053-0084); G03B (7/10); G03B (13/36)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2006/0269262	12/2005	Shin	348/E5.046	G03B 5/02
2007/0104044	12/2006	Kim	N/A	G11B 7/0932
2012/0140326	12/2011	Takeda	359/554	H04N 23/687
2012/0281517	12/2011	Lee	N/A	G11B 7/0933
2013/0163974	12/2012	Takei	396/55	G03B 5/00
2013/0177301	12/2012	Nakayama et al.	N/A	N/A
2015/0055220	12/2014	Lim	359/557	G02B 27/646
2017/0324892	12/2016	Kim	N/A	H04N 23/55
2017/0339346	12/2016	Chung et al.	N/A	N/A
2017/0353662	12/2016	Enta	N/A	N/A
2017/0363881	12/2016	Stec	N/A	N/A
2018/0173080	12/2017	Enta	N/A	H04N 23/57
2018/0348594	12/2017	Shin et al.	N/A	N/A
2020/0174271	12/2019	Minamisawa	N/A	G03B 5/00
2020/0174272	12/2019	Minamisawa	N/A	G03B 5/04
2020/0310150	12/2019	Minamisawa	N/A	N/A
2020/0371374	12/2019	Barak	N/A	G03B 17/02
2021/0215900	12/2020	Sue et al.	N/A	N/A
2021/0278689	12/2020	Kasahara	N/A	H02K 41/0356
2023/0336853	12/2022	Li	N/A	H04N 23/54
2023/0336855	12/2022	Li	N/A	G03B 17/12

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103200360	12/2012	CN	N/A
105573014	12/2015	CN	N/A
111474804	12/2019	CN	N/A
111953881	12/2019	CN	N/A

211880480	12/2019	CN	N/A
112637471	12/2020	CN	N/A
2006259247	12/2005	JP	N/A
2007312325	12/2006	JP	N/A
2016122055	12/2015	JP	N/A
2020024260	12/2019	JP	N/A
2020166020	12/2019	JP	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion of the International Searching Authority dated Mar. 1, 2022 as received in Application No. PCT/CN2021/138635. cited by applicant

Primary Examiner: Tissire; Abdelaaziz

Attorney, Agent or Firm: Price Heneveld LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation application of PCT International Application No. PCT/CN2021/138635 filed on Dec. 16, 2021, which claims priority to Chinese Patent Application No. 202011542405.X filed on Dec. 23, 2020, which are incorporated herein by reference in their entireties.

TECHNICAL FIELD

(1) This application belongs to the technical field of cameras, and specifically relates to a camera module and an electronic device.

BACKGROUND

(2) The wider application of cameras on electronic devices, especially mobile phones, makes cameras a popular selling point for mobile phones. During photographing and image recording, jitters caused by a hand or movement of a user blur the image and greatly lower the imaging quality. In the 5G era, video creating and sharing will usher in a new round of explosion, and requirements of people on video shooting devices are becoming higher. This requires electronic devices to have good image stabilization performance, compensate image offsets caused by jitters, and provide stable and clear images. Currently, the design of image stabilization gimbals has a large volume and has high requirements on the hardware architectural design of electronic devices.

SUMMARY

(3) According to a first aspect, an embodiment of this application provides a camera module, including: a housing, internally provided with an accommodation cavity; a lens assembly, movably arranged in the accommodation cavity; a circuit board, connected to the lens assembly; and a gimbal assembly, including: a support plate, where at least part of the support plate is movably arranged in the accommodation cavity, and the lens assembly and the circuit board are arranged on the support plate; a first driving assembly, where the first driving assembly is arranged on the housing, and at least part of the first driving assembly is connected to the support plate to drive the support plate to move in a first direction; and a second driving assembly, where the second driving assembly is arranged on the support plate, and at least part of the second driving assembly is connected to the support plate to drive the support plate to move in a second direction.

(4) According to a second aspect, an embodiment of this application provides an electronic device, including the foregoing camera module.

(5) Additional aspects and advantages of this application are partially provided in the following

description, and partially become apparent in the following description or understood through the practice of this application.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The foregoing and/or additional aspects and advantages of this application become apparent and comprehensible in the description of the embodiments made with reference to the following accompanying drawings.

(2) FIG. 1 is a cross-sectional view of an image stabilization gimbal in the related art.

(3) FIG. 2 is a top view of a camera module according to an embodiment of this application.

(4) FIG. 3 is a partial exploded view of a camera module according to an embodiment of this application.

(5) FIG. 4 is a schematic diagram of assembly of a first driving assembly, a second driving assembly, and a support plate of a camera module according to an embodiment of this application.

(6) FIG. 5 is a cross-sectional view along A-A in FIG. 2.

(7) FIG. 6 is a cross-sectional view along B-B in FIG. 2.

REFERENCE NUMERALS

(8) camera module **100**; housing **10**; accommodation cavity **11**; holder **12**; cover plate **13**; lens assembly **20**; circuit board **30**; first board body **31**; second board body **32**; support plate **40**; main board **41**; side plate **42**; first driving assembly **50**; first magnetic member **51**; first coil **52**; coil **521**; second driving assembly **60**; second magnetic member **61**; second coil **62**; flexible printed circuit board receiving portion **70**; first position feedback element **80**; cross support shaft **1**; Hall sensing element **2**; coil **3**; and magnet **4**.

DETAILED DESCRIPTION

(9) Embodiments of this application are described in detail below, and examples of the embodiments are shown in accompanying drawings, where the same or similar elements or the elements having same or similar functions are denoted by the same or similar reference numerals throughout the description. The embodiments that are described with reference to the accompanying drawings are exemplary, and are only used to interpret this application, instead limiting this application. All other embodiments obtained by a person of ordinary skill in the art based on the embodiments of this application without creative efforts shall fall within the protection scope of this application.

(10) In the specification and claims of this application, a feature defined to be “first” or “second” may explicitly or implicitly include one or more features. In the description of this application, unless otherwise stated, the meaning of “a plurality of” is two or more than two. In addition, in this specification and the claims, “and/or” represents at least one of the connected objects, and the character “/” generally indicates an “or” relationship between the associated objects.

(11) In the description of this application, it should be understood that, orientations or position relationships indicated by terms such as “center”, “longitudinal”, “transverse”, “length”, “width”, “thickness”, “up”, “down”, “front”, “back”, “left”, “right”, “vertical”, “horizontal”, “top”, “bottom”, “inner”, “outer”, “clockwise”, “counterclockwise”, “axial”, “radial”, and “circumferential” are orientations or position relationship shown based on the accompanying drawings, and are merely used for describing this application and simplifying the description, rather than indicating or implying that the apparatus or element should have a particular orientation or be constructed and operated in a particular orientation, and therefore, should not be construed as a limitation on this application.

(12) In the description of this application, it should be noted that, unless explicitly specified or limited otherwise, the terms “mount”, “interconnect”, and “connect” should be understood broadly,

for example, the connection may be a fixed connection, detachable connection, or integral connection; or the connection may be a mechanical connection or an electrical connection; or the connection may be a direct connection, an indirect connection through an intermediary, or internal communication between two components. A person of ordinary skill in the art may understand the specific meanings of the foregoing terms in this application according to specific situations.

(13) This application is an invention by the creator based on the following facts.

(14) FIG. 1 shows an image stabilization gimbal in the related art.

(15) As shown in FIG. 1, a camera module in the image stabilization gimbal according to the related art uses a dangling structure. Through the cooperation of a cross support shaft 1 with a connected diagonal line, an electromagnetic driving system, and a Hall sensing element 2, the camera module is driven to move and the position is fed back, so as to achieve the objective of image stabilization on the module. The electromagnetic driving system includes a coil 3 and a magnet 4 cooperating with each other.

(16) As can be seen from FIG. 1, a camera body is embedded in the gimbal, and the electromagnetic driving system is arranged at the outside of the camera body. To be specific, the dangling system and the driving system peculiar to the gimbal result in a large size of the overall gimbal, and lead to big troubles for structure stacking and design of the camera module.

(17) Based on this, the inventor of this application creatively obtained the following invention through long-term research and experiments.

(18) A camera module 100 according to an embodiment of this application includes: a housing 10, a lens assembly 20, a circuit board 30, and a gimbal assembly. The gimbal assembly includes: a support plate 40, a first driving assembly 50, and a second driving assembly 60.

(19) Specifically, the housing 10 is internally provided with an accommodation cavity 11, and the lens assembly 20 is movably arranged in the accommodation cavity 11. The circuit board 30 and the lens assembly 20 are connected to each other. The support plate 40 is at least partially movably arranged in the accommodation cavity 11, and the lens assembly 20 and the circuit board 30 are arranged on the support plate 40. The first driving assembly 50 is arranged in the housing 10, and at least part of the first driving assembly is connected to the support plate 40 to drive the support plate 40 to move in a first direction. The second driving assembly 60 is arranged on the support plate 40, and at least part of the second driving assembly is connected to the support plate 40 to drive the support plate 40 to move in a second direction.

(20) In other words, the camera module 100 according to this embodiment of this application mainly includes a housing 10, a lens assembly 20 mounted in the housing 10, a circuit board 30 electrically connected to the lens assembly 20, and a gimbal assembly. The gimbal assembly mainly includes a support plate 40 that can limit the lens assembly 20 and the circuit board 30, and a first driving assembly 50 and a second driving assembly 60 that can drive the support plate 40. The housing 10 is a basic component of the camera module 100, can provide a basis for mounting other components of the camera module 100, and protects the parts or components such as the driving assembly. In this embodiment of this application, the housing 10 has an accommodation cavity 11 that can accommodate the lens assembly 20.

(21) In the specific process of photographing, the camera module 100 may incline due to jittering, and eventually affect the photographing quality. In the camera module 100 disclosed in this embodiment of this application, the lens assembly 20 is movable relative to the housing 10. The first driving assembly 50 and the second driving assembly 60 drive the lens assembly 20 to move, so as to compensate an inclination caused by jittering of the camera module 100, thereby implementing effective image stabilization on the camera module 100.

(22) In this embodiment of this application, the lens assembly 20 and the circuit board 30 can move synchronously with the support plate 40, and the support plate 40 may serve as a reinforcement plate. Therefore, when the first driving assembly 50 and the second driving assembly 60 drive the support plate 40 to move, the lens assembly 20 and the circuit board 30 can move simultaneously,

so as to prevent the lens assembly **20** from moving relative to the circuit board **30** and dragging the circuit board **30**.

(23) Compared with the solution that the electromagnetic driving system directly drives the camera body in the related art, in the camera module **100** according to this embodiment of this application, the first driving assembly **50** and the second driving assembly **60** indirectly drive the lens assembly **20** and the circuit board **30** through the support plate **40**. In this way, the circuit board **30** and the lens assembly **20** can move synchronously, which prevents a flexible printed circuit board from dragging the camera body in the related art, and the lens assembly **20** according to this embodiment of this application can move farther and rotate through a larger angle. In addition, the defect that the volume of the overall structure of the camera module is large because the electromagnetic driving system is mounted on the camera body in the related art is avoided.

(24) It should be noted that, the first driving assembly **50** can drive the support plate **40** to move in the first direction, and the second driving assembly **60** can drive the support plate **40** to move in the second direction, and the first direction and the second direction may be the same direction or reverse directions, or intersect with each other. This is not limited herein. The first driving assembly **50** and the second driving assembly **60** may simultaneously or independently operate. This is not limited herein. Types of movement of the support plate **40** in the first direction and/or the second direction include moving and rotation types. This is not limited herein either. Through the cooperation of the first driving assembly **50** and the second driving assembly **60**, the support plate **40** is enabled to move in a larger space range, thereby expanding movement ranges of the lens assembly **20** and the circuit board **30**.

(25) Besides, any one of the first driving assembly **50** and the second driving assembly **60** includes, but is not limited to, a motor, or may be another driving structure that can enable the support plate **40** to move, such as a driving motor, including a driving motor, a transmission mechanism cooperating with the driving motor, and the like.

(26) Therefore, in the camera module **100** according to this embodiment of this application, the support plate **40** is connected to the lens assembly **20** and the circuit board **30** respectively, and the first driving assembly **50** and the second driving assembly **60** cooperate with each other to drive the support plate **40** to move in the first direction and the second direction. When the support plate **40** moves, the support plate **40** can drive the lens assembly **20** and the circuit board **30** to move synchronously, which can prevent the lens assembly **20** from dragging the circuit board **30** during moving, reduce a volume of the overall structure of the camera module **100**, improve the flexibility of the support plate **40**, and expand the movement range of the support plate **40**.

(27) According to an embodiment of this application, the housing **10** includes: a holder **12** and a cover plate **13**. The holder **12** is provided with an accommodation cavity **11** with an opening on a first side, the lens assembly **20** may be arranged in the accommodation cavity **11** and is movable relative to the holder **12**, and the circuit board **30** may be connected to the lens assembly **20** through the opening. The cover plate **13** is arranged on the first side of the holder **12**, and the first driving assembly **50** is arranged on the cover plate **13**. Optionally, a part of the first driving assembly **50** may be arranged on the cover plate **13**, and another part of the first driving assembly **50** may be arranged on the support plate **40** and is movable relative to the cover plate **13**.

(28) In some specific implementations of this application, the support plate **40** includes: a main board **41** and a side plate **42**. The lens assembly **20** and the circuit board **30** are arranged on a first side of the main board **41**, the first driving assembly **50** is at least partially located on a second side of the main board **41**. The side plate **42** is arranged on the first side of the main board **41**, and the second driving assembly **60** is arranged on the side plate **42**. In other words, the support plate **40** is divided into the main board **41** and the side plate **42**, to facilitate mounting of the first driving assembly **50** and the second driving assembly **60**.

(29) According to an embodiment of this application, the main board **41** and the side plate **42** are approximately perpendicular to each other.

(30) For ease of description, it is defined in the following that the camera module **100** is assembled in an up-down direction, a direction close to a viewer is a front side, and a direction away from the viewer is a rear side.

(31) The main board **41** is approximately a rectangular plate and extends in a front-rear direction. A straight line parallel to a length direction of the main board **41** is referred to as a Y axis, a straight line parallel to a width direction of the main board **41** is referred to as an X axis, and a straight line perpendicular to a plane in which the main board **41** is located is referred to as a Z axis. Each part or component of the camera module **100** may be assembled approximately in the Z-axis direction.

(32) As shown in FIG. 3, the lens assembly **20** and the circuit board **30** are located above the main board **41**, and the side plate **42** is located above the main board **41**. A lower end of the side plate **42** is connected to a length side of the main board **41**, and an upper end of the side plate **42** extends upward in the Z axis. The arrangement of the first driving assembly **50** on the main board **41** can enable the support plate **40** to rotate around the X-axis or Y-axis direction. The arrangement of the second driving assembly **60** on the side plate **42** can enable the support plate **40** to rotate around the X-axis or Y-axis direction.

(33) It should be noted that, the foregoing definitions of up, down, the front side, the rear side, the X axis, the Y axis, and the Z axis are merely for ease of description of position relationships or connection relationships of the components of the camera module **100** according to the embodiments of this application, and do not constitute any limitation on the embodiments of this application.

(34) In addition, for the same parts and components in the embodiments of this application, only one of the parts or components in the figures may be marked with a reference numeral, and the reference numeral is also applicable to the other same parts or components.

(35) Further, the circuit board **30** includes: a first board body **31** and a second board body **32**. The first board body **31** is arranged between the lens assembly **20** and the main board **41**, the lens assembly **20** is arranged on a first side of the first board body **31**, and a second side of the first board body **31** is connected to the first side of the main board **41**. The second board body **32** is arranged on the first side of the main board **41**, and is electrically connected to the first board body **31**. The second board body **32** may be a flexible printed circuit board, a conducting wire, or the like. As shown in FIG. 3, the first board body **31** is located behind the second board body **32** and under the lens assembly **20**. When the circuit board **30** and the main board **41** are assembled, lower sides of the first board body **31** and the second board body **32** may be respectively connected to an upper side of the main board **41**. Dividing the circuit board **30** into the first board body **31** and the second board body **32** is conducive to the connection between the circuit board **30** and the lens assembly **20** and the movement of the lens assembly **20** while implementing synchronous movement of the circuit board **30** and the main board **41**.

(36) Optionally, the first board body **31** is a printed circuit board, and the second board body **32** is a flexible printed circuit board. During assembly, the second board body **32** may be folded along an S shape. When the lens assembly **20** moves, the second board body **32** can synchronously expand and contract, thereby expanding the movement range of the lens assembly **20**. Further, the second board body **32** and the first driving assembly **50** are arranged opposite to each other, and the second driving assembly **60** is arranged at a periphery of the second board body **32**. In this way, the space below and at the periphery of the second board body **32** can be fully used, and the defect that the size of the overall structure of the camera module **100** is large because the first driving assembly **50** and the second driving assembly **60** are placed below the lens assembly **20** is avoided.

(37) Further, in a case that the housing **10** further includes a flexible printed circuit board receiving portion **70**, as shown in FIG. 3, the flexible printed circuit board receiving portion **70** may be located in front of the holder **12**. The second board body **32**, the first driving assembly **50**, and the second driving assembly **60** may all be located in the flexible printed circuit board receiving portion **70**, thereby fully using the receiving space of the flexible printed circuit board receiving

portion.

(38) According to an embodiment of this application, a shape of the first board body **31** corresponds to a shape of a surface of a first side of the lens assembly **20**, and a shape of the main board **41** corresponds to shapes of the first board body **31** and the second board body **32**. This improves the stability and reliability of the overall structure when the lens assembly **20** and the circuit board **30** move.

(39) In some specific implementations of this application, the first driving assembly **50** includes: a first magnetic member **51** and a first coil **52**. One of the first magnetic member **51** and the first coil **52** is connected to the cover plate **13**, and the other of the first magnetic member **51** and the first coil **52** is connected to the main board **41**. After being energized, the first coil **52** is movable relative to the first magnetic member **51** to drive the main board **41**. In other words, the first magnetic member **51** may be arranged on the cover plate **13**, and the first coil **52** may be arranged on the main board **41**; or the first magnetic member **51** may be arranged on the support plate **40**, and the first coil **52** may be arranged on the cover plate **13**. For example, as shown in FIG. 5, the first magnetic member **51** is connected to an upper end surface of the cover plate **13**. The first coil **52** is connected to an upper end surface of the main board **41** and a lower end surface of the second board body **32**, and cooperates with the first magnetic member **51**.

(40) It should be noted that, in a case that the first driving assembly **50** includes the first magnetic member **51** and the first coil **52**, the support plate **40** may be of a non-magnetically conductive rigid material. When the first driving assembly **50** operates, the first magnetic member **51** and the first coil **52** cooperate with each other. According to Fleming's left-hand rule, a force perpendicular to a magnetic field direction is generated in the energized first coil **52**, and the main board **41** can be controlled to move when the force acts on the main board **41**.

(41) Further, the first magnetic member **51** has a plate-shaped structure, and is attached onto the cover plate **13**. In other words, the first magnetic member **51** may be a flat coil, and can effectively save space. The first magnetic member **51** is attached onto the cover plate **13**, thereby facilitating the assembly of the first magnetic member **51**. It should be noted that, the first magnetic member **51** may be mounted on the cover plate **13** in another mounting manner, for example, clamping, insertion, or another detachable mounting manner.

(42) In this embodiment of this application, the first coil **52** are two annular coils **521** that are spaced apart on the main board **41**. In a case that there are more than two coils **521**, the balance of forces can be effectively ensured.

(43) Referring to FIG. 4, for example, the two annular coils **521** may respectively be a first annular coil and a second annular coil, and the first annular coil and the second annular coil may share a magnet. The main board **41** may rotate around a direction by controlling energization situations of the first annular coil and the second annular coil.

(44) In this embodiment of this application, the second board body **32** is a folded S-shaped flexible board, and the lower end surface of the second board body **32** is approximately a rectangular component. Length sides of the second board body **32** extend in the Y-axis direction, width sides of the second board body **32** extend in the X-axis direction, and the second board body **32** may be folded approximately in the Z-axis direction.

(45) The first annular coil and the second annular coil are located on the lower end surface of the second board body **32**, and are spaced apart in a length direction of the second board body **32**. The first annular coil and the second annular coil both are an elliptical component that extends approximately in a width direction of the second board body **32**. In a case that forces generated on the first annular coil and the second annular coil are the same, the support plate **40** rotates around the X-axis direction. In a case that the forces generated on the first annular coil and the second annular coil are different, the support plate **40** rotates around the Y axis. In a case that the first annular coil and the second annular coil both are turned on, the balance of forces can be ensured.

(46) According to an embodiment of this application, the camera module **100** further includes a

first position feedback element **80**. A movement position of the main board **41** can be fed back through the first position feedback element **80**. The first position feedback element **80** may be a Hall chip, or the like. This is not limited herein.

(47) Optionally, in a case that the coil **521** is an annular coil, the first position feedback element **80** may be mounted on a hollow structure of the annular coil, thereby saving space.

(48) In some specific implementations of this application, there are two side plates **42**. The two side plates **42** are arranged opposite to each other on the first side of the main board **41**, and each side plate **42** is provided with one second driving assembly **60**. In a case that the main board **41** is in a strip shape, the two side plates **42** may be spaced apart in the width direction of the main board **41**, and each side plate **42** extends in the length direction of the main board **41**.

(49) Further, the second driving assembly **60** includes: a second magnetic member **61** and a second coil **62**. One of the second magnetic member **61** and the second coil **62** is connected to the side plate **42**, and the other of the second magnetic member **61** and the second coil **62** is connected to the housing **10**. After being energized, the second coil **62** is movable relative to the second magnetic member **61** to drive the side plate **42**. In other words, the second magnetic member **61** may be arranged on the side plate **42**, and the second coil **62** may be arranged on the housing **10**; or the second magnetic member **61** may be arranged on the housing **10**, and the second coil **62** may be arranged on the side plate **42**. For example, as shown in FIG. 6, the second magnetic member **61** is arranged on an inner side wall of the housing **10**, and the second coil **62** is arranged on a side of the side plate **42** adjacent to the second board body **32**, and cooperates with the second magnetic member **61**.

(50) After being energized, the second coil **62** is movable relative to the second magnetic member **61** to drive the second board body **32**. A cooperation principle of the second magnetic member **61** and the second coil **62** is the same as a cooperation principle of the first magnetic member **51** and the first coil **52**. This is not described herein again.

(51) According to an embodiment of this application, the camera module **100** further includes a second position feedback element **90**. A movement position of the side plate **42** can be fed back through the second position feedback element **90**. The second position feedback element **90** may be a Hall chip, or the like. This is not limited herein.

(52) Optionally, in a case that the second coil **62** is an annular coil, the second position feedback element **90** may be mounted on a hollow structure of the annular coil, thereby saving space.

(53) It should be noted that, the first driving assembly **50** and the second driving assembly **60** may operate independently, or may operate cooperatively. In a case that the first driving assembly **50** and the second driving assembly **60** cooperate with each other, the support plate **40** can rotate around the X axis and the support plate **40** can rotate around the Y axis.

(54) For example, as shown in FIG. 4, it is set that the first coil **52** is subjected to forces F_1 and F_2 and the second coil **62** is subjected to forces F_3 and F_4 . In a case that directions of F_1 , F_2 , F_3 , and F_4 are the same, the support plate **40** is driven to move, so that the support plate **40** rotates around the X axis. In a case that the directions of F_1 and F_3 are the same, F_1 and F_3 are combined into one group that is represented by $[F_1, F_3]$; and in a case that the directions of F_2 and F_4 are the same, F_2 and F_4 are combined into one group that is represented by $[F_2, F_4]$. In a case that the directions of $[F_1, F_3]$ and $[F_2, F_4]$ are reverse, the support plate **40** is driven to rotate around the Y axis.

(55) Optionally, the second magnetic member **61** has a plate-shaped structure, and is attached onto the side plate **42**. This has advantages of facilitating assembly and saving the mounting space.

(56) An embodiment of this application further provides an electronic device, including the camera module **100** according to any one of the foregoing embodiments. The lens assembly **20** may be electrically connected to the main board **41** of the electronic device through the circuit board **30**, to supply power to the lens assembly **20**.

(57) The electronic device according to this embodiment of this application may be a smart phone, a tablet computer, a wearable device, or the like. This is not limited herein.

(58) In the descriptions of this specification, descriptions using reference terms “an embodiment”, “some embodiments”, “an exemplary embodiment”, “an example”, “a specific example”, or “some examples” mean that specific characteristics, structures, materials, or features described with reference to the embodiment or example are included in at least one embodiment or example of this application. In this specification, schematic descriptions of the foregoing terms do not necessarily point at a same embodiment or example. Moreover, the specific features, structures, materials, or characteristics described may be combined in any one or more embodiments or examples in an appropriate manner.

(59) Although the embodiments of this application have been shown and described, a person of ordinary skill in the art should understand that various changes, modifications, replacements and variations may be made to the embodiments without departing from the principles and spirit of this application, and the scope of this application is as defined by the appended claims and their equivalents.

Claims

1. A camera module, comprising: a housing, internally provided with an accommodation cavity; a lens assembly, movably arranged in the accommodation cavity; a circuit board, connected to the lens assembly; and a gimbal assembly, comprising: a support plate, wherein at least part of the support plate is movably arranged in the accommodation cavity, and the lens assembly and the circuit board are arranged on the support plate; a first driving assembly, wherein the first driving assembly is arranged on the housing, and at least part of the first driving assembly is connected to the support plate to drive the support plate to move in a first direction; and a second driving assembly, wherein the second driving assembly is arranged on the support plate, and at least part of the second driving assembly is connected to the support plate to drive the support plate to move in a second direction; wherein the support plate comprises: a main board, wherein the lens assembly and the circuit board are arranged on a first side of the main board, and the first driving assembly is at least partially located on a second side of the main board; and a side plate, wherein the side plate is arranged on the first side of the main board, and the second driving assembly is arranged on the side plate.
2. The camera module according to claim 1, wherein the housing comprises: a holder, provided with the accommodation cavity with an opening on a first side; and a cover plate, wherein the cover plate is arranged on the first side of the holder, and the first driving assembly is arranged on the cover plate.
3. The camera module according to claim 1, wherein the circuit board comprises: a first board body, wherein the first board body is arranged between the lens assembly and the main board, the lens assembly is arranged on a first side of the first board body, and a second side of the first board body is connected to the first side of the main board; and a second board body, wherein the second board body is arranged on the first side of the main board, and the second board body and the first board body are electrically connected to each other.
4. The camera module according to claim 3, wherein the first board body is a printed circuit board, and the second board body is a flexible printed circuit board.
5. The camera module according to claim 4, wherein a shape of the first board body corresponds to a shape of a surface of a first side of the lens assembly, and a shape of the main board corresponds to shapes of the first board body and the second board body.
6. The camera module according to claim 3, wherein two side plates are provided, the two side plates are arranged opposite to each other on the first side of the main board, and each of the side plates is provided with one second driving assembly.
7. The camera module according to claim 6, wherein the second driving assembly comprises: a second magnetic member and a second coil, wherein one of the second magnetic member and the

second coil is connected to the side plate, the other of the second magnetic member and the second coil is connected to the second board body, and after being energized, the second coil is movable relative to the second magnetic member to drive the second board body.

8. The camera module according to claim 7, wherein the second magnetic member has a plate-shaped structure and is attached onto the side plate.

9. The camera module according to claim 1, wherein the first driving assembly comprises a first magnetic member and a first coil, one of the first magnetic member and the first coil is connected to the cover plate, and the other of the first magnetic member and the first coil is connected to the main board, and after being energized, the first coil is movable relative to the first magnetic member to drive the main board.

10. The camera module according to claim 9, wherein the first magnetic member has a plate-shaped structure, and is attached onto the cover plate.

11. An electronic device, comprising a camera module; wherein the camera module comprises: a housing, internally provided with an accommodation cavity; a lens assembly, movably arranged in the accommodation cavity; a circuit board, connected to the lens assembly; and a gimbal assembly, comprising: a support plate, wherein at least part of the support plate is movably arranged in the accommodation cavity, and the lens assembly and the circuit board are arranged on the support plate; a first driving assembly, wherein the first driving assembly is arranged on the housing, and at least part of the first driving assembly is connected to the support plate to drive the support plate to move in a first direction; and a second driving assembly, wherein the second driving assembly is arranged on the support plate, and at least part of the second driving assembly is connected to the support plate to drive the support plate to move in a second direction; wherein the support plate comprises: a main board, wherein the lens assembly and the circuit board are arranged on a first side of the main board, and the first driving assembly is at least partially located on a second side of the main board; and a side plate, wherein the side plate is arranged on the first side of the main board, and the second driving assembly is arranged on the side plate.

12. The electronic device according to claim 11, wherein the housing comprises: a holder, provided with the accommodation cavity with an opening on a first side; and a cover plate, wherein the cover plate is arranged on the first side of the holder, and the first driving assembly is arranged on the cover plate.

13. The electronic device according to claim 11, wherein the circuit board comprises: a first board body, wherein the first board body is arranged between the lens assembly and the main board, the lens assembly is arranged on a first side of the first board body, and a second side of the first board body is connected to the first side of the main board; and a second board body, wherein the second board body is arranged on the first side of the main board, and the second board body and the first board body are electrically connected to each other.

14. The electronic device according to claim 13, wherein the first board body is a printed circuit board, and the second board body is a flexible printed circuit board.

15. The electronic device according to claim 14, wherein a shape of the first board body corresponds to a shape of a surface of a first side of the lens assembly, and a shape of the main board corresponds to shapes of the first board body and the second board body.

16. The electronic device according to claim 13, wherein two side plates are provided, the two side plates are arranged opposite to each other on the first side of the main board, and each of the side plates is provided with one second driving assembly.

17. The electronic device according to claim 11, wherein the first driving assembly comprises a first magnetic member and a first coil, one of the first magnetic member and the first coil is connected to the cover plate, and the other of the first magnetic member and the first coil is connected to the main board, and after being energized, the first coil is movable relative to the first magnetic member to drive the main board.

18. The electronic device according to claim 17, wherein the first magnetic member has a plate-shaped structure, and is attached onto the cover plate.
