

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408732
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Weeks; John Maxwell et al.

Footwear heel counter for easier foot entry or removal

Abstract

A shoe includes a heel counter with a heel cup. The heel cup may be uniformly molded with an upper portion, midportion, and a lower portion. The upper portion has a smaller mediolateral length than the midportion, and a thickness of the heel cup decreases from a peripheral portion of the heel cup toward a central region of the midportion. The central region of the midportion provides flexibility of the heel cup, and the rearmost portion of the heel cup has an overall vertical S wave cross-sectional shape.

Inventors: Weeks; John Maxwell (Los Angeles, CA), Kelley; Scott (Redondo Beach, CA), Chuang; Frank F (Cypress, CA), Liao; Pei-Chun (Torrance, CA), Tja; Johnson (Foshan, CN), Xie; Hui (Dongguan, CN), Stockbridge; Kurt (Palos Verdes Estates, CA)

Applicant: Skechers U.S.A., Inc. II (Manhattan Beach, CA)

Family ID: 85987889

Assignee: Skechers U.S.A., Inc. II (Manhattan Beach, CA)

Appl. No.: 18/639764

Filed: April 18, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240381977 A1	Nov. 21, 2024

Related U.S. Application Data

continuation parent-doc US 18199262 20230518 US 12011064 child-doc US 18639764

Publication Classification

Int. Cl.: A43B23/08 (20060101); A43B11/00 (20060101); A43B21/24 (20060101)

U.S. Cl.:

CPC A43B23/08 (20130101); A43B11/00 (20130101); A43B21/24 (20130101); A43B23/088 (20130101);

Field of Classification Search

CPC: A43B (23/28); A43B (23/17); A43B (23/08); A43B (11/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
863549	12/1906	Metz	N/A	N/A
912579	12/1908	Krech et al.	36/68	A43B 23/28
1028586	12/1911	McMullan	36/58.5	A43B 23/28
1174619	12/1915	Scholl	36/68	A43B 23/28
1812622	12/1930	Costello	36/58.5	A43B 23/28
2275191	12/1941	Schwartz	36/DIG.1	A43B 23/28
3768182	12/1972	Powers	36/114	A43B 23/227
4559722	12/1984	Norton	36/105	A43B 23/0235
4594798	12/1985	Autry	36/114	A43B 23/17
4608769	12/1985	Sturlaugson	36/51	A43B 11/00
4622764	12/1985	Boulrier	N/A	N/A
5894684	12/1998	Sand et al.	N/A	N/A
6041524	12/1999	Brooks	N/A	N/A
7373742	12/2007	Murphy	36/89	A43B 5/1616
9730494	12/2016	Feinstein	N/A	N/A
10455898	12/2018	Orand et al.	N/A	N/A
10687586	12/2019	Sullivan	N/A	N/A
11000091	12/2020	Kyle	N/A	N/A
2002/0008124	12/2001	Runge	N/A	N/A
2002/0066213	12/2001	Wells	223/118	A43B 3/0084
2002/0162250	12/2001	Campbell	36/173	A43B 23/17
2003/0121181	12/2002	Chang	36/77R	A43D 11/003
2005/0229436	12/2004	Bock	36/89	A43B 5/1691
2010/0319218	12/2009	Auger et al.	N/A	N/A
2011/0078921	12/2010	Greene et al.	N/A	N/A
2012/0180338	12/2011	Lin	36/56	A43B 9/02

2012/0198721	12/2011	Cavaliere	N/A	N/A
2012/0216422	12/2011	Ikezawa et al.	N/A	N/A
2012/0317839	12/2011	Pratt	N/A	N/A
2014/0090275	12/2013	Rackiewicz	36/102	A43B 23/047
2014/0259781	12/2013	Sakai	N/A	N/A
2014/0283410	12/2013	Marvin et al.	N/A	N/A
2014/0345158	12/2013	Fox	12/142R	A43B 23/28
2015/0113830	12/2014	Dillinger	12/147R	A43B 23/28
2015/0150339	12/2014	Van Hook	N/A	N/A
2015/0289589	12/2014	Nishiwaki	36/92	A43B 7/141
2016/0095383	12/2015	Surace	36/93	A43B 23/088
2016/0183635	12/2015	Mancini	36/58.6	A43B 23/28
2017/0303632	12/2016	Pratt	N/A	A43B 3/248
2018/0110288	12/2017	Hatfield et al.	N/A	N/A
2018/0110292	12/2017	Beers et al.	N/A	N/A
2018/0206588	12/2017	Pratt	N/A	A43B 23/28
2019/0011693	12/2018	Mizukami	N/A	N/A
2019/0045884	12/2018	Uda	N/A	A43B 23/0205
2019/0297991	12/2018	Bongers	N/A	A43B 23/042
2019/0297999	12/2018	Nakaya et al.	N/A	N/A
2020/0085136	12/2019	Pratt et al.	N/A	N/A
2020/0170348	12/2019	Beers et al.	N/A	N/A
2020/0196703	12/2019	Hopkins	N/A	A43B 23/027
2020/0196709	12/2019	Orand et al.	N/A	N/A
2020/0196787	12/2019	Dament	N/A	A47G 25/82
2020/0205511	12/2019	Hopkins et al.	N/A	N/A
2020/0253333	12/2019	Kilgore et al.	N/A	N/A
2020/0305552	12/2019	Cheney et al.	N/A	N/A
2020/0345098	12/2019	Xanthos et al.	N/A	N/A
2020/0345105	12/2019	Beers et al.	N/A	N/A
2020/0359745	12/2019	Tresser	N/A	A43B 7/24
2021/0068493	12/2020	Pratt	N/A	A43B 23/28
2021/0204644	12/2020	Kyle	N/A	N/A
2021/0282495	12/2020	Davis et al.	N/A	N/A
2021/0378356	12/2020	Cheney et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2017254675	12/2017	AU	N/A
202302394	12/2023	CL	N/A
202302395	12/2023	CL	N/A
202302396	12/2023	CL	N/A
941	12/2023	CL	N/A
945	12/2023	CL	N/A

2925168	12/2006	CN	N/A
101036540	12/2006	CN	N/A
100399958	12/2007	CN	N/A
201898951	12/2010	CN	N/A
102365035	12/2011	CN	N/A
102450770	12/2011	CN	N/A
104379014	12/2014	CN	N/A
104473371	12/2014	CN	N/A
204259964	12/2014	CN	N/A
105533927	12/2015	CN	N/A
105661719	12/2015	CN	N/A
104105424	12/2015	CN	N/A
107581703	12/2017	CN	N/A
108697196	12/2017	CN	N/A
108936966	12/2017	CN	N/A
108968234	12/2017	CN	N/A
208403416	12/2018	CN	N/A
109393642	12/2018	CN	N/A
109890236	12/2018	CN	N/A
107397292	12/2019	CN	N/A
106455754	12/2019	CN	N/A
212306984	12/2020	CN	N/A
112568548	12/2020	CN	N/A
112586837	12/2020	CN	N/A
113301824	12/2020	CN	N/A
215455754	12/2021	CN	N/A
215532079	12/2021	CN	N/A
114190654	12/2021	CN	N/A
114228214	12/2021	CN	N/A
114504166	12/2021	CN	N/A
114504167	12/2021	CN	N/A
114504168	12/2021	CN	N/A
216466141	12/2021	CN	N/A
114601230	12/2021	CN	N/A
114617336	12/2021	CN	N/A
109512082	12/2021	CN	N/A
114747839	12/2021	CN	N/A
217136975	12/2021	CN	N/A
217471364	12/2021	CN	N/A
217524082	12/2021	CN	N/A
217524104	12/2021	CN	N/A
217658374	12/2021	CN	N/A
19611797	12/1996	DE	N/A
10019865	12/2000	DE	N/A
1212954	12/2001	EP	N/A
2386217	12/2010	EP	N/A
2438826	12/2011	EP	N/A
3649881	12/2019	EP	N/A
3393290	12/2019	EP	N/A
4230076	12/2022	EP	A43B 11/02

764640	12/1955	GB	N/A
2321585	12/1997	GB	N/A
1999127907	12/1998	JP	N/A
11-187906	12/1998	JP	N/A
1999187906	12/1998	JP	N/A
2001011275	12/2000	JP	N/A
2009281615	12/2008	JP	N/A
2011083432	12/2010	JP	N/A
2012218004	12/2011	JP	N/A
3219334	12/2017	JP	N/A
2019033797	12/2018	JP	N/A
2019533526	12/2018	JP	N/A
2020501579	12/2019	JP	N/A
WO2022130537	12/2021	JP	N/A
1722701	12/2021	JP	N/A
7317385	12/2022	JP	N/A
101801510	12/2016	KR	N/A
102016091	12/2018	KR	N/A
1020200117515	12/2019	KR	N/A
2000762	12/2008	NL	N/A
201603738	12/2015	TW	N/A
M577255	12/2018	TW	N/A
202218573	12/2021	TW	N/A
202224592	12/2021	TW	N/A
M654731	12/2023	TW	N/A
2009154350	12/2008	WO	N/A
2013054358	12/2012	WO	N/A
2018155804	12/2017	WO	N/A
2018217455	12/2017	WO	N/A
2020176653	12/2019	WO	N/A
2021111529	12/2020	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion mailed Mar. 1, 2023 for PCT Application No. PCT/US2022/46726. cited by applicant

Examination report No. 1 for Australia patent application 2022362306, mailed Jul. 14, 2023. cited by applicant

Examination report No. 1 for Australia patent application 2023203319, mailed Jul. 14, 2023. cited by applicant

Examination report No. 1 for Canada patent application 3202848, mailed Jul. 31, 2023. cited by applicant

Office Action for TW113203112 dated May 1, 2025. cited by applicant

Notice of Preliminary Rejection_KR20247000010_dated Mar. 21, 2025. cited by applicant

Notice of Preliminary Rejection_KR20237000036_dated Mar. 21, 2025. cited by applicant

Office Action for FI20235903 dated Mar. 14, 2025. cited by applicant

Office Action for CH202401861 dated Mar. 19, 2025. cited by applicant

Office Action for CL202401866 dated Mar. 19, 2025. cited by applicant

Office Action for KR20247000012 dated Apr. 21, 2025. cited by applicant

Office Action for KR20247000014 dated Apr. 22, 2025. cited by applicant

Office Action for KR20247000016 dated Apr. 24, 2025. cited by applicant

Office Action for KR20247000015 dated Apr. 23, 2025. cited by applicant
Examination and Search Report for AEP60022202023 dated Apr. 27, 2025. cited by applicant
Office Action for JP 2024-076944 dated Dec. 5, 2024. cited by applicant
Office Action for JP 2024-076945 dated Nov. 11, 2024. cited by applicant
Office Action for JP 2024-076946 dated Sep. 2, 2024. cited by applicant
Office Action for No. 20230930 dated Oct. 15, 2024. cited by applicant
Office Action for PA 2024 70056 dated May 23, 2024. cited by applicant
Office Action for PT 119410 dated Oct. 31, 2024. cited by applicant
Office Action for PT 119411 dated May 13, 2024. cited by applicant
Office Action for PT 119412 dated May 13, 2024. cited by applicant
Office Action for PT 119413 dated May 13, 2024. cited by applicant
Office Action for PT 119414 dated May 13, 2024. cited by applicant
Office Action for PT 2023064568 dated Sep. 26, 2024. cited by applicant
Office Action for SE 2450381-5 dated Sep. 12, 2024. cited by applicant
Office Action for TW 113200202 dated Aug. 22, 2024. cited by applicant
Office Action for U20234070 dated Sep. 5, 2023. cited by applicant
Office Action for U20234070 dated Jan. 25, 2024. cited by applicant
Office Action for U20234088 dated Sep. 5, 2023. cited by applicant
Office Action for U20234089 dated Sep. 5, 2023. cited by applicant
Office Action for U20244001 dated May 15, 2024. cited by applicant
Office Action for U20244021 dated Apr. 12, 2024. cited by applicant
Office Action for U20244022 dated Apr. 12, 2024. cited by applicant
Office Action for U20244023 dated Apr. 12, 2024. cited by applicant
Office Action for U20244024 dated Apr. 12, 2024. cited by applicant
Office Action for U20244025 dated Apr. 12, 2024. cited by applicant
Office Action for UM 112204837 dated Jun. 28, 2024. cited by applicant
Office Action for PA 2024 70057 dated May 27, 2024. cited by applicant
Office Action for PT 119409 dated May 13, 2024. cited by applicant
Office Action for PT 119410 dated May 13, 2024. cited by applicant
Office Action for JP 2024-076945 dated Sep. 5, 2024. cited by applicant
Office Action for SE 2550020 dated Jan. 30, 2025. cited by applicant
Office Action for TW113203110 dated Feb. 11, 2025. cited by applicant
Office Action for SE25500216 dated Jan. 30, 2025. cited by applicant
Office Action for EPO 24155788.3 dated Feb. 13, 2025. cited by applicant
Office Action for SE25500224 dated Jan. 3, 2025. cited by applicant
Examination and Search Report of CN Application No. 2021113470414 and Translation. cited by applicant
Examination and Search Report of CN Application No. 2022102356725 and Translation. cited by applicant
Examination and Search Report of CN Application No. 2022102433153 and Translation. cited by applicant
Examination and Search Report of Finland No. 20235646. cited by applicant
Examination and Search Report of Finland No. 20235905. cited by applicant
Examination Report of Sweden No. 23507387. cited by applicant
Examination Report of Sweden No. 23508062. cited by applicant
Examination Report of Sweden No. 23508070. cited by applicant
Examination Report of Taiwan Application No. 112204839 and Translation. cited by applicant
Examination Report of UK Application No. GB23092695. cited by applicant
PCTUS2022046726—IPRP. cited by applicant
Examination Report No. 1 for Australia patent Application 2023203320. cited by applicant

Examination Report No. 2 for Canada patent Application 3202848. cited by applicant
Registered Community Design (RCD) 008849293-0006. cited by applicant
Registered Community Design (RCD) 0015002956-0001. cited by applicant
U.S. Appl. No. 60/415,242, Mei et al. cited by applicant
U.S. Appl. No. 60/415,244, Pete. cited by applicant
U.S. Appl. No. 60/415,244, Thomas. cited by applicant
U.S. Appl. No. 60/415,240, Zdravko. cited by applicant
Office Action and Search Report for 20245362 dated Jun. 20, 2024. cited by applicant
Office Action and Search Report for 20245364 dated Jun. 19, 2024. cited by applicant
Office Action and Search Report for 20245366 dated Jun. 19, 2024. cited by applicant
Office Action and Search Report for 20245367 dated Jun. 19, 2024. cited by applicant
Office Action and Search Report for 20245374 dated Jun. 19, 2024. cited by applicant
Office Action and Search Report for 2450280-9 dated Apr. 24, 2024. cited by applicant
Office Action for 112118133 dated Aug. 1, 2024. cited by applicant
Office Action for 112204837 dated Aug. 23, 2023. cited by applicant
Office Action for 112210168 dated Dec. 7, 2023. cited by applicant
Office Action for 112210175 dated Oct. 31, 2023. cited by applicant
Office Action for 113200202 dated Mar. 6, 2024. cited by applicant
Office Action for 113203110 dated May 17, 2024. cited by applicant
Office Action for 113203111 dated Apr. 30, 2024. cited by applicant
Office Action for 113203112 dated May 6, 2024. cited by applicant
Office Action for 20 2022 002 992.6 dated Apr. 12, 2024. cited by applicant
Office Action for 20 2022 002 993.4 dated Apr. 12, 2024. cited by applicant
Office Action for 2021113470414 dated Jun. 12, 2024. cited by applicant
Office Action for 2022102356725 dated Jun. 12, 2024. cited by applicant
Office Action for 2022102433153 dated Jun. 18, 2024. cited by applicant
Office Action for 202322423343.6 dated Apr. 2, 2024. cited by applicant
Office Action for 523450973 dated May 31, 2024. cited by applicant
Office Action for 523450976 dated May 31, 2024. cited by applicant
Office Action for BA 2023 00036 dated Oct. 23, 2023. cited by applicant
Office Action for BA 2024 00017 dated May 15, 2024. cited by applicant
Office Action for BA 2024 00018 dated May 15, 2024. cited by applicant
Office Action for BA 2024 00019 dated May 15, 2024. cited by applicant
Office Action for BA 2024 00020 dated May 15, 2024. cited by applicant
Office Action for CH000761/2023 dated Sep. 13, 2023. cited by applicant
Office Action for CH000761/2023 dated Mar. 8, 2024. cited by applicant
Office Action for CH000761/2023 dated Jul. 9, 2024. cited by applicant
Office Action for CL 202302373 dated Oct. 18, 2024. cited by applicant
Office Action for CL 202302394 dated Jun. 19, 2024. cited by applicant
Office Action for CL 202302394 dated Oct. 2, 2024. cited by applicant
Office Action for CL 202302398 dated Aug. 22, 2024. cited by applicant
Office Action for CL 202302399 dated Sep. 27, 2024. cited by applicant
Office Action for DE 11 2022 000 220.4 dated Sep. 18, 2024. cited by applicant
Office Action for DK BA 2024 00019 dated Jul. 30, 2024. cited by applicant
Office Action for DK PA 2024 70112 dated Jul. 1, 2024. cited by applicant
Office Action for DK PA 2024 70113 dated Jul. 1, 2024. cited by applicant
Office Action for EG/P/2023/1867. cited by applicant
Office Action for FI U20244042 dated Sep. 5, 2024. cited by applicant
Office Action for GB2309269.5 dated Nov. 28, 2023. cited by applicant
Office Action for IL302899 dated Jul. 21, 2024. cited by applicant

Office Action for IL302945 dated Jul. 21, 2024. cited by applicant
Office Action for JP 2023-545807 dated Sep. 2, 2024. cited by applicant
Office Action for JP 2024-076941 dated Sep. 17, 2024. cited by applicant
Office Action for JP 2024-076942 dated Sep. 2, 2024. cited by applicant
Office Action for JP 2024-076943 dated Sep. 2, 2024. cited by applicant
Office Action for JP 2024-076943 dated Nov. 11, 2024. cited by applicant
Office Action for JP 2024-076944 dated Sep. 2, 2024. cited by applicant

Primary Examiner: Pierorazio; Jillian K

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a divisional application of U.S. application Ser. No. 18/199,262, filed on May 18, 2023, which claims the benefit of priority to International Application No. PCT/US2022/46726, filed on Oct. 14, 2022, which claims the benefit of priority to U.S. Provisional Patent No. 63/256,521, filed on Oct. 15, 2021. These applications are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

(1) The present disclosure generally relates to a heel counter or a component of a heel counter of a shoe, and in particular a heel counter that is designed to allow for easier entry of the wearer's foot into the shoe.

BACKGROUND

(2) Conventionally, when donning footwear such as sports shoes, the user must often use one or both hands or operate a shoehorn separate from the shoe to properly insert the foot into the shoe and secure the quarter from collapsing under the heel.

BRIEF SUMMARY OF DISCLOSURE

(3) Aspects of this invention relate to an article of footwear that has a structure capable of distortion to support easier foot insertion.

(4) In one aspect of the invention, a heel cup may be uniformly molded with an upper portion, midportion, and lower portion, and the upper portion has a smaller mediolateral length than the midportion. The midportion and lower portion may form a concave structure configured to receive the heel. The upper portion of the heel cup has a first configuration in its native state and is capable of distorting into a second configuration under a load of a user's foot when the user is donning the footwear. In the second configuration, at least part of the upper portion is lowered relative to the first configuration and the upper portion is capable of returning to the first configuration after the load of the user's foot is removed. The midportion may include a peripheral portion having a first thickness and a central portion having a second thickness, and the second thickness is less than the first thickness.

(5) In another aspect of the invention, the upper portion of a heel cup has a first configuration in its native state and is capable of distorting into a second configuration under a load of a user's foot when the user is donning the footwear and the heel cup is capable of returning to the first configuration after the load of the user's foot is removed. In the first configuration, the upper portion has a downward incline with a first angle relative to a vertical line that is normal to a horizontal surface of the floor, and the upper portion in the second configuration has an incline with a second angle greater than the first angle. Additionally, in the second configuration, a lower region of a central portion of the heel cup extends outward in a direction away from the shoe opening that causes the shoe opening to widen along the mediolateral direction.

(6) In another aspect of the invention, an upper of an article of footwear includes a U-shaped foamed ankle collar that is substantially tubular in shape and forms the topmost region of the foot receiving shoe opening. The foamed ankle collar may extend at least partially around and over the foot receiving shoe opening and may be compressed by the user's heel during foot insertion. The ankle collar may exert pressure on the user's ankle once the foot is inserted into the footwear. The ankle collar may also have a flattened region along its length forming a downward angle from the topmost region toward the front of the article of footwear.

(7) In another aspect of the invention, a heel counter support is located on the upper and above the sole structure. The heel counter support may have at least two hollow receptacles with backward angles. Additionally, each one of the two hollow receptacles receive one end of a compressible component. The compressible component has a first configuration in its native state, and the compressible component is capable of distorting into a second configuration under a load of a user's foot when the user is donning the footwear and is capable of automatically returning to the first configuration after the user's foot is fully inserted into the footwear.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) By way of example only, selected embodiments and aspects of the present invention are described below. Each description refers to a figure ("FIG.") which shows the described matter. Some figures shown in drawings or photographs that accompany this specification may be for footwear that is for either the left or right foot. Each figure includes one or more identifiers for one or more part(s) or element(s) of the invention.
- (2) Various embodiments are described with reference to the drawings, in which:
- (3) FIG. 1 is a front view of a compressible heel cup.
- (4) FIG. 2 is a perspective view of the compressible heel cup of FIG. 1.
- (5) FIG. 3 is a side view of the compressible heel cup of FIG. 1.
- (6) FIGS. 4A and 4B are a side-by-side front perspective view of the compressible heel cup of FIG. 1 in its compressed configuration (4A) and its uncompressed configuration (4B).
- (7) FIGS. 4C and 4D are a side-by-side top view of the compressible heel cup of FIG. 1 placed within a shoe in its compressed configuration (4C) and its uncompressed configuration (4D).
- (8) FIG. 5 is a front view of a heel cup configured to have a series of crisscross beams.
- (9) FIG. 6A is a schematic illustration of a cross-section of arc lengths of the rearmost portion of the heel cup of FIG. 1.
- (10) FIG. 6B is cross-sectional view of the heel cup of FIG. 1 taken at lines 6-6 in FIG. 1.
- (11) FIG. 7 is a side view of a heel counter with a heel cup located in the interior of the heel counter.
- (12) FIG. 8 is a top view of the heel counter of FIG. 7.
- (13) FIG. 9 is a perspective view of the heel counter of FIG. 7.
- (14) FIG. 10 is a cross-sectional view of the heel counter of FIG. 8 taken at lines 10-10 in FIG. 8.
- (15) FIG. 11 is a perspective view of a shoe with a heel counter incorporating a rigid heel cup.
- (16) FIG. 12 is a side view of the shoe of FIG. 11.
- (17) FIG. 13 is a rear view of the shoe of FIG. 11.
- (18) FIG. 14 is a bottom view of a tongue and an instep support.
- (19) FIG. 15 is a perspective view of a shoe with a cushioned lining.
- (20) FIG. 16 is a side view of the cushioned lining of FIG. 15.
- (21) FIG. 17 is a perspective view of the cushioned lining of FIG. 15.
- (22) FIG. 18 is a top view of the cushioned lining of FIG. 15.
- (23) FIG. 19 is a cross-sectional view of the cushioned lining of FIG. 18 taken at lines 19-19, in

FIG. 18.

(24) **FIG. 20A** is a lateral view of a shoe with a heel counter support.

(25) **FIG. 20B** is a perspective view of a shoe with a heel counter support.

(26) **FIG. 20C** is a rear view of the shoe of **FIG. 20A**.

(27) **FIG. 21** is a perspective view of the bottom of the upper of the shoe of **FIGS. 20A-20C**.

(28) **FIG. 22** is a perspective view of the sole and heel counter support of the shoe of **FIGS. 20A-20C**.

DETAILED DESCRIPTION

(29) A shoe may comprise a sole and an upper. The sole may comprise an outsole, a midsole, and/or an integrally formed outsole and midsole. The upper may comprise a toe box, a vamp, a tongue, a medial quarter, a lateral quarter, and a heel counter. The shoe has a forefoot portion, a rear portion, a medial side and a lateral side. The upper may comprise an exterior layer, interior layers or interior structure, and/or an inner lining. The upper may form a shoe opening that is capable of receiving a user's foot when the user is donning the shoe.

(30) The heel counter or rear portion of the upper may comprise a structure(s) that enables easier insertion of the foot into the shoe opening. The structure(s) may also support easier removal of the foot. The heel counter or rear portion of the upper may further have a transient widening when the user is donning or removing the shoe. The widening of the shoe opening may be initiated by the user placing a load on the heel counter or rear portion of the upper that may be exerted by the user's foot with minimal to no assistance by the user's hands. In other embodiments of the invention, the heel counter may be compressible when placed under sufficient load and return to its uncompressed state. The lowering of the heel counter may also allow easier insertion of the user's foot. Once a foot is inserted into the shoe, the heel counter may have a compressible layer, such as a foam component, that secures or enhances securement of the foot during user's normal wear of the shoe.

(31) **Compressible Heel Cup.** Referring to the embodiments of **FIGS. 1-10** a heel counter **32** may comprise a compressible heel cup **52** which may be an interior component of the upper **16**, a portion of the inner lining **46** or an attachment adjacent to the inner lining **46** of the upper **16** such that the heel cup **52** makes contact with the foot, or a portion of the exterior layer **42** of the upper **16** or an attachment of an outer surface of the exterior layer **42** of the upper **16**.

(32) Referring to the exemplary embodiment of **FIGS. 1-4**, the heel cup **52** has a shape substantially corresponding to a heel covering and having a profile resembling a pear-like shape. The heel cup has a mediolateral width near the heel cup collar **84** that is less than the mediolateral width of the lower portion **54** as shown in **FIGS. 1-2**

(33) As shown in **FIG. 2**, the inner wall **66** of the upper portion **64** of the heel cup at the rearmost portion of the heel cup may have a downward incline of between 0 to 90 degrees relative to a vertical line **86** that is normal to the horizontal surface **88** of the floor. In this exemplary embodiment, the inner wall **66** of the upper portion **64** may have a downward incline of 30 degrees. The inner wall **66** of the upper portion **64** of the heel cup **52** may also have a convex curvature facing toward the shoe opening **48**. The top portion of the convex curvature has the downward incline **A1** of 30 degrees. The lower portion of the convex curvature extends just above the portion of the heel cup **52** that receives the heel. The lower portion of the convex curvature may have a downward incline less than the downward incline of **A1** and gradually decreases as it approaches an incline equal to the vertical line **86**. The heel cup **52** has a concave curvature that surrounds the rear portion of the heel. The medial and lateral sides of the heel cup **52** may also extend and form support of part of the quarter and even as far as the vamp.

(34) The thickness of the heel cup **52** may be reduced at various locations. The top edge line **68** may have a tapering of the inner surface of the heel cup **52** and outer surface of the heel cup **52**. The heel cup **52** may have increased thickness **T1** along the other perimeter edges, such as 2 to 3 mm. In another exemplary embodiment, the thickness **T1** may be reduced in certain areas to provide greater flexibility to the heel cup **52** when donning or removing the shoe **12**. In one

embodiment, the thickness T1 of the heel cup 52 may decrease gradually from a peripheral portion 70 forming an area at the periphery of the heel cup 52 toward the central portion or region 50 of the mid-portion 58. The minimum thickness T1 in the central region 50 of the mid-portion 58 may be approximately, but not limited to $\frac{1}{4}$ to $\frac{1}{6}$ the thickness relative to the thickest portions at the periphery of heel cup 52, such as 0.5 to 1 mm. The thickest region of the top portion may be greater than the thickest region of the bottom portion. The reduced thickness T1 of the central region of the mid-portion 58 may allow for the heel cup 52 to compress under sufficient load. In an alternate embodiment, the thickness T1 may be reduced across the entire mediolateral portion or in multiple regions such as regions in the mid-portion 58 and/or regions of the upper portion 64. The thinner regions may provide increased flexibility and bending of the heel cup 52 which provides the necessary compressibility under the load of a user's foot such as during the donning of a shoe 12. Such compression may allow the upper portion 64 and/or the mid-portion 58 of the heel cup 52 to move rearward and widen the shoe opening 48 to allow easier entry of the foot. The heel cup 52 is capable of distortion from a first configuration in its native state, to a second configuration under a load of a user's foot when the user is donning the footwear. For example, the heel cup 52 may be partially compressed such that the upper portion 64 and/or mid-portion 58 of the heel cup 52 is lowered sufficiently to allow the insertion of the user's foot. See for example FIGS. 4A and 4C. Once the user's foot is inserted into the shoe 12, the heel cup 52 may return to its uncompressed configuration.

(35) Further to this embodiment, when a user dons the shoe 12, the top portion of the convex curvature of the heel cup 52 or the uppermost segment of the heel counter 32 of the shoe 12 may be lowered and extend backward away from the foot as the heel counter 32 is compressed as shown in FIG. 4A. This action allows the user's foot to be inserted into the shoe opening 48 with a reduced degree of plantar flexion. During compression of the heel cup 52, portions of the heel cup 52 may move forward toward the direction of the forefoot portion. The distortion of the heel cup 52 may include the attached heel counter 32 widening with the medial and lateral sides of the heel cup moving outward thereby widening the opening of the shoe. The mediolateral widening of the shoe opening 48 allows easier entry such as easier insertion of the forefoot portion of the user's foot. In one exemplary embodiment, the shoe opening of 7.5 cm may widen up to 4 cm or about 50%. See FIGS. 4C and 4D. The widening may be less or more depending on the size of the shoe and the flexibility of the heel cup. In some shoes, the desired widening may be less or greater depending on the needs of securement and use.

(36) In an exemplary embodiment of the heel cup 52 as shown in FIGS. 1-4, the thickness T1 of a heel cup 52 made of a polymer material, such as Dupont Hytrel, may range from 0.4 millimeters to 4 millimeters. The range of thickness T1 of the heel cup may be thinner or thicker at various regions depending on the desired elastic and durable properties of the material. For example, the midpoint region may be thinner than the surrounding regions, and in particular a central portion may be thinner as shown in FIG. 6B. The central portion may be spaced away from the medial and lateral edges wherein the peripheral edges may have a greater thickness. Other suitable materials may include other thermoplastic elastomers or other polymers capable of providing the compressible characteristics of the heel cup.

(37) In another exemplary embodiment, the heel cup may be configured to have a series of crisscross beams that form an egg crate like configuration. FIG. 5 shows an exemplary embodiment with beams that are in a diagonal configuration. In an alternate embodiment, the beams may also be in a vertical and lateral configuration. The apertures between the beams may be approximately uniformly sized. The beams may be uniform in dimensions or vary in thickness and width. Beams that are thinner or less wide may be used to enhance flexibility and compressibility in designated locations while thicker or wider beams provide varying degrees of rigid support. For example, the beams may be thinner in the mid-portion, and in particular, the central portion of the mid-portion that is spaced away from the edges. The surrounding beams may be thicker than the central portion.

The central portion may allow for greater flexibility in order to distort under a load.

(38) In an exemplary embodiment, the rearmost portion of the heel cup **52** may have an overall vertical cross-sectional shape that resembles approximately an S wave as shown on a cross-sectional diagram of FIG. **6A**. The upper and lower portions of the S wave may be differentiated at the point **P1** through a horizontal plane, i.e. the midline **90**, which is drawn between the upper arc and lower arc ends of the S wave and intersects the heel counter **32** and the inflection point of the S wave. The amplitude (A.sub.U) and width (W.sub.U) of arc of the upper portion of the S wave may be different than the amplitude (A.sub.L) and width (W.sub.L) of the lower arc of the lower portion of the S wave. In the exemplary embodiment, the W.sub.U is approximately 0.44 times that of the W.sub.L. The A.sub.U is approximately 1/3 that of the A.sub.L. In one possible embodiment, the W.sub.U is approximately 2 centimeters and the W.sub.L is approximately 4.5 centimeters. The A.sub.U is roughly 3 millimeters and the A.sub.L is roughly 9 millimeters. The S configuration decreases both in A.sub.U/A.sub.L and W.sub.U/W.sub.L in the cross-sections in the areas extending from the rearmost portion's cross-section of the heel cup **52** and may only consist of the lower portion arc along the medial and lateral sides of the heel cup **52**. The measurements at the rearmost portion of the heel cup **52** of the exemplary embodiment are intended to be exemplary.

(39) The central region of the mid-portion of the heel cup may have a single aperture or a plurality of apertures. Just as the central region of the mid-portion may be constructed with less material than the maximum thickness of the collar and/or the maximum thickness of the base, the central region of the mid-portion of the heel cup may be constructed with a material of greater flexibility than the material forming its periphery. The resulting effects of the central region comprising a single aperture, a plurality of apertures, a lesser thickness, and/or a material of greater flexibility, may serve to facilitate entry and removal of the user's foot from the shoe.

(40) Further to the exemplary embodiment, the heel cup **52** may be attached at least to an interior foam layer **92**, as shown in FIG. **10**. The heel cup **52** may be located in the interior of the heel counter **32** of the upper **16** as shown in FIGS. **7-10**. The foam layer **92** may line both the inner wall **66** of the heel cup **52** and outer wall of the heel cup **52**. Around the upper portion and mid-portion, the foam layer **92** may protrude and extend further into the shoe opening **48**. The foam layer **92** may be thicker at or adjacent to the upper portion **64** and mid-portion **58** of the heel cup **52** thereby forming part of the cuff of the shoe opening **48**. The thicker foam layer **92** may provide securement of the user's foot once inserted within the shoe **12** as the foam would be located above the calcaneus bone region of the user's foot and extend around at least portions of the ankle region of the foot. Since the foam is compressible, the foam may be compressed by the heel during foot insertion or removal and hold the ankle of the user's foot once the foot is inserted.

(41) Rigid Heel Cup. In one exemplary embodiment, a shoe **12** may have a heel counter **32** located at the rear portion **36** of a shoe upper **16** as shown in FIGS. **11-13**. The heel counter **32** may comprise a heel cup **52** which may be an interior component of the upper **16**, a portion of the inner lining **46** or an attachment adjacent to the inner lining **46** of the upper **16** such that the heel cup **52** contacts the foot, or a portion of the exterior layer **42** of the upper **16** or an attachment of an outer surface of the exterior layer **42** of the upper **16**.

(42) The heel cup may have a lower portion that forms a heel cup configured to receive the heel of the foot. The lower portion of the heel cup may further have side extensions around both the medial side and lateral side. The heel cup may have a mid-portion located above the lower portion of the heel cup and that curves inward above the heel bone or may be composed of an aperture. The heel cup may have an aperture located at the rear of the heel cup. Further to this embodiment, the heel cup may be a rigid heel cup constructed of a substantially incompressible material under the load of the foot.

(43) At least one aperture may be incorporated into the mid-portion of the rigid heel cup that may be added to enhance the fit of the shoe around the foot of the heel. The upper material layers covering the aperture may comprise an elastic material such that the material stretches around the

contours of the heel. The tension created by the elastic material upon stretching may enhance the securement of the foot during normal use of the shoe.

(44) The upper portion of the heel cup may be configured with a smooth curvature extending from the top edge of the heel cup curved downward towards the shoe opening **48**. The inner wall of the upper portion has an overall downward incline that extends from the curved top edge of the upper portion toward the interior of the upper **16**. The inner wall of the upper portion may have dimensions akin to a shoehorn such that the smooth curvature and angle of the downward incline of the upper portion allows the heel of the foot to slide into the shoe **12** with greater ease. The heel cup may be constructed of a rigid material that does not substantially compress under the load of the user's foot. In an alternate embodiment, the heel cup may have some flexibility such that the upper portion of the heel cup may have some slight flexibility sufficient to bend downward and away from the shoe opening and/or widen the shoe opening **48** for easier foot insertion and/or removal.

(45) As shown in FIG. **11**, the top edge of the heel counter **32** may also form a resilient support structure of the rear heel collar **74**. When the heel cup **52** is incorporated into the upper **16**, a fabric material(s) or a suitable material(s) known in the art may be used to cover the heel cup **52** thereby forming the exterior layer **42** and interior layers or structures of the upper. The fabric material may extend above the heel cup **52** thereby forming an extension of the heel collar **74**.

(46) Foam material or any inner lining material(s) known in the art may be used as an inner compressible layer of the upper **16** of FIG. **11**. The foam material may be bonded to the inner surface of the heel cup **52** to provide cushioning against the rigid heel cup material. The thickness of the foam material may be uniform or vary at certain locations depending on the desired cushioning or support to the foot. In one exemplary embodiment, thicker foam material may be located at the inner wall **66** of the upper portion **64** and may further extend at least a portion along the mediolateral length of the inner wall **66**. The foam material may be configured to curve around at least a portion of the ankle above the heel when the shoe **12** is worn similar to the foam material configuration shown in FIG. **10**. In this embodiment, the user's foot may compress the foam material during foot insertion. Following foot insertion, the foam material may expand to its fully uncompressed state or partially expand thereby improving the security of the foot within the shoe **12**. A thinner foam material may be used to line the other portions of the heel cup **52**.

(47) The rigid heel cup **52** may be used in combination with a shoe upper **16** having at least one elastic region **78** located on the sides of the upper between the heel cup **52** and the front portion of the foot receiving shoe opening **48**. The elastic region **78** may have one or more elastic materials that allow the rear portion of the heel counter **32** to be temporarily moved back to widen the foot receiving shoe opening **48** for easier insertion of the foot into the shoe **12**. As shown in FIG. **11**, the elastic material may be a gore piece **80** configured to be fixed within a void of the upper such as in the form of a gusset on the medial quarter or lateral quarter or both. The elastic material may be in any spacing between the heel cup **52** and the upper portion located at the quarters **30** or vamp **24** or possibly a tongue. The elastic material may also be configured as a series of elastic strips or webbing extending between the heel cup **52** to the medial and lateral sides of the vamp **24** or possibly a tongue.

(48) Instep Support. In some embodiments, an instep support may be used to aid in preventing, in some instances, the instep of the user's foot from dragging a portion of the instep, or tongue partially into the throat area as the user dons the shoe.

(49) In some embodiments having a tongue **126** as shown in FIG. **14**, the medial side of the upper portion **132** of the tongue **126** is attached to the first or proximal end of a medial elastic strap **128** and the lateral side of the upper portion **132** of the tongue **126** is attached to the first or proximal end of a lateral elastic strap **130**. The front lower portion of the tongue is attached directly to the upper. Each of the medial and lateral elastic straps may be attached to the upper directly to the inner lining of the upper at its second or distal ends. In an alternate embodiment, the elastic straps

may extend through an opening of the inner lining of the medial quarter and lateral quarter respectively. The second end of each of the medial and lateral elastic straps may terminate respectively at the sole, sockliner, or a region within the upper's interior lining. The elastic straps function to maintain the general positioning of the tongue when the user dons the shoe.

(50) In other embodiments, each of the medial and lateral sides of the edge of the tongue or an upper portion of the tongue are attached by a gusset which may be of elastic material, to the inner lining of the upper of the medial quarter and lateral quarter of the upper. The gusset similarly may function to maintain the general positioning of the tongue when the user dons the shoe. In another embodiment of the tongue, the at least a portion of the medial and lateral edges of the tongue may be directly affixed or stitched to the interior portion of the upper and the tongue. Furthermore, the tongue may be extended wider than a conventional tongue along the mediolateral direction in the upper portion of the tongue and the edges or some portion of the extended portion may be affixed or stitched to the interior portion of the upper.

(51) In other embodiments, an instep or tongue support which may be constructed of a sheet-like material of greater hardness than the fabric of the instep or tongue may be attached to the outer surface of the tongue or embedded between an exterior tongue layer and an inner tongue layer facing the shoe opening. The instep or tongue support may reduce or prevent the instep or tongue from collapsing during the insertion of the foot. In one embodiment shown in FIG. 14, tongue support 134 may be a more rigid material such as a thermoplastic polymer configured to be more rigid than the tongue. In some embodiments, the instep or tongue support may have a thickness of 0.2 mm to 1 mm. The instep support may be coextensive with the instep or tongue, or it may extend beyond the medial or lateral sides of the instep or tongue. In the embodiment shown in FIG. 14, the tongue support 134 may be narrower and shorter than the instep or tongue.

(52) In one embodiment, a reinforcing quarter element may extend from the heel counter to the instep or eyestay. When a gusset is incorporated such as gusset 80 in FIG. 11-12, a reinforcing quarter element may extend from the heel counter 32 along the front lower edge of the gusset and around the top edge of the collar to the instep, a region near vamp 24, or an eyestay adjacent to a tongue. A reinforcing quarter element may be stiffer than the upper or quarter material. The reinforcing quarter element material may be constructed of leather, plastic, or rigid fabric. The reinforcing quarter element may be attached to the upper through bonding or stitching. The reinforcing quarter element may be configured as an elongated shape such as a strip that extends along the front lower edge of the gusset and the collar portion. The reinforcing quarter element may be located on the exterior surface or may be an interior layer of the upper such as a layer embedded within the upper or along a portion of the inner lining of the upper. A reinforcing quarter element may provide greater stability to the opening of the shoe such that it provides resistance against the quarters and instep region collapsing or moving inward into the opening of the shoe when the foot is inserted into the shoe and pushes the heel cup rearward.

(53) When the reinforcing quarter element is used in combination with an eyestay layer used in laced shoes, the eyestay may add additional structural support in providing resistance against the quarters and instep from collapsing or moving inward into the opening of the shoe. Thus, as a foot pushes against the heel cup and the gusset is stretched rearward, the reinforcing quarter element is not significantly pulled rearward. Accordingly, the shoe opening may attain a wider opening when the foot is inserted into the shoe and pushes the heel cup rearward.

(54) Compressible lining. In some embodiments, the inner surface of the heel counter and heel/ankle collar may have a portion having a compressible layer such as a foam layer. The compressible layer may extend into the shoe opening. The compressible layer is compressed under a load during the donning or removal of the shoe. After the foot is inserted into the shoe, the foam layer may expand fully or partially to its uncompressed state, and such expansion may enhance the securement of the foot within the shoe.

(55) In one exemplary embodiment, the compressible layer 100 is embedded at least within a

portion of the ankle collar **140** and the upper region of the heel counter **32**. See FIGS. **15-19**. The compressible layer **100** extends into the opening of the shoe. During the donning of the shoe, the foot exerts a load onto the compressible layer thereby widening the opening of the shoe through the transient compression of the compressible layer. After the foot is inserted into the shoe, the compressible layer expands partially or fully back to its original shape. Expansion of the compressible layer causes the foam to expand around the foot which may enhance comfort and securement of the foot. In some embodiments, the compressible layer extends above and/or around the calcaneus bone of the user's foot and around at least portions of the ankle region of the foot. (56) The compressible layer may be constructed of a material of a foam material such as EVA or polyurethane foam. The shape of the compressible layer may be pre-formed by molding the material, and affixing the compressible layer between at least two layers of textile material. The shape of the compressible layer may have at least partially a rounded outer surface that extends into the opening of the shoe and/or the ankle collar of the shoe. The volume of the compressible layer may be greater in the rear portion of the heel counter and taper along longitudinal direction of the inner portion of the foam layer at both sides of the shoe as shown in FIGS. **17-18**. The compressible layer may also taper or be rounded along the vertical axis and that the compressible layer is greater in volume at the upper portion of the ankle collar **140** and less at the lower portion of the ankle collar **140**. See FIGS. **18-19**. The compressible layer may be used to form the entire heel cup without the need of an additional heel cup or heel counter. Alternatively, the compressible layer can be used in combination with a compressible heel cup, such as shown in FIG. **1**. The heel cup can define an exterior surface of the upper, the heel cup can define an interior surface of the upper, or the heel cup can define an internal layer, for example, if embedded within the compressible layer.

(57) In the exemplary embodiment, a lower flange **118** may extend downward from the ankle collar and is configured to attach to the upper. The lower flange may be configured in any dimensions necessary to secure the ankle collar to the upper. The lower flange may also vary in the length. In some embodiments, the lower flange may define the portion of the ankle collar attached to the upper without extending downward from the ankle collar at all. In other embodiments, the lower flange may extend downward partially or fully to the bottom of the upper. In some embodiments, the lower flange may be configured to form the heel counter. In other embodiments, a heel cup, such as shown in FIG. **1**, may be partially or fully embedded in lower flange.

(58) The compressible layer **100** may be covered by any type of textile. The textile may be elastic and may have wicking properties. The textile may be form fitted to the exterior shape of the compressible layer. In a preferred embodiment, an adhesive such as a thermoplastic based adhesive is applied to the compressible layer after which the compressible layer is inserted into an elastic textile sleeve. The resulting product may also be affixed by any means such as glue or stitching according to the desired pattern of the ankle collar **140**. The textile may also include thermoplastic material and after the compressible layer **100** is inserted into the textile sleeve, heat may be applied to fuse the textile to the compressible layer **100**. In a preferred embodiment, steam may be applied so that the textile conforms to the preformed shape that forms a portion of the ankle collar and/or heel counter.

(59) Further to the exemplary embodiment, the ankle collar **140** is devoid of stitches or seams on its upper portion and may have a seam on the bottom portion where it is attached to the upper **16**. The seamless ankle collar **140** may extend from the medial quarter, around the heel, to the lateral quarter. As the user's foot is inserted into the footwear, the user's heel depresses the compressible layer **100** against the heel cup. The heel cup may keep the structural integrity of a portion of the heel region of the upper **16** from collapsing when the user's heel depresses the compressible layer **100**, thus allowing for an easier entry into the shoe by the user's foot without the use of the user's hands or an external shoehorn. Once the user's heel is fully inserted into the shoe, the compressible layer may rebound and may exert force against the back of the user's heel above the calcaneus bone

and around portions of the ankle region which may aid in providing comfort and securing the user's foot within the shoe.

(60) Further to the exemplary embodiment, the cross-section of the seamless upper portion of the ankle collar **140** is substantially round. The ankle collar **140** may be separated into a forward portion **142** and a rear portion **144**. Each of the forward portion and rear portion resemble an approximately circular cross-section or semicircular cross-section wherein the radius of the forward portion is greater than the radius of the rear portion. See FIGS. **18-19**. The compressible layer may be directly attached to the inner structure of the heel counter or via the textile sleeve covering the compressible layer material.

(61) Compressible Heel Counter with Heel Counter Support. In another exemplary embodiment, heel counter support **96** may partially form an exterior layer of the shoe and extend around the heel portion of the upper **16** from the medial quarter of the shoe to the lateral quarter of the shoe as shown in FIGS. **20-22**. In other embodiments, the heel counter support may further extend along a portion of the quarter, along the entire quarter, or along the entire quarter and into the vamp portion of the shoe. The heel counter support **96** may vary in height at different regions of the shoe. In the exemplary embodiment, the medial end and lateral end of the heel counter support **96** gradually decreases in height to the base of the upper **16** just above the sole **14**. The heel counter support **96** may have a medial region of a maximum height on the medial side of the heel portion of the upper, and a maximum height on the lateral side on the heel portion of the upper. The heel counter support **96** extends at least a portion of the height of the upper **16**. In the exemplary embodiment, the height of the medial and lateral side heel portions **98** of the upper **16** is roughly 5 cm above the lasting surface **116** and the maximum height of the heel counter support **96** on the medial and lateral sides of the heel portion is roughly 3 centimeters above the lasting surface **116**. The heel counter support **96** may gradually reduce in height from the region of its maximum height to a region of roughly uniform height along the rear of the heel portion **98** of the upper **16**. In the exemplary embodiment, the height along the heel portion **98** of the upper **16** extends up to roughly 3 centimeters above the lasting surface **116**, and the roughly uniform height of the portion forming rear portion of the heel counter support **96** is roughly 2 centimeters above the lasting surface **116**.

(62) The heel counter support **96** may partially form an exterior surface of the upper **16**. The heel counter support **96** may have an interior surface in contact with an outer surface of the heel portion **98** of the upper **16**. The heel counter support **96** may have a varying thickness across its exterior surface to its interior surface. In the exemplary embodiment, angular strips **102** form portions of increased thickness of the heel counter support **96**. The angular strips **102** may provide increased rigidity to the heel counter support **96** as well as be configured to receive the compressible component **100**.

(63) In the exemplary embodiments, the angular strips **102** have hollowed protrusions on the medial and lateral sides of the shoe **12** into which the ends of the compressible component **100** are secured. The compressible component **100** may be a pipe wherein each end of the pipe is secured within the hollowed protrusions **102**. A hollowed protrusion of the angular strips **102** may extend partially or completely around the surfaces of the compressible component **100**. In the exemplary embodiment, the compressible component **100** may be formed from polyoxymethylene or any other material with similar durability and sufficient rigidity to support the load of a foot and flexibility to curve from medial to lateral sides of the heel portion of the shoe **12**. The central segment **104** of the compressible component **100** may extend behind the ankle opening and above the heel counter of the shoe **12**. In the exemplary embodiment, the angular strips **102** may be designed to receive the compressible component **100** at an angle so that the compressible component **100** extends from inside the hollowed protrusions **102** at a rearward incline **A2** toward the back of the shoe **12**. The rearward incline **A2** of the compressible component **100** is approximately 45 degrees with respect to a level plane of the floor **88**. See FIG. **20A**. A foam layer **92** extending above the rear heel portion **98** of the upper **16** at the rear portion of the heel opening

may have a rearward incline **A2** that is coextensive with the compressible component **100**. The rearward incline **A2** of the foam layer **92** may assist in guiding the user's foot into the shoe **12** when donning the shoe.

(64) The central segment **104** of the compressible component **100** may extend behind the rearmost portion of the upper **16** and may be threaded through one or more guide tunnels **106** in the upper **16**. In the exemplary embodiment, strips of leather material are sewed to the foam layer **92** and extend above the upper at the rear portion of the heel opening. The ends of the strip of leather are stitched together to form guide tunnels **106** through which the compressible component is threaded.

(65) When donning the shoe **12**, the user's foot may depress the compressible component **100** and/or the rearwardly inclined foam layer **92** downward and rearward from the shoe opening. Once the user's foot has fully entered the shoe **12**, the compressible component **100** and the rearwardly inclined foam layer **92** return to their initial elevated positions.

(66) The additional interior heel support **114** made of foam material may have sufficient thickness that may enhance securing the foot at the Achilles tendon, and once the user dons the shoe **12**, the calcaneus bone may be located below the additional interior heel support **114**. The interior heel support **114** may have a sufficient height to be located above the calcaneus bone once the foot has been inserted into the shoe.

(67) Further to the exemplary embodiment, the shoe may have a heel cup **52** made of a flexible material configured to receive the rear portion of the heel. In one embodiment, the heel cup is a thermoplastic material that provides sufficient support as a heel counter. The interior heel support **114** may be foam material lining to provide the necessary comfort to the user's heel.

(68) Although the present invention has been described above by referring to particular embodiments, it should be understood that modifications and variations could be made to the sole structure without departing from the intended scope of invention.

(69) Clause 1. A shoe comprising a heel counter; the heel counter comprising a heel cup; the heel cup being uniformly molded with an upper portion, a midportion, and a lower portion; wherein the upper portion has a smaller mediolateral length than the midportion; wherein a thickness of the heel cup decreases from a peripheral portion of the heel cup toward a central region of the midportion; wherein the central region of the midportion provides flexibility of the heel cup, and wherein the rearmost portion of the heel cup has an overall vertical S wave cross-sectional shape.

(70) Clause 2. The shoe according to clause 1, wherein the heel cup is a compressible heel cup.

(71) Clause 3. The shoe according to clause 1, wherein the central region of the midportion in addition provides bending of the heel cup.

(72) Clause 4. The shoe according to clause 1, wherein the upper portion of the heel cup has a first configuration and is configured to be distorted into a second configuration under a load of a user's foot, when the user is donning the shoe, wherein in the second configuration, at least part of the upper portion is lowered relative to the first configuration and the upper portion is configured to return to the first configuration after the load of the user's foot is removed.

(73) Clause 5. The shoe according to clause 4, wherein the distortion of the heel cup into the second configuration comprises the heel counter widening with medial and lateral sides of the heel cup moving outward thereby widening an opening of the shoe.

(74) Clause 6. The shoe according to clause 1, wherein the peripheral portion forms an area at a periphery of the heel cup.

(75) Clause 7. The shoe according to clause 1, wherein the midportion and the lower portion form a concave structure configured to receive a heel and the concave structure forms a bottom part of the vertical S wave cross-sectional shape.

(76) Clause 8. The shoe according to clause 1, wherein an inner wall of the upper portion of the heel cup comprises a convex curvature facing toward a shoe opening and the convex structure forms a top part of the vertical S wave cross-sectional shape.

(77) Clause 9. The shoe according to clause 1, wherein the heel cup is attached at least to an

interior foam layer.

(78) Clause 10. The shoe according to clause 9, wherein the interior foam layer protrudes and extends into the shoe opening around the upper portion and midportion of the heel cup.

(79) Clause 11. The shoe according to clause 1, wherein the thickness of the heel cup decreases gradually from the peripheral portion of the heel cup toward the central region of the midportion.

(80) Clause 12. A shoe comprising a heel counter; the heel counter comprising a heel cup; the heel cup being molded with an upper portion, a midportion, and a lower portion; wherein the upper portion has a smaller mediolateral length than the midportion; wherein a midpoint region of the heel cup is thinner than the surrounding regions of the heel cup, and wherein the rearmost portion of the heel cup has an overall vertical S wave cross-sectional shape.

(81) Clause 13. The shoe according to clause 12, wherein the heel cup is a compressible heel cup.

(82) Clause 14. The shoe according to clause 12, wherein the heel cup is uniformly molded with the upper portion, the midportion, and the lower portion.

(83) Clause 15. A shoe comprising a heel counter; the heel counter comprising a heel cup; the heel cup being molded with an upper portion, a midportion, and a lower portion; wherein the upper portion has a smaller mediolateral length than the midportion; wherein in a vertical cross-section, the heel cup has an S wave shape; wherein in the vertical cross-section, the upper portion has a first thickness in a first location; wherein in the vertical cross-section, the midportion has a second thickness in a second location; wherein in the vertical cross-section, the lower portion has a third thickness in a third location; wherein the second thickness is smaller than at least one of the first thickness and the third thickness; and wherein the midportion provides flexibility of the heel cup.

(84) Clause 16. The shoe according to clause 15, wherein the heel cup is a compressible heel cup.

(85) Clause 17. The shoe according to clause 15 wherein the heel cup is uniformly molded with the upper portion, the midportion, and the lower portion.

(86) Clause 18. Shoe according to clause 15, wherein the thickness of the heel cup decreases gradually from the first location to the second location.

(87) Clause 19. The shoe according to clause 15, wherein the thickness of the heel cup decreases gradually from the third location to the second location.

(88) Clause 20. The shoe according to clause 15, wherein the upper portion of the heel cup has a first configuration and is configured to be distorted into a second configuration under a load of a user's foot, when the user is donning the shoe, wherein in the second configuration, at least part of the upper portion is lowered relative to the first configuration and the upper portion is configured to return to the first configuration after the load of the user's foot is removed.

(89) Clause 21. The shoe according to clause 20, wherein the distortion of the heel cup into the second configuration comprises the heel counter widening with medial and lateral sides of the heel cup moving outward thereby widening an opening of the shoe.

(90) Clause 22. The shoe according to clause 15, wherein the midportion and the lower portion form a concave structure configured to receive a heel.

(91) Clause 23. The shoe according to clause 15, wherein an inner wall of the upper portion of the heel cup comprises a convex curvature facing toward a shoe opening.

(92) Clause 24. The shoe according to clause 15, wherein the heel cup is attached at least to an interior foam layer.

(93) Clause 25. The shoe according to clause 24, wherein the interior foam layer protrudes and extends into the shoe opening around the upper portion and midportion of the heel cup.

(94) Clause 26. The shoe according to clause 15, wherein the vertical cross-section is the vertical cross-section of a rearmost portion of the heel cup.

(95) Clause 27. The shoe according to clause 15, wherein the second location is a location of an inflection point of the S wave.

(96) Clause 28. The shoe according to clause 15, wherein the midportion in addition provides bending of the heel cup.

Claims

1. A shoe comprising a heel counter; the heel counter comprising a heel cup; the heel cup being uniformly molded with an upper portion, a midportion, and a lower portion; wherein the upper portion has a smaller mediolateral length than the midportion; wherein the upper portion of the heel cup is located below an ankle collar of the upper; wherein a rearmost portion of the heel cup has an overall vertical S wave cross-sectional shape; wherein the heel cup includes at least one reduced cross-sectional thickness region below the upper portion providing flexibility to the heel cup when donning or removing the shoe.
2. The shoe according to claim 1, wherein the heel cup is a compressible heel cup.
3. The shoe according to claim 1, wherein a central region of the midportion in addition provides bending of the heel cup.
4. The shoe according to claim 1, wherein the upper portion of the heel cup has a first configuration and is configured to be distorted into a second configuration under a load of a user's foot, when the user is donning the shoe, wherein in the second configuration, at least part of the upper portion is lowered relative to the first configuration and the upper portion is configured to return to the first configuration after the load of the user's foot is removed.
5. The shoe according to claim 4, wherein the distortion of the heel cup into the second configuration comprises the heel counter widening with medial and lateral sides of the heel cup moving outward thereby widening an opening of the shoe.
6. The shoe according to claim 1, wherein a peripheral portion forms an area at a periphery of the heel cup.
7. The shoe according to claim 1, wherein the midportion and the lower portion form a concave structure configured to receive a heel and the concave structure forms a bottom part of the vertical S wave cross-sectional shape.
8. The shoe according to claim 1, wherein an inner wall of the upper portion of the heel cup comprises a convex curvature facing toward a shoe opening and the convex structure forms a top part of the vertical S wave cross-sectional shape.
9. The shoe according to claim 1, wherein the heel cup is attached at least to an interior foam layer.
10. The shoe according to claim 9, wherein the interior foam layer protrudes and extends into a shoe opening around the upper portion and midportion of the heel cup.
11. The shoe according to claim 1, wherein a thickness of the heel cup decreases gradually from a peripheral portion of the heel cup toward a central region of the midportion.
12. The shoe according to claim 1, wherein an interior foam layer adjacent to at least an interior wall of the upper portion of the heel cup, wherein the interior foam layer is compressible, wherein the interior foam layer extends into a shoe opening, providing securement of the foot once inserted.
13. A shoe comprising a heel counter and an upper; the heel counter comprising a heel cup; the heel cup being molded with an upper portion, a midportion, and a lower portion; wherein the upper portion of the heel cup is located below an ankle collar of the upper; wherein a midpoint region of the heel cup has a lesser cross-sectional thickness than the lower portion of the heel cup; and wherein a rearmost portion of the heel cup has an overall vertical S wave cross-sectional shape.
14. The shoe according to claim 13, wherein the heel cup is a compressible heel cup.
15. The shoe according to claim 13, wherein the heel cup is uniformly molded with the upper portion, the midportion, and the lower portion.
16. The shoe according to claim 13, wherein the heel cup includes at least one reduced thickness region providing flexibility to the heel cup when donning or removing the shoe.
17. A shoe comprising a heel counter; the heel counter comprising a heel cup; the heel cup being molded with an upper portion, a midportion, and a lower portion; wherein the upper portion has a smaller mediolateral length than the midportion; wherein the upper portion of the heel cup is

located below an ankle collar of the upper; wherein in a vertical cross-section, the heel cup has an S wave shape; wherein a midpoint region of the heel cup has a lesser cross-sectional thickness than the lower portion of the heel cup.

18. The shoe according to claim 17, wherein the heel cup is a compressible heel cup.

19. The shoe according to claim 17 wherein the heel cup is uniformly molded with the upper portion, the midportion, and the lower portion.

20. Shoe according to claim 17, wherein the lower portion has a first location, and the thickness of the heel cup decreases gradually from the first location toward the midpoint region.

21. The shoe according to claim 17, wherein the upper portion has a second location, and the thickness of the heel cup decreases gradually from the second location to the midpoint region.

22. The shoe according to claim 17, wherein the upper portion of the heel cup has a first configuration and is configured to be distorted into a second configuration under a load of a user's foot, when the user is donning the shoe, wherein in the second configuration, at least part of the upper portion is lowered relative to the first configuration and the upper portion is configured to return to the first configuration after the load of the user's foot is removed.

23. The shoe according to claim 22, wherein the distortion of the heel cup into the second configuration comprises the heel counter widening with medial and lateral sides of the heel cup moving outward thereby widening an opening of the shoe.

24. The shoe according to claim 17, wherein the midportion and the lower portion form a concave structure configured to receive a heel.

25. The shoe according to claim 17, wherein an inner wall of the upper portion of the heel cup comprises a convex curvature facing toward a shoe opening.

26. The shoe according to claim 17, wherein the heel cup is attached at least to an interior foam layer.

27. The shoe according to claim 26, wherein the interior foam layer protrudes and extends into the shoe opening around the upper portion and midportion of the heel cup.

28. The shoe according to claim 17, wherein the vertical cross-section is the vertical cross-section of a rearmost portion of the heel cup.

29. The shoe according to claim 17, wherein a flexibility of the midportion in addition provides bending of the heel cup.

30. The shoe according to claim 17, wherein an interior foam layer adjacent to at least an interior wall of the upper portion of the heel cup, wherein the interior foam layer is compressible, wherein the interior foam layer extends into a shoe opening, providing securement of the foot once inserted.
