

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408763
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Dixon; Jessica Lynn et al.

Controlling a bed remotely

Abstract

A remote control for a bed system is described. The remote control includes a case, a display screen, a first input area, at least one capacitive button, and a communications module. The case has a base surface, a display surface, and an upper surface. The display screen is on the display surface. The first input area is on the display surface. At least one capacitive button is separate from the first input area. The communication module allows communication between the remote control and a separate controller of the bed system.

Inventors: Dixon; Jessica Lynn (Ramsey, MN), Stusynski; Stacy (Blaine, MN), Negus; Natalie (Minneapolis, MN), Hartzler; Jeffrey Scott (Minneapolis, MN), Grabinger; Cory Lee (Maple Grove, MN)

Applicant: Sleep Number Corporation (Minneapolis, MN)

Family ID: 86229562

Assignee: Sleep Number Corporation (Minneapolis, MN)

Appl. No.: 17/523349

Filed: November 10, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230142604 A1	May. 11, 2023

Publication Classification

Int. Cl.: A47C31/00 (20060101); G06F3/044 (20060101); G08C17/02 (20060101)

U.S. Cl.:

CPC **A47C31/008** (20130101); **G06F3/044** (20130101); **G08C17/02** (20130101);
G08C2201/30 (20130101); G09G2360/144 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6507423	12/2002	Chen	455/343.2	H04B 10/1141
8444558	12/2012	Young et al.	N/A	N/A
8672853	12/2013	Young	N/A	N/A
8984687	12/2014	Stusynski et al.	N/A	N/A
9182750	12/2014	Rawls-Meehan	N/A	A47C 31/008
9370457	12/2015	Nunn et al.	N/A	N/A
9392879	12/2015	Nunn et al.	N/A	N/A
9445751	12/2015	Young et al.	N/A	N/A
9495768	12/2015	Elliott	N/A	G09G 5/343
9504416	12/2015	Young et al.	N/A	N/A
9510688	12/2015	Nunn et al.	N/A	N/A
9524633	12/2015	Mann et al.	N/A	N/A
9635953	12/2016	Nunn et al.	N/A	N/A
9757861	12/2016	Hong	N/A	B25J 9/1689
9770114	12/2016	Brosnan et al.	N/A	N/A
9844275	12/2016	Nunn et al.	N/A	N/A
9931085	12/2017	Young et al.	N/A	N/A
9984516	12/2017	Geerlings	N/A	G07C 9/30
10058467	12/2017	Stusynski et al.	N/A	N/A
10092242	12/2017	Nunn et al.	N/A	N/A
10149549	12/2017	Erko et al.	N/A	N/A
10182661	12/2018	Nunn et al.	N/A	N/A
10194753	12/2018	Fleury	N/A	A47C 31/008
10201234	12/2018	Nunn et al.	N/A	N/A
10251490	12/2018	Nunn et al.	N/A	N/A
10339741	12/2018	Geerlings	N/A	G08C 17/02
10342358	12/2018	Palashewski et al.	N/A	N/A
10424192	12/2018	Mann et al.	N/A	N/A
10441086	12/2018	Nunn et al.	N/A	N/A
10441087	12/2018	Karschnik et al.	N/A	N/A
10448749	12/2018	Palashewski et al.	N/A	N/A
10492969	12/2018	Stusynski et al.	N/A	N/A
10621803	12/2019	Geerlings	N/A	G07C 9/00857
10632032	12/2019	Stusynski et al.	N/A	N/A
10646050	12/2019	Nunn et al.	N/A	N/A
10674832	12/2019	Brosnan et al.	N/A	N/A
10694607	12/2019	Xu	N/A	H05B 45/22
10716512	12/2019	Erko et al.	N/A	N/A

10729255	12/2019	Erko et al.	N/A	N/A
10736432	12/2019	Brosnan et al.	N/A	N/A
10750875	12/2019	Palashewski et al.	N/A	N/A
10827846	12/2019	Karschnik et al.	N/A	N/A
10881219	12/2020	Nunn et al.	N/A	N/A
10957335	12/2020	Demirli et al.	N/A	N/A
10959535	12/2020	Karschnik et al.	N/A	N/A
D916745	12/2020	Stusynski et al.	N/A	N/A
10980351	12/2020	Nunn et al.	N/A	N/A
11096849	12/2020	Stusynski et al.	N/A	N/A
11122909	12/2020	Palashewski et al.	N/A	N/A
11160683	12/2020	Nunn et al.	N/A	N/A
11488519	12/2021	Hyeon	N/A	G09G 3/32
2006/0187195	12/2005	Chung	345/156	G09G 5/10
2008/0077020	12/2007	Young et al.	N/A	N/A
2010/0170043	12/2009	Young et al.	N/A	N/A
2011/0144455	12/2010	Young et al.	N/A	N/A
2011/0277242	12/2010	Dionne	5/613	A61G 7/0524
2013/0239324	12/2012	Mossbeck	29/428	A47C 20/041
2013/0289770	12/2012	Rawls-Meehan	700/275	A47C 20/041
2013/0322846	12/2012	Ferren	386/234	G06F 3/0482
2014/0059768	12/2013	Lemire	5/611	A61G 7/0527
2014/0268628	12/2013	Mann	361/752	G08C 17/02
2014/0277822	12/2013	Nunn et al.	N/A	N/A
2015/0023650	12/2014	Austin	386/241	H04N 21/4728
2015/0026896	12/2014	Fleury	5/713	A47C 27/082
2015/0228132	12/2014	Geerlings	340/5.22	G08C 17/02
2016/0015184	12/2015	Nunn et al.	N/A	N/A
2016/0120740	12/2015	Rawls-Meehan	601/49	A47C 31/008
2016/0367039	12/2015	Young et al.	N/A	N/A
2017/0065220	12/2016	Young et al.	N/A	N/A
2017/0112716	12/2016	Rawls-Meehan	N/A	A61H 23/0263
2017/0128001	12/2016	Torre et al.	N/A	N/A
2017/0143269	12/2016	Young et al.	N/A	N/A
2019/0053761	12/2018	Torre et al.	N/A	N/A
2019/0069840	12/2018	Young et al.	N/A	N/A
2019/0200069	12/2018	Maier	N/A	G06F 3/04895
2019/0200777	12/2018	Demirli et al.	N/A	N/A
2019/0201265	12/2018	Sayadi et al.	N/A	N/A
2019/0201266	12/2018	Sayadi et al.	N/A	N/A
2019/0201267	12/2018	Demirli et al.	N/A	N/A
2019/0201268	12/2018	Sayadi et al.	N/A	N/A
2019/0201270	12/2018	Sayadi et al.	N/A	N/A
2019/0201271	12/2018	Grey et al.	N/A	N/A
2019/0328146	12/2018	Palashewski et al.	N/A	N/A
2019/0328147	12/2018	Palashewski et al.	N/A	N/A
2019/0357696	12/2018	Palashewski et al.	N/A	N/A
2020/0020223	12/2019	Mann et al.	N/A	N/A
2020/0098214	12/2019	Geerlings	N/A	G08C 17/02
2020/0315367	12/2019	Demirli et al.	N/A	N/A

2020/0336010	12/2019	Holmvik et al.	N/A	N/A
2020/0359807	12/2019	Brosnan et al.	N/A	N/A
2020/0367663	12/2019	Nunn et al.	N/A	N/A
2020/0405070	12/2019	Palashewski et al.	N/A	N/A
2020/0405240	12/2019	Palashewski et al.	N/A	N/A
2021/0000261	12/2020	Erko et al.	N/A	N/A
2021/0034989	12/2020	Palashewski et al.	N/A	N/A
2021/0045541	12/2020	Nunn et al.	N/A	N/A
2021/0068552	12/2020	Palashewski et al.	N/A	N/A
2021/0112992	12/2020	Nunn et al.	N/A	N/A
2022/0018050	12/2021	Bernardino	N/A	D06F 23/02
2023/0142604	12/2022	Dixon	5/616	G06F 3/044

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2015199787	12/2014	WO	G01B 7/003

OTHER PUBLICATIONS

U.S. Appl. No. 16/719,177, filed Dec. 18, 2018, Nunn et al. cited by applicant
U.S. Appl. No. 17/091,094, filed Nov. 6, 2020, Karschnik et al. cited by applicant
U.S. Appl. No. 17/189,618, filed Mar. 2, 2021, Stusynski. cited by applicant
U.S. Appl. No. 17/207,149, filed Mar. 19, 2021, Demirli et al. cited by applicant
U.S. Appl. No. 17/216,297, filed Mar. 29, 2021, Karschnik et al. cited by applicant
U.S. Appl. No. 17/379,460, filed Jul. 19, 2021, Stusynski et al. cited by applicant
U.S. Appl. No. 17/476,093, filed Sep. 15, 2021, Nunn et al. cited by applicant
U.S. Appl. No. 17/479,907, filed Sep. 20, 2021, Palashewski et al. cited by applicant
U.S. Appl. No. 29/676,117, filed Jan. 8, 2019, Stusynski et al. cited by applicant
U.S. Appl. No. 29/776,258, filed Mar. 29, 2021, Stusynski et al. cited by applicant
U.S. Appl. No. 29/777,084, filed Apr. 2, 2021, Stusynski et al. cited by applicant
U.S. Appl. No. 29/814,835, filed Nov. 9, 2021, Dixon et al. cited by applicant

Primary Examiner: Garcia; Carlos

Attorney, Agent or Firm: Fish & Richardson P.C.

Background/Summary

(1) The present document relates to control of a consumer device such as an airbed.

BACKGROUND

(2) In general, a bed is a piece of furniture used as a location to sleep or relax. Many modern beds include a soft mattress on a bed frame. The mattress may include springs, foam material, and/or an air chamber to support the weight of one or more occupants.

SUMMARY

(3) An example implementation of the subject matter described within this disclosure is a bed system with the following features. Implementations can include any, all, or none of the following features.

(4) Implementations of the present disclosure include a remote control for a bed system. The remote control includes a case, a display screen, a first input area, at least one capacitive button, and a communication module. The case has a base surface, a display surface, and an upper surface.

The display screen is on the display surface. The first input area is on the display surface. At least one capacitive button is separate from the first input area. The communication module allows communication between the remote control and a separate controller of the bed system.

(5) In some implementations, a portion of the case is metallic. In some cases, the portion of the case is capacitively sensitive and the remote control wakes responsive to a signal from the portion of the case that is capacitively sensitive.

(6) In some implementations, the first input area includes a direction pad and a selection pad.

(7) In some implementations, the remote control further includes a slider switch on the upper surface. The slider switch toggles between a first position and a second position. In some cases, the slider switch adjusts an interface displayed on the display screen to a first side of a bed when the slider switch is in the first position and a second side of the bed when the slider switch is in the second position.

(8) In some implementations, the remote control is wirelessly coupled to the separate controller.

(9) In some implementations, the separate controller is a bed controller configured to control pressure, articulation, temperature, or light level of the bed system.

(10) In some implementations, the remote control pings the separate controller upon waking, receives a state from the separate controller, and displays an interface on the display screen responsive to the received state.

(11) In some implementations, the capacitive button is between the display screen and the first input area.

(12) In some implementations, the base surface is sized to allow the remote control to rest in a vertical position.

(13) In some implementations, the base surface is substantially triangular.

(14) In some implementations, the remote control further includes a light sensor to receive ambient light and produce a light signal representative of an ambient light level.

(15) In some implementations, the remote control adjusts a brightness of the display screen or the first input area responsive to the light signal.

(16) Further implementations of the present disclosure include a method of operating a bed system having a remote control. The method includes fetching, by the remote control, a state of a bed from a bed controller that is physically separate from the remote control. The method includes displaying an interface on a screen of the remote control responsive to the fetched state.

(17) In some implementations, the method further includes waking the remote control responsive to receiving a signal from a capacitive surface of the remote control, the signal being indicative of a touch by a user.

(18) In some implementations, fetching includes wirelessly communicating between the remote control and the bed controller.

(19) In some implementations, receiving a response includes the remote control receiving an indication of a new state and displaying an interface includes displaying an interface appropriate for the new state. In some cases, upon waking the remote control, receiving a response includes the remote control receiving an indication of no change in state since a previous fetch and displaying an interface includes displaying a last used interface.

(20) In some implementations, the method further includes transmitting, by the remote control, a command signal to the bed to change the state of the bed from the state to a new state. The method further includes receiving, by the bed controller, the command signal to change the state of the bed from the state to the new state. The method further includes adjusting, by the bed controller, the state of the bed based on the command signal. The method further includes transmitting, by the bed controller, a signal representing the new state to the remote control. The method further includes receiving, by the remote control, the signal representing the new state of the bed. The method further includes displaying, by the remote control, the new state of the bed on the screen of the remote control.

- (21) Further implementations of the present disclosure include a bed control system. The bed control system includes a bed controller and a remote control. The bed controller controls functions of a bed. The remote control is physically separate from the bed controller. The remote control is wirelessly coupled to the bed controller. The remote control includes a case having a base surface, a display surface, and an upper surface. A portion of the case is capacitively sensitive. The bed controller wakes responsive to a signal from the case. The remote control includes a display screen on the display surface. The remote control includes an input area on the display surface.
- (22) In some implementations, the remote control of the bed control system further includes a capacitive button separate from the input area. The capacitive button is between the display screen and the input area.
- (23) In some implementations, the remote control of the bed control system further includes a slider switch on the upper surface which toggles between a first position and a second position.
- (24) In some implementations, the base surface of the remote control is sized to allow the remote control to rest in a vertical position.
- (25) In some implementations, the base surface of the remote control is substantially triangular.
- (26) In some implementations, the remote control further includes a light sensor to receive ambient light and produce a light signal representative of an ambient light level. In some cases, the bed controller adjusts a brightness of the display screen and the input area responsive to the light signal.
- (27) Further implementations of the present disclosure include a remote control for a bed interface. The remote control includes a case, a display screen, an input area, and a light sensor. The case has a base surface, a display surface, and an upper surface. The display screen is on the display surface. The input area on the display surface. The light sensor receives ambient light and produces a light signal representative of an ambient light level.
- (28) In some implementations, the remote control is operatively coupled to the display screen and the light sensor. The remote control adjusts a brightness of the display screen and the input area responsive to the light signal.
- (29) Other features, aspects and potential advantages will be apparent from the accompanying description and figures.
-

Description

DESCRIPTION OF DRAWINGS

- (1) FIG. 1 shows an example air bed system.
- (2) FIG. 2 is a block diagram of an example of various components of an air bed system.
- (3) FIG. 3 shows an example environment including a bed in communication with devices located in and around a home.
- (4) FIGS. 4A-4E are perspective schematic diagrams of the example remote control of the air bed system.
- (5) FIGS. 5A and 5B are block diagrams of example data processing systems that can be associated with a bed.
- (6) FIGS. 6 and 7 are block diagrams of examples of motherboards that can be used in a data processing system that can be associated with a bed.
- (7) FIG. 8 is a block diagram of an example of a daughterboard that can be used in a data processing system that can be associated with a bed.
- (8) FIG. 9 is a block diagram of an example of a motherboard with no daughterboard that can be used in a data processing system that can be associated with a bed.
- (9) FIG. 10 is a block diagram of an example of a sensory array that can be used in a data processing system that can be associated with a bed.
- (10) FIG. 11 is a block diagram of an example of a control array that can be used in a data

processing system that can be associated with a bed

(11) FIG. 12 is a block diagram of an example of a computing device that can be used in a data processing system that can be associated with a bed.

(12) FIGS. 13-17 are block diagrams of example cloud services that can be used in a data processing system that can be associated with a bed.

(13) FIG. 18 is a block diagram of an example of using a data processing system that can be associated with a bed to automate peripherals around the bed.

(14) FIG. 19 is a schematic diagram that shows an example of a computing device and a mobile computing device.

(15) FIG. 20 is a flow chart of an example method of operating the light sensor of the remote control.

(16) FIG. 21 is a flow chart of an example method of operating a bed system with a remote control.

(17) Like reference symbols in the various drawings indicate like elements.

DETAILED DESCRIPTION

(18) This disclosure relates to controlling a bed remotely by a remote control for the bed. The remote control has a case with a base surface, a display surface, and an upper surface. A display screen is on the display surface. A first input area is also on the display surface. The remote control has at least one capacitive button separate from the first input area. The remote control includes a communications module to communicate between the remote control and a separate controller of the bed.

(19) In some embodiments, a bed system is operated by the remote control. A state of a bed is fetched, by the remote control, from a bed controller that is physically separate from the remote control. An interface is displayed on a screen of the remote control responsive to the fetched state.

(20) In some embodiments, a bed control system includes a bed controller to control functions of a bed. The bed control system includes a remote control physically separate from the bed controller. The remote control is wirelessly coupled to the bed controller. The remote control includes a case. The case includes a base surface, a display surface, and an upper surface. A portion of the case is capacitively sensitive. The bed controller wakes responsive to a signal from the capacitively sensitive case. The bed control system includes a display screen on the display surface and a first input area on the display surface.

(21) Example Airbed Hardware

(22) FIG. 1 shows an example air bed system 100 that includes a bed 112. The bed 112 includes at least one air chamber 114 surrounded by a resilient border 116 and encapsulated by bed ticking 118. The resilient border 116 can comprise any suitable material, such as foam.

(23) As illustrated in FIG. 1, the bed 112 can be a two chamber design having first and second fluid chambers, such as a first air chamber 114A and a second air chamber 114B. In alternative embodiments, the bed 112 can include chambers for use with fluids other than air that are suitable for the application. In some embodiments, such as single beds or kids' beds, the bed 112 can include a single air chamber 114A or 114B or multiple air chambers 114A and 114B. First and second air chambers 114A and 114B can be in fluid communication with a pump 120. The pump 120 can be in electrical communication with a remote control 122 via control box 124. The control box 124 can include a wired or wireless communications interface for communicating with one or more devices, including the remote control 122. The control box 124 can be configured to operate the pump 120 to cause increases and decreases in the fluid pressure of the first and second air chambers 114A and 114B based upon commands input by a user using the remote control 122. In some implementations, the control box 124 is integrated into a housing of the pump 120.

(24) The remote control 122 can include a display 126, a first input area 128, a capacitive button 130, and a slider switch 132. The first input area 128, the capacitive button 130, and the slider switch 132 can be used to control features of the bed 112, such as firmness, articulation, temperature, a lighting level, and/or other features of the bed 112. For example, when the bed 112

is divided into separate portions such as a head section, body section, and a foot section (not shown), articulation can include raising, lowering, or angling one or more of the head section, the body section, or the foot section relative to the other sections. For example, when the bed **112** has a massage assembly (not shown) to massage the user, articulating can include operating the massage assembly to massage the user. The first input area **128** can be a physical control (e.g., switch or button) or an input control displayed on display **126**. The slider switch **132** can control which side of the bed **112** is displayed and/or controlled on the screen **126**. Alternatively, separate remote control units can be provided for each air chamber and can each include the ability to control multiple air chambers. The capacitive button **130** can be one or more capacitive buttons **130**. The capacitive buttons **130** can be positioned next to one another or separate. In some implementations, the remote controller **122** can itself include capacitive sensing such that the controller **122** can wake up when the user touches the remote controller **122**, movement of the slider switch **132**, or the user pressing the first input area **128**. Adjusting the pressure within the selected air chamber can cause a corresponding adjustment to the firmness of the respective air chamber.

(25) FIG. 2 is a block diagram of an example of various components of an air bed system. For example, these components can be used in the example air bed system **100**. As shown in FIG. 2, the control box **124** can include a power supply **134**, a processor **136**, a memory **137**, a switching mechanism **138**, and an analog to digital (A/D) converter **140**. The switching mechanism **138** can be, for example, a relay or a solid state switch.

(26) In some implementations, the switching mechanism **138** can be located in the pump **120** rather than the control box **124**. The control box **124** receives signals from the remote control **122**. The control box **124** transmits signals indicative of control states to the remote control **122**.

(27) The pump **120** and the remote control **122** are in two-way communication with the control box **124**. The pump **120** includes a motor **142**, a pump manifold **143**, a relief valve **144**, a first control valve **145A**, a second control valve **145B**, and a pressure transducer **146**. The pump **120** is fluidly connected with the first air chamber **114A** and the second air chamber **114B** via a first tube **148A** and a second tube **148B**, respectively. The first and second control valves **145A** and **145B** can be controlled by switching mechanism **138**, and are operable to regulate the flow of fluid between the pump **120** and first and second air chambers **114A** and **114B**, respectively.

(28) The remote control **122** includes a communications module **202**. The communications module allows communication between the remote control **122** and the control box **124**. The communications module **202** transmits signals to the control box **124**. For example, the communications module **202** can transmit a status signal or a command signal from the remote control **122** to the control box **124**. For example, the status signal can be an electrical charge level (in other words a battery power percentage remaining), an error code representing an error condition of the remote **122**, or a level of ambient light sensed by the remote control **122** (described later). The command signal can be a signal to change a condition of the bed **112**. For example the condition of the bed can be a pressure, orientation, a temperature, a light level, a position of a portion of the bed **112**, a configuration the portions of the bed **112** or the user name. The communications module **202** transmits the bed status and remote control **122** status to the display **126** for the user to see. The communications module **202** receives input (the command signal) from the user when the user operates the input area **128**, the capacitive button **130**, and/or the slider switch **132** to operate (to change the condition of) the bed **112**. The communications module **202** communicates wirelessly with the control box **124**. For example, the communications module **2020** can communicate via WiFi radio, Bluetooth Low Energy (BLE) radio, ZigBee radio, Bluetooth Classic, personal area network (i.e., Thread, 6LoWPan, BLE mesh, and Z-Wave), or a proprietary 2.4 Ghz or Sub-Ghz communication technology, described later in reference to FIG. 6.

(29) In some implementations, the pump **120** and the control box **124** can be provided and packaged as a single unit. In some alternative implementations, the pump **120** and the control box **124** can be provided as physically separate units. In some implementations, the control box **124**,

the pump **120**, or both are integrated within or otherwise contained within a bed frame or bed support structure that supports the bed **112**. In some implementations, the control box **124**, the pump **120**, or both are located outside of a bed frame or bed support structure (as shown in the example in FIG. **1**).

(30) The example air bed system **100** depicted in FIG. **2** includes the two air chambers **114A** and **114B** and the single pump **120**. However, other implementations can include an air bed system having two or more air chambers and one or more pumps incorporated into the air bed system to control the air chambers. For example, a separate pump can be associated with each air chamber of the air bed system or a pump can be associated with multiple chambers of the air bed system. Separate pumps can allow each air chamber to be inflated or deflated independently and simultaneously. Furthermore, additional pressure transducers can also be incorporated into the air bed system such that, for example, a separate pressure transducer can be associated with each air chamber.

(31) In use, the user operates the input area **128**, the capacitive button **130**, and/or the slider switch **132** to generate the command signal to decrease pressure in one of the air chambers **114A** or **114B**. The communications module **202** receives the command signal to decrease pressure in one of the air chambers **114A** or **114B** and retransmits the command signal to decrease pressure in one of the air chambers **114A** or **114B** to the processor **136**. The processor **138** controls the switching mechanism **138** to convert the low voltage command signals sent by the processor **136** to higher operating voltages sufficient to operate the relief valve **144** of the pump **120** and open the control valve **145A** or **145B**. Opening the relief valve **144** can allow air to escape from the air chamber **114A** or **114B** through the respective air tube **148A** or **148B**. During deflation, the pressure transducer **146** can send pressure readings to the processor **136** via the A/D converter **140**. The A/D converter **140** can receive analog information from pressure transducer **146** and can convert the analog information to digital information usable by the processor **136**. The processor **136** can send the digital signal to the remote control **122** to update the display **126** in order to convey the pressure information to the user.

(32) As another example, the user operates either the input area **128** and/or the slider switch **132** to generate the command signal to increase pressure in one of the air chambers **114A** or **114B**. The communications module **202** receives the command signal to increase pressure in one of the air chambers **114A** or **114B**, then processes and retransmits command signal to increase pressure in one of the air chambers **114A** or **114B** to the processor **136**. The processor **136** sends an increase pressure command to the pump motor **142**. The pump motor **142** can be energized in response to the increase pressure command and send air to the designated one of the air chambers **114A** or **114B** through the air tube **148A** or **148B** via electronically operating the corresponding valve **145A** or **145B**. While air is being delivered to the designated air chamber **114A** or **114B** in order to increase the firmness of the chamber, the pressure transducer **146** can sense pressure within the pump manifold **143**. Again, the pressure transducer **146** can send pressure readings to the processor **136** via the A/D converter **140**. The processor **136** can use the information received from the A/D converter **140** to determine the difference between the actual pressure in air chamber **114A** or **114B** and the desired pressure. The processor **136** can send the digital signal to the remote control **122** to update display **126** in order to convey the pressure information to the user.

(33) In another example, the remote control **122** wakes up in response to an action of the user, for instance, the user touching the remote control **122**. Upon waking up, the remote control **122** transmits the status (a state of the user or the remote) signal, also called a ping, to the processor **136** in the control box **124**. In response to receiving the status signal, the processor **126** transmits another status (for example, a state or condition of the bed) signal to the remote control **122**. The remote control **122** receives the status signal from the processor **126**. The remote control **122** then displays an interface on the display **126** for the user to interpret (see).

(34) Generally speaking, during an inflation or deflation process, the pressure sensed within the

pump manifold **143** can provide an approximation of the pressure within the respective air chamber that is in fluid communication with the pump manifold **143**. An example method of obtaining a pump manifold pressure reading that is substantially equivalent to the actual pressure within an air chamber includes turning off pump **120**, allowing the pressure within the air chamber **114A** or **114B** and the pump manifold **143** to equalize, and then sensing the pressure within the pump manifold **143** with the pressure transducer **146**. Thus, providing a sufficient amount of time to allow the pressures within the pump manifold **143** and chamber **114A** or **114B** to equalize can result in pressure readings that are accurate approximations of the actual pressure within air chamber **114A** or **114B**. In some implementations, the pressure of the air chambers **114A** and/or **114B** can be continuously monitored using multiple pressure sensors (not shown).

(35) In some implementations, information collected by the pressure transducer **146** can be analyzed to determine various states of a person lying on the bed **112**. For example, the processor **136** can use information collected by the pressure transducer **146** to determine a heart rate or a respiration rate for a person lying in the bed **112**. For example, a user can be lying on a side of the bed **112** that includes the chamber **114A**. The pressure transducer **146** can monitor fluctuations in pressure of the chamber **114A** and this information can be used to determine the user's heart rate and/or respiration rate. As another example, additional processing can be performed using the collected data to determine a sleep state of the person (e.g., awake, light sleep, deep sleep). For example, the processor **136** can determine when a person falls asleep and, while asleep, the various sleep states of the person.

(36) Additional information associated with a user of the air bed system **100** that can be determined using information collected by the pressure transducer **146** includes motion of the user, presence of the user on a surface of the bed **112**, weight of the user, heart arrhythmia of the user, and apnea. Taking user presence detection for example, the pressure transducer **146** can be used to detect the user's presence on the bed **112**, e.g., via a gross pressure change determination and/or via one or more of a respiration rate signal, heart rate signal, and/or other biometric signals. For example, a simple pressure detection process can identify an increase in pressure as an indication that the user is present on the bed **112**. As another example, the processor **136** can determine that the user is present on the bed **112** if the detected pressure increases above a specified threshold (so as to indicate that a person or other object above a certain weight is positioned on the bed **112**). As yet another example, the processor **136** can identify an increase in pressure in combination with detected slight, rhythmic fluctuations in pressure as corresponding to the user being present on the bed **112**. The presence of rhythmic fluctuations can be identified as being caused by respiration or heart rhythm (or both) of the user. The detection of respiration or a heartbeat can distinguish between the user being present on the bed and another object (e.g., a suit case) being placed upon the bed.

(37) In some implementations, fluctuations in pressure can be measured at the pump **120**. For example, one or more pressure sensors can be located within one or more internal cavities of the pump **120** to detect fluctuations in pressure within the pump **120**. The fluctuations in pressure detected at the pump **120** can indicate fluctuations in pressure in one or both of the chambers **114A** and **114B**. One or more sensors located at the pump **120** can be in fluid communication with the one or both of the chambers **114A** and **114B**, and the sensors can be operative to determine pressure within the chambers **114A** and **114B**. The control box **124** can be configured to determine at least one vital sign (e.g., heart rate, respiratory rate) based on the pressure within the chamber **114A** or the chamber **114B**.

(38) In some implementations, the control box **124** can analyze a pressure signal detected by one or more pressure sensors to determine a heart rate, respiration rate, and/or other vital signs of a user lying or sitting on the chamber **114A** or the chamber **114B**. More specifically, when a user lies on the bed **112** positioned over the chamber **114A**, each of the user's heart beats, breaths, and other movements can create a force on the bed **112** that is transmitted to the chamber **114A**. As a result of

the force input to the chamber **114A** from the user's movement, a wave can propagate through the chamber **114A** and into the pump **120**. A pressure sensor located at the pump **120** can detect the wave, and thus the pressure signal output by the sensor can indicate a heart rate, respiratory rate, or other information regarding the user.

(39) With regard to sleep state, air bed system **100** can determine a user's sleep state by using various biometric signals such as heart rate, respiration, and/or movement of the user. While the user is sleeping, the processor **136** can receive one or more of the user's biometric signals (e.g., heart rate, respiration, and motion) and determine the user's present sleep state based on the received biometric signals. In some implementations, signals indicating fluctuations in pressure in one or both of the chambers **114A** and **114B** can be amplified and/or filtered to allow for more precise detection of heart rate and respiratory rate.

(40) The control box **124** can perform a pattern recognition algorithm or other calculation based on the amplified and filtered pressure signal to determine the user's heart rate and respiratory rate. For example, the algorithm or calculation can be based on assumptions that a heart rate portion of the signal has a frequency in the range of 0.5-4.0 Hz and that a respiration rate portion of the signal has a frequency in the range of less than 1 Hz. The control box **124** can also be configured to determine other characteristics of a user based on the received pressure signal, such as blood pressure, tossing and turning movements, rolling movements, limb movements, weight, the presence or lack of presence of a user, and/or the identity of the user. Techniques for monitoring a user's sleep using heart rate information, respiration rate information, and other user information are disclosed in U.S. Patent Application Publication No. 20100170043 to Steven J. Young et al., titled "APPARATUS FOR MONITORING VITAL SIGNS," the entire contents of which is incorporated herein by reference.

(41) For example, the pressure transducer **146** can be used to monitor the air pressure in the chambers **114A** and **114B** of the bed **112**. If the user on the bed **112** is not moving, the air pressure changes in the air chamber **114A** or **114B** can be relatively minimal, and can be attributable to respiration and/or heartbeat. When the user on the bed **112** is moving, however, the air pressure in the mattress can fluctuate by a much larger amount. Thus, the pressure signals generated by the pressure transducer **146** and received by the processor **136** can be filtered and indicated as corresponding to motion, heartbeat, or respiration.

(42) In some implementations, rather than performing the data analysis in the control box **124** with the processor **136**, a digital signal processor (DSP) can be provided to analyze the data collected by the pressure transducer **146**. Alternatively, the data collected by the pressure transducer **146** could be sent to a cloud-based computing system for remote analysis.

(43) In some implementations, the example air bed system **100** further includes a temperature controller configured to increase, decrease, or maintain the temperature of a bed, for example for the comfort of the user. For example, a pad can be placed on top of or be part of the bed **112**, or can be placed on top of or be part of one or both of the chambers **114A** and **114B**. Air can be pushed through the pad and vented to cool off a user of the bed. Conversely, the pad can include a heating element that can be used to keep the user warm. In some implementations, the temperature controller can receive temperature readings from the pad. In some implementations, separate pads are used for the different sides of the bed **112** (e.g., corresponding to the locations of the chambers **114A** and **114B**) to provide for differing temperature control for the different sides of the bed.

(44) In some implementations, the user of the air bed system **100** can use an input device, such as the remote control **122**, to input a desired temperature for the surface of the bed **112** (or for a portion of the surface of the bed **112**). The desired temperature can be encapsulated in a command data structure that includes the desired temperature as well as identifies the temperature controller as the desired component to be controlled. The command data structure can then be transmitted via Bluetooth or another suitable communication protocol to the processor **136**. In various examples, the command data structure is encrypted before being transmitted. The temperature controller can

then configure its elements to increase or decrease the temperature of the pad depending on the temperature input into remote control **122** by the user.

(45) In some implementations, data can be transmitted from a component back to the processor **136** or to one or more display devices, such as the display **126**. For example, the current temperature as determined by a sensor element of temperature controller, the pressure of the bed, the current position of the foundation or other information can be transmitted to control box **124**. The control box **124** can then transmit the received information to remote control **122** where it can be displayed to the user (e.g., on the display **126**).

(46) In some implementations, the example air bed system **100** further includes an adjustable foundation and an articulation controller configured to adjust the position of a bed (e.g., the bed **112**) by adjusting the adjustable foundation that supports the bed. For example, the articulation controller can adjust the bed **112** from a flat position to a position in which a head portion of a mattress of the bed is inclined upward (e.g., to facilitate a user sitting up in bed and/or watching television). In some implementations, the bed **112** includes multiple separately articulable sections. For example, portions of the bed corresponding to the locations of the chambers **114A** and **114B** can be articulated independently from each other, to allow one person positioned on the bed **112** surface to rest in a first position (e.g., a flat position) while a second person rests in a second position (e.g., an reclining position with the head raised at an angle from the waist). In some implementations, separate positions can be set for two different beds (e.g., two twin beds placed next to each other). The foundation of the bed **112** can include more than one zone that can be independently adjusted. The articulation controller can also be configured to provide different levels of massage to one or more users on the bed **112**.

(47) Example of a Bed in a Bedroom Environment

(48) FIG. 3 shows an example environment **300** including a bed **302** in communication with devices located in and around a home. In the example shown, the bed **302** includes pump **304** for controlling air pressure within two air chambers **306a** and **306b** (as described above with respect to the air chambers **114A-114B**). The pump **304** additionally includes circuitry for controlling inflation and deflation functionality performed by the pump **304**. The circuitry is further programmed to detect fluctuations in air pressure of the air chambers **306a-b** and used the detected fluctuations in air pressure to identify bed presence of a user **308**, sleep state of the user **308**, movement of the user **308**, and biometric signals of the user **308** such as heart rate and respiration rate. In the example shown, the pump **304** is located within a support structure of the bed **302** and the control circuitry **334** for controlling the pump **304** is integrated with the pump **304**. In some implementations, the control circuitry **334** is physically separate from the pump **304** and is in wireless or wired communication with the pump **304**. In some implementations, the pump **304** and/or control circuitry **334** are located outside of the bed **302**. In some implementations, various control functions can be performed by systems located in different physical locations. For example, circuitry for controlling actions of the pump **304** can be located within a pump casing of the pump **304** while control circuitry **334** for performing other functions associated with the bed **302** can be located in another portion of the bed **302**, or external to the bed **302**. As another example, control circuitry **334** located within the pump **304** can communicate with control circuitry **334** at a remote location through a LAN or WAN (e.g., the internet), either wireless or wired communications. As yet another example, the control circuitry **334** can be included in the control box **124** of FIGS. 1 and 2.

(49) The bed **300** includes the remote control **122**. The remote control **122** transmits command signals and status signals to the bed **300** as previously described in reference to FIGS. 1 and 2.

(50) In some implementations, one or more devices other than, or in addition to, the pump **304** and control circuitry **334** can be utilized to identify user bed presence, sleep state, movement, and biometric signals. For example, the bed **302** can include a second pump in addition to the pump **304**, with each of the two pumps connected to a respective one of the air chambers **306a-b**. For

example, the pump **304** can be in fluid communication with the air chamber **306b** to control inflation and deflation of the air chamber **306b** as well as detect user signals for a user located over the air chamber **306b** such as bed presence, sleep state, movement, and biometric signals while the second pump is in fluid communication with the air chamber **306a** to control inflation and deflation of the air chamber **306a** as well as detect user signals for a user located over the air chamber **306a**.

(51) As another example, the bed **302** can include one or more pressure sensitive pads or surface portions that are operable to detect movement, including user presence, user motion, respiration, and heart rate. For example, a first pressure sensitive pad can be incorporated into a surface of the bed **302** over a left portion of the bed **302**, where a first user would normally be located during sleep, and a second pressure sensitive pad can be incorporated into the surface of the bed **302** over a right portion of the bed **302**, where a second user would normally be located during sleep. The movement detected by the one or more pressure sensitive pads or surface portions can be used by control circuitry **334** to identify user sleep state, bed presence, or biometric signals.

(52) In some implementations, information detected by the bed (e.g., motion information) is processed by control circuitry **334** (e.g., control circuitry **334** integrated with the pump **304**) and provided to one or more user devices such as a user device **310** for presentation to the user **308** or to other users. In the example depicted in FIG. 3, the user device **310** is a tablet device; however, in some implementations, the user device **310** can be a personal computer, a smart phone, a smart television (e.g., a television **312**), or other user device capable of wired or wireless communication with the control circuitry **334**. The user device **310** can be in communication with control circuitry **334** of the bed **302** through a network or through direct point-to-point communication. For example, the control circuitry **334** can be connected to a LAN (e.g., through a Wi-Fi router) and communicate with the user device **310** through the LAN (either wired or wireless communications). As another example, the control circuitry **334** and the user device **310** can both connect to the Internet and communicate through the Internet. For example, the control circuitry **334** can connect to the Internet through a WiFi router and the user device **310** can connect to the Internet through communication with a cellular communication system. As another example, the control circuitry **334** can communicate directly with the user device **310** through a wireless communication protocol such as Bluetooth. As yet another example, the control circuitry **334** can communicate with the user device **310** through a wireless communication protocol such as ZigBee, Z-Wave, infrared, Thread, 6LoPan, BLE, Bluetooth, or another wireless communication protocol suitable for the application. As another example, the control circuitry **334** can communicate with the user device **310** through a wired connection such as, for example, a USB connector, serial/RS232, or another wired connection suitable for the application.

(53) The user device **310** can display a variety of information and statistics related to sleep, or user **308**'s interaction with the bed **302**. For example, a user interface displayed by the user device **310** can present information including amount of sleep for the user **308** over a period of time (e.g., a single evening, a week, a month, etc.) amount of deep sleep, ratio of deep sleep to restless sleep, time lapse between the user **308** getting into bed and the user **308** falling asleep, total amount of time spent in the bed **302** for a given period of time, heart rate for the user **308** over a period of time, respiration rate for the user **308** over a period of time, or other information related to user interaction with the bed **302** by the user **308** or one or more other users of the bed **302**. In some implementations, information for multiple users can be presented on the user device **310**, for example information for a first user positioned over the air chamber **306a** can be presented along with information for a second user positioned over the air chamber **306b**. In some implementations, the information presented on the user device **310** can vary according to the age of the user **308**. For example, the information presented on the user device **310** can evolve with the age of the user **308** such that different information is presented on the user device **310** as the user **308** ages as a child or an adult.

(54) The user device **310** can also be used as an interface for the control circuitry **334** of the bed

302 to allow the user **308** to enter information. The information entered by the user **308** can be used by the control circuitry **334** to provide better information to the user or to various control signals for controlling functions of the bed **302** or other devices. For example, the user can enter information such as weight, height, and age and the control circuitry **334** can use this information to provide the user **308** with a comparison of the user's tracked sleep information to sleep information of other people having similar weights, heights, and/or ages as the user **308**. As another example, the user **308** can use the user device **310** as an interface for controlling air pressure of the air chambers **306a** and **306b**, for controlling various recline or incline positions of the bed **302**, for controlling temperature of one or more surface temperature control devices of the bed **302**, or for allowing the control circuitry **334** to generate control signals for other devices (as described in greater detail below).

(55) In some implementations, control circuitry **334** of the bed **302** (e.g., control circuitry **334** integrated into the pump **304**) can communicate with other first, second, or third party devices or systems in addition to or instead of the user device **310**. For example, the control circuitry **334** can communicate with the television **312**, a lighting system **314**, a thermostat **316**, a security system **318**, or other household devices such as an oven **322**, a coffee maker **324**, a lamp **326** on a bedside table **340**, and a nightlight **328**. Other examples of devices and/or systems that the control circuitry **334** can communicate with include a system for controlling window blinds **330**, one or more devices for detecting or controlling the states of one or more doors **332** (such as detecting if a door is open, detecting if a door is locked, or automatically locking a door), and a system for controlling a garage door **320** (e.g., control circuitry **334** integrated with a garage door opener for identifying an open or closed state of the garage door **320** and for causing the garage door opener to open or close the garage door **320**). Communications between the control circuitry **334** of the bed **302** and other devices can occur through a network (e.g., a LAN or the Internet) or as point-to-point communication (e.g., using Bluetooth, radio communication, or a wired connection). In some implementations, control circuitry **334** of different beds **302** can communicate with different sets of devices. For example, a kid bed may not communicate with and/or control the same devices as an adult bed. In some embodiments, the bed **302** can evolve with the age of the user such that the control circuitry **334** of the bed **302** communicates with different devices as a function of age of the user.

(56) The control circuitry **334** can receive information and inputs from other devices/systems and use the received information and inputs to control actions of the bed **302** or other devices. For example, the control circuitry **334** can receive information from the thermostat **316** indicating a current environmental temperature for a house or room in which the bed **302** is located. The control circuitry **334** can use the received information (along with other information) to determine if a temperature of all or a portion of the surface of the bed **302** should be raised or lowered. The control circuitry **334** can then cause a heating or cooling mechanism of the bed **302** to raise or lower the temperature of the surface of the bed **302**. For example, the user **308** can indicate a desired sleeping temperature of 74 degrees while a second user of the bed **302** indicates a desired sleeping temperature of 72 degrees. The thermostat **316** can indicate to the control circuitry **334** that the current temperature of the bedroom is 72 degrees. The control circuitry **334** can identify that the user **308** has indicated a desired sleeping temperature of 74 degrees, and send control signals to a heating pad located on the user **308**'s side of the bed to raise the temperature of the portion of the surface of the bed **302** where the user **308** is located to raise the temperature of the user **308**'s sleeping surface to the desired temperature.

(57) The control circuitry **334** can also generate control signals controlling other devices and propagate the control signals to the other devices. In some implementations, the control signals are generated based on information collected by the control circuitry **334**, including information related to user interaction with the bed **302** by the user **308** and/or one or more other users. In some implementations, information collected from one or more other devices other than the bed **302** are

used when generating the control signals. For example, information relating to environmental occurrences (e.g., environmental temperature, environmental noise level, and environmental light level), time of day, time of year, day of the week, or other information can be used when generating control signals for various devices in communication with the control circuitry **334** of the bed **302**. For example, information on the time of day can be combined with information relating to movement and bed presence of the user **308** to generate control signals for the lighting system **314**. In some implementations, rather than or in addition to providing control signals for one or more other devices, the control circuitry **334** can provide collected information (e.g., information related to user movement, bed presence, sleep state, or biometric signals for the user **308**) to one or more other devices to allow the one or more other devices to utilize the collected information when generating control signals. For example, control circuitry **334** of the bed **302** can provide information relating to user interactions with the bed **302** by the user **308** to a central controller (not shown) that can use the provided information to generate control signals for various devices, including the bed **302**.

(58) Still referring to FIG. **3**, the control circuitry **334** of the bed **302** can generate control signals for controlling actions of other devices, and transmit the control signals to the other devices in response to information collected by the control circuitry **334**, including bed presence of the user **308**, sleep state of the user **308**, and other factors. For example, control circuitry **334** integrated with the pump **304** can detect a feature of a mattress of the bed **302**, such as an increase in pressure in the air chamber **306b**, and use this detected increase in air pressure to determine that the user **308** is present on the bed **302**. In some implementations, the control circuitry **334** can identify a heart rate or respiratory rate for the user **308** to identify that the increase in pressure is due to a person sitting, laying, or otherwise resting on the bed **302** rather than an inanimate object (such as a suitcase) having been placed on the bed **302**. In some implementations, the information indicating user bed presence is combined with other information to identify a current or future likely state for the user **308**. For example, a detected user bed presence at 11:00 am can indicate that the user is sitting on the bed (e.g., to tie her shoes, or to read a book) and does not intend to go to sleep, while a detected user bed presence at 10:00 pm can indicate that the user **308** is in bed for the evening and is intending to fall asleep soon. As another example, if the control circuitry **334** detects that the user **308** has left the bed **302** at 6:30 am (e.g., indicating that the user **308** has woken up for the day), and then later detects user bed presence of the user **308** at 7:30 am, the control circuitry **334** can use this information that the newly detected user bed presence is likely temporary (e.g., while the user **308** ties her shoes before heading to work) rather than an indication that the user **308** is intending to stay on the bed **302** for an extended period.

(59) In some implementations, the control circuitry **334** is able to use collected information (including information related to user interaction with the bed **302** by the user **308**, as well as environmental information, time information, and input received from the user) to identify use patterns for the user **308**. For example, the control circuitry **334** can use information indicating bed presence and sleep states for the user **308** collected over a period of time to identify a sleep pattern for the user. For example, the control circuitry **334** can identify that the user **308** generally goes to bed between 9:30 pm and 10:00 pm, generally falls asleep between 10:00 pm and 11:00 pm, and generally wakes up between 6:30 am and 6:45 am based on information indicating user presence and biometrics for the user **308** collected over a week. The control circuitry **334** can use identified patterns for a user to better process and identify user interactions with the bed **302** by the user **308**. If the user does stay in bed, then a new sleep pattern can be started.

(60) For example, given the above example user bed presence, sleep, and wake patterns for the user **308**, if the user **308** is detected as being on the bed at 3:00 pm, the control circuitry **334** can determine that the user's presence on the bed is only temporary, and use this determination to generate different control signals than would be generated if the control circuitry **334** determined that the user **308** was in bed for the evening. As another example, if the control circuitry **334**

detects that the user **308** has gotten out of bed at 3:00 am, the control circuitry **334** can use identified patterns for the user **308** to determine that the user has only gotten up temporarily (for example, to use the rest room, or get a glass of water) and is not up for the day. By contrast, if the control circuitry **334** identifies that the user **308** has gotten out of the bed **302** at 6:40 am, the control circuitry **334** can determine that the user is up for the day and generate a different set of control signals than those that would be generated if it were determined that the user **308** were only getting out of bed temporarily (as would be the case when the user **308** gets out of the bed **302** at 3:00 am). For other users **308**, getting out of the bed **302** at 3:00 am can be the normal wake-up time, which the control circuitry **334** can learn and respond to accordingly.

(61) As described above, the control circuitry **334** for the bed **302** can generate control signals for control functions of various other devices. The control signals can be generated, at least in part, based on detected interactions by the user **308** with the bed **302**, as well as other information including time, date, temperature, etc. For example, the control circuitry **334** can communicate with the television **312**, receive information from the television **312**, and generate control signals for controlling functions of the television **312**. For example, the control circuitry **334** can receive an indication from the television **312** that the television **312** is currently on. If the television **312** is located in a different room from the bed **302**, the control circuitry **334** can generate a control signal to turn the television **312** off upon making a determination that the user **308** has gone to bed for the evening. For example, if bed presence of the user **308** on the bed **302** is detected during a particular time range (e.g., between 8:00 pm and 7:00 am) and persists for longer than a threshold period of time (e.g., 10 minutes) the control circuitry **334** can use this information to determine that the user **308** is in bed for the evening. If the television **312** is on (as indicated by communications received by the control circuitry **334** of the bed **302** from the television **312**) the control circuitry **334** can generate a control signal to turn the television **312** off. The control signals can then be transmitted to the television (e.g., through a directed communication link between the television **312** and the control circuitry **334** or through a network). As another example, rather than turning off the television **312** in response to detection of user bed presence, the control circuitry **334** can generate a control signal that causes the volume of the television **312** to be lowered by a pre-specified amount.

(62) As another example, upon detecting that the user **308** has left the bed **302** during a specified time range (e.g., between 6:00 am and 8:00 am) the control circuitry **334** can generate control signals to cause the television **312** to turn on and tune to a pre-specified channel (e.g., the user **308** has indicated a preference for watching the morning news upon getting out of bed in the morning). The control circuitry **334** can generate the control signal and transmit the signal to the television **312** to cause the television **312** to turn on and tune to the desired station (which could be stored at the control circuitry **334**, the television **312**, or another location). As another example, upon detecting that the user **308** has gotten up for the day, the control circuitry **334** can generate and transmit control signals to cause the television **312** to turn on and begin playing a previously recorded program from a digital video recorder (DVR) in communication with the television **312**.

(63) As another example, if the television **312** is in the same room as the bed **302**, the control circuitry **334** does not cause the television **312** to turn off in response to detection of user bed presence. Rather, the control circuitry **334** can generate and transmit control signals to cause the television **312** to turn off in response to determining that the user **308** is asleep. For example, the control circuitry **334** can monitor biometric signals of the user **308** (e.g., motion, heart rate, respiration rate) to determine that the user **308** has fallen asleep. Upon detecting that the user **308** is sleeping, the control circuitry **334** generates and transmits a control signal to turn the television **312** off. As another example, the control circuitry **334** can generate the control signal to turn off the television **312** after a threshold period of time after the user **308** has fallen asleep (e.g., 10 minutes after the user has fallen asleep). As another example, the control circuitry **334** generates control signals to lower the volume of the television **312** after determining that the user **308** is asleep. As

yet another example, the control circuitry **334** generates and transmits a control signal to cause the television to gradually lower in volume over a period of time and then turn off in response to determining that the user **308** is asleep.

(64) In some implementations, the control circuitry **334** can similarly interact with other media devices, such as computers, tablets, smart phones, stereo systems, etc. For example, upon detecting that the user **308** is asleep, the control circuitry **334** can generate and transmit a control signal to the user device **310** to cause the user device **310** to turn off, or turn down the volume on a video or audio file being played by the user device **310**.

(65) The control circuitry **334** can additionally communicate with the lighting system **314**, receive information from the lighting system **314**, and generate control signals for controlling functions of the lighting system **314**. For example, upon detecting user bed presence on the bed **302** during a certain time frame (e.g., between 8:00 pm and 7:00 am) that lasts for longer than a threshold period of time (e.g., 10 minutes) the control circuitry **334** of the bed **302** can determine that the user **308** is in bed for the evening. In response to this determination, the control circuitry **334** can generate control signals to cause lights in one or more rooms other than the room in which the bed **302** is located to switch off. The control signals can then be transmitted to the lighting system **314** and executed by the lighting system **314** to cause the lights in the indicated rooms to shut off. For example, the control circuitry **334** can generate and transmit control signals to turn off lights in all common rooms, but not in other bedrooms. As another example, the control signals generated by the control circuitry **334** can indicate that lights in all rooms other than the room in which the bed **302** is located are to be turned off, while one or more lights located outside of the house containing the bed **302** are to be turned on, in response to determining that the user **308** is in bed for the evening. Additionally, the control circuitry **334** can generate and transmit control signals to cause the nightlight **328** to turn on in response to determining user **308** bed presence or whether the user **308** is asleep. As another example, the control circuitry **334** can generate first control signals for turning off a first set of lights (e.g., lights in common rooms) in response to detecting user bed presence, and second control signals for turning off a second set of lights (e.g., lights in the room in which the bed **302** is located) in response to detecting that the user **308** is asleep.

(66) In some implementations, in response to determining that the user **308** is in bed for the evening, the control circuitry **334** of the bed **302** can generate control signals to cause the lighting system **314** to implement a sunset lighting scheme in the room in which the bed **302** is located. A sunset lighting scheme can include, for example, dimming the lights (either gradually over time, or all at once) in combination with changing the color of the light in the bedroom environment, such as adding an amber hue to the lighting in the bedroom. The sunset lighting scheme can help to put the user **308** to sleep when the control circuitry **334** has determined that the user **308** is in bed for the evening.

(67) The control circuitry **334** can also be configured to implement a sunrise lighting scheme when the user **308** wakes up in the morning. The control circuitry **334** can determine that the user **308** is awake for the day, for example, by detecting that the user **308** has gotten off of the bed **302** (i.e., is no longer present on the bed **302**) during a specified time frame (e.g., between 6:00 am and 8:00 am). As another example, the control circuitry **334** can monitor movement, heart rate, respiratory rate, or other biometric signals of the user **308** to determine that the user **308** is awake even though the user **308** has not gotten out of bed. If the control circuitry **334** detects that the user is awake during a specified time frame, the control circuitry **334** can determine that the user **308** is awake for the day. The specified time frame can be, for example, based on previously recorded user bed presence information collected over a period of time (e.g., two weeks) that indicates that the user **308** usually wakes up for the day between 6:30 am and 7:30 am. In response to the control circuitry **334** determining that the user **308** is awake, the control circuitry **334** can generate control signals to cause the lighting system **314** to implement the sunrise lighting scheme in the bedroom in which the bed **302** is located. The sunrise lighting scheme can include, for example, turning on lights

(e.g., the lamp **326**, or other lights in the bedroom). The sunrise lighting scheme can further include gradually increasing the level of light in the room where the bed **302** is located (or in one or more other rooms). The sunrise lighting scheme can also include only turning on lights of specified colors. For example, the sunrise lighting scheme can include lighting the bedroom with blue light to gently assist the user **308** in waking up and becoming active.

(68) In some implementations, the control circuitry **334** can generate different control signals for controlling actions of one or more components, such as the lighting system **314**, depending on a time of day that user interactions with the bed **302** are detected. For example, the control circuitry **334** can use historical user interaction information for interactions between the user **308** and the bed **302** to determine that the user **308** usually falls asleep between 10:00 pm and 11:00 pm and usually wakes up between 6:30 am and 7:30 am on weekdays. The control circuitry **334** can use this information to generate a first set of control signals for controlling the lighting system **314** if the user **308** is detected as getting out of bed at 3:00 am and to generate a second set of control signals for controlling the lighting system **314** if the user **308** is detected as getting out of bed after 6:30 am. For example, if the user **308** gets out of bed prior to 6:30 am, the control circuitry **334** can turn on lights that guide the user **308**'s route to a restroom. As another example, if the user **308** gets out of bed prior to 6:30 am, the control circuitry **334** can turn on lights that guide the user **308**'s route to the kitchen (which can include, for example, turning on the nightlight **328**, turning on under bed lighting, or turning on the lamp **326**).

(69) As another example, if the user **308** gets out of bed after 6:30 am, the control circuitry **334** can generate control signals to cause the lighting system **314** to initiate a sunrise lighting scheme, or to turn on one or more lights in the bedroom and/or other rooms. In some implementations, if the user **308** is detected as getting out of bed prior to a specified morning rise time for the user **308**, the control circuitry **334** causes the lighting system **314** to turn on lights that are dimmer than lights that are turned on by the lighting system **314** if the user **308** is detected as getting out of bed after the specified morning rise time. Causing the lighting system **314** to only turn on dim lights when the user **308** gets out of bed during the night (i.e., prior to normal rise time for the user **308**) can prevent other occupants of the house from being woken by the lights while still allowing the user **308** to see in order to reach the restroom, kitchen, or another destination within the house.

(70) The historical user interaction information for interactions between the user **308** and the bed **302** can be used to identify user sleep and awake time frames. For example, user bed presence times and sleep times can be determined for a set period of time (e.g., two weeks, a month, etc.). The control circuitry **334** can then identify a typical time range or time frame in which the user **308** goes to bed, a typical time frame for when the user **308** falls asleep, and a typical time frame for when the user **308** wakes up (and in some cases, different time frames for when the user **308** wakes up and when the user **308** actually gets out of bed). In some implementations, buffer time can be added to these time frames. For example, if the user is identified as typically going to bed between 10:00 pm and 10:30 pm, a buffer of a half hour in each direction can be added to the time frame such that any detection of the user getting onto the bed between 9:30 pm and 11:00 pm is interpreted as the user **308** going to bed for the evening. As another example, detection of bed presence of the user **308** starting from a half hour before the earliest typical time that the user **308** goes to bed extending until the typical wake up time (e.g., 6:30 am) for the user can be interpreted as the user going to bed for the evening. For example, if the user typically goes to bed between 10:00 pm and 10:30 pm, if the user's bed presence is sensed at 12:30 am one night, that can be interpreted as the user getting into bed for the evening even though this is outside of the user's typical time frame for going to bed because it has occurred prior to the user's normal wake up time. In some implementations, different time frames are identified for different times of the year (e.g., earlier bed time during winter vs. summer) or at different times of the week (e.g., user wakes up earlier on weekdays than on weekends).

(71) The control circuitry **334** can distinguish between the user **308** going to bed for an extended

period (such as for the night) as opposed to being present on the bed **302** for a shorter period (such as for a nap) by sensing duration of presence of the user **308**. In some examples, the control circuitry **334** can distinguish between the user **308** going to bed for an extended period (such as for the night) as opposed to going to bed for a shorter period (such as for a nap) by sensing duration of sleep of the user **308**. For example, the control circuitry **334** can set a time threshold whereby if the user **308** is sensed on the bed **302** for longer than the threshold, the user **308** is considered to have gone to bed for the night. In some examples, the threshold can be about 2 hours, whereby if the user **308** is sensed on the bed **302** for greater than 2 hours, the control circuitry **334** registers that as an extended sleep event. In other examples, the threshold can be greater than or less than two hours.

(72) The control circuitry **334** can detect repeated extended sleep events to determine a typical bed time range of the user **308** automatically, without requiring the user **308** to enter a bed time range. This can allow the control circuitry **334** to accurately estimate when the user **308** is likely to go to bed for an extended sleep event, regardless of whether the user **308** typically goes to bed using a traditional sleep schedule or a non-traditional sleep schedule. The control circuitry **334** can then use knowledge of the bed time range of the user **308** to control one or more components (including components of the bed **302** and/or non-bed peripherals) differently based on sensing bed presence during the bed time range or outside of the bed time range.

(73) In some examples, the control circuitry **334** can automatically determine the bed time range of the user **308** without requiring user inputs. In some examples, the control circuitry **334** can determine the bed time range of the user **308** automatically and in combination with user inputs. In some examples, the control circuitry **334** can set the bed time range directly according to user inputs. In some examples, the control circuitry **334** can associate different bed times with different days of the week. In each of these examples, the control circuitry **334** can control one or more components (such as the lighting system **314**, the thermostat **316**, the security system **318**, the oven **322**, the coffee maker **324**, the lamp **326**, and the nightlight **328**), as a function of sensed bed presence and the bed time range.

(74) The control circuitry **334** can additionally communicate with the thermostat **316**, receive information from the thermostat **316**, and generate control signals for controlling functions of the thermostat **316**. For example, the user **308** can indicate user preferences for different temperatures at different times, depending on the sleep state or bed presence of the user **308**. For example, the user **308** may prefer an environmental temperature of 72 degrees when out of bed, 70 degrees when in bed but awake, and 68 degrees when sleeping. The control circuitry **334** of the bed **302** can detect bed presence of the user **308** in the evening and determine that the user **308** is in bed for the night. In response to this determination, the control circuitry **334** can generate control signals to cause the thermostat to change the temperature to 70 degrees. The control circuitry **334** can then transmit the control signals to the thermostat **316**. Upon detecting that the user **308** is in bed during the bed time range or asleep, the control circuitry **334** can generate and transmit control signals to cause the thermostat **316** to change the temperature to 68. The next morning, upon determining that the user is awake for the day (e.g., the user **308** gets out of bed after 6:30 am) the control circuitry **334** can generate and transmit control circuitry **334** to cause the thermostat to change the temperature to 72 degrees.

(75) In some implementations, the control circuitry **334** can similarly generate control signals to cause one or more heating or cooling elements on the surface of the bed **302** to change temperature at various times, either in response to user interaction with the bed **302** or at various pre-programmed times. For example, the control circuitry **334** can activate a heating element to raise the temperature of one side of the surface of the bed **302** to 73 degrees when it is detected that the user **308** has fallen asleep. As another example, upon determining that the user **308** is up for the day, the control circuitry **334** can turn off a heating or cooling element. As yet another example, the user **308** can pre-program various times at which the temperature at the surface of the bed should

be raised or lowered. For example, the user can program the bed **302** to raise the surface temperature to 76 degrees at 10:00 pm, and lower the surface temperature to 68 degrees at 11:30 pm.

(76) In some implementations, in response to detecting user bed presence of the user **308** and/or that the user **308** is asleep, the control circuitry **334** can cause the thermostat **316** to change the temperature in different rooms to different values. For example, in response to determining that the user **308** is in bed for the evening, the control circuitry **334** can generate and transmit control signals to cause the thermostat **316** to set the temperature in one or more bedrooms of the house to 72 degrees and set the temperature in other rooms to 67 degrees.

(77) The control circuitry **334** can also receive temperature information from the thermostat **316** and use this temperature information to control functions of the bed **302** or other devices. For example, as discussed above, the control circuitry **334** can adjust temperatures of heating elements included in the bed **302** in response to temperature information received from the thermostat **316**.

(78) In some implementations, the control circuitry **334** can generate and transmit control signals for controlling other temperature control systems. For example, in response to determining that the user **308** is awake for the day, the control circuitry **334** can generate and transmit control signals for causing floor heating elements to activate. For example, the control circuitry **334** can cause a floor heating system for a master bedroom to turn on in response to determining that the user **308** is awake for the day.

(79) The control circuitry **334** can additionally communicate with the security system **318**, receive information from the security system **318**, and generate control signals for controlling functions of the security system **318**. For example, in response to detecting that the user **308** is in bed for the evening, the control circuitry **334** can generate control signals to cause the security system to engage or disengage security functions. The control circuitry **334** can then transmit the control signals to the security system **318** to cause the security system **318** to engage. As another example, the control circuitry **334** can generate and transmit control signals to cause the security system **318** to disable in response to determining that the user **308** is awake for the day (e.g., user **308** is no longer present on the bed **302** after 6:00 am). In some implementations, the control circuitry **334** can generate and transmit a first set of control signals to cause the security system **318** to engage a first set of security features in response to detecting user bed presence of the user **308**, and can generate and transmit a second set of control signals to cause the security system **318** to engage a second set of security features in response to detecting that the user **308** has fallen asleep.

(80) In some implementations, the control circuitry **334** can receive alerts from the security system **318** (and/or a cloud service associated with the security system **318**) and indicate the alert to the user **308**. For example, the control circuitry **334** can detect that the user **308** is in bed for the evening and in response, generate and transmit control signals to cause the security system **318** to engage or disengage. The security system can then detect a security breach (e.g., someone has opened the door **332** without entering the security code, or someone has opened a window when the security system **318** is engaged). The security system **318** can communicate the security breach to the control circuitry **334** of the bed **302**. In response to receiving the communication from the security system **318**, the control circuitry **334** can generate control signals to alert the user **308** to the security breach. For example, the control circuitry **334** can cause the bed **302** to vibrate. As another example, the control circuitry **334** can cause portions of the bed **302** to articulate (e.g., cause the head section to raise or lower) in order to wake the user **308** and alert the user to the security breach. As another example, the control circuitry **334** can generate and transmit control signals to cause the lamp **326** to flash on and off at regular intervals to alert the user **308** to the security breach. As another example, the control circuitry **334** can alert the user **308** of one bed **302** regarding a security breach in a bedroom of another bed, such as an open window in a kid's bedroom. As another example, the control circuitry **334** can send an alert to a garage door controller (e.g., to close and lock the door). As another example, the control circuitry **334** can send

an alert for the security to be disengaged.

(81) The control circuitry **334** can additionally generate and transmit control signals for controlling the garage door **320** and receive information indicating a state of the garage door **320** (i.e., open or closed). For example, in response to determining that the user **308** is in bed for the evening, the control circuitry **334** can generate and transmit a request to a garage door opener or another device capable of sensing if the garage door **320** is open. The control circuitry **334** can request information on the current state of the garage door **320**. If the control circuitry **334** receives a response (e.g., from the garage door opener) indicating that the garage door **320** is open, the control circuitry **334** can either notify the user **308** that the garage door is open, or generate a control signal to cause the garage door opener to close the garage door **320**. For example, the control circuitry **334** can send a message to the user device **310** indicating that the garage door is open. As another example, the control circuitry **334** can cause the bed **302** to vibrate. As yet another example, the control circuitry **334** can generate and transmit a control signal to cause the lighting system **314** to cause one or more lights in the bedroom to flash to alert the user **308** to check the user device **310** for an alert (in this example, an alert regarding the garage door **320** being open). Alternatively, or additionally, the control circuitry **334** can generate and transmit control signals to cause the garage door opener to close the garage door **320** in response to identifying that the user **308** is in bed for the evening and that the garage door **320** is open. In some implementations, control signals can vary depend on the age of the user **308**.

(82) The control circuitry **334** can activate additional security features based on the presence of the user in bed **302**, such as motion tracking or other biometric tracking outside of the user's bedroom due to the security system knowing that the user was in bed and sleeping based on a signal from the control system. If the user wakes and gets out of bed, the additional features can be disabled until the user either is awake for their daily routine or the additional features can become re-enabled if the user returns to bed.

(83) The control circuitry **334** can similarly send and receive communications for controlling or receiving state information associated with the door **332** or the oven **322**. For example, upon detecting that the user **308** is in bed for the evening, the control circuitry **334** can generate and transmit a request to a device or system for detecting a state of the door **332**. Information returned in response to the request can indicate various states for the door **332** such as open, closed but unlocked, or closed and locked. If the door **332** is open or closed but unlocked, the control circuitry **334** can alert the user **308** to the state of the door, such as in a manner described above with reference to the garage door **320**. Alternatively, or in addition to alerting the user **308**, the control circuitry **334** can generate and transmit control signals to cause the door **332** to lock, or to close and lock. If the door **332** is closed and locked, the control circuitry **334** can determine that no further action is needed.

(84) Similarly, upon detecting that the user **308** is in bed for the evening, the control circuitry **334** can generate and transmit a request to the oven **322** to request a state of the oven **322** (e.g., on or off). If the oven **322** is on, the control circuitry **334** can alert the user **308** and/or generate and transmit control signals to cause the oven **322** to turn off. If the oven is already off, the control circuitry **334** can determine that no further action is necessary. In some implementations, different alerts can be generated for different events. For example, the control circuitry **334** can cause the lamp **326** (or one or more other lights, via the lighting system **314**) to flash in a first pattern if the security system **318** has detected a breach, flash in a second pattern if garage door **320** is on, flash in a third pattern if the door **332** is open, flash in a fourth pattern if the oven **322** is on, and flash in a fifth pattern if another bed has detected that a user of that bed has gotten up (e.g., that a child of the user **308** has gotten out of bed in the middle of the night as sensed by a sensor in the bed **302** of the child). Other examples of alerts that can be processed by the control circuitry **334** of the bed **302** and communicated to the user include a smoke detector detecting smoke (and communicating this detection of smoke to the control circuitry **334**), a carbon monoxide tester detecting carbon

monoxide, a heater malfunctioning, or an alert from any other device capable of communicating with the control circuitry **334** and detecting an occurrence that should be brought to the user **308**'s attention.

(85) The control circuitry **334** can also communicate with a system or device for controlling a state of the window blinds **330**. For example, in response to determining that the user **308** is in bed for the evening, the control circuitry **334** can generate and transmit control signals to cause the window blinds **330** to close. As another example, in response to determining that the user **308** is up for the day (e.g., user has gotten out of bed after 6:30 am) the control circuitry **334** can generate and transmit control signals to cause the window blinds **330** to open. By contrast, if the user **308** gets out of bed prior to a normal rise time for the user **308**, the control circuitry **334** can determine that the user **308** is not awake for the day and does not generate control signals for causing the window blinds **330** to open. As yet another example, the control circuitry **334** can generate and transmit control signals that cause a first set of blinds to close in response to detecting user bed presence of the user **308** and a second set of blinds to close in response to detecting that the user **308** is asleep.

(86) The control circuitry **334** can generate and transmit control signals for controlling functions of other household devices in response to detecting user interactions with the bed **302**. For example, in response to determining that the user **308** is awake for the day, the control circuitry **334** can generate and transmit control signals to the coffee maker **324** to cause the coffee maker **324** to begin brewing coffee. As another example, the control circuitry **334** can generate and transmit control signals to the oven **322** to cause the oven to begin preheating (for users that like fresh baked bread in the morning). As another example, the control circuitry **334** can use information indicating that the user **308** is awake for the day along with information indicating that the time of year is currently winter and/or that the outside temperature is below a threshold value to generate and transmit control signals to cause a car engine block heater to turn on.

(87) As another example, the control circuitry **334** can generate and transmit control signals to cause one or more devices to enter a sleep mode in response to detecting user bed presence of the user **308**, or in response to detecting that the user **308** is asleep. For example, the control circuitry **334** can generate control signals to cause a mobile phone of the user **308** to switch into sleep mode. The control circuitry **334** can then transmit the control signals to the mobile phone. Later, upon determining that the user **308** is up for the day, the control circuitry **334** can generate and transmit control signals to cause the mobile phone to switch out of sleep mode.

(88) In some implementations, the control circuitry **334** can communicate with one or more noise control devices. For example, upon determining that the user **308** is in bed for the evening, or that the user **308** is asleep, the control circuitry **334** can generate and transmit control signals to cause one or more noise cancellation devices to activate. The noise cancellation devices can, for example, be included as part of the bed **302** or located in the bedroom with the bed **302**. As another example, upon determining that the user **308** is in bed for the evening or that the user **308** is asleep, the control circuitry **334** can generate and transmit control signals to turn the volume on, off, up, or down, for one or more sound generating devices, such as a stereo system radio, computer, tablet, etc.

(89) Additionally, functions of the bed **302** are controlled by the control circuitry **334** in response to user interactions with the bed **302**. For example, the bed **302** can include an adjustable foundation and an articulation controller configured to adjust the position of one or more portions of the bed **302** by adjusting the adjustable foundation that supports the bed. For example, the articulation controller can adjust the bed **302** from a flat position to a position in which a head portion of a mattress of the bed **302** is inclined upward (e.g., to facilitate a user sitting up in bed and/or watching television). In some implementations, the bed **302** includes multiple separately articulable sections. For example, portions of the bed corresponding to the locations of the air chambers **306a** and **306b** can be articulated independently from each other, to allow one person positioned on the bed **302** surface to rest in a first position (e.g., a flat position) while a second person rests in a

second position (e.g., a reclining position with the head raised at an angle from the waist). In some implementations, separate positions can be set for two different beds (e.g., two twin beds placed next to each other). The foundation of the bed **302** can include more than one zone that can be independently adjusted. The articulation controller can also be configured to provide different levels of massage to one or more users on the bed **302** or to cause the bed to vibrate to communicate alerts to the user **308** as described above.

(90) The control circuitry **334** can adjust positions (e.g., incline and decline positions for the user **308** and/or an additional user of the bed **302**) in response to user interactions with the bed **302**. For example, the control circuitry **334** can cause the articulation controller to adjust the bed **302** to a first recline position for the user **308** in response to sensing user bed presence for the user **308**. The control circuitry **334** can cause the articulation controller to adjust the bed **302** to a second recline position (e.g., a less reclined, or flat position) in response to determining that the user **308** is asleep. As another example, the control circuitry **334** can receive a communication from the television **312** indicating that the user **308** has turned off the television **312**, and in response the control circuitry **334** can cause the articulation controller to adjust the position of the bed **302** to a preferred user sleeping position (e.g., due to the user turning off the television **312** while the user **308** is in bed indicating that the user **308** wishes to go to sleep).

(91) In some implementations, the control circuitry **334** can control the articulation controller so as to wake up one user of the bed **302** without waking another user of the bed **302**. For example, the user **308** and a second user of the bed **302** can each set distinct wakeup times (e.g., 6:30 am and 7:15 am respectively). When the wakeup time for the user **308** is reached, the control circuitry **334** can cause the articulation controller to vibrate or change the position of only a side of the bed on which the user **308** is located to wake the user **308** without disturbing the second user. When the wakeup time for the second user is reached, the control circuitry **334** can cause the articulation controller to vibrate or change the position of only the side of the bed on which the second user is located. Alternatively, when the second wakeup time occurs, the control circuitry **334** can utilize other methods (such as audio alarms, or turning on the lights) to wake the second user since the user **308** is already awake and therefore will not be disturbed when the control circuitry **334** attempts to wake the second user.

(92) Still referring to FIG. **3**, the control circuitry **334** for the bed **302** can utilize information for interactions with the bed **302** by multiple users to generate control signals for controlling functions of various other devices. For example, the control circuitry **334** can wait to generate control signals for, for example, engaging the security system **318**, or instructing the lighting system **314** to turn off lights in various rooms until both the user **308** and a second user are detected as being present on the bed **302**. As another example, the control circuitry **334** can generate a first set of control signals to cause the lighting system **314** to turn off a first set of lights upon detecting bed presence of the user **308** and generate a second set of control signals for turning off a second set of lights in response to detecting bed presence of a second user. As another example, the control circuitry **334** can wait until it has been determined that both the user **308** and a second user are awake for the day before generating control signals to open the window blinds **330**. As yet another example, in response to determining that the user **308** has left the bed and is awake for the day, but that a second user is still sleeping, the control circuitry **334** can generate and transmit a first set of control signals to cause the coffee maker **324** to begin brewing coffee, to cause the security system **318** to deactivate, to turn on the lamp **326**, to turn off the nightlight **328**, to cause the thermostat **316** to raise the temperature in one or more rooms to 72 degrees, and to open blinds (e.g., the window blinds **330**) in rooms other than the bedroom in which the bed **302** is located. Later, in response to detecting that the second user is no longer present on the bed (or that the second user is awake) the control circuitry **334** can generate and transmit a second set of control signals to, for example, cause the lighting system **314** to turn on one or more lights in the bedroom, to cause window blinds in the bedroom to open, and to turn on the television **312** to a pre-specified channel.

(93) Examples of a Remote Control for a Bed

(94) FIGS. 4A-4D are schematic diagrams of the example remote control 122 that can be associated with the bed system, including those described above with respect to FIGS. 1-3. The remote control 122 is substantially similar to the remote control 122. Referring to FIGS. 4A-4D, the remote control 122 includes a case 402. The case 402 is the outer body of the remote control 122.

(95) As shown in FIG. 4E, the case 402 is defined by a base surface 404. In some implementations, as shown in FIG. 4E, the base surface 404 is sized to allow the remote control 122 to rest in a vertical position on a horizontal surface 406 (seen in FIG. 4A). For example, referring to FIG. 3, the remote control 122 can rest in the vertical (upright) position on the top (horizontal) surface of the bedside table 340. Referring to FIG. 4E, in some implementations, the base surface 404 is substantially triangular. The triangular base surface 404 is defined by a first edge 408, a second edge 410, and a third edge 412.

(96) The case 402 is further defined by a display surface 414, as shown in FIGS. 4A, 4D, and 4E. The display surface 414 can also be referred to as the front surface or the front of the case 402. The display surface 414 is coupled to the base surface 404 by the first edge 408. The display surface 414 includes the display 126 previously described in reference to FIGS. 1-3. The display 126 can also be referred to as the display screen.

(97) The display 126 can be an input area 128 as previously stated. When the display 126 is an input area 128, the display 126 can include portions which correspond to a digital button or digital buttons (not shown), that, when physically contacted by the user, can control operations of the bed 112. For example, the user can control the position or configuration of the bed, the pressure of the bed, the temperature of the bed, or a light level of the bed 122. In some cases, the digital buttons can change based on the user selected menu, list, or command. For example, the digital button can be a single main menu button, or the digital buttons can be the main menu button and a sub-menu button.

(98) The display surface 414 also includes the input area 128, as previously described in reference to FIGS. 1-3. In some implementations, the input area 128 is a direction pad 432 and a selection pad 434. The direction pad 432 moves a cursor or selection icon (not shown) on the display 126 when the user applies a force to a respective area of the direction pad 432. In response, the cursor on the display 126 moves in the respective direction. When the remote control 122 is in a sleep state and user touches the input area 128, the input area 128 senses the touch of the user, the input area 128 generates a signal to the control circuitry 334 of the remote control 122 to wake the remote control 122. The operation of the remote control 122, in response to the signal to wake up from input area 128, is substantially similar to the operation of the capacitive button 130 is described below in reference FIG. 21. Waking up the remote control 122 by the user touching the capacitive button 130 can be referred to as “push to wake”. The direction pad 432 can be an outer portion 436 of the input area 128. The selection pad 434 can be a center portion 438 of the input area 128.

(99) The display surface 414 includes at least one capacitive button 130, described previously in reference to FIGS. 1-3. The capacitive button 130 can correspond to a capacitive zone or capacitive area of the remote control 122. The capacitive button 130 senses the touch of the user by the transmission (conduction) of an electrical charge from the user to the capacitive button 130. Alternatively, the transmission of the electrical charge can be from the capacitive button 130 to the user.

(100) When the capacitive button 130 senses the touch of the user, the capacitive button generates a signal to the control circuitry 334 of the remote control 122 to wake the remote control 122. The operation of the remote control 122 in response to the signal to wake up from the capacitive button 130 is described below in reference FIG. 21. Waking up the remote control 122 by the user touching the capacitive button 130 can be referred to as “grip to wake”.

(101) In some implementations, at least one of the capacitive buttons **130** is positioned between the display **126** and the input area **128**. The capacitive button **130** is positioned between the display **126** and the input area **128** for improved ergonomics for the user.

(102) Referring to FIG. **4D**, the case **402** includes an upper surface **416**. The upper surface **416** is coupled to the display surface **414**. The upper surface **416** is a rounded rectangle.

(103) The upper surface **416** includes the slider switch **132**, as previously described in reference to FIGS. **1-3**. The slider switch **132** moves (e.g. words toggles) between a first position **416** and a second position **418**. In some implementations, as shown in reference to FIGS. **3** and **4A-4D**, the slider switch **132** adjusts an interface displayed on the display **126** to a first side **336** of the bed **302** when the slider switch **132** is in the first position **416** and a second side **338** of the bed **302** when the slider switch **132** is in the second position **418**.

(104) As shown in FIGS. **4B** and **4C**, the case **402** is further defined by a back surface **420**. The back surface **420** is coupled to the base surface **404**, the display surface **414**, and the upper surface **416**. The edges **422a** and **422b** connecting the display surface **414** to the back surface **420** are rounded. The back surface **420** includes four flat triangular surfaces **424a-d**.

(105) A portion **430** of the back surface **420** is removable. The portion **430** of the back surface **420** can be removed to access the internal portions (not shown) of the remote control **122**.

(106) The remote control **122** includes a power source (not shown). The portion **430** of the back surface **420** can be removed to access the power source. The power source provides power to the control circuitry **334** to operate the remote control **122**. The power source can be a battery. For example, the power source can be a commercially available off the shelf alkaline battery such as CR3032, AA, AAA, C, D, and CR1016 batteries. Alternatively or in addition, the power source can be a removable rechargeable battery, a super capacitor, or a fixed rechargeable battery, for example, that can be charged by a universal serial bus (USB) connection.

(107) In some implementations, a portion of the case **402** is metallic. For example, the display surface **414** or the edges **422a** and **422b** can be metallic. In some implementations, the case **402** is capacitively sensitive. By capacitively sensitive, it is meant that the remote control **122** wakes up responsive to a signal from the capacitively sensitive case. For example, when the remote control **122** is in a rest state (no processing functions are occurring and/or the battery is in a low power mode) and the user touches the capacitively sensitive case, a processor in the remote control transitions from a sleep state to a wake state due to the change in capacitance resulting from the user touch. In the wake state, the remote control **122** is ready to receive input from the user to control the bed **112**. For example, the display surface **414**, the capacitive button **130**, or the edges **422a** and **422b** can be capacitively sensitive.

(108) In some implementations, as shown in FIGS. **4A**, **4D**, and **4E**, the remote control **122** includes a light sensor **426**. FIG. **20** is a flow chart of an example method of operating the light sensor **426** of the remote control **122**. Referring to FIGS. **4A**, **4D**, **4E**, and **19**, at **2002**, the light sensor **426** receives ambient light **428**. At **2004**, the light sensor **426** produces a signal representative of an ambient light **428** level (in other words intensity or brightness). The signal is a light signal produced by the light sensor **426**.

(109) After the light signal is produced (transmitted), at **2006**, it is then interpreted by the remote control **122** to adjust a brightness of the display **126** and the input area **128**. The initial brightness of the display area **126** and the input area **128** can be preset and/or stored in the controller **122** (stored locally). Alternatively, the remote control **122** can fetch a user desired brightness of the display area **126** and the input area **128** from the control circuitry **324** of the bed **112** (stored centrally). The user desired brightness of the display area **126** and the input area **128** adjusts how the remote control **122** adjusts the display area **126** and input area **128** brightness relative to the light signal produced from light sensor **426**. When the user chooses a brighter initial brightness of the display area **126** and the input area **128**, the remote control **122** will maintain that brightness relative to the ambient environment. The process occurs for medium and low user desired

brightness, relevant to the ambient light of the environment as detected by the light sensor **426**.

(110) FIG. **21** is a flow chart of an example method of operating a bed system with a remote control. Referring to FIGS. **1-3**, and **21**, at **2102** the remote control **122** of the bed **302** system in the example environment **300** the remote control **122** wakes up responsive to the touch of the user. When the user touches the capacitively sensitive case **402** (i.e. the capacitive button **130**), the capacitively sensitive case **402** sends a signal to the remote control **122** to wake up. At **2104**, responsive to waking up, the remote control **122** pings the control circuitry **334** of the bed. The remote control **122** pings the control circuitry **334** as a communications check to verify the bed **112** is within a communications range of the remote **122** and to verify a communications channel is available for the remote control **122** to communicate with the bed **112**.

(111) At **2106**, the control circuitry **334** responds to the ping by transmitting a response to the remote control **122**. For example, the response from control circuitry **334** to the remote control **122** can be that the bed **112** is within communications range of the remote control **122** and a communications channel is available. Alternatively, the response from control circuitry **334** to the remote control **122** can be that the bed **112** is within communications range of the control circuitry **334**, but no communications channel is available. Alternatively, when the bed **112** is out of communications range from the remote control **122**, the control circuitry **334** will not respond.

(112) At **2108**, responsive to receiving the response to the ping from the control circuitry **334** at the remote control **122**, the remote control fetches a state of the bed **302** from the control circuitry **334** in the bed **302** that is physically separate from the remote control **122**. In some implementations, the remote control **122** fetches the state of the bed **302** when waking up, as described earlier in reference to FIGS. **1-4D**. In some implementations, the remote control **122** fetches the state of the bed **302** by communicating wirelessly with the control circuitry **334** of the bed **302** (the bed controller).

(113) In some implementations, the remote control **122** pings the control circuitry **334** (the bed controller). The remote control then receives a response from the control circuitry **334** of the bed (**302**) in response to the ping.

(114) At **2110**, the remote control **122** displays the state of the bed **112** on a screen (the display **126**) of the remote control **122** responsive to the fetched state. In some implementations, receiving a response at the remote control **122** from the control circuitry **334** of the bed **302** includes receiving an indication of a new state and displaying an interface on the display **126** includes displaying an interface appropriate for the new state. For example, the new state can be a pressure of the bed **302**, a position of a portion of the bed **302** (a left side, a right side, a top portion, or a bottom portion), and/or a temperature, a light level, an error state. The new state can be all of the states of the bed. In some cases, only a relevant (user selected state) is fetched and displayed. In other cases, only states which have changed are fetched and displayed.

(115) In some implementations, receiving a response at the remote control **122** from the control circuitry **334** of the bed **302** includes receiving an indication of no change in state since a previous ping. In such cases, the interface continues to display the last used interface.

(116) Examples of Data Processing Systems Associated with a Bed

(117) Described here are examples of systems and components that can be used for data processing tasks that are, for example, associated with a bed. In some cases, multiple examples of a particular component or group of components are presented. Some of these examples are redundant and/or mutually exclusive alternatives. Connections between components are shown as examples to illustrate possible network configurations for allowing communication between components. Different formats of connections can be used as technically needed or desired. The connections generally indicate a logical connection that can be created with any technologically feasible format. For example, a network on a motherboard can be created with a printed circuit board, wireless data connections, and/or other types of network connections. Some logical connections are not shown for clarity. For example, connections with power supplies and/or computer readable memory may

not be shown for clarity's sake, as many or all elements of a particular component may need to be connected to the power supplies and/or computer readable memory.

(118) FIG. 5A is a block diagram of an example of a data processing system **500** that can be associated with a bed system, including those described above with respect to FIGS. 1-4. This system **500** includes a pump motherboard **502** and a pump daughterboard **504**. The system **500** includes a sensor array **506** that can include one or more sensors configured to sense physical phenomenon of the environment and/or bed, and to report such sensing back to the pump motherboard **502** for, for example, analysis. The system **500** also includes a controller array **508** that can include one or more controllers configured to control logic-controlled devices of the bed and/or environment. The pump motherboard **500** can be in communication with one or more computing devices **514** and one or more cloud services **510** over local networks, the Internet **512**, or otherwise as is technically appropriate. Each of these components will be described in more detail, some with multiple example configurations, below.

(119) In this example, a pump motherboard **502** and a pump daughterboard **504** are communicably coupled. They can be conceptually described as a center or hub of the system **500**, with the other components conceptually described as spokes of the system **500**. In some configurations, this can mean that each of the spoke components communicates primarily or exclusively with the pump motherboard **502**. For example, a sensor of the sensor array may not be configured to, or may not be able to, communicate directly with a corresponding controller. Instead, each spoke component can communicate with the motherboard **502**. The sensor of the sensor array **406** can report a sensor reading to the motherboard **502**, and the motherboard **502** can determine that, in response, a controller of the controller array **408** should adjust some parameters of a logic controlled device or otherwise modify a state of one or more peripheral devices. In one case, if the temperature of the bed is determined to be too hot, the pump motherboard **502** can determine that a temperature controller should cool the bed.

(120) One advantage of a hub-and-spoke network configuration, sometimes also referred to as a star-shaped network, is a reduction in network traffic compared to, for example, a mesh network with dynamic routing. If a particular sensor generates a large, continuous stream of traffic, that traffic may only be transmitted over one spoke of the network to the motherboard **502**. The motherboard **502** can, for example, marshal that data and condense it to a smaller data format for retransmission for storage in a cloud service **510**. Additionally or alternatively, the motherboard **502** can generate a single, small, command message to be sent down a different spoke of the network in response to the large stream. For example, if the large stream of data is a pressure reading that is transmitted from the sensor array **506** a few times a second, the motherboard **502** can respond with a single command message to the controller array to increase the pressure in an air chamber. In this case, the single command message can be orders of magnitude smaller than the stream of pressure readings.

(121) As another advantage, a hub-and-spoke network configuration can allow for an extensible network that can accommodate components being added, removed, failing, etc. This can allow, for example, more, fewer, or different sensors in the sensor array **506**, controllers in the controller array **508**, computing devices **514**, and/or cloud services **510**. For example, if a particular sensor fails or is deprecated by a newer version of the sensor, the system **500** can be configured such that only the motherboard **502** needs to be updated about the replacement sensor. This can allow, for example, product differentiation where the same motherboard **502** can support an entry level product with fewer sensors and controllers, a higher value product with more sensors and controllers, and customer personalization where a customer can add their own selected components to the system **500**.

(122) Additionally, a line of air bed products can use the system **500** with different components. In an application in which every air bed in the product line includes both a central logic unit and a pump, the motherboard **502** (and optionally the daughterboard **504**) can be designed to fit within a

single, universal housing. Then, for each upgrade of the product in the product line, additional sensors, controllers, cloud services, etc., can be added. Design, manufacturing, and testing time can be reduced by designing all products in a product line from this base, compared to a product line in which each product has a bespoke logic control system.

(123) Each of the components discussed above can be realized in a wide variety of technologies and configurations. Below, some examples of each component will be further discussed. In some alternatives, two or more of the components of the system **500** can be realized in a single alternative component; some components can be realized in multiple, separate components; and/or some functionality can be provided by different components.

(124) FIG. 5B is a block diagram showing some communication paths of the data processing system **500**. As previously described, the motherboard **502** and the pump daughterboard **504** may act as a hub for peripheral devices and cloud services of the system **500**. In cases in which the pump daughterboard **504** communicates with cloud services or other components, communications from the pump daughterboard **504** may be routed through the pump motherboard **502**. This may allow, for example, the bed to have only a single connection with the internet **512**. The computing device **514** may also have a connection to the internet **512**, possibly through the same gateway used by the bed and/or possibly through a different gateway (e.g., a cell service provider).

(125) Previously, a number of cloud services **510** were described. As shown in FIG. 5B, some cloud services, such as cloud services **510d** and **510e**, may be configured such that the pump motherboard **502** can communicate with the cloud service directly—that is the motherboard **502** may communicate with a cloud service **510** without having to use another cloud service **510** as an intermediary. Additionally or alternatively, some cloud services **510**, for example cloud service **510f**, may only be reachable by the pump motherboard **502** through an intermediary cloud service, for example cloud service **510e**. While not shown here, some cloud services **510** may be reachable either directly or indirectly by the pump motherboard **502**.

(126) Additionally, some or all of the cloud services **510** may be configured to communicate with other cloud services. This communication may include the transfer of data and/or remote function calls according to any technologically appropriate format. For example, one cloud service **510** may request a copy for another cloud service's **510** data, for example, for purposes of backup, coordination, migration, or for performance of calculations or data mining. In another example, many cloud services **510** may contain data that is indexed according to specific users tracked by the user account cloud **510c** and/or the bed data cloud **510a**. These cloud services **510** may communicate with the user account cloud **510c** and/or the bed data cloud **510a** when accessing data specific to a particular user or bed.

(127) FIG. 6 is a block diagram of an example of a motherboard **402** that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. 1-4E. In this example, compared to other examples described below, this motherboard **502** consists of relatively fewer parts and can be limited to provide a relatively limited feature set.

(128) The motherboard includes a power supply **600**, a processor **602**, and computer memory **612**. In general, the power supply includes hardware used to receive electrical power from an outside source and supply it to components of the motherboard **502**. The power supply can include, for example, a battery pack and/or wall outlet adapter, an AC to DC converter, a DC to AC converter, a power conditioner, a capacitor bank, and/or one or more interfaces for providing power in the current type, voltage, etc., needed by other components of the motherboard **502**.

(129) The processor **602** is generally a device for receiving input, performing logical determinations, and providing output. The processor **602** can be a central processing unit, a microprocessor, general purpose logic circuitry, application-specific integrated circuitry, a combination of these, and/or other hardware for performing the functionality needed.

(130) The memory **612** is generally one or more devices for storing data. The memory **612** can

include long term stable data storage (e.g., on a hard disk), short term unstable (e.g., on Random Access Memory) or any other technologically appropriate configuration.

(131) The motherboard **402** includes a pump controller **604** and a pump motor **606**. The pump controller **604** can receive commands from the processor **602** and, in response, control the function of the pump motor **606**. For example, the pump controller **604** can receive, from the processor **602**, a command to increase the pressure of an air chamber by 0.3 pounds per square inch (PSI). The pump controller **604**, in response, engages a valve so that the pump motor **606** is configured to pump air into the selected air chamber, and can engage the pump motor **606** for a length of time that corresponds to 0.3 PSI or until a sensor indicates that pressure has been increased by 0.3 PSI. In an alternative configuration, the message can specify that the chamber should be inflated to a target PSI, and the pump controller **604** can engage the pump motor **606** until the target PSI is reached.

(132) A valve solenoid **608** can control which air chamber a pump is connected to. In some cases, the solenoid **608** can be controlled by the processor **602** directly. In some cases, the solenoid **608** can be controlled by the pump controller **604**.

(133) A remote interface **610** of the motherboard **402** can allow the motherboard **402** to communicate with other components of a data processing system. For example, the motherboard **502** can be able to communicate with one or more daughterboards, with peripheral sensors, and/or with peripheral controllers through the remote interface **610**. The remote interface **610** can provide any technologically appropriate communication interface, including but not limited to multiple communication interfaces such as WiFi, Bluetooth, and copper-wired networks.

(134) FIG. 7 is a block diagram of an example of a motherboard **502** that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. 1-4E. Compared to the motherboard **502** described with reference to FIG. 6, the motherboard in FIG. 7 can contain more components and provide more functionality in some applications.

(135) In addition to the power supply **600**, processor **602**, pump controller **604**, pump motor **606**, and valve solenoid **608**, this motherboard **502** is shown with a valve controller **700**, a pressure sensor **702**, a universal serial bus (USB) stack **704**, a WiFi radio **706**, a Bluetooth Low Energy (BLE) radio **708**, a ZigBee radio **710**, a Bluetooth radio **712** and a computer memory **612**.

(136) Similar to the way that the pump controller **604** converts commands from the processor **602** into control signals for the pump motor **606**, the valve controller **700** can convert commands from the processor **602** into control signals for the valve solenoid **608**.

(137) In one example, the processor **602** can issue a command to the valve controller **700** to connect the pump to a particular air chamber out of the group of air chambers in an air bed. The valve controller **700** can control the position of the valve solenoid **608** so that the pump is connected to the indicated air chamber.

(138) The pressure sensor **702** can read pressure readings from one or more air chambers of the air bed. The pressure sensor **702** can also preform digital sensor conditioning.

(139) The motherboard **502** can include a suite of network interfaces, including but not limited to those shown here. These network interfaces can allow the motherboard to communicate over a wired or wireless network with any number of devices, including but not limited to peripheral sensors, peripheral controllers, computing devices, and devices and services connected to the Internet **512**.

(140) FIG. 8 is a block diagram of an example of a daughterboard **504** that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. 1-4E. In some configurations, one or more daughterboards **504** can be connected to the motherboard **502**. Some daughterboards **504** can be designed to offload particular and/or compartmentalized tasks from the motherboard **502**. This can be advantageous, for example, if the particular tasks are computationally intensive, proprietary, or subject to future revisions. For

example, the daughterboard **504** can be used to calculate a particular sleep data metric. This metric can be computationally intensive, and calculating the sleep metric on the daughterboard **504** can free up the resources of the motherboard **502** while the metric is being calculated. Additionally and/or alternatively, the sleep metric can be subject to future revisions. To update the system **500** with the new sleep metric, it is possible that only the daughterboard **504** that calculates that metric need be replaced. In this case, the same motherboard **502** and other components can be used, saving the need to perform unit testing of additional components instead of just the daughterboard **504**.

(141) The daughterboard **504** is shown with a power supply **800**, a processor **802**, computer readable memory **804**, a pressure sensor **806**, and a WiFi radio **808**. The processor can use the pressure sensor **806** to gather information about the pressure of the air chamber or chambers of an air bed. From this data, the processor **802** can perform an algorithm to calculate a sleep metric. In some examples, the sleep metric can be calculated from only the pressure of air chambers. In other examples, the sleep metric can be calculated from one or more other sensors. In an example in which different data is needed, the processor **802** can receive that data from an appropriate sensor or sensors. These sensors can be internal to the daughterboard **504**, accessible via the WiFi radio **808**, or otherwise in communication with the processor **802**. Once the sleep metric is calculated, the processor **802** can report that sleep metric to, for example, the motherboard **502**.

(142) FIG. **9** is a block diagram of an example of a motherboard **900** with no daughterboard that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. **1-4E**. In this example, the motherboard **900** can perform most, all, or more of the features described with reference to the motherboard **502** in FIG. **7** and the daughterboard **504** in FIG. **8**.

(143) FIG. **10** is a block diagram of an example of a sensory array **506** that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. **1-4E**. In general, the sensor array **506** is a conceptual grouping of some or all the peripheral sensors that communicate with the motherboard **502** but are not native to the motherboard **502**.

(144) The peripheral sensors of the sensor array **506** can communicate with the motherboard **502** through one or more of the network interfaces of the motherboard, including but not limited to the USB stack **704**, the WiFi radio **706**, the Bluetooth Low Energy (BLE) radio **708**, the ZigBee radio **710**, and the Bluetooth radio **712**, as is appropriate for the configuration of the particular sensor. For example, a sensor that outputs a reading over a USB cable can communicate through the USB stack **704**.

(145) Some of the peripheral sensors **1000** of the sensor array **506** can be bed mounted. These sensors can be, for example, embedded into the structure of a bed and sold with the bed, or later affixed to the structure of the bed. Other peripheral sensors **1002** and **1004** can be in communication with the motherboard **502**, but optionally not mounted to the bed. In some cases, some or all of the bed mounted sensors **1000** and/or peripheral sensors **1002** and **1004** can share networking hardware, including a conduit that contains wires from each sensor, a multi-wire cable or plug that, when affixed to the motherboard **502**, connect all of the associated sensors with the motherboard **502**. In some embodiments, one, some, or all of sensors **1002**, **1004**, **1006**, **1008**, and **1010** can sense one or more features of a mattress, such as pressure, temperature, light, sound, and/or one or more other features of the mattress. In some embodiments, one, some, or all of sensors **1002**, **1004**, **1006**, **1008**, and **1010** can sense one or more features external to the mattress. In some embodiments, pressure sensor **1002** can sense pressure of the mattress while some or all of sensors **1002**, **1004**, **1006**, **1008**, and **1010** can sense one or more features of the mattress and/or external to the mattress.

(146) FIG. **11** is a block diagram of an example of a controller array **508** that can be used in a data processing system that can be associated with a bed system, including those described above with

respect to FIGS. 1-4E. In general, the controller array **508** is a conceptual grouping of some or all peripheral controllers that communicate with the motherboard **502** but are not native to the motherboard **502**.

(147) The peripheral controllers of the controller array **508** can communicate with the motherboard **502** through one or more of the network interfaces of the motherboard, including but not limited to the USB stack **704**, the WiFi radio **706**, the Bluetooth Low Energy (BLE) radio **708**, the ZigBee radio **710**, and the Bluetooth radio **712**, as is appropriate for the configuration of the particular sensor. For example, a controller that receives a command over a USB cable can communicate through the USB stack **704**.

(148) Some of the controllers of the controller array **508** can be bed mounted **1100**. These controllers can be, for example, embedded into the structure of a bed and sold with the bed, or later affixed to the structure of the bed. Other peripheral controllers **1102** and **1104** can be in communication with the motherboard **502**, but optionally not mounted to the bed. In some cases, some or all of the bed mounted controllers **1100** and/or peripheral controllers **1102** and **1104** can share networking hardware, including a conduit that contains wires for each controller, a multi-wire cable or plug that, when affixed to the motherboard **502**, connects all of the associated controllers with the motherboard **502**.

(149) FIG. 12 is a block diagram of an example of a computing device **512** that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. 1-4E. The computing device **512** can include, for example, computing devices used by a user of a bed. Example computing devices **512** include, but are not limited to, mobile computing devices (e.g., mobile phones, tablet computers, laptops) and desktop computers.

(150) The computing device **512** includes a power supply **1200**, a processor **1202**, and computer readable memory **1204**. User input and output can be transmitted by, for example, speakers **1206**, a touchscreen **1208**, or other not shown components such as a pointing device or keyboard. The computing device **512** can run one or more applications **1210**. These applications can include, for example, application to allow the user to interact with the system **500**. These applications can allow a user to view information about the bed (e.g., sensor readings, sleep metrics), or configure the behavior of the system **500** (e.g., set a desired firmness to the bed, set desired behavior for peripheral devices). In some cases, the computing device **512** can be used in addition to, or to replace, the remote control **122** described previously.

(151) FIG. 13 is a block diagram of an example bed data cloud service **510a** that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. 1-4E. In this example, the bed data cloud service **510a** is configured to collect sensor data and sleep data from a particular bed, and to match the sensor and sleep data with one or more users that use the bed when the sensor and sleep data was generated.

(152) The bed data cloud service **510a** is shown with a network interface **1300**, a communication manager **1302**, server hardware **1304**, and server system software **1306**. In addition, the bed data cloud service **510a** is shown with a user identification module **1308**, a device management **1310** module, a sensor data module **1310**, and an advanced sleep data module **1314**.

(153) The network interface **1300** generally includes hardware and low level software used to allow one or more hardware devices to communicate over networks. For example the network interface **1300** can include network cards, routers, modems, and other hardware needed to allow the components of the bed data cloud service **410a** to communicate with each other and other destinations over, for example, the Internet **512**. The communication manger **1302** generally comprises hardware and software that operate above the network interface **1300**. This includes software to initiate, maintain, and tear down network communications used by the bed data cloud service **510a**. This includes, for example, TCP/IP, SSL or TLS, Torrent, and other communication sessions over local or wide area networks. The communication manger **1302** can also provide load balancing and other services to other elements of the bed data cloud service **510a**.

(154) The server hardware **1304** generally includes the physical processing devices used to instantiate and maintain bed data cloud service **510a**. This hardware includes, but is not limited to processors (e.g., central processing units, ASICs, graphical processors), and computer readable memory (e.g., random access memory, stable hard disks, tape backup). One or more servers can be configured into clusters, multi-computer, or datacenters that can be geographically separate or connected.

(155) The server system software **1306** generally includes software that runs on the server hardware **1304** to provide operating environments to applications and services. The server system software **1306** can include operating systems running on real servers, virtual machines instantiated on real servers to create many virtual servers, server level operations such as data migration, redundancy, and backup.

(156) The user identification **1308** can include, or reference, data related to users of beds with associated data processing systems. For example, the users can include customers, owners, or other users registered with the bed data cloud service **510a** or another service. Each user can have, for example, a unique identifier, user credentials, contact information, billing information, demographic information, or any other technologically appropriate information.

(157) The device manager **1310** can include, or reference, data related to beds or other products associated with data processing systems. For example, the beds can include products sold or registered with a system associated with the bed data cloud service **510a**. Each bed can have, for example, a unique identifier, model and/or serial number, sales information, geographic information, delivery information, a listing of associated sensors and control peripherals, etc. Additionally, an index or indexes stored by the bed data cloud service **510a** can identify users that are associated with beds. For example, this index can record sales of a bed to a user, users that sleep in a bed, etc.

(158) The sensor data **1212** can record raw or condensed sensor data recorded by beds with associated data processing systems. For example, a bed's data processing system can have a temperature sensor, pressure sensor, and light sensor. Readings from these sensors, either in raw form or in a format generated from the raw data (e.g. sleep metrics) of the sensors, can be communicated by the bed's data processing system to the bed data cloud service **510a** for storage in the sensor data **1312**. Additionally, an index or indexes stored by the bed data cloud service **510a** can identify users and/or beds that are associated with the sensor data **1312**.

(159) The bed data cloud service **510a** can use any of its available data to generate advanced sleep data **1314**. In general, the advanced sleep data **1314** includes sleep metrics and other data generated from sensor readings. Some of these calculations can be performed in the bed data cloud service **510a** instead of locally on the bed's data processing system, for example, because the calculations are computationally complex or require a large amount of memory space or processor power that is not available on the bed's data processing system. This can help allow a bed system to operate with a relatively simple controller and still be part of a system that performs relatively complex tasks and computations.

(160) FIG. **14** is a block diagram of an example sleep data cloud service **510b** that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. **1-4E**. In this example, the sleep data cloud service **510b** is configured to record data related to users' sleep experience.

(161) The sleep data cloud service **510b** is shown with a network interface **1400**, a communication manager **1402**, server hardware **1404**, and server system software **1406**. In addition, the sleep data cloud service **510b** is shown with a user identification module **1408**, a pressure sensor manager **1410**, a pressure based sleep data module **1412**, a raw pressure sensor data module **1414**, and a non-pressure sleep data module **1416**.

(162) The pressure sensor manager **1410** can include, or reference, data related to the configuration and operation of pressure sensors in beds. For example, this data can include an identifier of the

types of sensors in a particular bed, their settings and calibration data, etc.

(163) The pressure based sleep data **1412** can use raw pressure sensor data **1414** to calculate sleep metrics specifically tied to pressure sensor data. For example, user presence, movements, weight change, heart rate, and breathing rate can all be determined from raw pressure sensor data **1414**. Additionally, an index or indexes stored by the sleep data cloud service **510b** can identify users that are associated with pressure sensors, raw pressure sensor data, and/or pressure based sleep data.

(164) The non-pressure sleep data **1416** can use other sources of data to calculate sleep metrics. For example, user entered preferences, light sensor readings, and sound sensor readings can all be used to track sleep data. Additionally, an index or indexes stored by the sleep data cloud service **510b** can identify users that are associated with other sensors and/or non-pressure sleep data **1416**.

(165) FIG. **15** is a block diagram of an example user account cloud service **410c** that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. **1-4E**. In this example, the user account cloud service **510c** is configured to record a list of users and to identify other data related to those users.

(166) The user account cloud service **510c** is shown with a network interface **1500**, a communication manager **1502**, server hardware **1504**, and server system software **1506**. In addition, the user account cloud service **510c** is shown with a user identification module **1508**, a purchase history module **1510**, an engagement module **1512**, and an application usage history module **1514**.

(167) The user identification module **1508** can include, or reference, data related to users of beds with associated data processing systems. For example, the users can include customers, owners, or other users registered with the user account cloud service **510a** or another service. Each user can have, for example, a unique identifier, and user credentials, demographic information, or any other technologically appropriate information.

(168) The purchase history module **1510** can include, or reference, data related to purchases by users. For example, the purchase data can include a sale's contact information, billing information, and salesperson information. Additionally, an index or indexes stored by the user account cloud service **510c** can identify users that are associated with a purchase.

(169) The engagement **1512** can track user interactions with the manufacturer, vendor, and/or manager of the bed and or cloud services. This engagement data can include communications (e.g., emails, service calls), data from sales (e.g., sales receipts, configuration logs), and social network interactions.

(170) The usage history module **1514** can contain data about user interactions with one or more applications and/or remote controls of a bed. For example, a monitoring and configuration application can be distributed to run on, for example, computing devices **512**. This application can log and report user interactions for storage in the application usage history module **1514**. Additionally, an index or indexes stored by the user account cloud service **510c** can identify users that are associated with each log entry.

(171) FIG. **16** is a block diagram of an example point of sale cloud service **1600** that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. **1-4E**. In this example, the point of sale cloud service **1600** is configured to record data related to users' purchases.

(172) The point of sale cloud service **1600** is shown with a network interface **1602**, a communication manager **1604**, server hardware **1606**, and server system software **1608**. In addition, the point of sale cloud service **1600** is shown with a user identification module **1610**, a purchase history module **1612**, and a setup module **1614**.

(173) The purchase history module **1612** can include, or reference, data related to purchases made by users identified in the user identification module **1610**. The purchase information can include, for example, data of a sale, price, and location of sale, delivery address, and configuration options selected by the users at the time of sale. These configuration options can include selections made

by the user about how they wish their newly purchased beds to be setup and can include, for example, expected sleep schedule, a listing of peripheral sensors and controllers that they have or will install, etc.

(174) The bed setup module **1614** can include, or reference, data related to installations of beds that users' purchase. The bed setup data can include, for example, the date and address to which a bed is delivered, the person that accepts delivery, the configuration that is applied to the bed upon delivery, the name or names of the person or people who will sleep on the bed, which side of the bed each person will use, etc.

(175) Data recorded in the point of sale cloud service **1600** can be referenced by a user's bed system at later dates to control functionality of the bed system and/or to send control signals to peripheral components according to data recorded in the point of sale cloud service **1600**. This can allow a salesperson to collect information from the user at the point of sale that later facilitates automation of the bed system. In some examples, some or all aspects of the bed system can be automated with little or no user-entered data required after the point of sale. In other examples, data recorded in the point of sale cloud service **1600** can be used in connection with a variety of additional data gathered from user-entered data.

(176) FIG. **17** is a block diagram of an example environment cloud service **1700** that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. **1-4E**. In this example, the environment cloud service **1700** is configured to record data related to users' home environment.

(177) The environment cloud service **1700** is shown with a network interface **1702**, a communication manager **1704**, server hardware **1706**, and server system software **1708**. In addition, the environment cloud service **1700** is shown with a user identification module **1710**, an environmental sensor module **1712**, and an environmental factors module **1714**.

(178) The environmental sensors module **1712** can include a listing of sensors that users' in the user identification module **1710** have installed in their bed. These sensors include any sensors that can detect environmental variables—light sensors, noise sensors, vibration sensors, thermostats, etc. Additionally, the environmental sensors module **1712** can store historical readings or reports from those sensors.

(179) The environmental factors module **1714** can include reports generated based on data in the environmental sensors module **1712**. For example, for a user with a light sensor with data in the environment sensors module **1712**, the environmental factors module **1714** can hold a report indicating the frequency and duration of instances of increased lighting when the user is asleep.

(180) In the examples discussed here, each cloud service **510** is shown with some of the same components. In various configurations, these same components can be partially or wholly shared between services, or they can be separate. In some configurations, each service can have separate copies of some or all of the components that are the same or different in some ways. Additionally, these components are only supplied as illustrative examples. In other examples each cloud service can have different number, types, and styles of components that are technically possible.

(181) FIG. **18** is a block diagram of an example of using a data processing system that can be associated with a bed (such as a bed of the bed systems described herein) to automate peripherals around the bed. Shown here is a behavior analysis module **1800** that runs on the pump motherboard **502**. For example, the behavior analysis module **1800** can be one or more software components stored on the computer memory **612** and executed by the processor **602**. In general, the behavior analysis module **1800** can collect data from a wide variety of sources (e.g., sensors, non-sensor local sources, cloud data services) and use a behavioral algorithm **1802** to generate one or more actions to be taken (e.g., commands to send to peripheral controllers, data to send to cloud services). This can be useful, for example, in tracking user behavior and automating devices in communication with the user's bed.

(182) The behavior analysis module **1800** can collect data from any technologically appropriate

source, for example, to gather data about features of a bed, the bed's environment, and/or the bed's users. Some such sources include any of the sensors of the sensor array **506**. For example, this data can provide the behavior analysis module **1800** with information about the current state of the environment around the bed. For example, the behavior analysis module **1800** can access readings from the pressure sensor **1002** to determine the pressure of an air chamber in the bed. From this reading, and potentially other data, user presence in the bed can be determined. In another example, the behavior analysis module can access a light sensor **1008** to detect the amount of light in the bed's environment.

(183) Similarly, the behavior analysis module **1800** can access data from cloud services. For example, the behavior analysis module **1800** can access the bed cloud service **510a** to access historical sensor data **1312** and/or advanced sleep data **1314**. Other cloud services **510**, including those not previously described can be accessed by the behavior analysis module **1800**. For example, the behavior analysis module **1800** can access a weather reporting service, a 3.sup.rd party data provider (e.g., traffic and news data, emergency broadcast data, user travel data), and/or a clock and calendar service.

(184) Similarly, the behavior analysis module **1800** can access data from non-sensor sources **1804**. For example, the behavior analysis module **1800** can access a local clock and calendar service (e.g., a component of the motherboard **502** or of the processor **602**).

(185) The behavior analysis module **1800** can aggregate and prepare this data for use by one or more behavioral algorithms **1802**. The behavioral algorithms **1802** can be used to learn a user's behavior and/or to perform some action based on the state of the accessed data and/or the predicted user behavior. For example, the behavior algorithm **1802** can use available data (e.g., pressure sensor, non-sensor data, clock and calendar data) to create a model of when a user goes to bed every night. Later, the same or a different behavioral algorithm **1802** can be used to determine if an increase in air chamber pressure is likely to indicate a user going to bed and, if so, send some data to a third-party cloud service **510** and/or engage a peripheral controller **1102**.

(186) In the example shown, the behavioral analysis module **1800** and the behavioral algorithm **1802** are shown as components of the motherboard **502**. However, other configurations are possible. For example, the same or a similar behavioral analysis module and/or behavior algorithm can be run in one or more cloud services, and the resulting output can be sent to the motherboard **502**, a controller in the controller array **508**, or to any other technologically appropriate recipient.

(187) FIG. **19** shows an example of a computing device **1900** and an example of a mobile computing device that can be used to implement the techniques described here. The computing device **1900** is intended to represent various forms of digital computers, such as laptops, desktops, workstations, personal digital assistants, servers, blade servers, mainframes, and other appropriate computers. The mobile computing device is intended to represent various forms of mobile devices, such as personal digital assistants, cellular telephones, smart-phones, and other similar computing devices. The components shown here, their connections and relationships, and their functions, are meant to be exemplary only, and are not meant to limit implementations of the inventions described and/or claimed in this document.

(188) The computing device **1900** includes a processor **1902**, a memory **1904**, a storage device **1906**, a high-speed interface **1908** connecting to the memory **1904** and multiple high-speed expansion ports **1910**, and a low-speed interface **1912** connecting to a low-speed expansion port **1914** and the storage device **1906**. Each of the processor **1902**, the memory **1904**, the storage device **1906**, the high-speed interface **1908**, the high-speed expansion ports **1910**, and the low-speed interface **1912**, are interconnected using various buses, and can be mounted on a common motherboard or in other manners as appropriate. The processor **1902** can process instructions for execution within the computing device **1900**, including instructions stored in the memory **1904** or on the storage device **1906** to display graphical information for a GUI on an external input/output device, such as a display **1916** coupled to the high-speed interface **1908**. In other implementations,

multiple processors and/or multiple buses can be used, as appropriate, along with multiple memories and types of memory. Also, multiple computing devices can be connected, with each device providing portions of the necessary operations (e.g., as a server bank, a group of blade servers, or a multi-processor system).

(189) The memory **1904** stores information within the computing device **1900**. In some implementations, the memory **1904** is a volatile memory unit or units. In some implementations, the memory **1904** is a non-volatile memory unit or units. The memory **1904** can also be another form of computer-readable medium, such as a magnetic or optical disk.

(190) The storage device **1906** is capable of providing mass storage for the computing device **1900**. In some implementations, the storage device **1906** can be or contain a computer-readable medium, such as a floppy disk device, a hard disk device, an optical disk device, or a tape device, a flash memory or other similar solid state memory device, or an array of devices, including devices in a storage area network or other configurations. A computer program product can be tangibly embodied in an information carrier. The computer program product can also contain instructions that, when executed, perform one or more methods, such as those described above. The computer program product can also be tangibly embodied in a computer- or machine-readable medium, such as the memory **1904**, the storage device **1906**, or memory on the processor **1902**.

(191) The high-speed interface **1908** manages bandwidth-intensive operations for the computing device **1900**, while the low-speed interface **1912** manages lower bandwidth-intensive operations. Such allocation of functions is exemplary only. In some implementations, the high-speed interface **1908** is coupled to the memory **1904**, the display **1916** (e.g., through a graphics processor or accelerator), and to the high-speed expansion ports **1910**, which can accept various expansion cards (not shown). In the implementation, the low-speed interface **1912** is coupled to the storage device **1906** and the low-speed expansion port **1914**. The low-speed expansion port **1914**, which can include various communication ports (e.g., USB, Bluetooth, Ethernet, wireless Ethernet) can be coupled to one or more input/output devices, such as a keyboard, a pointing device, a scanner, or a networking device such as a switch or router, e.g., through a network adapter.

(192) The computing device **1900** can be implemented in a number of different forms, as shown in the figure. For example, it can be implemented as a standard server **1920**, or multiple times in a group of such servers. In addition, it can be implemented in a personal computer such as a laptop computer **1922**. It can also be implemented as part of a rack server system **1924**. Alternatively, components from the computing device **1900** can be combined with other components in a mobile device (not shown), such as a mobile computing device **1950**. Each of such devices can contain one or more of the computing device **1900** and the mobile computing device **1950**, and an entire system can be made up of multiple computing devices communicating with each other.

(193) The mobile computing device **1950** includes a processor **1952**, a memory **1964**, an input/output device such as a display **1954**, a communication interface **1966**, and a transceiver **1968**, among other components. The mobile computing device **1950** can also be provided with a storage device, such as a micro-drive or other device, to provide additional storage. Each of the processor **1952**, the memory **1964**, the display **1954**, the communication interface **1966**, and the transceiver **1968**, are interconnected using various buses, and several of the components can be mounted on a common motherboard or in other manners as appropriate.

(194) The processor **1952** can execute instructions within the mobile computing device **1950**, including instructions stored in the memory **1964**. The processor **1952** can be implemented as a chip set of chips that include separate and multiple analog and digital processors. The processor **1952** can provide, for example, for coordination of the other components of the mobile computing device **1950**, such as control of user interfaces, applications run by the mobile computing device **1950**, and wireless communication by the mobile computing device **1950**.

(195) The processor **1952** can communicate with a user through a control interface **1958** and a display interface **1956** coupled to the display **1954**. The display **1954** can be, for example, a TFT

(Thin-Film-Transistor Liquid Crystal Display) display or an OLED (Organic Light Emitting Diode) display, or other appropriate display technology. The display interface **1956** can comprise appropriate circuitry for driving the display **1954** to present graphical and other information to a user. The control interface **1958** can receive commands from a user and convert them for submission to the processor **1952**. In addition, an external interface **1962** can provide communication with the processor **1952**, so as to enable near area communication of the mobile computing device **1950** with other devices. The external interface **1962** can provide, for example, for wired communication in some implementations, or for wireless communication in other implementations, and multiple interfaces can also be used.

(196) The memory **1964** stores information within the mobile computing device **1950**. The memory **1964** can be implemented as one or more of a computer-readable medium or media, a volatile memory unit or units, or a non-volatile memory unit or units. An expansion memory **1974** can also be provided and connected to the mobile computing device **1950** through an expansion interface **1972**, which can include, for example, a SIMM (Single In Line Memory Module) card interface. The expansion memory **1974** can provide extra storage space for the mobile computing device **1950**, or can also store applications or other information for the mobile computing device **1950**. Specifically, the expansion memory **1974** can include instructions to carry out or supplement the processes described above, and can include secure information also. Thus, for example, the expansion memory **1974** can be provide as a security module for the mobile computing device **1950**, and can be programmed with instructions that permit secure use of the mobile computing device **1950**. In addition, secure applications can be provided via the SIMM cards, along with additional information, such as placing identifying information on the SIMM card in a non-hackable manner.

(197) The memory can include, for example, flash memory and/or NVRAM memory (non-volatile random access memory), as discussed below. In some implementations, a computer program product is tangibly embodied in an information carrier. The computer program product contains instructions that, when executed, perform one or more methods, such as those described above. The computer program product can be a computer- or machine-readable medium, such as the memory **1964**, the expansion memory **1974**, or memory on the processor **1952**. In some implementations, the computer program product can be received in a propagated signal, for example, over the transceiver **1968** or the external interface **1962**.

(198) The mobile computing device **1950** can communicate wirelessly through the communication interface **1966**, which can include digital signal processing circuitry where necessary. The communication interface **1966** can provide for communications under various modes or protocols, such as GSM voice calls (Global System for Mobile communications), SMS (Short Message Service), EMS (Enhanced Messaging Service), or MMS messaging (Multimedia Messaging Service), CDMA (code division multiple access), TDMA (time division multiple access), PDC (Personal Digital Cellular), WCDMA (Wideband Code Division Multiple Access), CDMA2000, or GPRS (General Packet Radio Service), among others. Such communication can occur, for example, through the transceiver **1968** using a radio-frequency. In addition, short-range communication can occur, such as using a Bluetooth, WiFi, or other such transceiver (not shown). In addition, a GPS (Global Positioning System) receiver module **1970** can provide additional navigation- and location-related wireless data to the mobile computing device **1950**, which can be used as appropriate by applications running on the mobile computing device **1950**.

(199) The mobile computing device **1950** can also communicate audibly using an audio codec **1960**, which can receive spoken information from a user and convert it to usable digital information. The audio codec **1960** can likewise generate audible sound for a user, such as through a speaker, e.g., in a handset of the mobile computing device **1950**. Such sound can include sound from voice telephone calls, can include recorded sound (e.g., voice messages, music files, etc.) and can also include sound generated by applications operating on the mobile computing device **1950**.

- (200) The mobile computing device **1950** can be implemented in a number of different forms, as shown in the figure. For example, it can be implemented as a cellular telephone **1980**. It can also be implemented as part of a smart-phone **1982**, personal digital assistant, or other similar mobile device.
- (201) Various implementations of the systems and techniques described here can be realized in digital electronic circuitry, integrated circuitry, specially designed ASICs (application specific integrated circuits), computer hardware, firmware, software, and/or combinations thereof. These various implementations can include implementation in one or more computer programs that are executable and/or interpretable on a programmable system including at least one programmable processor, which can be special or general purpose, coupled to receive data and instructions from, and to transmit data and instructions to, a storage system, at least one input device, and at least one output device.
- (202) These computer programs (also known as programs, software, software applications or code) include machine instructions for a programmable processor, and can be implemented in a high-level procedural and/or object-oriented programming language, and/or in assembly/machine language. As used herein, the terms machine-readable medium and computer-readable medium refer to any computer program product, apparatus and/or device (e.g., magnetic discs, optical disks, memory, Programmable Logic Devices (PLDs)) used to provide machine instructions and/or data to a programmable processor, including a machine-readable medium that receives machine instructions as a machine-readable signal. The term machine-readable signal refers to any signal used to provide machine instructions and/or data to a programmable processor.
- (203) To provide for interaction with a user, the systems and techniques described here can be implemented on a computer having a display device (e.g., a CRT (cathode ray tube) or LCD (liquid crystal display) monitor) for displaying information to the user and a keyboard and a pointing device (e.g., a mouse or a trackball) by which the user can provide input to the computer. Other kinds of devices can be used to provide for interaction with a user as well; for example, feedback provided to the user can be any form of sensory feedback (e.g., visual feedback, auditory feedback, or tactile feedback); and input from the user can be received in any form, including acoustic, speech, or tactile input.
- (204) The systems and techniques described here can be implemented in a computing system that includes a back end component (e.g., as a data server), or that includes a middleware component (e.g., an application server), or that includes a front end component (e.g., a client computer having a graphical user interface or a Web browser through which a user can interact with an implementation of the systems and techniques described here), or any combination of such back end, middleware, or front end components. The components of the system can be interconnected by any form or medium of digital data communication (e.g., a communication network). Examples of communication networks include a local area network (LAN), a wide area network (WAN), and the Internet.
- (205) The computing system can include clients and servers. A client and server are generally remote from each other and typically interact through a communication network. The relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other.

Claims

1. A remote control for a bed system, the remote control comprising: a case comprising a base surface, a display surface, an upper surface, and a portion of the case that is capacitively sensitive, the remote control being configured to wake responsive to a signal from the portion of the case that is capacitively sensitive due to a change in capacitance resulting from a user touch; a display screen on the display surface; a first input area on the display surface; at least one capacitive button

- separate from the first input area and the display screen; and a communication module configured to allow communication between the remote control and a separate controller of the bed system.
2. The remote control of claim 1, wherein a portion of the case is metallic.
 3. The remote control of claim 1, wherein the first input area comprises a direction pad and a selection pad.
 4. The remote control of claim 1, wherein the upper surface is a different surface than the display surface and is angled with respect to the display surface, and further comprising a slider switch on the upper surface, the slider switch configured to toggle between a first position and a second position.
 5. The remote control of claim 1, wherein the remote control is wirelessly coupled to the separate controller.
 6. The remote control of claim 1, wherein the separate controller is a bed controller configured to control pressure, articulation, temperature, or light level of the bed system.
 7. The remote control of claim 1, wherein the remote control is configured to: ping the separate controller upon waking, receive a state from the separate controller responsive to the ping, and display an interface on the display screen responsive to the received state.
 8. The remote control of claim 1, wherein the capacitive button is between the display screen and the first input area.
 9. The remote control of claim 1, wherein the base surface is sized to allow the remote control to rest in a vertical position with the base surface positioned opposite the upper surface.
 10. The remote control of claim 1, wherein the base surface is substantially triangular and the upper surface is a rounded rectangle.
 11. The remote control of claim 1, further comprising a light sensor configured to: receive ambient light, and produce a light signal representative of an ambient light level.
 12. The remote control of claim 11, wherein the remote control is configured to adjust a brightness of the display screen or the first input area responsive to the light signal.
 13. A remote control for a bed system, the remote control comprising: a case comprising a base surface, a display surface, and an upper surface; a display screen on the display surface; a first input area on the display surface; at least one capacitive button separate from the first input area and the display screen; a slider switch, the slider switch configured to toggle between a first position and a second position, wherein the slider switch adjusts an interface displayed on the display screen to control a first side of a bed when the slider switch is in the first position and adjusts the interface displayed on the display to control a second side of the bed when the slider switch is in the second position.
 14. A bed control system comprising: a bed controller configured to control functions of a bed; a remote control physically separate from the bed controller, wherein the remote control is wirelessly coupled to the bed controller, the remote control comprising: a case comprising a base surface, a display surface, and an upper surface, wherein a portion of the case separate from the display surface is capacitively sensitive, a display screen on the display surface, and an input area on the display surface, the remote control configured to: wake responsive to a signal from the case of the remote control due to a change in capacitance resulting from a user touch on the case of the remote control, ping the bed controller upon waking, receive a state from the bed controller responsive to the ping, and display an interface on the display screen responsive to the received state.
 15. The bed control system of claim 14, wherein the capacitive button is between the display screen and the input area.
 16. The bed control system of claim 14, wherein the upper surface is positioned opposite of the base surface, and further comprising a slider switch on the upper surface configured to toggle between a first position and a second position.
 17. The bed control system of claim 14, wherein the base surface of the remote control is sized to allow the remote control to rest in a vertical position.

18. The bed control system of claim 14, wherein the base surface of the remote control is substantially triangular, wherein the upper surface of the remote control is not substantially triangular, and wherein the remote control tapers from the base surface to the upper surface.
19. The bed control system of claim 14, wherein the remote control further comprises a light sensor configured to: receive ambient light, and produce a light signal representative of an ambient light level.
20. The bed control system of claim 19, wherein the bed controller is configured to adjust a brightness of the display screen and the input area responsive to the light signal.
-