

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410912
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Nick; Mackenzie J. et al.

Shadowless lighting system for a handheld power tool

Abstract

One example power tool includes a primary housing. A motor may be situated within the primary housing. The power tool may further include a transmission mechanism configured to transmit rotational energy from the motor to an output unit of the power tool. The power tool may further include a secondary housing in which at least a portion of the transmission mechanism is located. The power tool may further include a light source mounted to a front end of the secondary housing. The power tool may include one or more wires that extend through the passageway and that are electrically connected to the light source.

Inventors:	Nick; Mackenzie J. (Theresa, WI), Farley; Benjamin J. (Milwaukee, WI), Craig; Kentez L. (Milwaukee, WI)
Applicant:	MILWAUKEE ELECTRIC TOOL CORPORATION (Brookfield, WI)
Family ID:	86336609
Assignee:	MILWAUKEE ELECTRIC TOOL CORPORATION (Brookfield, WI)
Appl. No.:	18/699728
Filed (or PCT Filed):	November 01, 2022
PCT No.:	PCT/US2022/048534
PCT Pub. No.:	WO2023/086237
PCT Pub. Date:	May 19, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240410564 A1	Dec. 12, 2024

Related U.S. Application Data

us-provisional-application US 63321896 20220321
us-provisional-application US 63278719 20211112

Publication Classification

Int. Cl.: F21V23/00 (20150101); F21V33/00 (20060101); F21Y115/10 (20160101)

U.S. Cl.:

CPC F21V33/0084 (20130101); F21V23/001 (20130101); F21Y2115/10 (20160801)

Field of Classification Search

CPC: F21Y (2115/10); B25B (23/18); F21V (33/0084); H02K (7/145); H01R (39/64); B23Q (17/2404); F21L (13/00); F21S (9/04)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2310166	12/1942	Way	N/A	N/A
2525588	12/1949	Cameron et al.	N/A	N/A
5267129	12/1992	Anderson	N/A	N/A
6494590	12/2001	Paganini et al.	N/A	N/A
6886961	12/2004	Hara et al.	N/A	N/A
6981779	12/2005	Fukuoka	N/A	N/A
7137761	12/2005	Hara et al.	N/A	N/A
7185998	12/2006	Oomori et al.	N/A	N/A
7253541	12/2006	Kovarik et al.	N/A	N/A
7677752	12/2009	Tadokoro et al.	N/A	N/A
7850325	12/2009	Wall et al.	N/A	N/A
7934847	12/2010	Oomori et al.	N/A	N/A
8075155	12/2010	Watanabe et al.	N/A	N/A
8317350	12/2011	Friedman et al.	N/A	N/A
8328308	12/2011	Kurashina	N/A	N/A
8328381	12/2011	Dixon et al.	N/A	N/A
8446120	12/2012	Forster et al.	N/A	N/A
8496366	12/2012	Leong	N/A	N/A
8506108	12/2012	Friedman et al.	N/A	N/A
8517558	12/2012	Oomori et al.	N/A	N/A
8616300	12/2012	Suzuki et al.	N/A	N/A
8653787	12/2013	Cunanan et al.	N/A	N/A
8796995	12/2013	Cunanan et al.	N/A	N/A
8820955	12/2013	Dixon et al.	N/A	N/A
8827483	12/2013	Dixon et al.	N/A	N/A
8833485	12/2013	Svennung et al.	N/A	N/A

8981680	12/2014	Suda et al.	N/A	N/A
8988015	12/2014	Forster et al.	N/A	N/A
9000882	12/2014	Velderman et al.	N/A	N/A
9028088	12/2014	Vanko et al.	N/A	N/A
9071069	12/2014	Brotto et al.	N/A	N/A
9114512	12/2014	Beer et al.	N/A	N/A
9138846	12/2014	Svennung et al.	N/A	N/A
9209642	12/2014	Cunanan et al.	N/A	N/A
9225275	12/2014	Sterling et al.	N/A	N/A
9289832	12/2015	Kishima et al.	N/A	N/A
9302376	12/2015	Agehara et al.	N/A	N/A
9328915	12/2015	Vanko et al.	N/A	N/A
9352458	12/2015	Friedman et al.	N/A	N/A
9401250	12/2015	Velderman et al.	N/A	N/A
9406457	12/2015	Velderman et al.	N/A	N/A
9413088	12/2015	Brotto et al.	N/A	N/A
9444269	12/2015	Wohlmann et al.	N/A	N/A
9458996	12/2015	Francis et al.	N/A	N/A
9461379	12/2015	Cunanan et al.	N/A	N/A
9481081	12/2015	Hecht et al.	N/A	N/A
9508498	12/2015	Forster et al.	N/A	N/A
9539691	12/2016	Hirschburger	N/A	N/A
9561548	12/2016	Kishima et al.	N/A	N/A
9570822	12/2016	Cunanan et al.	N/A	N/A
9573257	12/2016	Kynast et al.	N/A	N/A
9644837	12/2016	Vanko et al.	N/A	N/A
9692157	12/2016	Brotto et al.	N/A	N/A
9722334	12/2016	Sterling et al.	N/A	N/A
9844849	12/2016	Hayashi et al.	N/A	N/A
9878435	12/2017	Ito	N/A	N/A
9914204	12/2017	Hosking	N/A	N/A
9960509	12/2017	Sterling et al.	N/A	N/A
9966774	12/2017	Wohlmann et al.	N/A	N/A
10027140	12/2017	Cunanan et al.	N/A	N/A
10040181	12/2017	Fu et al.	N/A	N/A
10052733	12/2017	Ely et al.	N/A	N/A
10256697	12/2018	Velderman et al.	N/A	N/A
10272548	12/2018	Wei et al.	N/A	N/A
10486291	12/2018	Bartoszek	N/A	N/A
10486296	12/2018	Ito	N/A	N/A
10525582	12/2019	Qiu et al.	N/A	N/A
10543588	12/2019	Vanko et al.	N/A	N/A
10651706	12/2019	Forster et al.	N/A	N/A
10666068	12/2019	Cunanan et al.	N/A	N/A
10686319	12/2019	Wohlmann et al.	N/A	N/A
10749353	12/2019	Tsuruta et al.	N/A	N/A
10821595	12/2019	Qiu et al.	N/A	N/A
10836019	12/2019	Matsushita et al.	N/A	N/A
10926368	12/2020	Chellew	N/A	N/A
10960509	12/2020	Ely et al.	N/A	N/A

11090786	12/2020	Puzio	N/A	N/A
11095239	12/2020	Delose et al.	N/A	N/A
11278973	12/2021	Nagasaka et al.	N/A	N/A
2006/0104085	12/2005	Walker et al.	N/A	N/A
2006/0262519	12/2005	Hirschburger et al.	N/A	N/A
2007/0256914	12/2006	Lohr et al.	N/A	N/A
2008/0074865	12/2007	Lutz	362/119	B25B 23/18
2010/0072833	12/2009	Canino et al.	N/A	N/A
2011/0058356	12/2010	Friedman et al.	N/A	N/A
2014/0232326	12/2013	Wohltmann et al.	N/A	N/A
2014/0262394	12/2013	Scott et al.	N/A	N/A
2019/0070720	12/2018	Rabe et al.	N/A	N/A
2020/0047322	12/2019	Ito	N/A	N/A
2020/0101587	12/2019	Niwa	N/A	N/A
2020/0114499	12/2019	Vanko et al.	N/A	N/A
2020/0130164	12/2019	Qiu et al.	N/A	N/A
2020/0198100	12/2019	Schneider	N/A	B25B 21/02
2020/0235638	12/2019	Velderman	N/A	N/A
2020/0295579	12/2019	Wohltmann et al.	N/A	N/A
2021/0122017	12/2020	Kelly	N/A	N/A
2021/0222866	12/2020	Niwa	N/A	N/A
2021/0260733	12/2020	Fischer et al.	N/A	N/A
2022/0009064	12/2021	Puzio	N/A	N/A
2023/0366533	12/2022	Chikaraishi et al.	N/A	N/A
2024/0058937	12/2023	Chikaraishi et al.	N/A	N/A
2024/0075609	12/2023	Zhao et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201201230	12/2008	CN	N/A
201470941	12/2009	CN	N/A
103231350	12/2012	CN	N/A
204209605	12/2014	CN	N/A
204470650	12/2014	CN	N/A
105798356	12/2015	CN	N/A
205765866	12/2015	CN	N/A
106393010	12/2016	CN	N/A
205938750	12/2016	CN	N/A
106475977	12/2016	CN	N/A
106625452	12/2016	CN	N/A
206344094	12/2016	CN	N/A
206605460	12/2016	CN	N/A
208867076	12/2018	CN	N/A
208961941	12/2018	CN	N/A
110170953	12/2018	CN	N/A
210173433	12/2019	CN	N/A
214418661	12/2020	CN	N/A
216030486	12/2021	CN	N/A
102011075663	12/2011	DE	N/A
102012009981	12/2011	DE	N/A

102011103656	12/2011	DE	N/A
102012205274	12/2012	DE	B25F 5/00
102012211580	12/2013	DE	N/A
102015214522	12/2016	DE	N/A
102015226420	12/2016	DE	N/A
3473383	12/2018	EP	N/A
3015224	12/2019	EP	N/A
3212359	12/2023	EP	N/A
2001057293	12/2000	JP	N/A
2019025636	12/2018	JP	N/A
M487960	12/2013	TW	N/A
2013136917	12/2012	WO	N/A
2019052920	12/2018	WO	N/A
2019170331	12/2018	WO	N/A
2021252702	12/2020	WO	N/A
2023086237	12/2022	WO	N/A

OTHER PUBLICATIONS

Search English translation of DE-102012205274-A1 (Year: 2013). cited by examiner

Search English translation of TW-M487960-U (Year: 2014). cited by examiner

U.S. Appl. No. 18/602,954, filed Mar. 12, 2024, by Nick et al. (Copy not submitted herewith pursuant to the waiver of 37 C.F. R. § 1.98(a)(2)(iii) issued by the Office on Oct. 19, 2004). cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2022/048534 dated Mar. 9, 2023 (12 pages). cited by applicant

Primary Examiner: Cadima; Omar Rojas

Attorney, Agent or Firm: Michael Best & Friedrich LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a national phase filing under 35 U.S.C. § 371 of International Application No. PCT/US2022/048534, filed Nov. 1, 2022, which claims priority to U.S. Provisional Application No. 63/321,896 filed Mar. 21, 2022, and to U.S. Provisional Application No. 63/278,719 filed Nov. 12, 2021, the entire contents of all of which are incorporated herein by reference.

FIELD OF THE INVENTION

(1) Some disclosed embodiments relate to a handheld power tool that includes a lighting assembly. Specifically, some disclosed embodiments relate to a handheld power tool that includes a shadowless lighting system.

SUMMARY

(2) Handheld power tools may include one or more work lights configured to illuminate a working area of the power tool. For example, a power tool may include a single work light positioned near an output unit of the power tool to illuminate an area on which the output unit is providing an output to, for example, drill into a work piece, secure a fastener in a work piece, or the like.

(3) Some power tools may include a work light located on a front surface of the power tool configured to illuminate a working area of the power tool. For example, a high-torque impact

wrench may include a single light-emitting diode (LED) positioned near an output unit that is configured to transfer rotational energy from the high-torque impact wrench to a fastener. While the high-torque impact wrench is being operated by a user, the LED may illuminate the fastener so that the user can more easily see the fastener. However, using a single LED may cause a shadow to be cast by the output unit, which can negatively affect the visibility of the fastener. To address this problem, a power tool may include multiple LEDs positioned radially around the output unit or end tool of the power tool. Providing multiple LEDs around the output unit creates even lighting applied to all sides of the output unit or end tool, which prevents shadows from being cast. This type of lighting may be generally referred to as shadowless lighting.

(4) While shadowless lighting helps to improve the visibility of the fastener, implementing shadowless lighting in a power tool (e.g., on a front surface of a hammer case) can raise additional issues. For example, each LED mounted to the front surface of the power tool may require multiple wires to provide power and/or control signals to the LEDs. As more LEDs are included, more wires may be needed. Therefore, power tools implementing shadowless lighting require an efficient method to locate these wires in the limited space provided within a handheld power tool.

(5) One embodiment provides a power tool that may include a primary housing. A motor may be situated within the primary housing. The power tool may further include a transmission mechanism configured to transmit rotational energy from the motor to an output unit of the power tool. The power tool may further include a secondary housing in which at least a portion of the transmission mechanism is located. The secondary housing may include an outer peripheral surface and a protrusion protruding outwardly from the outer peripheral surface. The power tool may further include a light source mounted to a front end of the secondary housing. The power tool may further include a passageway through the secondary housing. The passageway may include a first end at the front end of the secondary housing and a second end at a rear end of the secondary housing. At least part of the passageway may be located in the protrusion. The power tool may include one or more wires electrically connected to the light source. The one or more wires may extend through the passageway. The second end of the passageway may be open to an interior of the primary housing to direct the one or more wires into the primary housing.

(6) Another embodiment provides a power tool that may include a primary housing. A motor may be situated within the primary housing. The power tool may further include a transmission mechanism configured to transmit rotational energy from the motor to an output unit of the power tool. The power tool may further include a secondary housing configured to house the transmission mechanism. The power tool may further include a light source mounted to a front end of the secondary housing. The power tool may further include a passageway through the secondary housing. The power tool may further include one or more wires electrically connected to the light source. The one or more wires may extend through the passageway.

(7) Another embodiment provides a method of assembling a power tool. The method may include providing a primary housing, and situating a motor within the primary housing. The method may further include providing a secondary housing, and situating a transmission mechanism configured to transmit rotational energy from the motor to an output unit of the power tool within the secondary housing. The secondary housing may include a passageway. The method may further include mounting a light source to a front end of the secondary housing. The method may further include inserting one or more wires configured to be electrically connected to the light source through the passageway such that at least a portion of the one or more wires is located in the passageway.

(8) Another embodiment provides a power tool that may include a primary housing. A motor may be situated within the primary housing. The power tool may further include a transmission mechanism configured to transmit rotational energy from the motor to an output unit of the power tool. The power tool may further include a secondary housing configured to house the transmission mechanism. The power tool may further include a light holding device mounted to a front end of

the secondary housing. The power tool may further include a light source configured to be held by the light holding device. The power tool may further include a cover configured to cover at least a portion of a front surface of the light holding device. The secondary housing may include a first groove on a front surface of the secondary housing. The first groove may be configured to receive a rearwardly protruding part of the cover that protrudes further rearward than a main portion of the light holding device. The secondary housing may include a neck portion that includes a shoulder on an outer peripheral surface of the neck portion. The shoulder may be configured to receive an overhanging part of the cover that protrudes radially closer to an output axis of the output unit than the front surface of the light holding device.

(9) Before any embodiments are explained in detail, it is to be understood that the embodiments are not limited in its application to the details of the configuration and arrangement of components set forth in the following description or illustrated in the accompanying drawings. The embodiments are capable of being practiced or of being carried out in various ways. Also, it is to be understood that the phraseology and terminology used herein are for the purpose of description and should not be regarded as limiting. The use of “including,” “comprising,” or “having” and variations thereof are meant to encompass the items listed thereafter and equivalents thereof as well as additional items. Unless specified or limited otherwise, the terms “mounted,” “connected,” “supported,” and “coupled” and variations thereof are used broadly and encompass both direct and indirect mountings, connections, supports, and couplings.

(10) In addition, it should be understood that embodiments may include hardware, software, and electronic components or modules that, for purposes of discussion, may be illustrated and described as if the majority of the components were implemented solely in hardware. However, one of ordinary skill in the art, and based on a reading of this detailed description, would recognize that, in at least one embodiment, the electronic-based aspects may be implemented in software (e.g., stored on non-transitory computer-readable medium) executable by one or more processing units, such as a microprocessor and/or application specific integrated circuits (“ASICs”). As such, it should be noted that a plurality of hardware and software based devices, as well as a plurality of different structural components, may be utilized to implement the embodiments. For example, “servers” and “computing devices” described in the specification can include one or more processing units, one or more computer-readable medium modules, one or more input/output interfaces, and various connections (e.g., a system bus) connecting the components.

(11) Relative terminology, such as, for example, “about,” “approximately,” “substantially,” etc., used in connection with a quantity or condition would be understood by those of ordinary skill to be inclusive of the stated value and has the meaning dictated by the context (e.g., the term includes at least the degree of error associated with the measurement accuracy, tolerances [e.g., manufacturing, assembly, use, etc.] associated with the particular value, etc.). Such terminology should also be considered as disclosing the range defined by the absolute values of the two endpoints. For example, the expression “from about 2 to about 4” also discloses the range “from 2 to 4”. The relative terminology may refer to plus or minus a percentage (e.g., 1%, 5%, 10%, or more) of an indicated value.

(12) It should be understood that although certain drawings illustrate hardware and software located within particular devices, these depictions are for illustrative purposes only. Functionality described herein as being performed by one component may be performed by multiple components in a distributed manner. Likewise, functionality performed by multiple components may be consolidated and performed by a single component. In some embodiments, the illustrated components may be combined or divided into separate software, firmware and/or hardware. For example, instead of being located within and performed by a single electronic processor, logic and processing may be distributed among multiple electronic processors. Similarly, a component described as performing particular functionality may also perform additional functionality not described herein. For example, a device or structure that is “configured” in a certain way is

configured in at least that way but may also be configured in ways that are not explicitly listed.
(13) Other aspects of the embodiments will become apparent by consideration of the detailed description and accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 illustrates a power tool that includes a shadowless lighting system, according to some embodiments described herein.
- (2) FIG. 2 illustrates a cross-sectional view of the power tool of FIG. 1, according to some embodiments described herein.
- (3) FIG. 3 illustrates a block diagram of the power tool of FIG. 1, according to some embodiments described herein.
- (4) FIG. 4A illustrates a rear perspective view of a secondary housing of the power tool of FIG. 1, according to some embodiments described herein.
- (5) FIG. 4B illustrates a front perspective view of the secondary housing of the power tool of FIG. 1, according to some embodiments described herein.
- (6) FIG. 5A illustrates a rear perspective view of a retaining portion of the shadowless lighting system of the power tool of FIG. 1, according to some embodiments described herein.
- (7) FIG. 5B illustrates a front perspective view of the retaining portion of the shadowless lighting system of the power tool of FIG. 1, according to some embodiments described herein.
- (8) FIG. 5C illustrates a rear perspective view of a cover of the retaining portion of FIGS. 5A and 5B, according to some embodiments described herein.
- (9) FIG. 5D illustrates a rear perspective view of a light holding device of the retaining portion of FIGS. 5A and 5B, according to some embodiments described herein.
- (10) FIG. 5E illustrates a retention ring used to secure the retaining portion of FIGS. 5A and 5B to the secondary housing of FIGS. 4A and 4B according to one example embodiment.
- (11) FIG. 6 illustrates a shadowless lighting system of the power tool of FIG. 1, according to some embodiments described herein.
- (12) FIG. 7 illustrates a method for manufacturing a power tool including a shadowless lighting system, according to some embodiments described herein.
- (13) FIG. 8 illustrates another power tool that includes many similar features as the power tool 100 of FIGS. 1-6 and some different features than the power tool of FIGS. 1-6, according to some embodiments described herein.
- (14) FIG. 9A illustrates a side view of the power tool of FIG. 8 with one half of a clamshell housing removed, with a potting boat removed, and with a retaining portion removed, according to some embodiments described herein.
- (15) FIG. 9B illustrates a partially disassembled view of the power tool of FIG. 8, according to some embodiments described herein.
- (16) FIG. 9C illustrates a cross-sectional view of a front portion of the power tool of FIG. 8, according to some embodiments described herein.
- (17) FIG. 10A illustrates a rear perspective view of a secondary housing of the power tool of FIG. 8, according to some embodiments described herein.
- (18) FIG. 10B illustrates a front perspective view of the secondary housing of the power tool of FIG. 8, according to some embodiments described herein.
- (19) FIG. 11A illustrates a perspective view of a portion of a retaining portion of the power tool of FIG. 8, according to some embodiments described herein.
- (20) FIG. 11B illustrates a side view of a portion of the secondary housing of the power tool of FIG. 8, according to some embodiments described herein.

- (21) FIG. 12A illustrates a cross-sectional view of the retaining portion of the power tool of FIG. 8, according to some embodiments described herein.
- (22) FIG. 12B illustrates a cross-sectional view of the secondary housing of the power tool of FIG. 8, according to some embodiments described herein.
- (23) FIG. 13A illustrates a rear perspective view of the retaining portion of the power tool of FIG. 8, according to some embodiments described herein.
- (24) FIG. 13B illustrates a front perspective view of the secondary housing of the power tool of FIG. 8, according to some embodiments described herein.
- (25) FIG. 14A illustrates another rear perspective view of the retaining portion of the power tool of FIG. 8, according to some embodiments described herein.
- (26) FIG. 14B illustrates another front perspective view of the secondary housing of the power tool of FIG. 8, according to some embodiments described herein.
- (27) FIG. 15 illustrates a retention ring of the power tool of FIG. 8 that is used to secure the retaining portion of the power tool of FIG. 8 to the secondary housing of the power tool of FIG. 8, according to one example embodiment.
- (28) FIGS. 16A and 16B illustrate cross-sectional views of a front portion of the power tool of FIG. 8 with a second groove configured to receive the retention ring of FIG. 15 in different locations, according to some example embodiments.

DETAILED DESCRIPTION

(29) FIG. 1 illustrates a power tool **100** that includes a shadowless lighting system according to one example embodiment. The power tool **100** includes a primary housing **105**. The primary housing **105** may be a main body of the power tool **100**. The primary housing **105** may be configured to house a brushless direct current (BLDC) motor in an upper portion **107** of the primary housing **105**. Accordingly, the primary housing **105** (in particular, the upper portion **107** of the primary housing **105**) may also be referred to as a motor housing. In some embodiments, the primary housing **105** is formed from two pieces of plastic configured to mate (e.g., a clamshell housing), such that an interior cavity is formed within the primary housing **105**. A portion of the primary housing **105** may be formed into a handle **110** to allow a user to hold the power tool **100**. A trigger **115** may be positioned on the handle **110** to allow a user to actuate the trigger **115** to variably control at least one parameter of the power tool **100**. In some embodiments, the parameter may be an amount of power supplied to a motor of the power tool **100**. The primary housing **105** may further include a connection portion **120** (i.e., a foot portion of the power tool **100**) that may include an interface **122** (i.e., a battery pack interface **122**) configured to removably couple to a battery pack (not shown). The interface **122** may include electrical contacts to allow power to be transferred from the battery pack to the power tool **100** (e.g., to provide power to the motor and other components of the power tool **100**). The power tool **100** further includes an output unit **125** on one end of the upper portion **107** of the primary housing **105** to provide an output of the power tool. For example, the output of the power tool may be a rotational output, an impacting output, a reciprocating output, etc. In some embodiments, the output unit **125** may include a fitting (e.g., a chuck, a collet, or the like) to removably couple an end tool (e.g., a tool bit) to the output unit **125**. In other embodiments, the output unit **125** may be formed such that a fastener directly removably couples to the output unit **125** to perform a loosening or tightening operation of the fastener. In some embodiments, the power tool **100** includes a forward/reverse switch **127** configured to allow a user to select a rotational direction of the output unit **125**.

(30) The power tool **100** further includes a secondary housing **130** separate from the primary housing **105**. The secondary housing **130** may be configured to house a transmission mechanism of the power tool **100** configured to transmit rotational energy from a motor of the power tool **100** to the output unit **125**. In some embodiments, the secondary housing **130** is a gear case, a hammer case, or the like. The secondary housing **130** may be made of metal. The secondary housing **130** may be positioned such that an end surface of the secondary housing **130** contacts at least a portion

of an end surface of the primary housing **105**. For example, as shown in FIG. **1**, a rear end of the secondary housing **130** may be fastened to a front end of the upper portion **107** of the primary housing **105** using fasteners **132**. The secondary housing **130** is described in further detail with respect to FIGS. **4A** and **4B**.

(31) The power tool **100** further includes a retaining portion **135** configured to retain one or more light sources of the power tool **100**. In some embodiments, the retaining portion **135** is configured to surround the output unit **125**. The retaining portion **135** may include one or more lenses **140** to allow for one or more light sources to emit light through the retaining portion **135**. In some embodiments, the one or more light sources may be light-emitting diodes (LEDs) arranged about a center point of the retaining portion **135** (i.e., arranged about a output axis of the output unit **125**). The retaining portion **135** is described in further detail with respect to FIGS. **5A-5E**. While referred to as the retaining portion **135**, the retaining portion **135** may also be referred to as a lighting assembly **135**.

(32) The particular power tool **100** illustrated and described herein (e.g., an impact wrench) is merely an example. The lighting assembly **135** and associated wire routing designs disclosed herein may also be implemented on other types of power tools (e.g., a power drill, a hammer drill, an impact driver, etc.).

(33) FIG. **2** illustrates a cross-sectional view of the power tool **100** according to one example embodiment. The power tool **100** includes a motor **200** configured to provide a rotational output about an axis **202** (i.e., a motor axis or output axis). The power tool **100** further includes a transmission mechanism **205** (i.e., transmission device **205**) configured to transfer the rotational output of the motor **200** to the output unit **125**. The transmission mechanism **205** may be a gear transmission mechanism, an electronic transmission mechanism, an impacting transmission mechanism, a combination of multiple types of transmission mechanism, or the like. At least a portion of the transmission mechanism **205** may be positioned within the secondary housing **130**.

(34) In some embodiments, the transmission mechanism of the power tool **100** includes an impact mechanism that includes hammer with outwardly extending lugs and an anvil with outwardly extending lugs. The anvil may be coupled to the output unit **125**. During operation, impacting occurs when the anvil encounters a certain amount of resistance, e.g., when driving a fastener into a workpiece. When this resistance is met, the hammer may continue to rotate. A spring coupled to the back-side of the hammer causes the hammer to disengage the anvil by axially retreating. Once disengaged, the hammer will advance both axially and rotationally to again engage (i.e., impact) the anvil. When the impact mechanism is operated, the hammer lugs impact the anvil lugs every 180 degrees, for example. Accordingly, when the power tool **100** is impacting during operation, the hammer rotates 180 degrees without the anvil, impacts the anvil, and then rotates with the anvil a certain amount before repeating this process. For further reference on the functionality of the impact mechanism, see, for instance, the impact mechanism discussed in U.S. application Ser. No. 14/210,812, filed Mar. 14, 2014, which is herein incorporated by reference.

(35) The power tool **100** may further include a printed circuit board (PCB) **210** located in the handle **110** and a PCB **212** located in the connection portion **120**. One or both of the PCBs **210** and **212** include one or more electronic components that may implement a control system of the power tool **100**. In some embodiments, the PCB **212** includes an electronic processor configured to receive power from a power supply connected to the power tool **100** (e.g., a battery pack connected to the power tool **100** via the interface **122**). The electronic processor may be configured to control whether power is provided to the light sources and/or the motor **200**. The PCB **210** may include switching elements (e.g., field-effect transistors) that are controlled by the electronic processor to selectively provide power to coils of the motor **200** to allow operation thereof. In other embodiments, the PCBs **210** and **212** may include additional or alternative components. For example, the components located on each PCB **210** and **212** as described above may be located on the other PCB **210** and **212**.

(36) As can be seen by the cross-sectional view of FIG. 2 (and as shown in further detail in FIGS. 4A and 4B), the secondary housing **130** includes a passageway **215** (e.g., a through-hole) configured to receive one or more wires **220** that are configured to electrically connect to the LEDs to provide power to the LEDs. In some embodiments, an axis through a center of the passageway **215** may be approximately parallel with the axis **202** of the motor **200**. In some embodiments, the one or more wires **220** connect to the PCB **210** to receive power from a power supply of the power tool **100**. In some embodiments, the power supply that provides power to the LEDs via the one or more wires **220** is a battery pack configured to be connected to the interface **122** of the power tool **100**. In some embodiments, the power supply that provides power to the LEDs via the one or more wires **220** is a second power supply separate from the battery pack. For example, the second power supply is a coin cell battery or the like. In some embodiments, the second power supply is configured to provide power to the LEDs but not to the motor **200**.

(37) FIG. 3 illustrates a block diagram **300** of the power tool **100** according to one example embodiment. The power tool **100** may include a controller **305**. The controller **305** is electrically and/or communicatively connected to a variety of modules or components of the power tool **100**. For example, as illustrated by FIG. 3, the controller **305** is electrically connected to the motor **200**, a battery pack interface **122**, a trigger switch **315** (connected to the trigger **115**), one or more sensors or sensing circuits **320**, one or more indicators **325**, one or more light sources **330** (e.g., LEDs), a user input **335** (e.g., switches, buttons, a mode pad, etc.), power input circuitry **340**, and switching elements **345** (e.g., FET switches **345**). The controller **305** includes combinations of hardware and software that are operable to, among other things, control the operation of the power tool **100**, monitor the operation of the power tool **100**, activate the one or more indicators **325** and/or light sources **330** (e.g., an LED), etc.

(38) The controller **305** includes a plurality of electrical and electronic components that provide power, operational control, and protection to the components and modules within the controller **305** and/or the power tool **100**. For example, the controller **305** includes, among other things, an electronic processor **350** (e.g., a microprocessor, a microcontroller, or another suitable programmable device), a memory **355**, input units **360**, and output units **365**. The electronic processor **350** includes, among other things, a control unit **370**, an ALU **375**, and a plurality of registers **380** (shown as a group of registers in FIG. 3), and is implemented using a computer architecture (e.g., a modified Harvard architecture, a von Neumann architecture, etc.). The electronic processor **350**, the memory **355**, the input units **360**, and the output units **365**, as well as the various modules or circuits connected to the controller **305** are connected by one or more control and/or data buses (e.g., common bus **385**). The control and/or data buses are shown generally in FIG. 3 for illustrative purposes. The use of one or more control and/or data buses for the interconnection between and communication among the various modules, circuits, and components would be understood by a person skilled in the art in view of the embodiments described herein.

(39) The memory **355** is a non-transitory computer readable medium and includes, for example, a program storage area **357** and a data storage area **358**. The program storage area **357** and the data storage area **358** can include combinations of different types of memory, such as a ROM, a RAM (e.g., DRAM, SDRAM, etc.), EEPROM, flash memory, a hard disk, an SD card, or other suitable magnetic, optical, physical, or electronic memory devices. The electronic processor **350** is connected to the memory **355** and executes software instructions that are capable of being stored in a RAM of the memory **355** (e.g., during execution), a ROM of the memory **355** (e.g., on a generally permanent basis), or another non-transitory computer readable medium such as another memory or a disc. Software included in the implementation of the power tool **100** can be stored in the memory **355** of the controller **305**. The software includes, for example, firmware, one or more applications, program data, filters, rules, one or more program modules, and other executable instructions. The controller **305** is configured to retrieve from the memory **355** and execute, among

other things, instructions related to the control processes and methods described herein. In other constructions, the controller **305** includes additional, fewer, or different components.

(40) The battery pack interface **122** includes a combination of mechanical components (e.g., rails, grooves, latches, etc.) and electrical components (e.g., one or more terminals) configured to and operable for interfacing (e.g., mechanically, electrically, and communicatively connecting) the power tool **100** with a battery pack. For example, power provided by the battery pack to the power tool **100** is provided through the battery pack interface **122** to the power input circuitry **340**. The power input circuitry **340** includes combinations of active and passive components to regulate or control the power received from the battery pack prior to power being provided to the controller **305**. The battery pack interface **122** may also supply power to the FET switches **345** that are configured to selectively provide power to the motor **200** based in accordance with instructions from the controller **305**. The battery pack interface **122** also includes, for example, a communication line **390** configured to allow for communication between the controller **305** and the battery pack.

(41) The indicators **325** include, for example, one or more light-emitting diodes (“LEDs”). The indicators **325** can be configured to display conditions of, or information associated with, the power tool **100**. For example, the indicators **325** are configured to indicate measured electrical characteristics of the power tool **100**, the status of the device, etc. The user input **335** is operably coupled to the controller **305** to, for example, select a forward mode of operation or a reverse mode of operation, a torque and/or speed setting for the power tool **100** (e.g., using torque and/or speed switches or a mode pad), etc. In some embodiments, the user input **335** includes a combination of digital and analog input or output devices required to achieve a desired level of operation for the power tool **100**, such as one or more knobs, one or more dials, one or more switches, one or more buttons, a mode pad, etc.

(42) In some embodiments, the controller **305** (specifically, the electronic processor **350**) is configured to control whether power is provided to the light source(s) **330** (e.g., LEDs **610** shown in FIG. 6 of the lighting assembly **135**) via the one or more wires **220**. In some embodiments, the controller **305** may receive power from a power supply of the power tool **100** and provide power to the light source(s) **330** directly. In such embodiments, the controller **305** may condition received power as appropriate before providing power to the light source(s) **330**. In other embodiments, the light source(s) **330** may be electrically connected to the power supply (e.g., to the battery pack via the battery pack interface **122** and the one or more wires **220**) with a switch between the light source(s) **330** and the power supply. In such embodiments, the controller **305** may control the switch to allow or disallow power from be provided to the light source(s) **330**. In such embodiments, the electrical path from the power supply to the light source(s) **330** may include conditioning circuitry similar to the power input circuitry **340** to regulate or control the power received by the light source(s) **330** from the power supply. In some embodiments, the controller **305** controls the light source(s) **330** to be illuminated in response to determining that the trigger **115** has been actuated.

(43) The controller **305** may be configured to determine monitor tool conditions using the sensors **320**. For example, the controller **305** may be configured to determine whether a fault condition of the power tool **100** is present and generate one or more control signals related to the fault condition. In some embodiments, the sensors **320** include one or more current sensors, one or more speed sensors, one or more Hall Effect sensors, one or more temperature sensors, etc. The controller **305** calculates or includes, within memory **355**, predetermined operational threshold values and limits for operation of the power tool **100**. For example, when a potential thermal failure (e.g., of a FET, the motor **200**, etc.) is detected or predicted by the controller **305**, power to the motor **200** can be limited or interrupted until the potential for thermal failure is reduced. If the controller **305** detects one or more such fault conditions of the power tool **100** or determines that a fault condition of the power tool **100** no longer exists, the controller **305** is configured to provide information and/or

control signals to another component of the power tool **100** (e.g. the battery pack interface **122**, the indicators **325**, etc.). In some embodiments, the controller **305** is configured to control an output of the light source(s) **330** to indicate information to a user about a tool condition of the power tool **100** (e.g., by flashing the light source(s) **330** a predetermined number of times to indicate different types of fault conditions).

(44) FIG. **4A** illustrates a rear perspective view of the secondary housing **130** according to one example embodiment. The secondary housing **130** includes a ridge portion **400** (also referred to as a protrusion **400**) positioned on an outer peripheral surface of the secondary housing **130**. In some embodiments, the ridge portion **400** protrudes outwardly from an outer peripheral surface of the secondary housing **130**. In the embodiment shown in FIG. **4A**, the ridge portion **400** protrudes downwardly from a bottom of the outer peripheral surface of the secondary housing **130**. At least a portion of the passageway **215** is located in the ridge portion **400**. As illustrated by FIG. **4A**, the one or more wires **220** pass through the passageway **215** such that at least a portion of the one or more wires **220** is located in the passageway **215**.

(45) In some embodiments, the secondary housing **130** is ring-shaped to accommodate the output unit **125**. A cavity **405** may be formed on a rear surface **410** of the secondary housing **130**. At least a portion of the transmission mechanism **205** may be positioned within the cavity **405**. The rear surface **410** may include an opening to the cavity **405** such that the cavity **405** intersects with an interior opening of the primary housing **105**. In some embodiments, the passageway **215** may include a first end **412** at a front end of the secondary housing **130** and a second end **413** at a rear end of the secondary housing **130**. In these embodiments, the second end **413** may be open to the interior opening of the primary housing **105** to allow the one or more wires **220** to enter the primary housing **105** to be electrically connected to a power supply (e.g., a battery pack connected to the power tool **100**). For example, upon exiting the passageway **215** and extending rearwardly beyond the rear of the secondary housing **130**, the one or more wires **220** may extend downwardly past the trigger switch **315** to connect to the PCB **210** and/or the PCB **212**.

(46) FIG. **4B** illustrates a front perspective view of the secondary housing **130** according to one example embodiment. As illustrated by the front perspective view, the passageway **215** continues along the length of the ridge portion **400** so that the one or more wires **220** may be located along the length of the secondary housing **130**. The secondary housing **130** further includes a front surface **415** including a positioning block **420** for positioning the retaining portion **135**. The secondary housing **130** further includes at least one mounting lug **425** configured to receive a fastener to at least partially secure the secondary housing **130** to the primary housing **105**. In some embodiments, the fastener is configured to be inserted through a first hole in a first clamshell housing portion of the primary housing **105**, then through a second hole in the mounting lug **425**, and then through a third hole in a second clamshell housing portion of the primary housing **105** to at least partially secure the two clamshell housing portions and the secondary housing **130** together. As shown in FIG. **4B**, the mounting lug **425** may protrude (e.g., downwardly) from the ridge portion/protrusion **400**.

(47) The secondary housing **130** further includes a neck portion **430** protruding forwardly from the front surface **415**. The neck portion **430** may include one or more grooves **435** configured to receive a retention ring **518** (see FIG. **5E**). Only a single groove **435** is shown in the embodiment illustrated in FIG. **4B**. The combination of the retention ring **518** and the groove **435** may securely hold the retaining portion **135** on the front surface **415** of the secondary housing **130** as explained in greater detail below with respect to FIG. **5E**.

(48) FIG. **5A** illustrates a rear perspective view of the retaining portion/lighting assembly **135**. FIG. **5B** illustrates a front perspective view of the retaining portion **135**/lighting assembly **135**. The retaining portion **135** includes an extension portion **500** protruding (e.g., downwardly) from an outer peripheral surface of the retaining portion **135**. The extension portion **500** may generally align with the ridge portion **400** of the secondary housing **130**. In some embodiments, the

passageway **215** of the secondary housing **130** may align with an exterior opening **502** in the extension portion **500**. Additionally, the retaining portion **135** may include an interior opening **503** on a bottom of an inner surface of a cavity **504** of the retaining portion **135**. In some embodiments, the one or more wires **220** pass through the passageway **215** of the secondary housing **130**, through the exterior opening **502** of the extension portion **500** of the retaining portion **135**, and then through the interior opening **503** of the retaining portion **135** to connect to a PCB **605** located in the cavity **504** of the retaining portion **135**. In some embodiments, an LED **610** is located on the PCB **605** and receives power from the one or more wires **220** (see FIG. 6).

(49) In some embodiments, the retaining portion **135** includes two main elements: an inner portion **505** (i.e., a light holding device **505**) as shown in FIG. 5D and an outer portion **520** (i.e., a cover **520**) as shown in FIG. 5C. In some embodiments, the cover **520** is made of rubber or plastic and is overmolded onto the light holding device **505**. The light holding device **505** may be made of a transparent material, such as a clear plastic, resin, or the like. In some embodiments, the lenses **140** are integral with the light holding device **505**. In other words, the light holding device **505** may be made from a single transparent mold that includes multiple lenses **140** so as to prevent separate lenses from needing to be installed within, for example, openings in an opaque light holding device. Using such a single-piece transparent mold for the light holding device **505** simplifies the manufacturing and assembly process of the lighting system for the power tool **100**. In some embodiments, each of the lenses **140** protrude axially from a front surface of the light holding device **505** through a respective opening in the cover **520** (see FIG. 5B). In some embodiments, the lenses **140** protrude to be approximately flush with a front surface of the cover **520** (see FIG. 5B). In other embodiments, the lenses **140** protrude forward beyond the front surface of the cover **520**.

(50) As illustrated in FIGS. 5B and 5C, the cover **520** of the retaining portion **135** includes three openings **525** to allow a first light source **610A** behind lens **140A**, a second light source **610B** behind lens **140B**, and a third light source **610C** behind lens **140C** to emit light through the cover **520**. In some embodiments, the cover **520** prevents light from being emitted through the light holding device **505** in all areas except for through the lenses **140**. In other words, the cover **520** may be opaque to prevent light from being emitted through portions of the transparent light holding device **505** except through the lenses **140**.

(51) While the retaining portion **135** is shown and described as having two main components (i.e., the light holding device **505** and the cover **520**), in other embodiments, these components are combined into a single component. In some of such embodiments, the single-piece retaining portion **135** may be opaque and may include openings configured to receive separate lenses that allow light to be emitted through the openings and the lenses.

(52) As shown in FIG. 5D, the light holding device **505** may include three indentations **530** that are each configured to provide room for a light source (e.g., an LED **610** as shown in FIG. 6) to protrude into the indentation **530**. One indentation **530** may be located behind each lens **140** and/or may form part of each lens **140**. The light holding device **505** may also include one or more radially protruding portions **515** that protrude radially toward the output unit **125** and the output axis **202** from an edge of a central opening **517** of the light holding device **505**. The one or more radially protruding portions **515** may be configured to secure the retaining portion **135** to the secondary housing **130** (e.g., snap fit to the secondary housing **130**) using the retention ring **518** and the groove **435** of the neck portion **430** of the secondary housing **130**. For example, protruding portions **519** of the retention ring **518** may be configured to be respectively received in a groove between a radially protruding portion **515** and a rear surface of an edge of the central opening **517** of the light holding device **505**.

(53) FIG. 5E illustrates the retention ring **518** according to one example embodiment. In some embodiments, the retention ring **518** is approximately circular and may be a fully enclosed ring or a partially enclosed ring as shown in FIG. 5E. The retention ring **518** may include protruding portions **519** that protrude radially away from the output unit **125** and the output axis **202**. In some

embodiments, a majority of the retention ring **518** is located within the groove **435** of the neck portion **430** of the secondary housing **130**. However, the protruding portions **519** may protrude outside of the groove **435** to engage with corresponding radially protruding portions **515** of the light holding device **505** to hold/secure (e.g., snap fit) the light holding device **505** to the secondary housing **130**.

(54) Referring back to FIGS. **5A** and **5D**, in some embodiments, the light holding device **505** includes a positioning gap **510** configured to mate with the positioning block **420** of the secondary housing **130** to properly align the secondary housing **130** and the retaining portion **135**. The retaining portion **135** further includes a lighting system **600**. The lighting system **600** may be positioned within the cavity **504** of the light holding device **505** such that the lighting system **600** can be mounted to a front end of the power tool **100** and electrically connected to a power supply of the power tool **100** via the one or more wires **220**. In some embodiments, the one or more wires **220** terminate within the retaining portion **135**, in particular, by connecting to the lighting system **600** as explained below with respect to FIG. **6**.

(55) FIG. **6** illustrates a front view of the lighting system **600** according to one example embodiment. The lighting system **600** includes a first PCB **605A** including a first LED **610A**, a second PCB **605B** including a second LED **610B**, and a third PCB **605C** including a third LED **610C**. In alternate embodiments, the first PCB **605A**, the second PCB **605B**, and the third PCB **605C** may be formed as a single annular ring-shaped or substantially ring-shaped PCB. The first LED **610A**, the second LED **610B**, and the third LED **610C** may be positioned such that light emitted by the first LED **610A**, the second LED **610B**, and the third LED **610C** is emitted through a respective lens **140A**, **140B**, **140C** of the transparent light holding device **505**. In the embodiment shown, two wires **220** are respectively coupled to each of a first electrical connection junction **615** (e.g., a first soldering point) and a second electrical connection junction **620** (e.g., a second soldering point). Additional wires **622** may electrically connect the second PCB **605B** to the first PCB **605A**, and additional wires **625** may electrically connect the first PCB **605A** to the third PCB **605C**. Through the wires **220**, **622**, and **625** the first PCB **605A**, the second PCB **605B**, and the third PCB **605C** may all receive power from the power supply and/or control signals from the controller **305**. In some embodiments, the lighting system **600** includes additional or fewer PCBs **605** and/or LEDs **610**. In some embodiments, the PCBs **605** and/or LEDs **610** may be arranged in different locations around the output axis **202**. In some embodiments, the light source(s) **330** described above with respect to FIG. **3** include the LEDs **610**.

(56) FIG. **7** illustrates a method **700** for manufacturing a power tool (for example, the power tool **100**) including a lighting system (for example, a shadowless lighting system **600**). The method **700** includes, at block **705**, providing a primary housing (e.g., the primary housing **105**). The primary housing **105** may include an interior portion configured to hold various components of the power tool. At block **710**, the method **700** also includes situating a motor within the primary housing **105**. In some embodiments, the motor is the BLDC motor **200** described previously herein. At block **715**, the method **700** also includes providing a secondary housing (e.g., the secondary housing **130**). In some embodiments, the secondary housing **130** is formed from metal as described previously herein. In some embodiments, the secondary housing includes the protrusion **400** protruding downwardly from a bottom of an outer peripheral surface of the secondary housing **130** as described previously herein. At block **720**, the method **700** also includes situating a transmission device (e.g., transmission device **205**) within the secondary housing **130**. The transmission device **205** may be configured to transfer rotational energy between the motor **200** and an output unit **125** of the power tool **100** as described previously herein. In some embodiments, at least a portion of the transmission device **205** is situated within the secondary housing **130**. The secondary housing **130** may include a passageway **215** as described previously herein. At block **725**, the method **700** also includes mounting a light source (e.g., one or more LEDs **610** that may be mounted in a retaining portion **135**) to a front end of the secondary housing **130**. The light source may be a

shadowless lighting system **600** as described previously herein.

(57) At block **730**, the method **700** also includes inserting one or more wires (e.g., wires **220**) configured to be electrically connected to the light source **610** through the passageway **215** such that at least a portion of the one or more wires **220** is located in the passageway **215**. The passageway **215** may begin at the interior portion of the primary housing **105** and terminate at a front end of the secondary housing **130**. In some embodiments, at least part of the passageway **215** is located in the protrusion **400** of the secondary housing **130**. The passageway **215** may include a first end **412** at the front end of the secondary housing **130** and a second end **413** at a rear end of the secondary housing **130**. In some embodiments, inserting the one or more wires **220** through the passageway **215** includes opening the second end **413** to an interior of the primary housing **105**, routing the one or more wires **220** through the primary housing **105**, and electrically connecting the one or more wires **220** to a power supply.

(58) FIG. **8** illustrates a power tool **800** that includes many similar features as the power tool **100** of FIGS. **1-6** and some different features than the power tool **100** of FIGS. **1-6**. For the sake of brevity, many of the similar features will not be explained in detail. Rather, the primary differences between the power tool **100** and the power tool **800** are described in detail below. Features of the power tool **800** that correspond to features of the power tool **100** of FIGS. **1-6** are labeled with either an identical reference number (e.g., trigger switch **315**) or a reference number that is increased by 700 (e.g., trigger **115** of the power tool **100** may be similar to trigger **815** of the power tool **800**). In some embodiments, the features described below with respect to the power tool **800** may be implemented on corresponding parts of the power tool **100** (e.g., light cover **520** may be overlapped with groove/shoulders in the secondary housing **130** to prevent light bleeding as described below with respect to the power tool **800**). Similarly, in some embodiments, the features described previously herein with respect to the power tool **100** may be implemented on corresponding parts of the power tool **800**. In some embodiments, the block diagram **300** of FIG. **3** may be representative of the elements of the power tool **800**, and the functionality of the power tool **100** as explained previously herein may also apply to the power tool **800**.

(59) In some embodiments, the power tool **800** of FIG. **8** includes a primary housing **805** and a secondary housing **830** (e.g., a hammer case, a gear case, or the like). The power tool **800** may also include a retaining portion **835** configured to retain one or more light sources **610** of the power tool **800**.

(60) FIG. **9A** illustrates a side view of the power tool **800** of FIG. **8** with one half of a clamshell housing removed, with a potting boat of the PCB **910** removed, and with the retaining portion **835** removed. In FIGS. **9A-9C**, features of the power tool **800** that correspond to features of the power tool **100** of FIGS. **1-6** are labeled with a reference number that is increased by 700 (e.g., motor **200** of the power tool **100** may be similar to motor **900** of the power tool **800**). In some embodiments, LED power wires **922** may be similar to LED power wires **220**. As shown in FIG. **9A**, in some embodiments, the secondary housing **830** may not have a passageway **215** configured to house the one or more wires **922** that provide power to the light sources **610**. Similarly, the retaining portion **835** may not include openings **502**, **503** configured to received the one or more LED power wires **922**. Rather, as shown in FIG. **9A**, one or more wires **922** electrically connected to the light source **610** are routed along an outer peripheral side of the secondary housing **830** until the one or more wires **922** pass a rear end of the secondary housing **830** at which point the one or more wires **922** are routed downwardly toward a handle **810** of the power tool **800**.

(61) When looking at the front of the power tool **800**, the one or more wires **922** shown in FIG. **9A** run along a right outer peripheral side of the secondary housing **830** at approximately a three o'clock position. In some embodiments, the one or more wires **922** may alternatively run along a left outer peripheral side of the secondary housing **830** at approximately a nine o'clock position. In some embodiments, the one or more wires **922** may run along an outer peripheral surface of the secondary housing **830** at any location above the three o'clock position and the nine o'clock

position. In some of any of the these embodiments, the one or more wires **922** may not be routed downwardly toward the handle **810** until the one or more wires pass the rear end of the secondary housing **830**.

(62) In some embodiments, the retaining portion **835** includes wings **850** (see FIGS. **8** and **13A**) that protrude axially rearward from a main portion **855** of the retaining portion **835** toward a rear of the secondary housing **830** along an outer peripheral side surface of the secondary housing **830**. In some embodiments, a circular/partially cylindrical portion of the retaining portion **835** in which the light sources **610** are mounted may be considered the main portion **855** of the retaining portion **835** from which the wings **850** extend. In some embodiments, one of the wings **850** extends over the top of the one or more wires **922** as they run along the outer peripheral side of the secondary housing **830** to protect the one or more wires **922** (e.g., from debris, tampering, etc.). In some embodiments, the wing **850** that extends over the top of the one or more wires **922** may not support the one or more wires **922**. Rather, the outer peripheral side of the secondary housing **830** may include one or more first wire guides **950** in which the one or more wires **922** is configured to be friction fit (see FIG. **9A**). Additionally or alternatively, an interior surface of the primary housing **805** (e.g., an interior surface of a part of the clamshell housing) may include a second wire guide **955** in which the one or more wires **922** is configured to be friction fit (see FIG. **9B**). In some embodiments, the second wire guide **955** is rearward of the secondary housing **830** in a direction along the output axis **902** (see FIG. **9B**). In some embodiments, the interior surface of the primary housing **805** includes an additional or alternative second wire guide **955** that is adjacent to the outer peripheral side of the secondary housing **830**. As shown in FIG. **9B**, the second wire guides **955** may route the one or more wires **922** rearwardly in a direction that is approximately parallel to the output axis **902** and/or downwardly toward the handle **810** in a direction that is approximately perpendicular to the output axis **902**.

(63) In some embodiments, the one or more wires **922** connect to a power supply as explained previously herein with respect to the one or more wires **220**.

(64) FIG. **9C** illustrates a cross-sectional view of a front portion of the power tool **800**. As shown in FIG. **9C**, the retaining portion **835** may include an inner portion/light holding device **905** and an outer portion/cover **920** that are respectively similar to the inner portion/light holding device **505** and the outer portion/cover **520** described previously herein with the exception of the differences explained below. In some embodiments, the secondary housing **830** and the cover **920** include areas of overlap **960**, **965** to prevent/reduce light bleeding that may occur when a flat rear end of a cover merely abuts a flat front surface of the secondary housing. In other words, when flat surfaces of the cover and the secondary housing merely abut each other, light from the light sources **610** may bleed/leak out from a small opening between the cover and the secondary housing. Such light bleeding/leaking reduces the amount of light that is emitted forward toward a work area and may give a user a perception that the power tool was poorly designed/assembled. Accordingly, there is a problem with existing methods of mounting a light retaining portion on a secondary housing of a power tool.

(65) The power tool **800** addresses this problem by using a secondary housing **830** that includes a first groove **1055** on a front surface **1015** of the secondary housing **830** (see FIGS. **10B**, **12B**, and **13B**). The first groove **1055** may be configured to receive a rearwardly protruding part **1205** of the cover **920** that protrudes rearwardly further than the main portion **855** of the light holding device **905** (see FIGS. **12A** and **13A**). For example, the rearwardly protruding part **1205** protrudes rearwardly in the same direction as the wings **850** but may be included on the approximately half-circle-shaped portions of the main portion **855** of the retaining portion **835** (see FIG. **13A**). In some embodiments, the protruding part **1205** continues along the wings **850** (see FIGS. **12A** and **13A**) and is configured to fit in a continued portion of the first groove **1055** that continues rearwardly on an outer peripheral side of the secondary housing **830** (see FIG. **10B**). In some embodiments, the combination of the first groove **1055** and the protruding part **1205** create the areas of overlap **960**

as shown in FIG. 9C to prevent/reduce light bleeding/leaking between the cover **920** and the secondary housing **830** in a radial direction perpendicular to the output axis **902**.

(66) The power tool **800** may further address the light bleeding/leaking problem described above by using a secondary housing **830** that includes a neck portion **1030** that includes a shoulder **1050** on an outer peripheral surface of the neck portion **1030** (see FIGS. **10B** and **11B**). The shoulder **1050** may be configured to receive an overhanging part **1105** of the cover **920** that protrudes radially closer to an output axis **902** of the output unit **825** than a front surface of the light holding device **905** (see FIG. **11A**). As shown in FIG. **11B**, in some embodiments, the shoulder **1050** includes a groove/indent toward the output axis **902** at a front end of the neck portion **1030** of the secondary housing **830**. Although FIGS. **11A** and **11B** show only a portion of the cover **920** and the secondary housing **830**, in some embodiments, the overhanging part **1105** of the cover **920** and the shoulder **1050** of the secondary housing **830** are fully circular. In some embodiments, the combination of the overhanging part **1105** and the shoulder **1050** create the areas of overlap **965** as shown in FIG. **9C** to prevent/reduce light bleeding/leaking between the cover **920** and the secondary housing **830** in a forward direction parallel to the output axis **902**.

(67) FIGS. **14A** and **14B** illustrate perspective views of the retaining portion **835** and the secondary housing **830** with portions of each that are involved in securing the retaining portion **835** to the secondary housing **830** highlighted. In some embodiments, the power tool **800** includes a retention ring **1518** (see FIG. **15**) located in a second groove **1035** in the secondary housing **830** (e.g., on an outer peripheral surface of the neck portion **1030** of the secondary housing **830**). In some embodiments, the second groove **1035** is similar to the groove **435** explained previously herein with respect to the power tool **100** except that the second groove **1035** is discontinued at approximately the twelve o'clock position instead of being discontinued as approximately the three o'clock position. In some embodiments, the light holding device **905** includes two first protruding portions **1405** and **1410** that protrude radially toward the output axis **902**. In some embodiments, the protruding portion **1410** is similar to the protruding portion **515** described previously herein with respect to the power tool **100**. Although FIG. **14A** shows a single protruding portion **1410**, another protruding portion **1410** may be symmetrically located on an opposite side of the inner surface of the light holding device **905** to receive the symmetrical protruding portions **1519** of the retention ring **1518** (see FIG. **15**). The protruding portion **1405** may be a fully circular protrusion in some embodiments.

(68) In some embodiments, the retention ring **1518** includes two second protruding portions **1519** that protrude radially away from the output axis **902** (and out of the second groove **1035**) and that respectively engage with the two first protruding portions **1405**, **1410** of the light holding device **905** to secure the light holding device **905** to the secondary housing **830** (see FIG. **15**). In some embodiments, the second protruding portions **1519** protrude in opposite directions than each other and are approximately symmetrical to each other about a plane that passes through the output axis **902**. In some embodiments, the retention ring **1518** is similar to the retention ring **518** described previously herein with respect to the power tool **100** except that one of the second protruding portions **1519** protrudes leftward and the other of the second protruding portions **1519** protrudes rightward instead of protruding upward and downward as in the power tool **100**. In some embodiments, due to the shapes of the retention ring **518**, **1518**, the groove **435**, **1035**, and the protruding portions **515**, **1405**, **1410**, the retention ring **518**, **1518** is hidden from the view of a user when the retaining portion **135**, **835** is secured to the secondary housing **830**.

(69) In some embodiments, the second groove **1035** is less than 365 degrees around the neck portion **1030** of the secondary housing **830**. For example, as shown in FIG. **14B**, the second groove **1035** is discontinued at the twelve o'clock position such the second groove **435** does not form a complete circle around the neck portion **1030**. In some embodiments, the retention ring **1518** is a partially enclosed ring that is not a fully enclosed ring (see FIG. **15**). In some embodiments, the second groove **1035** forms a complete circle around the neck portion **1030**. In some embodiments,

the retention ring **1518** is a fully enclosed ring.

(70) In some embodiments, the second groove **1035** used to retain the retention ring **1518** may be located in a different location on the secondary housing **830** than described previously herein.

FIGS. **16A** and **16B** illustrate cross-sectional views of a front portion of the power tool **800** with the second groove **1035** in different locations. In FIG. **16A**, the second groove **1035** is located on an outer peripheral surface of the neck portion **1030** of the secondary housing **830** similar to the second groove **1035** shown in FIG. **14B**. In FIG. **16B**, the second groove **1035** is located on an outer peripheral surface of a forward axially protruding front face **1605** of the secondary housing **830**. These alternate locations similarly apply to the groove **435** of the power tool **100**.

(71) Thus, embodiments described herein provide a power tool including a lighting system, and more specifically, a shadowless lighting system. Various features and advantages are set forth in the following claims.

Claims

1. A power tool comprising: a primary housing; a motor situated within the primary housing; a transmission mechanism configured to transmit rotational energy from the motor to an output unit of the power tool; a secondary housing in which at least a portion of the transmission mechanism is located, the secondary housing including an outer peripheral surface and a protrusion protruding outwardly from the outer peripheral surface; a light holding device mounted to a front end of the secondary housing and configured to cover a portion of the secondary housing; a light source configured to be held by the light holding device; a passageway through the secondary housing, wherein at least part of the passageway is located in the protrusion; and one or more wires electrically connected to the light source, the one or more wires extending through the passageway and into an interior of the primary housing.
2. The power tool of claim 1, wherein the protrusion protrudes downwardly from a bottom of the outer peripheral surface of the secondary housing.
3. The power tool of claim 2, wherein the secondary housing includes a mounting lug configured to receive a fastener to at least partially secure the primary housing to the secondary housing; and wherein the mounting lug protrudes from the protrusion.
4. The power tool of claim 1, wherein an axis through a center of the passageway is approximately parallel with an axis of the motor; and wherein the secondary housing includes one of a hammer case and a gear case.
5. The power tool of claim 1, wherein the light source includes a plurality of LEDs arranged about an output axis about which the output unit of the power tool rotates.
6. The power tool of claim 1, wherein the passageway includes a first end at a front surface of the secondary housing and a second end at a rear end of the secondary housing; and wherein the one or more wires extend forward beyond the front surface of the secondary housing to electrically connect to the light source.
7. The power tool of claim 1, wherein at least a portion of a length of the passageway is fully enclosed around an axis through a center of the passageway.
8. The power tool of claim 1, wherein a first portion of the passageway at the front end of the secondary housing is fully enclosed around an axis through a center of the passageway, and wherein a second portion of the passageway rearward of the first portion is not fully enclosed around the axis through the center of the passageway.
9. The power tool of claim 1, wherein the passageway includes a through-hole that passes through a front surface of the secondary housing.
10. A power tool comprising: a primary housing; a motor situated within the primary housing; a transmission mechanism configured to transmit rotational energy from the motor to an output unit of the power tool; a secondary housing configured to house the transmission mechanism; a light

holding device mounted to a front end of the secondary housing and configured to over a portion of the secondary housing; a light source configured to be held by the light holding device; a through-hole through a front surface of the secondary housing; and one or more wires electrically connected to the light source, the one or more wires extending through the through-hole to an interior of the primary housing to be electrically connected to a power supply of the power tool, wherein the one or more wires extend forward beyond the front surface of the secondary housing to electrically connect to the light source.

11. The power tool of claim 10, wherein the secondary housing includes an outer peripheral surface and a protrusion protruding outwardly from the outer peripheral surface; and wherein at least part of the through-hole is located in the protrusion.

12. The power tool of claim 10, wherein the through-hole includes a first end at the front end of the secondary housing and a second end at a rear end of the secondary housing.

13. The power tool of claim 10, wherein at least a portion of a length of the through-hole is fully enclosed around an axis through a center of the through-hole.

14. The power tool of claim 10, wherein a first portion of the through-hole at the front end of the secondary housing is fully enclosed around an axis through a center of the through-hole, and wherein a second portion of the through-hole rearward of the first portion is not fully enclosed around the axis through the center of the through-hole.

15. A power tool comprising: a primary housing; a motor situated within the primary housing; a transmission mechanism configured to transmit rotational energy from the motor to an output unit of the power tool; a secondary housing configured to house the transmission mechanism; a light holding device mounted to a front end of the secondary housing; a light source configured to be held by the light holding device; and a cover configured to cover at least a portion of a front surface of the light holding device; the device is made of a material to provide a lens that is integral with the light holding device; wherein the light holding device is made of a transparent material to provide a lens that is integral with the light holding device; wherein the cover is made of an opaque material and is configured to prevent light from being emitted through the light holding device except for through the lens, wherein the secondary housing includes a first groove on a front surface of the secondary housing, the first groove configured to receive a rearwardly protruding part of the cover that protrudes further rearward than a main portion of the light holding device; and wherein the secondary housing includes a neck portion that includes a shoulder on an outer peripheral surface of the neck portion, the shoulder configured to receive an overhanging part of the cover that protrudes radially closer to an output axis of the output unit than the front surface of the light holding device.

16. The power tool of claim 15, further comprising a retention ring located in a second groove in the secondary housing; wherein the light holding device includes two first protruding portions that protrude radially toward the output axis; and wherein the retention ring includes two second protruding portions that protrude radially away from the output axis and that respectively engage with the two first protruding portions of the light holding device to secure the light holding device to the secondary housing.

17. The power tool of claim 16, wherein the second groove is less than 360 degrees around the neck portion of the secondary housing; and wherein the retention ring is a partially enclosed ring that is not a fully enclosed ring.

18. The power tool of claim 16, wherein the second groove is located on one of the outer peripheral surface of the neck portion of the secondary housing and an outer peripheral surface of a front face of the secondary housing.

19. The power tool of claim 16, wherein the second protruding portions protrude in opposite directions than each other and are approximately symmetrical to each other about a plane that passes through the output axis.

20. The power tool of claim 15, further comprising a through-hole through the secondary housing, wherein one or more wires electrically connected to the light source pass through the through-hole.

