

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411525
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Wang; Xinyu et al.

Support structure and display device

Abstract

Provided is a support structure. The support structure includes: a rotation shaft, two slidable connection mechanisms, at least two chains, and a first support assembly. The two slidable connection mechanisms are rotatably connected to the rotation shaft and disposed on two sides of the rotation shaft; the at least two chains are spaced apart in an axial direction of the rotation shaft, extension directions of the at least two chains are perpendicular to the axial direction of the rotation shaft, middle portions of the at least two chains are connected to the rotation shaft, and two ends of each of the at least two chains are respectively connected to the two slidable connection mechanisms; and in the axial direction of the rotation shaft, each of the at least one first support assembly is connected between two adjacent chains of the at least two chains.

Inventors:	Wang; Xinyu (Beijing, CN), Zhou; Yonghong (Beijing, CN), Chu; Shangchieh (Beijing, CN), Xu; Linlin (Beijing, CN)
Applicant:	BOE Technology Group Co., Ltd. (Beijing, CN)
Family ID:	86158979
Assignee:	BOE TECHNOLOGY GROUP CO., LTD. (Beijing, CN)
Appl. No.:	17/921231
Filed (or PCT Filed):	October 25, 2021
PCT No.:	PCT/CN2021/126217
PCT Pub. No.:	WO2023/070289
PCT Pub. Date:	May 04, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240219967 A1	Jul. 04, 2024

Publication Classification

Int. Cl.: G06F1/16 (20060101)

U.S. Cl.:

CPC **G06F1/1656** (20130101); **G06F1/1616** (20130101); **G06F1/1624** (20130101);
G06F1/1652 (20130101);

Field of Classification Search

CPC: G06F (1/1656); G06F (1/1616); G06F (1/1624); G06F (1/1652); G06F (1/1681); F16C
(11/04); G09F (9/30)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8720011	12/2013	Hsu	16/354	G06F 1/1681
9625947	12/2016	Lee	N/A	G06F 1/1616
9786207	12/2016	Kim et al.	N/A	N/A
10032391	12/2017	Kim et al.	N/A	N/A
10162389	12/2017	Tazbaz	N/A	H04M 1/022
10174534	12/2018	Tazbaz	N/A	G06F 1/1616
10429896	12/2018	Kuramochi	N/A	G06F 1/1681
10627867	12/2019	Cheng et al.	N/A	N/A
10834814	12/2019	Cho et al.	N/A	N/A
10847735	12/2019	Seo	N/A	N/A
11048305	12/2020	Ye et al.	N/A	N/A
11408214	12/2021	Hsu	N/A	H04M 1/022
11503728	12/2021	Sun	N/A	H05K 5/0226
11630491	12/2022	Huang	361/679.01	G06F 1/1616
11644873	12/2022	Hsu	361/679.27	G06F 1/1681
11720152	12/2022	Hsu	16/354	G06F 1/1681
11720153	12/2022	Hsu	16/250	G06F 1/1681
11812568	12/2022	Xie	N/A	H05K 5/0226
12032417	12/2023	Park	N/A	H04M 1/022
2014/0245569	12/2013	Cho	16/370	E05D 3/122
2017/0061836	12/2016	Kim et al.	N/A	N/A
2017/0365197	12/2016	Kim et al.	N/A	N/A
2018/0242446	12/2017	Cho et al.	N/A	N/A
2019/0179373	12/2018	Cheng et al.	N/A	N/A
2019/0196541	12/2018	O'Neil	N/A	G06F 1/1652
2020/0212325	12/2019	Seo	N/A	N/A
2020/0323091	12/2019	Nagai	N/A	H04M 1/022
2020/0409422	12/2019	Wang	N/A	F16C 11/045
2021/0011514	12/2020	Wang	N/A	G06F 1/1681
2021/0011527	12/2020	Alva et al.	N/A	N/A

2021/0059059	12/2020	Pai	N/A	G06F 1/1681
2021/0223826	12/2020	Ye et al.	N/A	N/A
2022/0039277	12/2021	Shen	N/A	G06F 1/1681
2022/0276675	12/2021	Hou	N/A	G06F 1/1652
2022/0321683	12/2021	Luo et al.	N/A	N/A
2023/0031086	12/2022	Hung	N/A	H05K 5/0226

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
205847346	12/2015	CN	N/A
106486018	12/2016	CN	N/A
207399685	12/2017	CN	N/A
108508967	12/2017	CN	N/A
108738258	12/2017	CN	N/A
109686261	12/2018	CN	N/A
208734715	12/2018	CN	N/A
110445913	12/2018	CN	N/A
209731335	12/2018	CN	N/A
111147630	12/2019	CN	N/A
111383533	12/2019	CN	N/A
111837089	12/2019	CN	N/A
112228445	12/2020	CN	N/A
112696426	12/2020	CN	N/A

Primary Examiner: Chowdhury; Rockshana D

Attorney, Agent or Firm: XSENSUS LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application is a U.S. national stage of international application No. PCT/CN2021/126217, filed on Oct. 25, 2021, the content which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

(2) The present disclosure relates to the field of display, and in particular, relates to a support structure and a display device.

BACKGROUND

(3) A bendable display device is widely used in the field of display, and a user adjusts a size of a screen of the bendable display device by bending the bendable display device as actual requirements. The bendable display device includes a flexible display panel and a support structure, and the support structure is configured to support the flexible display panel.

SUMMARY

(4) Embodiments of the present disclosure provide a support structure and a display device. The technical solutions are as follows.

(5) According to some embodiments of the present disclosure, a support structure is provided. The support structure is configured to support a flexible display panel. The support structure includes: a rotation shaft; two slidable connection mechanisms, wherein the two slidable connection mechanisms are rotatably connected to the rotation shaft, disposed on two sides of the rotation shaft, and configured to support an unbendable display region of the flexible display panel; at least

two chains, wherein the at least two chains are spaced apart in an axial direction of the rotation shaft, extension directions of the at least two chains are perpendicular to the axial direction of the rotation shaft, middle portions of the at least two chains are connected to the rotation shaft, and two ends of each of the at least two chains are respectively connected to the two slidable connection mechanisms; and at least one first support assembly, wherein in the axial direction of the rotation shaft, each of the at least one first support assembly is connected between two adjacent chains of the at least two chains, and a surface, distal from the rotation shaft, of the first support assembly and a surface, distal from the rotation shaft, of the chain are configured to support a bendable display region of the flexible display panel.

(6) In some embodiments, the first support assembly includes a plurality of first supports juxtaposed in the extension direction of the chain, wherein any two adjacent first supports of the plurality of first supports are rotatably connected, and a rotation centerline is parallel to the axial direction of the rotation shaft.

(7) In some embodiments, in the any two adjacent first supports of the plurality of first supports, an outer sidewall, facing towards the other first support, of one first support includes a first recess, and the other first support includes a first protrusion disposed in the first recess, wherein the first protrusion is rotatably connected to the first recess.

(8) In some embodiments, the support structure further includes: a first connection pin, wherein a middle portion of the first connection pin is fixedly connected to the chain, and one end of the first connection pin is fixedly connected to an end portion of the first support.

(9) In some embodiments, the support structure further includes: two second support assemblies, wherein in the axial direction of the rotation shaft, each of the at least two chains is disposed between the two second support assemblies, an end of one of the two second support assemblies is connected to a side face of one, proximal to one end of the rotation shaft, of the at least two chains, and an end of the other of the two second support assemblies is connected to a side face of one, proximal to the other end of the rotation shaft, of the at least two chains, wherein the side face of the chain is a face, facing towards an end portion of proximal rotation shaft, of the chain.

(10) In some embodiments, the second support assembly includes two pairs of supports, wherein the two pairs of supports are spaced apart in the extension direction of the chain, each of the two pairs of supports includes two second supports juxtaposed in the extension direction of the chain, and one end portion of each of the two second supports is connected to the side face of the chain; and outer sidewalls of the two second supports include second protrusions, wherein the outer sidewalls of the two second supports including the second protrusions are opposite to each other, and the second protrusions of the two second supports are rotatably connected.

(11) In some embodiments, the two slidable connection mechanisms include: at least two rotation plates respectively disposed on the two sides of the rotation shaft and rotatably connected to the rotation shaft; and at least one pair of shift plates, wherein each of the at least one pair of shift plates includes two spaced-apart shift plates, and different pairs of shift plates are spaced apart in the axial direction of the rotation shaft; wherein any one of the at least two rotation plates is opposite to one shift plate, the shift plate is slidably connected to an opposite rotation plate, and a slide direction of the shift plate is perpendicular to the axial direction of the rotation shaft.

(12) In some embodiments, the support structure further includes: a limit assembly, wherein the limit assembly is disposed between two shift plates of one pair of shift plates, one end of the limit assembly is abutted against a side face of at least one of the at least two rotation plates, and a middle portion of the limit assembly is fixedly connected to the rotation shaft; an end face of the other end of the limit assembly includes a plurality of first limit protrusions, wherein the plurality of first limit protrusions are circumferentially spaced apart, and a first limit recess is formed between two adjacent first limit protrusions; and a side face of the rotation plate abutted against the other end of the limit assembly includes a plurality of second limit protrusions, wherein the plurality of second limit protrusions are circumferentially spaced apart, a second limit recess is

formed between two adjacent second limit protrusions, and a centerline of the rotation shaft connected to the rotation plate and a centerline of a circumference of the plurality of second limit protrusions are collinear; wherein the first limit protrusion is disposed in the second limit recess, and the second limit protrusion is disposed in the first limit recess, or the first limit protrusion is abutted against the second limit protrusion.

(13) In some embodiments, the limit assembly includes: a first stopper, wherein the first limit protrusion is disposed on one end face, facing towards the rotation plate, of the first stopper; a second stopper spaced apart from the first stopper in the axial direction of the rotation shaft; an elastic member, wherein one end of the elastic member is connected to the other end face of the first stopper, and the other end of the elastic member is connected to one end face of the second stopper; and a mounting block connected to the other end face of the second stopper and fixedly connected to the rotation shaft.

(14) In some embodiments, the support structure further includes: a wrap assembly extending in the axial direction of the rotation shaft; and a rotation shaft connection block fixedly connected to a middle portion of the wrap assembly and including a first rotation shaft through hole for the rotation shaft passing through; wherein in a third direction, the limit assembly is disposed between the first support assembly and the wrap assembly, the third direction is perpendicular to the axial direction of the rotation shaft and the extension direction of the chain, and the wrap assembly is connected to the limit assembly.

(15) In some embodiments, the wrap assembly includes: a middle wrap plate extending in the axial direction of the rotation shaft, wherein the rotation shaft connection block is connected to a surface of the middle wrap plate; two rotation wrap plates extending in the axial direction of the rotation shaft, wherein in the extension direction of the chain, the two rotation wrap plates are respectively disposed on two sides of the middle wrap plate, and the two rotation wrap plates are rotatably connected to the middle wrap plate respectively; and a fixing protrusion connected to the surface of the middle wrap plate, wherein the rotation shaft connection block and the fixing protrusion are connected to the same surface of the middle wrap plate, and the fixing protrusion includes a first fixing boss; wherein the mounting block includes a fixed recess, and the first fixing boss is disposed in the fixing recess.

(16) In some embodiments, the wrap assembly further includes: four shield blocks, wherein two of the four shield blocks are arranged in the axial direction of the rotation shaft and are respectively connected to two ends of one of the two rotation wrap plates, the other two of the four shield blocks are arranged in the axial direction of the rotation shaft and are respectively connected to two ends of the other of the two rotation wrap plates, and in the axial direction of the rotation shaft, the first support assembly is disposed between the two of the four shield blocks, and is disposed between the other two of the four shield blocks.

(17) In some embodiments, the support structure includes: two rotation shafts; a gear plate, wherein a mounting face of the gear plate is parallel to the third direction, the gear plate is detachably connected to the middle wrap plate, and in the axial direction of the rotation shaft, the gear plate is disposed on end portions, on a same side, of the two rotation shafts, wherein the mounting face of the gear plate is a face, facing away from the chain, of the gear plate; a first transmission gear, wherein the first transmission gear is rotatably connected to the mounting face of the gear plate, and a rotation center of the first transmission gear is parallel to the axial direction of the rotation shaft; a second transmission gear, wherein the second transmission gear is rotatably connected to the mounting face of the gear plate, and the second transmission gear is engaged with the first transmission gear; a first synchronous gear, wherein the first synchronous gear is engaged with the first transmission gear, and the first synchronous gear is sleeved onto one of the two rotation shafts; and a second synchronous gear, wherein the second synchronous gear is engaged with the second transmission gear, and the second synchronous gear is sleeved onto the other of the two rotation shafts.

(18) In some embodiments, the support structure further includes: at least two mounting plates, wherein one of the at least two mounting plates is fixedly connected to an outer wall of the first synchronous gear and is connected to one of the at least two rotation plates, the other of the at least two mounting plates is fixedly connected to an outer wall of the second synchronous gear and is connected to the other of the at least two rotation plates, and two rotation plates connected to the at least two mounting plates are disposed on an end portion, on a same side, of the rotation shaft.

(19) In some embodiments, the support structure further includes: an elevator assembly, wherein one end of the elevator assembly is connected to the middle portion of the chain, the other end of the elevator assembly is connected to the rotation shaft, and the elevator assembly is configured to change a distance between the middle portion of the chain and the rotation shaft.

(20) In some embodiments, the elevator assembly includes: a first connection block, wherein the first connection block includes a second rotation shaft through hole, a middle portion of the rotation shaft is disposed in the second rotation shaft through hole, and the first connection block includes a protrusion through hole; a second connection block, wherein the second connection block includes a connection pin through hole, a part of the second connection block is disposed in the protrusion through hole, another part of the second connection block is disposed outside the protrusion through hole, the second connection block is slidably connected to the first connection block, and a slide direction of the second connection block is perpendicular to the axial direction of the rotation shaft and the extension direction of the chain; a second connection pin, wherein one end of the second connection pin is connected to the middle portion of the chain, and the other end of the second connection pin is connected to the connection pin through hole; and an elastic plate, wherein one end of the elastic plate is connected to the first connection block, and the other end of the elastic plate is connected to the second connection block.

(21) In some embodiments, the chain includes: a first link, wherein one end of the first link is connected to one shift plate of the one pair of shift plates; and a plurality of second links, wherein the plurality of second links are sequentially rotatably connected, second links, on one end, of the plurality of second links are connected to the other end of the first link, and second links, on the other end, of the plurality of second links are connected to the other shift plate of the one pair of shift plates; wherein both the first link and the second link include a first limit face and a second limit face, and the second link further includes a third limit face and a fourth limit face, wherein the first limit face is attached to the third limit face in the case that the support structure is not bent, and the second limit face is attached to the fourth limit face in the case that the support structure is in a maximally bending status.

(22) In some embodiments, the support structure includes: four chains and three first support assemblies, wherein the four chains are spaced apart in the axial direction of the rotation shaft, the three first support assemblies are disposed between two adjacent chains of the four chains, and the three first support assemblies are disposed between different two adjacent chains.

(23) In some embodiments, the two slidable connection mechanisms include: four rotation plates and one pair of shift plates, wherein two of the four rotation plates are disposed on one side end portion of the rotation shaft, and are respectively disposed on the two sides of the rotation shaft; the other two of the four rotation plates are disposed on the other side end portion of the rotation shaft, and are respectively disposed on the two sides of the rotation shaft; and one shift plate of the one pair of shift plates is connected to one end of each of the four chains, and the other shift plate of the one pair of shift plates is connected to the other end of each of the four chains.

(24) According to some embodiments of the present disclosure, a display device is provided in the embodiments of the present disclosure. The display device includes: a flexible display panel and the support structure according to above embodiments, wherein the flexible display panel includes a bendable display region, the support structure is disposed on a back face of the flexible display panel, and the rotation shaft is opposite to the bendable display region.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) For clearer description of the technical solutions in the embodiments of the present disclosure, the following briefly describes the accompanying drawings required for describing the embodiments. Apparently, the accompanying drawings in the following description show merely some embodiments of the present disclosure, and those of ordinary skill in the art may still derive other drawings from these accompanying drawings without any creative efforts.

- (2) FIG. 1 is a schematic structural diagram of a bendable display device in a not bent status according to some embodiments of the present disclosure;
- (3) FIG. 2 is a schematic structural diagram of a bendable display device in a bent status according to some embodiments of the present disclosure;
- (4) FIG. 3 is a schematic structural diagram of a support structure according to some embodiments of the present disclosure;
- (5) FIG. 4 is a schematic structural diagram of a support structure according to some embodiments of the present disclosure;
- (6) FIG. 5 is a schematic structural diagram of a support structure in a bent status according to some embodiments of the present disclosure;
- (7) FIG. 6 is a schematic diagram of assembling a first support assembly, a chain, and a shift plate according to some embodiments of the present disclosure;
- (8) FIG. 7 is schematic structural diagram of the support structure show in FIG. 6 in a bent status;
- (9) FIG. 8 is a schematic structural diagram of a chain according to some embodiments of the present disclosure;
- (10) FIG. 9 is a schematic structural diagram of a first link according to some embodiments of the present disclosure;
- (11) FIG. 10 is a schematic structural diagram of a second link according to some embodiments of the present disclosure;
- (12) FIG. 11 is a schematic structural diagram of a bent chain according to some embodiments of the present disclosure;
- (13) FIG. 12 is a bottom view of a support structure according to some embodiments of the present disclosure;
- (14) FIG. 13 is a schematic structural diagram of an elevator assembly according to some embodiments of the present disclosure;
- (15) FIG. 14 is a schematic structural diagram of an elevator assembly in another status according to some embodiments of the present disclosure;
- (16) FIG. 15 is a schematic diagram of assembling a first connection block and a second connection block according to some embodiments of the present disclosure;
- (17) FIG. 16 is a locally schematic diagram of a support structure according to some embodiments of the present disclosure;
- (18) FIG. 17 is a locally schematic diagram of a support structure according to some embodiments of the present disclosure;
- (19) FIG. 18 is a locally schematic diagram of a support structure according to some embodiments of the present disclosure;
- (20) FIG. 19 is a locally schematic diagram of a support structure according to some embodiments of the present disclosure;
- (21) FIG. 20 is a schematic structural diagram of a limit assembly according to some embodiments of the present disclosure;
- (22) FIG. 21 is a schematic diagram of assembling a wrap assembly and a rotation shaft connection block;

- (23) FIG. 22 is a schematic structural diagram of a rotation shaft wrap member according to some embodiments of the present disclosure;
- (24) FIG. 23 is a schematic structural diagram of assembling a rotation shaft wrap member and a rotation shaft in a not bent status according to some embodiments of the present disclosure;
- (25) FIG. 24 is a schematic structural diagram of assembling a rotation shaft wrap member and a rotation shaft in a bent status according to some embodiments of the present disclosure;
- (26) FIG. 25 is a schematic structural diagram of a gear assembly according to some embodiments of the present disclosure;
- (27) FIG. 26 is a locally schematic structural diagram of a support structure according to some embodiments of the present disclosure;
- (28) FIG. 27 is a schematic structural diagram of a rotation plate according to some embodiments of the present disclosure;
- (29) FIG. 28 is a schematic structural diagram of a rotation plate according to some embodiments of the present disclosure;
- (30) FIG. 29 is a schematic structural diagram of a slide block according to some embodiments of the present disclosure;
- (31) FIG. 30 is a schematic structural diagram of a rotation rod according to some embodiments of the present disclosure;
- (32) FIG. 31 is a schematic structural diagram of a support structure according to some embodiments of the present disclosure in another view;
- (33) FIG. 32 is an exploded schematic structural diagram of a support structure according to some embodiments of the present disclosure;
- (34) FIG. 33 is a schematic structural diagram of a support structure according to some embodiments of the present disclosure in another view;
- (35) FIG. 34 is a schematic structural diagram of a support structure according to some embodiments of the present disclosure in another view; and
- (36) FIG. 35 is a schematic structural diagram of a support structure according to some embodiments of the present disclosure in another view.

REFERENCE NUMERALS

- (37) **1**—first plane display portion; **2**—bendable display portion; **3**—second plane display portion; **10**—rotation shaft; **20**—rotation plate; **201**—second limit protrusion; **202**—second limit recess; **203**—first waist-shaped hole; **204**—sector-shaped recess; **2041**—circle-shaped hole; **2042**—slide hole; **205**—second waist-shaped hole; **206**—rotation plate protrusion; **2061**—rotation plate through hole; **207**—gear fixing hole; **30**—shift plate; **301**—first waist-shaped recess; **302**—second waist-shaped recess; **303**—third waist-shaped hole; **40**—chain; **41**—first chain; **42**—second chain; **43**—third chain; **44**—fourth chain; **401**—first link; **402**—second link; **403**—first limit face; **404**—second limit face; **405**—third limit face; **406**—fourth limit face; **407**—first through hole; **408**—recess; **409**—protrusion; **4010**—second through hole; **50**—first support assembly; **501**—first support; **5011**—mounting recess; **502**—first recess; **503**—first protrusion; **60**—first connection pin; **70**—second support assembly; **701**—support; **702**—second support; **703**—second protrusion; **80**—limit assembly; **801**—first limit protrusion; **802**—first limit recess; **803**—first stopper; **804**—second stopper; **805**—elastic member; **806**—mounting block; **807**—fixing recess; **8071**—first fixing sub-recess; **8072**—second fixing sub-recess; **808**—mounting through hole; **90**—wrap assembly; **901**—middle wrap plate; **902**—rotation wrap plate; **9011**—third limit protrusion; **903**—fixing protrusion; **9031**—first fixing boss; **9032**—second fixing protrusion; **904**—shield block; **905**—rotation shaft wrap member; **9051**—rotation shaft mounting recess; **100**—rotation shaft connection block; **1001**—first rotation shaft through hole; **110**—gear plate; **1101**—third limit recess; **120**—first transmission gear; **130**—second transmission gear; **140**—first synchronous gear; **150**—second synchronous gear; **160**—mounting plate; **1000**—rotation sub-shaft; **1601**—mounting hole; **1602**—second screw; **170**—elevator assembly; **1701**—first connection block; **1702**—second

rotation shaft through hole; **1703**—second connection block; **1704**—connection pin through hole; **1705**—second connection pin; **1706**—elastic plate; **1707**—protrusion through hole; **1708**—square through hole; **180**—snap ring; **190**—slide block; **200**—slide plate; **2001**—slide way; **2002**—fourth waist-shaped hole; **210**—rotation rod; **2101**—body rod; **2102**—first protrusion; **2103**—second protrusion; **2104**—third protrusion; **220**—shield plate; **230**—support plate; **240**—stud; **250**—rear shell; **260**—fixing plate.

DETAILED DESCRIPTION

(38) To make the objectives, technical solutions, and advantages of the present disclosure clearer, the embodiments of the present disclosure are further described in detail hereinafter with reference to the accompanying drawings.

(39) FIG. 1 is a schematic structural diagram of a bendable display device in a not bent status according to some embodiments of the present disclosure. Referring to FIG. 1, the bendable display device includes a first plane display portion **1**, a bendable display portion **2**, and a second plane display portion **3** that are sequentially connected. In FIG. 1, the bendable display device is not bent. In this case, a surface of the first plane display portion **1**, a surface of the bendable display portion **2**, and a surface of the second plane display portion **3** are coplanar.

(40) FIG. 2 is a schematic structural diagram of a bendable display device in a bent status according to some embodiments of the present disclosure. Referring to FIG. 2, the bendable display device is bent at the bendable display portion **2**, such that a bottom face of the first plane display portion **1** is opposite to a bottom face of the second plane display portion **3**. In this case, the bendable display device is bent, such that the bendable display device is portable. The surface of the display portion is a face for displaying, the bottom face of the display portion is opposite to the surface of the display portion.

(41) The bendable display device includes a flexible display panel and a support structure, and the support structure is configured to support the flexible display panel.

(42) In some practices, the support structure includes a rotation shaft, a chain, a support plate, and two slidable connection mechanisms. The rotation shaft and the support plate are configured to support a bendable display region of the flexible display panel. The two slidable connection mechanisms are rotatably connected to the rotation shaft, disposed on two sides of the rotation shaft, and configured to support an unbendable display region of the flexible display panel. A middle portion of the chain is connected to the rotation shaft, and two ends of the chain are respectively connected to the two slidable connection mechanisms.

(43) The rotation shaft, the chain, and the support plate are laminated. In the case that thicknesses of the rotation shaft and the chain are determined, the support plate is designed to be thin enough to reduce a thickness of the support structure. Thus, the support plate is prone to being damaged, and the support structure is further damaged.

(44) FIG. 3 is a schematic structural diagram of a support structure according to some embodiments of the present disclosure. Referring to FIG. 3, the support structure includes a rotation shaft **10**, a slidable connection mechanism **23**, and at least two chains **40**.

(45) The two slidable connection mechanisms **23** are rotatably connected to the rotation shaft **10**, disposed on two sides of the rotation shaft **10**, and configured to support an unbendable display region of the flexible display panel. The at least two chains **40** are spaced apart in an axial direction of the rotation shaft **10**, extension directions of the at least two chains **40** are perpendicular to the axial direction of the rotation shaft **10**, middle portions of the at least two chains **40** are connected to the rotation shaft **10**, and two ends of each of the at least two chains **40** are respectively connected to the two slidable connection mechanisms **23**.

(46) It is noted that, for displaying the rotation shaft, and other structures, FIG. 3 does not show all structures of the support structure.

(47) FIG. 4 is a schematic structural diagram of a support structure according to some embodiments of the present disclosure. Referring to FIG. 4, in the axial direction of the rotation

shaft **10**, each of the at least one first support assembly **50** is connected between two adjacent chains **40** of the at least two chains **40**, and a surface, distal from the rotation shaft **10**, of the first support assembly **50** and a surface, distal from the rotation shaft **10**, of the chain **40** are configured to support a bendable display region of the flexible display panel.

(48) In the embodiments of the present disclosure, as the first support assembly **50** is disposed between two adjacent chains **40**, the surface of the first support assembly **50** and the surface of the chain **40** form a support face to support the bendable display region of the flexible display panel. In the case that thicknesses of the chain **40** and the rotation shaft **10** are determined, it is not necessary to dispose the support face above the chain **40**, such that a thickness of a bendable support device is reduced. As the first support assembly **50** is disposed between two adjacent chains **40**, a height for disposing the first support assembly **50** is increased, and a thickness of the first support assembly **50** is increased. Thus, a support strength of the entire support structure is increased, and a possibility of damaging the bendable support device is reduced.

(49) In the embodiments of the present disclosure, the rotation shaft **10** extends in a first direction a, and the first support assembly **50** extends in the first direction a.

(50) Referring to FIG. 3 and FIG. 4, two slidable connection mechanisms **23** include at least two rotation plates **20** and at least one pair of shift plates **30**.

(51) In a second direction b, the at least two rotation plates **20** are respectively disposed on two sides of the rotation shaft **10** and rotatably connected to the rotation shaft. The second direction b is perpendicular to the first direction a. Each of the at least one pair of shift plates **30** includes two shift plates **30** spaced apart in the second direction b, and different pairs of shift plates **30** are spaced apart in the first direction a. At least two chains **40** extend in the second direction b, at least two chains **40** are spaced apart in the first direction a, and the middle portions of at least two chains **40** are connected to the rotation shaft **10**. Any of the at least two chains **40** is disposed between two shift plates **30** of one pair of shift plates **30**, and two ends of the any of the at least two chains **40** are respectively connected to two shift plates **30** of one pair of shift plates **30**. Any one of the at least two rotation plates **20** is opposite to one shift plate **30**, the shift plate **30** is slidably connected to an opposite rotation plate **20**, and a slide direction of the shift plate **30** is perpendicular to the second direction b.

(52) In the embodiments of the present disclosure, a face, distal from the rotation plate **20**, of the shift plate **30** receives the flexible display panel to support the flexible display panel, so as to ensure the shape of the flexible display panel. Two ends of the chain **40** are connected to the shift plate **30**, and the chain **40** supports the flexible display panel in the case that the shift plate **30** supports the flexible display panel. The first support assembly **50** is disposed between two adjacent chains **40**, and thus, the first support assembly **50** supports the flexible display panel.

(53) In the embodiments of the present disclosure, the rotation shaft **10** and the chain **40** are opposite to the bendable display portion **2**, and the shift plates **30** on two sides of the rotation shaft **10** are opposite to the first plane display portion **1** and the second plane display portion **3**. In the case that the bendable display device needs to be bent, the bendable display device is bent at the first plane display portion **1** and the second plane display portion **3**, and the rotation plate **20** rotates about the rotation shaft **10** and the shift plate **30** rotates under the reaction of the squeeze force. As a centerline of rotating the rotation plate **20** is a centerline of the rotation shaft **10**, a centerline of rotating the shift plate **30** is a centerline of the chain **40**, and the centerlines are not coincident, a slide occurs between the shift plate **30** and the rotation plate **20** in rotating, such that the bendable display device changes from a not bent status to a bent status.

(54) Referring to FIG. 3 and FIG. 4, the support structure includes four chains **40** and three first support assemblies **50**, the four chains **40** are spaced apart in the first direction a, the three first support assemblies **50** are disposed between two adjacent chains **40** of the four chains **40**, and the three first support assemblies **50** are disposed between different two adjacent chains **40**.

(55) In the embodiments of the present disclosure, four chains **40** are disposed, and the shift plate

30 is driven to rotate based on the rotation of the plurality of chains **40**, such that the shift plate **30** is prone to rotating. The first support assembly **50** is disposed between any two adjacent chains **40**, such that the support face formed by the chain **40** and the first support assembly **50** is complete and larger, and the support property of the support structure is improved.

(56) In some embodiments, another number of chains **40** is disposed, for example, two, three, five, or more, which is not limited in the present disclosure.

(57) Referring to FIG. 4, the four chains **40** include a first chain **41**, a second chain **42**, a third chain **43**, and a fourth chain **44** that are arranged in the first direction a. A distance **L1** between the first chain **41** and the second chain **42** is equal to a distance **L2** between the third chain **43** and the fourth chain **44**, and is less than a distance **L3** between the second chain **42** and the third chain **43**. That is, a length of the first support assembly **50** between the first chain **41** and the second chain **42** is equal to a length of the first support assembly **50** between the third chain **43** and the fourth chain **44**, and is less than a length of the first support assembly **50** between the second chain **42** and the third chain **43**. The length of the first support assembly **50** is a length of the first support assembly **50** in the first direction a.

(58) In some embodiments, the distance **L1** between the first chain **41** and the second chain **42**, the distance **L2** between the third chain **43** and the fourth chain **44**, and the distance **L3** between the second chain **42** and the third chain **43** are equal. In some embodiments, **L1**, **L2**, and **L3** are not equal.

(59) In the embodiments of the present disclosure, the rotation shaft **10** includes four rotation sub-shafts (not shown in the drawing) arranged in the first direction a, and the first chain **41**, the second chain **42**, the third chain **43**, and the fourth chain **44** are connected to different rotation sub-shafts.

(60) Referring to FIG. 3 and FIG. 4, the support structure includes four rotation plates **20** and one pair of shift plates **30**. Two of the four rotation plates **20** are disposed on one side end portion of the rotation shaft **10**, and are respectively disposed on two sides of the rotation shaft **10**. The other two of the four rotation plates **20** are disposed on the other side end portion of the rotation shaft **10**, and are respectively disposed on two sides of the rotation shaft **10**. One shift plate **30** of the one pair of shift plates **30** is connected to one end of each of the four chains **40**, and the other shift plate **30** of the one pair of shift plates **30** is connected to the other end of each of the four chains **40**.

(61) In the embodiments of the present disclosure, one pair of shift plates **30** is disposed. One shift plate **30** includes two slide portions and a middle elongated connection portion, the two slide portions are connected to the connection portion, such that the shift plate **30** on one side of the rotation shaft **10** is entire. As such, a part of the shift plate **30** is disposed between the second chain **42** and the third chain **43**, and the part of the shift plate **30** supports the flexible display panel to improve the support property of the support structure. The rotation plate **20** is disposed above the shift plate **30**, and thus has less effect on the support property of the support structure. Thus, four rotation plates **20** are disposed, and the rotation plate **20** is not disposed between the second chain **42** and the third chain **43**, such that the weight of the entire rotation plate **20** is reduced to facilitate the portability of the support structure.

(62) In some embodiments, other numbers of rotation plates **20** and shift plates **30** are disposed, for example, two rotation plates **20** and four shift plates **30** (in this case, the shift plate **30** on one side of the rotation shaft **10** is not entire) are disposed, which is not limited in the present disclosure.

(63) FIG. 5 is a schematic structural diagram of a support structure in a bent status according to some embodiments of the present disclosure. Referring to FIG. 5, in the case that the support structure is bent, the first support assembly **50** is bent along with the chain (**41**, **42**, **43**, and **44**) to ensure the bending property of the support structure.

(64) FIG. 6 is a schematic diagram of assembling a first support assembly, a chain, and a shift plate according to some embodiments of the present disclosure. Referring to FIG. 6, the first support assembly **50** includes a plurality of first supports **501** juxtaposed in the second direction b, any two adjacent first supports **501** of the plurality of first supports **501** are rotatably connected, and a

rotation centerline is parallel to the first direction a. In a third direction c, the chain **40** and the first support **501** are disposed on a same side of the rotation shaft **10**. The first direction a, the second direction b, and the third direction c are perpendicular to each other.

(65) In the embodiments of the present disclosure, two adjacent first supports **501** are rotated about each other in the case that the first support assembly **50** is to bend, such that the first support assembly **50** is bent.

(66) FIG. **7** is schematic structural diagram of the support structure show in FIG. **6** in a bent status. Referring to FIG. **6** and FIG. **7**, the first support assembly **50** includes a plurality of first supports **501**.

(67) Referring to FIG. **6**, in any two adjacent first supports **501** of the plurality of first supports **501**, an outer sidewall, facing towards the other first support **501**, of one first support **501** includes a first recess **502**, and the other first support **501** includes a first protrusion **503** disposed in the first recess **502**, and the first protrusion **503** is rotatably connected to the first recess **502**.

(68) In the embodiments of the present disclosure, the first recess **502** is disposed on one of the first support **501**, and the first protrusion **503** is disposed on the adjacent first support **501**, and the first protrusion **503** is rotatably connected to the first recess **502**. As such, the first protrusion **503** is rotated in the first recess **502** in the case that the first support assembly **50** is to bend, such that the first support assembly **50** is bent.

(69) FIG. **8** is a schematic structural diagram of a chain according to some embodiments of the present disclosure. Referring to FIG. **8**, the support structure further includes a first connection pin **60**. A middle portion of the first connection pin **60** is fixedly connected to the chain **40**, and one end of the first connection pin **60** is fixedly connected to an end portion of the first support **501**. Part of the first support **501** is not shown in FIG. **7** for clearer description of the first connection pin **60**.

(70) In the embodiments of the present disclosure, the middle portion of the first connection pin **60** is connected to the chain **40**, and two ends of the first connection pin **60** are respectively connected to the end portions of two first supports **501**, such that the chain **40** and the first support **501** are connected, and the first support **501** is driven to rotate based on the rotation of the chain **40**.

(71) In the embodiments of the present disclosure, the end portion of the first support **501** is in a tubular structure. The first connection pin **60** is inserted into the cavity of the tubular structure, and thus the first connection pin **60** and the tubular structure are in interference fit, such that the first support **501** and the first connection pin **60** are connected without other portions, and the structure is simple.

(72) Referring to FIG. **7**, mounting recesses **5011** are disposed in the middle portions in the middle of the first supports **501** of the plurality of first supports **501**. The flexible display panel includes mounting protrusions corresponding to the mounting recesses **5011**, such that the mounting protrusions are disposed in the mounting recesses **5011** to align in the case that the support structure and the flexible display panel are mounted.

(73) In some embodiments, the mounting recess **5011** is a rectangular mounting recess.

(74) In some embodiments, the mounting protrusion is a steel strip, for example, a stainless steel (SUS) structure in the panel.

(75) Referring to FIG. **7**, the support structure further includes two second support assemblies **70**. In the first direction a, each of the at least two chains **40** is disposed between the two second support assemblies **70**, a side face of one of the two second support assemblies **70** is connected to a side face of one, proximal to one end of the rotation shaft **10**, of the at least two chains **40**, and an end of the other of the two second support assemblies **70** is connected to a side face of one, proximal to the other end of the rotation shaft **10**, of the at least two chains **40**. The side face of the chain **40** is a face, facing towards an end portion of proximal rotation shaft **10**, of the chain **40**.

(76) In the embodiments of the present disclosure, the second support assembly **70** is disposed on the end portion. Thus, the second support assembly **70** forms the support face to support the flexible display panel, and the support property of the support structure is improved.

(77) Referring to FIG. 6, the second support assembly **70** includes two pairs of supports **701**. The two pairs of supports **701** are spaced apart in the second direction **b**, each of the two pairs of supports **701** includes two second supports **702** juxtaposed in the second direction **b**, and one end portion of each of the two second supports **702** is connected to the side face of the chain **40**. Outer sidewalls of the two second supports **702** include second protrusions **703**. The outer sidewalls of the two second supports **702** including the second protrusions **703** are opposite to each other, and the second protrusions **703** of the two second supports **702** are rotatably connected.

(78) In the embodiments of the present disclosure, two second supports **702** in one pair of supports **701** are rotatably connected by the second protrusion **703**, and thus, the second support **702** is driven to rotate based on the rotation of the chain **40**, such that the support structure is bent.

(79) Referring to FIG. 6, two ends of the first connection pin **60** connected to the fourth chain **44** are respectively connected to the first support assembly **50** and the second support **702**. That is, the fourth chain **44** is connected to the first support assembly **50** and the second support **702** by the first connection pin **60**.

(80) Likewise, the first chain **41** is connected to the first support assembly **50** and the second support **702** by the first connection pin **60**.

(81) In some embodiments, both the second support **702** and the second protrusion **703** include through holes (not shown in the drawing). Thus, the first connection pin **60** and the through hole are in interference fit, such that the first connection pin **60** and the second support **702** are connected.

(82) As shown in FIG. 6 and FIG. 7, the support structure further includes a second connection pin **1705**, and the second connection pin **1705** is connected to the middle portion of the chain **40** (for example, the fourth chain **44**). A snap ring **180** is disposed on the end portion of the second connection pin **1705**, so as to prevent the second connection pin **1705** from sliding out of the chain **40**.

(83) Referring to FIG. 8, the chain **40** includes: a first link **401** and a plurality of second links **402**. One end of the first link **401** is connected to one shift plate **30** of the one pair of shift plates **30**. The plurality of second links **402** are sequentially connected, second links **402**, on one end, of the plurality of second links **402** are connected to the other end of the first link **401**, and second links **402**, on the other end, of the plurality of second links **402** are connected to the other shift plate **30** of the one pair of shift plates **30**.

(84) In the embodiments of the present disclosure, the chain **40** is divided into a plurality of links to facilitate the rotation of the chain **40**.

(85) As shown in FIG. 8, one end of the first link **401** is connected to the middle portion of the first connection pin **60**. Referring to FIG. 8 and FIG. 7, one end of the first link **401** is connected to the shift plate **30** by the first connection pin **60**. The first link **401** is connected to the second link **402** by the first connection pin **60**, middle second links **402** are connected to adjacent second links **402** by the second connection pins **1705** (not shown in FIG. 8), and other second links **402** are connected by the first connection pin **60**. In conjunction with FIG. 8 and FIG. 7, the second links **402** on the second end are connected to the shift plate **30** by the first connection pin **60**. That is, the first connection pins **60** connect to the chain **40**, the shift plate **30**, and the first support **501**.

(86) As shown in FIG. 8, one chain **40** includes one first link **401** and five second links **402**, that is, one chain **40** includes six links. One chain **40** is connected to six first connection pins **60**. As the chain **40** is connected to the first support assembly **50** by the first connection pin **60**, the first support assembly **50** also includes six first supports **501**.

(87) In some embodiments, one chain **40** includes other number of links. Likewise, numbers of the first connection pins **60** and the first support assemblies **50** are adjusted.

(88) FIG. 9 is a schematic structural diagram of a first link according to some embodiments of the present disclosure. Referring to FIG. 9, the first link **401** is in an I-shape. One end of the I-shaped first link **401** includes two first through holes **407**, and the first connection pin **60** passes through

the first through hole **407** to connect the first link **401** to the shift plate **30** and the first support **501**. The other end of the I-shaped first link **401** also includes two first through holes **407**.

(89) FIG. **10** is a schematic structural diagram of a second link according to some embodiments of the present disclosure. Referring to FIG. **10**, one end of the second link includes a protrusion **409** matching with a recess **408** on the other end of the I-shaped first link **401**. The protrusion **409** is disposed in the recess **408**, and the protrusion **409** also includes a second through hole **4010**. The first support **501** is connected to the first link **401** and the second link **402** by sequentially passing through one first through hole **407** on the first link **401**, the second through hole **4010** on the second link **402**, and the other first through hole **407** on the first link **401**.

(90) Referring to FIG. **8** and FIG. **9**, the first link **401** includes a first limit face **403** and a second limit face **404**. Referring to FIG. **8** and FIG. **10**, the second link **402** also includes the first limit face **403** and the second limit face **404**, and the second link **402** further includes a third limit face **405** and a fourth limit face **406**.

(91) Referring to FIG. **8**, in the case that the chain **40** is not bent, the first limit face **403** is attached to the third limit face **405**, such that a flatness of the surface of the chain **40** is ensured.

(92) FIG. **11** is a schematic structural diagram of a bent chain according to some embodiments of the present disclosure. Referring to FIG. **11**, in the case that the chain **40** is in a maximally bending status, the second limit face **404** is attached to the fourth limit face **406**. In this case, the chain is not bent anymore, so as to avoid over-bending or reversely bending the chain.

(93) FIG. **12** is a bottom view of a support structure according to some embodiments of the present disclosure. Referring to FIG. **12**, the support structure includes two rotation shafts **10** juxtaposed in the second direction **b**. Two rotation plates **20** on two sides of the two rotation shafts **10** are respectively connected to the two rotation shafts.

(94) Referring to FIG. **12**, the bendable support structure further includes an elevator assembly **170**. Referring to FIG. **4**, one end of the elevator assembly **170** is connected to the middle portion of the chain **40**, the other end of the elevator assembly **170** is connected to the rotation shaft **10**, and the elevator assembly **170** is configured to change a distance between the middle portion of the chain **40** and the rotation shaft **10**.

(95) In the embodiments of the present disclosure, the elevator assembly **170** is configured to connect the rotation shaft **10** and the chain **40**, so as to ensure the stability of the chain **40**. One end of the elevator assembly **170** is connected to the middle portion of the chain **40**, such that the chain **40** is bent in the middle portion. The elevator assembly **170** is configured to change a distance between the middle portion of the chain **40** and the rotation shaft **10**, such that the effort is saved in bending.

(96) FIG. **13** is a schematic structural diagram of an elevator assembly according to some embodiments of the present disclosure. Referring to FIG. **13**, the elevator assembly **170** includes: a first connection block **1701**, a second connection block **1703**, and an elastic plate **1706**. The second connection block **1703** is slidably connected to the first connection block **1701**, the first connection block **1701** includes a second rotation shaft through hole **1702**, and a middle portion of the rotation shaft **10** is disposed in the second rotation shaft through hole **1702**. The second connection block **1703** includes a connection pin through hole **1704**. One end of the elastic plate **1706** is connected to the first connection block **1701**, and the other end of the elastic plate **1706** is connected to the second connection block **1703**. In conjunction with FIG. **4**, one end of the second connection pin **1705** is connected to the middle portion of the chain **40**, and the other end of the second connection pin **1705** is connected to the connection pin through hole **1704**.

(97) In the embodiments of the present disclosure, the second connection block **1703** is slidably connected to the first connection block **1701**, such that the elastic plate **1706** is elastic. The second connection block **1703** is controlled to slide in the first connection block **1701** based on the elastic force of the elastic plate **1706**, and a distance between the second rotation shaft through hole **1702** and the connection pin through hole **1704** is changed, such that the distance between the middle

portion of the chain **40** and the rotation shaft **10** is changed.

(98) In the elevator assembly shown in FIG. **13**, the elastic plate **1706** is in a compressed status. FIG. **14** is a schematic structural diagram of an elevator assembly in another status according to some embodiments of the present disclosure. In rotating the support structure, the distance between the middle portion of the chain **40** and the rotation shaft **10** is changed, and the elevator assembly **170** is configured to change the distance between the middle portion of the chain **40** and the rotation shaft **10**. In the case that the support structure is in a planar status, the distance between the middle portion of the chain **40** and the rotation shaft **10** is reduced. In this case, the elastic plate **1706** is compressed, and a distance between the second connection block **1703** and the first connection block **1701** is reduced, such that the distance between the middle portion of the chain **40** and the rotation shaft **10** is reduced. In the case that the support structure is bent, the distance between the middle portion of the chain **40** and the rotation shaft **10** is increased. In this case, the elastic force of the elastic plate **1706** increases the distance between the second connection block **1703** and the first connection block **1701**, such that the distance between the middle portion of the chain **40** and the rotation shaft **10** is increased.

(99) In some embodiments, the first connection block **1701** and the second connection block **1703** are in a block structure, and the elastic plate **1706** is in a “W” structure.

(100) In some embodiments, the elastic plate **1706** is composed of sheet structures on two ends and a middle elastic connection portion. The sheet structures on two ends are configured to connect and limit, and the middle elastic connection portion is configured to provide the elastic force.

(101) In some embodiments, the elevator assembly does not include the elastic plate, and the elevator function of the elevator assembly is achieved by the assembling relationship of the first connection block and the second connection block.

(102) FIG. **15** is a schematic diagram of assembling a first connection block and a second connection block according to some embodiments of the present disclosure. Referring to FIG. **15**, the first connection block **1701** includes a protrusion through hole **1707** for disposing the second connection block **1703**, one end of the second connection block **1703** is disposed in the protrusion through hole **1707**, and the other end of the second connection block **1703** is disposed outside the protrusion through hole **1707**. The other end of the second connection block **1703** includes a limit protrusion **1709** configured to prevent the other end of the second connection block **1703** from escaping from the protrusion through hole **1707**. Both the first connection block **1701** and the second connection block **1703** include square through holes **1708**. Referring to FIG. **13** and FIG. **14**, two end of the elastic plate **1706** are respectively disposed in two square through holes **1708**.

(103) FIG. **16** is a locally schematic diagram of a support structure according to some embodiments of the present disclosure. Referring to FIG. **16**, the support structure further includes a limit assembly **80**.

(104) FIG. **17** is a locally schematic diagram of a support structure according to some embodiments of the present disclosure. Referring to FIG. **17**, one end of the limit assembly **80** is abutted against a side face of at least one of the at least two rotation plates **20**, and a middle portion of the limit assembly **80** is fixedly connected to the rotation shaft **10**. An end face of the other end of the limit assembly **80** includes a plurality of first limit protrusions **801**, the plurality of first limit protrusions **801** are circumferentially spaced apart, and a first limit recess **802** is formed between two adjacent first limit protrusions **801**. A side face of the rotation plate **20** abutted against the other end of the limit assembly **80** includes a plurality of second limit protrusions **201**. The plurality of second limit protrusions **201** are circumferentially spaced apart, a second limit recess **202** is formed between two adjacent second limit protrusions **201**, and a centerline of the rotation shaft **10** connected to the rotation plate **20** and a centerline of a circumference of the plurality of second limit protrusions **201** are collinear. The first limit protrusion **801** is disposed in the second limit recess **202**, and the second limit protrusion **201** is disposed in the first limit recess **802**, or the first limit protrusion **801** is abutted against the second limit protrusion **201**. The limit assembly **80** is disposed between two

shift plates **30** of one pair of shift plates **30**.

(105) Referring to FIG. **17**, the limit assembly **80** includes: a first stopper **803**, a second stopper **804**, an elastic member **805**, and a mounting block **806**. The first limit protrusion **801** is disposed on one end face, facing towards the rotation plate **20**, of the first stopper **803**. The second stopper **804** is spaced apart from the first stopper **803** in the axial direction of the rotation shaft **10**. One end of the elastic member **805** is connected to the other end face of the first stopper **803**, and the other end of the elastic member **805** is connected to one end face of the second stopper **804**. The mounting block **806** is connected to the other end face of the second stopper **804** and fixedly connected to the rotation shaft **10**).

(106) FIG. **18** is a locally schematic diagram of a support structure according to some embodiments of the present disclosure. FIG. **18** and FIG. **17** are differed in the shape of the second stopper **804**. In FIG. **17**, the second stopper **804** is in a pillar-shaped structure laminated by a plurality of rounded rectangle sheets. In FIG. **18**, the second stopper **804** is in a T-shaped structure.

(107) Hereinafter is illustrated by taking the support structure in FIG. **18** as an example. A limit assembly **80** is added in the support structure. In the case that the support structure is in different bending status, the limit assembly **80** is configured to limit, such that the support structure keeps in a specific status, for example, a complete open status, a complete close status, a semi-open status, and the like.

(108) In FIG. **18**, the support structure is in a complete close status. In this case, the first limit protrusion **801** is disposed in the second limit recess **202**, and the second limit protrusion **201** is disposed in the first limit recess **802**.

(109) FIG. **19** is a locally schematic diagram of a support structure according to some embodiments of the present disclosure. Referring to FIG. **19**, the support structure is in a complete open status. In bending the support structure, the rotation plate **20** rotates, and the second limit protrusion **201** on the rotation plate **20** rotates along with the rotation plate **20**. Thus, the second limit protrusion **201** needs to overcome the resistance between the second limit protrusion **201** and the first limit protrusion **801** to be abutted against the first limit protrusion **801**. Or, relative positions of the second limit protrusion **201** and the first limit recess **802** are changed, and the second limit protrusion **201** is disposed in another first limit recess **802**. Thus, the support structure keeps in a specific status.

(110) FIG. **20** is a schematic structural diagram of a limit assembly according to some embodiments of the present disclosure. Referring to FIG. **20**, the end portion of the rotation shaft **10** is connected to the mounting block **806** after the rotation shaft **10** sequentially passes through the first stopper **803**, the elastic member **805**, and the second stopper **804**.

(111) It is noted that, in the embodiments of the present disclosure, the rotation shaft **10** is composed of a plurality of rotation sub-shafts, and the plurality of rotation sub-shafts are disconnected to each other. For example, in FIG. **16**, one rotation sub-shaft passes through the chain **40** on the left side, and another rotation sub-shaft passes through the chain **40** on the right side and is connected to the limit assembly **80**.

(112) In the embodiments of the present disclosure, the first stopper **803** is configured to dispose the first limit protrusion **801**, and the elastic member **805** provides the elastic force to the first limit protrusion **801**, such that the first limit protrusion **801** squeezes the rotation plate **20**. As such, the rotation plate **20** rotates on the premise of overcoming the elastic force, such that the support structure keeps in a specific status. The mounting block **806** is configured to fix the second stopper **804**, such that the position of the second stopper **804** is not changed. As such, the elastic member **805** is compressed, such that the elastic force is generated on the first limit protrusion **801**.

(113) In the embodiments of the present disclosure, the first stopper **803** includes two turns of first limit protrusions **801**, and the two turns of first limit protrusions **801** respectively correspond to the second limit protrusions **201** on two rotation plates **20**. That is, one turn of first limit protrusion **801** corresponds to the second limit protrusion **201** on one rotation plate **20**.

(114) In the embodiments of the present disclosure, the support structure achieves the fixation of the rotation plate **20** in rotating by damping of the elastic member **805** in the limit assembly **80**, that is, the support structure achieves self-locking by the limit assembly **80**.

(115) In some embodiments, the elastic member **805** is a spring, a rubber boot, and the like.

(116) In the embodiments of the present disclosure, a number of the elastic members **805** between the first stopper **803** and the second stopper **804** is one, two, three, or more.

(117) Referring to FIG. **20**, the limit assembly **80** further includes a mounting through hole **808**, and the mounting through hole **808** is configured to connect to other portions.

(118) In the embodiments of the present disclosure, the mounting block **806** and the second stopper **804** are integrally formed, or are connected in other ways.

(119) Referring to FIG. **3**, the support structure further includes: a wrap assembly **90**. The wrap assembly **90** extends in the first direction a.

(120) FIG. **21** is a schematic diagram of assembling a wrap assembly and a rotation shaft connection block. Referring to FIG. **21**, the support structure further includes a rotation shaft connection block **100**. The rotation shaft connection block **100** is fixedly connected to a middle portion of the wrap assembly **90** and includes a first rotation shaft through hole **1001** for the rotation shaft **10** passing through. In the third direction c, the limit assembly **80** is disposed between the first support assembly **50** and the wrap assembly **90**, and the wrap assembly **90** is connected to the limit assembly **80**.

(121) In the embodiments of the present disclosure, the wrap assembly **90** wraps two ends of the support structures to ensure the aesthetic of the bendable display device. The rotation shaft connection block **100** is disposed, the rotation shaft connection block **100** is connected to the wrap assembly **90**, and the rotation shaft **10** passes through the first rotation shaft through hole **1001** in the rotation shaft connection block **100**, such that the rotation shaft **10** is connected to the wrap assembly **90**, and the stability of the wrap assembly **90** is ensured.

(122) Referring to FIG. **21**, the wrap assembly **90** includes a middle wrap plate **901**, two rotation wrap plates **902**, and a fixing protrusion **903**. The middle wrap plate **901** extends in the first direction a, and the rotation shaft connection block **100** is connected to a surface of the middle wrap plate **201**. The two rotation wrap plates **902** extend in the first direction a. In the second direction b, the two rotation wrap plates **902** are respectively disposed on two sides of the middle wrap plate **901**, and the two rotation wrap plates **902** are rotatably connected to the middle wrap plate **901** respectively. The fixing protrusion **903** is connected to the surface of the middle wrap plate **901**. The rotation shaft connection block **100** and the fixing protrusion **903** are connected to the same surface of the middle wrap plate **901**, and the fixing protrusion **903** includes a first fixing boss **9031**. Referring to FIG. **16**, the mounting block **806** includes a fixing recess **807**, and the first fixing boss **9031** is disposed in the fixing recess **807**.

(123) In the embodiments of the present disclosure, the middle wrap plate **901** is configured to connect to the rotation shaft connection block **100** and shield a part of the rotation shaft **10**. The two rotation wrap plates **902** are disposed on two sides of the middle wrap plate **901** and shield parts, on two sides, of the rotation shaft **10**. The two rotation wrap plates **902** are rotatably connected to the middle wrap plate **901**, and the two rotation wrap plates **902** rotates in rotating the rotation plate **20**, so as to avoid bending of the support structure.

(124) The fixing protrusion **903** is connected to the surface of the middle wrap plate **901**, and the fixing protrusion **903** is disposed in the fixing recess **807** in the mounting block **806**. As such, in the case that the support structure and the flexible display panel are disposed, the fixing recess **807** limits the movements of the fixing protrusion **903**, that is, the movements of the middle wrap plate **901**, such that the wrap assembly **90** is disposed together with the limit assembly **80**. As such, the wrap assembly **90** is disposed together with the limit assembly **80**, and the fixing protrusion **903** is directly fetched from the fixing recess **807** in detaching to separate the wrap assembly **90** and the limit assembly **80**, which is more convenient.

(125) In some embodiments, the fixing recess **807** includes a first fixing sub-recess **8071** and a second fixing sub-recess **8072**, and the fixing protrusion **903** includes the first fixed boss **9031** and a second fixing boss **9032**. The first fixing boss **9031** is disposed in the first fixing sub-recess **8071**, and the second fixing boss **9032** is disposed in the second fixing sub-recess **8072**. The stability of the limit assembly **80** is ensured by matching the plurality of fixing protrusions and fixing recesses.

(126) In some embodiments, the wrap assembly **90** includes the fixing recess, and the limit assembly **80** includes the fixing protrusion, which are not limited in the present disclosure.

(127) Referring to FIG. **21**, the wrap assembly **90** further includes four shield blocks **904**. Two of the four shield blocks **904** are arranged in the first direction **a**, and are respectively connected to two side faces of one of the two rotation wrap plates **902**. The other two of the four shield blocks **904** are arranged in the first direction **a**, and are respectively connected to two ends of the other of the two rotation wrap plates **902**. In the first direction **a**, the first support assembly **50** is disposed between the two of the four shield blocks **904**, and is disposed between the other two of the four shield blocks **904**.

(128) In the embodiments of the present disclosure, the four shield blocks **904** shield two sides of the support structure, such that the aesthetic of the display device is ensured after the support structure and the flexible display panel are disposed.

(129) In some embodiments, the shield block **904** and the rotation wrap plate **902** are fixed together by welding.

(130) Referring to FIG. **1** and FIG. **2**, the wrap assembly **90** includes two rotation shaft wrap members **905**. The two rotation shaft wrap members **905** are arranged in the first direction **a**, one of the two rotation shaft wrap members **905** is disposed between the two of the four shield blocks **904**, and the other of the two rotation shaft wrap members **905** is disposed between the other two of the four shield blocks **904**. The two rotation shaft wrap members **905** shield the end portion of the rotation shaft **10** to avoid affecting the aesthetic.

(131) FIG. **22** is a schematic structural diagram of a rotation shaft wrap member according to some embodiments of the present disclosure. Referring to FIG. **22**, a middle portion of the rotation shaft wrap member **905** includes two rotation shaft mounting recesses **9051**.

(132) FIG. **23** is a schematic structural diagram of assembling a rotation shaft wrap member and a rotation shaft in a not bent status according to some embodiments of the present disclosure. Referring to FIG. **23**, the end portion of the rotation shaft is disposed in the rotation shaft mounting recess **9051**, and the rotation shaft mounting recesses **9051** and the rotation shaft **10** are in interference fit, such that the robustness of the connection of the rotation shaft wrap member **905** and the rotation shaft **10** is ensured.

(133) FIG. **24** is a schematic structural diagram of assembling a rotation shaft wrap member and a rotation shaft in a bent status according to some embodiments of the present disclosure. Referring to FIG. **24**, an outer surface of the rotation shaft wrap member **905** is in an arc-shaped. In the case that the support structure is bent along with the flexible display panel, the outer surface of the rotation shaft wrap member **905** and the flexible display panel transition smoothly, such that the display device is aesthetic.

(134) In the embodiments of the present disclosure, the support structure includes two rotation shafts **10**, and thus, the rotation shaft wrap member **905** includes two rotation shaft mounting recesses **9051**. In some embodiments, the support structure includes one rotation shaft **10**, and thus, the rotation shaft wrap member **905** includes one rotation shaft mounting recess **9051**.

(135) In the embodiments of the present disclosure, the two rotation shafts **10** are connected by a gear assembly for the synchronous-transfer of the two rotation shafts **10**.

(136) FIG. **25** is a schematic structural diagram of a gear assembly according to some embodiments of the present disclosure. Referring to FIG. **25**, the support structure further includes: a gear plate **110**, a first transmission gear **120**, a second transmission gear **130**, a first synchronous gear **140**, and a second synchronous gear **150**. A mounting face of the gear plate **110** is parallel to the third

direction c, the gear plate **110** is detachably connected to the middle wrap plate **901**. In the first direction a, the gear plate **110** is disposed on end portions, on a same side, of the two rotation shafts. The first transmission gear **120** is connected to the mounting face of the gear plate **110**, and a rotation center of the first transmission gear **120** is parallel to the first direction a. The second transmission gear **130** is connected to the mounting face of the gear plate **110**, and the second transmission gear **130** is engaged with the first transmission gear **120**. The first synchronous gear **140** is engaged with the first transmission gear **120**, and the first synchronous gear **140** is sleeved onto one of the two rotation shafts **10**. The second synchronous gear **150** is engaged with the second transmission gear **120**, and the second synchronous gear **150** is sleeved onto the other of the two rotation shafts **10**.

(137) The mounting face of the gear plate **110** is a face, facing away from the chain **40** (not shown in FIG. 25, and referred to the position relationship in FIG. 32), of the gear plate **110**.

(138) In the embodiments of the present disclosure, the support structure includes two rotation shafts **10**, and the synchronous-transfer of the two rotation shafts **10** is achieved by the first transmission gear **120**, the second transmission gear **130**, the first synchronous gear **140**, and the second synchronous gear **140**. The first synchronous gear **140** is sleeved onto one of the two rotation shafts **10**, the rotation shaft **10** rotates to drive the rotation of the first synchronous gear **140**, the first synchronous gear **140** drives the rotation of the first transmission gear **120**, the first transmission gear **120** drives the rotation of the second transmission gear **130**, the second transmission gear **130** drives the rotation of the second synchronous gear **150**, and the second synchronous gear **150** is sleeved onto the other of the two rotation shafts **10**, such that the other of the two rotation shafts **10** rotates, and the synchronous-transfer of the two rotation shafts **10** is achieved.

(139) Referring to FIG. 25, the support structure further includes two mounting plates **160**. The two mounting plates **160** and the gear plate **110** are arranged side by side. One of the two mounting plates **160** is fixedly connected to an outer wall of the first synchronous gear **140**, and is connected to one of the at least two rotation plates **20**. The other of the two mounting plates **160** is fixedly connected to an outer wall of the second synchronous gear **150**, and is connected to the other of the at least two rotation plates **20**. Two rotation plates **20** connected to the at least two mounting plates are disposed on an end portion, on a same side, of the rotation shaft **10**.

(140) In the embodiments of the present disclosure, the two mounting plates **160** are respectively configured to dispose the first synchronous gear **140** and the second synchronous gear **150**, and the two mounting plates **160** are driven to rotate in the rotation of the first synchronous gear **140** and the second synchronous gear **150**. The two mounting plates **160** are respectively connected to the two rotation plates **20**, and the two rotation plates **20** are further driven to rotate, such that the bending and flatting of the support structure are achieved.

(141) Referring to FIG. 25, the mounting plate **160** includes two mounting holes **1601**, and the mounting plate **160** is connected to the rotation plate **20**, for example, by a second screw **1602**.

(142) Referring to FIG. 21, the middle wrap plate **901** includes a third limit protrusion **9011**.

Referring to FIG. 25, a middle portion of the gear plate **110** includes a third limit recess **1101**.

(143) FIG. 26 is a locally schematic structural diagram of a support structure according to some embodiments of the present disclosure. Referring to FIG. 26, the third limit protrusion **9011** is disposed in the third limit recess **1101**.

(144) In the embodiments of the present disclosure, a length of the middle wrap plate **901** is greater, and thus, two ends of the middle wrap plate **901** are prone to cocking. As the third limit protrusion **9011** is disposed in the middle wrap plate **901**, and the third limit protrusion **9011** is disposed in the third limit recess **1101**, in the case that the middle wrap plate **901** is prone to cocking, the third limit protrusion **9011** blocks on the bottom face of the third limit recess **1101** to prevent the middle wrap plate **901** from cocking.

(145) FIG. 27 is a schematic structural diagram of a rotation plate according to some embodiments

of the present disclosure. Referring to FIG. 27, the rotation plate **20** includes a first waist-shaped hole **203**, a sector-shaped recess **204**, and a second waist-shaped hole **205** that are spaced apart in the first direction. Both a length direction of the first waist-shaped hole **203** and a length direction of the second waist-shaped hole **205** are the second direction **b**. A center point of the sector-shaped recess **204** is in a side, proximal to the second waist-shaped hole **205**, of the sector-shaped recess **204**, an arc face of the sector-shaped groove **204** is in a side, proximal to the first waist-shaped hole **203**, of the sector-shaped recess **204**, a side, proximal to the center point, of the sector-shaped recess **204** includes a circle-shaped hole **2041**, and a side, proximal to the arc face, of the sector-shaped recess **204** includes a slide hole **2042** with the same extension direction as the arc face. A center point of the circle-shaped hole **2041**, a center point of the sector-shaped recess **204**, and a center of the arc face are in a same line. The line is a central symmetry axis of the first waist-shaped hole **203**, and the line is also a central symmetry axis of the second waist-shaped hole **205**.

(146) FIG. 27 shows a rotation plate on one side of the rotation shaft. FIG. 28 is a schematic structural diagram of a rotation plate according to some embodiments of the present disclosure, and shows a rotation plate on the other side of the rotation shaft.

(147) Referring to FIG. 27 and FIG. 28, a side edge of the rotation plate **20** includes a plurality of rotation plate protrusions **206**, and the plurality of rotation plate protrusions **206** include rotation plate through holes **2061** extending in the first direction **a**. The rotation plate through holes **2061** is used for the rotation shaft **10** passing through, such that the rotation plate **20** is connected to the rotation shaft **10**.

(148) Referring to FIG. 27 and FIG. 28, a side edge of the rotation plate **20** includes a gear fixing hole **207**, the second screw **1602** passes through the gear fixing hole **207** to connect to the mounting hole **1601**, such that the mounting plate **160** is connected to the rotation plate **20**.

(149) Referring to FIG. 16, the support structure further includes a plurality of slide blocks **190** and a rotation rod **210**. A bottom face of any of the plurality of slide blocks **190** is disposed in a waist-shaped recess of one of the first waist-shaped hole **203** and the second waist-shaped hole **205**, and each of the first waist-shaped hole **203** and each of the second waist-shaped hole **205** include one slide block **190**. As the support structure includes four rotation plates **20**, and each rotation plate **20** includes one first waist-shaped hole **203** and one second waist-shaped hole **205**, the support structure includes eight slide blocks **190**.

(150) FIG. 29 is a schematic structural diagram of a slide block according to some embodiments of the present disclosure. Referring to FIG. 29, the slide block **190** is in waist-shaped, but a size of the slide block **190** is less than a size of the waist-shaped recess (**301** and **302** in FIG. 31), such that the slide block **190** is capable of sliding in the waist-shaped recess.

(151) FIG. 30 is a schematic structural diagram of a rotation rod according to some embodiments of the present disclosure. Referring to FIG. 30, the rotation rod **210** includes a body rod **2101**, a first protrusion **2102**, a second protrusion **2103**, and a third protrusion **2104**. The first protrusion **2102** and the second protrusion **2103** are disposed on a same side of the body rod **2101**, the first protrusion **2102** and the second protrusion **2103** are respectively disposed on two ends of the body rod **2101**, and the third protrusion **2104** is disposed on the other side of the body rod **2101**.

(152) In conjunction with FIG. 16, FIG. 27, and FIG. 28, the first protrusion **2102** is disposed in the circle-shaped hole **2041**, and the second protrusion **2103** is disposed in the slide hole **2042**.

(153) FIG. 31 is a schematic structural diagram of a support structure according to some embodiments of the present disclosure in another view. Referring to FIG. 31, a face, opposite to the rotation plate **20**, of the shift plate **30** includes first waist-shaped recesses **301** in one to one correspondence to the first waist-shaped holes **203**, and second waist-shaped recesses **302** in one to one correspondence to the second waist-shaped holes **205**. Sizes of the first waist-shaped recess **301** and the second waist-shaped recess **302** are slightly greater than the size of the slide block, but the sizes of the first waist-shaped recess **301** and the second waist-shaped recess **302** are less than sizes of the first waist-shaped hole **203** and the second waist-shaped hole **205**. A surface of any of

the plurality of slide blocks **190** is disposed in one of the first waist-shaped recess **301** and the second waist-shaped recess **302**. The shift plate **30** further includes third waist-shaped holes **303** in one to one correspondence to the sector-shaped recesses **204**. A length direction of the third waist-shaped hole **303** is coincident with the first direction **a**, and the third protrusion **2104** is disposed in the third waist-shaped hole **303**. As such, the shift plate **30** is connected to the rotation plate **20** by the slide block **190** and the rotation rod **210**, and in the rotation of the rotation plate **20**, the slide block **190** rotates in the first waist-shaped hole **203** or the second waist-shaped hole **205** to drive the rotation of the shift plate **30**.

(154) FIG. **32** is an exploded schematic structural diagram of a support structure according to some embodiments of the present disclosure. Referring to FIG. **32**, the support structure further includes a slide plate **200**. The slide plate **200** is slidably connected to the shift plate **30**, and is configured to improve the support property of the support structure.

(155) As shown in FIG. **32**, one rotation shaft **10** is composed of a plurality of rotation sub-shafts. FIG. **32** merely shows two rotation sub-shafts, and the two rotation sub-shafts **1000** are separated. FIG. **32** does not show middle limit assembly **80** and the rotation sub-shaft connected to the limit assembly **80**.

(156) Referring to FIG. **3**, two sides of the slide plate **200** include slide ways **2001**, and two slide ways **2001** are respectively slidably connected to the two sides of the shift plate **30**.

(157) In conjunction with FIG. **13**, FIG. **16**, and FIG. **30**, a surface of the slide plate **200** includes a fourth waist-shaped hole **2002**. The second protrusion **2103** passes through the slide hole **2042** and the fourth waist-shaped hole **2002**, such that the slide plate **200** does not slide out of the shift plate **30**.

(158) FIG. **33** is a schematic structural diagram of a support structure according to some embodiments of the present disclosure in another view. Referring to FIG. **33**, the support structure further includes two shield plates **220**. The two shield plates **220** covers two sides of the shift plate **30** to shield the shift plate **30**.

(159) Referring to FIG. **33**, the support structure further includes two support plates **230**. The two support plates **230** are respectively connected to the two shift plates **30**, and support the flexible display panel in other regions.

(160) FIG. **34** is a schematic structural diagram of a support structure according to some embodiments of the present disclosure in another view. Referring to FIG. **34**, the support plate **230** is connected to the shift plate **30** by a stud **240**.

(161) FIG. **35** is a schematic structural diagram of a support structure according to some embodiments of the present disclosure in another view. Referring to FIG. **35**, the support structure further includes a rear shell **250** configured to shield the support plate **230**, the shift plate **30**, and the stud **240**.

(162) Referring to FIG. **34** and FIG. **35**, a periphery of the support structure includes a turn of fixing plate **260** configured to protect the periphery of the rear shell **250** and reduce the possibility of damaging the periphery of the rear shell **250**.

(163) The embodiments of the present disclosure further provide a display device. The display device includes a flexible display panel and above support structure. The flexible display panel includes a bendable display region, the support structure is disposed on a back face of the flexible display panel, and the rotation shaft is opposite to the bendable display region.

(164) In the embodiments of the present disclosure, the display device is an organic light-emitting diode (OLED) display device, or a quantum dot light-emitting diodes (QLED) display device.

(165) In some embodiments, the display device is an outward bend display device.

(166) In actual application, the display device in the embodiments of the present disclosure is any product or components with display functions, such as a mobile phone, a tablet computer, a television, a monitor, a laptop computer, a digital photo frame, a navigator, and the like.

(167) Described above are example embodiments of the present disclosure, and are not intended to

limit the present disclosure. Any modifications, equivalent replacements, improvements and the like made within the spirit and principles of the present disclosure should be included within the scope of protection of the present disclosure.

Claims

1. A support structure, configured to support a flexible display panel, the support structure comprising: a rotation shaft; two slidable connection mechanisms, wherein the two slidable connection mechanisms are rotatably connected to the rotation shaft, disposed on two sides of the rotation shaft, and configured to support an unbendable display region of the flexible display panel; at least two chains, wherein the at least two chains are spaced apart in an axial direction of the rotation shaft, extension directions of the at least two chains are perpendicular to the axial direction of the rotation shaft, middle portions of the at least two chains are connected to the rotation shaft, and two ends of each of the at least two chains are respectively connected to the two slidable connection mechanisms; and at least one first support assembly, wherein in the axial direction of the rotation shaft, each of the at least one first support assembly is connected between two adjacent chains of the at least two chains, and a surface, distal from the rotation shaft, of the at least one first support assembly and a surface, distal from the rotation shaft, of the chain are configured to support a bendable display region of the flexible display panel; wherein the at least one first support assembly comprises a plurality of first supports juxtaposed in the extension direction of the chain, wherein any two adjacent first supports of the plurality of first supports are rotatably connected, and a rotation centerline is parallel to the axial direction of the rotation shaft; and each of the plurality of first supports extends along the axial direction of the rotation shaft; wherein in the any two adjacent first supports of the plurality of first supports, an outer sidewall, facing towards the other first support, of one first support comprises a first recess, and the other first support comprises a first protrusion disposed in the first recess, wherein the first protrusion is rotatably connected to the first recess.

2. The support structure according to claim 1, further comprising: a first connection pin, wherein a middle portion of the first connection pin is fixedly connected to the chain, and one end of the first connection pin is fixedly connected to an end portion of the first support.

3. The support structure according to claim 1, further comprising: two second support assemblies, wherein in the axial direction of the rotation shaft, each of the at least two chains is disposed between the two second support assemblies, an end of one of the two second support assemblies is connected to a side face of one, proximal to one end of the rotation shaft, of the at least two chains, and an end of the other of the two second support assemblies is connected to a side face of one, proximal to the other end of the rotation shaft, of the at least two chains, wherein the side face of the chain is a face, facing towards an end portion of proximal rotation shaft, of the chain.

4. The support structure according to claim 3, wherein the second support assembly comprises two pairs of supports, wherein the two pairs of supports are spaced apart in the extension direction of the chain, each of the two pairs of supports comprises two second supports juxtaposed in the extension direction of the chain, and one end portion of each of the two second supports is connected to the side face of the chain; and outer sidewalls of the two second supports comprise second protrusions, wherein the outer sidewalls of the two second supports comprising the second protrusions are opposite to each other, and the second protrusions of the two second supports are rotatably connected.

5. The support structure according to claim 1, wherein the two slidable connection mechanisms comprise: at least two rotation plates respectively disposed on the two sides of the rotation shaft and rotatably connected to the rotation shaft; and at least one pair of shift plates, wherein each of the at least one pair of shift plates comprises two spaced-apart shift plates, and different pairs of shift plates are spaced apart in the axial direction of the rotation shaft; wherein any one of the at

least two rotation plates is opposite to one shift plate, the shift plate is slidably connected to an opposite rotation plate, and a slide direction of the shift plate is perpendicular to the axial direction of the rotation shaft.

6. The support structure according to claim 5, further comprising: a limit assembly, wherein the limit assembly is disposed between two shift plates of one pair of shift plates, one end of the limit assembly is abutted against a side face of at least one of the at least two rotation plates, and a middle portion of the limit assembly is fixedly connected to the rotation shaft; an end face of the other end of the limit assembly comprises a plurality of first limit protrusions, wherein the plurality of first limit protrusions are circumferentially spaced apart, and a first limit recess is formed between two adjacent first limit protrusions; and a side face of the rotation plate abutted against the other end of the limit assembly comprises a plurality of second limit protrusions, wherein the plurality of second limit protrusions are circumferentially spaced apart, a second limit recess is formed between two adjacent second limit protrusions, and a centerline of the rotation shaft connected to the rotation plate and a centerline of a circumference of the plurality of second limit protrusions are collinear; wherein the first limit protrusion is disposed in the second limit recess, and the second limit protrusion is disposed in the first limit recess, or the first limit protrusion is abutted against the second limit protrusion.

7. The support structure according to claim 6, wherein the limit assembly comprises: a first stopper, wherein the first limit protrusion is disposed on one end face, facing towards the rotation plate, of the first stopper; a second stopper spaced apart from the first stopper in the axial direction of the rotation shaft; an elastic member, wherein one end of the elastic member is connected to the other end face of the first stopper, and the other end of the elastic member is connected to one end face of the second stopper; and a mounting block connected to the other end face of the second stopper and fixedly connected to the rotation shaft.

8. The support structure according to claim 7, further comprising: a wrap assembly extending in the axial direction of the rotation shaft; and a rotation shaft connection block fixedly connected to a middle portion of the wrap assembly and comprising a first rotation shaft through hole for the rotation shaft passing through; wherein in a third direction, the limit assembly is disposed between the at least one first support assembly and the wrap assembly, the third direction is perpendicular to the axial direction of the rotation shaft and the extension direction of the chain, and the wrap assembly is connected to the limit assembly.

9. The support structure according to claim 8, wherein the wrap assembly comprises: a middle wrap plate extending in the axial direction of the rotation shaft, wherein the rotation shaft connection block is connected to a surface of the middle wrap plate; two rotation wrap plates extending in the axial direction of the rotation shaft, wherein in the extension direction of the chain, the two rotation wrap plates are respectively disposed on two sides of the middle wrap plate, and the two rotation wrap plates are rotatably connected to the middle wrap plate respectively; and a fixing protrusion connected to the surface of the middle wrap plate, wherein the rotation shaft connection block and the fixing protrusion are connected to the same surface of the middle wrap plate, and the fixing protrusion comprises a first fixing boss; wherein the mounting block comprises a fixing recess, and the first fixing boss is disposed in the fixing recess.

10. The support structure according to claim 9, the wrap assembly further comprises: four shield blocks, wherein two of the four shield blocks are arranged in the axial direction of the rotation shaft and are respectively connected to two ends of one of the two rotation wrap plates, the other two of the four shield blocks are arranged in the axial direction of the rotation shaft and are respectively connected to two ends of the other of the two rotation wrap plates, and in the axial direction of the rotation shaft, the at least one first support assembly is disposed between the two of the four shield blocks and is disposed between the other two of the four shield blocks.

11. The support structure according to claim 9, comprising two rotation shafts; a gear plate, wherein a mounting face of the gear plate is parallel to the third direction, the gear plate is

detachably connected to the middle wrap plate, and in the axial direction of the rotation shaft, the gear plate is disposed on end portions, on a same side, of the two rotation shafts, wherein the mounting face of the gear plate is a face, facing away from the chain, of the gear plate; a first transmission gear, wherein the first transmission gear is rotatably connected to the mounting face of the gear plate, and a rotation center of the first transmission gear is parallel to the axial direction of the rotation shaft; a second transmission gear, wherein the second transmission gear is rotatably connected to the mounting face of the gear plate, and the second transmission gear is engaged with the first transmission gear; a first synchronous gear, wherein the first synchronous gear is engaged with the first transmission gear, and the first synchronous gear is sleeved onto one of the two rotation shafts; and a second synchronous gear, wherein the second synchronous gear is engaged with the second transmission gear, and the second synchronous gear is sleeved onto the other of the two rotation shafts.

12. The support structure according to claim 11, further comprising: at least two mounting plates, wherein one of the at least two mounting plates is fixedly connected to an outer wall of the first synchronous gear and is connected to one of the at least two rotation plates, the other of the at least two mounting plates is fixedly connected to an outer wall of the second synchronous gear and is connected to the other of the at least two rotation plates, and two rotation plates connected to the at least two mounting plates are disposed on an end portion, on a same side, of the rotation shaft.

13. The support structure according to claim 1, further comprising: an elevator assembly, wherein one end of the elevator assembly is connected to the middle portion of the chain, the other end of the elevator assembly is connected to the rotation shaft, and the elevator assembly is configured to change a distance between the middle portion of the chain and the rotation shaft.

14. The support structure according to claim 13, wherein the elevator assembly comprises: a first connection block, wherein the first connection block comprises a second rotation shaft through hole, a middle portion of the rotation shaft is disposed in the second rotation shaft through hole, and the first connection block comprises a protrusion through hole; a second connection block, wherein the second connection block comprises a connection pin through hole, a part of the second connection block is disposed in the protrusion through hole, another part of the second connection block is disposed outside the protrusion through hole, the second connection block is slidably connected to the first connection block, and a slide direction of the second connection block is perpendicular to the axial direction of the rotation shaft and the extension direction of the chain; a second connection pin, wherein one end of the second connection pin is connected to the middle portion of the chain, and the other end of the second connection pin is connected to the connection pin through hole; and an elastic plate, wherein one end of the elastic plate is connected to the first connection block, and the other end of the elastic plate is connected to the second connection block.

15. The support structure according to claim 5, wherein the chain comprises: a first link, wherein one end of the first link is connected to one shift plate of the one pair of shift plates; and a plurality of second links, wherein the plurality of second links are sequentially rotatably connected, second links, on one end, of the plurality of second links are connected to the other end of the first link, and second links, on the other end, of the plurality of second links are connected to the other shift plate of the one pair of shift plates; wherein both the first link and the second link comprise a first limit face and a second limit face, and the second link further comprises a third limit face and a fourth limit face, wherein the first limit face is attached to the third limit face in the case that the support structure is not bent, and the second limit face is attached to the fourth limit face in the case that the support structure is in a maximally bending status.

16. The support structure according to claim 5, comprising: four chains and three first support assemblies, wherein the four chains are spaced apart in the axial direction of the rotation shaft, the three first support assemblies are disposed between two adjacent chains of the four chains, and the three first support assemblies are disposed between different two adjacent chains.

17. The support structure according to claim 16, wherein the two slidable connection mechanisms

comprise: four rotation plates and one pair of shift plates, wherein two of the four rotation plates are disposed on one side end portion of the rotation shaft, and are respectively disposed on the two sides of the rotation shaft; the other two of the four rotation plates are disposed on the other side end portion of the rotation shaft, and are respectively disposed on the two sides of the rotation shaft; and one shift plate of the one pair of shift plates is connected to one end of each of the four chains, and the other shift plate of the one pair of shift plates is connected to the other end of each of the four chains.

18. A display device, comprising: a flexible display panel and a support structure, wherein the support structure comprises: a rotation shaft; two slidable connection mechanisms, wherein the two slidable connection mechanisms are rotatably connected to the rotation shaft, disposed on two sides of the rotation shaft, and configured to support an unbendable display region of the flexible display panel; at least two chains, wherein the at least two chains are spaced apart in an axial direction of the rotation shaft, extension directions of the at least two chains are perpendicular to the axial direction of the rotation shaft, middle portions of the at least two chains are connected to the rotation shaft, and two ends of each of the at least two chains are respectively connected to the two slidable connection mechanisms; and at least one first support assembly, wherein in the axial direction of the rotation shaft, each of the at least one first support assembly is connected between two adjacent chains of the at least two chains, and a surface, distal from the rotation shaft, of the at least one first support assembly and a surface, distal from the rotation shaft, of the chain are configured to support a bendable display region of the flexible display panel; wherein the at least one first support assembly comprises a plurality of first supports juxtaposed in the extension direction of the chain, wherein any two adjacent first supports of the plurality of first supports are rotatably connected, and a rotation centerline is parallel to the axial direction of the rotation shaft; and each of the plurality of first supports extends along the axial direction of the rotation shaft; wherein in the any two adjacent first supports of the plurality of first supports, an outer sidewall, facing towards the other first support, of one first support comprises a first recess, and the other first support comprises a first protrusion disposed in the first recess, wherein the first protrusion is rotatably connected to the first recess; and the flexible display panel comprises the bendable display region, the support structure is disposed on a back face of the flexible display panel, and the rotation shaft is opposite to the bendable display region.
