

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412116
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Coady; Stephen et al.

Push notification qubit manipulation

Abstract

Performing qubit manipulation using push notifications is disclosed herein. In one example, a quantum computing device comprises a system memory and a processor device communicatively coupled to the system memory. The processor device is to receive a push notification that includes an identifier of a qubit and a push notification payload, such as a data value to be written to the qubit and/or one or more qubit manipulation commands to be performed using the qubit. Upon receiving the push notification, the processor device obtains write access to the qubit, and then applies the push notification payload to the qubit, for example by writing the data value to the qubit and/or by executing the one or more qubit manipulation commands using the qubit.

Inventors:	Coady; Stephen (Waterford, IE), Griffin; Leigh (Waterford, IE)
Applicant:	Red Hat, Inc. (Raleigh, NC)
Family ID:	86146330
Assignee:	Red Hat, Inc. (Raleigh, NC)
Appl. No.:	17/513308
Filed:	October 28, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230133503 A1	May. 04, 2023

Publication Classification

Int. Cl.: G06N10/80 (20220101); G06N10/20 (20220101); G06N10/40 (20220101)

U.S. Cl.:

Field of Classification Search**USPC:** None**References Cited****U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7518120	12/2008	Monroe et al.	N/A	N/A
8386899	12/2012	Goto et al.	N/A	N/A
8897449	12/2013	Broadbent	N/A	N/A
10826845	12/2019	Dadashikelayeh et al.	N/A	N/A
2015/0163178	12/2014	Jeon	709/206	H04L 67/55
2017/0093943	12/2016	Alsina	N/A	H04L 67/55
2019/0042264	12/2018	Zou	N/A	G06F 9/30
2019/0179730	12/2018	Geller	N/A	G06F 11/3698
2021/0112130	12/2020	LeClair et al.	N/A	N/A
2021/0390439	12/2020	Ramasamy	N/A	G06N 10/60
2022/0405626	12/2021	Naveh	N/A	G06N 10/00
2023/0034075	12/2022	Griffin	N/A	G06N 10/00
2023/0129967	12/2022	Oh	706/62	G06N 10/80
2023/0139281	12/2022	Coady	716/100	G06F 12/0246
2023/0196175	12/2022	Griffin	706/62	G06F 9/4868
2023/0244972	12/2022	Griffin	706/62	G06N 10/80
2024/0020561	12/2023	Coady	N/A	G06N 10/20

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2021055999	12/2020	WO	N/A

OTHER PUBLICATIONS

Aharonov, D. et al., “Interactive Proofs for Quantum Computations,” arXiv:1704.04487v1 [quant-ph], Apr. 14, 2017, 75 pages. cited by applicant

Han, J. et al., “Enhancing Data and Privacy Security in Mobile Cloud Computing through Quantum Cryptography,” 7th IEEE International Conference on Software Engineering and Service Science (ICSESS), Aug. 26-28, 2016, Beijing, China, IEEE, pp. 398-401. cited by applicant

Primary Examiner: Barrett; Ryan

Attorney, Agent or Firm: Dority & Manning, P.A.

Background/Summary

BACKGROUND

(1) Quantum computing involves the use of quantum bits, referred to herein as “qubits,” which have characteristics that differ from those of classical (i.e., non-quantum) bits used in classical computing. Qubits may be employed by quantum services that are executed by quantum computing devices. As quantum computing continues to increase in popularity and become more commonplace, an ability to efficiently manipulate and configure qubits will be desirable.

SUMMARY

(2) The examples disclosed herein implement a push notification service for performing qubit manipulation using push notifications. The push notification service, executing on a quantum computing device, receives a push notification that identifies a qubit and includes a push notification payload, and, in response, applies the push notification payload to the qubit. In this manner, a data value and/or a quantum state of the qubit may be manipulated or configured to prepare the qubit for use and/or to propagate a result of a previous quantum operation.

(3) In one example, a method for performing qubit manipulation using push notifications is disclosed. The method comprises receiving, by a first quantum computing device, a push notification comprising an identifier of a qubit and a push notification payload. The method further comprises obtaining write access to the qubit. The method also comprises applying the push notification payload to the qubit.

(4) In another example, a computing system comprising a first quantum computing device for performing qubit manipulation using push notifications is disclosed. The quantum computing device comprises a first system memory and a first processor device communicatively coupled to the first system memory. The first processor device is to receive a push notification comprising an identifier of a qubit and a push notification payload. The first processor device is further to obtain write access to the qubit. The first processor device is also to apply the push notification payload to the qubit.

(5) In another example, a non-transitory computer-readable medium is disclosed. The non-transitory computer-readable medium stores thereon computer-executable instructions that, when executed, cause one or more processor devices receive a push notification comprising an identifier of a qubit and a push notification payload. The computer-executable instructions further cause the one or more processor devices to obtain write access to the qubit. The computer-executable instructions further cause the one or more processor devices to apply the push notification payload to the qubit.

(6) Individuals will appreciate the scope of the disclosure and realize additional aspects thereof after reading the following detailed description of the examples in association with the accompanying drawing figures.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawing figures incorporated in and forming a part of this specification illustrate several aspects of the disclosure and, together with the description, serve to explain the principles of the disclosure.

(2) FIG. 1 is a block diagram of a computing system in which examples may be practiced;

(3) FIGS. 2A-2B are flowcharts illustrating operations performed by the computing system of FIG. 1 for performing qubit manipulation using push notifications, according to one example;

(4) FIG. 3 is a simpler block diagram of the computing system of FIG. 1 for performing qubit manipulation using push notifications, according to one example;

(5) FIG. 4 is a flowchart of a simplified method for performing qubit manipulation using push

notifications by the quantum computing device of FIG. 3, according to one example;
(6) FIG. 5 is a block diagram of a quantum computing device suitable for implementing examples, according to one example; and
(7) FIG. 6 is a block diagram of a classical computing device suitable for implementing examples, according to one example.

DETAILED DESCRIPTION

(8) The examples set forth below represent the information to enable individuals to practice the examples and illustrate the best mode of practicing the examples. Upon reading the following description in light of the accompanying drawing figures, individuals will understand the concepts of the disclosure and will recognize applications of these concepts not particularly addressed herein. It should be understood that these concepts and applications fall within the scope of the disclosure and the accompanying claims.

(9) Any flowcharts discussed herein are necessarily discussed in some sequence for purposes of illustration, but unless otherwise explicitly indicated, the examples are not limited to any particular sequence of steps. The use herein of ordinals in conjunction with an element is solely for distinguishing what might otherwise be similar or identical labels, such as “first qubit” and “second qubit,” and does not imply a priority, a type, an importance, or other attribute, unless otherwise stated herein. The term “about” used herein in conjunction with a numeric value means any value that is within a range of ten percent greater than or ten percent less than the numeric value. As used herein and in the claims, the articles “a” and “an” in reference to an element refers to “one or more” of the element unless otherwise explicitly specified. The word “or” as used herein and in the claims is inclusive unless contextually impossible. As an example, the recitation of A or B means A, or B, or both A and B.

(10) Quantum computing involves the use of quantum bits, referred to herein as “qubits,” which have characteristics that differ from those of classical (i.e., non-quantum) bits used in classical computing. Qubits may be employed by quantum services that are executed by quantum computing devices. As quantum computing continues to increase in popularity and become more commonplace, an ability to efficiently manipulate and configure qubits will be desirable. In particular, it may be desirable to provide “push” functionality for modifying data values and/or quantum states of qubits to, e.g., prepare the qubits for use in quantum operations, or to propagate a result of a quantum operation using another set of qubits.

(11) In this regard, the examples disclosed herein implement a push notification service for performing qubit manipulation using push notifications. As used herein, the term “push notification” and derivatives thereof are used to refer to a message transmitted from a sender to one or more recipients not as a result of the recipient(s) specifically requesting the transmission, but rather as a result of the recipient subscribing to receive the message at some point in the future. In exemplary operation, the push notification service, executing on a quantum computing device, receives a push notification that includes an identifier of a qubit as well as a push notification payload. The push notification payload may comprise, as non-limiting examples, a data value to be written to the qubit, and/or one or more qubit manipulation commands to be executed using the qubit (e.g., commands for entangling the qubit or setting a quantum state of the qubit). The push notification may be generated and transmitted by another quantum computing device based on a result of a previous quantum operation, or may be generated and transmitted by a classical computing device based on input data (e.g., data values to be stored or qubit manipulation operations to be performed using the qubit).

(12) Upon receiving the push notification, the push notification service obtains write access to the qubit, and then applies the push notification payload to the qubit. In examples in which the push notification payload includes a data value to be written to the qubit, applying the push notification payload to the qubit may comprise obtaining the data value from the push notification payload, and then writing the data value to the qubit. Examples in which the push notification payload includes

one or more qubit manipulation commands may provide that applying the push notification payload to the qubit comprises obtaining the one or more qubit manipulation commands from the push notification payload, and then executing the one or more qubit manipulation commands using the qubit.

(13) Some examples may further provide that, after applying the push notification payload to the qubit, the quantum computing device may subsequently execute a quantum service to which the qubit is allocated. In this manner, the push notification service may be used to initialize or pre-configure the qubit for use by the quantum service, and may also enable multiple quantum services to be “daisy-chained,” with the results of one quantum service being pushed into qubits in preparation for further quantum computations by another quantum service.

(14) FIG. 1 is a block diagram of a computing system **10** according to one example. The computing system **10** includes a quantum computing device **12** that comprises a system memory **14** and a processor device **16**; a quantum computing device **18** that comprises a system memory **20** and a processor device **22**; and a classical computing device **24** that comprises a system memory **26** and a processor device **28**. The quantum computing device **12**, the quantum computing device **18**, and the classical computing device **24** in the example of FIG. 1 are all communicatively coupled via a classical communications link (not shown), which may comprise a private network or a public network such as the internet. The quantum computing device **12** and the quantum computing device **18** may also be communicatively coupled via a quantum channel (not shown) over which qubits may be transmitted. It is to be understood that the computing system **10**, according to some examples, may include more or fewer quantum computing devices and/or classical computing devices than illustrated in FIG. 1. Additionally, the quantum computing device **12**, the quantum computing device **18**, and/or the classical computing device **24** in some examples may include constituent elements in addition to those illustrated in FIG. 1.

(15) The quantum computing device **12** and the quantum computing device **18** in the example of FIG. 1 operate in quantum environments, but are capable of operating using classical computing principles or quantum computing principles. When using quantum computing principles, the quantum computing device **12** and the quantum computing device **18** perform computations that utilize quantum-mechanical phenomena, such as superposition and/or entanglement states. The quantum computing device **12** and the quantum computing device **18** may operate under certain environmental conditions, such as at or near zero degrees (0°) Kelvin. When using classical computing principles, the quantum computing device **12** and the quantum computing device **18** utilize binary digits that have a value of either zero (0) or one (1).

(16) In the example of FIG. 1, the quantum computing device **12** executes a quantum service **30**, which comprises a process that employs one or more qubits, such as a qubit **32**, to perform quantum operations to provide desired functionality. To maintain information for qubits such as the qubit **32**, the quantum computing device **12** may include a qubit registry **34**, which comprises a plurality of qubit registry entries each corresponding to a qubit such as the qubit **32**. The qubit registry **34** maintains and provides access to data relating to the qubits implemented by the quantum computing device **12**, such as a count of the total number of qubits implemented by the quantum computing device **12** and a count of the number of available qubits that are currently available for allocation, as non-limiting examples. Each of the qubit registry entries of the qubit registry **34** also stores qubit metadata for a corresponding qubit. The qubit metadata may include, as non-limiting examples, an identifier of the corresponding qubit, an availability indicator that indicates whether the corresponding qubit is available for use or is in use by a specific quantum service, an identifier of a quantum service that is associated with the corresponding qubit or to which the corresponding qubit is allocated, and/or an entanglement indicator that indicates whether the corresponding qubit is in an entangled state.

(17) Execution of quantum services such as the quantum service **30** is facilitated by a quantum task manager **36** and a quantum service scheduler **38**, which operate in a manner analogous to their

conventional classical counterparts. Thus, the quantum task manager **36** of the quantum computing device **12** handles operations for creating, monitoring, and terminating quantum services, while the quantum service scheduler **38** of the quantum computing device **12** controls the scheduling of quantum services for execution by the processor device **16**, and the allocation of processing resources to executing quantum services. The functionality of the quantum task manager **36** and the quantum service scheduler **38** may be made accessible to other services and processes (e.g., via a defined application programming interface (API), as a non-limiting example).

(18) The qubit **32** of the quantum service **30** may be used to store a data value **40**, and/or may have a quantum state **42** (e.g., spin, as a non-limiting example) into which the qubit **32** is programmatically placed. Circumstances may arise in which it is desirable to pre-configure or initialize the data value **40** and/or the quantum state **42** of the qubit **32**. For instance, the quantum service **30** may not be configured to initialize the qubit **32** itself, and/or a result value from a previous quantum operation may need to be propagated to the qubit **32** for use as input to a next quantum operation to be performed by the quantum service **30**. In this regard, the quantum computing device **12** of FIG. **1**

(19) implements a push notification service **44** for performing qubit manipulation using push notifications. The push notification service **44** in the example of FIG. **1** is communicatively coupled to the quantum task manager **36**, the quantum service scheduler **38**, and the qubit registry **34**, and thus may access data related to qubit allocation and deallocation, qubit state, the use of qubits by executing quantum services, and the current and upcoming state of executing quantum services, as non-limiting examples. The push notification service **44** may comprise a table or other appropriate data structure for tracking quantum services and/or devices, such as the quantum computing device **18** and/or the classical computing device **24**, from which the push notification service **44** is configured to receive push notifications, and to validate push notifications received by the push notification service **44**.

(20) In exemplary operation, the push notification service **44** receives a push notification **46**, which may conform to a predefined format or protocol, over a classical communications link. The push notification **46** includes an identifier **48** of a qubit (e.g., the qubit **32**) to which the push notification **46** is directed, and also includes a push notification payload **50**. The identifier **48** may comprise a unique identifier corresponding to the qubit **32**, or may comprise an identifier of the quantum service **30** to which the qubit **32** is allocated. The push notification payload **50** may comprise, as a non-limiting example, a data value **52** representing a value to be written to the qubit **32**. The push notification payload **50** may also or alternatively comprise one or more qubit manipulation commands **54** to be executed using the qubit **32**. For instance, the one or more qubit manipulation commands **54** may include a command for entangling the qubit **32**, or for setting a quantum state (e.g., spin) of the qubit **32**.

(21) In some examples, the push notification **46** may be generated and transmitted by the quantum computing device **18** based on a result **56** of a previous quantum operation carried out by the quantum computing device **18**. For example, the result **56** may comprise the data value **52** that is included as part of the push notification payload **50**, and that may serve as input for a next quantum operation to be performed by the quantum service **30**. According to some examples, the push notification **46** may be generated and transmitted by the classical computing device **24** based on input data **58**, which may comprise, for example, the data value **52** to be stored in the qubit **32** or the one or more qubit manipulation commands **54** to be performed using the qubit **32**.

(22) Upon receiving the push notification **46**, the push notification service **44** obtains write access to the qubit **32**. This may be accomplished in some examples by the push notification service **44** accessing functionality of the qubit registry **34** to determine whether the qubit **32** is in an accessible state, and/or obtaining exclusive access to the qubit **32**. In examples in which the identifier **48** comprises an identifier of the quantum service **30**, operations for obtaining write access to the qubit **32** may include operations for first identifying the qubit **32** based on the identifier of the quantum

service **30**. The push notification service **44** then applies the push notification payload **50** to the qubit **32**. Some examples in which the push notification payload **50** includes the data value **52**, operations for applying the push notification payload **50** to the qubit **32** may comprise obtaining the data value **52** from the push notification payload **50**, and then writing the data value **52** to the qubit **32**. In examples in which the push notification payload **50** includes the one or more qubit manipulation commands **54**, operations for applying the push notification payload **50** to the qubit **32** may comprise obtaining the one or more qubit manipulation commands **54** from the push notification payload **50**, and then executing the one or more qubit manipulation commands **54** using the qubit **32**.

(23) According to some examples, the quantum computing device **12**, after applying the push notification payload **50** to the qubit **32**, may subsequently execute the quantum service **30** to which the qubit **32** is allocated. The push notification service **44** thus may be used to “daisy-chain” multiple quantum services, such that the results of one quantum service are pushed into the qubit **32** in preparation for further quantum computations by the quantum service **30**.

(24) It is to be understood that, because the push notification service **44** is a component of the quantum computing device **12**, functionality implemented by the push notification service **44** may be attributed to the computing system **10** generally. Moreover, in examples where the push notification service **44** comprises software instructions that program the processor device **16** to carry out functionality discussed herein, functionality implemented by the push notification service **44** may be attributed herein to the processor device **16**. It is to be further understood that while, for purposes of illustration only, the push notification service **44** is depicted as a single component, the functionality implemented by the push notification service **44** may be implemented in any number of components, and the examples discussed herein are not limited to any particular number of components. Additionally, it is noted that while, for purposes of illustration and simplicity, the examples are illustrated as being implemented by a processor device set that includes a single processor device on a single computing device, in other environments, such as a distributed and/or clustered environment, the examples may be implemented on a computer system that includes a processor device set that includes a plurality of processor devices of a plurality of different computing devices, and functionality of the examples may be implemented on different processor devices of different computing devices. Thus, irrespective of the implementation, the examples may be implemented on a computer system that includes a processor device set made up of one or more processor devices of one or more computing devices.

(25) To illustrate exemplary operations performed by the computing system **10** of FIG. **1** for performing qubit manipulation using push notifications according to one example, FIGS. **2A** and **2B** provide a flowchart **60**. Elements of FIG. **1** are referenced in describing FIGS. **2A** and **2B** for the sake of clarity. In FIG. **2A**, operations begin in some examples with a quantum computing device (such as the quantum computing device **18** of FIG. **1**, also referred to herein as the “second quantum computing device **18**”) obtaining a result of a quantum operation (such as the result **56** of FIG. **1**) (block **62**). The second quantum computing device **18** may then generate a push notification payload (e.g., the push notification payload **50** of FIG. **1**) based on the result **56** of the quantum operation (block **64**). Some examples may provide that operations begin with a classical computing device (such as the classical computing device **24** of FIG. **1**) obtaining input data directed to a qubit (e.g., the input data **58** directed to the qubit **32** of FIG. **1**) (block **66**). The classical computing device **24** may then generate the push notification payload **50** based on the input data **58** (block **68**).

(26) The second quantum computing device **18** or the classical computing device **24**, in their respective examples above, may then generate the push notification **46** (block **70**). The second quantum computing device **18** or the classical computing device **24** may then transmit the push notification **46** to a quantum computing device (such as the quantum computing device **12** of FIG. **1**, also referred to herein as the “first quantum computing device **12**”) (block **72**).

(27) The processor device **16** of the quantum computing device **12** (e.g., by executing the push notification service **44** of FIG. **1**) receives the push notification **46** comprising an identifier (e.g., the identifier **48** of FIG. **1**) of the qubit **32** and a push notification payload (e.g., the push notification payload **50** of FIG. **1**) (block **74**). The processor device **16** next obtains write access to the qubit **32** (block **76**). This may be accomplished in some examples by accessing functionality provided by the quantum task manager **36**, the quantum service scheduler **38**, and/or the qubit registry **34** of FIG. **1**. Operations then continue at block **78** of FIG. **2B**.

(28) Referring now to FIG. **2B**, the processor device **16** applies the push notification payload **50** to the qubit **32** (block **78**). In some examples, the operations of block **78** for applying the push notification payload **50** to the qubit **32** may include the processor device **16** obtaining a data value (e.g., the data value **52**) from the push notification payload **50** (block **80**). The processor device **16** may then write the data value **52** to the qubit **32** (block **82**). Some examples may provide that the operations of block **78** for applying the push notification payload **50** to the qubit **32** comprise the processor device **16** obtaining one or more qubit manipulation commands (e.g., the qubit manipulation command(s) **54** of FIG. **1**) from the push notification payload **50** (block **84**). The processor device **16** may then execute the one or more qubit manipulation commands **54** using the qubit **32** (block **86**). In some examples, the processor device **16** may subsequently execute a quantum service (e.g., the quantum service **30** of FIG. **1**) to which the qubit **32** is allocated (block **88**).

(29) FIG. **3** is a simpler block diagram of the computing system **10** of FIG. **1** for performing qubit manipulation using push notifications, according to one example. In the example of FIG. **3**, a computing system **90** includes a quantum computing device **92** that comprises a system memory **94** and a processor device **96**. In exemplary operation, the processor device **96** receives a push notification **98**, which comprises an identifier **100** of a qubit **102** to which the push notification **98** is directed, and also includes a push notification payload **104**. Upon receiving the push notification **98**, the processor device **96** obtains write access to the qubit **102**, and then applies the push notification payload **104** to the qubit **102**.

(30) FIG. **4** provides a flowchart **106** of a simplified method for performing qubit manipulation using push notifications by the quantum computing device **92** of FIG. **3**, according to one example. For the sake of clarity, elements of FIG. **3** are referenced in describing FIG. **4**. Operations in FIG. **4** begin with the processor device **96** of the quantum computing device **92** receiving the push notification **98** comprising the identifier **100** of the qubit **102** and the push notification payload **104** (block **108**). The processor device **96** next obtains write access to the qubit **102** (block **110**). The processor device **96** then applies the push notification payload **104** to the qubit **102** (block **112**).

(31) FIG. **5** is a block diagram of a quantum computing device **114**, such as the quantum computing device **12** of FIG. **1**, suitable for implementing examples according to one example. The quantum computing device **114** may comprise any suitable quantum computing device or devices. The quantum computing device **114** can operate using classical computing principles or quantum computing principles. When using quantum computing principles, the quantum computing device **114** performs computations that utilize quantum-mechanical phenomena, such as superposition and entanglement. The quantum computing device **114** may operate under certain environmental conditions, such as at or near zero degrees (0°) Kelvin. When using classical computing principles, the quantum computing device **114** utilizes binary digits that have a value of either zero (0) or one (1).

(32) The quantum computing device **114** includes a processor device **116** and a system memory **118**. The processor device **116** can be any commercially available or proprietary processor suitable for operating in a quantum environment. The system memory **118** may include volatile memory **120** (e.g., random-access memory (RAM)). The quantum computing device **114** may further include or be coupled to a non-transitory computer-readable medium such as a storage device **122**. The storage device **122** and other drives associated with computer-readable media and computer-

usable media may provide non-volatile storage of data, data structures, computer-executable instructions, and the like. The storage device may also provide functionality for storing one or more qubits **124(0)-124(N)**.

(33) A number of modules can be stored in the storage device **122** and in the volatile memory **120**, including an operating system **126** and one or more modules, such as a push notification service **128**. All or a portion of the examples may be implemented as a computer program product **130** stored on a transitory or non-transitory computer-usable or computer-readable medium, such as the storage device **122**, which includes complex programming instructions, such as complex computer-readable program code, to cause the processor device **116** to carry out the steps described herein. Thus, the computer-readable program code can comprise computer-executable instructions for implementing the functionality of the examples described herein when executed on the processor device **116**.

(34) An operator may also be able to enter one or more manipulation commands through a keyboard (not illustrated), a pointing device such as a mouse (not illustrated), or a touch-sensitive surface such as a display device (not illustrated). The quantum computing device **114** may also include a communications interface **132** suitable for communicating with other quantum computing systems, including, in some implementations, classical computing devices.

(35) FIG. **6** is a block diagram of a processor-based computing device **134** (“computing device **134**” or “classical computing device **134**”), such as the classical computing device **24** of FIG. **1**, suitable for implementing examples according to one example. The computing device **134** may comprise any computing or electronic device capable of including firmware, hardware, and/or executing software instructions to implement the functionality described herein, such as a computer server, a desktop computing device, a laptop computing device, a smartphone, a computing tablet, or the like. The computing device **134** includes a processor device **136**, a system memory **138**, and a system bus **140**. The system bus **140** provides an interface for system components including, but not limited to, the system memory **138** and the processor device **136**. The processor device **136** can be any commercially available or proprietary processor.

(36) The system bus **140** may be any of several types of bus structures that may further interconnect to a memory bus (with or without a memory controller), a peripheral bus, and/or a local bus using any of a variety of commercially available bus architectures. The system memory **138** may include non-volatile memory **142** (e.g., read-only memory (ROM), erasable programmable ROM (EPROM), electrically EPROM (EEPROM), etc.), and volatile memory **144** (e.g., RAM). A basic input/output system (BIOS) **146** may be stored in the non-volatile memory **142** and can include the basic routines that help to transfer information among elements within the computing device **134**. The volatile memory **144** may also include a high-speed RAM, such as static RAM, for caching data.

(37) The computing device **134** may further include or be coupled to a non-transitory computer-readable storage medium such as a storage device **148**, which may comprise, for example, an internal or external hard disk drive (HDD) (e.g., enhanced integrated drive electronics (EIDE) or serial advanced technology attachment (SATA)), for storage, flash memory, or the like. The storage device **148** and other drives associated with computer-readable media and computer-usable media may provide non-volatile storage of data, data structures, computer-executable instructions, and the like. Although the description of computer-readable media above refers to an HDD, it should be appreciated that other types of media that are readable by a computer, such as Zip disks, magnetic cassettes, flash memory cards, cartridges, and the like, may also be used in the operating environment, and, further, that any such media may contain computer-executable instructions for performing novel methods of the disclosed examples.

(38) A number of modules can be stored in the storage device **148** and in the volatile memory **144**, including an operating system **150** and one or more program modules **152** which may implement the functionality described herein in whole or in part. It is to be appreciated that the examples can

be implemented with various commercially available operating systems **150** or combinations of operating systems **150**. All or a portion of the examples may be implemented as a computer program product stored on a transitory or non-transitory computer-usable or computer-readable storage medium, such as the storage device **148**, which includes complex programming instructions, such as complex computer-readable program code, to cause the processor device **136** to carry out the steps described herein. Thus, the computer-readable program code can comprise software instructions for implementing the functionality of the examples described herein when executed on the processor device **136**. The processor device **136** may serve as a controller, or control system, for the computing device **134** that is to implement the functionality described herein.

(39) An operator may also be able to enter one or more manipulation commands through a keyboard (not illustrated), a pointing device such as a mouse (not illustrated), or a touch-sensitive surface such as a display device (not illustrated). Such input devices may be connected to the processor device **136** through an input device interface **154** that is coupled to the system bus **140** but can be connected by other interfaces, such as a parallel port, an Institute of Electrical and Electronic Engineers (IEEE) 1394 serial port, a Universal Serial Bus (USB) port, an IR interface, and the like.

(40) The computing device **134** may also include a communications interface **156** suitable for communicating with a network as appropriate or desired. The computing device **134** may also include a video port **158** to interface with a display device to provide information to a user.

(41) Individuals will recognize improvements and modifications to the preferred examples of the disclosure. All such improvements and modifications are considered within the scope of the concepts disclosed herein and the claims that follow.

Claims

1. A method, comprising: receiving, by a first quantum computing device, a push notification over a quantum channel, the push notification comprising an identifier of a first qubit and a push notification payload, the push notification payload comprising a second qubit transmitted over the quantum channel; obtaining write access to the first qubit; and applying the push notification payload to the first qubit.
2. The method of claim 1, further comprising subsequently executing a quantum service to which the first qubit is allocated.
3. The method of claim 1, wherein: the push notification payload comprises one or more qubit manipulation commands; and applying the push notification payload to the first qubit comprises: obtaining the one or more qubit manipulation commands from the push notification payload; and executing the one or more qubit manipulation commands using the first qubit.
4. The method of claim 3, wherein the one or more qubit manipulation commands comprises one or more of a command for placing the first qubit into an entangled state and a command for setting a quantum state of the first qubit.
5. The method of claim 1, further comprising: obtaining, by a second quantum computing device, a result of a quantum operation; generating the push notification payload based on the result of the quantum operation; generating the push notification; and transmitting the push notification to the first quantum computing device.
6. The method of claim 1, further comprising: obtaining, by a classical computing device, input data directed to the first qubit; generating the push notification payload based on the input data; generating the push notification; and transmitting the push notification to the first quantum computing device.
7. A computing system, comprising: a first quantum computing device, comprising: a first system memory; and a first processor device communicatively coupled to the first system memory, the first

processor device to: receive a push notification over a quantum channel, the push notification comprising an identifier of a first qubit and a push notification payload, the push notification payload comprising a second qubit transmitted over the quantum channel; obtain write access to the first qubit; and apply the push notification payload to the first qubit.

8. The computing system of claim 7, wherein the first processor device is further to subsequently execute a quantum service to which the first qubit is allocated.

9. The computing system of claim 7, wherein: the push notification payload comprises one or more qubit manipulation commands; and to apply the push notification payload to the first qubit is to: obtain the one or more qubit manipulation commands from the push notification payload; and execute the one or more qubit manipulation commands using the first qubit.

10. The computing system of claim 9, wherein the one or more qubit manipulation commands comprises one or more of a command for placing the first qubit into an entangled state and a command for setting a quantum state of the first qubit.

11. The computing system of claim 7, further comprising: a second quantum computing device, comprising: a second system memory; and a second processor device communicatively coupled to the second system memory, the second processor device to: obtain a result of a quantum operation; generate the push notification payload based on the result of the quantum operation; generate the push notification; and transmit the push notification to the first quantum computing device.

12. The computing system of claim 7, further comprising: a classical computing device, comprising: a third system memory; and a third processor device communicatively coupled to the third system memory, the third processor device to: obtain input data directed to the first qubit; generate the push notification payload based on the input data; generate the push notification; and transmit the push notification to the first quantum computing device.

13. A non-transitory computer-readable medium having stored thereon computer-executable instructions that, when executed, cause one or more processor devices to: receive a push notification over a quantum channel, the push notification comprising an identifier of a first qubit and a push notification payload, the push notification payload comprising a second qubit transmitted over the quantum channel; obtain write access to the first qubit; and apply the push notification payload to the first qubit.

14. The non-transitory computer-readable medium of claim 13, wherein: the push notification payload comprises one or more qubit manipulation commands; and to apply the push notification payload to the first qubit is to: obtain the one or more qubit manipulation commands from the push notification payload; and execute the one or more qubit manipulation commands using the first qubit.

15. The non-transitory computer-readable medium of claim 14, wherein the one or more qubit manipulation commands comprises one or more of a command for placing the first qubit into an entangled state and a command for setting a quantum state of the first qubit.

16. The non-transitory computer-readable medium of claim 13, wherein the computer-executable instructions further cause the one or more processor devices to: obtain a result of a quantum operation; generate the push notification payload based on the result of the quantum operation; generate the push notification; and transmit the push notification.

17. The non-transitory computer-readable medium of claim 13, wherein the computer-executable instructions further cause the one or more processor devices to: obtain input data directed to the first qubit; generate the push notification payload based on the input data; generate the push notification; and transmit the push notification.
