

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412767
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Park; Gui Su et al.

Apparatus for treating substrate and method for treating substrate

Abstract

The inventive concept provides a substrate treating apparatus. The substrate treating apparatus includes a first process treating unit configured to treat a substrate in a single-type method; a second process treating unit configured to treat a substrate in a batch-type method; and a posture changing unit provided between the first process treating unit and the second process treating unit and configured to change a posture of the substrate between a vertical posture and a horizontal posture, and wherein the substrate is loaded to and unloaded from the first process treating unit.

Inventors: Park; Gui Su (Chungcheongnam-do, KR), Choi; Jun Young (Chungcheongbuk-do, KR), Jang; Young Jin (Chungcheongnam-do, KR), Ko; Yong Sun (Gyeonggi-do, KR), Chang; Kyu Hwan (Chungcheongnam-do, KR), Lim; Jun Hyun (Seoul, KR)

Applicant: SEMES CO., LTD. (Chungcheongnam-do, KR)

Family ID: 86187570

Assignee: SEMES CO., LTD. (Chungcheongnam-Do, KR)

Appl. No.: 17/980995

Filed: November 04, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230147919 A1	May. 11, 2023

Publication Classification

Int. Cl.: H01L21/67 (20060101); B08B3/08 (20060101); B08B13/00 (20060101); F26B5/00 (20060101); G03F7/20 (20060101); H01L21/677 (20060101); H01L21/687 (20060101); B25J11/00 (20060101)

U.S. Cl.:

CPC **H01L21/67718** (20130101); **B08B3/08** (20130101); **B08B13/00** (20130101); **F26B5/005** (20130101); **G03F7/2043** (20130101); **H01L21/68707** (20130101); B25J11/0095 (20130101)

Field of Classification Search

CPC: H01L (21/67063)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2018/0090358	12/2017	Miyamoto	N/A	H01L 21/67288

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2012-146862	12/2011	JP	N/A
10-0761576	12/2006	KR	N/A
10-2011-0002419	12/2010	KR	N/A
10-2013-0031048	12/2012	KR	N/A
10-2020-0060280	12/2019	KR	N/A
10-2021-0043445	12/2020	KR	N/A

OTHER PUBLICATIONS

Korean Office Action issued in corresponding KR Patent Application No. 10-2021-0150990, dated Jul. 31, 2023, with English translation. cited by applicant
Korean Office Action issued in corresponding KR Patent Application No. 10-2021-0150990, dated Aug. 30, 2024, with English translation. cited by applicant

Primary Examiner: Ko; Jason Y
Attorney, Agent or Firm: Carter, DeLuca & Farrell LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) A claim for priority under 35 U.S.C. § 119 is made to Korean Patent Application No. 10-2021-0150990 filed on Nov. 5, 2021, in the Korean Intellectual Property Office, the entire contents of which are hereby incorporated by reference.

BACKGROUND

(2) Embodiments of the inventive concept described herein relate to a substrate treating apparatus and a substrate treating method.
(3) In order to manufacture a semiconductor element, a desired pattern is formed on a substrate such as a wafer through various processes such as a photolithography process, an etching process, an ashing process, an ion implantation process, and a thin film deposition process on the substrate.

Various treating liquids and treating gases are used in each process, and particles and process by-products are generated during a process. In order to remove a thin film, particles, and process by-products on the substrate from the substrate, a liquid treatment process is performed on the substrate before and after each process. In a general liquid treatment process, the substrate is treated with a chemical and a rinsing liquid and then dried. In the liquid treatment process, a SiN on the substrate may be stripped.

(4) In addition, a substrate treating method using a treating liquid such as a chemical and/or a rinsing liquid can be divided into a batch-type treating method of treating a plurality of substrates in batches and a single-type treating method of treating substrates one by one.

(5) In the batch-type treating method for collectively treating the plurality of substrates, a substrate treatment is performed by collectively immersing the plurality of substrates in a vertical posture in a treating bath in which a chemical or a rinsing liquid is stored. For this reason, a mass productivity of the substrate treatment is excellent, and a treating quality between each substrate is uniform. In the batch-type treating method, a plurality of substrates having a pattern formed on a top surface are immersed in the vertical posture. Accordingly, if the pattern formed on the substrate has a high aspect ratio, a pattern leaning phenomenon may occur at the pattern formed on the substrate during a process such as lifting the substrate. In addition, if a drying treatment is not quickly performed within a short period of time in a state in which the plurality of substrates are exposed to the air, a water mark may be generated in some of the plurality of substrates exposed to the air.

(6) On the other hand, in the case of the single-type treating method of treating substrates one by one, a substrate treatment is performed to supply a chemical or a rinsing liquid to a single substrate rotating in a horizontal posture. Also, in the single-type treating method, since a transferred substrate maintains the horizontal posture, a risk of the pattern leaning phenomenon is reduced, and the substrate is treated one by one and a treated substrate is immediately dried or liquid-treated, so a risk of the water mark is reduced. However, in the case of the single-type treating method, the mass productivity of the substrate treatment is poor, and the treating quality between each substrate is relatively uneven compared to the batch-type treating method.

(7) In addition, if the substrate is spin-dried by a rotation, if the pattern formed on the substrate has the high aspect ratio, there is a concern that a leaning phenomenon, in which the pattern formed on the substrate collapses, may occur.

SUMMARY

(8) Embodiments of the inventive concept provide a substrate treating apparatus and method for efficiently treating a substrate.

(9) Embodiments of the inventive concept provide a substrate treating apparatus and method for improving a mass productivity of a substrate treating.

(10) Embodiments of the inventive concept provide a substrate treating apparatus and method for improving a uniformity of a treatment quality between each substrate.

(11) Embodiments of the inventive concept provide a substrate treating apparatus and method for minimizing a risk of generating a water mark on a substrate.

(12) Embodiments of the inventive concept provide a substrate treating apparatus and method for minimizing a generation of a leaning phenomenon of a pattern formed on a substrate.

(13) Embodiments of the inventive concept provide a substrate treating apparatus and method for efficiently treating a substrate at which a pattern with a high aspect ratio is formed.

(14) Embodiments of the inventive concept provide a substrate treating apparatus and method for minimizing a generation of a fume and reducing a size of an apparatus to increase a space utilization.

(15) The technical objectives of the inventive concept are not limited to the above-mentioned ones, and the other unmentioned technical objects will become apparent to those skilled in the art from the following description.

(16) The inventive concept provides a substrate treating apparatus. The substrate treating apparatus

includes a first process treating unit configured to treat a substrate in a single-type method; a second process treating unit configured to treat a substrate in a batch-type method; and a posture changing unit provided between the first process treating unit and the second process treating unit and configured to change a posture of the substrate between a vertical posture and a horizontal posture, and wherein the substrate is loaded to and unloaded from the first process treating unit.

(17) In an embodiment, the posture changing unit includes: a posture changing robot for changing the posture of the substrate between the vertical posture and the horizontal posture; a posture changing treating bath having a storage space for storing the substrate; and a support member positioned within the storage space of the posture changing treating bath and which supports the substrate which has its posture changed by the posture changing robot in the vertical posture.

(18) In an embodiment, the first process treating unit includes: a liquid treating unit configured to treat the substrate in the single-type method by supplying a first treating liquid to the substrate in the horizontal posture; and a buffer unit configured to store the substrate which has been treated at the liquid treating unit in the horizontal posture.

(19) In an embodiment, the posture changing robot moves between the buffer unit and the posture changing treating bath, and the posture changing robot changes the substrate which is stored at the buffer unit in the horizontal posture to the vertical posture to transfer to the posture changing treating bath, and changes the substrate which is stored at the posture changing treating bath in the vertical posture to the horizontal posture to transfer to the buffer unit.

(20) In an embodiment, the second process treating unit includes: a plurality of batch-type treating baths for batch-type treating the substrate; and a transfer unit configured to transfer the substrate between the posture changing treating bath and the plurality of batch-type treating baths.

(21) In an embodiment, the plurality of batch-type treating baths include: a first batch-type treating bath for batch-type treating the substrate by supplying a second treating liquid to the substrate; and a second batch-type treating bath for batch-type treating the substrate by supplying a third treating liquid to the substrate.

(22) In an embodiment, the first process treating unit includes: an organic solvent treating unit configured to single-type treat the substrate by supplying an organic solvent to the substrate; a supercritical treating unit configured to single-type treat the substrate by supplying a drying fluid to the substrate; and a transfer treating unit configured to transfer the substrate between the buffer unit, the liquid treating unit, the organic solvent treating unit, and the dry treating unit.

(23) In an embodiment, the first process treating unit includes a load port unit configured to include a plurality of load ports, and a portion of the plurality of load ports are provided as a first load port unit at which the substrate is loaded in the horizontal posture, and the other portion of the plurality of load ports are provided as a second load port unit at which the substrate is unloaded in the horizontal posture.

(24) In an embodiment, the posture changing robot includes: a hand which is configured to hold the substrate; and an arm which moves the hand.

(25) In an embodiment, the substrate treating apparatus further includes a controller, and wherein the controller controls the substrate to sequentially perform: a substrate loading step for loading the substrate to the load port of the first process treating unit in the horizontal posture; a first single-type treating step for treating the substrate at the liquid treating unit of the first process treating unit in the horizontal posture; a first posture changing step for changing the posture of the substrate from the horizontal posture to the vertical posture; a batch-type treating step for treating the substrate at the second process treating unit in the vertical posture; a second posture changing step for changing the posture of the substrate from the vertical posture to the horizontal posture; a second single-type treating step for treating the substrate at the first process treating unit in the horizontal posture; and a substrate unloading step for unloading the substrate to the load port of the first process treating unit in the horizontal posture.

(26) The inventive concept provides a substrate treating apparatus. The substrate treating apparatus

includes a first process treating unit configured to treat a substrate in a single-type method; a second process treating unit configured to treat a substrate in a batch-type method; a third process treating unit configured to treat a substrate in a single-type method; a first posture changing unit provided between the first process treating unit and the second process treating unit and which is configured to change a posture of the substrate between a vertical posture and a horizontal posture; and a second posture changing unit provided between the second process treating unit and the third process treating unit and which is configured to change a posture of the substrate between the vertical posture and the horizontal posture, and wherein the second process treating unit is provided between the first process treating unit and the third process treating unit, and the substrate is provided to be loaded and unloaded in a single-type method.

(27) In an embodiment, the substrate is loaded to the first process treating unit, and the substrate is unloaded by the second process treating unit.

(28) In an embodiment, the first process treating unit includes: a first load port unit configured to include a plurality of load ports at which the substrate is loaded in the horizontal posture; a liquid treating unit configured to single-type treat the substrate in the horizontal posture by supplying a first treating liquid to the substrate; and a first buffer unit configured to store a substrate which has been treated at the liquid treating unit in the horizontal posture, and wherein the third process treating unit includes: an organic solvent treating unit configured to single-type treat the substrate in the horizontal posture by supplying an organic solvent to the substrate; a dry treating unit configured to single-type treat the substrate in the horizontal posture by supplying a drying fluid to the substrate; and a second buffer unit configured to store the substrate which has been single-type treated at the organic solvent treating unit and the dry treating unit in the horizontal posture.

(29) In an embodiment, the first posture changing unit includes: a first posture changing robot for changing the posture of the substrate between the vertical posture and the horizontal posture; a first posture changing treating bath having a storage space for storing the substrate; and a first support member positioned within the storage space of the first posture changing treating bath and which supports the substrate which has its posture changed by the first posture changing robot in the vertical posture, and wherein the first posture changing robot changes the substrate stored at the first buffer unit in the horizontal posture to the vertical posture to transfer to the first posture changing treating bath.

(30) In an embodiment, the second posture changing unit includes: a second posture changing robot for changing the posture of the substrate between the vertical posture and the horizontal posture; a second posture changing treating bath having a storage space for storing the substrate; and a second support member positioned within the storage space of the second posture changing treating bath and which supports the substrate which has its posture changed by the second posture changing robot in the vertical posture, and wherein the second posture changing robot changes the substrate stored at the second posture changing treating bath in the vertical posture to the horizontal posture to transfer to the second buffer unit.

(31) In an embodiment, the second process treating unit includes: a plurality of batch-type treating baths for batch-type treating the substrate; and a transfer unit configured to transfer the substrate between the first posture changing treating bath, the second posture changing treating bath, and the plurality of batch-type treating baths, and wherein the plurality of batch-type treating baths include: a first batch-type treating bath for batch-type treating the substrate by supplying a second treating liquid to the substrate; and a second batch-type treating bath for batch-type treating the substrate by supplying a third treating liquid to the substrate.

(32) In an embodiment, the first posture changing unit includes a first posture changing robot which changes the posture of the substrate from the horizontal posture to the vertical posture, and the second posture changing unit includes a second posture changing robot which changes the posture of the substrate from the vertical posture to the horizontal posture, and wherein the first posture changing robot and the second posture changing robot each include: a hand which is

configured to hold the substrate; and an arm which moves the hand.

(33) In an embodiment, the substrate treating apparatus further includes a controller, and wherein the controller controls the substrate to sequentially perform: a substrate loading step for loading the substrate to a load port of the first process treating unit in the horizontal posture; a first single-type treating step for treating the substrate at the first process treating unit in the horizontal posture; a first posture changing step for changing the posture of the substrate from the horizontal posture to the vertical posture; a batch-type treating step for treating the substrate at the second process treating unit in the vertical posture; a second posture changing step for changing the posture of the substrate from the vertical posture to the horizontal posture; a second single-type treating step for treating the substrate at the third process treating unit in the horizontal posture; and a substrate unloading step for unloading the substrate to a load port of the third process treating unit in the horizontal posture.

(34) In an embodiment, the vertical posture refers to a posture at which a top surface or a bottom surface of the substrate is parallel to a direction perpendicular to the ground, and the horizontal posture refers to a posture at which the top surface or the bottom surface of the substrate is parallel to the ground.

(35) In an embodiment, the first treating liquid is a removing liquid for removing an oxide film on the substrate, the second treating liquid is a chemical for removing a contaminant remaining on the substrate, and the third treating liquid is a pure water.

(36) According to an embodiment of the inventive concept, a substrate may be efficiently treated.

(37) According to an embodiment of the inventive concept, a mass productivity of a substrate treating may be improved.

(38) According to an embodiment of the inventive concept, a uniformity of a treatment quality between each substrate may be improved.

(39) According to an embodiment of the inventive concept, a risk of generating a water mark on a substrate may be minimized.

(40) According to an embodiment of the inventive concept, a leaning phenomenon of a pattern formed on a substrate may be minimized.

(41) According to an embodiment of the inventive concept, a substrate at which a pattern with a high aspect ratio is formed may be efficiently treated.

(42) According to an embodiment of the inventive concept, a generation of a fume may be minimized and a size of an apparatus may be reduced to increase a space utilization of an apparatus.

(43) The effects of the inventive concept are not limited to the above-mentioned ones, and the other unmentioned effects will become apparent to those skilled in the art from the following description.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) The above and other objects and features will become apparent from the following description with reference to the following figures, wherein like reference numerals refer to like parts throughout the various figures unless otherwise specified, and wherein:

(2) FIG. 1 is a schematic top view of a substrate treating apparatus according to an embodiment of the inventive concept.

(3) FIG. 2 illustrates a substrate treating apparatus provided to a single-type liquid treating chamber of FIG. 1.

(4) FIG. 3 illustrates a substrate treating apparatus provided to a single-type drying chamber of FIG. 1.

(5) FIG. 4 illustrates a state of a buffer unit of FIG. 1.

- (6) FIG. 5 illustrates a state of a posture changing treating bath of FIG. 1.
- (7) FIG. 6 schematically illustrates a posture changing robot of FIG. 1.
- (8) FIG. 7 illustrates a hand of FIG. 6.
- (9) FIG. 8 illustrates any one batch-type treating bath among batch-type treating baths of FIG. 1.
- (10) FIG. 9 is a schematic top view of the substrate treating apparatus according to another embodiment of the inventive concept.
- (11) FIG. 10 is a flowchart illustrating a substrate treating method using the substrate treating apparatus of FIG. 1 or the substrate treating apparatus of FIG. 2.
- (12) FIG. 11 and FIG. 12 illustrates a state in which the posture changing robot changes a posture of a substrate to a horizontal posture in a second posture changing step of FIG. 10.
- (13) FIG. 13 illustrates the posture changing robot performing a wetting step of FIG. 10.
- (14) FIG. 14 is a top view illustrating a state in which a liquid supply member supplies a wetting liquid at the wetting step of FIG. 9.
- (15) FIG. 15 is a side view illustrating a state in which the liquid supply member supplies the wetting liquid at the wetting step of FIG. 10.
- (16) FIG. 16 illustrates the hand according to another embodiment of the inventive concept.
- (17) FIG. 17 is a top view illustrating a state in which the liquid supply member of FIG. 15 supplies the wetting liquid to the substrate.
- (18) FIG. 18 illustrates the posture changing robot according to another embodiment of the inventive concept.
- (19) FIG. 19 is a top view of the hand according to another embodiment of the inventive concept.
- (20) FIG. 20 is a side view of the hand of FIG. 18.
- (21) FIG. 21 is a top view of the hand according to another embodiment of the inventive concept.
- (22) FIG. 22 is a side view of a holder of FIG. 19.

DETAILED DESCRIPTION

- (23) The inventive concept may be variously modified and may have various forms, and specific embodiments thereof will be illustrated in the drawings and described in detail. However, the embodiments according to the concept of the inventive concept are not intended to limit the specific disclosed forms, and it should be understood that the present inventive concept includes all transforms, equivalents, and replacements included in the spirit and technical scope of the inventive concept. In a description of the inventive concept, a detailed description of related known technologies may be omitted when it may make the essence of the inventive concept unclear.
- (24) The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the inventive concept. As used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises”, “comprising”, “includes”, and/or “including” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items. Also, the term “example” is intended to refer to an example or illustration.
- (25) It will be understood that, although the terms “first”, “second”, “third”, etc., may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer or section from another region, layer or section. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the inventive concept.
- (26) It should be understood that when an element or layer is referred to as being “on,” “connected to,” “coupled to,” or “covering” another element or layer, it may be directly on, connected to,

coupled to, or covering the other element or layer or intervening elements or layers may be present. In contrast, when an element is referred to as being “directly on,” “directly connected to,” or “directly coupled to” another element or layer, there are no intervening elements or layers present. Other terms such as “between”, “adjacent”, “near” or the like should be interpreted in the same way.

(27) Unless otherwise defined, all terms used herein, including technical or scientific terms, have the same meaning as those generally understood by those skilled in the art to which the inventive concept belongs. Terms such as those defined in commonly used dictionaries should be interpreted as consistent with the context of the relevant technology and not as ideal or excessively formal unless clearly defined in this application.

(28) In addition, components that transfer the substrate W described below, for example, the following transfer unit or transfer robots, may be referred to as a transfer module.

(29) Hereinafter, an embodiment of the inventive concept will be described with reference to FIG. 1 to FIG. 22.

(30) FIG. 1 is a schematic top view of a substrate treating apparatus according to an embodiment of the inventive concept.

(31) Referring to FIG. 1, a substrate treating apparatus 1 according to an embodiment of the inventive concept may include a first process treating unit 10, a posture changing unit 20, a second process treating unit 30, and a controller 900. The first process treating unit 10 and the second process treating unit 30 may be arranged along a first direction X when viewed from above. Hereinafter, when viewed from above, a direction perpendicular to the first direction X is referred to as a second direction Y, and a direction perpendicular to the first direction X and the second direction Y is referred to as a third direction Z.

(32) The first process treating unit 10 may treat the substrate W in a single-type method. The first process treating unit 10 may load or unload the substrate W in a horizontal posture. The first process treating unit 10 may treat the substrate W in a horizontal posture. The first process treating unit 10 may include a load port unit 110, an index unit 120, an organic solvent treating unit 140, a dry treating unit 150, a buffer unit 160, and a transfer treating unit 170. The load port unit 110 and the index unit 120 may be referred to as an index module, and the liquid treating unit 130, the organic solvent treating unit 140, the dry treating unit 150, the buffer unit 160, and the transfer treating unit 170 are referred to as a process module.

(33) The load port unit 110 may include a plurality of load ports. A transfer container F in which at least one substrate W is stored may be placed on the load ports of the load port unit 110. The plurality of substrates W may be stored at the transfer container F. For example, 25 substrates may be stored at the transfer container F. The transfer container F may be referred to as a cassette, a pod, a FOUP, or the like. The transfer container F may be loaded and unloaded on the load port unit 110 by a container transfer apparatus.

(34) The substrates W stored at the transfer container F placed in a portion of the plurality of load port units 110 may be untreated substrates W. An untreated substrate W may be, for example, a substrate W on which a treatment has not been taken out, or substrates W on which some treatment has been taken out but a liquid treatment is required. The substrates W stored in the transfer container F placed in the remaining portion of the plurality of load ports may be substrates W treated by the first process treating unit 10 and the second process treating unit 30. In other words, a portion of the plurality of load ports may serve to load the substrate W which requires a treatment, and the remaining portion of the plurality of load ports may serve to unload the treated substrate W from the substrate treating apparatus 1. For example, referring to FIG. 1, the load port unit 110 may include four load ports, two of the four load ports may be provided with a first load port unit in which the untreated substrate W is loaded, and the other two load ports may be provided as a second load port unit in which the treated substrate W is unloaded. Although the number of load ports is illustrated as four in this specification, the number is not limited thereto,

and may be provided in various numbers according to conditions such as a process efficiency or a footprint.

(35) In addition, only a container **F** in which the untreated substrate **W** is stored may be placed in the load port unit **110**. That is, the load port unit **110** may perform only a role of which a substrate **W** requiring a treatment is loaded.

(36) The load port unit **110** may be coupled to the index unit **120**. The index unit **120** and the load port unit **110** may be arranged along the second direction **Y**. The first index unit **120** may include an index robot **122**. The index robot **122** may take out the untreated substrate **W** or the substrate requiring a treatment from a container **F** mounted on the load port unit **110**. The index robot **122** may take out the substrate **W** from the container **F** and into the process module. The index robot **122** may take the substrate **W** out of the container **F** and transfer the substrate **W** to the liquid treating unit **130** or the buffer unit **160** to be described later among the process module. The index robot **122** may transfer the substrate **W** which a treatment has been completed to the container **F** mounted on the load port unit **110**. The index robot may transfer the substrate **W** which a treatment has been completed and which is stored at the buffer unit **160** to the container **F** placed on the load port. The index robot **122** may take the treated substrate **W** to the container **F** which is placed on the load port included in the second load port unit among the load port unit **110**. The container may be transferred to outside of the substrate treating apparatus **1** by an article transfer apparatus (for example, an OHT).

(37) The index robot **122** may have a hand capable of holding and transferring the substrate **W**. The index robot **122** may have a plurality of hands, of which a portion may be used only to take the substrate **W** out of the container **F** and transfer it to the process module, and the other portion may be used only to transfer the treated substrate **W** from the process module to the container **F**. The hand of the index robot **122** may be a single-type hand for transferring the substrate **W** one by one. The hand of the index robot **122** may be provided to be movable along the first direction **X**, the second direction **Y**, and the third direction **Z**. In addition, the hand of the index robot **122** may be provided rotatable with the third direction **Z** as a rotation axis.

(38) FIG. 2 illustrates a state of a substrate treating apparatus provided in the single-type liquid treating chamber of FIG. 1.

(39) Referring to FIG. 2, the liquid treating unit **130** may treat the substrate in a single-type method. A plurality of liquid treating units **130** may be provided. A plurality of liquid treating units **130** may be provided and stacked in the vertical direction. The liquid treating unit **130** may rotate the substrate **W** in a horizontal posture, but may supply the first treating liquid to the rotating substrate **W** to treat the substrate **W**. The liquid treating unit **130** may treat the substrate **W** one by one. The first treating liquid supplied from the liquid treating unit **130** may be provided as a treating liquid capable of etching the oxide film on the substrate **W**. For example, the first treating liquid supplied from the liquid treating unit **130** may be a dilute hydrofluoric acid (DHF). The liquid treating unit **130** may supply the first treating liquid to the rotating substrate **W**, and may rotate the substrate **W** to treat the substrate **W**.

(40) A substrate treating apparatus **400** may be provided to perform a single-type liquid treatment at the liquid treating unit **130**. The substrate treating apparatus **400** may include a housing **410**, a treating container **420**, a support unit **440**, a lifting/lowering unit **460**, and a liquid supply unit **480**.

(41) The housing **410** has a treating space **412** therein. The housing **410** may have a cylindrical shape having a space therein. The inner space **412** of the housing **410** may be provided with a treating container **420**, a support unit **440**, a lifting/lowering unit **460**, and a liquid supply unit **480**. The housing **410** may have a rectangular shape when viewed from a front surface. However, the inventive concept is not limited thereto, and the housing **410** may be transformed into various shapes that may have a treating space **412**.

(42) The treating container **420** has a cylindrical shape with an open top. The treating container **420** has an inner recollecting container **422** and an outer recollecting container **426**. Each of the

recollecting containers **422** and **426** recollects different treating liquids among the treating liquids used in a process. The inner recollecting container **422** is provided in an annular ring shape surrounding the support unit **440**, and the outer recollecting container **426** is provided in an annular ring shape surrounding the inner recollecting container **422**. An inner space **422a** of the inner recollecting container **422** and the inner recollecting container **422** function as a first inlet **422a** through which the treating liquid flows into the inner recollecting container **422**. A space **426a** between the inner recollecting container **422** and the outer recollecting container **426** functions as a second inlet **426a** through which the treating liquid flows into the outer recollecting container **426**. According to an embodiment, each inlet **422a** and **426a** may be positioned at different heights. The recollecting lines **422b** and **426b** are connected below bottom surfaces of each of the recollecting containers **422** and **426**. A treating liquid taken into each of the recollecting containers **422** and **426** can be reused and provided to an outer treating liquid regeneration system (not shown) through the recollecting lines **422b** and **426b**.

(43) The support unit **440** supports the substrate W in the treating space **412**. The support unit **440** supports and rotates the substrate W during the process. The support unit **440** includes a support plate **442**, a support pin **444**, a chuck pin **446**, and rotation driving members **448** and **449**.

(44) The support plate **442** is provided in a substantially circular plate shape and has a top surface and a bottom surface. The bottom surface has a smaller diameter than the top surface. That is, the support plate **442** may have a shape of a top wide-bottom narrow structure with a wide top surface and a narrow bottom surface. The top surface and the bottom surface are positioned so that their central axes coincide with each other. In addition, a heating means (not shown) may be provided at the support plate **442**. The heating means provided to the support plate **442** may heat the substrate W placed on the support plate **442**. The heating means may generate a heat. The heat generated by the heating means may be warm or cold. The heat generated by the heating means may be transferred to the substrate W placed on the support plate **442**. In addition, the heat transferred to the substrate W may heat the treating liquid supplied to the substrate W. The heating means may be a heater and/or a cooling coil. However, the inventive concept is not limited thereto, and the heating means may be variously modified by known devices.

(45) A plurality of support pins **444** are provided. The support pin **444** is disposed to be spaced apart at a predetermined space at an edge portion of a top surface of the support plate **442** and upwardly protrudes from the support plate **442**. The support pins **444** are arranged to have an annular ring shape as a whole by combination with each other. The support pin **444** supports an edge region of a bottom surface of the substrate W so that the substrate W is spaced apart from the top surface of the support plate **442** by a predetermined distance.

(46) A plurality of chuck pins **446** are provided. The chuck pin **446** is disposed farther from a center of the support plate **442** than the support pin **444**. The chuck pin **446** is provided to upwardly protrude from the top surface of the support plate **442**. The chuck pin **446** supports a side portion of the substrate W so that the substrate W is not separated from a correct position in a lateral direction when the support plate **442** is rotated. The chuck pin **446** is provided to be linearly moved between an outer position and an inner position along a radial direction of the support plate **442**. The outer position is a position farther from the center of the support plate **442** than the inner position. If the substrate W is loaded or unloaded on the support plate **442**, the chuck pin **446** is positioned at the outer position, and of a process is performed on the substrate W, the chuck pin **446** is positioned at the inner position. The inner position is a position at which the chuck pin **446** and the side portion of the substrate W contact each other, and the outer position is a position at which the chuck pin **446** and the substrate W are spaced apart from each other.

(47) The rotation driving members **448** and **449** rotate the support plate **442**. The support plate **442** may be rotated around its center axis by rotation driving members **448** and **449**. The rotation driving members **448** and **449** include a support shaft **448** and a driving unit **449**. The support shaft **448** has a cylindrical shape facing the fourth direction **16**. A top end of the support shaft **448** is

fixedly coupled to the bottom surface of the support plate **442**. According to an embodiment, the support shaft **448** may be fixedly coupled to a center of the bottom surface of the support plate **442**. The driving unit **449** provides a driving force such that the support shaft **448** is rotated. The support shaft **448** may be rotated by the driving unit **449**, and the support plate **442** may be rotated together with the support shaft **448**.

(48) The lifting/lowering unit **460** linearly moves the treating container **420** in the up/down direction. As the treating container **420** is moved up and down, a relative height of the treating container **420** with respect to the support plate **442** is changed. If the substrate W is loaded on or unloaded on the support plate **442**, the treating container **420** is lowered so that the support plate **442** protrudes above the treating container **420**. In addition, if the process is performed, a height of the treating container **420** is adjusted so that the treating liquid may flow into predetermined recollecting containers **422** and **426** according to a type of treating liquid supplied to the substrate W. The lifting/lowering unit **460** has a bracket **462**, a moving shaft **464**, and a driver **466**. The bracket **462** is fixedly installed on an outer wall of the treating container **420**, and the moving shaft **464** which is moved in the up/down direction by the driver **466** is fixedly coupled to the bracket **462**. Selectively, the lifting/lowering unit **460** may move the support plate **442** in the up/down direction.

(49) The liquid supply unit **480** may supply a first treating liquid to the substrate W. The first treating liquid may be a chemical. In an embodiment, the first treating liquid may be provided as a treating liquid which can etch an oxide film on the substrate. In an embodiment, a dilute hydrofluoric acid (DHF) may be used.

(50) The liquid supply unit **480** may include a moving member **481** and a nozzle **489**. The moving member **481** moves the nozzle **489** to a process position and a standby position. The process position is a position at which the nozzle **489** faces the substrate W supported by the support unit **440**. According to an embodiment, the process position is a position at which the treating liquid is discharged to the top surface of the substrate W. The process position also includes a first supply position and a second supply position. The first supply position may be a position closer to the center of the substrate W than the second supply position, and the second supply position may be a position including an end of the substrate. Selectively, the second supply position may be a region adjacent to the end of the substrate. The standby position is defined as a position at which the nozzle **489** deviates from the process position. According to an embodiment, the standby position may be a position at which the nozzle **489** stands-by before or after a process treatment is completed on the substrate W.

(51) The moving member **481** includes an arm **482**, a support shaft **483**, and a driver **484**. The support shaft **483** is positioned at a side of the treating container **420**. The support shaft **483** has a rod shape with its lengthwise direction in the third direction Z. The support shaft **483** may be provided to be rotatable by the driver **484**. The support shaft **483** is provided to be able to move up and down. The arm **482** is coupled to the top end of the support shaft **483**. The arm **482** extends vertically from the support shaft **484**. A nozzle **489** is coupled to an end of the arm **482**. As the support shaft **483** is rotated, the nozzle **489** may swing together with the arm **482**. The nozzle **489** may be swing-moved to the process position and the standby position. Selectively, the arm **482** may be provided to be capable of being forwardly and backwardly moved in its lengthwise direction. When viewed from above, a path through which the nozzle **489** moves may coincide with a central axis of the substrate W at the process position.

(52) The organic solvent treating unit **140** may be provided with a substrate treating apparatus in which a liquid treatment is performed in a single-type method. The substrate treating apparatus provided to the organic solvent treating unit **140** may have the same structure as the substrate treating apparatus **400** provided to the liquid treating unit **130** shown in FIG. 1. Thus, the same drawing number is assigned to the same structure, and a redundant description is omitted.

(53) A plurality of organic solvent treating units **140** may be provided. A plurality of organic

solvent treating units **140** may be provided and stacked in the vertical direction. The organic solvent treating unit **140** may rotate the substrate W in a horizontal posture, but may supply the treating liquid to the rotating substrate W to treat the substrate W. The organic solvent treating unit **140** may treat the substrate W one by one. The treating liquid supplied from the organic solvent treating unit **140** can be replaced with the rinsing liquid described later and provided as a liquid capable of removing the rinsing liquid remaining on the surface of the substrate W. For example, the treating liquid supplied from the organic solvent treating unit **140** may be an organic solvent. For example, the treating liquid supplied from the organic solvent treating unit **140** may be isopropyl alcohol (IPA). The organic solvent treating unit **140** may supply the organic solvent to the rotating substrate W, and may dry the substrate W by rotating the substrate W. In contrast, the organic solvent treating unit **140** supplies the organic solvent to the rotating substrate W, and is transferred to the dry treating unit **150** described later while the substrate W is wet with the organic solvent, so that the substrate W may be dried in the dry treating unit **150**.

(54) FIG. 3 illustrates the substrate treating apparatus provided in the single-type drying chamber of FIG. 1.

(55) Referring to FIG. 3, the substrate treating apparatus **500** at which a single-type substrate dry treatment is performed may be provided to the dry treating unit **150**. At the dry treating unit **150**, the treating liquid remaining on the substrate W may be removed by using a drying fluid G in a supercritical state. The dry treating unit **500** can be a supercritical chamber which removes the treating liquid (e.g., a rinsing liquid or an organic solvent) remaining on the substrate W using the supercritical fluid. For example, the substrate treating apparatus **500** provided in the dry treating unit **150** may perform a drying process of removing the organic solvent remaining on the substrate W using a carbon dioxide (CO₂) in the supercritical state.

(56) The substrate treating apparatus **500** provided in the dry treating unit **150** may include a body **510**, a heating member **520**, a fluid supply unit **530**, a fluid exhaust unit **550**, and a lifting/lowering member **560**. The body **510** may have an inner space **518** in which the substrate W is treated. The body **510** may provide an inner space **518** in which the substrate W is treated. The body **510** may provide an inner space **518** at which the substrate W is dried by the drying fluid in the supercritical state.

(57) The body **510** may include a top body **512** and a bottom body **514**. The top body **512** and the bottom body **514** may be combined with each other to form the inner space **518**. The substrate W may be supported in the inner space **518**. For example, the substrate W may be supported by a support member (not shown) in the inner space **518**. The support member may be configured to support a bottom surface of the edge region of the substrate W. Any one of the top body **512** or the bottom body **514** may be coupled to the lifting/lowering member **560** to be moved in the up/down direction. For example, the bottom body **514** may be coupled to the lifting/lowering member **560** and may be moved in the up/down direction by the lifting/lowering member **560**. Accordingly, the inner space **518** of the body **510** may be selectively sealed. Although the above-described example has been described as an example in which the bottom body **514** is coupled to the lifting/lowering member **560** and moves in the up/down direction, the inventive concept is not limited to it. For example, the top body **512** may be coupled to the lifting/lowering member **560** to move in the up/down direction.

(58) The heating member **520** may heat the drying fluid supplied to the inner space **518**. The heating member **520** may increase a temperature of the inner space **518** of the body **510** to phase-change the drying fluid supplied to the inner space **518** into the supercritical state. In addition, the heating member **520** may increase the temperature of the inner space **518** of the body **510** so that the drying fluid in a supercritical state supplied to the inner space **518** maintains the supercritical state.

(59) In addition, the heating member **520** may be embedded in the body **510**. For example, the heating member **520** may be embedded in any one of the top body **512** or the bottom body **514**. For

example, the heating member **520** may be provided in the bottom body **514**. However, the inventive concept is not limited thereto, and the heating member **520** may be provided at various positions capable of increasing the temperature of the inner space **518**. In addition, the heating member **520** may be a heater. However, the inventive concept is not limited thereto, and the heating member **520** can be variously modified as a known device capable of increasing the temperature of the inner space **518**.

(60) The fluid supply unit **530** may supply the drying fluid to the inner space **518** of the body **510**. The drying fluid supplied by the fluid supply unit **530** may include a carbon dioxide CO.sub.2. The fluid supply unit **530** may include a fluid supply source **531**, a first supply line **533**, a first supply valve **535**, a second supply line **537**, and a second supply valve **539**.

(61) The fluid supply source **531** may store and/or supply the drying fluid supplied to the inner space **518** of the body **510**. The fluid supply source **531** may supply the drying fluid to the first supply line **533** and/or the second supply line **537**. For example, the first supply valve **535** may be installed on the first supply line **533**. In addition, the second supply valve **539** may be installed on the second supply line **537**. The first supply valve **535** and the second supply valve **539** may be on/off valves. According to on/off of the first supply valve **535** and the second supply valve **539**, the drying fluid may selectively flow through the first supply line **533** or the second supply line **537**.

(62) In the above-described example, the first supply line **533** and the second supply line **537** are connected to one fluid supply source **531**, but are not limited thereto. For example, a plurality of fluid supply sources **531** may be provided, the first supply line **533** may be connected to one of the plurality of fluid supply sources **531**, and the second supply line **537** may be connected to another other of the fluid supply sources **531**.

(63) Also, the first supply line **533** may be a top supply line which supplies a drying gas from above of the inner space **518** of the body **510**. For example, the first supply line **533** may supply the drying gas to the inner space **518** of the body **510** in a direction from a top to a bottom. For example, the first supply line **533** may be connected to the top body **512**. Also, the second supply line **537** may be a bottom supply line which supplies the drying gas from below the inner space **518** of the body **510**. For example, the second supply line **537** may supply the drying gas to the inner space **518** of the body **510** in a direction from the bottom to the top. For example, the second supply line **537** may be connected to the bottom body **514**.

(64) The fluid exhaust unit **550** may exhaust the drying fluid G from the inner space **518** of the body **510**.

(65) The buffer unit **160** may provide a storage space for temporarily storing the substrate W. The buffer unit **160** may temporarily store the substrate W treated by the liquid treating unit **130**, the organic solvent treating unit **140**, and the dry treating unit **150**. In addition, the buffer unit **160** may store the substrate W treated by the batch-type second process treating unit **30** to be described later. The buffer unit **160** may include a plurality of buffer units **160**, and each of the plurality of buffer units **160** may store a substrate W treated by the liquid treating unit **130**, a substrate W treated by the organic solvent treating unit **140**, a substrate W treated by the dry treating unit **150**, and a substrate W treated by the second process treating unit **30**.

(66) The buffer unit **160** may be disposed on a side of the transfer treating unit **170** to be described later. When viewed from above, the buffer unit **160** may be open toward the posture changing unit **20** to be described later. When viewed from above, the buffer unit **160** may be open toward the transfer treating unit **170** to be described later. Accordingly, the posture changing robot **220** may change the posture of the substrate W in the posture changing treating bath **210** and transfer the substrate W having a changed posture to the buffer unit **160**. In addition, the substrate W transferred to the first buffer unit **210** may be taken out by the first transfer robot **172** of the transfer treating unit **170**. The taken out substrate W may be transferred to the single-type organic solvent treating unit **140** and/or the single-type dry treating unit **150**.

(67) FIG. 4 illustrates a state of the buffer unit of FIG. 1.

(68) Referring to FIG. 4, the buffer unit **160** may have a structure of supplying a wetting liquid to the storage space so as to prevent the substrate W taken into the storage space from being dried (to maintain a wettability of the substrate W). In addition, the substrates W stored in the buffer unit **160** may be stored in respective storage spaces partitioned in the buffer unit **160**.

(69) The buffer unit **160** may include a support shelf **161**, a drain partition **162**, a wetting nozzle **163**, and a drain line **164**.

(70) The support shelf **161**, the drain partition **162**, and the wetting nozzle **163** may be provided in a plurality to correspond to each substrate W taken into the buffer unit **160**. The support shelf **161** may support the substrate W in a space provided by the buffer unit **160**. In addition, a weight sensor **161a** may be installed on the support shelf **161**. The weight sensor senses the weight of the substrate W supported by the support shelf **161**, thereby confirming the amount of the wetting liquid W supplied on the substrate W.

(71) The controller **900** may adjust the amount of wetting liquid WL per unit time sprayed from the wetting nozzle **163** based on the weight of the substrate W supported by the support shelf **161**. The support shelf **161** may be provided to support the bottom surfaces of a side and the other side of the substrate W.

(72) The wetting nozzle **163** may be configured to spray the wetting liquid in a stream manner or spray manner. A plurality of wetting nozzles **163** may be provided. A pair of wetting nozzles **163** may spray the wetting liquid onto the substrate W to each substrate W. The wetting nozzle **163** may include a chemical capable of maintaining the wettability of the substrate W taken back to the storage space of the buffer unit **160** or a nozzle for supplying a mist. The chemical or the mist may supply a wetting liquid selected among an isopropyl alcohol (IPA), the above-described chemical, and the above-described rinsing liquid.

(73) The drain partition wall **162** may be disposed below the support shelf **161**. The drain partition wall **162** may be disposed below each of the substrates W supported on the support shelf **161**. The drain partition wall **162** may serve as a liquid receiver to receive the wetting liquid sprayed by the wetting nozzle **163**, and may partition the spaces in which the respective substrates W are disposed. The drain partition wall **162** has a square cylindrical shape with an open top so as to have a liquid receiving space, and the liquid receiving space of the drain partition wall **162** may be connected to the drain line **164**. Accordingly, the wetting liquid sprayed by the wetting nozzle **163** may be discharged to the outside.

(74) The transfer treating unit **170** may be disposed between the buffer unit **160** and the substrate treating unit for treating the substrate W in a single-type method. A liquid treating unit **130** and a buffer unit **160** may be disposed on a side of the transfer treating unit **170**, and an organic solvent treating unit **140** and a dry treating unit **150** may be disposed on the other side of the transfer treating unit **170**.

(75) The transfer treating unit **170** may have a first transfer robot **172**. The first transfer robot **172** may have a single-type transfer hand for transferring one substrate W by one by one. The first transfer robot **172** may transfer the substrate W between the liquid treating unit **130** and the buffer unit **160**. The first transfer robot **172** may take out the substrate W from the liquid treating unit **130** and transfer the substrate W to the buffer unit **160**. In this case, the posture changing robot **220** to be described later may transfer the substrate W taken into the buffer unit **160** to the second process treating unit **30**. The first transfer robot **172** may transfer the substrate W between the buffer unit **160**, the organic solvent treating unit **140**, and the dry treating unit **4**. The first transfer robot **172** may transfer the substrate W taken into the buffer unit **160** to the organic solvent treating unit **140**. The first transfer robot **172** may transfer the substrate W treated by the organic solvent treating unit **140** to the dry treating unit **150**. The first transfer robot **172** transfers the substrate W treated by the dry treating unit **150** to the buffer unit **160**, and the index robot **122** can take the substrate W from the buffer unit **160** and bring the substrate W into the container F placed in the load port. That is,

the transfer treating unit **170** may transfer the substrate **W** between the buffer unit **160** and the substrate treating unit which treats the substrate **W** in a single-type method.

(76) Referring back to FIG. **1**, the posture changing unit **20** may change the posture of the substrate **W**. The posture change unit **20** may be disposed between the first process treating unit **10** which treats the substrate **W** in a single-type method and the second process treating unit **30** which treats the substrate in a batch-type method. The posture change unit **20** may be disposed between the first process treating unit **10** which treats the substrate **W** in a horizontal posture and the second process treating unit **30** which treats the substrate **W** in a vertical posture. The posture changing unit **20** may change the posture of the substrate **W** between the vertical posture and the horizontal posture. The posture changing unit **20** may change the substrate **W** having the vertical posture to the horizontal posture. The posture changing unit **20** may change the substrate **W** having a horizontal posture to a vertical posture. The posture changing unit **20** may change the substrate **W** treated in the horizontal posture in the liquid treating unit **130** of the first process treating unit **10** or the substrate **W** stored in the horizontal posture in the buffer unit **150** of the first process treating unit **10** to the vertical posture. The posture change unit **20** may change the posture of the substrate **W** so that the substrate **W** treated in a vertical posture in the second process treating unit **30** may be post-treated in the organic solvent treating unit **140** and the dry treating unit **150** of the first process treating unit **10** with respect to one substrate **W** in a horizontal position.

(77) FIG. **5** illustrates a state of the posture changing treating bath of FIG. **1**.

(78) Referring to FIG. **5**, the posture changing treating bath **151** may include a treating bath **152**, a support member **153**, a supply line **154**, and a recollecting line **155**.

(79) The treating bath **211** may have a cylindrical shape with an open top. The treating bath **211** may have a rectangular cylindrical shape with an open top. The treating bath **211** may have accommodation spaces **A** and **B** in which the treating liquid **L** may be stored. The treating liquid **L** stored in the treating bath **211** may be a liquid containing water. The type of the treating liquid **L** stored in the treating bath **211** may be the same type of wetting liquid sprayed from the buffer unit **160**. For example, both the treating liquid **L** stored in the treating bath **211** and the wetting liquid sprayed from the buffer unit **160** may be a liquid containing water.

(80) The support member **212** may be disposed in the accommodation spaces **A** and **B** to support the substrate **W**. The support member **212** may be configured to support a plurality of substrates **W**. For example, the support member **212** may be configured to support 50 substrates **W**. The support member **212** may be arranged so that a pair of rod-shaped bodies face each other, and a support groove (not shown) through which the substrate **W** can be supported is formed in each body.

(81) The supply line **213** may supply the treating liquid **L** to the accommodation spaces **A** and **B**. The recollecting line **214** may drain the treating liquid **L** in the accommodation spaces **A** and **B**. A valve is installed in each of the supply line **213** and the recollecting line **214** and the amount of the treating liquid **L** stored in the accommodation spaces (i.e., the accommodation spaces (**A**, **B**)) can be adjusted to a set level based on the level of the treating liquid **L** sensed by the liquid level sensor which is not shown.

(82) In addition, the accommodation spaces **A** and **B** may include a support region **A** and a posture changing region **B**. The support region **A** may be a region in which the support member **212** supports the substrate **W**. The posture changing region **B** may be a region in which the posture of the substrate **W** is changed by the posture changing robot **220** to be described later.

(83) Referring back to FIG. **1**, the posture changing robot **220** may be disposed on a side of the posture changing treating bath **210**. The posture changing robot **220** may be disposed between the posture changing treating bath **210** and the transfer treating unit **170**. The posture changing robot **220** may be disposed between the posture changing treating bath **210** and the buffer unit **160**. The posture changing robot **220** may transfer the substrate **W** between the buffer unit **160** and the posture changing treating bath **210**. The posture changing robot **220** may include a hand **230** and a joint unit **240**. The hand **230** may be coupled to the joint unit **240**. The joint unit **240** may change

the position of the hand **230**.

(84) FIG. **6** schematically illustrates the posture changing robot of FIG. **1**. Referring to FIG. **6**, the posture changing robot **220** may change the posture of the substrate **W** between the vertical posture and the horizontal posture in the posture changing treating bath **210**. The posture changing robot **220** may transfer the substrate **W** stored in the buffer unit **160** to the posture changing treating bath **210** and change the substrate **W** in the horizontal posture to the vertical posture in the posture changing treating bath **210**. In addition, the posture changing robot **220** may change the posture of the substrate **W** from the vertical posture to the horizontal posture in the posture changing treating bath **210** and transfer the substrate **W** to the buffer unit **160** of the first process treating unit **10**. The posture changing robot **220** may be a multi-joint robot. The posture changing robot **220** may be a six-axis multi-joint robot.

(85) The joint portion **240** may be a multi-joint arm composed of at least two or more axes. For example, the joint portion **240** may be a 6-axis multi-joint arm. The joint unit **240** may change the position of the hand **230** by moving the hand **230** in at least one of the first direction **X**, the second direction **Y**, and the third direction **Z**. In addition, the joint unit **240** may rotate the hand **230** based on one of the axes of the first direction **X**, the second direction **Y**, and the third direction **Z**.

(86) The posture changing robot **220** may include a base **241**, a rotating body **242**, a first arm **243**, a second arm **244**, a third arm **245**, and a fourth arm **246**.

(87) The base **241** may be coupled to the rotating body **242**. The rotating body **242** may rotate with respect to the base **241**. The rotation body **242** may be rotated with a direction perpendicular to the ground as a rotation axis. The first arm **243** may be coupled to the rotating body **242**. The first arm **243** may be rotated with respect to the rotation body with the horizontal direction as a rotation axis. The second arm **244** may be coupled to the first arm **243**. The second arm **244** may be rotated with respect to the first arm **243** with the horizontal direction as a rotation axis. The third arm **245** may be coupled to the second arm **244**. The third arm **245** may be rotated around a lengthwise direction (or a lengthwise direction of the third arm **245**) of the second arm **244** as a rotation axis. The fourth arm **246** may be rotated with a direction perpendicular to the lengthwise direction of the third arm **245** as a rotation axis. In addition, the fourth arm **246** may rotate the hand **230**. For example, the fourth arm **246** may have a rotation shaft (not shown) capable of rotating the hand **230**. The hand **230** may be rotated with a direction perpendicular to the rotation axis of the fourth arm **246** as a rotation axis.

(88) FIG. **7** illustrates the hand of FIG. **6**. Referring to FIG. **7**, the hand **230** of the posture changing robot **220** may include a support body **231**, a first guide unit **232**, a second guide unit **233**, a driving member **234**, a chucking body **235**, a fastening body **236**, a vision member **237**, and a liquid supply member **238**.

(89) The support body **231** may support a bottom surface of the substrate **W**. The support body **231** may support a top surface on which a pattern of the substrate **W** is formed, a bottom surface on which a pattern is not formed, and a bottom surface of the substrate **W**. That is, the substrate **W** may be placed on the support body **231**.

(90) A first guide portion **232** and a second guide portion **233** may be provided in the support body **231**. The first guide portion **232** may be a support pad close to the fastening body **236** to be described later. The second guide portion **233** may be a support pad far from the fastening body **236** to be described later. Each of the first guide portion **232** and the second guide portion **233** may be provided in a pair. The first guide portion **232** and the second guide portion **233** may support a bottom surface and/or a side surface of the substrate **W**. The first guide portion **232** and the second guide portion **233** may have a stepped shape on top surfaces thereof. For example, a height of an inner region supporting the bottom surface of the substrate **W** among the top surfaces of the first guide part **232** may be lower than a height of an outer region supporting the bottom surface of the substrate **W**. Similarly, the height of the inner region supporting the bottom surface of the substrate **W** among the top surfaces of the second guide unit **233** may be lower than the height of the outer

region supporting the bottom surface of the substrate W. That is, the substrate W may be placed on the support body **231** via a first guide portion **232** and a second guide portion **233** installed on the support body **231**. The substrate W placed on the support body **231** should be interpreted to include not only the case where the support body **231** and the substrate W come into direct contact, but also the substrate W placed on the first guide part **232** and the second guide part **233** installed on the support body **231**.

(91) The driving member **234** may be fastened to the fastening body **236**. The driving member **234** may be a driver capable of moving the chucking body **235** in a lateral direction. A pair of driving members **234** may be provided. For example, the driving member **234** may be provided to correspond to each of the chucking bodies **235** provided in a pair. The pair of driving members **234** may move the pair of chucking bodies **235** in the lateral direction. The chucking bodies **235** may be moved in a direction close to the side of the substrate W and in a direction away from the side of the substrate W. Accordingly, the chucking body **235** may chuck the substrate W placed on the support body **231**. In other words, the support body **231** and the chucking body **235** may be bodies holding the substrate W.

(92) The fastening body **236** may be a body for coupling the chucking body **235** and the support body **231** to the joint portion **220-R**. The fastening body **236** may be a body that couples the chucking body **235** and the support body **231** to the fourth arm **246** of the joint **220-R**. The fastening body **236** may be fastened to a rotation shaft of the fourth arm **246** of the joint **220-R**.

(93) A first guide portion **232** and a second guide portion **233** may be provided to each of the support bodies **231**. The first guide portion **232** may be a protrusion close to the fastening body **236** to be described later. The second guide portion **233** may be a protrusion relatively far from the fastening body **236** to be described later. The second guide portion **233** may be disposed farther from the fastening body **236** than the first guide portion **232**. The first guide portion **232** and the second guide portion **233** may support the side portion of the substrate W. The first guide part **232** and the second guide part **233** support the side of the substrate W, and the distance between the two may be slightly smaller than the diameter of the substrate W.

(94) The vision member **247** may acquire an image by photographing the substrate W and/or the support body **231**. The acquired image may be transmitted to the controller **900** to be described later. The controller **900** may generate a control signal for controlling the driving of the posture changing robot **220** based on the image acquired by the vision member **237**.

(95) The liquid supply member **238** may supply the wetting liquid WL to the substrate W placed on the support body **231**. The wetting liquid WL may include water. The wetting liquid WL supplied by the liquid supply member **238** may be the same kind of liquid as the treating liquid L that stores in the accommodation spaces A and B. In addition, the wetting liquid WL supplied by the liquid supply member **238** may be the same type of the wetting liquid WL supplied by the buffer unit **160** to be described later.

(96) The liquid supply member **238** may include a first nozzle **238a** and a second nozzle **238b**. At least one of the first nozzles **238a** and the second nozzles **238b** may be provided. A plurality of first nozzles **238a** and a plurality of second nozzles **238b** may be provided. The first nozzle **238a** may supply the wetting liquid WL to the first region of the substrate W placed on the support body **231**. The second nozzle **238b** may supply the wetting liquid WL to the second region of the substrate W placed on the support body **231**. The first region and the second region may be different regions. The first region and the second region may be edge regions of the substrate W as described below. The first region may be adjacent to the first nozzle **238a**, and the second region may be adjacent to the second nozzle **238b**.

(97) A distance between the first region and the first nozzle **238a** may be shorter than a distance between the second region and the second nozzle **238b**. That is, the injection distance of the wetting liquid WL supplied from the first nozzle **238a** may be different from the injection distance of the wetting liquid WL supplied from the second nozzle **238b**. For example, the injection distance

of the wetting liquid WL supplied from the first nozzle **238a** may be shorter than the injection distance of the wetting liquid WL supplied from the second nozzle **238b**.

(98) Also, when viewed from above, the first nozzles **238a** may be disposed between the second nozzles **238b**. The second nozzles **238b** may be disposed at a position relatively close to the chucking body **235**, that is, an outside. The first nozzles **238a** may be disposed at a position relatively far from the chucking body **235**, that is, an inside.

(99) The spraying directions of the wetting liquid WL of the first nozzle **238a** and the second nozzle **238b** may be different from each other. For example, based on a virtual reference line passing through a center of the substrate W and a center of the vision member **237** when seen from above, the first nozzle **238a** may supply the wetting liquid WL in a direction parallel to the reference line, and the second nozzle **238b** may supply the wetting liquid WL in a direction inclined to the reference line.

(100) A diameter of the injection holes of the first nozzle **238a** and the second nozzle **238b** may be different from each other. For example, the diameter of the injection hole of the first nozzle **238a** may be greater than the diameter of the injection hole of the second nozzle **238a**. For example, a supply flow rate of the wetting liquid WL transmitted to the first nozzle **238a** and the second nozzle **238b** may be the same per unit time. Accordingly, the injection distance of the wetting liquid WL injected from the first nozzle **238a** may be shorter than the injection distance of the wetting liquid WL injected from the second nozzle **238b**.

(101) In addition, the first nozzle **238a** and the second nozzle **238b** may be installed on the support body **231**.

(102) Referring back to FIG. **1**, the second process treating unit **30** may treat the substrate W treated by the first process treating unit **10**. The second process treating unit **30** may treat the liquid-treated substrate W in the first process treating unit **10**. The second process treating unit **30** may collectively liquid treat a plurality of substrates W in a batch-type method. For example, the second process treating unit **30** may clean a plurality of substrates W in a batch-type method. The second process treating unit **30** may simultaneously treat the plurality of substrates W in a vertical posture (a posture at which a top or bottom surface of the substrate W is parallel to a direction perpendicular to the ground).

(103) The second process treating unit **30** may include a first batch-type treating bath **310**, a second batch-type treating bath **320**, and a transfer unit **330**.

(104) In the first batch-type treating bath **310**, a plurality of substrates W may be simultaneously liquid-treated with a second treating liquid. The second treating liquid may be a chemical. The second treating liquid may be a chemical having the properties of a strong acid or a strong base. The chemical may include, for example, an ammonia-hydrogen peroxide mixture (APM), a hydrochloric acid-hydrogen peroxide mixture (HPM), a hydrofluoric acid-hydrogen peroxide mixture (FPM), a diluted sulfuric acid peroxide (DSP), a chemical including a SiN, a chemical including a phosphoric acid, and a chemical including a sulfuric acid.

(105) In the second batch-type treating bath **320**, the plurality of substrates W may be simultaneously liquid-treated with a third treating liquid. The second treating liquid may be a rinsing liquid. The rinsing liquid may be a liquid containing water. For example, the rinsing liquid may be appropriately selected from a pure water or an ozone water.

(106) Since the first batch-type treating bath **310** and the second batch-type treating bath **320** have the same or similar structures except for the type of treating liquid used, only the first batch-type treating bath **310** will be described below, and repeated descriptions of the second batch-type treating bath **320** will be omitted.

(107) FIG. **8** illustrates a state of a batch-type treating bath of any one of the batch-type treating baths of FIG. **1**. For example, FIG. **8** illustrates the first batch-type treating bath **310**.

(108) Referring to FIG. **8**, the first batch-type treating bath **310** may include a treating bath **311**, a heating member **313**, a supply line **314**, a recollecting line **315**, and a support member **316**.

(109) The treating bath **311** may have an accommodation space **312** therein. The treating bath **311** may have a cylindrical shape with an open top. The treating liquid L may be stored in the accommodation space **312** of the treating bath **311**. In order to adjust a temperature of the treating liquid L stored in the accommodation space **312**, a heating member **313** may be installed in the treating bath **311**. The heating member **313** may heat the temperature of the treating liquid L stored in the accommodation space **312** of the treating bath **311** to a set temperature based on the temperature of the treating liquid L sensed by the temperature sensor which is not shown.

(110) The supply line **314** may supply the treating liquid L to the accommodation space **312**. The recollecting line **315** may drain the treating liquid L in the accommodation space **312**. A valve is installed in each of the supply line **314** and the recollecting line **315**, and the liquid level (i.e., the amount of the liquid L stored in the accommodation space **312**) can be adjusted to a set level based on the liquid level of the treating liquid L sensed by the liquid level sensor (not shown).

(111) The support member **316** may be disposed in the accommodation space **312** to support the substrate W. The support member **316** may be configured to support a plurality of substrates W. For example, the support member **316** may be configured to support 50 substrates W. The support member **316** may be arranged so that a pair of rod-shaped bodies face each other, and a support groove (not illustrated) through which the substrate W can be supported is formed in each body.

(112) Referring back to FIG. **1**, the transfer unit **330** may transfer the substrate W between the posture changing unit **20**, the first batch-type treating bath **310**, and the second batch-type treating bath **320**.

(113) The transfer unit **330** may include a rail extending along the first direction X and a hand configured to transfer the plurality of substrates W at once. The transfer unit **330** may hold the substrate W whose posture has been changed in the posture change treating bath **210** and transfer the gripped substrate W to the second process treating unit **30**. The transfer unit **330** may hold the substrates W whose posture has been changed in the posture change treating bath **210** and transfer the substrates W to the first batch-type treating bath **310**. The transfer unit **330** may hold the substrate W on which the liquid treatment has been completed in the first batch-type treating bath **310** and transfer it to the second batch-type treating bath **320**. The transfer unit **330** may hold the substrate W that has been treated with liquid in the second batch-type treating bath **320** and transfer it to the posture change treating bath **210**.

(114) FIG. **9** is a schematic view of a substrate treating apparatus according to another embodiment of the inventive concept as viewed from above.

(115) Referring to FIG. **9**, the substrate treating apparatus **2** according to another embodiment of the inventive concept may include a first process treating unit **40**, a first posture changing unit **50**, a second process treating unit **60**, a second posture changing unit **70**, a third process treating unit **80**, and a controller **900**. The first process treating unit **40**, the first posture changing unit **50**, the second process treating unit **60**, the second posture changing unit **70**, and the third process treating unit **80** may be arranged in the first direction X when viewed from above. Hereinafter, when viewed from above, a direction perpendicular to the first direction X is referred to as the second direction Y, and the direction perpendicular to the first direction X and the second direction Y is referred to as the third direction Z.

(116) Hereinafter, the substrate treating apparatus **2** according to another embodiment of the inventive concept will be described focusing on differences from the substrate treating apparatus **1** according to an embodiment of the inventive concept, and the same drawing number will be assigned to the same configuration, and redundant descriptions will be omitted.

(117) The first process treating unit **40** may treat the substrate W in a single-type method. The first process treating unit **40** may load the substrate W in the horizontal position. The first process treating unit **40** may treat the substrate W in the horizontal posture. The first process treating unit **40** may include a first load port unit **110-1**, a first index unit **120-1**, a liquid treating unit **130**, a first buffer unit **160-1**, and a first transfer treating unit **170-1**. The first load port unit **110-1** and the first

index unit **120-1** may be referred to as a first index module, and the liquid treating unit **130**, the first buffer unit **160-1**, and the first transfer treating unit **170-1** may be referred to as a first process module.

(118) The first load port unit **110-1** may include a plurality of load ports. A transfer container F in which at least one substrate W is stored may be placed on the load ports of the first load port unit **110-1**. A plurality of substrates W may be stored in the transfer container F. For example, 25 substrates may be stored in the transfer container F. The transfer container F may be referred to as a cassette, a pod FOD, a FOUP, or the like. The transfer container F may be loaded onto the first load port unit **110-1** by a container transfer apparatus (in an embodiment, an OHT). Only the container F in which the untreated substrate W is stored may be placed on the first load port unit **110-1**. That is, the first load port unit **110-1** may only serve to load the substrate W requiring a treatment.

(119) The first index unit **120-1** may be coupled to the first load port unit **110-1**. The first index unit **120-1** and the first load port unit **110-1** may be arranged in the second direction Y. The first index unit **120-1** may be disposed between the first load port unit **110-1** and the first buffer unit **160-1**. The first index unit **120-1** may include a first index robot **122-1**. The first index robot **122-1** may take out the untreated substrate W or the substrate W requiring a treatment from the container F mounted on the first load port unit **110-1**. The first index robot **122-1** may take the substrate W into the first process module by taking the substrate W out of the container F. The first index robot **122-1** may take out the substrate W from the container F and transfer the substrate W to the liquid treating unit **130** or a first buffer unit **160-1** to be described later.

(120) The first index robot **122-1** may have a hand capable of holding and transferring the substrate W. The hand of the first index robot **122-1** may be a single-type hand for transferring the substrate W one by one. The hand of the first index robot **122-1** may be provided to be movable along the first direction X, the second direction Y, and the third direction Z. In addition, the hand of the first index robot **122-1** may be rotatably provided with the third direction Z as a rotation axis.

(121) The first process treating unit **40** may be provided with a liquid treating unit **130** for treating a substrate in a single-type method. A plurality of liquid treating units **130** may be provided. The plurality of liquid treating units **130** may be provided and stacked in the vertical direction. The liquid treating unit **130** may be provided on a side surface of the first transfer treating unit **170-1** to be described later. The liquid treating unit **130** may face the first buffer unit **160-1** with respect to the first transfer treating unit **170-1**. The liquid treating unit **130** may treat the substrate W by rotating the substrate W in a horizontal posture and supplying the first treating liquid to the rotating substrate W. The liquid treating unit **130** may treat the substrate W one by one. The first treating liquid supplied from the liquid treating unit **130** may be provided as a treating liquid capable of etching an oxide film on the substrate W. For example, the first treating liquid supplied from the liquid treating unit **130** may be provided as a treating liquid capable of etching the oxide film on the substrate W. In an embodiment, a dilute hydrofluoric acid (DHF) may be used as the first treating liquid. The liquid treating unit **130** may supply the first treating liquid to the rotating substrate W, and may rotate the substrate W to treat the substrate W.

(122) The liquid treating unit **130** may have the same structure as the liquid treating unit **130** provided in the first process treating unit **10** of the substrate treating apparatus **1** according to an embodiment of the inventive concept. The liquid treating unit **130** may be provided with the same apparatus as the single-type substrate treating apparatus **400** of FIG. 2. Hereinafter, a redundant description of the liquid treating unit **130** of the substrate treating apparatus **2** according to another embodiment will be omitted.

(123) The first buffer unit **160-1** may provide a storage space for temporarily storing the substrate W. The first buffer unit **160-1** may temporarily store the untreated substrate W or the substrate W requiring a treatment. In addition, the first buffer unit **160-1** may temporarily store the substrate W treated by the liquid treating unit **130**. The first buffer unit **160-1** may include a plurality of first buffer units **160-1**, and each of the plurality of first buffer units **160-1** may store a substrate W

treated by the liquid treating unit **130** or an untreated substrate W transferred through the index robot **122**.

(124) The first buffer unit **160-1** may be disposed on any one of both side surfaces of the first transfer treating unit **170-1** to be described later. The first buffer unit **160-1** may face the liquid treating unit **130** based on the first transfer treating unit **170-1**. The first buffer unit **160-1** may include a plurality of first buffer units **160-1**. When viewed from above, the plurality of first buffer units **160-1** may be arranged in the first direction X. Some of the plurality of first buffer units **160-1** may store the untreated substrate W transferred from the first index robot **122-1** of the first index unit **120-1** or the substrate W requiring a treatment (hereinafter, 1-1 buffer unit **160-1a**). Another part of the plurality of first buffer units **160-1** may store a substrate W that has been liquid-treated in the liquid treating unit **130** in a single-type method (hereinafter, referred to as a 1-2 buffer unit **160-1b**). In an embodiment, the 1-1 buffer unit (**160-1a**) in which the liquid-treated substrate W is stored in the liquid treating unit **130** may be provided adjacent to the first posture changing unit **50** to be described later than the 1-2 buffer unit **160-1b** in which the untreated substrate W or the substrate W requiring a treatment is stored.

(125) The 1-1 buffer unit **160-1a** may be opened toward the first transfer treating unit **170-1**. Accordingly, the untreated substrate W transferred to the 1-1 buffer unit **160-1a** or the substrate W requiring a treatment may be taken out by the first transfer robot **172-1** of the first transferring treating unit **170-1**. The substrate W taken out from the 1-1 buffer unit **160-1a** by the first transfer robot **172-1** may be transferred to the liquid treating unit **130** to be liquid-treated in a single-type method.

(126) The 1-2 buffer unit **160-1b** may be opened toward the first posture changing unit **50**. Accordingly, the substrate W treated by the liquid treating unit **130** and stored in the 1-2 buffer unit **160-1b** may be gripped by the first posture changing robot **220-1** and transferred to the first posture changing unit **50**. In addition, the 1-2 buffer unit **160-1b** may be opened toward the first transfer treating unit **170-1**. Accordingly, the substrate W treated by the liquid treating unit **130** may be transferred to the 1-2 buffer unit **160-1b** by the first transfer robot **172-1**. The substrate W, which has been treated by the liquid treating unit **130** and stored in the 1-2 buffer unit **160-1b**, may change its posture from the horizontal posture to a vertical posture by the first posture changing robot **220-1**.

(127) The first buffer unit **160-1** may be provided in the same structure as the buffer unit **160** provided in the first process treating unit **10** of the substrate treating apparatus **1** according to an embodiment of the inventive concept (see FIG. 4). In addition, the 1-1 buffer unit **160-1a** and the 1-2 buffer unit **160-1b** may have the same structure. Hereinafter, a redundant description of the first buffer unit **160-1** of the substrate treating apparatus **2** according to another embodiment will be omitted.

(128) The first transfer treating unit **170-1** may be provided between the liquid treating unit **130** and the first buffer unit **160-1**. The liquid treating unit **130** may be provided on a side of the first transfer treating unit **170-1**, and a first buffer unit **160-1** may be provided on the other side. The first transfer treating unit **170-1** may have a first transfer robot **172-1**. The first transfer robot **172-1** may have a single-type transfer hand for transferring the substrate W one by one. The first transfer robot **172-1** may transfer the substrate W between the liquid treating unit **130** and the first buffer unit **160-1**. The first transfer robot **172-1** may take out the untreated substrate W or the substrate W requiring a treatment from the first buffer unit **160-1** and transfer it to the liquid treating unit **130**. The first transfer robot **172-1** may transfer the untreated substrate W taken into the 1-1 buffer unit **160-1a** or the substrate W required to be treated to the liquid treating unit **130**. The first transfer robot **172-1** may take out the substrate W treated by the liquid treating unit **130** and transfer the substrate W to the 1-1 buffer unit **160-1a**. In this case, the first posture changing robot **220-1** may transfer the liquid-treated substrate W stored in the 1-2 buffer unit **160-1b** to the first posture changing unit **50**.

(129) The posture of the substrate W of the first posture changing unit **50** may be changed. The first posture changing unit **50** may be positioned between the first process treating unit **40** that treats the substrate W in a single-type method and the second process treating unit **60** that treats the substrate in a batch-type method. The first posture changing unit **50** may be positioned between the first process treating unit **40** that treats the substrate W in the horizontal posture and the second process treating unit **60** that treats the substrate W in the vertical posture. The first posture changing unit **50** may convert the posture of the substrate W from the horizontal posture to the vertical posture. The first posture changing unit **50** may change the substrate W treated in the horizontal posture in the first process treating unit **40** to the vertical posture.

(130) The first posture changing unit **50** may be provided in the same structure as the posture changing unit **20** provided to the substrate treating apparatus **1** according to an embodiment. The first posture changing unit **50** may include a first posture changing treating bath **210-1** and a first posture changing robot **220-1**. The first posture changing treating bath **210-1** is provided to have the same structure as the posture changing treating bath **210** of the posture changing unit **20** according to an embodiment of the inventive concept. In addition, the first posture changing robot **220-1** is provided to have the same structure as the posture changing robot **220** of the posture changing unit **20** according to an embodiment of the inventive concept. Hereinafter, redundant descriptions will be omitted.

(131) The first posture changing robot **220-1** transfers the substrate W treated by the first process treating unit **40** to the first posture changing treating bath **210-1**. The first posture changing robot **220-1** transfers the substrate W stored in the first buffer unit **160-1** to the first posture changing treating bath **210-1**. The first posture changing robot **220-1** transfers the treated substrate W stored in the 1-2 buffer unit **160-1b** to the first posture changing treating bath **210-1**. The first posture changing robot **220-1** converts the posture of the substrate W from the horizontal posture to the vertical posture in the first posture changing treating bath **210-1**.

(132) The first posture changing treating bath **210-1** is provided in the same structure as the posture changing treating bath **210** according to an embodiment of the inventive concept (see FIG. 5). The first posture changing robot **220-1** is provided in the same structure as the posture changing robot **220** according to an embodiment of the inventive concept (see FIG. 6). Hereinafter, redundant descriptions will be omitted.

(133) The second process processor **60** may treat the substrate W treated by the first process treating unit **40**. The second process treating unit **60** may treat the liquid-treated substrate W in the first process treating unit **40**. The second process treating unit **60** may collectively liquid treat a plurality of substrates W in a batch-type method. For example, the second process treating unit **60** may clean the plurality of substrates W in the batch-type method. The second process treating unit **60** may simultaneously process multiple substrates W in the vertical posture (a posture where the top or bottom surface of the substrate W is parallel to the direction perpendicular to the ground).

(134) The second process treating unit **60** may include a first batch-type treating bath **310**, a second batch-type treating bath **320**, and a transfer unit **340**. In the first batch-type treating bath **310**, the plurality of substrates W may be simultaneously liquid-treated with the second treating liquid. The second treating liquid may be a chemical. The second treating liquid may be a chemical having the properties of a strong acid or a strong base. The chemical may include, for example, an ammonia-hydrogen peroxide mixture (APM), a hydrochloric acid-hydrogen peroxide mixture (HPM), a hydrofluoric acid-hydrogen peroxide mixture (FPM), a diluted sulfuric acid peroxide (DSP), a chemical including a SiN, a chemical including a phosphoric acid, and a chemical including a sulfuric acid.

(135) In the second batch-type treating bath **320**, the plurality of substrates W may be simultaneously liquid-treated with a third treating liquid. The second treating liquid may be a rinsing liquid. The rinsing liquid may be a liquid containing a water. For example, the rinsing liquid may be appropriately selected from a pure water or ozone water.

(136) Each of the first batch-type treating bath **310** and the second batch-type treating bath **320** is provided to have the same structure as the first batch-type treating bath **310** and the second batch-type treating bath **320** according to an embodiment of the inventive concept. Hereinafter, redundant descriptions will be omitted.

(137) The transfer unit **340** may transfer the substrate W between the first posture changing unit **50**, the second process treating unit **60**, and the second posture changing unit **70**. The transfer unit **340** may transfer the substrate W between the first posture changing treating bath **210-1**, the first batch-type treating bath **310**, the second batch-type treating bath **320**, and the second posture changing treating bath **210-2**.

(138) Referring to FIG. **9**, the transfer unit **340** may include a rail extending along the first direction X and a hand configured to carry a plurality of substrates W at once. The transfer unit **340** may hold the substrates W which posture has been changed in the first posture changing treating bath **210-1** and transfer the gripped substrate W to the second process treating unit **60**. The transfer unit **340** may hold a plurality of substrates W in a vertical posture in the first posture changing treating bath **210-1**, and transfer the plurality of substrates W to the first batch-type treating bath **310**.

(139) The transfer unit **340** may hold the treated substrates W in the first batch-type treating bath **310** and transfer them to the second batch-type treating bath **320**. The transfer unit **340** may hold the substrate W that has been treated with liquid in the second batch-type treating bath **320** and transfer it to the second posture changing treating bath **210-2**. When the substrate W needs to be treated with the second treating liquid in the first batch-type treating bath **310** and the third treating liquid in the second batch-type treating bath **320**, the transfer unit **340** may repeatedly transfer the substrate W between the first batch-type treating bath **310** and the second batch-type treating bath **320**.

(140) The second posture changing unit **70** may change the posture of the substrate W. The second posture change unit **70** may be disposed between the second process treating unit **60** that treats the substrate in a batch-type method and the third treating unit **80** that treats the substrate W in a single-type method. The second posture changing part **70** may be positioned between the second process treating unit **60** that treats the substrate W in the vertical posture and the third process treating unit **80** that treats the substrate W in the horizontal posture. The second posture changing unit **70** may convert the posture of the substrate W from the vertical posture to the horizontal posture.

(141) The second posture changing unit **70** may be provided in the same structure as the posture changing unit **20** provided to the substrate treating apparatus **1** according to an embodiment. The second posture change unit **70** may include a second posture changing treating bath **210-2** and a second posture changing robot **220-2**. The second posture changing treating bath **210-2** is provided to have the same structure as the posture changing treating bath **210** of the posture changing unit **20** in accordance with an embodiment of the inventive concept. The second posture changing robot **220-2** is provided to have the same structure as the posture changing robot **220** of the posture changing unit **20** according to an embodiment of the inventive concept. Hereinafter, redundant descriptions will be omitted.

(142) The second posture changing robot **220-2** transfers the substrate W treated by the second process treating unit **60** to the second posture changing treating bath **210-2**. The second posture changing robot **220-2** changes the posture of the substrate W stored in the second posture changing treating bath **210-2**. The second posture changing robot **220-2** changes the posture of the substrate W stored in the second posture changing treating bath **210-2** from the horizontal posture to the vertical posture. The second posture changing robot **220-2** grips a plurality of substrates W converted into the vertical posture and transfers the plurality of substrates W to the second buffer unit **160-2** of the third process treating unit **80**.

(143) The second posture changing treating bath **210-2** is provided in the same structure as the

posture changing treating bath **210** according to an embodiment of the inventive concept (see FIG. 5). The second posture changing robot **220-2** is provided in the same structure as the posture changing robot **220** according to an embodiment of the inventive concept (see FIG. 6). Hereinafter, redundant descriptions will be omitted.

(144) The third process treating unit **80** may treat the substrate W in a single-type method. The third process treating unit **80** may unload the substrate W in the horizontal posture. The third process treating unit **80** may treat the substrate W in the horizontal posture. The third process treating unit **80** may include a second load port unit **110-2**, a second index unit **120-2**, an organic solvent treating unit **140**, a drying treating unit **150**, a second buffer unit **160-2**, and a second transfer treating unit **170-2**. The second load port unit **110-2** and the second index unit **120-2** may be referred to as a second index module, and the organic solvent treating unit **140**, the drying treating unit **150**, the second buffer unit **160-2**, and the second transport treating unit **170-2** may be referred to as a second process module.

(145) The second load port unit **110-2** may include a plurality of load ports. A transfer container F in which at least one substrate W is stored may be placed on the load ports of the second load port unit **110-2**. A plurality of substrates W may be stored in the transfer container F. For example, 25 substrates may be stored in the transfer container F. The transfer container F may be referred to as a cassette, a pod FOD, a FOUP, or the like. The transfer container F may be unloaded from the second load port unit **110-2** by a container transport device (e.g., OHT). The transfer container F placed in the second load port unit **110-2** may store the substrates W treated in the first process treating unit **40**, the second treating unit **60**, and the third treating unit **80**. The transfer container F placed in the second load port unit **110-2** may store only the substrate W treated in the first process treating unit **40**, the second treating unit **60**, and the third treating unit **80**. That is, the second load port unit **110-2** may perform a function of unloading the treated substrate W from the substrate treating apparatus.

(146) The second index unit **120-2** may be coupled to the second load port unit **110-2**. The second index unit **120-2** and the second load port unit **110-2** may be arranged in the second direction Y. The second index portion **120-2** may be disposed between the second load port unit **110-2** and the second buffer portion **160-2**. The second index unit **120-2** may include a second index robot **122-2**. The second index robot **122-2** may take out the treated substrate W taken into the second buffer unit **160-2** and transfer it to the container F mounted on the second load port unit (**110-2**). The container F may be transferred to the outside of the substrate treating apparatus **2** by an article transfer apparatus (e.g., OHT).

(147) The second index robot **122-2** may have a hand capable of holding and transferring the substrate W. The hand of the second index robot **122-2** may be a single-type hand for transferring the substrate W one by one. The hand of the second index robot **122-2** may be provided to be movable along the first direction X, the second direction Y, and the third direction Z. In addition, the hand of the second index robot **122-2** may be rotatably provided with the third direction Z as a rotation axis.

(148) The organic solvent treating unit **140** may be provided with the substrate treating apparatus in which a liquid treating is performed in a single-type method. The substrate treating apparatus provided to the organic solvent treating unit **140** may have the same structure as the substrate treating apparatus **400** provided to the liquid treating unit **130** shown in FIG. 2. Thus, the same drawing number is assigned to the same structure, and a redundant description is omitted.

(149) A plurality of organic solvent treating units **140** may be provided. The plurality of organic solvent treating units **140** may be provided and stacked in the vertical direction. The organic solvent treating unit **140** may be disposed on a side of the first transfer treating unit **170-1**. The organic solvent treating unit **140** may face the second buffer unit **160-2** based on the first transfer treating unit **170-1**. When viewed from above, the organic solvent treating unit **140** may be arranged in the first direction X with the dry treating unit **150**.

(150) The organic solvent treating unit **140** may treat the substrate W one by one. The organic solvent treating unit **140** may treat the substrate W in the horizontal posture one by one. The organic solvent treating unit **140** may treat the substrate W by rotating the substrate W in the horizontal posture and supplying the treating liquid to the rotating substrate W. The treating liquid supplied from the organic solvent treating unit **140** may be substituted with the rinsing liquid to be provided as a liquid capable of removing the rinsing liquid remaining on the surface of the substrate W. For example, the treating liquid supplied from the organic solvent treating unit **140** may be an organic solvent. For example, the treating liquid supplied from the organic solvent treating unit **140** may be an isopropyl alcohol (IPA).

(151) The organic solvent treating unit **140** may supply the organic solvent to the substrate W in a rotating horizontal posture, and may dry the substrate W by rotating the substrate W. In contrast, the organic solvent treating unit **140** supplies the organic solvent to the rotating horizontal substrate W, and is transferred to the dry treating unit **150** described later while the substrate W is wet with the organic solvent, so that the substrate W may be dried in the dry treating unit **150**.

(152) The dry treating unit **150** may be provided with the substrate treating apparatus **500** in which a dry treating of the substrate is performed in a single-type method. The dry treating unit **150** may remove the treating liquid remaining on the substrate W using the drying fluid in a supercritical state. The dry treating unit **150** may be provided as a supercritical chamber to remove a treating liquid (e.g., a rinsing liquid or an organic solvent) remaining on the substrate W using a supercritical fluid. For example, the substrate treating apparatus **500** provided in the dry treating unit **150** may perform a drying process of removing the organic solvent remaining on the substrate W using supercritical carbon dioxide (CO.sub.2).

(153) The dry treating unit **150** provided in the substrate treating apparatus **2** according to another embodiment of the inventive concept may have the same structure as the dry treating unit **150** provided in the first process treating unit **10** of the substrate treating apparatus **1** according to an embodiment of the inventive concept. That is, the substrate treating apparatus **500** provided in the dry treating unit **150** according to another embodiment may be provided in the same manner as the substrate treating apparatus **500** provided in the dry treating unit **150** according to an embodiment. Hereinafter, redundant descriptions will be omitted.

(154) The second buffer unit **160-2** may provide a storage space for temporarily storing the substrate W. The second buffer unit **160-2** may temporarily store the substrate W treated by the second process treating unit **60**. The second buffer unit **160-2** may store the substrate W whose posture is changed in the second posture changing unit **70**. The second buffer unit **160-2** may temporarily store the substrate W treated by the organic solvent treating unit **140** and/or the dry treating unit **150**.

(155) The first buffer unit **160-1** may be disposed on a side of the second transfer treating unit **170-2**. The first buffer unit **160-1** may face the organic solvent treating unit **140** and/or the dry treating unit **150** with respect to the second transfer treating unit **170-2**.

(156) The second buffer unit **160-2** may include a plurality of second buffer units **160**. Some of the plurality of second buffer units **160-2** may temporarily store the substrate W treated by the second process treating unit **60** and/or the substrate W whose which has changed in the second posture changing unit **70** (hereinafter, referred to as the 2-1 buffer unit **160-2a**). The other part of the plurality of second buffer units **160-2** may temporarily store the substrate W treated by the organic solvent treating unit **140** and/or the dry treating unit **150** (hereinafter, referred to as the 2-2 buffer unit **160-2b**). The 2-1 buffer unit **160-2a** may be disposed closer to the second posture changing unit **70** than the 2-2 buffer unit **160-2b**.

(157) The 2-1 buffer unit **160-2a** may be opened toward the second posture changing unit **70** when viewed from above. Accordingly, the 2-1 buffer unit **160-2a** may be transferred to the 2-1 buffer unit **160-2a** by the second transfer robot **172-2** with the substrate W treated by the second process treating unit **60** or the substrate W which posture has been changed by the second posture changing

unit **70**. In addition, the 2-1 buffer unit **160-2a** may be opened toward the transfer treating unit **170** when viewed from above. Accordingly, the substrate W stored in the 2-1 buffer unit **160-2a** may be transferred to the organic solvent treating unit **140** and/or the dry treating unit **150** through the second transfer robot **172-2**.

(158) The 2-2 buffer unit **160-2b** may be opened toward the second transfer treating unit **170-2** when viewed from above. Accordingly, the substrate W treated by the organic solvent treating unit **140** and/or the dry treating unit **150** may be transferred to the 2-1 buffer unit **160-2a** through the second transfer robot **172-2**. The treated substrate W may be transferred to the second load port unit **110-2** by the index robot **122**.

(159) The second buffer unit **160-2** may be provided in the same structure as the buffer unit **160** provided in the first process treating unit **10** of the substrate treating apparatus **10** according to an embodiment of the inventive concept (see FIG. **4**). Hereinafter, a redundant description will be omitted.

(160) The second transfer treating unit **170-2** may be provided between the organic solvent treating unit **140** and the second buffer unit **160-2**. The second transfer treating unit **170-2** may be provided between the dry treating unit **150** and the second buffer unit **160-2**. An organic solvent treating unit **140** and a dry treating unit **150** may be provided on a side of the transfer treating unit **170**. A second buffer unit **160-2** may be provided on the other side of the second transfer treating unit **170-2**. The second transfer treating unit **170-2** may have a second transfer robot **172-2**. The second transfer robot **172-2** may have a single-type transfer hand for transferring a substrate W by one by one. The second transfer robot **172-2** may transfer the substrate W between the organic solvent treating unit **140**, the dry treating unit **150**, and the buffer unit **160**.

(161) The second transfer robot **172-2** may take out the substrate W from the 2-1 buffer unit **160-2a** and transfer the substrate W to the organic solvent treating unit **140**. The second transfer robot **172-2** may transfer the substrate W treated by the organic solvent treating unit **140** to the dry treating unit **150**. The second transfer robot **172-2** may supply the organic solvent from the organic solvent treating unit **140** to the 2-2 buffer unit **160-2b**, which means that the substrate W is dried by rotating the substrate W while the substrate W is wet into the organic solvent. The second transfer robot **172-2** may transfer the substrate W treated by the dry treating unit **150** to the 2-2 buffer unit **160-2b**.

(162) The controller **900** may control the substrate treating apparatus **1** and **2**. For example, the controller **900** may control components of the substrate treating apparatus **1** and **2**. For example, the controller **900** may control the substrate treating apparatus **1** and **2** so that the substrate treating apparatus **1** and **2** may perform a process of treating the substrate W.

(163) The controller may comprise a process controller consisting of a microprocessor (computer) that executes a control of the substrate treating apparatus, a user interface such as a keyboard via which an operator inputs commands to manage the substrate treating apparatus, and a display showing the operation situation of the substrate treating apparatus, and a memory unit storing a treating recipe, i.e., a control program to execute treating processes of the substrate treating apparatus by controlling the process controller or a program to execute components of the substrate treating apparatus according to data and treating conditions. In addition, the user interface and the memory unit may be connected to the process controller. The treating recipe may be stored in a storage medium of the storage unit, and the storage medium may be a hard disk, a portable disk, such as a CD-ROM or a DVD, or a semiconductor memory, such as a flash memory.

(164) FIG. **10** is a flowchart illustrating a substrate treating method using the substrate treating apparatus of FIG. **1** or the substrate treating apparatus of FIG. **2**. FIG. **11** and FIG. **12** illustrate a posture changing robot changing the posture of a substrate to the horizontal posture in a second posture changing step of FIG. **10**. FIG. **13** illustrates the posture changing robot performing the wetting step of FIG. **10**. FIG. **14** is a top view illustrating a state in which the liquid supply member supplies the wetting liquid in the wetting step of FIG. **10**. FIG. **15** is a side view of a state in which

the liquid supply member supplies the wetting liquid in the wetting step of FIG. 19. FIG. 16 illustrates a hand according to another embodiment of the inventive concept. FIG. 17 is a top view illustrating a state in which the liquid supply member of FIG. 16 supplies the wetting liquid to the substrate.

(165) Referring to FIG. 10, the substrate treating method **S100** according to an embodiment of the inventive concept may include a substrate loading step **S110**, a first single-type treating step **S120**, a first posture changing step **S130**, a batch-type treating step **S140**, a second posture changing step **S150**, a second single-type treating step **S160**, and a substrate unloading step **S170**.

(166) In the substrate loading step **S110**, a so-called substrate **W** in an untreated state, which requires treating, may be loaded on the substrate treating apparatus **1** and **2**. In the substrate loading step **S110**, a transfer container **F** may be placed on the first load port unit **110-1**.

(167) In the substrate treating apparatus **1** of FIG. 1, the substrate **W** stored in the transfer container **F** may be taken out by the index robot **122** and transferred to the buffer unit **160**. In the substrate treating apparatus **2** of FIG. 9, the substrate **W** stored in the transfer container **F** may be taken out by the first index robot **122-1** and transferred to the first buffer unit **160-1**. In the substrate treating apparatus **2** of FIG. 9, the substrate **W** stored in the transfer container **F** may be taken out by the first index robot **122-1** and transferred to the 1-1 buffer unit **160-1a**.

(168) In the first single-type treating step **S120**, the substrate **W** having a horizontal posture may be treated in a single-type method. In the first single-type treating step **S120**, the substrate **W** may be treated by supplying a first treating liquid capable of etching an oxide film to the substrate **W**. The first treating liquid may be a dilute hydrofluoric acid (DHF). In the first single-type treating step **S120**, the first treating liquid may be supplied to the substrate **W**, and the substrate **W** may be rotated to treat the substrate **W**.

(169) In the substrate treating apparatus **1** of FIG. 1, the first transfer robot **172** may take out the substrate **W** from the buffer unit **160** and transfer it to the liquid treating unit **130**. The first transfer robot **172** may transfer the substrate **W** taken out from the buffer unit **160** in the horizontal posture. The first transfer robot **172** may transfer the substrate **W** taken out from the buffer unit **160** to the substrate treating apparatus **400** of the liquid treating unit **130**, and may seat the substrate **W** on the support unit **440** in the horizontal posture. The support unit **440** may rotate the substrate **W**. The liquid supply unit **480** may supply the first treating liquid to the rotating substrate **W**. The substrate **W** treated by the liquid treating unit **130** may be transferred to the buffer unit **160** by the first transfer robot **172**.

(170) In the substrate treating apparatus **1** of FIG. 2, the first transfer robot **172-1** can take out the substrate **W** from the 1-1 buffer unit **160a** and transfer it to the liquid treating unit **130**. The first transfer robot **172-1** may transfer the substrate **W** taken out from the 1-1 buffer unit **160-1a** in the horizontal posture. The first transfer robot **172-1** transfers the substrate **W** taken out from the 1-1 buffer unit **160-1a** to the substrate treating apparatus **400** of the liquid treating unit **130**, and can seat the substrate **W** on the support unit **440** in a horizontal posture. The support unit **440** may rotate the substrate **W**. The liquid supply unit **480** may supply the first treating liquid to the rotating substrate **W**. The substrate **W** treated by the liquid treating unit **130** may be transferred to the 1-2 buffer unit **160-1a** by the first transfer robot **172-1**.

(171) In the first posture changing step **S130**, the posture of the substrate **W** may be changed from the horizontal posture to the vertical posture. In the first posture changing step **S130**, the positions of the plurality of substrates **W** may be changed at once.

(172) In the substrate treating apparatus **1** of FIG. 1, the posture of the plurality of substrates **W** placed on the buffer unit **160** may be changed at once by the posture changing unit **20**. The posture changing robot **220** may transfer a plurality of substrates **W** stored in the horizontal position to the buffer unit **160** to the posture changing treating bath **211**. The posture changing robot **220** may change the posture of a plurality of substrates **W** from the horizontal posture to the vertical posture in the posture changing treating bath **211**. The substrate **W** changed to the vertical posture may be

transferred to the first batch-type treating bath **310** of the second process treating unit **30** by the transfer unit **330**.

(173) In the substrate treating apparatus **2** of FIG. **9**, the posture of the plurality of substrates **W** placed on the 1-2 buffer unit **160-2a** may be changed at once by the first posture changing unit **50**. The first posture changing robot **220-1** may transfer a plurality of substrates **W** stored in a horizontal position in the 1-2 buffer unit **160-1b** to the first posture changing treating bath **210-1**. The first posture changing robot **220-1** may change the posture of a plurality of substrates **W** from the horizontal posture to the vertical posture in the first posture changing treating bath **210-1**. The substrate **W** changed to the vertical posture may be transferred to the first batch-type treating bath **310** of the second process treating unit **60** by the transfer unit **340**.

(174) In the batch-type treating step **S140**, a liquid treatment may be performed on the plurality of substrates **W** in the vertical posture. In the batch-type treating step **S140**, the plurality of substrates **W** may be simultaneously liquid-treated with the second treating liquid, and then the plurality of substrates **W** may be simultaneously treated with the third treating liquid. The second treating liquid may be a chemical having the properties of a strong acid or a strong base. The chemical may include, for example, an ammonia-hydrogen peroxide mixture (APM), a hydrochloric acid-hydrogen peroxide mixture (HPM), a hydrofluoric acid-hydrogen peroxide mixture (FPM), a diluted sulfuric acid peroxide (DSP), a chemical including a SiN, a chemical including a phosphoric acid, and a chemical including a sulfuric acid.

(175) In the substrate treating apparatus **1** and **2** of FIGS. **1** and **9**, the plurality of substrates **W** may be simultaneously treated with a second treating liquid in the first batch-type treating bath **310**. If the treating is completed in the first batch-type treating bath **310**, the transfer units **330** and **340** simultaneously transfer the plurality of substrates **W** stored in the first batch-type treating bath **310** to the second batch-type treating bath **320**. In the second batch-type treating bath **320**, the plurality of substrates **W** may be simultaneously liquid-treated with a third treating liquid.

(176) In the substrate treating apparatus **1** of FIG. **1**, if the treating is completed in the second batch-type treating bath **320**, the plurality of substrates **W** rinse-treated with the third treating liquid may be transferred to the posture change unit **330**. The transfer unit **330** may transfer the plurality of rinse-treated substrates **W** to the posture changing treating bath **210** at once.

(177) In the substrate treating apparatus **2** of FIG. **9**, if the treating is completed in the second batch-type treating bath **320**, the plurality of substrates **W** rinse-treated with the third treating liquid may be transferred to the second posture changing unit **70** by the transfer unit **340**. The transfer unit **340** may transfer the plurality of rinse-treated substrates **W** to the second posture changing treating bath **210-2** at once.

(178) The second posture changing step **S150** may be performed at the posture changing unit **20** in the substrate treating apparatus **1** of FIG. **1**, and at a second posture changing unit **70** in the substrate treating apparatus **2** of FIG. **9**. The second posture changing step **S150** may include a holding step of holding the substrate **W** and a rotation step of changing the posture of the substrate **W**. A posture change of the substrate **W** may be performed by each sheet at the second posture changing step **S150**.

(179) For example, as shown in FIG. **11**, in the holding step of the second posture changing step **S150**, the hand **230** may approach any one of the substrates **W** supported by the support member **212** in a vertical posture. The hand **230** may be moved so that the substrate **W** may be positioned between the first guide portion **162** and the second guide portion **163**. If the substrate **W** is positioned between the first guide portion **162** and the second guide portion **163**, the chucking body **165** may hold the substrate **W**.

(180) If the hand **230** holds the substrate **W**, the substrate **W** may be upwardly moved so that the substrate **W** may escape from the support groove formed at the support member **212**.

(181) Thereafter, as shown in FIG. **11**, in the rotation step of the second posture changing step **S150**, the substrate **W** may be linearly moved along a direction (for example, a horizontal direction)

to change the position of the substrate W while rotating the substrate W based on an axis of the fastening member **236**. That is, in the rotation step, the hand **230** may rotate with respect to an axis, and the hand **230** may linearly move according to the horizontal direction. In this case, a position of an end of the substrate W may be changed while drawing a virtual curve (e.g., a cut parabola). That is, the posture of the substrate W may be changed from the vertical posture to the horizontal posture in a state immersed in the treating liquid L while drawing the cut parabola. Also, the rotation of the substrate W may be performed in a direction in which an end of the substrate W moves away from the hand **156-H**.

(182) In addition, a difference between a time at which a rotation of the substrate W ends and a time at which a linear movement of the substrate W ends may be less than or equal to a set time. For example, these two time points may be the same time point. That is, at a time point at which the linear movement of the substrate W is finished, the rotation of the substrate W by the fastening body **166** may be simultaneously be terminated.

(183) In addition, while the substrate W is held and the substrate W is rotated, the vision member **167** may not be immersed in the treating liquid L. That is, the vision member **167** may be installed at a position which is not immersed in the treating liquid L stored in the posture changing treating bath **211**, **210-1**, and **210-2**. Accordingly, it is possible to minimize a problem of the vision member **167** being damaged by the treating liquid L.

(184) If the posture of the substrate W is changed to a state in which the substrate W is immersed in the treating liquid L, the substrate W may be damaged by a resistance of the treating liquid L. However, as in the inventive concept, if the posture is changed while the substrate W is immersed in the treating liquid L by linearly moving and rotating simultaneously, it is possible to suppress the resistance caused by the treating liquid L from being transferred to the substrate W as much as possible. In addition, if the substrate W is moved away from the treating liquid L (i.e., exposed to air) and the posture is changed, the wettability of the substrate W may not be maintained and a water mark may be generated on the substrate W, and this problem can be minimized by changing the posture of the substrate W while the substrate W is immersed in the treating liquid L.

(185) After the second posture changing step **S150** is performed, the wetting step (not shown) may be performed. The wetting step **S50** may be performed between the second posture changing step **S150** and the second single-type treating step **S160**.

(186) In a case of the substrate treating apparatus of FIG. **1**, the wetting step may be performed at the posture changing robot **220** and/or the buffer unit **160**. In a case of the substrate treating apparatus **2** of FIG. **9**, the wetting step may be performed by the second posture changing robot **220-2** and/or the 2-1 buffer unit **160-2a**.

(187) In the wetting step **S50**, a natural drying of the substrate W may be prevented by spraying the wetting liquid to the substrate W exposed to the outside away from the treating liquid L. The wetting liquid may be the same type of liquid as the treating liquid L stored in the above-described posture changing treating bath **220**, **220-1**, and **220-2**. In contrast, the wetting liquid may be a type of liquid different from the above-described treating liquid L.

(188) For example, as illustrated in FIG. **13**, a posture changing of the substrate W is completed, and the posture changing robot **220** and **220-2** may upwardly move the substrate W to deviate from the treating liquid L stored at the posture changing treating bath **220** and **220-2**. If the substrate W deviates from the treating liquid L, the liquid supply member **168** may supply the wetting liquid WL. In this case, as shown in FIG. **14** and FIG. **15**, the wetting liquid WL may be supplied to the first region and the second region which are edge regions of the substrate W. The wetting liquid WL supplied to the edge region of the substrate W may flow along the top surface of the substrate W to form a liquid film on the top surface of the substrate W. If the wetting liquid WL flows along the edge region of the substrate W to form the liquid film, a splashing of the wetting liquid WL is maximally suppressed, thereby making a more efficient treatment of the substrate W possible.

(189) Also, the wetting step **S50** may be performed at the first buffer unit **210** as described above.

The substrate W on which the second posture changing step S150 is performed may be transferred to the first buffer unit **210** by the posture changing robot **156**. In the wetting step S30, if the substrate W is taken into the first buffer unit **210**, the wetting nozzle **216** of the first buffer unit **210** may spray the wetting liquid to the substrate W.

(190) As the wetting step S30 is performed, it is possible to minimize the natural drying of the substrate W before the substrate W is taken into the single-type treating chamber.

(191) The single-type treating step S60 may include a liquid treating step S61 and a drying step S162.

(192) In the second single-type treating step S160, treating may be performed on a single substrate W in the horizontal posture. The second single-type treating step S160 may include an organic solvent treating step S161 and a drying step S162. An organic solvent such as IPA may be supplied onto the substrate W to the organic solvent treating step S161. An organic solvent such as IPA may be supplied onto the substrate W to the organic solvent treating step S161.

(193) The organic solvent treating step S161 may liquid treat the substrate W in a single-type method.

(194) In the case of the substrate treating apparatus **1** of FIG. **1**, if the substrate which is temporarily stored at the buffer unit **160** is transferred to the organic solvent treating unit **140**, the organic solvent treating step S161 may be performed at the organic solvent treating unit **140**. In the case of the substrate treating apparatus **2** of FIG. **9**, if the substrate W which is temporarily stored at the 2-2 buffer unit **160-2b** is transferred to the organic solvent treating unit **140**, the organic solvent treating step S161 may be performed at the organic solvent treating unit **140**.

(195) In the drying step S162, the substrate W may be dried in a single-type method. The drying step S162 can be performed at the dry treating chamber **150** if the substrate W which is liquid treated in the liquid treating step S161 is transferred to the dry treating chamber **150**. In the drying step S162, a treating fluid in a supercritical state (e.g., supercritical carbon dioxide) may be supplied to the substrate W to remove an organic solvent, a wetting liquid, or a treating liquid L remaining on the substrate.

(196) In some cases, the drying step S162 may not be performed at the dry treating unit **150**, but the substrate W may be dried by rotating the substrate W at the organic solvent treating unit **140** at a high speed (so-called spin drying).

(197) If the drying step **162** is completed, a substrate unloading step S170 of unloading the substrate W is performed.

(198) In the case of the substrate treating apparatus in FIG. **1**, in the substrate unloading step S170, the substrate W on which the second single-type treating step S160 is performed may be transferred to the buffer unit **160** and then transferred to the transfer container F placed on the second load port unit by the first transfer robot **172**, and the transfer container F placed on the second load port unit may be held by a transfer apparatus such as an OHT to be unloaded from the substrate treating apparatus.

(199) In the case of the substrate treating apparatus **2** of FIG. **9**, in the substrate unloading step S170, the substrate W on which the second single-type treating step S160 is performed may be transferred to the 2-2 buffer unit **160-2b**, and then transferred to the transfer container F placed on the second load port unit **110-2**, and the transfer container F placed on the second load port unit **110-2** may be held by a transfer apparatus such as an OHT to be unloaded from the substrate treating apparatus **2**.

(200) As described above, the substrate treating apparatus **1** and **2** according to an embodiment of the inventive concept may include both a batch-type treating unit and a single-type liquid treating unit. Accordingly, it may have all the advantages of the batch-type liquid treating method and the single-type liquid treating method.

(201) For example, since the batch-type treating unit **30** and **60** may treat a plurality of substrates W at once, a mass productivity of the substrate W treatment is excellent, and a treatment uniformity

between the substrates W is very high. In addition, if the pattern formed on the substrate W has a high aspect ratio, the batch-type treating unit **30** and **60** may supplement a portion that has not quite been treated (e.g., a portion that has not quite been etched) by a single-type treatment of supplying a chemical, a rinsing liquid, etc.

(202) In addition, the substrate W (e.g., a wafer) wetted by the organic solvent supplied from the organic solvent treating unit **140** may be transferred to the dry treating unit **150** for drying the substrate W by supplying a supercritical fluid. The supercritical fluid may have a high penetration force with respect to a space between patterns formed on the substrate W and may dry the substrate W without rotating the substrate W, thereby minimizing the above-described pattern leaning phenomenon. In addition, the substrate treating apparatus **1** and **2** of the inventive concept may perform all of the single-type liquid treating method, the batch-type liquid treating method, and the method of drying the substrate W using the supercritical fluid, thereby improving defects due to a particle, a falling, and a flowability. In addition, since the number of substrates W that can be treated at the batch-type treating unit **30** and **60** is relatively large, a large number of liquid treating chambers are not required, and thus a footprint of the substrate treating apparatus **10** may be reduced.

(203) In addition, like the substrate treating apparatus **1** and **2** according to an embodiment of the inventive concept, if both the second process treating unit **30** and **60** which performs a batch-type treatment and the process treating unit batch-type treating unit **140** (**10** in the case of FIGS. **1** and **40** and **80** in the case of FIG. **9**) which performs a single-type treatment are both provided, it is essential to change the posture of the substrate W from the vertical posture to the horizontal posture. Accordingly, the substrate treating apparatus **1** and **2** according to an embodiment of the inventive concept includes a posture changing robot **220**, **220-1**, **220-2** to change the posture of the substrate W from the vertical posture to the horizontal posture. In this case, the posture change of the substrate W is conducted in a state in which the substrate W is immersed in the treating liquid L so as to maintain the wettability of the substrate W as much as possible (if not, the substrate W may dry and generate a water mark).

(204) In the above-described example, it has been described that the liquid supply member **238** is installed on the support body **233**, but the inventive concept is not limited thereto. For example, as shown in FIG. **16**, the liquid supply member **239** may be installed on the fastening body **166**. The liquid supply member **239** may be a supply pipe on which a first nozzle **239a**, a second nozzle **239b**, and a third nozzle **239c** are formed. The first nozzle **239a**, the second nozzle **239b**, and the third nozzle **239c** may spray the wetting liquid WL toward the substrate W in a downwardly inclined direction. At least one of the first nozzle **239a**, the second nozzle **239b**, and the third nozzle **239c** may be formed. For example, a plurality of first nozzles **239a**, a plurality of second nozzles **239b**, and a plurality of third nozzles **239c** may be formed. The first nozzles **239a** may be disposed between the second nozzles **239b**, and the second nozzles **239b** may be disposed between the third nozzles **239c**. The first nozzles **239a** may be disposed relatively at an inner side, and the third nozzles **239c** may be disposed relatively at an outer side. Also, as illustrated in FIG. **17**, diameters of spray holes of the first nozzle **239a**, the second nozzle **239b**, and the third nozzle **239c** may be different from each other. A diameter of the spray hole of the first nozzle **239a** may be larger than that of the second nozzle **239b**, and a diameter of the spray hole of the second nozzle **239b** may be larger than that of the third nozzle **239c**. Furthermore, a supply flow rate of the wetting liquid WL per unit time transferred to the first nozzle **239a**, the second nozzle **239b**, and the third nozzle **239c** may be the same. Accordingly, regarding an injection distance of the wetting liquid WL supplied from the first nozzle **239a**, the second nozzle **239b**, and the third nozzle **239c**, the first nozzle **239a** may be the shortest, and the third nozzle **239c** may be the longest. In addition, the first nozzle **239a**, the second nozzle **239b**, and the third nozzle **239c** may supply the wetting liquid WL to the edge region of the substrate W.

(205) In the above-described example, it has been described that the posture changing robot **220**,

220-1 and **220-2** supplies the wetting liquid WL to the edge region of the substrate W, but the inventive concept is not limited thereto. For example, as shown in FIG. **18**, the liquid supply member **247** may be fastened to the third arm **175**. In addition, the liquid supply member **247** may be provided to be rotatable with a direction parallel to a rotation axis of the fourth arm **176** as a rotation axis, and may be configured to supply the wetting liquid WL to a center region of the substrate W placed on the hand **231**.

(206) FIG. **19** is a top view of the hand according to another embodiment of the inventive concept, and FIG. **20** is a side view of the hand of FIG. **19**.

(207) Referring to FIG. **19** and FIG. **20**, the hand **250** according to another embodiment that the posture changing robot **220**, **220-1**, and **220-2** may have may include a support body **251**, a guide portion **252**, a chucking body **253**, a driving member **254**, a rotation member **255**, a rotation motor **256**, a connection body **257**, and a vision member **258**.

(208) The support body **251** may have a finger shape. The guide portion **252** may be provided at a distal end of the support body **251**. The guide portion **252** may support a side portion of the substrate W, and the support body **251** may support the bottom surface of the substrate W.

(209) The chucking body **253** may move in a direction by the driving member **254**. The chucking body **253** may be moved between a chucking position for chucking the substrate W and a standby position for not chucking the substrate W by the driving member **254**. The rotation member **255** may rotate the support body **251** and the substrate W based on an axis, and the rotation motor **255** may transfer a driving force for rotating the rotation member **256**. The connection body **257** may be connected to the joint portion **156-R** of the posture changing robot **220**, **220-1**, and **220-2**. The vision member **258** may perform the same or a similar function as the above-described vision member **257**. In addition, similar to the vision member **257**, the vision member **258** may be installed at a position which is not immersed in the treating liquid L stored in the posture changing treating bath **151** when the posture of the substrate W is changed.

(210) FIG. **21** is a top view of a hand according to another embodiment of the inventive concept, and FIG. **22** is a side view of the holder of FIG. **21**. Referring to FIG. **21** and FIG. **22**, the hand **260** of the posture changing robots **220**, **220-1**, **220-2** according to another embodiment of the inventive concept may include a fastening body **261**, a rotating member **262**, a chucking body **263**, and a holder **264**. The fastening body **261** may be coupled to the joint portion **156-R** of the posture changing robots **220**, **220-1**, and **220-2**. The rotation member **262** may rotate the chucking body **263**. A plurality of grippers **264** may be installed in the chucking body **263**. A hold groove **265** for holding a side portion of the substrate W may be formed in the holder **264**.

(211) In the above-described example, the substrate treating apparatus **1** and **2** according to an embodiment of the inventive concept includes both a liquid treating chamber unit **130**, an organic solvent treating unit **140**, and a dry treating chamber **150**, but is not limited thereto. For example, the substrate treating apparatus **1** and **2** may include only one of the liquid treating unit **130**, the organic solvent treating unit **140**, and the dry treating chamber **150**.

(212) In the above-described example, the substrate W taken out from the batch-type treating unit **30** and **60** is transferred to the organic solvent treating unit **140**, and after the substrate W treatment is completed at the organic solvent treating unit **140**, the substrate W is transferred to the dry treating chamber **150**. For example, if a particle level is good, the substrate W may be directly transferred to the dry treating unit **150** from the batch-type liquid treating unit **30** and **60**.

(213) In the above-described example, the liquid treating unit **130** may liquid treat the substrate W by a first treating liquid including a hydrofluoric acid or the like, and the first batch-type treating bath **310** may liquid treat the substrate with a second treating liquid including a phosphoric acid, but the inventive concept is not limited thereto. For example, the liquid treating unit **130** may treat the substrate with a second treating liquid containing a phosphoric acid, etc., and the substrate W may be batch-treated with a first treating liquid containing a hydrofluoric acid in the first batch-type treating bath **310**.

(214) The substrate treating apparatus **1** and **2** according to an embodiment of the inventive concept may minimize the number of batch-type treating baths included in the substrate treating apparatus **1** and **2** by configuring a substrate treatment according to the first treating liquid among the first to the third treating liquids in the single-type method and according to the second and the third treating liquids in the batch-type method. The batch-type treating bath has a problem in that the amount of fume generated by the treating liquid is higher than that of the single-type treating apparatus, and according to the embodiment of the inventive concept, the number of batch-type treating baths may be minimized.

(215) In addition, the substrate treating apparatus **1**, **2** according to the embodiment of this invention have the advantage of reducing a total length of the substrate treating apparatus **1**, **2** by reducing the number of batch-type treating baths.

(216) The effects of the inventive concept are not limited to the above-mentioned effects, and the unmentioned effects can be clearly understood by those skilled in the art to which the inventive concept pertains from the specification and the accompanying drawings.

(217) Although the preferred embodiment of the inventive concept has been illustrated and described until now, the inventive concept is not limited to the above-described specific embodiment, and it is noted that an ordinary person in the art, to which the inventive concept pertains, may be variously take out the inventive concept without departing from the essence of the inventive concept claimed in the claims and the modifications should not be construed separately from the technical spirit or prospect of the inventive concept.

Claims

1. A substrate treating apparatus comprising: a first process treating unit configured to treat a substrate in a single-type method; a second process treating unit configured to treat a substrate in a batch-type method; and a posture changing unit configured to transfer the substrate between the first process treating unit and the second process treating unit and to change a posture of the substrate between a vertical posture and a horizontal posture, wherein the posture changing unit comprises: a posture changing treating bath having a storage space for storing the substrate and includes at least one of a first, second, or third treating liquid; and a posture changing robot configured to discharge the substrate immersed in liquid within the storage space one by one, change the posture of the substrate from the vertical posture to the horizontal posture, and transfer the substrate to a buffer unit, wherein the buffer unit is configured to store the substrate in the horizontal posture.
2. The substrate treating apparatus of claim 1, wherein the posture changing unit further comprises: a support member positioned within the storage space of the posture changing treating bath and which supports the substrate which has its posture changed by the posture changing robot in the vertical posture.
3. The substrate treating apparatus of claim 1, wherein the first process treating unit comprises: a liquid treating unit configured to treat the substrate in the single-type method by supplying a first treating liquid to the substrate in the horizontal posture; and the buffer unit configured to store the substrate which has been treated at the liquid treating unit in the horizontal posture.
4. The substrate treating apparatus of claim 3, wherein the posture changing robot transfers the substrate between the buffer unit and the posture changing treating bath, and the posture changing robot changes the substrate which is stored at the buffer unit in the horizontal posture to the vertical posture to transfer to the posture changing treating bath, and changes the substrate which is stored at the posture changing treating bath in the vertical posture to the horizontal posture to transfer to the buffer unit.
5. The substrate treating apparatus of claim 4, wherein the second process treating unit comprises: a plurality of batch-type treating baths for batch-type treating the substrate; and a transfer unit

configured to transfer the substrate between the posture changing treating bath and the plurality of batch-type treating baths.

6. The substrate treating apparatus of claim 5, wherein the plurality of batch-type treating baths comprise: a first batch-type treating bath for batch-type treating the substrate by supplying a second treating liquid to the substrate; and a second batch-type treating bath for batch-type treating the substrate by supplying a third treating liquid to the substrate.

7. The substrate treating apparatus of claim 4, wherein the first process treating unit comprises: an organic solvent treating unit configured to single-type treat the substrate by supplying an organic solvent to the substrate; a supercritical treating unit configured to single-type treat the substrate by supplying a drying fluid to the substrate; and a transfer treating unit configured to transfer the substrate between the buffer unit, the liquid treating unit, the organic solvent treating unit, and the supercritical treating unit.

8. The substrate treating apparatus of claim 1, wherein the first process treating unit includes a load port unit configured to include a plurality of load ports, and a portion of the plurality of load ports are provided as a first load port unit at which the substrate is loaded in the horizontal posture, and the other portion of the plurality of load ports are provided as a second load port unit at which the substrate is unloaded in the horizontal posture.

9. The substrate treating apparatus of claim 1, wherein the posture changing robot comprises: a hand which is configured to hold the substrate; and an arm which moves the hand, wherein a surface of the substrate stored in the buffer unit remains in a wetted state.

10. The substrate treating apparatus of claim 1, further comprising a controller, and wherein the controller controls the substrate to sequentially perform: a substrate loading step for loading the substrate to the load port of the first process treating unit in the horizontal posture; a first single-type treating step for treating the substrate at the liquid treating unit of the first process treating unit in the horizontal posture; a first posture changing step for changing the posture of the substrate from the horizontal posture to the vertical posture; a batch-type treating step for treating the substrate at the second process treating unit in the vertical posture; a second posture changing step for changing the posture of the substrate from the vertical posture to the horizontal posture; a second single-type treating step for treating the substrate at the first process treating unit in the horizontal posture; and a substrate unloading step for unloading the substrate to the load port of the first process treating unit in the horizontal posture.

11. A substrate treating apparatus comprising: a first process treating unit configured to treat a substrate in a single-type method; a second process treating unit configured to treat a plurality of substrates in a batch-type method; a third process treating unit configured to treat the substrate in a single-type method; a first posture changing unit provided between the first process treating unit and the second process treating unit and which is configured to change a posture of the substrate between a vertical posture and a horizontal posture; and a second posture changing unit provided between the second process treating unit and the third process treating unit and which is configured to change a posture of the substrate between the vertical posture and the horizontal posture, wherein the second process treating unit is provided between the first process treating unit and the third process treating unit, wherein the second process treating unit further comprises a transfer unit configured to transfer the plurality of substrates treated in the second process treating unit to the second posture changing unit, wherein the second posture changing unit comprises: a second posture changing treating bath having a storage space for storing the substrate and includes at least one of a first, second, or third treating liquid; and a second posture changing robot configured to discharge the substrate immersed in liquid within the storage space one by one, change the posture of the substrate from the vertical posture to the horizontal posture, and transfer the substrate to a second buffer unit, wherein the second buffer unit is configured to store the substrate in the horizontal posture.

12. The substrate treating apparatus of claim 11, wherein the substrate is loaded to the first process

treating unit, and the substrate is unloaded by the second process treating unit, and wherein a surface of the substrate stored in the second buffer unit remains in a wetted state.

13. The substrate treating apparatus of claim 11, wherein the first process treating unit comprises: a first load port unit configured to include a plurality of load ports at which the substrate is loaded in the horizontal posture; a liquid treating unit configured to single-type treat the substrate in the horizontal posture by supplying a first treating liquid to the substrate; and a first buffer unit configured to store a substrate which has been treated at the liquid treating unit in the horizontal posture, and wherein the third process treating unit comprises: an organic solvent treating unit configured to single-type treat the substrate in the horizontal posture by supplying an organic solvent to the substrate; a dry treating unit configured to single-type treat the substrate in the horizontal posture by supplying a drying fluid to the substrate; and a second buffer unit configured to store the substrate which has been single-type treated at the organic solvent treating unit and the dry treating unit in the horizontal posture.

14. The substrate treating apparatus of claim 13, wherein the first posture changing unit comprises: a first posture changing robot for changing the posture of the substrate between the vertical posture and the horizontal posture; a first posture changing treating bath having a storage space for storing the substrate, wherein the posture changing treating bath includes at least one of a first, second, or third treating liquid; and a first support member positioned within the storage space of the first posture changing treating bath and which supports the substrate which has its posture changed by the first posture changing robot in the vertical posture, wherein the first posture changing robot changes the substrate stored at the first buffer unit in the horizontal posture to the vertical posture to transfer to the first posture changing treating bath.

15. The substrate treating apparatus of claim 14, wherein the second posture changing unit further comprises: a second support member positioned within the storage space of the second posture changing treating bath and which supports the substrate which has its posture changed by the second posture changing robot in the vertical posture.

16. The substrate treating apparatus of claim 15, wherein the second process treating unit comprises: a plurality of batch-type treating baths for batch-type treating the substrate; and a transfer unit configured to transfer the substrate between the first posture changing treating bath, the second posture changing treating bath, and the plurality of batch-type treating baths, and wherein the plurality of batch-type treating baths comprise: a first batch-type treating bath for batch-type treating the substrate by supplying a second treating liquid to the substrate; and a second batch-type treating bath for batch-type treating the substrate by supplying a third treating liquid to the substrate.

17. The substrate treating apparatus of claim 11, wherein the first posture changing unit includes a first posture changing robot which changes the posture of the substrate from the horizontal posture to the vertical posture, and the second posture changing unit includes a second posture changing robot which changes the posture of the substrate from the vertical posture to the horizontal posture, and wherein the first posture changing robot and the second posture changing robot each comprise: a hand which is configured to hold the substrate; and an arm which moves the hand.

18. The substrate treating apparatus of claim 11, further comprising a controller, and wherein the controller controls the substrate to sequentially perform: a substrate loading step for loading the substrate to a load port of the first process treating unit in the horizontal posture; a first single-type treating step for treating the substrate at the first process treating unit in the horizontal posture; a first posture changing step for changing the posture of the substrate from the horizontal posture to the vertical posture; a batch-type treating step for treating the substrate at the second process treating unit in the vertical posture; a second posture changing step for changing the posture of the substrate from the vertical posture to the horizontal posture; a second single-type treating step for treating the substrate at the third process treating unit in the horizontal posture; and a substrate unloading step for unloading the substrate to a load port of the third process treating unit in the

horizontal posture.

19. The substrate treating apparatus of claim 1, wherein the vertical posture refers to a posture at which a top surface or a bottom surface of the substrate is parallel to a direction perpendicular to the ground, and the horizontal posture refers to a posture at which the top surface or the bottom surface of the substrate is parallel to the ground.

20. The substrate treating apparatus of claim 6, wherein the first treating liquid is a removing liquid for removing an oxide film on the substrate, the second treating liquid is a chemical for removing a contaminant remaining on the substrate, and the third treating liquid is a pure water.
