

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413552
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Yahata; Kazuki et al.

In-vehicle control apparatus

Abstract

An in-vehicle control system mounted on a vehicle includes: a first control unit; a second control unit connected to the first control unit via a first communication path; and a third control unit connected to the second control unit via a second communication path. The second control unit has an internal communication path configured to be able to connect the first communication path and the second communication path and connects the first communication path and the second communication path via the internal communication path when the vehicle is in a predetermined operation state.

Inventors:	Yahata; Kazuki (Tokyo, JP), Okuno; Takeshi (Tokyo, JP)
Applicant:	Honda Motor Co., Ltd. (Tokyo, JP)
Family ID:	86055335
Assignee:	Honda Motor Co., Ltd. (Tokyo, JP)
Appl. No.:	17/970000
Filed:	October 20, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230128557 A1	Apr. 27, 2023

Foreign Application Priority Data

JP	2021-174395	Oct. 26, 2021
----	-------------	---------------

Publication Classification

Int. Cl.: H04L9/40 (20220101); G06F8/65 (20180101); H04L45/02 (20220101)

U.S. Cl.:

CPC **H04L63/0209** (20130101); **G06F8/65** (20130101); **H04L45/02** (20130101);

Field of Classification Search

CPC: H04L (45/02); H04L (63/0209); G06F (8/65)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6161071	12/1999	Shuman	340/901	G07C 5/085
6353785	12/2001	Shuman	340/901	B60R 25/00
6577937	12/2002	Shuman	701/48	G08G 1/096827
6675081	12/2003	Shuman	701/48	B60R 25/302
9374355	12/2015	Schwarz	N/A	H04L 63/12
10427655	12/2018	Nix	N/A	G06F 11/3072
10668929	12/2019	Tochioka	N/A	B60W 30/025
10764134	12/2019	Barrett	N/A	H04L 63/0263
10991175	12/2020	Zhang	N/A	H04L 63/062
11290437	12/2021	Zhang	N/A	H04L 63/065
11360762	12/2021	Teraoka	N/A	G06F 8/658
11538287	12/2021	Fang	N/A	G07C 5/008
11539727	12/2021	Haga	N/A	H04W 4/48
11546363	12/2022	Haga	N/A	H04L 63/1425
11563726	12/2022	Green	N/A	G06F 13/42
11645062	12/2022	Nakaguma	717/168	G06F 8/65
11671463	12/2022	Leuwer	726/1	H04L 12/40032
11721137	12/2022	Fang	701/31.5	G07C 5/0808
11736357	12/2022	Fang	709/223	H04L 41/0893
11765016	12/2022	Park	370/216	H04L 43/065
11972248	12/2023	Ishikawa	N/A	G07C 5/008
12046085	12/2023	Fang	N/A	H04L 67/125
12046086	12/2023	Fang	N/A	G07C 5/008
12073664	12/2023	Fang	N/A	G07C 5/008
12073665	12/2023	Fang	N/A	G07C 5/0816
12118830	12/2023	Fang	N/A	G07C 5/008
12142091	12/2023	Fang	N/A	G07C 5/008
12164902	12/2023	Sakurai	N/A	G06F 8/65
2003/0065432	12/2002	Shuman	701/1	B60R 25/00
2015/0121070	12/2014	Lau et al.	N/A	N/A
2015/0121071	12/2014	Schwarz	713/168	H04L 63/12
2017/0113664	12/2016	Nix	N/A	G07C 5/0891
2017/0353350	12/2016	Gussen	N/A	H04B 10/116
2018/0107473	12/2017	Ahmed	N/A	G06F 8/654
2018/0281810	12/2017	Tochioka	N/A	B60W 40/09
2018/0281812	12/2017	Tochioka	N/A	B60W 50/0098
2019/0354363	12/2018	Nakaguma	N/A	G06F 13/128

2019/0394089	12/2018	Barrett	N/A	H04W 12/088
2020/0137099	12/2019	Haga	N/A	B60R 16/023
2020/0174778	12/2019	David	N/A	H04W 4/80
2020/0211301	12/2019	Zhang	N/A	H04L 63/065
2020/0213287	12/2019	Zhang	N/A	H04L 63/123
2020/0249937	12/2019	Teraoka	N/A	G06F 8/658
2020/0304532	12/2019	Haga	N/A	H04L 12/4625
2021/0176092	12/2020	Frischmuth	N/A	H04L 12/40032
2021/0192867	12/2020	Fang	N/A	G07C 5/0808
2021/0291821	12/2020	Dakemoto	N/A	B60W 30/09
2022/0004375	12/2021	Satoh	N/A	G06F 8/61
2022/0063585	12/2021	Tabata	N/A	B60L 58/20
2022/0253304	12/2021	Tamachi	N/A	B60W 50/04
2023/0004376	12/2022	Ishikawa	N/A	G06F 8/61
2023/0005305	12/2022	Sakurai	N/A	G06F 13/00
2023/0033167	12/2022	Sakurai	N/A	G06F 8/65
2024/0086174	12/2023	Nakamura	N/A	B60R 16/02
2024/0134628	12/2023	Teraoka	N/A	G06F 13/00
2024/0231798	12/2023	Teraoka	N/A	G06F 8/65
2024/0267221	12/2023	Yoshimi	N/A	H04L 9/0822

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2020088568	12/2019	JP	N/A
2021105924	12/2020	JP	N/A

OTHER PUBLICATIONS

Japanese office action; Application 2021-174395; Oct. 15, 2024. cited by applicant

Primary Examiner: Lynch; Sharon S

Attorney, Agent or Firm: Duft & Bornsen, PC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application is based upon and claims the benefit of priority from Japanese Patent Application No. 2021-174395 filed on Oct. 26, 2021, the content of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

(2) This invention relates to an in-vehicle control system including electronic control units connected to each other via an in-vehicle communication network.

Description of the Related Art

(3) Conventionally, as this type of apparatus, an apparatus is known in which update data for updating software of an electronic control apparatus included in a vehicle is downloaded from an external server and installed in the electronic control apparatus (see JP 2021-105924 A). In the apparatus described in JP 2021-105924 A, an update management unit connected to the Internet supplies update data downloaded from an external server via the Internet to the electronic control

apparatus.

(4) In recent years, the data size of update data has increased in vehicles and the like equipped with an advanced driver-assistance function. In addition, in a vehicle equipped with an advanced driver-assistance function, security in communication with the outside is regarded as important. Therefore, it is desirable to form an in-vehicle communication network that can easily achieve both efficient data transmission and security. However, in the apparatus described in JP 2021-105924 A, there is a possibility that unauthorized access is performed to the electronic control apparatus via the update management unit connected to the Internet.

SUMMARY OF THE INVENTION

(5) An aspect of the present invention is an in-vehicle control system mounted on a vehicle, includes: a first control unit; a second control unit connected to the first control unit via a first communication path; and a third control unit connected to the second control unit via a second communication path. The second control unit has an internal communication path configured to be able to connect the first communication path and the second communication path and connects the first communication path and the second communication path via the internal communication path when the vehicle is in a predetermined operation state.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The objects, features, and advantages of the present invention will become clearer from the following description of embodiments in relation to the attached drawings, in which:
- (2) FIG. 1A is a diagram illustrating a reference example of an in-vehicle control system;
- (3) FIG. 1B is a diagram illustrating an example of a configuration of the in-vehicle control system in FIG. 1A;
- (4) FIG. 2 is a diagram illustrating an example of a configuration of an in-vehicle control system according to an embodiment of the present invention;
- (5) FIG. 3 is a block diagram illustrating a configuration of a main part of a software update apparatus according to the embodiment of the present invention;
- (6) FIG. 4 is a flowchart illustrating an example of processing executed by the processing unit of a software update apparatus;
- (7) FIG. 5 is a diagram illustrating another example of the configuration of the in-vehicle control system according to the embodiment of the present invention; and
- (8) FIG. 6 is a block diagram illustrating an example of a configuration of an in-vehicle control system according to a modification of the embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

(9) An embodiment of the present invention will be described below with reference to FIGS. 1A to 6. An in-vehicle control system according to an embodiment of the present invention can be applied to a vehicle having an advanced driver-assistance system (ADAS).

(10) First, the in-vehicle control system will be described. FIG. 1A is a diagram illustrating the example of the in-vehicle control system. As illustrated in FIG. 1A, an in-vehicle control system **10** is mounted on a vehicle **1**. The in-vehicle control system **10** is communicably connected to an external device such as a server **3** via a network **2**. The network **2** includes not only public wireless communication networks, but also a closed communication network provided for each predetermined management area, for example, a wireless LAN, Wi-Fi (registered trademark), Bluetooth (registered trademark), and the like. FIG. 1B is a diagram illustrating a reference example of a configuration of the in-vehicle control system **10** in FIG. 1A. As illustrated in FIG. 1B, the in-vehicle control system **10** includes electronic control units (ECUs) **11** to **14**. Further, the in-vehicle control system **10** includes a plurality of in-vehicle communication networks connected

via a controller area network (CAN), specifically, an in-vehicle communication network including ECUs **311** and **312** and an in-vehicle communication network including ECUs **321** and **322**.

(11) The ECU **14** is a communication unit (telematics control unit (TCU)) that performs wireless communication with an external device such as the server **3** via the network **2**. The ECU **13** is a central gateway (CGW) and has a gateway function. The ECU (CGW) **13** relays communication between an external device and an in-vehicle communication network, or communication between a plurality of in-vehicle communication networks, which is performed via the ECU (TCU) **14**. The CGW **13** further has a function of integrating various controls for causing the vehicle **1** to travel, such as powertrain control and chassis control.

(12) The ECU **12** is a map positioning unit (MPU) that generates information (hereinafter, referred to as map data) on a highly accurate map (a map having a larger information amount than a map used by a navigation unit). The ECU (MPU) **12** includes a memory unit (not illustrated), and stores the generated map data in the memory unit. When map data having a region overlapping with the generated map data is stored in the memory unit, the MPU **12** updates the map data stored in the memory unit with the generated map data. In response to a request from the ECU **11**, the MPU **12** reads the map data from the memory unit and supplies the map data to the ECU **11**.

(13) The ECU **11** is an ADAS ECU (hereinafter, simply referred to as ADAS) that implements an advanced driver-assistance function (ADAS) of the vehicle **1**. A camera **21** is connected to the ECU (ADAS) **11** via a signal line of low voltage differential signaling (LVDS). Furthermore, a radar **22** is connected to the ADAS **11** via CAN with Flexible Data Rate (CAN-FD). The ADAS **11** controls an actuator for traveling and the like based on information (map data) supplied from the MPU **12** and information detected by the camera **21** and the radar **22**. For example, a steering actuator that drives a steering device is controlled so that the vehicle **1** does not deviate from the lane on which the vehicle **1** is traveling. In this manner, the ADAS **11** implements the advanced driver-assistance function of the vehicle **1**.

(14) The ADAS **11** and the CGW **13**, the CGW **13** and the MPU **12**, and the MPU **12** and the TCU **14** are connected via a communication path L1, a communication path L2, and a communication path L3, respectively. The communication paths L1, L2, and L3 include a communication line having a higher speed than the CAN and the CAN-FD, for example, an Ethernet line.

(15) The CGW **13** includes an internal communication path IL1 that can connect the communication path L1 and the communication path L2. The CGW **13** includes an Ethernet switch (not illustrated), and controls the Ethernet switch to bring the internal communication path IL1 into a connected state or a disconnected state. The MPU **12** includes an internal communication path IL2 that can connect the communication path L2 and the communication path L3. The MPU **12** includes an Ethernet switch (not illustrated), and controls the Ethernet switch to bring the internal communication path IL2 into a connected state or a disconnected state.

(16) The server **3** includes a memory unit (not illustrated), and stores data (hereinafter, referred to as update data) for updating software (program) executed by each ECU of the in-vehicle control system **10** in the memory unit. The server **3** stores at least update data of software executed by the ADAS **11**. The in-vehicle control system **10** downloads update data of each ECU from the server **3** via the network **2**, supplies the update data to each ECU, and updates software of each ECU.

(17) In recent years, with the advancement of ADAS and connectivity functions, the amount of data transmitted and received between the in-vehicle control system **10** and an external device and the amount of data transmitted and received between the in-vehicle communication networks of the in-vehicle control system **10** have increased. In addition, the data size of software installed in each ECU responsible for these functions also increases. Furthermore, in the ADAS and the connectivity function, security in communication with an external device is regarded as important. In order to cope with such a situation, it is required to further improve data transmission performance and security of the in-vehicle control system **10**. Therefore, the present embodiment configures an in-vehicle control system as follows.

(18) FIG. 2 is a diagram illustrating an example of a configuration of an in-vehicle control system according to an embodiment of the present invention. In an in-vehicle control system **10a** illustrated in FIG. 2, the MPU **12** disposed between the TCU **14** and the CGW **13** in the in-vehicle control system **10** in FIG. 1B is disposed on a downstream side of the CGW **13**. Specifically, the MPU **12** is disposed between the CGW **13** and the ADAS **11**. Hereinafter, a side close to the TCU **14** is referred to as an upstream side, and a side far from the TCU **14** is referred to as a downstream side. As described above, by disposing the MPU **12** on the downstream side of the CGW **13**, it is possible to add a firewall on the downstream side of the CGW **13**. More specifically, by installing a firewall in the MPU **12** disposed on the downstream side of the CGW **13**, the firewall can be added on the downstream side of the CGW **13**. This makes it easy to suppress unauthorized access to the ADAS **11** via the CGW **13**.

(19) In addition, by moving the MPU **12** to the downstream side of the CGW **13** as illustrated in FIG. 2 and directly connecting the CGW **13** and the TCU **14** through a communication path (Ethernet line) **L12** faster than the communication paths **L2** and **L3** in FIG. 1B, the data transmission speed between the CGW **13** and the TCU **14** can be increased. Note that the communication path **L12** only needs to be a communication line having a speed higher than at least the CAN or the CAN-FD, and may have a communication capacity equivalent to that of the communication paths **L2** and **L3**.

(20) The MPU **12** is connected to the ADAS **11** via the communication path **L1**, and is connected to the CGW **13** via a communication path **L11**. The MPU **12** can connect the communication path **L1** and the communication path **L11** via the internal communication path **IL2**. As a result, the CGW **13** and the ADAS **11** can be connected by a communication path **CL1** constructed by the communication path **L1**, the MPU **12** (internal communication path **IL2**), and the communication path **L11**. Therefore, only by adding the communication path **L11** to the configuration in FIG. 1B, the MPU **12** can be disposed between the CGW **13** and the ADAS **11** without reducing the data transmission speed between the CGW **13** and the ADAS **11**. Note that the communication path **L11** has a communication capacity equal to or larger than at least the communication capacity of the communication path **L1**.

(21) Further, by disposing the MPU **12** having the internal communication path **IL2** between the CGW **13** and the ADAS **11**, the CGW **13** and the ADAS **11** can be connected or disconnected as necessary. For example, only when the software is installed in the ADAS **11**, the internal communication path **IL2** is brought into the connected state to connect the CGW **13** and the ADAS **11**, and otherwise, the internal communication path **IL2** is brought into the disconnected state to disconnect the CGW **13** and the ADAS **11**. As a result, unauthorized access to the ADAS **11** via the CGW **13** is more easily suppressed.

(22) FIG. 3 is a block diagram illustrating a configuration of a main part of a software update apparatus according to the embodiment of the present invention. A software update apparatus **100** in FIG. 3 constitutes a part of the in-vehicle control system **10a**. As illustrated in FIG. 3, the software update apparatus **100** includes a computer including a processing unit **110** such as a CPU, a memory unit **120** such as a ROM, a RAM, and a hard disk, and other peripheral circuits. The processing unit **110** includes, as functional configurations, a command reception unit **111**, a data acquisition unit **112**, a state determination unit **113**, a path construction unit **114**, and a data supply unit **115**. The command reception unit **111**, the data acquisition unit **112**, the state determination unit **113**, and the path construction unit **114** are configured by a CPU (not illustrated) included in the MPU **12**. The data supply unit **115** is configured by a CPU (not illustrated) included in the CGW **13**. Note that the processing unit **110** may be configured by a single CPU (CPU included in a single ECU), or may be configured by combining CPUs included in a plurality of ECUs as described above. Furthermore, the memory unit **120** may be configured by a ROM or the like included in a single ECU, or may be configured by combining ROMs or the like included in a plurality of ECUs.

(23) The command reception unit **111** receives an update command for updating software of each ECU of the in-vehicle control system **10a**. The update command includes information of an ECU as a software update target (for example, identification information of the ECU as an update target) and information (for example, URL) that can specify a storage location of update data. The command reception unit **111** may receive an update command transmitted from an external device via the TCU **14**, or may receive an update command output in response to a user operation from an operation unit (not illustrated) (a liquid crystal display or the like having a touch panel) provided in the vehicle **1**.

(24) The data acquisition unit **112** acquires update data for updating software of each ECU from an external device or the like based on the update command received by the command reception unit **111**. For example, when the update command indicates that the ECU as an update target is the ADAS **11** and the storage location of the update data is the server **3**, the data acquisition unit **112** downloads, from the server **3**, the update data of the ADAS **11** stored in the memory unit (not illustrated) of the server **3** and acquires the update data.

(25) The state determination unit **113** determines whether the vehicle **1** is in a predetermined operation state. The predetermined operation state is a state in which software update processing (program rewriting) of the ADAS **11** is possible, and is, for example, a state in which the vehicle **1** is stopped and an ignition switch is turned off.

(26) When the state determination unit **113** determines that the vehicle **1** is in the predetermined operation state, the path construction unit **114** constructs a communication path for supplying update data to the ADAS **11**. Specifically, the path construction unit **114** brings the internal communication path **IL2** into a connected state to connect the communication path **L1** and the communication path **L11**. On the other hand, when the state determination unit **113** determines that the vehicle **1** is no longer in the predetermined operation state, the path construction unit **114** brings the internal communication path **IL2** into a disconnected state to disconnect the communication path **L1** and the communication path **L11**. For example, when the ignition switch is turned on, the state determination unit **113** determines that the predetermined operation state is no longer established. The initial state of the internal communication path **IL2** is a disconnected state.

(27) The data supply unit **115** supplies the update data acquired by the data acquisition unit **112** to the ADAS **11** via the communication path **CL1** constructed by the path construction unit **114**, and installs the software. More specifically, the data supply unit **115** develops the update data in a ROM (not illustrated) of the ADAS **11** to update the software of the ADAS **11**.

(28) FIG. **4** is a flowchart illustrating an example of processing executed by the processing unit **110** of the software update apparatus **100** according to a program stored in advance. The processing illustrated in this flowchart is started, for example, when power is supplied to the in-vehicle control system **10a**, and is repeated at a predetermined cycle. Hereinafter, a case where update data is stored in the memory unit of the server **3**, and the software update apparatus **100** downloads the update data from the memory unit of the server **3** and updates the software of the ECU as an update target will be described as an example.

(29) First, in step **S1** (S: processing step), it is determined whether an update command has been received. When the determination is negative in **S1**, the processing is ended. When the determination is affirmative in **S1**, update data is acquired in **S2**. Specifically, the update data is downloaded from the memory unit of the server **3** based on the information included in the update command. The downloaded update data is stored in the memory unit **120**.

(30) In **S3**, it is determined whether it is necessary to construct a communication path necessary for installing software, that is, the communication path **CL1**. When the determination is negative in **S3**, the processing proceeds to **S5**. When the determination is affirmative in **S3**, the communication path **CL1** is constructed in **S4**. For example, when the update command received in **S1** includes information indicating that the ADAS **11** is a software update target, it is determined in **S3** that the communication path **CL1** needs to be constructed. Then, in **S4**, when the vehicle **1** is in a

predetermined operation state, the internal communication path IL2 is brought into a connected state to connect the communication path L1 and the communication path L11. At this time, the internal communication path IL1 is also brought into a connected state to connect the communication path L11 and the communication path L12. These communication paths are established, for example, by activating the ECUs 11 to 14 by the software update apparatus 100 when the ignition switch is turned off. Note that the internal communication path IL1 may be set to the connected state at all times while power is supplied to the in-vehicle control system 10a.

(31) In S5, the update data downloaded in S1 is read from the memory unit 120 and developed in the ROM of the ADAS 11 to update the software of the ADAS 11.

(32) According to the embodiment of the present invention, the following operational effects can be achieved.

(33) (1) The in-vehicle control system 10a is mounted on the vehicle 1, and includes the ADAS 11 as a first control unit, the MPU 12 as a second control unit connected to the ADAS 11 via a first communication path (communication path L1), and the CGW 13 as a third control unit connected to the MPU 12 via a second communication path (communication path L11). The MPU 12 generates map data and supplies the map data to the ADAS 11 via the communication path L1. The MPU 12 has a first internal communication path (internal communication path IL2) that can connect the communication path L1 and the communication path L11, and connects the communication path L1 and the communication path L11 via the internal communication path IL2 when the vehicle 1 is in a predetermined operation state.

(34) With this configuration, a communication path for supplying data from the CGW 13 to the ADAS 11 is constructed by the internal communication path IL2 of the MPU 12 and the communication path L1 for supplying map data from the MPU 12 to the ADAS 11. Therefore, data can be supplied from the CGW 13 to the ADAS 11 only by adding the communication path L11 without separately providing a communication path that directly connects the CGW 13 and the ADAS 11. Therefore, an increase in cost of the in-vehicle control system 10a can be suppressed.

(35) Further, by disposing the MPU 12 between the CGW 13 and the ADAS 11, a firewall can be added to the downstream side of the CGW 13. FIG. 5 is a diagram illustrating another example of the configuration of the in-vehicle control system according to the embodiment of the present invention. FIG. 5 illustrates an example in which a firewall FW is installed in each of the MPU 12, the CGW 13, and the TCU 14 of the in-vehicle control system 10a in FIG. 2. As illustrated in FIG. 5, by installing the firewall FW in the MPU 12 disposed between the CGW 13 and the ADAS 11, the firewall can be added to the downstream side of the CGW 13. As a result, unauthorized access to the ADAS 11 from an external device or another in-vehicle communication network via the CGW 13 can be suppressed.

(36) (2) When the program of the ADAS 11 is being rewritten, the MPU 12 connects the communication path L1 and the communication path L11 via the internal communication path IL2. With this configuration, the update data for rewriting the program of the ADAS 11 can be supplied from the CGW 13 to the ADAS 11 via the MPU 12. In addition, since the communication path L1 and the communication path L11 are connected only when the program of the ADAS 11 is rewritten, unauthorized access to the ADAS 11 from an external device or another in-vehicle communication network via the CGW 13 can be further suppressed.

(37) (3) The ADAS 11, the MPU 12, and the CGW 13 are connected to each other via a third communication path (communication path L13) having a smaller communication capacity than any of the communication paths L1 and L11 and the internal communication path IL2. With this configuration, the communication path can be switched based on the capacity of the data transmitted among the ADAS 11, the MPU 12, and the CGW 13. For example, the communication path L13 is used when data having a relatively small capacity such as a command or control data is transmitted between the ADAS 11, the MPU 12, and the CGW 13, and the communication path constructed by the communication path L1, the MPU 12 (internal communication path IL2), and

the communication path L11 is used when data having a relatively large capacity such as update data is transmitted. Accordingly, power consumption required for data transmission can be reduced.

(38) (4) The in-vehicle control system 10a further includes the TCU 14 capable of communicating with a device outside the vehicle 1 (for example, the server 3). The CGW 13 acquires update data for rewriting the program of the ADAS 11 from an external device via the TCU 14. With this configuration, the CGW 13 can acquire the update data from the external device, and can flexibly update the software of the ADAS 11. Furthermore, the CGW 13 and the TCU 14 are connected via a fourth communication path (communication path L12) having a larger communication capacity than the communication path L13. With this configuration, the time (download time) required for the CGW 13 to download the update data from the external device can be shortened. Therefore, energy efficiency required for software update can be improved.

(39) The above embodiment can be changed to various forms. Hereinafter, a modification will be described. In the above embodiment, the in-vehicle control system 10a including the MPU 12 that supplies the map data to the ADAS 11 has been described as an example. However, the present invention is also applicable to an in-vehicle control system including an ECU (hereinafter, referred to as a recognition extension unit (ADAS Perception Extension: APEX)) that supplies information of a traveling path (hereinafter, track information) of the vehicle 1 to the ADAS 11. FIG. 6 is a block diagram illustrating an example of a configuration of an in-vehicle control system according to the present modification.

(40) As illustrated in FIG. 6, an in-vehicle control system 10b includes the ADAS 11, the ECU (APEX) 15, and the CGW 13. A camera 23 is connected to the APEX 15 via a communication path L14. The camera 23 captures an image of a space (for example, a front space) around the vehicle 1, and outputs captured image data to the APEX 15 via the communication path L14. The communication path L14 is, for example, a signal line of the LVDS, and has a larger communication capacity than the communication path L13.

(41) The APEX 15 recognizes a traveling path of the vehicle 1 based on the captured image data input from the camera 23, and outputs traveling path information including the recognition result to the ADAS 11 via the communication path L1. In addition, the APEX 15 has an internal communication path IL3 capable of connecting the communication path L1 and the communication path L11. Further, the APEX 15 includes an Ethernet switch (not illustrated), and controls the Ethernet switch to bring the internal communication path IL3 into a connected state or a disconnected state. The ADAS 11 controls an actuator for traveling or the like so that the vehicle 1 does not deviate from the lane on which the vehicle 1 is traveling based on the information (traveling path information) supplied from the APEX 15. As described above, in the present modification, the ADAS 11 implements the advanced driver-assistance function of the vehicle 1 based on the traveling path information supplied from the APEX 15.

(42) The configuration and operation of the software update apparatus constituting a part of the in-vehicle control system 10b are similar to the configuration and operation of the software update apparatus 100 in FIG. 3. In the software update apparatus according to the present modification, when the state determination unit 113 determines that the vehicle 1 is in the predetermined operating state, the path construction unit 114 brings the internal communication path IL3 into a connected state to connect the communication path L1 and the communication path L11. When the state determination unit 113 determines that the vehicle 1 is no longer in the predetermined operation state, the path construction unit 114 brings the internal communication path IL3 into a disconnected state to disconnect the communication path L1 and the communication path L11.

(43) With this configuration, since data can be supplied from the ADAS 11 to the CGW 13 via the communication path CL2 constructed by the communication path L1, the APEX 15 (internal communication path IL3), and the communication path L11, it is not necessary to separately provide a communication path that directly connects the ADAS 11 and the CGW 13. Therefore, an increase in cost of the in-vehicle control system 10b can be suppressed. Further, by installing the

firewall in the APEX 15 disposed between the ADAS 11 and the CGW 13, security of data supplied from an external device or an in-vehicle communication network to the ADAS 11 can be improved.

(44) In the above embodiment, the Ethernet switch included in the MPU 12 brings the internal communication path IL1 into the connected state or the disconnected state, but other network devices than the Ethernet switch may bring a first internal communication path into the connected state or the disconnected state. Similarly, the Ethernet switches included in the ECUs 13 and 15 (CGW 13 and APEX 15) respectively bring the internal communication path IL2 and IL3 into the connected state or the disconnected state, but other network devices than the Ethernet switch may bring a second internal communication path into the connected state or the disconnected state.

(45) In the above embodiment, the configuration of the in-vehicle control system 10b has been described using the case where the camera 23 as an image capturing unit is connected to the APEX 15 via the communication path L14 (fifth communication path) which is the LVDS as an example. However, the fifth communication path may be any communication line (signal line) with greater communication capacity than the communication path L13, and the image capturing unit and the APEX 15 may be connected via other communication lines (signal lines).

(46) The above embodiment can be combined as desired with one or more of the above modifications. The modifications can also be combined with one another.

(47) According to the present invention, it is possible to form an in-vehicle communication network that can achieve both efficient data transmission and security.

(48) Above, while the present invention has been described with reference to the preferred embodiments thereof, it will be understood, by those skilled in the art, that various changes and modifications may be made thereto without departing from the scope of the appended claims.

Claims

1. An in-vehicle control system mounted on a vehicle, the in-vehicle control system comprising: a first electronic control unit configured to implement an advanced driver-assistance function of the vehicle; a second electronic control unit connected to the first electronic control unit via a first communication path; a third electronic control unit connected to the second control unit via a second communication path, and a communication unit capable of communicating with an external device outside the vehicle, wherein the second electronic control unit has a first internal communication path configured to be able to connect the first communication path and the second communication path and a network switch switching the first internal communication path between a connected state and a disconnected state, controls the network switch to set the first internal communication path to the connected state when receiving an update command for updating software of the first electronic control unit while an ignition switch is turned off, and controls the network switch to set the first internal communication path to the disconnected state when receiving the update command while the ignition switch is turned on, the third electronic control unit includes a second internal communication path configured to be able to connect the second communication path and a fourth communication path connecting the third electronic control unit and the communication unit, and the second electronic control unit, the third electronic control unit and the communication unit include a firewall, respectively, and wherein the firewall of the second electronic control unit is installed on the first internal communication path, the firewall of the third electronic control unit is installed on the second internal communication path, and the third electronic control unit supplies, via the second internal communication path, the second communication path, the first internal communication path and the first communication path, the first electronic control unit with update data for updating a program of the first electronic control unit acquired via the firewall of the communication unit and the fourth communication path from the external device.
2. The in-vehicle control system according to claim 1, wherein the first electronic control unit, the

second electronic control unit and the third electronic control unit are connected to each other via a third communication path whose communication capacity is smaller than the communication capacity of each of the first communication path, the second communication path and the first internal communication path.

3. The in-vehicle control system according to claim 2, wherein the third electronic control unit and the communication unit are connected via the fourth communication path whose communication capacity is larger than the third communication path.

4. The in-vehicle control system according to claim 3, wherein the third electronic control unit acquires the update data from the external device via the communication unit.

5. The in-vehicle control system according to claim 1, wherein the second electronic control unit is an electronic control unit generating map data.

6. The in-vehicle control system according to claim 5, wherein the second electronic control unit supplies the map data to the first electronic control unit via the first communication path.

7. The in-vehicle control system according to claim 2, wherein the second electronic control unit is an electronic control unit recognizing a traveling path of the vehicle, is connected to an image capturing unit outputting captured image data of a surrounding area of the vehicle via a fifth communication path whose communication capacity is larger than the third communication path, and acquires the captured image data from the image capturing unit via the fifth communication path to supply the captured image data to the first control unit via the first communication path.

8. The in-vehicle control system according to claim 1, wherein the second electronic control unit controls the network switch to set the first internal communication path to the disconnected state when the update command is not received.
