

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414234
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Park; Jeonggyun et al.

Electronic device including conductive fixing member

Abstract

According to an embodiment of the disclosure, an electronic device may comprise: a housing including a front surface facing a first direction, a rear surface facing in a second direction opposite to the first direction, and a side structure including a side surface at least partially surrounding a space between the front surface and the rear surface, a coaxial cable at least partially disposed in the housing, a fixing member comprising a conductive material having electrical conductivity and disposed in the housing surrounding at least a portion of the coaxial cable, and an electrical/electronic component disposed in the housing and including a body portion at least partially disposed in the housing and a flexible printed circuit board extending from the body portion. The fixing member may be configured to electrically connect the coaxial cable and the flexible printed circuit board with the housing.

Inventors: Park; Jeonggyun (Suwon-si, KR), Ahn; Seungjae (Suwon-si, KR), Jung; Youngduck (Suwon-si, KR), Na; Hyoseok (Suwon-si, KR), Choi; Youngbaek (Suwon-si, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 85798850

Assignee: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Appl. No.: 17/887834

Filed: August 15, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230112105 A1	Apr. 13, 2023

Foreign Application Priority Data

KR	10-2021-0133110	Oct. 07, 2021
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/007350 20220524 PENDING child-doc US 17887834

Publication Classification

Int. Cl.: **H05K5/00** (20250101); **H01Q1/24** (20060101); **H01Q1/38** (20060101); **H01R12/52** (20110101); **H01R24/50** (20110101); **H05K1/11** (20060101); **H05K1/18** (20060101)

U.S. Cl.:

CPC **H05K1/118** (20130101); **H01Q1/243** (20130101); **H01Q1/38** (20130101); **H01R12/52** (20130101); **H01R24/50** (20130101); **H05K1/189** (20130101); **H05K5/006** (20130101); **H01R2201/02** (20130101); **H05K2201/09809** (20130101)

Field of Classification Search

CPC: H01Q (1/243); H01Q (1/38); H01R (12/52); H01R (24/50); H01R (2201/02); H05K (1/18); H05K (5/006); H05K (2201/09809)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4115779	12/1977	Dantzler	343/882	H01Q 1/084
7564412	12/2008	Walker	343/702	H01Q 1/2266
7876274	12/2010	Hobson	343/702	H01Q 1/38
8269674	12/2011	Camacho	343/702	G06F 1/1616
10206299	12/2018	Kim	N/A	H05K 7/1427
11800600	12/2022	Tan	N/A	G06F 1/182
2007/0035456	12/2006	Jeong	N/A	N/A
2011/0080696	12/2010	Nishikawa et al.	N/A	N/A
2011/0273339	12/2010	Hornung	N/A	N/A
2014/0104118	12/2013	Kim	N/A	N/A
2017/0164498	12/2016	Song et al.	N/A	N/A
2017/0172005	12/2016	Kim et al.	N/A	N/A
2020/0127404	12/2019	Seo et al.	N/A	N/A
2020/0267868	12/2019	Park	N/A	N/A
2021/0006648	12/2020	Han et al.	N/A	N/A
2021/0298165	12/2020	Jeon	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110797678	12/2019	CN	N/A
2002-252479	12/2001	JP	N/A
2015-050416	12/2014	JP	N/A
10-2007-0018511	12/2006	KR	N/A
10-1091884	12/2010	KR	N/A
10-2017-0066990	12/2016	KR	N/A

10-2017-0097917	12/2016	KR	N/A
10-2018-0088172	12/2017	KR	N/A
10-1918298	12/2017	KR	N/A
10-2019-0103814	12/2018	KR	N/A
10-2019-0139597	12/2018	KR	N/A
10-2020-0012153	12/2019	KR	N/A
10-2020-0045661	12/2019	KR	N/A
10-2021-0108741	12/2020	KR	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion of the International Searching Authority for PCT/KR2022/007350 mailed Aug. 30, 2022 and English translation, 8 pages. cited by applicant

Primary Examiner: Girardi; Vanessa

Attorney, Agent or Firm: Nixon & Vanderhye P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of International Application No. PCT/KR2022/007350 designating the United States, filed on May 24, 2022, in the Korean Intellectual Property Receiving Office and claiming priority to Korean Patent Application No. 10-2021-0133110, filed on Oct. 7, 2021, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

Field

(1) The disclosure relates to an electronic device, e.g., an electronic device including a conductive fixing member.

Description of Related Art

(2) The term “electronic device” may refer, for example, to a device performing a particular function according to its equipped program, such as a home appliance, an electronic scheduler, a portable multimedia player, a mobile communication terminal, a tablet PC, a video/sound device, a desktop PC or laptop computer, a navigation for automobile, etc. For example, electronic devices may output stored information as voices or images. As electronic devices are highly integrated, and high-speed or high-volume wireless communication becomes commonplace, an electronic device, such as a mobile communication terminal, is recently being equipped with various functions. For example, an electronic device comes with the integrated functionality, including an entertainment function, such as playing video games, a multimedia function, such as replaying music/videos, a communication and security function for mobile banking, and/or a scheduling or e-wallet function. As the electronic device is highly integrated, portability is further enhanced, and wearable electronic devices, such as wrist-type or glasses-type electronic devices, have been commercialized, and electronic devices are more comfortably carried and used.

(3) The above-described information may be provided as background for the purpose of helping understanding of the disclosure. No claim or determination is made as to whether any of the foregoing is applicable as background art in relation to the disclosure.

(4) It may be difficult to provide a stable operating environment in a downsized electronic device, such as a mobile communication terminal or a tablet PC. For example, an electric shock, such as static electricity, may cause malfunction or damage to various integrated circuit chips or

electric/electronic components, and may cause discomfort to the user.

SUMMARY

(5) Embodiments of the disclosure provide an electronic device having a stable operating environment by including a conductive fixing member.

(6) Embodiments of the disclosure provide an electronic device capable of suppressing or preventing/reducing malfunction or damage to an electrical/electronic component due to static electricity.

(7) According to an example embodiment of the disclosure, an electronic device may comprise: a housing including a front surface, a rear surface facing in a direction opposite to the front surface, and a side structure including a side surface at least partially surrounding a space between the front surface and the rear surface, a coaxial cable at least partially disposed in the housing, a fixing member comprising a conductive material and having electrical conductivity and disposed in the housing surrounding at least a portion of the coaxial cable, and an electrical/electronic component disposed in the housing and including a body portion at least partially disposed in the housing and a flexible printed circuit board extending from the body portion. The fixing member may be configured to electrically connect the coaxial cable and the flexible printed circuit board with the housing.

(8) According to an example embodiment of the disclosure, an electronic device may comprise: a rear plate, a frame-shaped side structure comprising a side wall disposed corresponding to an edge of the rear plate, a coaxial cable at least partially disposed on the side structure in an area facing the rear plate, a fixing member comprising a conductive material disposed on the side structure and surrounding at least a portion of the coaxial cable, and an electrical/electronic component disposed in the housing and including a body portion at least partially disposed on the rear plate and a flexible printed circuit board extending from the body portion and configured to be disposed on an inner surface of the rear plate to contact the fixing member. The fixing member may be configured to electrically connect the coaxial cable and the flexible printed circuit board with the side structure.

(9) According to an example embodiment, the fixing member electrically connects a coaxial cable or a flexible printed circuit board for transmitting various signals to a conductive structure (e.g., the housing), thereby mitigating the user's electric shock or discomfort due to static electricity.

(10) In various example embodiments, the fixing member may suppress electromagnetic interference or noise generation and provide a stable operating environment by providing a stable grounding environment for adjacent other electrical/electronic components and/or various signal lines.

(11) In an example embodiment, the fixing member may be easily installed or assembled even in a narrow space and may be easy to repair/replace.

(12) Other aspect(s), advantage(s) and major configuration(s) of the disclosure will become apparent to one of ordinary skill in the art from the following detailed description of various example embodiments with reference to the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features, and/or advantages of certain embodiments of the present disclosure will be more apparent from the following detailed description, taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a front perspective view illustrating an electronic device;

(3) FIG. 2 is a rear perspective view thereof;

(4) FIG. 3 is an exploded perspective view thereof;

- (5) FIG. 4 is a cross-sectional view illustrating a portion of an electronic device;
- (6) FIG. 5 is a diagram including a partial perspective view illustrating a placement of a fixing member in an electronic device;
- (7) FIG. 6 is an exploded perspective view illustrating a placement of a portion of a fixing member in an electronic device;
- (8) FIG. 7 is a diagram illustrating a placement of a portion of a fixing member in an electronic device;
- (9) FIG. 8 is an exploded perspective view illustrating a coupling of a portion of a fixing member of an electronic device to a coaxial cable;
- (10) FIG. 9 is a cross-sectional view illustrating a coupling of a portion of a fixing member of an electronic device to a coaxial cable;
- (11) FIG. 10 is a cross-sectional view illustrating a portion of an electronic device, taken along line B-B' of FIG. 7;
- (12) FIG. 11 is an exploded perspective view illustrating a placement of another portion of a fixing member of an electronic device;
- (13) FIG. 12 is a diagram illustrating a placement of another portion of a fixing member of an electronic device;
- (14) FIG. 13 is a partial perspective sectional view illustrating a fixing member taken along line C-C' of FIG. 12;
- (15) FIG. 14 is a cross-sectional view illustrating a portion of an electronic device, taken along line D-D' of FIG. 12;
- (16) FIG. 15 is a perspective view illustrating a state in which a fastening member is bound in an electronic device;
- (17) FIG. 16 is a diagram illustrating a state in which a fastening member is bound in an electronic device;
- (18) FIG. 17 is a perspective view illustrating a state in which a fastening member is bound in an electronic device;
- (19) FIG. 18 is a partial perspective view illustrating a placement of an electrical/electronic component in an electronic device;
- (20) FIG. 19 is an exploded perspective view illustrating a coupling of a housing and a rear plate in an electronic device; and
- (21) FIG. 20 is a cross-sectional view illustrating a portion of a flexible printed circuit board, taken along line E-E' of FIG. 18.
- (22) Throughout the drawings, like reference numerals may be assigned to like parts, components, and/or structures.

DETAILED DESCRIPTION

- (23) The following description taken in conjunction with the accompanying drawings may be presented to provide an understanding of various implementations of the disclosure. The various example embodiments disclosed in the following description entail various specific details to aid understanding, but are regarded as one of various embodiments. Accordingly, it will be apparent to those skilled in the art that various changes and modifications may be made to the various implementations described in the disclosure without departing from the scope and spirit of the disclosure. Further, descriptions of well-known functions and configurations may be omitted for clarity and brevity.
- (24) The terms and words used in the following description and claims are not limited to the bibliographical meaning, but may be used to clearly and consistently describe the various embodiments of the disclosure. Therefore, it will be apparent to those skilled in the art that the following description of various implementations of the disclosure is provided only for the purpose of description, not for the purpose of limiting the disclosure.
- (25) The singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless

the context clearly indicates otherwise. Thus, as an example, “a component surface” may be interpreted as including one or more of the surfaces of a component.

(26) The electronic device according to various embodiments of the disclosure may be various types of devices. The electronic devices may include, for example, a portable communication device (e.g., a smart phone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, a home appliance, or the like. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(27) It should be appreciated that various embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(28) As used herein, the term “module” may include a unit implemented in hardware, software, or firmware, or any combination thereof, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(29) Various embodiments as set forth herein may be implemented as software (e.g., the program) including one or more instructions that are stored in a storage medium (e.g., internal memory or external memory) that is readable by a machine (e.g., the electronic device). For example, a processor of the machine (e.g., the electronic device) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the “non-transitory” storage medium is a tangible device, and may not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(30) According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program products may be traded as commodities between sellers and buyers. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., Play Store™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's

server, a server of the application store, or a relay server.

(31) According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities. Some of the plurality of entities may be separately disposed in different components. According to various embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(32) FIG. 1 is a front perspective view illustrating an electronic device **100** according to various embodiments. FIG. 2 is a rear perspective view illustrating an electronic device **100** according to various embodiments.

(33) Referring to FIGS. 1 and 2, the electronic device **100** according to an embodiment may include a housing **110** including a first surface (or front surface) **110A**, a second surface (or rear surface) **110B**, and a side surface **110C** surrounding a space the first surface **110A** and the second surface **110B**. According to an embodiment (not shown), the housing may denote a structure forming the first surface **110A** of FIG. 1, the second surface **110B** of FIG. 2, and some of the side surfaces **110C** of FIG. 1. According to an embodiment, the first surface **110A** may be formed by a front plate **102** (e.g., a glass plate or polymer plate with various coat layers) at least part of which is substantially transparent. According to an embodiment, the front plate **102** may be coupled with the housing **110** and, along with the housing **110**, may form an internal space. According to various embodiments, the ‘internal space’ may refer, for example, to a space, as an internal space of the housing **110**, for receiving at least part of the display **101**.

(34) According to an embodiment, the second surface **110B** may be formed of a substantially opaque rear plate **111**. The rear plate **111** may be formed of, e.g., laminated or colored glass, ceramic, polymer, metal (e.g., aluminum, stainless steel (STS), or magnesium), or a combination of at least two thereof. The side surface **110C** may be formed by a side bezel structure (or a “side structure”) **118** that couples to the front plate **102** and the rear plate **111** and includes a metal and/or polymer. According to various embodiments, the rear plate **111** and the side bezel structure **118** may be integrally formed together and include the same or similar material (e.g., a metal, such as aluminum).

(35) In the embodiment illustrated, the front plate **102** may include two first areas **110D** (e.g., curved areas), which seamlessly and bendingly extend from the first surface **110A** to the rear plate **111**, on both the long edges of the front plate **102**. In the embodiment illustrated, the rear plate **111** may include second areas **110E** (e.g., curved areas), which seamlessly and bendingly extend from the second surface **110B** to the front plate **102**, on both the long edges. According to various embodiment, the front plate **102** (or the rear plate **111**) may include only one of the first areas **110D** (or the second areas **110E**). In an embodiment, some of the first areas **110D** or the second areas **110E** may not be included. In the above-described embodiments, at side view of the electronic device **100**, the side bezel structure **118** may have a first thickness (or width) for sides (e.g., the side where the connector hole **108** is formed) that do not have the first areas **110D** or the second areas **110E** and a second thickness, which is smaller than the first thickness, for sides (e.g., the side where the key input device **117** is disposed) that have the first areas **110D** or the second areas **110E**.

(36) According to an embodiment, the electronic device **100** may include at least one or more of a display **101**, audio modules **103**, **107**, and **114**, a sensor module **104**, camera modules **105** and **155**, a key input device **117**, a light emitting device **106**, and connector holes **108** and **109**. According to

various embodiments, the electronic device **100** may exclude at least one (e.g., the key input device **117** or the light emitting device **106**) of the components or may add other components.

(37) The display **101** may be visible through a significant portion of the front plate **102**. According to an embodiment, at least a portion of the display **101** may be visible through the front plate **102** forming the first surface **110A** and the first areas **110D** of the side surface **110C**. According to various embodiments, the edge of the display **101** may be formed to be substantially the same in shape as an adjacent outer edge of the front plate **102**. According to an embodiment (not shown), the interval between the outer edge of the display **101** and the outer edge of the front plate **102** may remain substantially even to give a larger area of exposure the display **101**.

(38) According to an embodiment, the screen display area (e.g., the active area), or an area (e.g., the inactive area) off the screen display area, of the display **101** may have a recess or opening in a portion thereof, and at least one or more of the audio module **114**, sensor module **104**, camera modules **105** and **155**, and light emitting device **106** may be aligned with the recess or opening. According to an embodiment (not shown), at least one or more of the audio module **114**, sensor module **104**, camera modules **105** and **155**, and light emitting device **106** may be included on the rear surface of the screen display area of the display **101**. According to an embodiment, the display **101** may be disposed to be coupled with, or adjacent, a touch detecting circuit, a pressure sensor capable of measuring the strength (pressure) of touches, and/or a digitizer for detecting a magnetic field-type stylus pen. According to an embodiment, at least part of the sensor module **104** and/or at least part of the key input device **117** may be disposed in the first areas **110D** and/or the second areas **110E**.

(39) The audio modules **103**, **107**, and **114** may include a microphone hole **103** and speaker holes **107** and **114**. The microphone hole **103** may have a microphone inside to obtain external sounds. According to an embodiment, there may be a plurality of microphones to be able to detect the direction of a sound. The speaker holes **107** and **114** may include an external speaker hole **107** and a phone receiver hole **114**. According to an embodiment, the speaker holes **107** and **114** and the microphone hole **103** may be implemented as a single hole, or speakers may be rested without the speaker holes **107** and **114** (e.g., piezo speakers).

(40) The sensor module **104** may produce an electrical signal or data value corresponding to the internal operation state or external environment state of the electronic device **100**. The sensor module **104** may include a first sensor module **104** (e.g., a proximity sensor) and/or a second sensor module (not shown) (e.g., a fingerprint sensor) disposed on the first surface **110A** of the housing **110** and/or another sensor module (not shown) (e.g., an HRM sensor or fingerprint sensor) disposed on the second surface **110B** of the housing **110**. The fingerprint sensor may be disposed on the second surface **110A** as well as on the first surface **110B** (e.g., the display **101**) of the housing **110**. The electronic device **100** may further include sensor modules not shown, e.g., at least one of a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor **104**.

(41) The camera modules **105** and **155** may include a first camera device **105** disposed on the first surface **110A** of the electronic device **100** and a second camera device **155** disposed on the second surface **110B**. The second camera device **155** may include, e.g., an infrared light source, an infrared receiver, a flicker detection sensor, and/or a plurality of cameras. The camera modules **105** and **155** may include one or more lenses, an image sensor, and/or an image signal processor. A flash (not shown) may be disposed on the second surface **110B**. The flash may include, e.g., a light emitting diode (LED) or a xenon lamp. According to an embodiment, two or more lenses (an infrared (IR) camera, a wide-angle lens, and a telescopic lens) and image sensors may be disposed on one surface of the electronic device **100**.

(42) The key input device **117** may be disposed on the side surface **110C** of the housing **110**. According to an embodiment, the electronic device **100** may exclude all or some of the above-

mentioned key input devices **117** and the excluded key input devices **117** may be implemented in other forms, e.g., as soft keys, on the display **101**.

(43) The light emitting device **106** may be disposed on, e.g., the first surface **110A** of the housing **110**. The light emitting device **106** may provide, e.g., information about the state of the electronic device **100** in the form of light. According to an embodiment, the light emitting device **106** may provide a light source that interacts with, e.g., the camera module **105**. The light emitting device **106** may include, e.g., a light emitting diode (LED), an infrared (IR) LED, or a xenon lamp.

(44) The connector holes **108** and **109** may include a first connector hole **108** for receiving a connector (e.g., a universal serial bus (USB) connector) for transmitting or receiving power and/or data to/from an external electronic device and/or a second connector hole **109** (e.g., an earphone jack) for receiving a connector for transmitting or receiving audio signals to/from the external electronic device.

(45) FIG. **3** is an exploded perspective view illustrating an electronic device **200** (e.g., the electronic device **100** of FIG. **1** or **2**) according to various embodiments.

(46) Referring to FIG. **3**, an electronic device **200** (e.g., the electronic device **100** of FIG. **1** or **2**) may include a side structure **210** (e.g., the side surface **110C** of FIG. **1** or **2**), a first supporting member **211** (e.g., a bracket), a front plate **220**, a display **230** (e.g., the display **101** of FIG. **1**), a printed circuit board **240a** and **240b**, a battery **250**, a second supporting member **260** (e.g., a rear case), an antenna (not shown), and/or a rear plate **280**. The side surface **210** has, e.g., a frame shape at least partially surrounding the space between the front plate **220** and the rear plate **280** and be disposed on the edge of the front plate **220** and the rear plate **280**. According to an embodiment, the electronic device **200** may exclude at least one (e.g., the first supporting member **211** or the second supporting member **260**) of the components or may add other components. At least one of the components of the electronic device **200** may be the same or similar to at least one of the components of the electronic device **100** of FIG. **1** or **2** and no duplicate description is made below.

(47) The first supporting member **211** may be disposed inside the electronic device **200** to be connected with the side structure **210** or integrated with the side structure **210**. The first supporting member **211** may be formed of, e.g., a metallic material and/or non-metallic material (e.g., polymer). The display **230** may be joined onto one surface of the first supporting member **211**, and the printed circuit board **240a** and **240b** may be disposed on the opposite surface of the first supporting member **211**.

(48) According to an embodiment, the printed circuit board **240a** and **240b** may include a first circuit board **240a** disposed in a first area (e.g., an upper space of the battery **250** inside the electronic device **200**) of the electronic device **200** or a second circuit board **240b** disposed in a second area (e.g., a lower space of the battery **250** inside the electronic device **200**). In the illustrated embodiment, the electronic device **200** may electrically connect the first circuit board **240a** and the second circuit board **240b** by including a coaxial cable **271**. According to an embodiment, the electronic device **200** may further include at least one wiring member (e.g., a flexible printed circuit board or a ribbon cable) electrically connecting the first circuit board **240a** and the second circuit board **240b**. A processor, memory, and/or interface may be disposed on the printed circuit board **240a** and **240b**. The processor may include one or more of, e.g., a central processing unit, an application processor, a graphic processing device, an image signal processing, a sensor hub processor, or a communication processor.

(49) According to an embodiment, the printed circuit board **240a** and **240b**, e.g., the first circuit board **240a** and/or the second circuit board **240b** may include a ground that provides a reference potential of the electronic device **200**. For example, the ground may be implemented as a circuit pattern or a flat conductor included in the printed circuit board **240a** and **240b**. In various embodiments, when the housing **201** (e.g., the side structure **210**, the first supporting member **211**, and/or the second supporting member **260**) includes a conductive material, the housing **210** may be electrically connected with the printed circuit board **240a** and **240b** (e.g., ground). For example,

when the conductive material is included, the structure, such as the housing **201**, may provide a stable operating environment by providing a ground of the electronic device **200**.

(50) According to an embodiment, the coaxial cable **271** may be disposed on or adjacent to the side structure **210**. For example, the side structure **210** may include a slot (e.g., the slot **311** of FIGS. 5 to 7) (or slit) for wiring the coaxial cable **271** in at least a partial area of the surface facing the rear plate **280**, and the coaxial cable **271** may be at least partially received in the slot **311** while one end of the coaxial cable **271** may be connected to the first circuit board **240a**, and the other end thereof may be connected to the second circuit board **240b**. In an embodiment, the electronic device **200** may include a fixing member **273** (e.g., a conductive gasket **273a** and a first clamp **273b**), thereby fixing the coaxial cable **271** to the side structure **210** while electrically connecting the coaxial cable **271** (e.g., an outer conductor of an inner conductor and the outer conductor of the coaxial cable **271**) to the housing **201** or the side structure **210**.

(51) The memory may include, e.g., a volatile or non-volatile memory.

(52) The interface may include, e.g., a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, and/or an audio interface. The interface may electrically or physically connect, e.g., the electronic device **200** with an external electronic device and may include a USB connector, an SD card/multimedia card (MMC) connector, or an audio connector.

(53) The battery **250** may be a device for supplying power to at least one component of the electronic device **200**. The battery **450** may include, e.g., a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell. At least a portion of the battery **250** may be disposed on substantially the same plane as the printed circuit board **240a** and **240b**. The battery **250** may be integrally or detachably disposed inside the electronic device **200**.

(54) An antenna not shown may be disposed between the rear plate **280** and the battery **250**. The antenna may include, e.g., a near-field communication (NFC) antenna, a wireless charging antenna, and/or a magnetic secure transmission (MST) antenna. The antenna may perform short-range communication with, e.g., an external device or may wirelessly transmit or receive power necessary for charging. According to an embodiment of the present disclosure, an antenna structure may be formed by a portion or combination of the side structure **210** and/or the first supporting member **211**.

(55) According to an embodiment, the electronic device **200** may include various electrical/electronic components **275** and **279** and/or an additional antenna module **277**. The electrical/electronic components **275** and **279** may include, e.g., a haptic module, a speaker module, a camera, a fingerprint sensor, a proximity sensor, an illuminance sensor, a touch sensor, a grip sensor, a light emitting element and/or a connector, and may be placed in an appropriate position according to the function or operation that each implements. The fingerprint sensor **275** illustrated by way of non-limiting example as one of the electrical/electronic components **275** and **279** may include a body portion **275a** and a flexible printed circuit board **275b**, and the body portion **275a** may be disposed in a position adjacent to the coaxial cable **271** on the side structure **210**. In an embodiment, the flexible printed circuit board **275b** may extend from the body portion **275a** to be electrically connected to the printed circuit board **240a** and **240b**. The antenna module **277** may be disposed, e.g., at least partially on the side structure **210** and be disposed to form a beam toward the outside of the housing **201**. For example, the antenna module **277** may include an array antenna and may radiate a radio signal along the direction in which the side structure **210** faces. In various embodiments, in a direction parallel to the first surface (e.g., first surface **110A** of FIG. 1) or second surface (e.g., second surface **110B** of FIG. 2), the antenna module **277** may be disposed to face the outer space of the housing **201** or to form a beam toward the outside of the housing **201**.

(56) According to an embodiment, the camera **279** disposed as an example of the electrical/electronic component may be disposed on the first circuit board **240a** or on a side of the first circuit board **240a**. A plurality of cameras having different optical characteristics may be

disposed adjacent to each other. In various embodiments, the camera **279** may receive external light through a path passing through the second supporting member **260** and/or the rear plate **280**. (57) In the illustrated embodiment, the fingerprint sensor **275** or the camera **279** is illustrated by way on non-limiting example as an example of the electrical/electronic component, but it should be noted that various embodiments of the disclosure are not limited thereto. Although not shown, as another example of the electrical/electronic component, a light emitting element may be disposed adjacent to the camera **279**, and the light emitting element may provide illumination to the subject upon shooting by radiating light in the direction in which the camera **279** is oriented. For example, although not shown in the drawings, as mentioned above, the electronic device **200** may include various other types of electrical/electronic components, such as a haptic module, a speaker module, and/or a connector.

(58) In the following description, the components easy to understand from the description of the above embodiments are denoted with or without the same reference numerals and their detailed description may be skipped. In the following description of embodiments, the configuration of the above-described electronic device may be referred to as necessary. In various embodiments, reference number '275' assigned as a fingerprint sensor may be utilized as a reference number illustrating an electrical/electronic component.

(59) FIG. **4** is a cross-sectional view illustrating a portion of an electronic device **200** (e.g., the electronic device **100** of FIG. **1** or **2**) according to various embodiments. FIG. **4** is a cross-sectional view illustrating a portion of the edge of the electronic device **100** or **200**, taken along line A-A' of FIG. **2** according to various embodiments.

(60) Referring to FIG. **4**, the coaxial cable **271** or the fixing member **273** may be disposed on the side structure **210** in a state of at least partially facing the rear plate **280**. For example, the rear plate **280** may be coupled to a portion of the side structure **210** by a coupling member **293**, such as a double-sided tape, and when viewed in cross-sectional view, the coaxial cable **271** or the fixing member **273** may be substantially disposed inside the space surrounded by the side structure **210** and the rear plate **280**. When viewed from the rear surface (e.g., the second surface **110B** of FIG. **2**) of the electronic device **200**, the coupling member **293** may have a substantially closed loop shape and may form a waterproof structure between the housing **201** and the rear plate **280**.

(61) According to an embodiment, the coaxial cable **271** may be disposed or fixed on the side structure **210** by the fixing member **273**, and the fixing member **273** may be formed of a conductive material to electrically connect the coaxial cable **271** to the housing **201** or the side structure **210**. The housing **201**, e.g., the side structure **210** and/or the first supporting member **211**, may be at least partially formed of a conductive material and may thus serve as a ground for the electronic device **200**, and the coaxial cable **271** may be electrically connected to the housing **201**. In various embodiments, when the flexible printed circuit board **275b** of the electrical/electronic component **275** is disposed on or adjacent to the side structure **210**, the flexible printed circuit board **275b** may be disposed in contact with the fixing member **273** and be electrically connected to the housing **210** through the fixing member **273**. For example, since at least the coaxial cable **271** and/or the flexible printed circuit board **275b** is electrically connected to a common ground (e.g., the housing **201**) inside the electronic device **200**, it is possible to suppress noise in various signal transmissions and suppress or prevent damage to the electrical/electronic components **275** and **279**, such as a fingerprint sensor or a camera.

(62) According to an embodiment, the coaxial cable **271** may be electrically connected to the housing **201** (e.g., the side structure **210**) via the fixing member **273**, e.g., a conductive gasket **273a** and, in an embodiment, the coaxial cable **271** may be electrically connected to the housing **201** through the conductive gasket **273a** and the first clamp **273b**. In various embodiments, in a structure in which the coaxial cable **271** and the housing **201** are electrically connected via the conductive gasket **273a**, the first clamp **273b** may be formed of an insulating material. As is described below, the first clamp **273b** together with a second clamp (e.g., the second clamp **277c** of

FIG. 5) of the antenna module **277** may be fastened or bound to the side structure **210**, and as the first clamp **273b** is formed of a conductive material, multiple electrical connection paths may be provided between the coaxial cable **271** (or flexible printed circuit board **275b**) and the housing **201**. According to an embodiment, the flexible printed circuit board **275b** may be electrically connected to the housing **201** by being disposed at least partially in contact with the conductive gasket **273a**. For example, the flexible printed circuit board **275b** may include a ground (e.g., ground layer **675d** of FIG. **20**), and a portion of a conductor or printed circuit pattern serving as a ground may be disposed in direct contact with the conductive gasket **273a**.

(63) FIG. **5** is a diagram including a partial perspective view illustrating a placement of a fixing member (e.g., the fixing member **273** of FIG. **3** or **4**) in an electronic device **200** according to various embodiments.

(64) Referring to FIG. **5**, the electronic device **200** and/or the side structure **210** may include a slot **311** for receiving the coaxial cable **271** and/or the antenna module **277**. The slot **311** may be formed, e.g., in an area facing the rear plate (e.g., the rear plate **280** of FIG. **3** or **4**) in the surface of the side structure **210**. In an embodiment, the coaxial cable **271** may be configured to transfer electrical signals between the first circuit board **240a** disposed in the first area and the second circuit board **240b** disposed in the second area, inside the electronic device **200**. For example, the placement structure of the coaxial cable **271** bypasses the area where the battery **250** is disposed and uses the slot **311** formed in the side structure **210**, so that substantially no influence may be had on the size or thickness of the electronic device **200**. In various embodiments, a wiring structure (not shown) may be disposed to overlap the battery **250** to electrically connect the first circuit board **240a** and the second circuit board **240b**. As the wiring structure disposed to overlap the battery **250**, e.g., a flat plate-type or film-type flexible printed circuit board or ribbon cable may be utilized.

(65) According to an embodiment, the electronic device **200** may include a fixing member **273** for fixing the coaxial cable **271** to the side structure **210**. The fixing member **273** may include, e.g., a conductive gasket **273a** coupled to surround at least part of the coaxial cable **271** or a first clamp **273b** fixing the conductive gasket **273a** onto the side structure **210**. The conductive gasket **273a** may be formed of, e.g., an elastic material based on any one or a combination of two or more of fabric, polyurethane foam, or polyethylene terephthalate (PET). The first clamp **273b** may be formed of, e.g., a metallic material, such as stainless steel. In an embodiment, in a structure in which the conductive gasket **273a** is disposed in direct contact with the housing **201** (e.g., the side structure **210**), the first clamp **273b** may be formed of an insulating material and may bring the conductive gasket **273a** in tight contact to the coaxial cable **271** or the side structure **210**, on the side structure **210**. In various embodiments, the first clamp **273b** pressurizes the conductive gasket **273a** into tight contact with the coaxial cable **271**, and the rear plate **280** is coupled with the side structure **210**, bringing the conductive gasket **273a** in tight contact to the side structure **210**.

(66) According to an embodiment, the antenna module **277** may include an antenna substrate **277a** and a wiring board **277b** extending from the antenna substrate **277a**. The antenna substrate **277a** may include an array antenna including a plurality of radiation patches disposed or fixed to, e.g., the side structure **210** (e.g., a portion of the slot **311**, indicated by '**211a**' of FIG. **6**). In an embodiment, the antenna substrate **277a** may be disposed on the side structure **210** so that the array antenna forms a beam toward an external space, and the slot **311** may be shaped to at least partially receive the antenna substrate **277a** in an appropriate position. The wiring board **277b** may be electrically connected to the first circuit board **240a** while extending from the antenna substrate **277a**. In various embodiments, the wiring board **277b** may be formed substantially integrally with the antenna substrate **277a** and may have higher flexibility than the antenna substrate **277a**. In an embodiment, when the antenna module **277** transmits and receives a signal in a high frequency band up to several tens of GHz, the electronic device **200** may include an additional antenna module **277'** disposed in a different position of the side structure **210**. For example, to implement

omnidirectionality in wireless communication, the electronic device **200** may include a plurality of antenna modules **277** and **277'**.

(67) According to an embodiment, the antenna module **277** may include at least one second clamp **277c**. For example, the second clamp **277c** may be formed to surround at least a portion of the antenna substrate **277a** and may extend from the edge of the antenna substrate **277a** and tightly contact or be fixed onto the side structure **210**. In an embodiment, the second clamp **277c** may be electrically connected to the housing **201** by directly contacting the side structure **210**. For example, the antenna module **277** may be electrically connected to the housing **201** through the second clamp **277c**. In various embodiments, a portion (e.g., the second fixing portion **473c** of FIG. **11**) of the first clamp **273b** may be disposed to overlap a portion of the second clamp **277c**. For example, the first clamp **273b** may partially be fixed to the side structure **210** by the fastening member **291** (e.g., a screw), with a portion of the second clamp **277c** disposed therebetween. In an embodiment, when the first clamp **273b** has good conductivity, a portion of the second clamp **277c** may be fixed to the side structure **210** by the fastening member **291** with a portion of the first clamp **273b** disposed therebetween.

(68) Hereinafter, an arrangement or assembly structure of the coaxial cable **271** and/or the electrical/electronic component **275** (e.g., the flexible printed circuit board **275b** of FIG. **3**) is described in greater detail below with reference to FIGS. **6** to **20**.

(69) FIG. **6** is an exploded perspective view illustrating a placement of a portion (e.g., the conductive gasket **273a**) of a fixing member **273** in an electronic device (e.g., the electronic device **200** of FIGS. **3** to **5**) according to various embodiments. FIG. **7** is a diagram illustrating a placement of a portion of a fixing member **273** in an electronic device **200** according to various embodiments. FIG. **8** is an exploded perspective view illustrating a coupling of a portion of a fixing member **273** of an electronic device **200** to a coaxial cable **271** according to various embodiments. FIG. **9** is a cross-sectional view illustrating a coupling of a portion of a fixing member **273** of an electronic device **200** to a coaxial cable **271** according to various embodiments. FIG. **10** is a cross-sectional view illustrating a portion of the electronic device **200**, taken along line B-B' of FIG. **7** according to various embodiments.

(70) Referring to FIGS. **6**, **7**, **8**, **9** and **10** (which may be referred to as FIGS. **6** to **10**), the coaxial cable **271** may be substantially received in the slot **311** and be electrically connected to a printed circuit board **240a** and **240b**, e.g., the first circuit board **240a** or the second circuit board (e.g., the second circuit board **240b** of FIG. **3** or **5**), through a coaxial connector **271a** provided at either or both ends. In an embodiment, the coaxial cable **271** is disposed substantially on the side structure **210**, and both ends (e.g., the coaxial connector **271a**) are disposed inside the space surrounded by the side structure **210** and may be coupled to the printed circuit board **240a** and **240b**. In an embodiment, the section of the slot **311**, where the coaxial cable **271** is disposed, may at least partially or substantially have a width corresponding to the diameter of the cross section of the coaxial cable **271**. For example, the coaxial cable **271** may be disposed in contact with the inner wall of the slot **311** and be fixed onto the side structure **210**. In an embodiment, a portion of the section where the coaxial cable **271** is disposed may be formed to be larger than the cross-sectional diameter of the coaxial cable **271** and may thus receive the fixing member **273**, e.g., the conductive gasket **273a** or the first clamp **273b**.

(71) In an embodiment, in the section where the fixing member **273** is received, the electronic device **200** and/or the side structure **210** may include a plurality of partitions formed inside the slot **311**. For example, in the slot **311**, the partitions **313** may support or fix the coaxial cable **271**, the conductive gasket **273a**, and/or the first clamp **273b**. According to an embodiment, referring to FIG. **7**, the electronic device **200** and/or the side structure **210** may include four partitions **313** forming a 2 column x 2 row array. In various embodiments, the coaxial cable **271** may be disposed between two rows formed by the partitions **313**, and the conductive gasket **273a** may be disposed between two columns formed by the partitions **313**. In an embodiment, the partitions **313** may

protrude from the bottom of the slot **311** and be spaced apart from the inner wall of the slot **311**. The gap formed between the partitions **313** and the inner wall of the slot **311** may be used as a space for receiving or fixing a portion of the first clamp **273b**.

(72) According to an embodiment, the conductive gasket **273a** may be coupled to surround at least a portion (e.g., the first stripped portion **271b** described below) of the coaxial cable **271** and be brought in tight contact to the bottom surface of the slot **311** by the rear plate **280**. In an embodiment, as the conductive gasket **273a** has a width larger than the slot **311**, the conductive gasket **273a** may be fixed to the slot **311** while in tight contact with the inner wall of the slot **311**. For example, as compressed while being coupled to the slot by having a width larger than the slot **311** and being formed of an elastic material, the conductive gasket **273a** may be brought in tight contact to the inner wall of the slot **311** and the outer circumferential surface of the coaxial cable **271**. For example, depending on the size and shape of the conductive gasket **273a**, the fixing member **273** may not include the first clamp **273b**, and the coaxial cable **271** may be stably connected to the housing **201** by the conductive gasket **273a**. As is described below, when another electrical/electronic component **275** or the antenna module **277** is disposed in a position adjacent to the fixing member **273**, the first clamp **273b** may be useful in providing a common ground to the coaxial cable **271**, the other electrical/electronic component **275**, and/or the antenna module **277**.

(73) According to an embodiment, the conductive gasket **273a** may include a binding recess **373a** for receiving a portion of the coaxial cable **271** and/or a dummy hole **373b** formed in parallel with the binding recess **373a**. The binding recess **373a** may be formed through the conductive gasket **273a** along the extending direction of, e.g., the coaxial cable **271**, and be shaped to be exposed or opened to a lower surface (e.g., the surface facing the bottom of the slot **311**) of the conductive gasket **273a**. For example, the coaxial cable **271** may be received in the binding recess **373a** from the lower surface of the conductive gasket **273a**. In various embodiments, the binding recess **373a** may have a diameter smaller than the cross-sectional diameter of the coaxial cable **271**. For example, if the coaxial cable **271** is received in the binding recess **373a**, the conductive gasket **273a** may come in tight contact to the outer circumferential surface of the coaxial cable **271** (e.g., the outer circumferential surface of the first stripped portion **271b** described below).

(74) According to an embodiment, the dummy hole **373b** may be disposed between the binding recess **373a** and the rear plate **280** on the electronic device **200**. In various embodiments, in a portion between the dummy hole **373b** and the rear plate **280**, the conductive gasket **273a** may contact the flexible printed circuit board (e.g., the flexible printed circuit board **275b** of FIG. 4) or the rear plate **280**. The dummy hole **373b** may stably maintain the contact state of the conductive gasket **273a** and the flexible printed circuit board **275b** and prevent/inhibit the rear plate **280** from being separated from the side structure **210** by the elastic force of the conductive gasket **273a**. For example, the portion of the conductive gasket **273a** surrounding the dummy hole **373b** may be stably brought in contact to the flexible printed circuit board **275b** and may accumulate significantly lower elastic force than the coupling force between the rear plate **280** and the side structure **210**.

(75) According to an embodiment, when electrically connected with the conductive gasket **273a** or the side structure **210**, the coaxial cable **271** may be partially stripped off in a designated position (hereinafter, a 'first stripped portion **271b**'), exposing the outer conductor to the external space. For example, although not shown, the coaxial cable **271** may be structured to have an inner conductor for signal transmission and an outer conductor disposed to surround the inner conductor to provide electromagnetic shielding or reference potential and may include insulation layers disposed to surround the outer conductor and/or between the outer conductor and the inner conductor. In an embodiment, as the insulation layer surrounding the outer conductor is partially removed, the outer conductor of the coaxial cable **271** may be exposed from the first stripped portion **271b**.

(76) According to an embodiment, when the coaxial cable **271** has a structure of transferring high-frequency signals for wireless communication, the position where the conductive gasket **273a** is

coupled or the position of the first stripped portion **271b** may differ from the position which is **214** away from one end of the coaxial cable **271**. Here, ' λ ' may refer, for example, to the resonant frequency wavelength of the high-frequency signal transferred through the coaxial cable **271**. In an embodiment, according to the position of the first stripped portion **271b**, a parasitic resonance may be generated in the coaxial cable **271** in the process of transferring a high-frequency signal, reducing the power efficiency or the signal transmission efficiency of the coaxial cable or increasing the noise of the transmitted signal. In various embodiments of the disclosure, the first stripped portion **271b** may be formed at a point different from the **214** distance from one end of the coaxial cable **271**, suppressing noise while having good signal transmission efficiency in transmission of high-frequency signals.

(77) According to an embodiment, the antenna module **277** may be disposed adjacent to the position of the fixing member **273**, in the side structure **210**. In various embodiments, the antenna module **277** may include the second clamp **277c** extending from at least one side and, together with the fixing member **273** (e.g., the first clamp **273b**), be disposed or fixed to the side structure **210** by one fastening member **291**. In an embodiment, the second clamp **277c** may be provided separately from the antenna module **277** and, in a state of surrounding at least a portion of the antenna substrate (e.g., the antenna substrate **277a** of FIG. 5), the second clamp **277c**, together with the antenna module **277** and/or the fixing member **273** (e.g., the first clamp **273b**), may be disposed or fixed to the side structure **210**. The structure in which the antenna module **277** is disposed or fixed to the side structure **210** is described in greater detail with reference to the embodiment illustrated by way of non-limiting example in FIG. 15. According to an embodiment, since the antenna module **277** is disposed in a position separate from the coaxial cable **271** or the fixing member **273** (e.g., the conductive gasket **273a**), the antenna module **277**, the coaxial cable **271**, and/or the conductive gasket **273a** may be assembled in various orders.

(78) FIG. 11 is an exploded perspective view illustrating a placement of another portion (e.g., the first clamp **273b**) of a fixing member **273** of an electronic device **200** according to various embodiments. FIG. 12 is a diagram illustrating a placement of another portion of a fixing member **273** of an electronic device **200** according to various embodiments. FIG. 13 is a partial cross-sectional perspective view illustrating a fixing member **273** taken along line C-C' of FIG. 12 according to various embodiments. FIG. 14 is a cross-sectional view illustrating a portion of an electronic device **200**, taken along line D-D' of FIG. 12.

(79) Referring to FIGS. 11, 12, 13 and 14 (which may be referred to as FIGS. 11 to 14), the fixing member **273**, e.g., the first clamp **273b**, may be disposed in the slot **311** in a state of receiving at least a portion of the conductive gasket **273a**. In an embodiment, the first clamp **273b** may at least partially be press-fitted between the inner wall of the slot **311** and the partition **313**. In various embodiments, as the first clamp **273b** includes pressurizing protrusion(s) **473d** and **473e** formed on the outer surface and/or inner surface, it is possible to securely bind the first clamp **273b** between the partition **313** and the inner wall of the slot **311** or pressurize the conductive gasket **273a**. For example, the first clamp **273b** includes the pressurizing protrusion(s) **473d** and **473e** and may thus be securely fitted into the slot **311** while pressurizing the conductive gasket **273a** in tight contact with the coaxial cable **271**.

(80) According to an embodiment, the first clamp **273b** may include a first fixing portion **473a** received in the slot **311** and a second fixing portion **473c** extending from at least one side of the first fixing portion **473a**. According to an embodiment, at least a portion of the edge of the first fixing portion **473a** may be substantially bound between the partition **313** and the inner wall of the slot **311**, and the pressurizing protrusion(s) **473d** and **473e** may be formed substantially on the outer surface or inner surface of the first fixing portion **473a**. In various embodiments, the second fixing portion **473c** may at least partially be disposed to face the surface of the side structure **210**, and the fastening member **291** (see FIG. 15) may be bound through the second fixing portion **473c** to the side structure **210**. In various embodiments, when the antenna module **277** or another

electrical/electronic component is disposed adjacent to the fixing member **273** and is fixed by the second clamp **277c**, the second clamp **277c** may at least partially be disposed between the second fixing portion **473c** and the side structure **210**. In an embodiment, a portion (e.g., the second fixing portion **473c**) of the first clamp **273b** may be disposed between the second clamp **277c** and the side structure **210**. For example, as is described in connection with FIG. **15**, the fastening member **291** may be fastened through the second fixing portion **473c** and the second clamp **277c** to the side structure **210**, and one fastening member **291** may dispose or fix the fixing member **273** or the antenna module **277** on the side structure **210**. Accordingly, the fastening member **291** and/or the pressurizing protrusions **473d** and **473e** pressurizing the conductive gasket **273a** may substantially dispose or fix the first clamp **273b**, conductive gasket **273a**, and/or coaxial cable **271** in the slot **311**.

(81) According to an embodiment, the fixing member **273** may further include an opening portion **473b** formed through the first clamp **273b** (e.g., the first fixing portion **473a**). The opening portion **473b** may expose, e.g., a portion of the conductive gasket **273a**, to the outside of the slot **311** or the first clamp **273b** and, in the portion exposed through the opening portion **473b**, the conductive gasket **273a** may contact the flexible printed circuit board (e.g., the flexible printed circuit board **275b** of FIG. **4**) or the rear plate (e.g., the rear plate **280** of FIG. **4**). Since the conductive gasket **273a** is disposed in contact or tight contact with the side structure **210** (e.g., the bottom of the slot **311**), the coaxial cable **271** or the flexible printed circuit board **275b** may substantially be connected to the housing **201** (e.g., the side structure **210**) by the conductive gasket **273a**. In various embodiments, when the first clamp **273b** has high electrical conductivity, the coaxial cable **271** or the flexible printed circuit board **275b** may be electrically connected to the housing **201** through an additional path that passes through the first clamp **273b**.

(82) FIG. **15** is a perspective view illustrating a state in which a fastening member **291** is bound in an electronic device **200** according to various embodiments. FIG. **16** is a diagram illustrating a state in which a fastening member **291** is bound in an electronic device **200** according to various embodiments. FIG. **17** is a perspective view illustrating a state in which a fastening member **291** is bound in an electronic device **200** according to various embodiments.

(83) Referring to FIGS. **15**, **16** and **17** (which may be referred to as FIGS. **15** to **17**), when the antenna module **277** or another electrical/electronic component (e.g., the fingerprint sensor **275** or camera **279** of FIG. **3**) is disposed adjacent, the fixing member **273**, together with the other electrical/electronic component or the antenna module **277**, may be disposed or fixed to the housing **201** (e.g., the side structure **210**) by one fastening member **291**. In the illustrated embodiment, the antenna module **277** may be disposed adjacent to the fixing member **273**, and the antenna module **277** may be received in another area or space provided by, e.g., the slot **311** of FIG. **6** or **7**.

(84) As described in connection with FIG. **5**, the antenna module **277** may include an antenna substrate **277a** and a wiring board **277b** extending from the antenna substrate **277a**, and the wiring board **277b** may be formed substantially integrally with the antenna substrate **277a**, thus having higher flexibility than the antenna substrate **277a**. According to an embodiment, an additional antenna module (e.g., the antenna module **277'** of FIG. **5**) may further be disposed in a position different from that in the illustrated embodiment. According to an embodiment, the antenna module **277** may be fixed to the side structure **210** by the second clamp **277c** and/or fastening member **291** respectively extending from two opposite sides of the antenna substrate **277a**. Accordingly, the coaxial cable **271**, together with the other adjacent electrical/electronic component or the antenna module **277**, may be electrically connected to the common ground (e.g., the housing or side structure). In an embodiment, the second clamp **277c** is a portion of the structure surrounding at least a portion of the antenna substrate (e.g., the antenna substrate **277a** of FIG. **5**) and may protrude or extend from at least one side of the antenna substrate.

(85) FIG. **18** is a perspective view illustrating a placement of an electrical/electronic component

275 (e.g., a fingerprint sensor) in an electronic device 200 according to various embodiments. FIG. 19 is an exploded perspective view illustrating a coupling of a housing 201 and a rear plate 280 in an electronic device 200 according to various embodiments. FIG. 20 is a cross-sectional view illustrating a portion of a flexible printed circuit board 275b, taken along line E-E' of FIG. 18 according to various embodiments.

(86) In the embodiment of FIGS. 18, 19 and 20 (which may be referred to as FIGS. 18 to 20), the rear plate 280 may be shaped to surround a portion of the side structure 210. For example, while the side surface 110c of the electronic device 100 or the housing 110 is substantially formed by the side structure 210 of FIG. 3 in the embodiment of FIG. 1 or 2, at least a portion of the side surface of the electronic device 200 may be formed by the rear plate 280 in the embodiment of FIGS. 18 to 20. Such a difference in shape may be appropriately selected considering the outer appearance of the electronic device (e.g., the electronic device 100 of FIG. 1 or the electronic device 200 of FIG. 19) or the arrangement of electrical/electronic components inside.

(87) Referring to FIGS. 18 to 20, the electronic device 200 may further include at least one electrical/electronic component 275 disposed adjacent to the coaxial cable (e.g., the coaxial cable 271 of FIGS. 3 to 5 or FIG. 11) or the fixing member (e.g., the fixing member 273 of FIGS. 3 to 5 or FIG. 11). In an embodiment, the electrical/electronic component 275 may include a fingerprint sensor and, according to an embodiment, another electrical/electronic component, not a fingerprint sensor, may be disposed adjacent to the coaxial cable 271 or the fixing member 273. In various embodiments, the electrical/electronic component 275 may include a body portion 275a where a sensing element is disposed and a flexible printed circuit board 275b extending from the body portion 275a. The 'sensing element' may include at least one of an optical element, an ultrasonic element, a transparent electrode, and a load cell, and may detect information about the user's fingerprint, approach by the user's body, contact by the user's body, and/or external environment (e.g., illuminance).

(88) According to an embodiment, the electrical/electronic component 275 may be disposed on the rear plate 280. However, various embodiments of the disclosure are not limited thereto, and similarly to the antenna module 277, the electrical/electronic component 275 may be disposed on the side structure 210. In the illustrated embodiment, the rear plate 280 may have a shape surrounding a portion of the side structure 210, and the electrical/electronic component 275 may be disposed substantially on a portion of the side structure 210. In various embodiments, when shaped to surround a portion of the side structure 210, the rear plate 280 may provide at least a portion of the side surface (e.g., the side surface 110C of FIG. 1) of the housing 201 or the electronic device 200. According to an embodiment, when shaped to surround a portion of the side structure 210, the rear plate 280 may include a key hole 281 and/or a fixing piece 283, and a key input device (e.g., the key input device 117 of FIG. 1 or 2) may be disposed through the key hole 281. The key input device 117 may be one of the electrical/electronic components mentioned in the embodiment. For example, similar to the embodiment described below, the key input device 117 disposed in the key hole 281 may be electrically connected with the housing 201 through the fixing member 273 and be thereby provided with a ground. The fixing piece 283 may be disposed on the inner surface of the rear plate 280 and may fix the body portion 275a of the electric/electronic component 275 to the inner surface of the rear plate 280. In various embodiments, the body portion 275a may be exposed to the outside of the rear plate 280 and directly contact the user's body. In an embodiment, the body portion 275 may be visually exposed to the outside but may not contact the user's body. In an embodiment, the body portion 275a may be exposed to the external space and contact the user's body but may not be visually recognized by the user. A configuration related to exposure or concealment to the external space may be appropriately selected depending on the function or the manner of implementing the function, assigned to the electrical/electronic component 275.

(89) According to an embodiment, the flexible printed circuit board 275b may extend from the body portion 275a and be disposed substantially on the inner surface of the rear plate 280. In

various embodiments, the flexible printed circuit board **275b** may be substantially disposed between the side structure **210** and the rear plate **280** or between a second supporting member (e.g., the second supporting member **260** of FIG. 3) and the rear plate **280**. In an embodiment, an end of the flexible printed circuit board **275b** may pass through the second supporting member **260** to be mechanically or electrically coupled to the printed circuit board (e.g., the first circuit board **240a** of FIG. 3).

(90) According to an embodiment, similar to the first striped portion (e.g., the first striped portion **271b** of FIG. 8) of the coaxial cable (e.g., the coaxial cable **271** of FIG. 8), the flexible printed circuit board **275b** may include a second stripped portion **275c**. The flexible printed circuit board **275b** may include a plurality of insulation layers **675a**, **675c**, and **675e**, and a plurality of wiring layers. According to an embodiment, among the wiring layers, a first wiring layer may include a plurality of signal lines **675b** formed between, e.g., a first insulation layer **675a** and a second insulation layer **675c**. Among the wiring layers, a second wiring layer may be, e.g., a ground layer **675d** (or ground line) formed between the second insulation layer **675c** and a third insulation layer **675e**. According to an embodiment, the flexible printed circuit board **275b** may include an additional wiring layer or additional insulation layer (not shown), which may be varied depending on the function and manner of implementing the function, assigned to the electrical/electronic component **275** (e.g., the body portion **275b**).

(91) According to an embodiment, the second stripped portion **275c** may include an exposure area **675f** that exposes a portion of the ground layer **675d** to the external space. For example, as a portion of the third insulation layer **675e** is removed, a portion of the ground layer **675d** may be exposed to the external space. In an embodiment, if the rear plate **280** is coupled to the housing **201** (e.g., the side structure **210**), the second stripped portion **275c** and/or the exposure area **675f** may substantially be disposed to face the fixing member **273** (e.g., the conductive gasket **273a** of FIG. 4 or 5). For example, the ground layer **675d** of the flexible printed circuit board **275b** may be electrically connected with the housing **201** substantially through the conductive gasket **273a**. Accordingly, the electrically conductive portion **275** or the flexible printed circuit board **275b**, together with the coaxial cable **271** and/or the antenna module **277**, may be electrically connected substantially with the housing **201** or the side structure **210** and may thus be provided with the common ground. For example, the electrical/electronic component **275**, the flexible printed circuit board **275b**, the coaxial cable **271**, and/or the antenna module **277** may be electrically connected to the printed circuit board (e.g., the printed circuit board **240a** and **240b** (e.g., ground) of FIG. 3) via the housing **201** or the side structure **210**.

(92) As described above, according to an example embodiment of the disclosure, an electronic device (e.g., the electronic device **100** or **200** of FIGS. 1 to 5) may comprise: a housing (e.g., the housing **201** of FIG. 3 or 4) including a front surface (e.g., the first surface **110A** of FIG. 1) facing a first direction, a rear surface (e.g., the second surface **110B** of FIG. 2) facing in a second direction opposite to the front direction, and a side structure (e.g., the side structure **210** of FIGS. 3 to 5) including a side surface at least partially surrounding a space between the front surface and the rear surface, a coaxial cable (e.g., the coaxial cable **271** of FIGS. 3 to 5) at least partially disposed in the housing, a fixing member comprising a conductive material (e.g., the fixing member **273** of FIGS. 3 to 5) having electrical conductivity and disposed in the housing surrounding at least a portion of the coaxial cable, and an electrical/electronic component (e.g., the electrical/electronic component **275** of FIG. 3 or 18) disposed in the housing and including a body portion (e.g., the body portion **275a** of FIGS. 3 to 18) at least partially disposed in the housing and a flexible printed circuit board (e.g., the flexible printed circuit board **275b** of FIG. 3 or 5) extending from the body portion. The fixing member may be configured to electrically connect the coaxial cable and the flexible printed circuit board with the housing.

(93) According to an example embodiment, the fixing member may be fixed to the side structure, and the flexible printed circuit board may be disposed to contact the fixing member between the

rear surface and the side structure.

(94) According to an example embodiment, the flexible printed circuit board may be disposed to at least partially face a surface of the side structure with the fixing member disposed therebetween.

(95) According to an example embodiment, the electronic device may further comprise: at least one printed circuit board (e.g., the printed circuit board **240a** and **240b** of FIG. **3** or **5**) received in a space between the front surface and the rear surface and including a ground. The housing may be electrically connected with the ground of the printed circuit board.

(96) According to an example embodiment, the fixing member may include a conductive gasket (e.g., the conductive gasket **273a** of FIGS. **3** to **5**) comprising an elastic material. The conductive gasket may be coupled to at least partially surround an outer circumferential surface of the coaxial cable and is disposed to contact the side structure.

(97) According to an example embodiment, the fixing member may include a conductive gasket comprising an elastic material and coupled to at least partially surround an outer circumferential surface of the coaxial cable and a first clamp (e.g., the first clamp **273b** of FIGS. **3** to **5**) coupled to the conductive gasket and configured to pressurize at least a portion of the conductive gasket. At least a portion of the first clamp may be bound or fixed to the side structure.

(98) According to an example embodiment, the fixing member may further include an opening portion (e.g., the opening portion **473b** of FIG. **11**) formed through the first clamp. A portion of the conductive gasket may be disposed to contact the flexible printed circuit board through the opening portion.

(99) According to an example embodiment, the side structure may include at least one slot (e.g., the slot **311** of FIG. **5** or **6**) formed in at least a portion of a surface facing the rear surface. At least one of the coaxial cable, the conductive gasket, or the first clamp may be at least partially received in the at least one slot.

(100) According to an example embodiment, the conductive gasket may include a binding recess (e.g., the binding recess **373a** of FIG. **8**) receiving a portion of the coaxial cable and a dummy hole (e.g., the dummy hole **373b** of FIG. **8**) in parallel with the binding recess.

(101) According to an example embodiment, the electronic device may further comprise an antenna module (e.g., the antenna module **277** of FIG. **3**, **5**, or **11**) including an antenna disposed on the side structure and including at least one second clamp (e.g., the second clamp **277c** of FIG. **11**) extending to a side. A portion of any one of the first clamp and the second clamp may be bound to the side structure, with a portion of the other one of the first clamp and the second clamp disposed therebetween, forming an electrical connection between the coaxial cable and the side structure.

(102) According to an example embodiment, the antenna module may be disposed to face an external space of the housing along a direction parallel to the front surface or the rear surface.

(103) According to an example embodiment, the electronic device may further comprise a fastener (e.g., the fastening member **291** of FIG. **3** or **15**) bound to the side structure through a portion of the first clamp and a portion of the second clamp.

(104) According to an example embodiment, the electronic device may further comprise: a rear plate (e.g., the rear plate **280** of FIG. **3**, **4**, or **18**) coupled to face at least a portion of the side structure and configured to provide at least a portion of the rear surface and at least one slot formed in a surface of the side structure in an area at least partially facing the rear plate. As at least a portion of the fixing member is received in the slot, another portion of the fixing member may be disposed to face the rear plate, and the flexible printed circuit board may be configured to be disposed on an inner surface of the rear plate to contact the fixing member.

(105) According to an example embodiment, the electrical/electronic component may include at least one of a fingerprint sensor, a key input device, a touch sensor, a pressure sensor, or a grip sensor.

(106) According to an example embodiment of the disclosure, an electronic device (e.g., the electronic device **100** or **200** of FIGS. **1** to **5**) may comprise: a rear plate (e.g., the rear plate **280** of

FIG. 3, 4, or 18), a frame-shaped side structure (e.g., the side structure **210** of FIGS. 3 to 5) including a side surface disposed corresponding to an edge of the rear plate, a coaxial cable (e.g., the coaxial cable **271** of FIGS. 3 to 5) at least partially disposed on the side structure in an area facing the rear plate, a fixing member comprising a conductive material (e.g., the fixing member **273** of FIGS. 3 to 5) disposed on the side structure surrounding at least a portion of the coaxial cable, and an electrical/electronic component (e.g., the electrical/electronic component **275** of FIG. 3 or 18) disposed in the housing and including a body portion (e.g., the body portion **275a** of FIG. 3 or 18) at least partially disposed on the rear plate and a flexible printed circuit board (e.g., the flexible printed circuit board **275b** of FIG. 3 or 5) extending from the body portion and configured to be disposed on an inner surface of the rear plate to contact the fixing member. The fixing member may be configured to electrically connect the coaxial cable and the flexible printed circuit board with the side structure.

(107) According to an example embodiment, the fixing member may include a conductive gasket (e.g., the conductive gasket **273a** of FIGS. 3 to 5) comprising an elastic material and coupled to at least partially surround an outer circumferential surface of the coaxial cable, a clamp (e.g., the first clamp **273b** of FIGS. 3 to 5) coupled to the conductive gasket and configured to pressurize at least a portion of the conductive gasket and having at least a portion bound or fixed to the side structure, and an opening portion (e.g., the opening portion **473b** of FIG. 11) formed through the clamp. A portion of the conductive gasket may contact the flexible printed circuit board through the opening portion.

(108) According to an example embodiment, the clamp may include at least one first pressurizing protrusion (e.g., the pressurizing protrusion indicated by '473e' of FIG. 13) contacting the conductive gasket.

(109) According to an example embodiment, the electronic device may further comprise: at least one slot (e.g., the slot **311** of FIG. 5 or 6) formed in the side structure in an area facing the rear plate and a plurality of partitions (e.g., the partition **313** of FIG. 7 or 14) formed in an inner space of the slot. The coaxial cable may be disposed between the plurality of partitions. A portion of the fixing member may be bound between at least one of the partitions and an inner wall of the slot.

(110) According to an example embodiment, the fixing member may include at least one second pressurizing protrusion (e.g., the pressurizing protrusion indicated by '473d' of FIG. 13 or 14) contacting the inner wall of the slot.

(111) According to an example embodiment, the electronic device may further comprise a printed circuit board (e.g., the printed circuit board **240a** and **240b** of FIG. 3 or 5) received in a space or an area surrounded by the side structure. The coaxial cable or the flexible printed circuit board may be electrically connected with the printed circuit board through the fixing member and the side structure.

(112) While the disclosure has been described and shown in connection with various example embodiments, it should be appreciated that various embodiments are not intended as limiting the disclosure but as illustrative. It will be apparent to one of ordinary skill in the art that various changes may be made in form and detail without departing from the overall scope of the disclosure, including the appended claims and their equivalents. For example, although the electric/electronic component and the antenna module (e.g., the antenna module **277** of FIG. 3) are separately described, various embodiments of the disclosure are not limited thereto, and the antenna module **277** may be one of the electrical/electronic components included in the electronic device (e.g., the electronic device **100** or **200** of FIGS. 1 to 5). In the above-described embodiments, as an electrical/electronic component electrically connected to the housing (e.g., the housing **201** of FIGS. 3 to 5) by the fixing member (e.g., the fixing member **273** of FIGS. 3 to 5), a fingerprint sensor or a flexible printed circuit board of the fingerprint sensor is illustrated by way of non-limiting example, but other various types of electrical/electronic components, such as proximity sensors, illuminance sensors, grip sensors, touch sensors, and/or pressure sensors, may be

electrically connected with the housing through the fixing member. It will also be understood that any of the embodiment(s) described herein may be used in conjunction with any other embodiment(s) described herein.

Claims

1. An electronic device comprising: a housing including a front surface facing a first direction, a rear surface facing a second direction opposite to the first direction, and a side structure including a side surface at least partially surrounding a space between the front surface and the rear surface; a coaxial cable at least partially disposed in the housing; a fixing member, comprising a conductive gasket, having electrical conductivity and disposed in the housing in a state of surrounding at least a portion of the coaxial cable; and an electrical/electronic component disposed in the housing and including a body portion at least partially disposed in the housing and a flexible printed circuit board extending from the body portion, wherein the fixing member includes a conductive gasket comprising an elastic material and coupled to at least partially surround an outer circumferential surface of the coaxial cable, and a clamp coupled to the conductive gasket and configured to pressurize at least a portion of the conductive gasket, wherein at least a portion of the clamp is bound or fixed to the side structure, wherein the conductive gasket includes a binding recess configured for receiving a portion of the coaxial cable, and a dummy hole formed in parallel with the binding recess, and wherein the fixing member is configured to electrically connect the coaxial cable and the flexible printed circuit board with the housing.
2. The electronic device of claim 1, wherein the fixing member is fixed to the side structure, and wherein the flexible printed circuit board is disposed to contact the fixing member between the rear surface and the side structure.
3. The electronic device of claim 1, wherein the flexible printed circuit board is disposed to at least partially face a surface of the side structure with the fixing member disposed therebetween.
4. The electronic device of claim 1, further comprising at least one printed circuit board received in a space between the front surface and the rear surface and including a ground, wherein the housing is electrically connected with the ground of the printed circuit board.
5. The electronic device of claim 1, wherein the conductive gasket is coupled to at least partially surround an outer circumferential surface of the coaxial cable and is disposed to contact the side structure.
6. The electronic device of claim 1, wherein the fixing member further includes an opening portion formed through the clamp, and wherein a portion of the conductive gasket is disposed to contact the flexible printed circuit board through the opening portion.
7. The electronic device of claim 1, wherein the side structure includes at least one slot formed in at least a portion of a surface facing the rear surface, and wherein at least one of the coaxial cable, the conductive gasket, or the first clamp is at least partially received in the at least one slot.
8. The electronic device of claim 1, further comprising: a rear plate coupled to face at least a portion of the side structure and configured to provide at least a portion of the rear surface; and at least one slot formed in a surface of the side structure in an area at least partially facing the rear plate, wherein as at least a portion of the fixing member is received in the slot, another portion of the fixing member is disposed to face the rear plate, and the flexible printed circuit board is disposed on an inner surface of the rear plate to contact the fixing member.
9. The electronic device of claim 1, wherein the electrical/electronic component includes at least one of a fingerprint sensor, a key input device, a touch sensor, a pressure sensor, or a grip sensor.
10. The electronic device of claim 1, wherein the clamp comprises a first clamp, the electronic device further comprising an antenna module including at least one antenna disposed on the side structure and including at least one second clamp extending to a side, wherein a portion of any one of the first clamp and the second clamp is bound to the side structure, with a portion of the other

one of the first clamp and the second clamp disposed therebetween, forming an electrical connection between the coaxial cable and the side structure.

11. The electronic device of claim 10, wherein the antenna module is disposed to face an external space of the housing along a direction parallel to the front surface or the rear surface.

12. The electronic device of claim 10, further comprising a fastener bound to the side structure through a portion of the first clamp and a portion of the second clamp.

13. An electronic device comprising: a rear plate; a frame-shaped side structure including a side surface disposed corresponding to an edge of the rear plate; a coaxial cable at least partially disposed on the side structure in an area facing the rear plate; a fixing member comprising a conductive material disposed on the side structure surrounding at least a portion of the coaxial cable; and an electrical/electronic component including a body portion at least partially disposed on the rear plate and a flexible printed circuit board extending from the body portion and disposed on an inner surface of the rear plate to contact the fixing member, wherein the fixing member includes a conductive gasket comprising an elastic material and coupled to at least partially surround an outer circumferential surface of the coaxial cable, and a first clamp coupled to the conductive gasket and configured to pressurize at least a portion of the conductive gasket, wherein at least a portion of the first clamp is bound or fixed to the side structure, wherein the conductive gasket includes a binding recess receiving a portion of the coaxial cable, and a dummy hole formed in parallel with the binding recess, and wherein the fixing member is configured to electrically connect the coaxial cable and the flexible printed circuit board with the side structure.

14. The electronic device of claim 13, further comprising a printed circuit board received in a space or an area surrounded by the side structure, wherein the coaxial cable or the flexible printed circuit board is electrically connected with the printed circuit board through the fixing member and the side structure.

15. The electronic device of claim 13, wherein the fixing member further includes: an opening portion formed through the first clamp, and wherein a portion of the conductive gasket contacts the flexible printed circuit board through the opening portion.

16. The electronic device of claim 15, wherein the first clamp includes at least one first pressurizing protrusion contacting the conductive gasket.

17. The electronic device of claim 13, further comprising: at least one slot formed in the side structure in an area facing the rear plate; and a plurality of partitions formed in an inner space of the slot, wherein the coaxial cable is disposed between the plurality of partitions, and wherein a portion of the fixing member is bound between at least one of the partitions and an inner wall of the slot.

18. The electronic device of claim 17, wherein the fixing member includes at least one second pressurizing protrusion contacting the inner wall of the slot.
