

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412550
Kind Code	B1
Date of Patent	September 09, 2025
Inventor(s)	Murski; Paul John

Drum set transportation apparatus and method of use

Abstract

A drum set transportation apparatus is provided that includes a cover and a frame adapted to hold a kick drum and additional drum components. The cover contains a set of wheels and a handle and is removably attached to the frame so that a user may place the cover over the frame and transport the kick drum and additional components with ease. The frame has a plurality of attachment points that allow for a user to attach additional instrument components such as instruments stands. The apparatus further contains padded inserts to protect the enclosed instruments during transportation and the padded inserts may include features to allow for storage of other components such as drumsticks.

Inventors:	Murski; Paul John (Brenham, TX)
Applicant:	Murski; Paul John (Brenham, TX)
Family ID:	96950486
Appl. No.:	18/808384
Filed:	August 19, 2024

Publication Classification

Int. Cl.: G10D13/10 (20200101); G10G7/00 (20060101)

U.S. Cl.:

CPC G10D13/28 (20200201); G10G7/005 (20130101);

Field of Classification Search

CPC: G10D (13/28); G10G (7/005)

USPC: 84/412

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3188046	12/1964	Cervenka	403/197	F16B 9/054
3326074	12/1966	Osty	84/411R	G10D 13/03
D253229	12/1978	Spranger	D34/19	N/A
4333682	12/1981	Iser	190/8	A47C 9/08
4579229	12/1985	Porcaro	N/A	N/A
4593596	12/1985	Gauger	N/A	N/A
5240264	12/1992	Williams	280/654	B62B 3/006
5464236	12/1994	Benting	280/30	B62B 3/02
6550860	12/2002	Lombardi	297/188.09	A47C 13/00
6610916	12/2002	Torrez	N/A	N/A
7608769	12/2008	Izen	84/411R	G10D 13/02
8657129	12/2013	Marks	N/A	N/A
9601099	12/2016	Steele	N/A	G10H 1/32
9754567	12/2016	Griffin	N/A	G10D 13/02
9792887	12/2016	Pinelli	N/A	G10D 13/02
9884638	12/2017	Sulcer, Jr.	N/A	B62B 1/18
10013960	12/2017	Wish	N/A	G10D 13/11
10783861	12/2019	Fowler	N/A	G10D 13/02
10822194	12/2019	Hegler	N/A	B65H 75/4402
11862130	12/2023	Murthy	N/A	G10D 13/28
2005/0252358	12/2004	Izen	84/411R	G10D 13/02
2010/0043622	12/2009	Sandson	84/411R	G10D 13/28
2010/0051488	12/2009	Allen	206/314	A45C 13/26
2020/0105233	12/2019	Savona	N/A	G10D 13/11
2021/0158787	12/2020	Wish	N/A	G10D 13/28
2021/0241727	12/2020	Wish	N/A	G10D 13/02
2023/0386434	12/2022	Wish	N/A	F16M 13/022
2023/0395043	12/2022	Wish	N/A	G10D 13/11

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2005203236	12/2006	AU	G10D 13/10
2933183	12/2022	ES	G10D 13/06
2017509934	12/2016	JP	G10D 13/02
WO-2015144461	12/2014	WO	G10D 13/02

Primary Examiner: Schreiber; Christina M

Background/Summary

BACKGROUND

(1) In order for a drummer to play its instruments, the drummer must first utilize a large amount of hardware to set up and support those instruments. As an example, there may be as many as five to

ten separate stands that support the individual instruments that make up a drum kit—all of which must be set up prior to playing. Additionally, when the drummer is done playing, the drummer must reverse the process and break down the hardware that was laboriously set up. Thus, this large amount of hardware presents a labor-intensive problem for drummers that frequently set up and tear down their drum kit. Although there have been attempts to reduce the amount of hardware (and time) required to set up a drummer's instruments—by providing a frame configured to quickly receive portions of a drum kit's existing hardware—these solutions still require the drummer to store the additional instrument hardware separately prior to transportation. As a result, these solutions do not reduce the amount of hardware required, nor do they save a significant amount of set-up or tear-down time. In all of the aforementioned solutions, the large amount of hardware can easily become disorganized. Finally, traditional means for the storage and transportation of drums kits—e.g., cardboard boxes or hard-shell carrying cases—require a drummer to either carry their drum kit's heavy and unwieldy stands or bring another piece of equipment to aid in their transportation. As exhibited by the foregoing limitations of existing transportation solutions, the set-up and tear-down processes for a drummer's instruments continue to be lengthy and labor-intensive.

(2) For the foregoing reasons, there is a need for a device that facilitates the transportation and rapid assembly of a drum set by storing and transporting the kick drum and hardware together as one piece to which the other instruments can be attached as needed.

SUMMARY

(3) The present application is directed towards an apparatus that stores and transports a kick drum together with the hardware necessary for a drum kit, as one piece, which substantially reduces the time and effort required to transport and set up a drum kit.

(4) In some embodiments, the apparatus includes a frame, where the frame includes a base with a first base rail and a second base rail, the first and second base rails connected by a horizontal base rail, a first upright and second upright connected to the first base rail and a third upright and fourth upright connected to the second base rail, a first top rail connected to the first upright and second upright, a second top rail connected to the third upright and fourth upright, a plurality of instrument stands removably attached to the frame and a rectangular cuboid cover with an open face adapted to overlay the frame at least two handles disposed on a pair of opposite faces of the cover and at least two wheels mounted to the cover, the wheels mounted on opposite faces of the cover and disposed near the open face of the cover.

(5) In some embodiments, the first base rail is connected to a first anterior horizontal member and the second base rail is connected to a second anterior horizontal member. In some embodiments, the frame includes a solid bottom face connected to the first base rail on one edge and the second base rail at an opposite edge. In some embodiments, the first and second anterior horizontal members are disposed inline and a space separating the first and second anterior horizontal members is adapted to fit a kick drum pedal.

(6) In some embodiments, the top rails include at least one longitudinally extending opening which is configured to receive fasteners. In some embodiments, the base rails include longitudinally extending openings configured to receive fasteners. In some embodiments, the frame includes at least two turnbuckles affixed to the base rails and used to mount a kick drum to the frame. In some embodiments, the frame includes a first and second cylindrical members which are attached to the anterior horizontal members and the horizontal member. The cylindrical members are spaced to support a kick drum.

(7) In some embodiments, instrument stands are attached to the top and bottom rails and secured by fasteners which attach to the longitudinal openings. In some embodiments, the instrument stands are hollow posts and are configured to receive additional instrument elements. In some embodiments, a padded insert is included with the apparatus. The padded insert may be shaped to protect a kick drum. In some embodiments the padded insert contains cavities to hold instrument

elements.

(8) In some embodiments the cover includes a padded layer on an upper interior surface of the cover. In some embodiments, non-slip pads are attached to the bottom of the solid bottom face. In some embodiments, the non-slip pads have adjustable mounts that may be used to adjust the height of the frame.

(9) In another aspect of this disclosure, an instrument transportation apparatus is disclosed and includes a rectangular cuboid frame. The frame includes top rails and bottom rails, connected by uprights. The bottom rails are connected by a horizontal rail. The frame is configured to hold an article. The transportation apparatus includes a cover which is configured to fit around the frame, the cover having an open bottom face. Wheels are disposed in parallel along the bottom of the cover, and a retractable handle is disposed at the top of the cover. The apparatus includes accessory connection poles and the accessory connection poles are configured to attach to the frame and a set of secondary articles. In some embodiments the frame has at least two turnbuckles attached to the bottom rails and configured to secure the article. In some embodiments, the frame includes non-stick pads on the bottom.

(10) In another aspect of the disclosure a method for using a drum set transportation apparatus is described. The method includes setting down the drum set transportation apparatus, unlatching a set of retaining latches that are affixed to the cover of the apparatus, lifting the cover, removing a padded insert, attaching instrument poles, adjusting the height of the drum set transportation apparatus, and placing a kick drum placing a kick drum pedal in an opening on the frame of the transportation apparatus.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) These and other features, aspects, and advantages of the present invention will become better understood with regard to the following description, appended claims, and accompanying drawings where:

(2) FIG. 1 illustrates an embodiment of a drum set transportation apparatus that depicts the outside of a cover in accordance with one aspect of this specification.

(3) FIG. 2 illustrates an embodiment of a drum set transportation apparatus that depicts the removal of a cover and a padded insert on a frame in accordance with one aspect of this specification.

(4) FIG. 3 illustrates an embodiment of a drum set transportation apparatus that depicts a frame in accordance with one aspect of this specification.

(5) FIG. 4 illustrates an embodiment of a drum set transportation apparatus that depicts a frame with a kick drum and instrument stands in accordance with one aspect of this specification.

(6) FIG. 5 illustrates an embodiment of a drum set transportation apparatus that depicts the removal of a cover and a padded layer on an inner surface of a cover from a side perspective in accordance with one aspect of this specification.

(7) FIG. 6 illustrates an embodiment of a drum set transportation apparatus that depicts a cover placed upon a frame from a side perspective in accordance with one aspect of this specification.

(8) FIG. 7 illustrates a process for deploying a drum kit using the drum kit apparatus.

DETAILED DESCRIPTION

(9) The embodiments of the invention described herein are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Rather, the embodiments selected for description have been chosen to enable one skilled in the art to practice the invention.

(10) Referring to FIGS. 1-6, various examples of a drum set transportation apparatus are depicted. Drum set transportation apparatus **100** is designed to reduce the time and labor required to transport and set up a drum set by storing a kick drum and necessary hardware together.

(11) As shown in FIG. 1, drum set transportation apparatus **100** includes cover **102**. As shown, cover **102** includes a pair of wheels **110**, protruding handle **104**, recessed handles **106**, and a plurality of retaining latches **108**. In some embodiments, there may be more or fewer retaining latches. As shown in FIG. 1, cover **102** is in the shape of a rectangular cuboid without a lower face, although other shapes may be possible, such as a cuboid with uneven sides. Cover **102** may be comprised of a material strong enough to resist deformation during transportation. As an example, cover **102** may be comprised of fiberglass or another material such as plastic or carbon fiber.

(12) As depicted in FIG. 1, wheels **110** are disposed on opposing sides along a lower edge of cover **102**. In some embodiments, wheels **110** may be removable. In some embodiments, handle **104** may be disposed along a top of one edge of cover **102**. Handle **104** may be extendable and retractable by means of one or more telescoping members. In some embodiments, a plurality of retaining latches **108** are disposed along lower edges of at least two opposing sides of cover **102**. Retaining latches are configured to attach to protrusions of a frame designed to sit inside of cover **102** as further depicted in FIG. 2.

(13) Referring still to FIG. 1, with the cover attached to an enclosed frame, using a force applied downward and backward on protruding handle **104**, the user can tilt drum set transportation apparatus **100** backward such that drum set transportation apparatus **100** pivots about the axis formed by wheels **110**. In this tilted position, the user can exert a pulling or pushing force on protruding handle **104**, leveraging the rotational movement of wheels **110** to transport drum set transportation apparatus **100**.

(14) As shown in FIG. 2, cover **102** may be configured to fit over and enclose frame **201**, where frame **201** may be further specifically adapted to hold an instrument. Cover **102** may comprise a plurality of retaining latches **108** adapted to secure cover **102** to frame **201** when the latches are engaged. Frame **201** may have a plurality of retaining latch catches **209** disposed along at least one lower edge to receive and secure retaining latches **108**. Other latching configurations may be possible.

(15) As further shown in FIG. 2, drum set transportation apparatus **100** may further comprise at least one padded insert **203** adapted to fit over an upper surface of frame **201**. In some embodiments, padded insert **203** is removeable. In alternative embodiments, padded insert **203** may be affixed to the inside of cover **102** such that when cover **102** is removed, padded insert **203** is also removed, exposing the complete contents of the enclosed frame and instruments. Padded insert **203** may be made of a soft material that may deform temporarily under impact. As an example, padded insert **203** may be made of packing foam. In some embodiments, the packing foam may be polyethylene foam. Padded insert **203** may have a minimum thickness between 0.25 inches and 3 inches, although in some areas padded insert may be thicker to fill otherwise empty space within the enclosure.

(16) Padded insert **203** may include one or more cavities **205** on its upper surface. Cavities **205** may be rectangular in shape with a length of between 1 inch and 30 inches, a width of between 1 inch and 30 inches, and a depth of between 1 inch and 4 inches. In this manner cavities **205** may act to store various drum kit accessories. Cavities **205** may be suitably shaped and sized to hold various accessories for a drum kit, or for drum set transportation apparatus **100**.

(17) As shown in FIG. 3, drum set transportation apparatus **300** includes frame **201**. Frame **201** comprises base frame elements made up of first base rail **312**, second base rail **314**, anterior member **322**, anterior member **323**, and posterior member **207** coupled together. Frame **201** further comprises first upright **302** at the connection point between first base rail **312** and anterior members **322** and **323**, second upright **304** at the connection point between first base rail **312** and posterior member **207**, third upright **306** at the connection point between the second base rail **314** and anterior member **322**, and fourth upright **308** at the connection point between second base rail **314** and posterior member **207**. In alternative embodiments (not shown), uprights **302**, **304**, **306**, and **308** may be offset from the connection points of the base rails with the anterior and posterior

members. As shown, first upright **302** and second upright **304** are connected by first top rail **316**, and third upright **306** and fourth upright **308** are connected by second top rail **318**. Frame **201** may further comprise turnbuckles **328**, each affixed to one of the first and second base rails **312** and **314**. Frame **201** may be comprised of aluminum or another material of sufficient strength and rigidity to resist deformation during transportation and use. Frame **201** may also be comprised of carbon fiber.

(18) In some embodiments, uprights **302**, **304**, **306**, and **308** may be coupled to the base utilizing a plurality of bracing members **330**. The plurality of bracing members **330** may be utilized to support structural integrity of the frame by attaching upright members to horizontal components.

(19) In some embodiments, dimensions of frame **201** may be approximately 28 inches in width, 21 inches in depth, and 16 inches in height. However, in other embodiments, the dimensions of frame **201** may vary to accommodate differently sized instruments or varying amounts of hardware. For example, the dimensions of frame **201** may have a width between 16 and 36 inches, a depth between 4 and 26 inches, and a height between 6 and 36 inches.

(20) As depicted, frame **201** includes opening **334** between anterior members **322** and **323** substantially spaced to accommodate a kick drum pedal. In some embodiments, anterior members **322** and **323** may be connected and may not have opening **334**. In some embodiments, the dimensions of opening **334** may be approximately 11 inches in width. As shown in FIG. 3, center member **315** is disposed behind opening **334** to allow sufficient space for placement of the kick drum pedal or other apparatus. As depicted, center member **315** is approximately 12 inches behind opening **334**, however in alternative embodiments, the distance between center member **315** and opening **334** may vary to accommodate appropriate instruments.

(21) In some embodiments, frame **201** may further comprise a solid floor **332**. Solid floor **332** may be comprised of a material of sufficient strength and rigidity to resist deformation during transportation and use. In some embodiments, solid floor **332** may be comprised of aluminum. In other embodiments, solid floor **332** may be comprised of fiberglass.

(22) As shown, frame **201** includes a plurality of longitudinally extending openings **320** disposed along first base rail **312**, second base rail **314**, first top rail **316** and second top rail **318**. While a plurality of openings are shown, fewer openings may be utilized. The longitudinally extending openings **320** may be used in conjunction with a plurality of U-bolts **342**, and a plurality of securing plates **340** to attach additional drum hardware elements. Alternative hardware known to those in the art may be used for attaching other drum hardware elements.

(23) In some embodiments, the lower face of frame **201** may comprise a plurality of non-slip pads **336** attached on the lower face of the first base rail **312** and second base rail **314**. Non-slip pads **336** may be comprised of a non-rigid material. In some embodiments, non-slip pads **336** may be comprised of hard rubber. Non-slip pads **336** may have a height of between 0.125 inches and 2 inches. Plurality of non-slip pads **336** may be attached to the solid floor **332** by a plurality of adjustable mounts **338** configured to allow the pads to be disposed at varying distances from the lower face of the solid floor **332**. As an example, adjustable mounts **338** may comprise a screw that may be extended from or retracted into the base or a portion of one of the uprights by rotating—thereby allowing non-slip pads **336** to be disposed at varying distances from the lower face of frame **201**.

(24) In some embodiments, frame **201** further includes a first cylinder **324** and a second cylinder **326**. First cylinder **324** may be connected at one end to the anterior member **322** and at the opposite end to the posterior member **207**. Second cylinder **326** may be connected at one end to the anterior member **323** and at the opposite end to the posterior member **207**. First cylinder **324** and second cylinder **326** may be connected at their midpoints by a center member **315**.

(25) As shown in FIG. 4, drum set transportation apparatus **400** includes frame **201** which is configured to support kick drum **444** in place under tension by use of at least two turnbuckles **328**. Drum set transportation apparatus **400** further includes kick drum **444**, high hats **448**, or other

secondary articles, etc. In alternative embodiments, not shown, drum set transportation apparatus **400** may be configured to hold other instruments, including, for example, slide guitar, keyboard, xylophone, or any other similar structures, components, or technologies that would be understood by one skilled in the art.

(26) As depicted in FIG. 4, anterior members **322** and **323** do not connect, however in other embodiments (not shown), anterior members **322** and **323** may connect inline. As depicted, opening **334** is disposed between anterior members **322** and **323**. Opening **334** may provide access to one or more latches (not shown) that allow kick drum **444** to be removably attached to frame **201**.

(27) As further shown in FIG. 4, drum set transportation apparatus **400** may comprise a plurality of adjustable instrument stands **450** that may be removably attached to frame **201** via the longitudinally extending openings **320** within the first base rail **312**, second base rail **314**, first top rail **316**, and second top rail **318**. Adjustable instrument stands **446** may be accessory connection poles or may comprise a removable hollow post structure **452** and a vertical rod **454**. Vertical rod **454** of adjustable instrument stands **450** may sit within the removable hollow post structure **452**. Adjustable instrument stands **450** may be fastened to frame **201** by U-bolts **342** and securing plates **340** disposed through the longitudinally extending openings **320** in the first base rail **312**, second base rail **314**, first top rail **316**, and second top rail **318**.

(28) As shown in FIG. 5, drum set transportation apparatus **100** includes a padded insert **203** that may be configured to fit over kick drum **444** and between frame **201** and cover **102** and may be removable. Padded insert **203** may be comprised of a soft material which deforms temporarily under impact. As an example, padded insert **203** may be made of packing foam. In some embodiments, the packing foam may be made of polyethylene foam. In some embodiments, padded insert **203** may be excluded. As depicted in FIG. 5, padded insert **203** is shaped to conform to the curve of kick drum **444**. In alternative embodiments, other packaging materials may be used.

(29) As further shown in FIG. 5, cover **102** contains a padded layer **512** that is attached to an inner surface of cover **102**. As an example, in embodiments where cover **102** has the shape of a hollow cuboid without a lower face, padded layer **512** is located on an underside of an upper face of cover **102**. Padded layer **512** is made of a soft material which deforms temporarily under impact. As an example, padded layer **512** may be packing foam. In some embodiments, the packing foam may be made of polyethylene foam. In some embodiments, padded layer **512** has a thickness between 0.25 inches and 3 inches. In other embodiments (not shown) padded layer **512** may be omitted.

(30) As shown in FIG. 6, cover **102** may be configured to fit over and enclose frame **201** while at least one padded insert **203** rests on an upper surface of frame **201**.

(31) As further shown in FIG. 7, a method **700** for deploying a drum kit using the above-described drum kit apparatus is described. When a user arrives at a music venue, at step **702** a user begins assembly of a drum kit by setting down drum set transportation apparatus. At step **704**, the user then may modify the height of the drum set transportation apparatus by adjusting the plurality of non-slip pads attached to the lower face of the frame. At step **706**, the user may then remove the cover from the frame by unlatching the plurality of retaining latches disposed along the cover. At step **708**, the user may remove the padded insert located on top of the kick drum. At step **710**, the user may remove the additional instrument elements placed in the cavities in the upper surface of the removable padded insert. At step **712**, the user may fasten the removable instrument stands to the longitudinally extending openings within the first base rail, second base rail, first top rail, and second top rail. At step **714**, the user may place a kick drum pedal in the opening between the anterior members. At step **716**, the user may then place a seat in front of and use the drum set apparatus. The order of these steps may be adjusted according to the user's preferences. A user may pack the drum kit for transportation by essentially practicing each of the above steps in reverse (e.g., removing kick drum and instrument stands, removing additional instrument elements, replacing padded insert, replacing cover, latching cover, adjusting feet, and transporting device to the next

desired location). Although an order of steps is provided above, a user may perform various steps in any order as would be apparent to one of skill in the art.

(32) References to specific materials such as fiberglass, aluminum, carbon fiber, and plastic, etc. in the embodiments described above should not be construed to exclude other possible materials which will be apparent to one of skill in the art.

(33) It may be apparent to one of ordinary skill in the art that the drum set transportation apparatus may be created using some or all of the mentioned features and components without departing from the spirit and scope of the present invention.

Claims

1. A drum set transportation apparatus comprising: a frame comprising: a base comprising a first base rail and a second base rail; wherein the first and second base rails are connected by a horizontal base rail; a first upright and second upright connected to the first base rail and a third upright and fourth upright connected to the second base rail; a first top rail connected to the first upright and second upright; a second top rail connected to the third upright and fourth upright; a plurality of instrument stands removably attached to the frame; a rectangular cuboid cover with an open face configured to overlay the frame; wherein the rectangular cuboid cover comprises at least a solid top face opposite an open bottom face, a front face opposite a rear face, and a first lateral face opposite a second lateral face; wherein the solid top face has a rear edge adjacent to the rear face and a retractable handle extending upward from the solid top face near the rear edge; wherein the first lateral face has a bottom edge adjacent to the open bottom face and a rear edge adjacent to the rear face; wherein the second lateral face has a bottom edge adjacent to the open bottom face and a rear edge adjacent to the rear face; wherein a first wheel is mounted on the first lateral face near the bottom edge and rear edge of the first lateral face; and wherein a second wheel is mounted on the second lateral face near the bottom edge and rear edge of the second lateral face.
2. The apparatus of claim 1, wherein the first base rail is connected to a first anterior horizontal member and the second base rail is connected to a second anterior horizontal member.
3. The apparatus of claim 2, wherein the frame further comprises a solid bottom face connected to the first base rail on one edge and the second base rail at an opposite edge.
4. The apparatus of claim 3, wherein the first and second anterior horizontal members are disposed inline with each other and wherein a space separating the first and second anterior horizontal members is configured to fit a kick drum pedal.
5. The apparatus of claim 4, wherein each top rail further comprises at least one longitudinally extending opening configured to receive fasteners.
6. The apparatus of claim 5, wherein the first and second base rail further comprises at least one longitudinally extending opening configured to receive fasteners.
7. The apparatus of claim 6, the frame further comprising at least two turnbuckles affixed to the base rails to mount a kick drum to the frame.
8. The apparatus of claim 2, the frame further comprising a first cylindrical member with a first longitudinal and a second longitudinal end and a second cylindrical member with a first longitudinal and a second longitudinal end; wherein the first cylindrical member is connected to the first anterior horizontal member at the first longitudinal end and the horizontal base rail at the second longitudinal end, the second cylindrical member is connected to the second anterior horizontal member at the first longitudinal end and the horizontal base rail at the second longitudinal end; and wherein the first and second cylindrical members are spaced to support a kick drum.
9. The apparatus of claim 6, wherein the plurality of instrument stands are removably attached to the first and second base rail and the first and second top rail by fasteners extending through the longitudinally extending openings in the top rails and base rails.

10. The apparatus of claim 9, wherein the plurality of instrument stands comprise: a removable hollow post structure; and a vertical rod moveably disposed within the removable hollow post structure; wherein the vertical rod is configured to extend out of the removable hollow post structure; and wherein the vertical rod is configured to receive a plurality of additional instrument elements.

11. The apparatus of claim 10, wherein the apparatus further comprises a removable padded insert configured to fit inside the rectangular cuboid cover and shaped to secure an instrument.

12. The apparatus of claim 11, wherein the removable padded insert further comprises at least one cavity in an upper surface to contain one or more pieces of equipment.

13. The apparatus of claim 10, wherein the cover further comprises a padded layer on an upper interior surface.

14. The apparatus of claim 3, wherein the frame further comprises a plurality of non-slip pads located on the solid bottom face.

15. The apparatus of claim 14, wherein the plurality of non-slip pads are attached to the solid bottom face by a plurality of adjustable mounts configured to allow the non-slip pads to be disposed at varying distances from the solid bottom face.

16. An instrument transportation apparatus, comprising: a rectangular cuboid frame comprising; a set of top rails and a set of bottom rails; wherein the top rails and the bottom rails are connected by uprights; wherein the bottom rails are connected by a connecting horizontal rail; and wherein the rectangular frame is configured to receive an article; a cover configured to fit around the frame, the cover comprising a top face, a plurality of lateral faces, a front face, a rear face, an open bottom face, a set of wheels disposed in along opposite edges of the bottom face and near a rear edge of the bottom face, wherein the rear edge of the bottom face is adjacent to the rear face of the cover, and a retractable handle on the top face; wherein the retractable handle is disposed above the set of wheels and near a rear edge of the top face of the cover, wherein the retractable handle extends upward from the top face of the cover, and wherein the rear edge of the top face is adjacent to the rear face; and a plurality of accessory connection poles; wherein the accessory connection poles are configured to attach to the rectangular frame; and wherein the accessory connection poles are configured to attach to a set of secondary articles.

17. The apparatus of claim 16, further comprising at least two turnbuckles; wherein the turnbuckles are configured to attach to the rectangular frame; wherein turnbuckles are configured to secure the article received by the rectangular frame.

18. The apparatus of claim 16, wherein the set of bottom rails comprises a first bottom rail and a second bottom rail, and wherein the first bottom rail is connected to a first anterior horizontal member and the second bottom rail is connected to a second anterior horizontal member.

19. The apparatus of claim 18, the frame further comprising a first cylindrical member with a first longitudinal and a second longitudinal end and a second cylindrical member with a first longitudinal and a second longitudinal end; wherein the first cylindrical member is connected to the first anterior horizontal member at the first longitudinal end and the connecting horizontal rail at the second longitudinal end, the second cylindrical member is connected to the second anterior horizontal member at the first longitudinal end and the connecting horizontal rail at the second longitudinal end; and wherein the first and second cylindrical members are spaced to support a kick drum.

20. A method for deploying a drum set using a drum set transportation apparatus, comprising: setting down the drum set transportation apparatus at a desired location, the drum set apparatus further comprising: a frame with a plurality of non-slip pads attached to a lower face of the frame; a cover overlaying the frame, the cover having a plurality of engaged retaining latches; a kick drum attached to the frame; and a removable padded insert located on top of the kick drum within the frame; a plurality of additional instrument elements, wherein the frame further comprises a first base rail, a second base rail, a first top rail, and a second top rail; modifying a height of the drum

set transportation apparatus by adjusting the plurality of non-slip pads attached to a lower face of the frame; removing the cover from the frame by unlatching the plurality of retaining latches disposed along the cover and lifting the cover; removing the padded insert located on top of the kick drum within the frame; removing the plurality of additional instrument elements placed in cavities in an upper surface of the removable padded insert; fastening a plurality of removable instrument stands to at least one of a set of longitudinally extending openings within the first base rail, the second base rail, the first top rail, and the second top rail of the frame; and placing a kick drum pedal in an opening between a pair of anterior members of the frame.
