

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12413434

Kind Code

B1

Date of Patent

September 09, 2025

Inventor(s)

Mirza; Khurram Ahmad et al.

Service aware proxy-call session control function (P-CSCF) traffic routing

Abstract

Solutions for service aware proxy-call session control function (P-CSCF) traffic routing include: receiving, at a master P-CSCF in a pool of a plurality of P-CSCFs, internet protocol (IP) multimedia subsystem (IMS) traffic from a device; determining, by the master P-CSCF, a traffic type (e.g., 5G, 4G, SMS, WiFi, etc.) of the IMS traffic from the device; based on at least the traffic type of the IMS traffic from the device, selecting, by the master P-CSCF, a serving P-CSCF from the pool for the device; and forwarding, by the serving P-CSCF for the device, the IMS traffic from the device to an IMS. In some examples, the serving P-CSCF selection also includes loading considerations. In some examples, an alternate P-CSCF is available for failover as the new master P-CSCF. In some examples, a network includes multiple pools of P-CSCFs, with each pool having its own master P-CSCF and alternate P-CSCF.

Inventors: Mirza; Khurram Ahmad (Bellevue, WA), Mufti; Shujaur (Snoqualmie, WA)

Applicant: T-Mobile USA, Inc. (Bellevue, WA)

Family ID: 96950518

Assignee: T-Mobile USA, Inc. (Bellevue, WA)

Appl. No.: 17/221761

Filed: April 02, 2021

Publication Classification

Int. Cl.: H04L47/12 (20220101); H04L12/14 (20060101); H04L65/1016 (20220101);
H04L65/1045 (20220101)

U.S. Cl.:

CPC **H04L12/1407** (20130101); **H04L47/12** (20130101); **H04L65/1016** (20130101);
H04L65/1045 (20220501);

Field of Classification Search

CPC: H04L (12/1407); H04L (65/1045); H04L (47/12); H04L (65/1016)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9332041	12/2015	Bakker	N/A	H04L 65/1096
9516577	12/2015	Punz	N/A	N/A
9560082	12/2016	Rasanen	N/A	N/A
10154371	12/2017	Rahat	N/A	H04W 4/02
10284420	12/2018	Livanos et al.	N/A	N/A
10326804	12/2018	Agarwal	N/A	H04L 65/1069
10491753	12/2018	Al-Mehdar et al.	N/A	N/A
10764376	12/2019	Stammers	N/A	N/A
10917527	12/2020	Ahmadi	N/A	N/A
2006/0090001	12/2005	Collins	709/230	H04L 65/1101
2008/0256251	12/2007	Huotari	709/229	H04L 67/1001
2009/0116467	12/2008	Shi	370/338	H04L 67/30
2009/0144429	12/2008	Astrom	709/227	H04L 65/40
2010/0299451	12/2009	Yigang et al.	N/A	N/A
2011/0075655	12/2010	Sahin	370/352	H04L 65/1045
2011/0076982	12/2010	Li	370/352	H04L 65/1016
2011/0165901	12/2010	Baniel et al.	N/A	N/A
2011/0200013	12/2010	Cheng	370/331	H04W 36/0011
2012/0069840	12/2011	Zhu	370/353	H04L 65/104
2014/0086177	12/2013	Adjakple	370/329	H04W 74/04
2015/0326619	12/2014	Lau	370/328	H04L 65/1073
2015/0350983	12/2014	Kwok	370/331	H04W 36/247
2015/0358853	12/2014	Kiss	370/230	H04W 28/0263
2016/0057607	12/2015	Dubesset	455/433	H04W 8/04
2016/0156678	12/2015	Li	370/352	H04L 12/1407
2016/0255490	12/2015	Mufti et al.	N/A	N/A
2016/0344817	12/2015	Renzullo et al.	N/A	N/A
2017/0111915	12/2016	Mathias	N/A	H04W 4/12
2018/0007612	12/2017	Jahangir	N/A	H04L 61/503
2018/0103500	12/2017	Chiang	N/A	H04L 65/1073
2018/0262924	12/2017	Dao	N/A	H04W 72/535
2019/0037451	12/2018	Chaponniere	N/A	H04W 76/38
2019/0059024	12/2018	Mufti	N/A	H04L 65/1069
2019/0075139	12/2018	Bouvet	N/A	H04L 67/1014
2019/0215729	12/2018	Oyman	N/A	H04L 65/1016
2020/0413337	12/2019	Liu	N/A	G06F 21/81
2021/0044628	12/2020	Foti	N/A	H04L 67/52
2021/0176817	12/2020	Takakura	N/A	H04L 65/1069

2022/0131908	12/2021	Oyman	N/A	H04L 65/752
2022/0131911	12/2021	Das	N/A	H04L 65/1016
2022/0201639	12/2021	Abtin	N/A	H04L 65/1104
2022/0232376	12/2021	Dauneria et al.	N/A	N/A

OTHER PUBLICATIONS

Non-Final Office Action mailed on Feb. 2, 2022, in U.S. Appl. No. 17/232,073, 11 pages. cited by applicant

Final Office Action mailed on Aug. 4, 2022, in U.S. Appl. No. 17/232,073, 12 pages. cited by applicant

Non-Final Office Action mailed on Dec. 5, 2022, in U.S. Appl. No. 17/232,073, 11 pages. cited by applicant

Notice of Allowance mailed on Apr. 4, 2022, in U.S. Appl. No. 17/233,248, 8 pages. cited by applicant

Primary Examiner: Ali; Syed

Attorney, Agent or Firm: Foley IP Law, PLLC

Background/Summary

BACKGROUND

(1) A proxy-call session control function (P-CSCF) is a session initiation protocol (SIP) proxy that is the first point of contact for a user equipment (UE) in a mobile network. SIP traffic to and from a UE passes through a P-CSCF and an internet protocol (IP) multimedia subsystem (IMS). For example, in order to make a voice or video call, a UE sends a SIP message (e.g., a SIP invite) to a P-CSCF, which forwards it to the IMS, in order to reach the called party. Different types of IMS traffic, such as fifth generation (5G) cellular, fourth generation (4G) cellular, short message service (SMS), WiFi, in-vehicle local area network (LAN), and rich communication services (RCS), currently exist and must be supported by all P-CSCFs. When a P-CSCF ceases operation (e.g., due to being overloaded, maintenance, or some other reason) large numbers of users (e.g., humans with a UE, internet of things (IoT) devices, or others) lose service.

SUMMARY

(2) The following summary is provided to illustrate examples disclosed herein, but is not meant to limit all examples to any particular configuration or sequence of operations.

(3) Solutions for service aware proxy-call session control function (P-CSCF) traffic routing include: receiving, at a master P-CSCF in a pool of a plurality of P-CSCFs, internet protocol (IP) multimedia subsystem (IMS) traffic from a device; determining, by the master P-CSCF, a traffic type (e.g., 5G, 4G, SMS, WiFi, etc.) of the IMS traffic from the device; based on at least the traffic type of the IMS traffic from the device, selecting, by the master P-CSCF, a serving P-CSCF from the pool for the device; and forwarding, by the serving P-CSCF for the device, the IMS traffic from the device to an IMS. In some examples, the serving P-CSCF selection also includes loading considerations. In some examples, an alternate P-CSCF is available for failover as the new master P-CSCF. In some examples, a network includes multiple pools of P-CSCFs, with each pool having its own master P-CSCF and alternate P-CSCF. In some examples, the traffic type may be: fifth generation (5G) cellular, fourth generation (4G) cellular, short message service (SMS), WiFi, in-

vehicle local area network (LAN), rich communication services (RCS), or another cellular generation.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The disclosed examples are described below with reference to the accompanying drawing figures listed below, wherein:
- (2) FIG. 1 illustrates an exemplary arrangement that advantageously enables service aware proxy-call session control function (P-CSCF) traffic routing;
- (3) FIG. 2 illustrates an alternative configuration that also advantageously enables service aware P-CSCF traffic routing;
- (4) FIG. 3 illustrates a generic architecture that incorporates features of the arrangements of FIG. 1 and/or FIG. 2;
- (5) FIG. 4 illustrates a flowchart of exemplary operations that may be associated with examples of the arrangement of FIG. 3;
- (6) FIG. 5 illustrates another flowchart of exemplary operations that may be associated with examples of the arrangement of FIG. 3; and
- (7) FIG. 6 illustrates a block diagram of a computing device suitable for implementing various aspects of the disclosure.
- (8) Corresponding reference characters indicate corresponding parts throughout the drawings. References made throughout this disclosure relating to specific examples, are provided for illustrative purposes, and are not meant to limit all implementations or to be interpreted as excluding the existence of additional implementations that also incorporate the recited features.

DETAILED DESCRIPTION

- (9) Solutions for service aware proxy-call session control function (P-CSCF) traffic routing include: receiving, at a master P-CSCF in a pool of a plurality of P-CSCFs, internet protocol (IP) multimedia subsystem (IMS) traffic from a device (e.g., a user equipment (UE) or another device); determining, by the master P-CSCF, a traffic type of the IMS traffic from the device; based on at least the traffic type of the IMS traffic from the device, selecting, by the master P-CSCF, a serving P-CSCF from the pool for the device; and forwarding, by the serving P-CSCF for the device, the IMS traffic from the device to an IMS. In some examples, the serving P-CSCF selection also includes loading considerations. In some examples, an alternate P-CSCF is available for failover as the new master P-CSCF. In some examples, a network includes multiple pools of P-CSCFs, with each pool having its own master P-CSCF and alternate P-CSCF. In some examples, the traffic type may be: fifth generation (5G) cellular, fourth generation (4G) cellular, short message service (SMS), WiFi, in-vehicle local area network (LAN) such as in-flight wireless, rich communication services (RCS), or another cellular generation such as third generation (3G) or (when it arrives) sixth generation (6G).
- (10) Aspects of the disclosure simplify and improve the operation of computer networks by permitting consolidation of traffic type on different P-CSCFs (e.g., providing a network slicing functionality), thereby relaxing the requirement that every P-CSCF support every type of traffic. Not only may this reduce the cost of provisioning P-CSCFs, but also, in some scenarios, a P-CSCF may exhibit superior performance by handling only limited traffic types. These advantages are enabled by a master P-CSCF selecting a serving P-CSCF for a device, based on at least the traffic type of the IMS traffic from the device. The master P-CSCF serves as a traffic sorter and load balancer for P-CSCFs in a pool (e.g., a region). The master P-CSCF distributes traffic to other P-CSCFs on the basis of their services and provides load balancing properties, fault/outage detection, distributed denial of service (DDOS) response, network robustness and resilience.

(11) For example, a common core network may have six to ten pools of approximately a dozen or more P-CSCFs each. In a pool, two may cater to 5G traffic; four may cater to 4G traffic; one each may cater to SMS, RCS traffic, or in-flight wireless, or serve integration access; and two may handle any traffic type, as necessary. Two P-CSCFs will perform additional duties, one as the master P-CSCF, to act as an initial traffic entry point and steer traffic to one of the P-CSCFs in the pool (based on type and/or for load balancing), and one as an alternate master. As traffic types change (e.g., users migrating from 4G to 5G, the balance of P-CSCFs dedicated to 5G and 4G traffic may change. As 6G is rolled out, further significant advantageous savings may be realized by reducing the number of P-CSCFs (if 6G uses P-CSCFs) that must be compatible with 6G, immediately upon 6G availability.

(12) FIG. 1 illustrates an exemplary arrangement **100** that advantageously enables service aware P-CSCF traffic routing, for example when establishing a data traffic session **106** for a device **102** on a network **110**. Data traffic sessions include voice and video calls between UEs and streaming video. In some examples, device **102** comprises a UE, and data traffic session **106** comprises a voice or video call with another UE **104**. In some examples, device **102** streams video over data traffic session **106** from a remote resource **108**. In some examples, device **102** comprises an internet of things (IoT) device, such as a connected appliance, a smart home security system, an autonomous factory or farming machine, a wearable health monitor, a wireless inventory tracker, or another device, which uploads or downloads data from remote resource **108** using data traffic session **106**. Device **102** sets up data traffic session **106** using session initiation protocol (SIP) signaling **116**, such as a SIP invite. SIP signaling **116** and data traffic session **106** are each IMS traffic, because they pass through IMS **150**.

(13) Data traffic session **106** passes from device **102**, over an air interface **114**, through a radio access network (RAN) **112**, a packet routing node **124**, a selected one of a plurality of P-CSCFs **142a-142d** (in a P-CSCF pool **140a**), and an IMS Access Media Gateway (IMS-AGW) **152** in an IMS **150**. P-CSCF pool **140a** comprises a pool of a plurality of P-CSCFs. Although only a single packet routing node **124** is shown, it should be understood that network **110** may have multiple packet routing nodes. In some examples, device **102** is assigned to packet routing node **124** via a session management node **120**, and device **102** communicates with session management node **120** via an access node **122**.

(14) Arrangement **100** is shown as 5G cellular, in which packet routing node **124** comprises a user plane function (UPF), session management node **120** comprises a session management function (SMF), and access node **122** comprises an access and mobility management function (AMF). FIG. 2 illustrates an alternative 4G cellular configuration **200**, in which access node **122** comprises a mobility management entity (MME), session management node **120** comprises a system architecture (SAE) evolution gateway—control plane (SAEGW-C), and packet routing node **124** comprises an SAE evolution gateway—user plane (SAEGW-U). An SAEGW-C is the combination of a serving gateway (SGW)—control plane (SGW-C) and a packet data network gateway (PGW)—control plane (PGW-C). An SAEGW-U is the combination of an SGW—user plane (SGW-U) and a PGW—user plane (PGW-U). The functional aspects of arrangement **200** are similar to those of arrangement **100**, with respect to the operation of P-CSCF pool **140a**.

(15) FIG. 3 illustrates an arrangement **300** that incorporates features of the arrangements of FIG. 1 and/or FIG. 2. The various 5G and/or 4G components of network **110** (of FIGS. 1 and 2) are represented as an IP connectivity access network (IP-CAN) **312** within a common core network **310**. Thus, device **102** communicates with an IMS **150** via air interface **114**, IP-CAN **312**, and P-CSCF pool **140a**. A second device **322** communicates with an IMS **150** via air interface **314**, IP-CAN **312**, and a P-CSCF pool **140b**. As indicated, common core network **310** comprises a plurality of P-CSCF pools: P-CSCF pool **140a**, P-CSCF pool **140b**, and a P-CSCF pool **140c**. In some examples, P-CSCF pools **140a-140c** are defined, at least in part, by geographical regions (e.g. devices **102** and **322** use different P-CSCF pools because they are in different geographical

regions). Each of P-CSCF pools **140a-140c** comprises a plurality of P-CSCFs.

(16) For example, as already indicates in FIGS. **1** and **2**, P-CSCF pool **140a** comprises P-CSCF **142a**, P-CSCF **142b**, P-CSCF **142c**, and P-CSCF **142d**. P-CSCF **142a** performs as a master node for P-CSCF pool **140a**, and P-CSCF **142b** is an alternate master node in the event of a failover (e.g., if P-CSCF **142a** is not functioning as a master node because it has ceased operation or has another problem). P-CSCF pool **140b** is similarly structured, and comprises a P-CSCF **142e**, a P-CSCF **142f**, a P-CSCF **142g**, and a P-CSCF **142h**. P-CSCF **142e** performs as a master node for P-CSCF pool **140b**, and P-CSCF **142f** is an alternate master node in the event of a failover (e.g., if P-CSCF **142e** is not functioning as a master node because it has ceased operation or has another problem). P-CSCF pool **140c** is also similarly configured.

(17) P-CSCF **142a** has a P-CSCF list **302** that identifies P-CSCFs within P-CSCF pool **140a**, and their ability to handle IMS traffic, such as traffic loading and status (functioning or out of service). For example, P-CSCF identification (ID) **304a** indicates loading and status for P-CSCF **142a**, P-CSCF ID **304b** indicates loading and status for P-CSCF **142b**, P-CSCF ID **304c** indicates loading and status for P-CSCF **142c**, and P-CSCF ID **304d** indicates loading and status for P-CSCF **142d**. A selection logic **306** selects a serving P-CSCF (e.g., one of P-CSCFs **142a-142d**) for device **102** based on at least the traffic type and using loading and status information in P-CSCF list **302**.

(18) P-CSCF **142a** is also shown as including a failover control **308**, although failover control **308** may be located within IP-CAN **312** (e.g., within session management node **120**), within P-CSCF **142b**, and/or within another node within P-CSCF pool **140a**. In the event that P-CSCF **142a** is unable to function properly as the master node for P-CSCF pool **140a**, failover control **308** performs a failover to P-CSCF **142b** so that P-CSCF **142b** functions as the master node for P-CSCF pool **140a**. P-CSCF **142e** and the master P-CSCF for P-CSCF pool **140c** are configured similarly P-CSCF **142a**, and P-CSCF pools **140b** and **140c** have similar failover capability. The operations of arrangement **300** with respect to service aware P-CSCF traffic routing are described in relation to FIG. **4**.

(19) FIG. **4** illustrates a flowchart **400** of exemplary operations that may be associated with examples of arrangement **300** (and thus, by extension, also arrangements **100** and **200**). That is, flowchart **400** identifies exemplary operations associated with service aware P-CSCF traffic routing. In some examples, at least a portion of flowchart **400** may each be performed using one or more computing devices **600** of FIG. **6**. A decision operation **402** determines whether (initially-designated) master P-CSCF **142a** in P-CSCF pool **140a** (e.g., a pool of a plurality of P-CSCFs) is functioning as a master node for P-CSCF pool **140a**. If it is not, then operation **404** includes, based on at least determining that P-CSCF **142a** is not functioning as the master node for P-CSCF pool **140a**, performing a failover to P-CSCF **142b** (the alternate master P-CSCF) in P-CSCF pool **140a**. For the remainder of flowchart **400** (until P-CSCF **142a** is restored as the master node, alternate master P-CSCF **142b** functions as the master node for P-CSCF pool **140a**.

(20) Operation **406** includes receiving, at P-CSCF **142a** (if P-CSCF **142a** is performing as the master P-CSCF, or P-CSCF **142b**, if P-CSCF **142b** is performing as the master P-CSCF), IMS traffic from device **102**. In some examples, device **102** comprises a cellular UE mobile device or an IoT device. In some examples, the IMS traffic comprises a session SIP invite. Operation **408** includes determining, by master P-CSCF **142a**, a traffic type of the IMS traffic from device **102**. In some examples, the traffic type is selected from a list consisting of: 5G cellular, 4G cellular, SMS, WiFi, in-vehicle LAN (e.g., in-flight WiFi), RCS, and another cellular generation.

(21) Decision operation **410** includes determining, by master P-CSCF **142a**, whether a P-CSCF that is a candidate for being the serving P-CSCF for device **102** is able to handle traffic for device **102**. In some examples, determining whether a P-CSCF is able to handle traffic for a device includes both determining whether the P-CSCF is properly functioning (e.g., is not down), and also determining whether the P-CSCF is overloaded (e.g., determining load balancing of a particular P-CSCF relative to other available P-CSCFs). If a P-CSCF is overloaded or down, it is not selected as

the serving P-CSCF, for example by identifying it as not suitable at **412**, so that another P-CSCF will instead be considered for selection in decision operation **410**.

(22) When a suitable P-CSCF is located, operation **414** includes, based on at least the traffic type of the IMS traffic from device **102**, selecting, by master P-CSCF **142a**, a serving P-CSCF for device **102**. In some example, load balancing is also a selection criteria, and selecting the serving P-CSCF for device **102** comprises: selecting the serving P-CSCF for device **102** based on at least the traffic type of the IMS traffic from device **102** and based on at least determining that the serving P-CSCF for device **102** is able to handle traffic for device **102**. For example, master P-CSCF **142a** may select itself or P-CSCF **142c**. However, if P-CSCF **142a** may select itself or P-CSCF **142c** are heavily loaded, and P-CSCF **142a** handles a different traffic type (e.g., 4G versus 5G), P-CSCF **142a** may instead select P-CSCF **142d**.

(23) Operation **416** includes forwarding, by the serving P-CSCF for device **102**, the IMS traffic from device **102** to IMS **150**. In some examples, IMS **150** comprises IMS-AGW **152**. Flowchart **400** returns to decision operation **402** to determine whether a master node failover is needed.

(24) Additional implementations of flowchart **400** operating in parallel for P-CSCF pools **140b** and **140c**. In a parallel version of flowchart **400** for P-CSCF pool **140b**, for example, operation **406** includes receiving, at P-CSCF **142e** (a second master P-CSCF) in P-CSCF pool **140b** (a second pool of a plurality of P-CSCFs), IMS traffic from device **322**, wherein P-CSCF pool **140a** and P-CSCFs pool **140b** reside within common core network **310**. Operation **408** in the parallel flowchart **400** includes determining, by P-CSCF **142e**, a traffic type of the IMS traffic from device **322**. Operation **414** in the parallel flowchart **400** includes, based on at least the traffic type of the IMS traffic from device **322**, selecting, by P-CSCF **142e**, a serving P-CSCF for device **322**. Operation **416** in the parallel flowchart **400** includes forwarding, by the serving P-CSCF for device **322**, the IMS traffic from device **322** to IMS **150**.

(25) FIG. 5 illustrates a flowchart **500** of exemplary operations associated with service aware P-CSCF traffic routing. In some examples, at least a portion of flowchart **500** may be performed using one or more computing devices **600** of FIG. 6. Operation **502** includes receiving, at a first master P-CSCF in a first pool of a plurality of P-CSCFs, IMS traffic from a first device. Operation **504** includes determining, by the first master P-CSCF, a traffic type of the IMS traffic from the first device. Operation **506** includes based on at least the traffic type of the IMS traffic from the first device, selecting, by the first master P-CSCF, a serving P-CSCF from the first pool for the first device. Operation **508** includes forwarding, by the serving P-CSCF for the first device, the IMS traffic from the first device to an IMS.

(26) FIG. 6 illustrates a block diagram of computing device **600** that may be used as a component of arrangement **100**, for example, as any component described herein that may require computational or storage capacity. Computing device **600** has at least a processor **602** and a memory **604** that holds program code **610**, data area **620**, and other logic and storage **630**. Memory **604** is any device allowing information, such as computer executable instructions and/or other data, to be stored and retrieved. For example, memory **604** may include one or more random access memory (RAM) modules, flash memory modules, hard disks, solid-state disks, persistent memory devices, and/or optical disks. Program code **610** comprises computer executable instructions and computer executable components including any instructions necessary to perform operations described herein. Data area **620** holds any data necessary to perform operations described herein. Memory **604** also includes other logic and storage **630** that performs or facilitates other functions disclosed herein or otherwise required of computing device **600**. An input/output (I/O) component **640** facilitates receiving input from users and other devices and generating displays for users and outputs for other devices. A network interface **650** permits communication over a network **660** with a remote node **670**, which may represent another implementation of computing device **600**.

Additional Examples

(27) An example method of service aware P-CSCF traffic routing comprises: receiving, at a first

master P-CSCF in a first pool of a plurality of P-CSCFs, IMS traffic from a first device; determining, by the first master P-CSCF, a traffic type of the IMS traffic from the first device; based on at least the traffic type of the IMS traffic from the first device, selecting, by the first master P-CSCF, a serving P-CSCF from the first pool for the first device; and forwarding, by the serving P-CSCF for the first device, the IMS traffic from the first device to an IMS.

(28) An example system for service aware P-CSCF traffic routing comprises: a processor; and a computer-readable medium storing instructions that are operative upon execution by the processor to: receive, at a first master P-CSCF in a first pool of a plurality of P-CSCFs, IMS traffic from a first device; determine, by the first master P-CSCF, a traffic type of the IMS traffic from the first device: based on at least the traffic type of the IMS traffic from the first device, select, by the first master P-CSCF, a serving P-CSCF from the first pool for the first device; and forward, by the serving P-CSCF for the first device, the IMS traffic from the first device to an IMS.

(29) One or more example computer storage devices has computer-executable instructions stored thereon, which, upon execution by a computer, cause the computer to perform operations comprising: receiving, at a first master P-CSCF in a first pool of a plurality of P-CSCFs, IMS traffic from a first device; determining, by the first master P-CSCF, a traffic type of the IMS traffic from the first device; based on at least the traffic type of the IMS traffic from the first device, selecting, by the first master P-CSCF, a serving P-CSCF from the first pool for the first device; and forwarding, by the serving P-CSCF for the first device, the IMS traffic from the first device to an IMS.

(30) Alternatively, or in addition to the other examples described herein, examples include any combination of the following: determining, by the first master P-CSCF, whether the serving P-CSCF for the first device is able to handle traffic for the first device, wherein selecting the serving P-CSCF for the first device comprises: selecting the serving P-CSCF for the first device based on at least the traffic type of the IMS traffic from the first device and based on at least determining that the serving P-CSCF for the first device is able to handle traffic for the first device; determining whether a P-CSCF is able to handle traffic for a device includes both determining whether the P-CSCF is properly functioning, and also determining whether the P-CSCF is overloaded; determining whether the first master P-CSCF in the first pool of a plurality of P-CSCFs is functioning as a master node for the first pool of a plurality of P-CSCFs; based on at least determining that the first master P-CSCF in the first pool of a plurality of P-CSCFs is not functioning as the master node for the first pool of a plurality of P-CSCFs, performing a failover to an alternate master P-CSCF in the first pool of a plurality of P-CSCFs; functioning, by the alternate master P-CSCF, as the master node for the first pool of a plurality of P-CSCFs; receiving, at a second master P-CSCF in a second pool of a plurality of P-CSCFs, IMS traffic from a second device, wherein the first pool of a plurality of P-CSCFs and the second pool of a plurality of P-CSCFs reside within a common core network; determining, by the second master P-CSCF, a traffic type of the IMS traffic from the second device; based on at least the traffic type of the IMS traffic from the second device, selecting, by the second master P-CSCF, a serving P-CSCF from the second pool for the second device; forwarding, by the serving P-CSCF for the second device, the IMS traffic from the second device to the IMS; the traffic type is selected from a list consisting of: 5G cellular, 4G cellular, SMS, WiFi, in-vehicle LAN, RCS, and another cellular generation; the first device comprises a cellular UE mobile device or an IoT device; the IMS comprises an IMS-AGW; and the IMS traffic comprises a SIP invite.

(31) The order of execution or performance of the operations in examples of the disclosure illustrated and described herein is not essential, unless otherwise specified. That is, the operations may be performed in any order, unless otherwise specified, and examples of the disclosure may include additional or fewer operations than those disclosed herein. For example, it is contemplated that executing or performing a particular operation before, contemporaneously with, or after another operation is within the scope of aspects of the disclosure. It will be understood that the

benefits and advantages described above may relate to one embodiment or may relate to several embodiments. When introducing elements of aspects of the disclosure or the examples thereof, the articles “a,” “an,” “the,” and “said” are intended to mean that there are one or more of the elements. The terms “comprising,” “including,” and “having” are intended to be inclusive and mean that there may be additional elements other than the listed elements. The term “exemplary” is intended to mean “an example of.”

(32) Having described aspects of the disclosure in detail, it will be apparent that modifications and variations are possible without departing from the scope of aspects of the disclosure as defined in the appended claims. As various changes may be made in the above constructions, products, and methods without departing from the scope of aspects of the disclosure, it is intended that all matter contained in the above description and shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense.

Claims

1. A method of service aware proxy-call session control function (P-CSCF) traffic routing, the method comprising: receiving, at a master P-CSCF, a session initiation protocol (SIP) invite for internet protocol (IP) multimedia subsystem (IMS) traffic from a mobile device that is a fifth generation (5G) capable device; determining, by the master P-CSCF, a specific traffic type of the IMS traffic prior to serving P-CSCF assignment, the specific traffic type of the IMS traffic being identified from a list including a 5G cellular traffic type, a Short Messaging Service (SMS) traffic type, a Wi-Fi traffic type, and an in-vehicle local area network (LAN) traffic type; based on at least the specific traffic type of the IMS traffic, selecting, by the master P-CSCF, a serving P-CSCF to assign to the mobile device based at least partially on the serving P-CSCF supporting the specific traffic type of the IMS traffic; and forwarding, by the master P-CSCF, the SIP invite to the serving P-CSCF.
2. The method of claim 1, wherein the mobile device is a cellular user equipment (UE).
3. The method of claim 1, wherein the mobile device is an internet of things (IoT) device.
4. The method of claim 1, wherein the specific traffic type of the IMS traffic is the 5G cellular traffic type.
5. The method of claim 1, wherein the specific traffic type of the IMS traffic is the SMS traffic type.
6. The method of claim 1, wherein the specific traffic type of the IMS traffic is the Wi-Fi traffic type.
7. The method of claim 1, wherein the specific traffic type of the IMS traffic is the in-vehicle LAN traffic type.
8. A master proxy-call session control function (P-CSCF) comprising: a processor; and computer-readable medium storing programming instructions that, when executed by the processor, cause the processor to: receive a session initiation protocol (SIP) invite for internet protocol (IP) multimedia subsystem (IMS) traffic from a mobile device that is a fifth generation (5G) capable device; determine a specific traffic type of the IMS traffic received from the mobile device prior to serving P-CSCF assignment, the specific traffic type of the IMS traffic being identified from a list including a 5G cellular traffic type, a Short Messaging Service (SMS) traffic type, a Wi-Fi traffic type, and an in-vehicle local area network (LAN) traffic type; based on at least the specific traffic type of the IMS traffic, select a serving P-CSCF to assign to the mobile device based at least partially on the serving P-CSCF supporting the specific traffic type of the IMS traffic; and forward the SIP invite to the serving P-CSCF.
9. The master P-CSCF of claim 8, wherein the mobile device is a cellular user equipment (UE).
10. The master P-CSCF of claim 8, wherein the mobile device is an internet of things (IoT) device.
11. One or more computer storage devices storing programming instructions that, when executed

by a processor, cause the processor to: receive, at a master P-CSCF, a session initiation protocol (SIP) invite for internet protocol (IP) multimedia subsystem (IMS) traffic from a mobile device that is a fifth generation (5G) capable device; determine, by the master P-CSCF, a specific traffic type of the IMS traffic prior to serving P-CSCF assignment, the specific traffic type of the IMS traffic being identified from a list including a 5G cellular traffic type, a Short Messaging Service (SMS) traffic type, a Wi-Fi traffic type, and an in-vehicle local area network (LAN) traffic type; based on at least the specific traffic type of the IMS traffic, select, by the master P-CSCF, a serving P-CSCF to assign to the mobile device based at least partially on the serving P-CSCF supporting the specific traffic type of the IMS traffic; and forward, by the master P-CSCF, the SIP invite to the serving P-CSCF.

12. The one or more computer storage devices of claim 11, wherein the mobile device is a cellular user equipment (UE).

13. The one or more computer storage devices of claim 11, wherein the mobile device is an internet of things (IoT) device.
