

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12414277

Kind Code

B1

Date of Patent

September 09, 2025

Inventor(s)

Trumbull; Donald W.

Portable electromagnetic shielding enclosure having a compression hatch point of entry and associated method(s)

Abstract

An electromagnetic shielding enclosure includes an inner shielded housing having an open point of entry (POE) chamber. A compression hatch assembly is operably coupled to the inner shielded housing. An outer casing is situated about the inner shielded housing and is affixed to a bottom plate, and a plurality of compression pins are frictionally and removably abutted with the compression hatch assembly and the outer casing. The compression pins are configured to evenly distribute external forces against a metal flange and the compression hatch assembly within the POE chamber after the compression hatch assembly is closed and the compression pins are rotated. A stowed tool and lock affix the compression pins to the enclosure and prevent the compression pins from undesirable displacement.

Inventors: Trumbull; Donald W. (Salt Springs, FL)

Applicant: Trumbull; Donald W. (Salt Springs, FL)

Family ID: 96950510

Appl. No.: 18/431939

Filed: February 03, 2024

Related U.S. Application Data

us-provisional-application US 63483078 20230203

Publication Classification

Int. Cl.: H05K9/00 (20060101)

U.S. Cl.:

Field of Classification Search

CPC: H05K (9/0049); H05K (9/0015)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4399318	12/1982	Waters	174/359	H01R 13/6592
4831211	12/1988	McPherson	174/371	H05K 9/0049
6297969	12/2000	Mottahed	361/752	H05K 9/0045
8530756	12/2012	Winch	174/382	H05K 9/0001
11071233	12/2020	Robert	N/A	H05K 9/0049
2021/0153340	12/2020	Lee	N/A	H05K 7/20445
2023/0032158	12/2022	Ulmer	N/A	H05K 5/061
2024/0258004	12/2023	Yoshida	N/A	H05K 9/0049

Primary Examiner: Ngo; Hung V

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This is a non-provisional patent application that claims priority to and benefit of U.S. provisional patent application No. 63/483,078 filed Feb. 3, 2023, which is incorporated by reference herein in its entirety.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

(1) Not Applicable.

REFERENCE TO A MICROFICHE APPENDIX

(2) Not Applicable.

BACKGROUND

Technical Field

(3) Exemplary embodiment(s) of the present disclosure relate to faraday cages and, more particularly, to a specially configured electromagnetic shielding enclosure having a high shielding effectiveness (SE) value and being provided with a removable compression hatch assembly, having an electromagnetically insulated (EMI) gasket, located at a point of entry (POE) of an inner housing of the enclosure.

Prior Art

(4) As the proliferation and risk of electromagnetic pulse/high altitude electromagnetic pulse/intentional electromagnetic interference (EMP/HEMP/IEMI) weapons designed to compromise or destroy unshielded critical electronics and critical infrastructures continues at a rapid pace, and the proliferation of radiofrequency generating devices continues at a rapid pace, there is an ongoing and growing need to effectively shield objects from both destructive and unwanted electromagnetic radiation for various purposes. For example, certain electronics will be destroyed/rendered inoperative if exposed to high amplitude EMP/IEMP/IEMI frequencies. Additionally, certain electronic equipment requires an electromagnetically “quiet” environment to function properly. Such equipment includes, for example, some medical diagnostic and imaging

equipment. In addition, testing of electronic equipment often requires a similar electromagnetically “quiet” environment.

(5) Any point of entry (POE) of a shielding enclosure, where access to the interior is inherently required, the POE is the weak link of all Faraday cage enclosures due to the structural challenges associated with ensuring an ongoing and reliable electrically conductive seal to the other five sides when the point of entry is closed. Furthermore, when the enclosure is moved, or when the enclosure is transported within the rugged or unstable environment, this weak link associated with its POE is further challenged to maintain an ongoing and reliable electrically conductive seal to the other five sides of an enclosure while the enclosure is under stress or disturbed. In some situations, there is the need to prevent radiofrequencies from leaving a confined physical area. Such situations include, for example, the use of computer and military electronics where there is the risk of unwanted detection of a radiated radiofrequency signal or unwanted detection of the associated harmonics and signature of radiofrequency activity. In all cases, whether static or dynamic, the shielding enclosure's weak link is its POE.

(6) Further, testing such as electromagnetic compatibility/electromagnetic interference (EMC) testing requires the monitoring of electromagnetic energy released from a device under test in a controlled environment where there are little or no outside sources of electromagnetic radiation that could interfere with the monitoring of the device under test. Such testing may also include subjecting a device under test to external electromagnetic energy and monitoring the impact of this external electromagnetic energy on the proper functioning of the device under test.

(7) With the advent of metallized fabrics and textiles, including solid aluminum metal, lightweight shielded tents and other portable enclosures are readily available today. However, while these enclosures are essentially a Faraday Cage where electromagnetic signals should not pass, many of these lightweight materials used to construct shielding enclosures, such as metalized fabrics and textiles, including solid aluminum, and due to their low permeability and low-confidence POE design limitations, fail to shield the interior and reduce the attenuation in decibels (dB) in both the electric and magnetic fields to a survivable level with respect to EMP/IEMP/IEMI. In addition to the deficient POE design limitations and lesser shielding effectiveness of these lightweight materials, both lightweight materials and higher shielding effectiveness materials such as solid steel and copper with higher permeability, when fragile or inferior point of entry (POE) designs are incorporated into the shielding enclosure, the risk of an ongoing failure to maintain a reliable RF (radiofrequency) tight seal at the seams surrounding the point of entry (POE) perimeter exists when the enclosure is subjected to any movement.

(8) Such enclosures come in many shapes and sizes and are available from various manufacturers. While such enclosures are available, the shielding effectiveness of metalized fabric and textiles, including solid aluminum, solid steel, and solid copper, are all subject to insufficient shielding effectiveness when defending threats from high-amplitude EMP/HEMP/IEMI in the unstable environment. Without a point of entry (POE) capable of maintaining continual perimeter compression in the unstable environment, radiofrequency leakage at enclosure seams and/or points of entry (POE) will likely occur when the enclosure is disturbed. As such, the overall material, design, and construction of a portable electromagnetically shielded enclosure and point of entry (POE) is vital to both the performance and reliability of the shielded enclosure. For EMP/HEMP, the U.S Army Corps of Engineers recommends solid steel with a general thickness of ¼" for enclosures. For points of entry (POE), multiple bolt fasteners spaced closely together, or other methods which compress the POE at its perimeter and maintain continual perimeter continuity is required. For unstable environments where the enclosure is subjected to movement and/or vibration, a suitable POE design is intrinsically required.

(9) In addition, larger enclosures, such as those with man-size doors and larger POE's often use an exterior compression apparatus which incorporates a high cost, high weight, electrically driven, air bladder or pneumatic mechanisms to compress the entire circumference of a POE against a door

flange and EMI gasket. Some large door POE's will use a mechanical compression system using latches that are only usable in the static/upright/stable environment. This large door compression method is only suitable for fixed/non-portable enclosures in the static environment due to the limiting mechanical design, high weight, and associated exterior power source (electricity, pneumatics, hydraulic, air bladder, etc.).

(10) Conventional shielding devices of the portable size have been bound to a lesser shielding effectiveness integrity due to the use of fasteners and/or clamps to compress a POE against a flange at specific clamping points around the circumference of POE. Fasteners (screws/bolts) and clamps that are used to achieve the same maximum shielding effectiveness of larger, more complex POE compression mechanisms must be equally and closely spaced (1-2 inches apart). If the POE fasteners/clamps are not consistently torqued accurately, or if the spacing of fasteners/clamps is deficient, uneven compression of the POE will degrade shielding effectiveness significantly. Additionally, those POE designs using multiple fasteners and/or clamps are bound to the static environment where movement and/or vibration may degrade clamping force and nullify the shielding effectiveness of enclosure. These competing devices require fasteners/clamps at closely spaced intervals around the circumference of the POE, also require peripheral tools, trained personnel, and/or cumbersome procedures to open/close the POE.

(11) As noted above, such large man-sized door POE and those made for certain large-scale civilian/military HEMP installations exist, wherein the POE seal is equally compressed around its circumference via electric, pneumatic, air bladder, hydraulic, or other systems. However, such conventional POE compression devices have high costs and are highly complex. While they have been widely used in the larger fixed-base/non-portable enclosure market, these large scale devices are unusable in the small, portable enclosure market due to weight, size, complexity, and cost.

(12) With the various requirements for electromagnetically shielded enclosures, and more particularly, with respect to defending against the destructive threats of EMP/IEMP/IEMI, there exists a need to make these enclosures portable, low cost, rugged, rapidly deployable within a stable and unstable environment, constructed out of solid metal with magnetic properties such as steel or copper, and designed with a high confidence point of entry (POE) system that achieves sufficient, ongoing, and reliable shielding effectiveness (SE) capable of attenuating the destructive frequencies associated with EMP/IHEMP/IEMI to a survivable level within the unstable environment.

(13) Accordingly, a need remains for a specially configured portable electromagnetic shielding enclosure to overcome at least one of the above-noted shortcomings. The exemplary embodiment(s) satisfy such a need by a specially configured portable, steel, electromagnetic shielding enclosure that is convenient and easy to use, lightweight yet durable in design, versatile in its applications, and structurally configured to provide (1) an ergonomic, on-demand, reliable ingress/egress access of the POE in the field by untrained personnel, (2) superior continual perimeter compression of POE against its metal flange/EMI gasket in both the static and unstable environment, and (3) superior shielding effectiveness reliability to an interior of the enclosure when subjected to movement within the unstable environment and/or repeated opening/closing a compression hatch point of entry (POE) in the field.

BRIEF SUMMARY OF NON-LIMITING EXEMPLARY EMBODIMENT(S) OF THE PRESENT DISCLOSURE

(14) In view of the foregoing background, it is therefore an object of the non-limiting exemplary embodiment(s) to provide a specially configured portable or stationary, high shielding effectiveness (SE) electromagnetic shielding enclosure for providing ergonomic, on-demand, reliable ingress/egress of point of entry (POE) in the field by untrained personnel, superior continual perimeter compression of POE against its metal flange/electromagnetically insulated (EMI) gasket in both a static and an unstable environment, and superior shielding effectiveness reliability to an interior of the enclosure when subjected to movement within the unstable environment and/or

repeated opening/closing of a compression hatch point of entry (POE) in the field. These and other objects, features, and advantages of the non-limiting exemplary embodiment(s) are provided by a portable electromagnetic shielding enclosure for providing even distribution of seal forces. The portable electromagnetic shielding enclosure includes a portable inner shielded housing having an open point of entry. Such an enclosure further includes a compression hatch assembly operably coupled to the open point of entry and being configured to electromagnetically seal the open point of entry, a portable bottom plate and a portable outer casing affixed to the portable bottom plate and being configured to define a chamber configured to linearly receive the portable inner shielded housing, and a plurality of compression pins frictionally and removably abutted with the compression hatch assembly and the portable outer casing. Advantageously, the compression hatch assembly and the portable inner shielded housing are axially reciprocated, along a bi-directional travel path, into and out from the chamber. Advantageously, the compression pins are configured to evenly distribute external forces against the compression hatch assembly operably engaged with the open point of entry after the compression hatch assembly is closed and locked from its open and manually pre-compressed position.

(15) In a non-limiting exemplary embodiment, the portable inner shielded housing further includes a rear side, an axial bore, a flange disposed about the axial bore at an outer perimeter of the open point of entry, and a rear plate attached to the rear side. Advantageously, the compression hatch assembly is operably engaged with the flange and axially opposed from the rear plate.

(16) In a non-limiting exemplary embodiment, the compression hatch assembly includes a preset nut and a fastener operably coupled thereto, a front compression plate operably coupled to the preset nut, a compressible foam layer directly engaged with the front compression plate, a back stainless steel end cap (rear compression plate) directly engaged with the compressible foam layer and the fastener, and an electromagnetically insulated (EMI) gasket directly engaged with the back stainless steel end cap (rear compression plate) and the flange. Advantageously, the pre-set nut and the fastener are configured to establish a fixed, pre-harnessed compression state suitable for the compression hatch assembly to operably and electromagnetically seal the point of entry.

Advantageously, the compression hatch assembly and the portable inner shielded housing are further configured to be contemporaneously inserted into the portable outer casing.

(17) In a non-limiting exemplary embodiment, the portable electromagnetic shielding enclosure further includes a stowable tool removably engaged with the compression pins as well as the portable outer casing, and a lock detachably engaged with the stowable tool and the portable outer casing.

(18) In a non-limiting exemplary embodiment, the stowable tool and the lock are located exterior of the portable inner shielded housing and the portable outer casing.

(19) In a non-limiting exemplary embodiment, the compression pins include a plurality of generally D-shaped compression pins configured to roll and transfer opposing forces that compresses the EMI gasket against the flange along an entirety of the outer perimeter of the point of entry at the portable inner shielded housing.

(20) In a non-limiting exemplary embodiment, the portable electromagnetic shielding enclosure further includes a rotating handle operably engaged with the pre-set nut.

(21) In a non-limiting exemplary embodiment, the rotating handle is configured to be rotated in opposed rotational directions to respectively tighten and loosen the pre-set nut and further configured to enable the compression hatch assembly to be inserted into the chamber.

(22) In a non-limiting exemplary embodiment, the compression hatch assembly, the portable inner shielded housing, and the portable outer casing are coaxially aligned.

(23) There has thus been outlined, rather broadly, the more important features of non-limiting exemplary embodiment(s) of the present disclosure so that the following detailed description may be better understood, and that the present contribution to the relevant art(s) may be better appreciated. There are additional features of the non-limiting exemplary embodiment(s) of the

present disclosure that will be described hereinafter and which will form the subject matter of the claims appended hereto.

Description

BRIEF DESCRIPTION OF THE NON-LIMITING EXEMPLARY DRAWINGS

- (1) The novel features believed to be characteristic of non-limiting exemplary embodiment(s) of the present disclosure are set forth with particularity in the appended claims. The non-limiting exemplary embodiment(s) of the present disclosure itself, however, both as to its organization and method of operation, together with further objects and advantages thereof, may best be understood by reference to the following description taken in connection with the accompanying drawings in which:
- (2) FIG. 1 is a perspective view of an electromagnetic shielding enclosure having a compression hatch point of entry employing rotating generally D-shaped compression pins, in accordance with a non-limiting exemplary embodiment of the present disclosure;
- (3) FIG. 2 is a front elevational view of the electromagnetic shielding enclosure shown in FIG. 1;
- (4) FIG. 3 is a rear elevational view of the electromagnetic shielding enclosure shown in FIG. 1;
- (5) FIG. 4 is a perspective view of the electromagnetic shielding enclosure shown in FIG. 1 wherein the stowable tool is removed from the stowed position;
- (6) FIG. 5 is a perspective view of the electromagnetic shielding enclosure shown in FIG. 1 wherein the stowable tool is operably and rotatably engaged with the unlocked generally D-shaped compression pin;
- (7) FIG. 6 is a perspective view of the electromagnetic shielding enclosure shown in FIG. 1 wherein the stowable tool operably and rotatably locks the generally D-shaped compression pin;
- (8) FIG. 7 is a perspective view of the electromagnetic shielding enclosure shown in FIG. 1 wherein the stowable tool is removed from the locked generally D-shaped compression pin;
- (9) FIG. 8 is an enlarged perspective view of the stowable tool shown in FIG. 1;
- (10) FIG. 9 is an enlarged top plan view showing a planar (flat) side of a generally D-shaped compression pin shown in FIG. 1;
- (11) FIG. 10 is a perspective view showing a curvilinear (arcuate) side of the generally D-shaped compression pin shown in FIG. 9;
- (12) FIG. 11 is a perspective view showing a planar (flat) side of the generally D-shaped compression pin shown in FIG. 9;
- (13) FIG. 12 is a top plan view of the electromagnetic shielding enclosure shown in FIG. 1;
- (14) FIG. 13 is a left side elevational view of the electromagnetic shielding enclosure shown in FIG. 1;
- (15) FIG. 13A is a cross-sectional view taken along line 13A-13A in FIG. 13;
- (16) FIG. 14 is a right side elevational view of the electromagnetic shielding enclosure shown in FIG. 1;
- (17) FIG. 14A is a cross-sectional view taken along line 14A-14A in FIG. 14;
- (18) FIG. 15 is a partially exploded view of the electromagnetic shielding enclosure shown in FIG. 1 wherein the stowable tool and lock are removed from the enclosure;
- (19) FIG. 16 is another partially exploded view of the electromagnetic shielding enclosure shown in FIG. 1 wherein the stowable tool, lock, and generally D-shaped compression pins are removed from the enclosure;
- (20) FIG. 17 is another partially exploded view of the electromagnetic shielding enclosure shown in FIG. 1 wherein the stowable tool, lock, generally D-shaped compression pins, compression hatch assembly, and shielded inner housing are removed from the outer casing;
- (21) FIG. 18 is fully exploded view of the electromagnetic shielding enclosure shown in FIG. 1;

(22) FIG. 19 is an exploded view of another electromagnetic shielding enclosure having a compression hatch point of entry employing a rotating compression wheel, in accordance with another non-limiting exemplary embodiment of the present disclosure; and

(23) FIG. 20 is a graph illustrating test results from the Boeing Little Mountain Test Facility (LMTF) showing the shielding effectiveness (SE) of the electromagnetic shielding enclosure's POE shown in FIGS. 1-18. This test result confirms the shielding enclosure's POE exceeds the SE standards of MIL-STD-188-125-1.

(24) Those skilled in the art will appreciate that the figures are not intended to be drawn to any particular scale; nor are the figures intended to illustrate every non-limiting exemplary embodiment(s) of the present disclosure. The present disclosure is not limited to any particular non-limiting exemplary embodiment(s) depicted in the figures nor the shapes, relative sizes or proportions shown in the figures.

DETAILED DESCRIPTION OF NON-LIMITING EXEMPLARY EMBODIMENT(S) OF THE PRESENT DISCLOSURE

(25) The present disclosure will now be described more fully hereinafter with reference to the accompanying drawings, in which non-limiting exemplary embodiment(s) of the present disclosure is shown. The present disclosure may, however, be embodied in many different forms and should not be construed as limited to the non-limiting exemplary embodiment(s) set forth herein. Rather, such non-limiting exemplary embodiment(s) are provided so that this application will be thorough and complete and will fully convey the true spirit and scope of the present disclosure to those skilled in the relevant art(s). Like numbers refer to like elements throughout the figures.

(26) The illustrations of the non-limiting exemplary embodiment(s) described herein are intended to provide a general understanding of the structure of the present disclosure. The illustrations are not intended to serve as a complete description of all of the elements and features of the structures, systems and/or methods described herein. Other non-limiting exemplary embodiment(s) may be apparent to those of ordinary skill in the relevant art(s) upon reviewing the disclosure. Other non-limiting exemplary embodiment(s) may be utilized and derived from the disclosure such that structural, logical substitutions and changes may be made without departing from the true spirit and scope of the present disclosure. Additionally, the illustrations are merely representational and are to be regarded as illustrative rather than restrictive.

(27) One or more embodiment(s) of the disclosure may be referred to herein, individually and/or collectively, by the term “non-limiting exemplary embodiment(s)” merely for convenience and without intending to voluntarily limit the true spirit and scope of this application to any particular non-limiting exemplary embodiment(s) or inventive concept. Moreover, although specific embodiment(s) have been illustrated and described herein, it should be appreciated that any subsequent arrangement designed to achieve the same or similar purpose may be substituted for the specific embodiment(s) shown. This disclosure is intended to cover all subsequent adaptations or variations of other embodiment(s). Combinations of the above embodiment(s), and other embodiment(s) not specifically described herein, will be apparent to those of skill in the relevant art(s) upon reviewing the description.

(28) References in the specification to “one embodiment(s)”, “an embodiment(s)”, “a preferred embodiment(s)”, “an alternative embodiment(s)” and similar phrases mean that a particular feature, structure, or characteristic described in connection with the embodiment(s) is included in at least an embodiment(s) of the non-limiting exemplary embodiment(s). The appearances of the phrase “non-limiting exemplary embodiment” in various places in the specification are not necessarily all meant to refer to the same embodiment(s).

(29) Directional and/or relationary terms such as, but not limited to, left, right, nadir, apex, top, bottom, vertical, horizontal, back, front and lateral are relative to each other and are dependent on the specific orientation of an applicable element or article, and are used accordingly to aid in the description of the various embodiment(s) and are not necessarily intended to be construed as

limiting.

(30) If used herein, “about,” “generally,” and “approximately” mean nearly and in the context of a numerical value or range set forth means $\pm 15\%$ of the numerical.

(31) If used herein, “substantially” means largely if not wholly that which is specified but so close that the difference is insignificant.

(32) The term “generally D-shaped compression pin” means a compression pin having a generally D-shaped cross-section having a flat (planar) side and a curvilinear (arcuate) side opposed therefrom.

(33) The non-limiting exemplary embodiment(s) is/are referred to generally in FIGS. **1-20** and is/are intended to a non-limiting exemplary embodiment(s) of the present disclosure is referred to generally in the figures and is intended to provide a specially configured portable electromagnetic shielding enclosure **20**, made of steel, meeting or exceeding minimum standards outlined in U.S. military's high-altitude electromagnetic pulse (HEMP) protection for ground-based facilities performing critical, time-urgent missions (MIL-STD-188-125), and providing ergonomic, on-demand, reliable ingress/egress access of POE **23** in the field by untrained personnel, superior continual perimeter compression of POE **23** against its metal flange **32**/EMI gasket **40** in both the static and unstable environment, and superior shielding effectiveness reliability to an interior of the enclosure **20** when subjected to movement within an unstable environment and/or repeated opening/closing a compression hatch point of entry **23** (POE) in the field. It should be understood that the exemplary embodiment(s) may be used to shield a variety of electromagnetic signals and should not be limited to any particular electromagnetic signal having a specific wavelength described herein. The present disclosure may be commercially marketed by the trademark FARASAFE.TM.TM, or another trademark.

(34) Referring to FIGS. **1-20** in general, a specially configured portable or stationary electromagnetic shielding enclosure **20** for providing high shielding effectiveness (SE), ergonomic, on-demand, reliable ingress/egress of point of entry **23** (POE) in the field by untrained personnel, superior continual perimeter compression of POE **23** against its metal flange **32**/EMI gasket **40** in both the static and unstable environment, and superior shielding effectiveness reliability to an interior of the enclosure **20** when subjected to movement within an unstable environment and/or repeated opening/closing of a compression hatch point of entry **23** (POE) in the field.

Advantageously, the compression pins **27** are configured to evenly distribute external forces against the metal flange **32**/EMI gasket **40** within the point of entry **23** (POE) chamber **26** after the compression hatch assembly **24** is closed and second independent compression mechanism is activated (via the handwheel or rotating of the generally D-shaped compression pins **27**), and whereby the opposing forces are transferred within the POE **23** chamber **26** from its open, pre-compressed position **45** obtained via the first independent compression mechanism established by handwheel or pre-set nut **35**.

(35) The portable electromagnetic shielding enclosure **20** provides even distribution of seal forces. Such a portable electromagnetic shielding enclosure **20** includes and a portable inner shielded housing **22** having an open point of entry **23**. Such an enclosure **20** further includes a compression hatch assembly **24** operably coupled to the open point of entry **23** and being configured to electromagnetically seal the open point of entry **23**, a portable bottom plate **21** and a portable outer casing **25** affixed to the portable bottom plate **21** and being configured to define a chamber **26** configured to linearly receive the portable inner shielded housing **22**, and a plurality of compression pins **27** frictionally and removably abutted with the compression hatch assembly **24** and the portable outer casing **25**. Advantageously, the compression hatch assembly **24** and the portable inner shielded housing **22** are axially reciprocated, along a bi-directional travel path **28**, into and out from the chamber **26**. Advantageously, the compression pins **27** are configured to evenly distribute external forces against the compression hatch assembly **24** operably engaged with the open point of entry **23** after the compression hatch assembly **24** is closed and locked from its

open and manually pre-compressed position **45**.

(36) In a non-limiting exemplary embodiment, the portable inner shielded housing **22** further includes a rear side **30**, an axial bore **31**, a flange **32** disposed about the axial bore **31** at an outer perimeter **33** of the open point of entry **23**, and a rear plate **34** attached to the rear side **30**. Advantageously, the compression hatch assembly **24** is operably engaged with the flange **32** and axially opposed from the rear plate **34**.

(37) In a non-limiting exemplary embodiment, the compression hatch assembly **24** includes a preset nut **35** and a fastener **36** operably coupled thereto, a front compression plate **37** operably coupled to the preset nut **35**, a compressible foam layer **38** directly engaged with the front compression plate **37**, a back stainless steel end cap (rear compression plate) **39** directly engaged with the compressible foam layer **38** and the fastener **36**, and an electromagnetically insulated (EMI) gasket **40** directly engaged with the back stainless steel end cap (rear compression plate) **39** and the flange **32**. The EMI gasket **40** may be made of silicon, copper, and silver. Advantageously, the pre-set nut **35** and the fastener **36** are configured to establish a fixed, pre-harnessed compression state **45** suitable for the compression hatch assembly **24** to operably and electromagnetically seal the point of entry **23**. Advantageously, the compression hatch assembly **24** and the portable inner shielded housing **22** are further configured to be contemporaneously inserted into the portable outer casing **25**.

(38) In a non-limiting exemplary embodiment, the portable electromagnetic shielding enclosure **20** further includes a stowable tool **46** removably engaged with the compression pins **27** as well as the portable outer casing **25**, and a lock **47** detachably engaged with the stowable tool **46** and the portable outer casing **25**. A shoulder **25a** of the portable outer casing **25** has an opening **25b** for securing the tool thereto via lock **47**.

(39) In a non-limiting exemplary embodiment, the stowable tool **46** and the lock **47** are located exterior of the portable inner shielded housing **22** and the portable outer casing **25**.

(40) In a non-limiting exemplary embodiment, the compression pins **27** include a plurality of generally D-shaped compression pins **27** configured to roll and transfer opposing forces that compresses the EMI gasket **40** against the flange **32** along an entirety of the outer perimeter **33** of the point of entry **23** at the portable inner shielded housing **22**.

(41) In a non-limiting exemplary embodiment, the portable electromagnetic shielding enclosure **20** further includes a rotating handle **50** operably engaged with the pre-set nut **35**.

(42) In a non-limiting exemplary embodiment, the rotating handle **50** is configured to be rotated in opposed rotational directions to respectively tighten and loosen the pre-set nut **35** and further configured to enable the compression hatch assembly **24** to be inserted into the chamber **26**.

(43) In a non-limiting exemplary embodiment, the compression hatch assembly **24**, the portable inner shielded housing **22**, and the portable outer casing **25** are coaxially aligned.

(44) In a non-limiting exemplary embodiment, each generally D-shaped compression pin **27** has a planar (flat) side **27a** and a curvilinear (arcuate) side **27b**. When the planar (flat) side **27a** faces the compression hatch assembly **24**, the compression hatch assembly **24** is not at a final compressed state. When the curvilinear (arcuate) side **27b** faces and abuts against the compression hatch assembly **24**, the compression hatch assembly **24** is at a final compressed state. The same structural configuration is associated with pins **78** in the embodiment of FIG. **19**.

(45) Referring to FIGS. **1-20** in general, in a non-limiting exemplary embodiment(s), the electromagnetic shielding enclosure **20** includes an outer casing **25**, independent (separable) of the inner shielded enclosure **20** and used to perform an independent compression function, and a POE end cap (rear compression plate) **39** with a machined groove to receive an EMI gasket **40**, which may include aluminum and steel, respectively, or other suitable materials for preventing electromagnetic signals from passing through the end cap (rear compression plate) **39** and into the interior of the inner shielded enclosure **20**. Advantageously, a compression hatch assembly **24** is detachably affixed to the interior shield housing **22** and enables the transfer of opposing forces

between two separate and independent compression mechanisms (e.g., pre-set nut **35**/fastener **36** and generally D-shaped compression pins **27**). In particular, the compression hatch assembly **24** includes a compression foam layer **38** or compression material serving as a spring with compression force deflection (CFD) sandwiched between two steel plates **37**, **39**, which is then pre-compressed via the pre-set nut **35** and associated fastener **36** manual (with or without the handwheel **50**) for minute adjustment or set at a fixed pre-compressed position **45** with a pre-set adjustment (by tightening/loosening the pre-set nut **35**/fastener **36**) so that it can be inserted within the outer casing **25** after being loaded against the steel flange **32** that is welded to the inner steel shielded housing **22**, which is removably positioned within the outer casing **25**. When pre-compressed (with or without manual handwheel **50**) for minute adjustment of pre-set nut **35** for pre-set adjustment, the compression hatch assembly **24** can be positioned within chamber **26** created by the outer casing **25** at a specific depth just beyond a plurality of apertures **58** for receiving the associated generally D-shaped compression pins **27** (clevis pins). These generally D-shaped compression pins **27** have generally D-shaped cross-sections depending on whether manual handwheel **50** or pre-set nut **35** is used for securing depth adjustment for placement of the compression hatch assembly **24** into chamber **26** created by outer casing **25**. When these generally D-shaped compression pins **27** (stop/clevis pins) are inserted into apertures **58**, the second independent compression mechanism can then be activated by rotatably engaging tool **46** with generally D-shaped compression pins **27** so that a desired compression force is maintained at the POE **23** (or by rotatably loosening handwheel **50**). The offset and non-concentric generally D-shaped cross-section of the compression pins **27** enables the increased compression force to be maintained at the POE **23**. Advantageously, such a structural configuration yields a new, useful, and unexpected rugged, on-demand, rapidly deployable enclosure **20** with a POE **23** designed to withstand the unstable environment associated with land vehicles and other mission requirements existing in the field, and additionally, designed for repeated open/close cycles without the need for trained personnel, exterior tools, inferior fasteners, or inferior clamps.

(46) In a non-limiting exemplary embodiment, after tightening the pre-compressed hatch assembly **24** (e.g., a power tool is used to pre-tighten the pre-set nut **35** and fastener **36**), the compression force is transferred to and maintained by the generally D-shaped compression pins **27** by rotating such pins **27** in an associated rotational direction via tool **46**. Thus, the first compression mechanism includes the pre-set nut **35** and associated fastener **36**, and the second compression mechanism includes the generally D-shaped compression pins **27**, which are rotatably activated after being inserted into the apertures **58** of outer casing **25**, and subsequent release of the first compression mechanism (via a hydraulic/pneumatic tool) by way of rotatably unwinding the pre-set nut **35** and fastener **36** (with or without the handwheel **50**). Rotating (rotating) non-concentric generally D-shaped compression pins **27**, which then captures the pre-compressed compression hatch assembly **24** contained in the first compression mechanism and transfers the opposing forces between the generally D-shaped compression pins **27** and the steel flange **32** of inner shielded housing **22**.

(47) In a non-limiting exemplary embodiment, the electromagnetic shielding enclosure **20** has a portable, heavy-duty six-sided steel outer casing **25** including a compression hatch assembly **24** located at the POE **23**. The electromagnetic shielding enclosure **20** provides portable, rugged, high confidence shielding of critical electronics from electromagnetic pulses (EMP), high-altitude EMP (HEMP), and intentional electromagnetic interference (IEMI) via a versatile, low-cost structural configuration that achieves continual POE **23** shielding effectiveness (SE) within both static and unstable environments, exceeds the shielding effectiveness established by MIL-STD-188-125-1A, and removes the need for cumbersome fasteners or electric/pneumatic/auxiliary compression components.

(48) In a non-limiting exemplary embodiment, the electromagnetic shielding enclosure **20** is built in accordance with specific military standards (MIL-STD-188-125-1A), which includes a five-

sided one-quarter inch steel outer casing **25** with an open sixth side dedicated as the point of entry **23** (POE). Such a sixth side POE **23** has been designed in a new and useful way that yields unexpected superior electrical continuity integrity/shielding effectiveness around both the entire circumference perimeter of the POE **23** and the entire surface area of POE **23**, and additionally compresses the POE **23** against the flange **32** so as to achieve metal to metal contact/electrical mating of steel end cap (rear compression plate **39**) against steel flange **32** while at the same time meeting the prescribed compression forces required to compress the installed EMI gasket **40** within its associated groove. Such a POE **23** is weatherproof, shockproof, lockable, requires no peripheral power tools or cumbersome fasteners to open/close, and is conducive to rapid and repeated open/close cycles by non-trained/general personnel.

(49) In a non-limiting exemplary embodiment, the compression hatch assembly **24**, at the POE **23**, serves as an access door to be routinely opened/closed for the purposes of insertion/access/removal of critical electronics designated to be shielded from EMP/IEMP/IEMI within the interior of the housing.

(50) In a non-limiting exemplary embodiment, the electromagnetic shielding enclosure **20** is an EMP/IEMP/IEMI shielding enclosure **20** including a 6-sided metal (or conductive material) outer casing **25**, and an inner shielded housing **22** electromagnetically shielded from outside electromagnetic frequencies/pulses when all six sides are conductively (electrically) sealed to one another by welding and/or its achievable equivalent of abutting an appropriately compressed compression hatch assembly **24**, having an EMI gasket **40** and metal to metal contact, against a flange **32** of POE **23**.

(51) In a non-limiting exemplary embodiment, advantageously, the compression hatch assembly **24** at POE **23** can be routinely opened/closed without compromising the effectiveness of the SE after repeated use. When closed, the electromagnetic shielding enclosure **20** maintains constant high confidence shielding effectiveness (SE) using one-quarter inch steel, flange **32**, EMI gasket **40**, and generally D-shaped compression pins **27**. This structural configuration maintains an effective and superior compression state for the compression hatch assembly **24** that ensures an ongoing and continual electrically conductive, maximum shielding effectiveness with metal to metal mating of flange **32**, EMI gasket **40** (mounted in a machined groove), and rear compression plate **39**, to the steel flange **32** that is welded to the end of the five-sided steel inner shielded housing **22**).

Advantageously, such a structural configuration yields a new, useful, and unexpected rugged, on-demand, rapidly deployable enclosure **20** with a POE **23** designed to withstand the unstable environment associated with land vehicles and other mission requirements existing in the field, and additionally, designed for repeated open/close cycles without the need for trained personnel, power tools, inferior fasteners, or inferior clamps.

(52) In a non-limiting exemplary embodiment, the compression hatch assembly **24** at the POE **23** includes several components: a stainless steel end cap (rear compression plate **39**) with a welded stud or multiple studs, and electromagnetically insulated (EMI) gasket **40** situated within a machined groove of the rear compression plate **39**, a stainless steel machined flat flange **32**, a compression foam layer **38** or other suitable compression material serving as a spring with compression force deflection (CFD), an aluminum or steel front compression plate **37**, a pre-set nut **35** and associated fastener **36**, an aluminum outer casing **25** surrounding the one-quarter inch steel interior faraday shielded housing **22**, a plurality of generally D-shaped compression pins **27**, an onboard actuating tool **46** for rotating generally D-shaped compression pins **27** between tightened and loosened positions, and an associated stowable lock **47** for preventing the generally D-shaped compression pins **27** from disengaging apertures **58**. The compression hatch assembly **24** in combination with the generally D-shaped compression pins **27** provide a 2-stage compression open/close function for the POE **23**. Optionally, a handwheel **50** may be employed.

(53) In a non-limiting exemplary embodiment, the generally D-shaped compression pins **27** are rotatably inserted through the apertures **58** of outer casing **25** to hold opposing forces established

by the pre-installed pre-set nut **35** (or optional rotatable handwheel **50**) and fastener **36** at the compression hatch assembly **24**. Thus, opposing forces are then transferred via rotation of generally D-shaped compression pins **27** (or handwheel **50**) so that compression hatch assembly **24** is now compressed between the generally D-shaped compression pins **27** and steel flange **32**. Compression occurs where the rear compression plate **39** and EMI gasket **40** are compressed against steel flange **32**. The compression may have a value ranging from 30-50 psi. Thus, the compression hatch assembly **24** (via handwheel **50** or pre-set nut **35**/fastener **36**) provides an initial and independent pre-compression function/force before the generally D-shaped compression pins **27** are inserted. Then, the generally D-shaped compression pins **27** are inserted and an additional (supplemental) compression force is exerted against the compression hatch assembly **24** by rotating and pressing the generally D-shaped compression pins **27** against an outer face of the front compression plate **37**, thereby providing additional compression force and urging the compression hatch assembly **24** further beyond apertures **58** at the outer casing **25**. The non-concentric (generally D-shaped) cross-section of the compression pins **27** urges and presses the compression hatch assembly **24** against flange **32** to maintain a tight seal at POE **23**.

(54) In a non-limiting exemplary embodiment, advantageously, the compression hatch assembly **24** provides advantages over competing devices using conventional fasteners/clamps. The compression hatch assembly **24** provides (1) continuous compression over the entire surface area and perimeter of POE **23** thereby eliminating the need for cumbersome fasteners and inferior clamps; (2) exceeds the dynamic performance within the unstable environment of conventional spaced fasteners and clamps by simulating a continuous shockproof weld over the circumference/perimeter of POE **23**; (3) suitable clamping structure of equal compression that is unaffected by normal temperature variations, improper torquing, and inadvertent fastener/clamp failure; (4) requires no peripheral power tools to open/close the compression hatch assembly **24**; (5) eliminates the time-consuming process of removing/replacing multiple fasteners which can be improperly torqued, thereby allowing for easy on-demand open/close at the POE **23**; (6) provides the same high/maximum shielding effectiveness outcome and results of the larger sized (non-portable) POE **23** at a significantly lower cost, lower weight, and lower complexity; (7) suitable for small enclosure POE **23** where hydraulics/pneumatics/other are not a practical method for compressing or pre-compressing POE **23** when compared to the present disclosure's two independent manual compression mechanisms performed via pre-set nut **35**/fastener **36** and manual insertion of generally D-shaped compression pins **27**; (8) and provides a shock absorbing/impact resistance/outflow valve capability due to the compression foam or compression material serving as a spring with CFD acting as a continuous shock absorber in rugged conditions and/or rapid uncontrolled exterior pressure differentials; and (9) is additionally secured by the generally D-shaped steel compression pins **27** acting as an impact resistant compression lock at chamber **26** while compression hatch assembly **24** is in the closed and sealed position. Additionally, in the event of rapid uncontrolled decompression of the surrounding air, the compression hatch assembly **24** may momentarily open (burp) and then immediately close when interior and exterior pressure is equalized.

(55) Advantageously, the present disclosure provides an ergonomic and effective electromagnetic shielding enclosure **20** that does not require peripheral power tools to open/close compression hatch assembly **24** at POE **23** while effectively yielding the new, useful, and unexpected benefit of a higher confidence, higher integrity, maximized shielding effectiveness POE **23** within both static and unstable environments. The compression hatch assembly **24** at POE **23** provides an obvious superior seal than conventional shielding enclosures using fasteners/clamps. The electromagnetic shielding enclosure **20** provides significantly faster open/close cycles and a superior compression hatch assembly **24** seal at POE **23** upon being tightened and compressed via the generally D-shaped compression pins **27**. The electromagnetic shielding enclosure **20** provides a simple, low cost, low weight, manual, and superior compression seal relative to other high cost/high weight enclosures

(electric, pneumatic, air bladder, hydraulic, other) designed for large POEs.

(56) In a non-limiting exemplary embodiment, the present disclosure includes a portable electromagnetic shielding enclosure **20** for providing even distribution of compression hatch assembly **24** seal forces at the POE **23** of the inner shielded housing **25**. Advantageously, the generally D-shaped compression pins **27** are configured to evenly distribute external forces against the compression hatch assembly **24** and flange **32** at POE **23** after the compression hatch assembly **24** is closed (via rotation of generally D-shaped compression pins **27**) from its open, pre-compressed position **45** established by pre-set nut **35**/fastener **36** (an optionally handwheel **50**). During manufacture of the compression hatch assembly **24**, a power tool is used to tighten the pre-set nut **35**/fastener **36** to the desired pre-compressed position **45**. Then, the compression hatch assembly **24** is positioned at the POE **23** and further tightened (compressed) against flange **32**, via rotation of the generally D-shaped compression pins **27**. Once the compression pin lock **47**/onboard tool **46** is stowed in its proper position, the shielded enclosure **20** is now locked in the sealed/closed position whereby the stainless-steel end cap (rear compression plate **39**) and EMI gasket **40** are compressed against the stainless-steel flange **32** along the entirety of the outer perimeter **33** of the POE **23** and the compression pins **78** are restrained from disengagement.

(57) In a non-limiting exemplary embodiment, referring to FIG. **11**, the compression hatch assembly **24** includes a rotatable handle **50** and/or an associated fastener **77** operably coupled thereto, a front compression plate **37** operably coupled to the rotatable handle **50**, a compressible foam layer **38** directly engaged with the front compression plate **37**, a back stainless steel plate end cap (rear compression plate **39**) directly engaged with the compressible foam layer **38**, an EMI gasket **40** positioned within a machined groove directly engaged with the back stainless steel plate end cap (rear compression plate) **39**, and a machined flat, stainless steel flange **32** welded to the inner shielded enclosure **20**. Advantageously, the initial pre-compression function is achieved via rotation of the rotatable handle **50** in opposed rotational directions to tighten and loosen the axial compression force between the front compression plate **37** and the back stainless steel end cap (rear compression plate **39**). Once the pre-compressed hatch assembly **24** is installed into the chamber **26** at its proper depth, set against the flange **32**, and compression pins **78** are installed, the pre-compression force is then transferred by loosening the handwheel **50** and/or rotating compression pins **78**, thereby transferring the opposing forces between the compression/clevis pins **78** and the stainless steel flange **32**. The shielded enclosure **20** is now locked in the sealed/closed position whereby the stainless-steel end cap (rear compression plate **39**) and EMI gasket **40** are compressed against the stainless-steel flange **32** along the entirety of the outer perimeter **33** of the POE **23**.

(58) FIG. **20** is a graph illustrating experimental testing results wherein the FARASAFE.TM enclosure **20** employed its compression hatch assembly **24** vs. BOEING.RTM Little Mountain Testing Facility's (LMTF) blank steel plate (panel) in a radiated susceptibility, transient electromagnetic field (RS105) screen room at LMTF. The mounting of the compression hatch assembly **24** is suitable to bring the shielding effectiveness of the RS105 screen room back into compliance to the requirements of high-altitude electromagnetic pulse (HEMP) protection for fixed ground-based facilities performing critical, time-urgent missions (MIL-STD-188-125-1A). The test concentrated on the area of the compression hatch assembly **24**. Replacing the LMTF blank steel plate with the compression hatch assembly **24** from SAFESTATE.TM brought the effectiveness of the continuous wave shielding of the RS105 screen room back into compliance with MIL-STD-188-125-1A. In the end, the compression hatch assembly **24** was removed and the LMTF one-eighth inches thick blank steel plate (panel) was re-installed and tested for SE of the RS105 screen room and for the comparison between FARASAFE.TM hatch compression assembly **24** and LMTF blank steel plate (panel). The compression hatch assembly **24** closed configuration met all the requirements of MIL-STD-188-125-1A for the area of concern. All SE test frequencies for all antennas in both antenna polarities showed above the MIL-STD-188-125-1A pass/fail limit line **81**.

(59) While various embodiments have been described, the description is intended to be exemplary,

rather than limiting, and it is understood that many more embodiments and implementations are possible that are within the scope of the embodiments. Although many possible combinations of features are shown in the accompanying figures and discussed in this detailed description, many other combinations of the disclosed features are possible. Any feature of any embodiment may be used in combination with or substituted for any other feature or element in any other embodiment unless specifically restricted. Therefore, it will be understood that any of the features shown and/or discussed in the present disclosure may be implemented together in any suitable combination. Accordingly, the embodiments are not to be restricted except in light of the attached claims and their equivalents. Also, various modifications and changes may be made within the scope of the attached claims.

(60) While the foregoing has described what are considered to be the best mode and/or other examples, it is understood that various modifications may be made therein and that the subject matter disclosed herein may be implemented in various forms and examples, and that the teachings may be applied in numerous applications, only some of which have been described herein. It is intended by the following claims to claim any and all applications, modifications and variations that fall within the true scope of the present teachings.

(61) Unless otherwise stated, all measurements, values, ratings, positions, magnitudes, sizes, and other specifications that are set forth in this specification, including in the claims that follow, are approximate, not exact. They are intended to have a reasonable range that is consistent with the functions to which they relate and with what is customary in the art to which they pertain.

(62) The scope of protection is limited solely by the claims that now follow. That scope is intended and should be interpreted to be as broad as is consistent with the ordinary meaning of the language that is used in the claims when interpreted in light of this specification and the prosecution history that follows and to encompass all structural and functional equivalents. Notwithstanding, none of the claims are intended to embrace subject matter that fails to satisfy the requirement of Sections **101**, **102**, or **103** of the Patent Act, nor should they be interpreted in such a way. Any unintended embracement of such subject matter is hereby disclaimed.

(63) Except as stated immediately above, nothing that has been stated or illustrated is intended or should be interpreted to cause a dedication of any component, step, feature, object, benefit, advantage, or equivalent to the public, regardless of whether it is or is not recited in the claims.

(64) It will be understood that the terms and expressions used herein have the ordinary meaning as is accorded to such terms and expressions with respect to their corresponding respective areas of inquiry and study except where specific meanings have otherwise been set forth herein. Relational terms such as first and second and the like may be used solely to distinguish one entity or action from another without necessarily requiring or implying any actual such relationship or order between such entities or actions. The terms “comprises,” “comprising,” or any other variation thereof, are intended to cover a non-exclusive inclusion, such that a process, method, article, or apparatus that comprises a list of elements does not include only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus. An element preceded by “a” or “an” does not, without further constraints, preclude the existence of additional identical elements in the process, method, article, or apparatus that comprises the element.

(65) The Abstract of the Disclosure is provided to allow the reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. In addition, in the foregoing Detailed Description, it can be seen that various features are grouped together in various examples for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the claims require more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive subject matter lies in less than all features

of a single disclosed example. Thus, the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separately claimed subject matter.

Claims

1. A portable electromagnetic shielding enclosure for providing even distribution of seal forces, said portable electromagnetic shielding enclosure comprising: a portable inner shielded housing having an open point of entry; a compression hatch assembly coupled to said open point of entry and being configured to electromagnetically seal said open point of entry; a portable bottom plate and a portable outer casing affixed to said portable bottom plate and being configured to define a chamber configured to receive said portable inner shielded housing; and a plurality of compression pins removably abutted with said compression hatch assembly and said portable outer casing; wherein said compression hatch assembly and said portable inner shielded housing are reciprocated, along a bi-directional travel path, into and out from said chamber; wherein said compression pins are configured to evenly distribute external forces against said compression hatch assembly operably engaged with said open point of entry after said compression hatch assembly is closed and locked from its open and manually pre-compressed position.
2. The portable electromagnetic shielding enclosure of claim 1, wherein said portable inner shielded housing further comprises: a rear side; an axial bore; a flange disposed about said axial bore at an outer perimeter of said open point of entry; and a rear plate attached to said rear side; wherein said compression hatch assembly is operably engaged with said flange and axially opposed from said rear plate.
3. The portable electromagnetic shielding enclosure of claim 2, wherein said compression hatch assembly comprises: a preset nut and a fastener operably coupled thereto; a front compression plate operably coupled to said preset nut; a compressible foam layer directly engaged with said front compression plate; a rear compression plate directly engaged with said compressible foam layer and said fastener; and an electromagnetically insulated (EMI) gasket directly engaged with said rear compression plate and said flange; wherein said pre-set nut and said fastener are configured to establish a fixed, pre-harnessed compression state suitable for said compression hatch assembly to operably and electromagnetically seal said point of entry; wherein said compression hatch assembly and said portable inner shielded housing are further configured to be contemporaneously inserted into said portable outer casing.
4. The portable electromagnetic shielding enclosure of claim 3, wherein said portable electromagnetic shielding enclosure further comprises: a stowable tool removably engaged with said compression pins as well as said portable outer casing; and a lock detachably engaged with said stowable tool and said portable outer casing.
5. The portable electromagnetic shielding enclosure of claim 4, wherein said stowable tool and said lock are located exterior of said portable inner shielded housing and said portable outer casing.
6. The portable electromagnetic shielding enclosure of claim 5, wherein said compression pins comprise: a plurality of generally D-shaped compression pins configured to roll and transfer opposing forces that compresses said EMI gasket against said flange along an entirety of said outer perimeter of said point of entry at said portable inner shielded housing.
7. The portable electromagnetic shielding enclosure of claim 3, wherein said portable electromagnetic shielding enclosure further comprises: a rotating handle operably engaged with said pre-set nut.
8. The portable electromagnetic shielding enclosure of claim 7, wherein said rotating handle is configured to be rotated in opposed rotational directions to respectively tighten and loosen said pre-set nut and further configured to enable said compression hatch assembly to be inserted into said chamber.
9. The portable electromagnetic shielding enclosure of claim 1, wherein said compression hatch

assembly, said portable inner shielded housing, and said portable outer casing are coaxially aligned.

10. A portable electromagnetic shielding enclosure for providing even distribution of seal forces, said portable electromagnetic shielding enclosure comprising: a portable inner shielded housing having an open point of entry; a compression hatch assembly operably coupled to said open point of entry and being configured to electromagnetically seal said open point of entry; a portable bottom plate and a portable outer casing affixed to said portable bottom plate and being configured to define a chamber configured to linearly receive said portable inner shielded housing; and a plurality of compression pins frictionally and removably abutted with said compression hatch assembly and said portable outer casing; wherein said compression hatch assembly and said portable inner shielded housing are axially reciprocated, along a bi-directional travel path, into and out from said chamber; wherein said compression pins are configured to evenly distribute external forces against said compression hatch assembly operably engaged with said open point of entry after said compression hatch assembly is closed and locked from its open and manually pre-compressed position.

11. The portable electromagnetic shielding enclosure of claim 10, wherein said portable inner shielded housing further comprises: a rear side; an axial bore; a flange disposed about said axial bore at an outer perimeter of said open point of entry; and a rear plate attached to said rear side; wherein said compression hatch assembly is operably engaged with said flange and axially opposed from said rear plate.

12. The portable electromagnetic shielding enclosure of claim 11, wherein said compression hatch assembly comprises: a preset nut and a fastener operably coupled thereto; a front compression plate operably coupled to said preset nut; a compressible foam layer directly engaged with said front compression plate; a rear compression plate directly engaged with said compressible foam layer and said fastener; and an electromagnetically insulated (EMI) gasket directly engaged with said rear compression plate and said flange; wherein said pre-set nut and said fastener are configured to establish a fixed, pre-harnessed compression state suitable for said compression hatch assembly to operably and electromagnetically seal said point of entry; wherein said compression hatch assembly and said portable inner shielded housing are further configured to be contemporaneously inserted into said portable outer casing.

13. The portable electromagnetic shielding enclosure of claim 12, wherein said portable electromagnetic shielding enclosure further comprises: a stowable tool removably engaged with said compression pins as well as said portable outer casing; and a lock detachably engaged with said stowable tool and said portable outer casing.

14. The portable electromagnetic shielding enclosure of claim 13, wherein said stowable tool and said lock are located exterior of said portable inner shielded housing and said portable outer casing.

15. The portable electromagnetic shielding enclosure of claim 14, wherein said compression pins comprise: a plurality of generally D-shaped compression pins configured to roll and transfer opposing forces that compresses said EMI gasket against said flange along an entirety of said outer perimeter of said point of entry at said portable inner shielded housing.

16. The portable electromagnetic shielding enclosure of claim 12, wherein said portable electromagnetic shielding enclosure further comprises: a rotating handle operably engaged with said pre-set nut.

17. The portable electromagnetic shielding enclosure of claim 16, wherein said rotating handle is configured to be rotated in opposed rotational directions to respectively tighten and loosen said pre-set nut and further configured to enable said compression hatch assembly to be inserted into said chamber.

18. The portable electromagnetic shielding enclosure of claim 10, wherein said compression hatch assembly, said portable inner shielded housing, and said portable outer casing are coaxially aligned.
