

US Patent & Trademark Office

Patent Public Search | Text View

United States Design Patent

D1092814

Kind Code

S

Date of Patent

September 09, 2025

Inventor(s)

Hopkins; Michael J. et al.

Portable light

Inventors: Hopkins; Michael J. (Antioch, IL), Kirk; Kevin R. (Minnetonka, MN), Kuta; Jonathan (Milwaukee, WI), Prestidge-Kadrlik; Christina (Hartland, WI), Spenner; Jeffrey L. (Germantown, WI), Bulow; Jessica L. (Milwaukee, WI)

Applicant: MILWAUKEE ELECTRIC TOOL CORPORATION (Brookfield, WI)

Assignee: MILWAUKEE ELECTRIC TOOL CORPORATION (Brookfield, WI)

() Term:** 15 Years **Appl. No.:**

D/822863

Filed:

January 12, 2022

Publication Classification

LOC Cl.: 2605

U.S. Cl.:

USPC D26/44; D26/63

Field of Classification Search

CPC: F21S (9/00); F21S (9/02); F21L (4/00); F21L (4/005); F21W (2131/10)

USPC: D26/24; D26/37; D26/43; D26/44; D26/46; D26/49; D26/60; D26/61; D26/63; D26/65; D26/93; D26/104; D26/106; D26/110

Description

- (1) FIG. 1 is a first perspective view of a first embodiment of a portable light in a first configuration.
- (2) FIG. 2 is a second perspective view of the portable light of FIG. 1 in the first configuration.
- (3) FIG. 3 is a first side view of the portable light of FIG. 1 in the first configuration.
- (4) FIG. 4 is a second side view of the portable light of FIG. 1 in the first configuration.

- (5) FIG. 5 is a front view of the portable light of FIG. 1 in the first configuration.
- (6) FIG. 6 is a rear view of the portable light of FIG. 1 in the first configuration.
- (7) FIG. 7 is a bottom view of the portable light of FIG. 1 in the first configuration.
- (8) FIG. 8 is a top view of the portable light of FIG. 1 in the first configuration.
- (9) FIG. 9 is a first perspective view of the portable light of FIG. 1 in a second configuration.
- (10) FIG. 10 is a second perspective view of the portable light of FIG. 1 in the second configuration.
- (11) FIG. 11 is a first side view of the portable light of FIG. 1 in the second configuration.
- (12) FIG. 12 is a second side view of the portable light of FIG. 1 in the second configuration.
- (13) FIG. 13 is a front view of the portable light of FIG. 1 in the second configuration.
- (14) FIG. 14 is a rear view of the portable light of FIG. 1 in the second configuration.
- (15) FIG. 15 is a bottom view of the portable light of FIG. 1 in the second configuration.
- (16) FIG. 16 is a top view of the portable light of FIG. 1 in the second configuration.
- (17) FIG. 17 is a first perspective view of a second embodiment of a portable light in a first configuration.
- (18) FIG. 18 is a second perspective view of the portable light of FIG. 17 in the first configuration.
- (19) FIG. 19 is a first side view of the portable light of FIG. 17 in the first configuration.
- (20) FIG. 20 is a second side view of the portable light of FIG. 17 in the first configuration.
- (21) FIG. 21 is a front view of the portable light of FIG. 17 in the first configuration.
- (22) FIG. 22 is a rear view of the portable light of FIG. 17 in the first configuration.
- (23) FIG. 23 is a bottom view of the portable light of FIG. 17 in the first configuration.
- (24) FIG. 24 is a top view of the portable light of FIG. 17 in the first configuration.
- (25) FIG. 25 is a first perspective view of the portable light of FIG. 17 in a second configuration.
- (26) FIG. 26 is a second perspective view of the portable light of FIG. 17 in the second configuration.
- (27) FIG. 27 is a first side view of the portable light of FIG. 17 in the second configuration.
- (28) FIG. 28 is a second side view of the portable light of FIG. 17 in the second configuration.
- (29) FIG. 29 is a front view of the portable light of FIG. 17 in the second configuration.
- (30) FIG. 30 is a rear view of the portable light of FIG. 17 in the second configuration.
- (31) FIG. 31 is a bottom view of the portable light of FIG. 17 in the second configuration.
- (32) FIG. 32 is a top view of the portable light of FIG. 17 in the second configuration.
- (33) FIG. 33 is a first perspective view of a third embodiment of a portable light in a first configuration.
- (34) FIG. 34 is a second perspective view of the portable light of FIG. 33 in the first configuration.
- (35) FIG. 35 is a first side view of the portable light of FIG. 33 in the first configuration.
- (36) FIG. 36 is a second side view of the portable light of FIG. 33 in the first configuration.
- (37) FIG. 37 is a front view of the portable light of FIG. 33 in the first configuration.
- (38) FIG. 38 is a rear view of the portable light of FIG. 33 in the first configuration.
- (39) FIG. 39 is a bottom view of the portable light of FIG. 33 in the first configuration.
- (40) FIG. 40 is a top view of the portable light of FIG. 33 in the first configuration.
- (41) FIG. 41 is a first perspective view of the portable light of FIG. 33 in a second configuration.
- (42) FIG. 42 is a second perspective view of the portable light of FIG. 33 in the second configuration.
- (43) FIG. 43 is a first side view of the portable light of FIG. 33 in the second configuration.
- (44) FIG. 44 is a second side view of the portable light of FIG. 33 in the second configuration.
- (45) FIG. 45 is a front view of the portable light of FIG. 33 in the second configuration.
- (46) FIG. 46 is a rear view of the portable light of FIG. 33 in the second configuration.
- (47) FIG. 47 is a bottom view of the portable light of FIG. 33 in the second configuration; and,
- (48) FIG. 48 is a top view of the portable light of FIG. 33 in the second configuration.

(49) Portions of the portable light shown in broken lines are for illustrative purposes only and form no part of the claimed design.

Claims

The ornamental design for a portable light, as shown and described.
