

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404008
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Labry; Pierre-Jacques

Control mechanism

Abstract

A control mechanism for an aircraft includes: a conversion mechanism having a translatable part and a rotatable part, the translatable part being reversibly translatable and being connectable to an inceptor; an inceptor connector connected to the translatable part of the conversion mechanism; a differential device connected to the rotatable part of the conversion mechanism, the conversion mechanism being configured to reversibly convert translational motion of the inceptor connector to rotational motion of the differential device; an adjustment member connected to the differential device; and a control member connected to the differential device; wherein the differential device is configured such that the adjustment member is maintainable in position during an aircraft control process to permit: translation of the inceptor connector from a translational neutral position; and corresponding movement of the control member, to control the aircraft through the differential device.

Inventors:	Labry; Pierre-Jacques (Faycelles, FR)
Applicant:	RATIER-FIGEAC SAS (Figeac, FR)
Family ID:	87378034
Assignee:	RATIER-FIGEAC SAS (Figeac, FR)
Appl. No.:	18/748170
Filed:	June 20, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250121930 A1	Apr. 17, 2025

Foreign Application Priority Data

EP	23306019	Jun. 26, 2023
EP	24305416	Mar. 20, 2024

Publication Classification

Int. Cl.: B64C13/34 (20060101)

U.S. Cl.:

CPC B64C13/34 (20130101);

Field of Classification Search

CPC: B64C (13/34); B64C (13/044); B64C (13/06); B64C (13/042); B64C (13/22); B64C (13/50)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2478546	12/1948	Pickens	244/235	B64C 13/044
4470570	12/1983	Sakurai	244/236	B64C 13/06
4848708	12/1988	Farrell	244/235	B64C 13/044
10196130	12/2018	Gemmati et al.	N/A	N/A
10377468	12/2018	Carner	N/A	B64C 13/12
2017/0174324	12/2016	Carner	N/A	B64C 13/12
2017/0253317	12/2016	Elliott	N/A	G05G 1/44
2017/0369154	12/2016	Zimmer	N/A	G05G 1/40
2019/0315452	12/2018	Labry	N/A	F16H 51/00
2021/0129975	12/2020	Voiles	N/A	B64C 13/50

OTHER PUBLICATIONS

European Search Report for Application No. 23306019.3, mailed Dec. 8, 2023, 6 pages. cited by applicant

European Search Report for Application No. 24305416.0, mailed Aug. 13, 2024, 6 pages. cited by applicant

Primary Examiner: Benedik; Justin M

Attorney, Agent or Firm: CANTOR COLBURN LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims the benefit of European Patent Application No. 23306019.3 filed Jun. 26, 2023 and European Patent Application No. 24305416.0 filed Mar. 20, 2024, the disclosures of which are incorporated herein by reference in their entirety.

TECHNICAL FIELD

(2) This disclosure relates to a control mechanism for an aircraft.

BACKGROUND

(3) Control mechanisms in aircraft allow adjustment processes to be performed in which an inceptor neutral position and/or morphology of the control mechanism is adapted for a pilot's stature. These mechanisms also allow aircraft control processes to be carried out, for example, rudder control.

(4) It is desirable to have the inceptor trajectory be as close as possible to linear. Current control mechanisms typically feature long arms in order to limit curving of the inception motion, but a compromise is necessary to limit the size and weight of the control mechanisms. It is therefore desirable to improve control mechanisms, as well as reduce the space they occupy in the aircraft and reduce their weight.

SUMMARY

(5) According to a first aspect, there is provided a control mechanism for an aircraft, the control mechanism comprising: a conversion mechanism having a translatable part and a rotatable part, the translatable part being reversibly translatable; an inceptor connector connected to the translatable part of the conversion mechanism; a differential device connected to the rotatable part of the conversion mechanism, the conversion mechanism being configured to reversibly convert translational motion of the inceptor connector to rotational motion of the differential device; an adjustment member connected to the differential device; and a control member connected to the differential device; wherein the differential device is configured such that the adjustment member is maintainable in position during an aircraft control process to permit: translation of the inceptor connector from a translational neutral position; and corresponding movement of the control member, to control the aircraft through the differential device; and wherein the differential device is configured such that the control member is maintainable in position during an adjustment process to permit: translation of the inceptor connector; and corresponding movement of the adjustment member through the differential device, to adjust the translational neutral position. By providing a differential device as described above, the motion of the control member is disconnected from the motion of the adjustment member, and vice versa. This arrangement is more compact and means that the adjustment process does not affect the feel force for the aircraft control process.

Additionally, the provision of a reversible translation to rotation conversion mechanism allows the control mechanism to be provided as hand-operated if desired.

(6) The control mechanism may comprise an adjustment member maintaining device. The adjustment member maintaining device may be configured to, during the aircraft control process, resist movement of the adjustment member.

(7) The adjustment member maintaining device may be configured to, during the adjustment process, provide discrete positions of the inceptor connector along the conversion mechanism to allow variation of the translational neutral position. More specifically, the adjustment member maintaining device may be configured to, during the adjustment process, provide discrete positions of the inceptor connector and the translatable part of the conversion mechanism along the rotatable part of the conversion mechanism to allow variation of the translational neutral position.

(8) The adjustment member maintaining device may comprise a plurality of notches. Each of the plurality of notches may be configured to, during the adjustment process, provide discrete positioning of the inceptor connector along the conversion mechanism. More specifically, each of the plurality of notches may be configured to, during the adjustment process, provide discrete positioning of the inceptor connector and the translatable part of the conversion mechanism along the rotatable part of the conversion mechanism.

(9) The adjustment member maintaining device may comprise a disc. The disc may comprise a plurality of notches around a circumference of the disc. The disc may be coupled to the adjustment member.

(10) The adjustment member maintaining device may comprise a locking member. The locking member may be configured, during a control process, to engage one of the plurality of notches.

(11) The adjustment member maintaining device may comprise an elastic member. The elastic

member may be configured to bias the locking member to, during a control process, engage one of the plurality of notches.

(12) Alternatively, the adjustment member maintaining device may comprise a non-reversible device. The non-reversible device may be configured to, during the adjustment process, provide continuous positioning of the inceptor connector along the conversion mechanism. More specifically, the non-reversible device may be configured to, during the adjustment process, provide continuous positioning of the inceptor connector and the translatable part of the conversion mechanism along the rotatable part of the conversion mechanism.

(13) The non-reversible device may be manually or electrically actuatable.

(14) The control mechanism may comprise an elastic element configured to bring the translation neutral position of the inceptor connector back toward a pilot.

(15) The control mechanism may comprise a control member maintaining device configured to, during the adjustment process, resist movement of the control member.

(16) The control member maintaining device may be a control member locking device configured to, during the adjustment process, lock movement of the control member.

(17) The control member may be rotatable during the aircraft control process. For example, the control member may be rotatable, during the aircraft movement control process, to allow translation of the inceptor connector from the translational neutral position to a control position. Additionally, the control member may be rotatable, during the aircraft movement control process, to allow translation of the inceptor connector from the control position to the translational neutral position.

(18) The control member maintaining device may comprise a control member biasing device configured to, during the aircraft control process, bias the inceptor connector towards the translational neutral position.

(19) The biasing device may comprise a feeling unit. The feeling unit may comprise a centering spring.

(20) The control mechanism may comprise a motor configured to rotate the control member during the aircraft movement control process.

(21) The adjustment member may be rotatable during the adjustment process. For example, the adjustment member may be rotatable, during the adjustment process, to allow translation of the inceptor connector along the conversion mechanism to allow variation of the translational neutral position of the inceptor connector. More specifically, the adjustment member may be rotatable, during the adjustment process, to allow translation of the inceptor connector and the translatable part of the conversion mechanism along the rotatable part of the conversion mechanism to allow variation of the translational neutral position of the inceptor connector.

(22) The control mechanism may comprise a motor configured to rotate the adjustment member during the adjustment process.

(23) The differential device may comprise an epicyclic gear train.

(24) The epicyclic gear train may comprise a sun gear, wherein the rotatable part of the conversion mechanism is coupled to the sun gear such that the rotatable part of the conversion mechanism rotates with the sun gear.

(25) The epicyclic gear train may comprise a carrier, wherein the control member is coupled to the carrier such that the carrier rotates with the control member during the aircraft control process.

(26) The epicyclic gear train may comprise a ring gear, wherein the adjustment member is coupled to the ring gear, such that the ring gear rotates with the adjustment member during the adjustment process.

(27) The differential device may comprise a harmonic drive, a conical gear differential, or a spur gear differential.

(28) The differential device may comprise a first planetary gear, wherein the rotatable part of the conversion mechanism is coupled to the first planetary gear such that the rotatable part of the

conversion mechanism rotates with the first planetary gear.

(29) The differential device may comprise a satellite gear, wherein the first planetary gear is coupled to the satellite gear such that the first planetary gear rotates with the satellite gear.

(30) The differential device may comprise a second planetary gear, wherein the satellite gear is coupled to the second planetary gear such that the second planetary gear rotates with the satellite gear.

(31) The differential device may be configured such that during the aircraft control process, the adjustment member prevents rotation of the satellite gear to cause the satellite gear to be rigidly connected to the first and second planetary gears. The differential device may be configured such that during the aircraft control process, the first and second planetary gears rotate together.

(32) The differential device may be configured such that during the adjustment process, the satellite gear is permitted to rotate to permit opposing rotation of the first and second planetary gears.

(33) The first planetary gear and/or second planetary gear may comprise a compound gear.

(34) The rotatable part of the conversion mechanism may comprise a gear.

(35) The conversion mechanism may be configured to be inclined relative to a horizontal axis when installed. The conversion mechanism may be configured to be inclined relative to a longitudinal axis of an aircraft when installed on the aircraft.

(36) The translatable part of the conversion mechanism may be a nut. The rotatable part of the translation mechanism may be a screw. The nut may be configured to reversibly translate along the screw upon rotation of the screw. The differential device may be actuatable to reversibly rotate the screw upon translation of the inceptor connector.

(37) Alternatively, the rotatable part of the conversion mechanism may be a nut. The translatable part of the conversion mechanism may be a screw.

(38) The inceptor connector may be integral with the translatable part of the conversion mechanism. The inceptor may be integral with the inceptor connector. Thus, both the inceptor connector and the inceptor may be integral with the translatable part of the conversion mechanism. However, for maintenance convenience, it is preferred that the inceptor connector, the inceptor and the translatable part of the conversion mechanism are distinct parts.

(39) The control mechanism may comprise a guiding mechanism. The guiding mechanism may be configured to maintain an orientation of the inceptor connector during translation of the inceptor connector. The guiding mechanism may be configured to prevent rotation of the inceptor connector around a longitudinal axis of the conversion mechanism during translation of the inceptor connector.

(40) The inceptor connector may be coupled to the guiding mechanism.

(41) The guiding mechanism may comprise a rail, the inceptor connector being slidably coupled to the rail.

(42) The guiding mechanism may comprise a first arm and a second arm, the first arm being pivotally coupled to the inceptor connector and the second arm, and the second arm being pivotally coupled to a fixed point.

(43) The guiding mechanism may comprise a clasp, the inceptor connector being coupled to the clasp, and the clasp being connectable to a clasp of an additional inceptor connector.

(44) The guiding mechanism may comprise a hinge device. The hinge device may comprise an arm connectable to an arm of an additional inceptor connector, the arm being coupled to the inceptor connector.

(45) The control mechanism may comprise one or more sensors configured to detect rotation of the control member during the aircraft control process. The one or more sensors may be configured to output a signal in response to detecting the rotation of the control member. The signal may be a rudder control signal.

(46) The signal may comprise an image of a rotational position of the control member during the aircraft control process.

- (47) The one or more sensors may be connected to the control member.
- (48) The control mechanism may comprise a stop to prevent movement of the control member when the inceptor connector reaches a maximum translation distance during the aircraft control process.
- (49) The control mechanism may be a rudder control mechanism.
- (50) The inceptor may be a pedal.
- (51) According to a second aspect, there is provided a bilateral control mechanism comprising: a further conversion mechanism having a translatable part and a rotatable part, the translatable part being reversibly translatable; and a further inceptor connector connected to the translatable part of the further conversion mechanism.
- (52) The differential device may be connected to the rotatable part of the further conversion mechanism. The further conversion mechanism may be configured to convert rotational motion of the differential device to translational motion of the further inceptor connector.
- (53) The second planetary gear may be coupled to the rotatable part of the further conversion mechanism such that the rotatable part of the further conversion mechanism rotates with the second planetary gear.
- (54) According to a third aspect, there is provided a bilateral control mechanism comprising: a first control mechanism as described above; and a second control mechanism as described above.
- (55) The differential device of the first control mechanism may be configured to engage with the differential device of the second control mechanism. The differential device of the first control mechanism may be indirectly engaged with the differential device of the second control mechanism. The differential device of the first control mechanism may be directly engaged with the differential device of the second control mechanism.
- (56) The differential device of the first control mechanism and the differential device of the second control mechanism may be synchronised such that on translation of the inceptor connector of the first control mechanism during the aircraft control process the inceptor connector of the second control mechanism translates in an opposing direction to the inceptor connector of the first control mechanism.
- (57) The differential device of the first control mechanism and the differential device of the second control mechanism may be synchronised such that on translation of the inceptor connector of the first control mechanism during the adjustment process the inceptor connector of the second control mechanism translates in the same direction as the inceptor connector of the first control mechanism.
- (58) The bilateral control mechanism may comprise only one control member and one adjustment member. The control member of the first control mechanism and the control member of the second control mechanism may be the same control member. The adjustment member of the first control mechanism and the adjustment member of the second control mechanism may be the same adjustment member.
- (59) The bilateral control mechanism may comprise only one differential device. The differential device of the first control mechanism and the differential device of the second control mechanism may be the same differential device.
- (60) According to a fourth aspect, there is provided a control mechanism for an aircraft, the control mechanism comprising: an inceptor connector connectable to an inceptor; a linear conversion mechanism having a translatable part and a rotatable part, the inceptor connector being reversibly translatable with the translatable part of the linear conversion mechanism on the rotatable part of the linear conversion mechanism from a translational neutral position. By providing a linear conversion mechanism as described above, the motion of the inceptor connector is made linear. This arrangement is more ergonomic for a pilot and means that the control mechanism can be provided with long strokes, without requiring a large control mechanism. Additionally, pilots of different statures using this arrangement can experience the same feel force regardless of their

stature.

(61) The control mechanism may comprise any of the features described above.

(62) According to a fifth aspect, there is provided an aircraft comprising a control mechanism as described above or a bilateral control mechanism as described above.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) Embodiments will be further described and explained by way of example with reference to the accompanying drawings in which:

(2) FIG. **1a** shows a schematic of a bilateral control mechanism;

(3) FIG. **1b** shows a schematic of a section of a bilateral control mechanism;

(4) FIG. **2a** shows a schematic of a bilateral control mechanism during an aircraft control process;

(5) FIG. **2b** shows a schematic of a section of a bilateral control mechanism during an aircraft control process;

(6) FIG. **3a** shows a schematic of a bilateral control mechanism during an adjustment process;

(7) FIG. **3b** shows a schematic of a section of a bilateral control mechanism during an adjustment process;

(8) FIG. **4a** shows a schematic of a bilateral control mechanism during an aircraft control process;

(9) FIG. **4b** shows a schematic of a section of a bilateral control mechanism during an aircraft control process;

(10) FIG. **5a** shows a schematic of a bilateral control mechanism during an adjustment process;

(11) FIG. **5b** shows a schematic of a section of a bilateral control mechanism during an adjustment process;

(12) FIG. **6** shows a schematic of a guiding mechanism;

(13) FIGS. **7a-7c** show a schematic of a guiding mechanism;

(14) FIG. **8** shows a schematic of a guiding mechanism; and

(15) FIGS. **9a-9c** show a schematic of a guiding mechanism.

DETAILED DESCRIPTION

(16) With reference to FIGS. **1a-1b**, a bilateral control mechanism **100** comprises a left control mechanism. The left control mechanism comprises a left inceptor connector **102a**, a left conversion mechanism **104a**, and a left differential device **112a**. A left axle **106a** is coupled to the left inceptor connector **102a** and a left inceptor **108a** (e.g. a left pedal) is rotationally coupled to the left axle **106a**.

(17) The left conversion mechanism **104a** comprises a translatable part and a rotatable part. In this embodiment, the translatable part is a nut **105a** and the rotatable part is a threaded shaft **103a** (e.g. a ball screw or a roller screw) having a first end and a second, opposite end. The first end is rotationally coupled to a first plate **110a**. The second end passes through a second plate **110b** and is coupled to the left differential device **112a**. The first plate **110a** and the second plate **110b** provide structural support to the left conversion mechanism **104a**. The first plate **110a** and the second plate **110b** are fixed to a fixed point on the aircraft (e.g. an aircraft floor). The inceptor connector **102a** is connected to the nut **105a** and the nut **105a** is moveably engaged with the threaded shaft **103a**.

(18) As illustrated in FIG. **1a**, the bilateral control mechanism **100** further comprises a right control mechanism. The right control mechanism comprises a right inceptor connector **102b**, a right conversion mechanism **104b**, a right axle **106b**, a right inceptor **108b** (e.g. a right pedal), and a right differential device **112b**. These components are positioned symmetrically along an axis of the bilateral control mechanism **100** with respect to the left control mechanism, and operate in the same manner as the left inceptor connector **102a**, left conversion mechanism **104a**, left axle **106a**, left inceptor **108a**, and left differential device **112a**. Repeated description of the additional components

is omitted.

(19) The left differential device **112a** is coupled to a control member **114**. The right differential device **112b** is coupled to the control member **114**. The right differential device **112b** is coupled to an adjustment member **116**. The left differential device **112a** is coupled to the adjustment member **116** via the right differential device **112b**. The control member **114** and adjustment member **116** each comprise a rigid rod. This arrangement allows the differential devices **112a**, **112b** to be synchronised (e.g. configured such that movement of one differential device causes movement of the other differential device, as described below). However, in other arrangements, the differential devices **112a**, **112b** may be synchronised using one or more gearsets.

(20) The adjustment member **116** is connected to an adjustment member maintaining device **117** that resists movement of the adjustment member **116** during an aircraft control process. As will be described later, the use of an adjustment member maintaining device **117** prevents a simultaneous aircraft control process and adjustment process from occurring.

(21) The adjustment member maintaining device **117** may be a reversible locking mechanism comprising a plurality of notches that engage complementary features (not shown) of the adjustment member **116** to provide discrete positions in order to lock the inceptor connectors **102a**, **102b** at different translational neutral positions along the threaded shafts of the conversion mechanisms **104a**, **104b** as required. In these embodiments, the bilateral control mechanism **100** may comprise an elastic element, such as a mechanical spring **119** that brings the translational neutral position of the inceptor connectors **102a**, **102b** back toward a pilot during an adjustment process. The mechanical spring **119** may be a torsion spring.

(22) Alternatively, the adjustment member **116** may be connected to a non-reversible device that provides continuous positioning of the inceptor connectors **102a**, **102b** along the threaded shafts **103a**, **103b** of the conversion mechanisms **104a**, **104b**. The non-reversible device may be actuated manually, e.g. by a pilot, or may be actuated electrically, e.g. by a motor. The term “non-reversible” here means that the device is configured, when actuated by a motor, to prevent back driving of the motor.

(23) In a similar manner, the control member **114** is connected to a control member maintaining device **115** that resists movement of the control member **114** during an adjustment process. As will be described later, the use of a control member maintaining device **115** prevents a simultaneous aircraft control process and adjustment process from occurring.

(24) In some embodiments, the control member maintaining device **115** may be a control member locking device that locks the control member **114** in position. Alternatively, the control member maintaining device **115** may comprise a control member biasing device, such as a feeling unit, that prevents and/or reverses any movement of the control member **114** by biasing the inceptor connector **102a** towards a translation neutral position.

(25) Although not illustrated, in some embodiments, the bilateral control mechanism **100** may comprise two control members and two adjustment members.

(26) The threaded shafts **103a**, **103b** of the conversion mechanisms **104a**, **104b** are threaded in opposite directions. Alternatively, the threaded shafts **103a**, **103b** of the conversion mechanisms **104a**, **104b** may be threaded in the same direction. However, in such arrangements, the coupling of the control member **114** and adjustment member **116**, as described above, is reversed.

(27) As illustrated in FIG. **1b**, the left differential device **112a** comprises a left epicyclic gear train and the right differential device **112b** comprises a right epicyclic gear train. In other arrangements (not shown), the differential devices **112a**, **112b** may be replaced by a harmonic drive, a conical gear differential, or a spur gear differential.

(28) Each epicyclic gear train comprises a sun gear **118a**, **118b**, a plurality of planetary gears **120a**, **120b**, a carrier **122a**, **122b**, and a ring gear **124a**, **124b**. The outer circumferential edge of each sun gear **118a**, **118b** engages (e.g. meshes) with the outer circumferential edge of each of the plurality of planetary gears **120a**, **120b**. The centre of each of the planetary gears **120a**, **120b** is rotationally

coupled to the respective carrier **122a**, **122b** and the outer circumferential edge of each of the plurality of planetary gears **120a**, **120b** engages (e.g. meshes) with the inner circumferential edge of the respective ring gear **124a**, **124b**. This results in the left epicyclic gear train **112a** having a left sun gear **118a**, a plurality of left planetary gears **120a**, a left carrier **122a** and a left ring gear **124a**. Similarly, the right epicyclic gear train **112b** has a right sun gear **118b**, a plurality of right planetary gears **120b**, a right carrier **122b** and a right ring gear **124b**.

(29) The threaded shafts **103a**, **103b** of the conversion mechanisms **104a**, **104b** are rigidly coupled to the sun gears **118a**, **118b**, with a threaded shaft **103a** of the left conversion mechanism **104a** connected to the left sun gear **118a** and a threaded shaft **103b** of the right mechanism **104b** connected to the right sun gear **118b**. The outer circumferential edge of the left carrier **122a** and the outer circumferential edge of the right carrier **122b** each engage (e.g. mesh) with the control member **114**. The outer circumferential edge of the left ring gear **124a** engages (e.g. meshes) with the outer circumferential edge of the right ring gear **124b**. The adjustment member **116** engages (e.g. meshes) with the outer circumferential edge of the right ring gear **124b**. In alternative arrangements, as described above, the coupling of the control member **114** and adjustment member **116** may be reversed and/or the adjustment member **116** or control member **114** may be rotationally coupled to the outer circumferential edge of the left ring gear **124a**.

(30) The terms “engage”, “connect” and “couple” as used herein means that components may be directly or indirectly engaged, coupled or connected. In embodiments in which components are indirectly engaged, coupled or connected, intermediate components may be present.

(31) With reference to FIGS. **2a-2b**, when the left inceptor **108a** is actuated during an aircraft control process, e.g. by a pilot, the left inceptor connector **102a** translates along the threaded shaft **103a** of the left conversion mechanism **104a** from a translational neutral position e.g. in the direction indicated (i.e. towards the first plate **110a**). Since the left inceptor connector **102a** is connected to a nut **105a**, through which the threaded shaft **103a** of the left conversion mechanism **104a** extends, translation of the left inceptor connector **102a** relative to the left conversion mechanism **104a** causes the threaded shaft **103a** of the left conversion mechanism **104a** to rotate about an axis of the threaded shaft **103a** in an anti-clockwise direction as indicated in FIG. **2a** (i.e. anti-clockwise from the perspective of the pilot looking towards the first plate **110a**). This in turn causes the left differential device **112a** to rotate with the threaded shaft **103a** of the left conversion mechanism **104a**. Specifically, the left sun gear **118a** rotates about an axis of the left differential device **112a** in the same rotational direction as the threaded shaft **103a** of the left conversion mechanism **104a** (i.e. anti-clockwise). Because the left sun gear **118a** engages (e.g. meshes) with the plurality of planetary gears **120a**, each of the plurality of left planetary gears **120a** also rotates, but in the opposite direction (i.e. clockwise) about an axis of each respective planetary gear **120a**.

(32) As described later, the left ring gear **124a** is maintained in position during an aircraft control process. This means that the rotation of each of the plurality of planetary gears **120a** causes them to orbit the left sun gear **118a** along the inner circumferential edge of the left ring gear **124a** in the same direction as the sun gear **118a** (i.e. anti-clockwise). Because the plurality of planetary gears **120a** are coupled to the left carrier **122a**, the left carrier **122a** rotates with the orbit of the plurality of left planetary gears **120a**, while the control member **114**, which engages (e.g. meshes) with the carrier **122a**, rotates in the same direction (i.e. clockwise).

(33) Rotation of the control member **114** causes the right carrier **122b** to rotate in the direction indicated in FIG. **2b** (i.e. anticlockwise) and the plurality of right planetary gears **120b** to orbit the right sun gear **118b** in the same direction (i.e. anti-clockwise). This in turn causes each of the plurality of right planetary gears **120b** to rotate about an axis of each respective planetary gear **120b** in the opposite direction (i.e. clockwise). Because the right sun gear **118b** is coupled to each of the plurality of right planetary gears **120b**, the right sun gear **118b** and the threaded shaft **103b** of the right conversion mechanism **104b**, which is coupled to the right sun gear **118b**, rotate in the direction indicated in FIG. **2b** (i.e. anticlockwise).

(34) The right inceptor **108b** is also connected to a nut **105a**, through which the threaded shaft **103b** of the right conversion mechanism **104b** extends. As a result, the right inceptor **108b** translates along the threaded shaft **103b** of the right conversion mechanism **104b** in the opposite direction to the actuated left inceptor **108a** (i.e. towards the second plate **110b**).

(35) As illustrated in FIG. 2b, during the aircraft control movement process, the adjustment member **116** is maintained in position via the adjustment member maintaining device **117**, causing each of the ring gears **124a**, **124b** to be maintained in position (due to the left ring gear **124a** engaging (e.g. meshing) with the right ring gear **124b**) so that the differential devices **112a**, **112b** undergo fixed ring motion as described above. This prevents a simultaneous aircraft control process and adjustment process from occurring.

(36) It will be understood that when the right inceptor **108b** is translated forwards (i.e. towards the first plate **110a**) the threaded shafts **103a**, **103b** of the conversion mechanisms **104a**, **104b** and components of the differential devices **112a**, **112b** rotate in opposite directions to those described above. This causes the left inceptor **108a** to translate backwards (i.e. in the opposite direction to the right inceptor **108a** towards the second plate **110b**) and the control member **114** to rotate in the opposite direction to that described above.

(37) The above relates to a manual operation of the bilateral control mechanism **100**. However, the bilateral control mechanism **100** may also be electrically actuated, e.g. by an autopilot system. In such arrangements, the aircraft control process is initiated by actuating (i.e. rotating) the control member **114** directly, rather than one of the inceptors **108a**, **108b**, for example, with an electro-mechanical actuator such as a motor. The bilateral control mechanism **100** results in translation of the inceptors **108a** **108b** corresponding to the rotation of the control member **114**.

(38) With reference to FIGS. 3a-3b, when the right inceptor **108b** of the right control mechanism is actuated during an adjustment process (in which the translational neutral positions of the inceptors are adjusted), e.g. by a pilot, the right inceptor connector **102b** translates along the threaded shaft **103b** of the right conversion mechanism **104b** in the direction indicated (i.e. towards first the plate **110a**). Movement of the right inceptor connector **102b** causes the threaded shaft **103b** of the right conversion mechanism **104b** to rotate about an axis of the threaded shaft **103b** in an anti-clockwise direction as indicated in FIG. 3a (i.e. anti-clockwise). This in turn causes the right differential device **112b** to rotate with the threaded shaft **103b** of the right conversion mechanism **104b**.

Specifically, the sun gear **118b** rotates about an axis of the right differential device **112b** in the same rotational direction as the threaded shaft **103b** of the right conversion mechanism **104b** (i.e. anti-clockwise). Because the right sun gear **118b** engages (e.g. meshes) with the plurality of right planetary gears **120b**, each of the plurality of right planetary gears **120b** also rotates, but in the opposite direction (i.e. clockwise) about an axis of each respective right planetary gear **120b**.

(39) In contrast to the aircraft control process, during an adjustment process, the ring gears **124a**, **124b** are not maintained in position. However, the control member **114** is maintained in position via the control member maintaining device **115**, resulting in the carriers **118a** **118b** being maintained in position. The planetary gears **120a** **120b** are therefore unable to orbit their respective sun gears **118a** **118b**. Rotation of each of the plurality of right planetary gears **120b** about its axis causes the right ring gear **124b** to rotate about an axis of the right differential device **112b** in the same direction as the plurality of right planetary gears **120b** (i.e. clockwise). Because the right ring gear **124b** is coupled to the adjustment member **116**, the adjustment member **116** also rotates, but in the opposite direction (i.e. anti-clockwise).

(40) Rotation of the right ring gear **124b** causes the left ring gear **124a** and the plurality of left planetary gears **120a** coupled to the left ring gear **124a** to rotate in the direction indicated in FIG. 3b (i.e. anticlockwise). This in turn causes the left sun gear **118a**, which engages (e.g. meshes) with the plurality of left planetary gears **120a**, and the threaded shaft **103a** of the left conversion mechanism **104a**, which engages (e.g. meshes) with the left sun gear **118a**, to rotate in the opposite direction (i.e. clockwise). As a result, the left inceptor **108a** translates along the threaded shaft **103a**

of the left conversion mechanism **104a** in the same direction to the actuated right inceptor **108b** (i.e. towards the first plate **110a**).

(41) It will be understood that the adjustment process can also be performed by translating the left inceptor **108a**, which results in corresponding translation of the right inceptor **108b**.

(42) Because the control member **114** is maintained in position during the adjustment process, the translational neutral position of the inceptors **108a**, **108b** can be adjusted.

(43) In other arrangements, rather than a pilot actuating the inceptor(s) **104a**, **104b**, the adjustment member **116** can be actuated (i.e. rotated), e.g. manually by a pilot or by an electro-mechanical actuator such as a motor (not shown). As will be understood, rotation of the adjustment member **116** causes translation of the inceptors **108a**, **108b** via the differential devices **112a**, **112b** as described above. Specifically, actuation of the adjustment member **116** causes the adjustment member **116** to rotate, for example, in an anti-clockwise direction as indicated in FIG. **3b**. This in turn causes the right ring gear **124b**, and the plurality of right planetary gears **120b** engaging (e.g. meshing) with the right ring gear **124b** to rotate in the opposite direction (i.e. clockwise). Because the right sun gear **118b** engages (e.g. meshes) with the plurality of right planetary gears **120b**, the right sun gear **118b** and the threaded shaft **103b** of the right conversion mechanism **104b**, which engages (e.g. meshes) with the right sun gear **118b**, rotate in the direction indicated in FIG. **3b** (i.e. anti-clockwise). As a result, the right inceptor **108b** translates along the threaded shaft **103b** of the right conversion mechanism **104b** towards the first plate **110a**.

(44) During this process, rotation of the right ring gear **124b** causes rotation of the left ring gear **124b**, actuating the left differential device **112a** as described above. This results in corresponding movement of the left inceptor **108a**, and a repeated description of this is omitted.

(45) As illustrated in FIG. **3b**, during the adjustment process, the control member **114** is maintained in position via the control member maintaining device **115**, causing each of the carriers **122a**, **122b** to be maintained in position so that the differential devices **112a**, **112b** undergo fixed carrier motion, as described above. This prevents a simultaneous aircraft control process and adjustment process from occurring.

(46) The adjustment process is performed when the aircraft is stationary. The adjustment process permits the pilot to adjust the translational neutral position of the inceptor connectors **102a**, **102b**, permitting pilots of different stature to be accommodated in the aircraft.

(47) Additionally, the bilateral control mechanism **100** may comprise a stop (not shown) to prevent movement of the control member **114** when the inceptor connector **102a**, **102b** reaches a maximum translation distance during the aircraft control process.

(48) With reference to FIGS. **4-5**, in an alternative arrangement, the left differential device **112a** and the right differential device **112b** are replaced by a single differential device **138**. This arrangement is otherwise the same as that described above.

(49) As illustrated, in this arrangement, the left conversion mechanism **104a** is rigidly coupled to a left gear **140a** and is rotationally coupled to a third plate **110c** via the second end of the threaded shaft **103a** of the left conversion mechanism **104a**. Similarly, the right conversion mechanism **104b** is rigidly coupled to a right gear **140b** and is rotationally coupled to the third plate **110c** via the second end of the threaded shaft **103b** of the right conversion mechanism **104b**. Like the first and second plates **110a**, **110b**, the third plate **110c** provides structural support to the left and right conversion mechanisms **104a**, **104b**, and is fixed to a fixed point on the aircraft (e.g. an aircraft floor). Each of the left and right conversion mechanisms **104a**, **104b** is permitted to rotate relative to the third plate **110c**.

(50) The differential device **138** comprises a front planetary gear **142**, a back planetary gear **144**, and a satellite gear **146**. The planetary gears **142**, **144** rotate about the axis of the control member **114**, which extends through the centre of each of the planetary gears **142**, **144**. The adjustment member **116** extends through the control member **114** in a direction perpendicular to the direction in which the control member **114** extends and rotates about an axis perpendicular to the axis of

rotation of the planetary gears **142**, **144**. The satellite gear **146** is rigidly coupled to the adjustment member **116** and rotates with the adjustment member **116**.

(51) The front planetary gear **142** is a compound gear comprising a first gear **142a** and a second gear **142b** rigidly coupled to each other, and which rotate together about the same axis (i.e. the axis of the control member **114**). Similarly, the back planetary gear **144** is a compound gear comprising a first gear **144a** and a second gear **144b** rigidly coupled to each other, and which rotate together about the same axis (i.e. the axis of the control member **114**). The first gear **142a**, **144a** of each of the planetary gears **142**, **144** has a radius that is greater than the radius of the second gear **142b**, **144b** of each of the planetary gears **142**, **144**. The radius of the first gears **142a**, **144a** are the same and the radius of the second gears **142b**, **144b** are the same.

(52) The outer circumferential edge of the left gear **140a** engages (e.g. meshes) with the outer circumferential edge of the first gear **144a** of the back planetary gear **144**. In a similar manner, the outer circumferential edge of the right gear **140b** engages (e.g. meshes) with the outer circumferential edge of the first gear **142a** of the front planetary gear **142**. The two planetary gears **142**, **144** are also coupled to each other via the satellite gear **146**, which rotates about an axis perpendicular to the axis around which the planetary gears **142**, **144** rotate. Specifically, the outer circumferential edge of the satellite gear **146** engages (e.g. meshes) with the outer circumferential edges of the second gears **142b**, **144b** of each of the planetary gears **142**, **144**. This arrangement allows the left and right conversion mechanisms **104a**, **104b** to be synchronised (e.g. configured such that movement of one of the conversion mechanism **104a**, **104b** causes movement of the other conversion mechanism **104a**, **104b**, as described below).

(53) In this arrangement, the adjustment member maintaining device **117** is a reversible locking mechanism comprising a locking shaft **148** coupled to a mechanical spring **150**, and a disc **152** having a plurality of notches. The disc **152** is rigidly coupled to the adjustment member **116** and rotates with the adjustment member **116**, i.e. around an axis perpendicular to the axis of rotation of the planetary gears **142**, **144**. Each of the plurality of notches is configured to engage with the locking shaft **148** to provide discrete positions in order to lock the inceptor connectors **102a**, **102b** at different translational neutral positions along the threaded shafts **103a**, **103b** of the conversion mechanisms **104a**, **104b** as required.

(54) As described in detail below, during the aircraft control process, the satellite gear **146** provides a rigid coupling between the planetary gears **142**, **144** so that the components of the differential device **138** rotate as a single unit.

(55) With reference to FIGS. **4a-4b**, when the left inceptor **108a** is actuated during an aircraft control process, the threaded shaft **103a** of the left conversion mechanism **104a** rotates about an axis of the threaded shaft **103a** in an anti-clockwise direction. This in turn causes the left gear **140a** to rotate with the threaded shaft **103a** of the left conversion mechanism **104a**. Specifically, the left gear **140a** rotates about an axis of the left conversion mechanism **104a** in the same rotational direction as the threaded shaft **103a** of the left conversion mechanism **104a** (i.e. anti-clockwise). Because the left gear **140a** engages (e.g. meshes) with the first gear **144a** of the back planetary gear **144**, the back planetary gear **144**, and therefore the second gear **144b** of the back planetary gear **144**, also rotate, but in the opposite direction (i.e. clockwise) about an axis of the back planetary gear **144**.

(56) During the aircraft control process, the adjustment member **116** is prevented from rotating about its own axis via the adjustment member maintaining device **117**. This means that the satellite gear **146** cannot rotate and becomes rigidly coupled to the planetary gears **142**, **144**. As such, rotation of the second gear **144b** of the back planetary gear **144** causes the satellite gear **146** to revolve around the axis of the control member **114** in the same direction that the back planetary gear **144** rotates (i.e. clockwise). Because the satellite gear **146** is coupled to the adjustment member **116** and the adjustment member **116** passes through the control member **114**, the control member **114** rotates clockwise about its own axis.

(57) Moreover, since the satellite gear **146** is rigidly coupled to the planetary gears **142**, **144**, movement of the satellite gear **146** around the axis of the control member **114** causes the second gear **142b** of the front planetary gear **142** to rotate in the clockwise direction, and therefore the front planetary gear **142** and the first gear **142a** of the front planetary gear **142** to rotate in the same direction (i.e. clockwise). This in turn causes the right gear **140b** to rotate about an axis of the right conversion mechanism **104b** in the opposite direction (i.e. anti-clockwise). Because the right gear **140b** is coupled to the right conversion mechanism **104b**, the right conversion mechanism **104b** rotates in the anti-clockwise direction. As a result, the right inceptor **108b** translates along the threaded shaft **103b** of the right conversion mechanism **104b** in the opposite direction to the actuated left inceptor **108a** (i.e. towards the second plate **110b**).

(58) During the aircraft control movement process, the adjustment member maintaining device **117** prevents the adjustment member **116** from rotating about its own axis. Specifically, the mechanical spring **150** biases the locking shaft **148** to engage with one of the plurality of notches on the disc **152** in order to prevent rotation of the adjustment member **116** about its own axis. This prevents a simultaneous aircraft control process and adjustment process from occurring.

(59) It will be understood that when the right inceptor **108b** is translated forwards (i.e. towards the first plate **110a**) the threaded shafts **103a**, **103b** of the conversion mechanisms **104a**, **104b** and components of the differential device **138** rotate in opposite directions to those described above. This causes the left inceptor **108a** to translate backwards (i.e. in the opposite direction to the right inceptor **108a** towards the second plate **110b**) and the control member **114** to rotate in the opposite direction to that described above.

(60) The above relates to a manual operation of the bilateral control mechanism **100**. However, the bilateral control mechanism **100** may also be electrically actuated, e.g. by an autopilot system. In such arrangements, the aircraft control process is initiated by actuating (i.e. rotating) the control member **114** directly, rather than one of the inceptors **108a**, **108b**, for example, with an electro-mechanical actuator such as a motor. The bilateral control mechanism **100** results in translation of the inceptors **108a** **108b** corresponding to the rotation of the control member **114**.

(61) As described in detail below, during the adjustment process, the satellite gear **146** is rotationally coupled to the planetary gears **142**, **144** so that the components of the differential device **138** rotate separately.

(62) With reference to FIGS. **5a-5b**, when the right inceptor **108b** of the right control mechanism is actuated during an adjustment process the threaded shaft **103b** of the right conversion mechanism **104b** rotates about an axis of the threaded shaft **103b** in a clockwise direction. This in turn causes the right gear **140b** to rotate with the threaded shaft **103b** of the right conversion mechanism **104b**. Specifically, the right gear **140b** rotates about an axis of the right conversion mechanism **104b** in the same rotational direction as the threaded shaft **103b** of the right conversion mechanism **104b** (i.e. clockwise). Because the right gear **140b** engages (e.g. meshes) with the first gear **142a** of the front planetary gear **142**, the front planetary gear **142**, and therefore the second gear **142b** of the front planetary gear **142**, also rotate, but in the opposite direction (i.e. anti-clockwise) about an axis of the front planetary gear **142**.

(63) In contrast to the aircraft control process, during an adjustment process, the adjustment member **116** can rotate about its own axis. However, the control member **114** is maintained in position via the control member maintaining device **115**. This means that the satellite gear **146** can rotate about the axis perpendicular to the axis of rotation of the planetary gears **142**, **144**, but cannot revolve around the axis of the control member **114**. As such, rotation of the second gear **142b** of the front planetary gear **142** causes the satellite gear **146** to rotate about its own axis in a backward direction (i.e. from the perspective of the pilot looking towards the first plate **110a**). Because the satellite gear **146** is coupled to the adjustment member **116**, the adjustment member **116** rotates with the satellite gear **146**.

(64) Rotation of the satellite gear **146** about its own axis causes the second gear **144b** of the back

planetary gear **144** to rotate in the clockwise direction, and therefore the back planetary gear **144** and the first gear **144a** of the back planetary gear **144** to rotate in the same direction (i.e. clockwise). This in turn causes the left gear **140a**, which engages (e.g. meshes) with the first gear **144a** of the back planetary gear **144**, and the threaded shaft **103a** of the left conversion mechanism **104a** to rotate in the opposite direction (i.e. anti-clockwise). As a result, the left inceptor **108a** translates along the threaded shaft **103a** of the left conversion mechanism **104a** in the same direction to the actuated right inceptor **108b** (i.e. towards the first plate **110a**).

(65) During the adjustment process, the adjustment member maintaining device **117** is disengaged from the adjustment member **116** so that the components of the differential device **138** can rotate separately. Specifically, the locking shaft **148** is pulled toward the first plate **110a**, compressing the mechanical spring **150** and disengaging the locking shaft **148** from the disc **152** so that the adjustment member **116** can rotate about its own axis. If the right inceptor **104b** is not actuated by the pilot, the mechanical spring **119** biases the adjustment member **116** to rotate in a forward direction, causing the position of the right inceptor **104b** to move back towards the pilot. If the right inceptor **104b** is actuated, the mechanical spring **119** becomes twisted. When the adjustment process is complete, the mechanical spring **150** biases the locking shaft **148** to re-engage with one of the plurality of notches, which may be a different notch in accordance with the adjustment.

(66) It will be understood that the adjustment process can also be performed by translating the left inceptor **108a**, which results in corresponding translation of the right inceptor **108b**.

(67) In other arrangements, rather than a pilot actuating the inceptor(s) **104a**, **104b**, the adjustment member **116** can be actuated (i.e. rotated), e.g. manually by a pilot or by an electro-mechanical actuator such as a motor (not shown). As will be understood, rotation of the adjustment member **116** causes translation of the inceptors **108a**, **108b** via the differential device **138** as described above. Specifically, actuation of the adjustment member **116** causes the adjustment member **116** to rotate, for example, in a forward direction as indicated in FIG. **5b**. This in turn causes the satellite gear **146** to rotate in a forward direction, the front planetary gear **142** to rotate in a clockwise direction and the back planetary gear **144** to rotate in the opposite direction (i.e. anti-clockwise). Because the right gear **140b** engages (e.g. meshes) with the first gear **142a** of the front planetary gear **142**, the right gear **140b** and the threaded shaft **103b** of the right conversion mechanism **104b**, which engages (e.g. meshes) with the right gear **140b**, rotate in the anti-clockwise direction. As a result, the right inceptor **108b** translates along the threaded shaft **103b** of the right conversion mechanism **104b** away the first plate **110a**.

(68) During this process, rotation of the back planetary gear **144** causes rotation of the left gear **140a**. This results in corresponding movement of the left inceptor **108a**, and a repeated description of this is omitted.

(69) As illustrated in FIG. **5a-5b**, during the adjustment process, the control member **114** is maintained in position via the control member maintaining device **115**, preventing the satellite gear **146** from rotating about an axis of the control member **114**, as described above. This prevents a simultaneous aircraft control process and adjustment process from occurring.

(70) The threaded shafts **103a**, **103b** of the conversion mechanisms **104a**, **104b** are threaded in opposite directions. Alternatively, the threaded shafts **103a**, **103b** of the conversion mechanisms **104a**, **104b** may be threaded in the same direction. However, in such arrangements, the positions of the control member **114** and adjustment member **116** are reversed.

(71) With reference to FIGS. **6-9**, the bilateral control mechanism **100** further comprises a guiding mechanism. The guiding mechanism prevents the inceptor connectors **102a**, **102b** from rotating around the threaded shafts **103a**, **103b** of the conversion mechanisms **104a**, **104b** when the inceptor connectors **102a**, **102b** translate along the conversion mechanisms **104a**, **104b** during an aircraft control process and/or adjustment process.

(72) As illustrated in FIG. **6**, the guiding mechanism comprises a rail **126a** (in this example, a left rail **126a**) having a first end and a second, opposite end. The first end is coupled to the first plate

110a, and the second end is coupled to the second plate **110b**. The rail **126a** extends parallel to the threaded shaft **103a** of the left conversion mechanism **104a**. The left inceptor connector **102a** is slidably coupled to the left rail **126a**, such that the left inceptor connector **102a** can slide along the left rail **126a** when the left inceptor connector **102a** translates along the threaded shaft **103a** of the left conversion mechanism **104a**. This prevents rotation of the left inceptor **108a** about the threaded shaft **103a** of the left conversion mechanism **104a**, maintaining the left inceptor **108a** in an ergonomic position for the pilot. In this arrangement, the left rail **126a** is positioned below the threaded shaft **103a** of the left conversion mechanism **104a**. However, in other arrangements, the left rail **126a** may be positioned above the inceptor connector **102a** or in between the threaded shafts **103a**, **103b** of the conversion mechanisms **104a**, **104b**. The guiding mechanism further comprises a right rail (not shown), which operates in the same manner for the right inceptor **108b**. Repeated description in relation to the right rail is omitted. The left rail **126a** and the right rail are not coupled to each other.

(73) As illustrated in FIGS. **7a-7c**, in other arrangements, the guiding mechanism comprises a frame for each inceptor **108a**, **108b**. The frame of the left inceptor **108a** and the frame of the right inceptor **108b** are not coupled to each other. The frame comprises a first arm **128a**, **128b** and a second arm **130a**, **130b**, each having a first end and a second, opposite end. The first end of the first arm **128a**, **128a** is pivotally coupled to the inceptor connector **102a**, **102b**, and the second end of the first arm **128a**, **128b** is pivotally coupled to the first end of the second arm **130a**, **130b**. The second end of the second arm **130a**, **130b** is pivotally coupled to a fixed point (e.g. an aircraft floor). This arrangement forms a planar linkage mechanism. The arms **128a**, **128b**, **130a**, **130b** rotate during translation of the inceptors **108a**, **108b**. The arms **128a**, **128b**, **130a**, **130b** are constrained to move in a plane, preventing rotation of the inceptors **108a**, **108b** about the threaded shafts **103a**, **103b** of the conversion mechanisms **104a**, **104b**.

(74) FIG. **8** illustrates a further guiding mechanism comprising a left clasp **132a** and a right clasp **132b**. Each clasp **132a**, **132b** is rotationally coupled to a respective inceptor connector **102a**, **102b**. In contrast to the arrangements described above, the left clasp **132a** is rotatably coupled to the right clasp **132b** via a rod **134**. Again, the clasp **132a**, **132b** provide a planar linkage mechanism. This arrangement prevents rotation of the inceptors **108a**, **108b** about the threaded shafts **103a**, **103b** of the conversion mechanisms **104a**, **104b** by coupling the left inceptor **108a** to the right inceptor **108b**, with the clasps **132a**, **132b** constrained to move in a plane, in particular a horizontal plane.

(75) With reference to FIGS. **9a-9c**, in alternative arrangements, the guiding mechanism comprises a hinge having a left arm **134a** and a right arm **134b**. The left arm **134a** comprises a first end and a second, opposite end. The first end of the left arm **134a** is pivotally coupled to the left inceptor connector **102a** and the second end of the left arm **134a** is pivotally coupled to a first end of the right arm **134b**. As with the arrangement described in FIG. **8**, this arrangement prevents rotation of the inceptors **108a**, **108b** about the threaded shafts **103a**, **103b** of the conversion mechanisms **104a**, **104b** by coupling the left inceptor **108a** to the right inceptor **108b** using a planar linkage mechanism.

(76) The bilateral control mechanism **100** is preferably a rudder control mechanism.

(77) In some embodiments, there is provided an aircraft comprising the bilateral control mechanism **100**. The aircraft may comprise a controller (not shown). The controller may be configured to determine the translational neutral position of the inceptor connectors **102a**, **102b**. For example, the controller may detect the rotational position of the adjustment member **116** and then determine the translational neutral position of the inceptor connectors **102a**, **102b** based on the rotational position of the adjustment member **116**. In this case, the controller may directly detect the rotational position of the adjustment member **116** via a sensor, e.g. a RVDT sensor, a hall effect sensor, an optical sensor or other equivalent. Alternatively, the controller may indirectly detect the rotational position of the adjustment member **116** based on data related to the bilateral control mechanism **100**.

(78) Likewise, the controller may be configured to determine the rotational position of the control member **114** from a translational neutral position. In this case, the controller may directly detect the rotational position of the control member **114** via a sensor, e.g. a RVDT sensor, a hall effect sensor, an optical sensor or other equivalent. Alternatively, the controller may indirectly detect the rotational position of the control member **114** based on data related to the bilateral control mechanism **100**.

(79) For example, the control member **114** may comprise a rotation sensor (not shown). The rotation sensor may detect rotation of the control member **114** and output a signal (e.g. an image of the current rotational position of the control member **114**).

(80) In these embodiments, the controller outputs an aircraft control signal based on the translational neutral position of the inceptor connectors **102a**, **102b** and the rotational position of the control member **114**. When the control member **114** (and the inceptor connectors **102a**, **102b**) are at the translation neutral position, the aircraft control signal is zero.

(81) Although not illustrated, there may be provided a unilateral control mechanism. In this arrangement, the inceptor **108a**, **108b** may comprise a side stick unit or a gas throttle assembly, i.e. the control mechanism may be hand-operated.

(82) Various aspects of the control mechanism disclosed in the various embodiments may be used alone, in combination, or in a variety of arrangements not specifically discussed in the embodiments described in the foregoing and this disclosure is therefore not limited in its application to the details and arrangement of components set forth in the foregoing description or illustrated in the drawings. For example, aspects described in one embodiment may be combined in any manner with aspects described in other embodiments. Although particular embodiments have been shown and described, it will be obvious to those skilled in the art that changes and modifications may be made without departing from the invention in its broader aspects. The scope of the following claims should not be limited by the embodiments set forth in the examples, but should be given the broadest reasonable interpretation consistent with the description as a whole.

Claims

1. A control mechanism for an aircraft, the control mechanism comprising: a conversion mechanism having a translatable part and a rotatable part, the translatable part being reversibly translatable; an inceptor connector connected to the translatable part of the conversion mechanism; a differential device connected to the rotatable part of the conversion mechanism, the conversion mechanism being configured to convert translational motion of the inceptor connector to rotational motion of the differential device; an adjustment member connected to the differential device; and a control member connected to the differential device; wherein the differential device is configured such that the adjustment member is maintainable in position during an aircraft control process to permit: translation of the inceptor connector from a translational neutral position; and corresponding movement of the control member to control the aircraft through the differential device; and wherein the differential device is configured such that the control member is maintainable in position during an adjustment process to permit: translation of the inceptor connector; and corresponding movement of the adjustment member through the differential device to adjust the translational neutral position.

2. The control mechanism as claimed in claim 1, further comprising: an adjustment member maintaining device, wherein the adjustment member maintaining device is configured to, during the aircraft control process, resist movement of the adjustment member; and a control member maintaining device, the control member maintaining device being configured to, during the adjustment process, resist movement of the control member.

3. The control mechanism as claimed in claim 2, wherein the adjustment member maintaining device is configured to, during the adjustment process, provide discrete positioning of the inceptor

connector on the conversion mechanism to allow variation of the translational neutral position.

4. The control mechanism as claimed in claim 3, wherein the control member maintaining device comprises a control member locking device configured to, during the adjustment process, lock movement of the control member.

5. The control mechanism as claimed in claim 1, wherein the control member is rotatable during an aircraft control process, and the adjustment member is rotatable during an adjustment process.

6. The control mechanism as claimed in claim 1, wherein the differential device comprises an epicyclic gear train.

7. The control mechanism as claimed in claim 6, wherein the epicyclic gear train comprises: a sun gear, wherein the rotatable part of the conversion mechanism is coupled to the sun gear such that the rotatable part of the conversion mechanism rotates with the sun gear.

8. The control mechanism as claimed in claim 7, wherein the epicyclic gear train comprises a carrier, wherein the control member is coupled to the carrier such that the carrier rotates with the control member during the aircraft control process.

9. The control mechanism as claimed in claim 6, wherein the epicyclic gear train comprises a ring gear, wherein the adjustment member is coupled to the ring gear such that the ring gear rotates with the adjustment member during the adjustment process.

10. The control mechanism as claimed in claim 1, wherein the conversion mechanism is configured to be inclined relative to a longitudinal axis of an aircraft when installed on the aircraft.

11. The control mechanism as claimed in claim 1, wherein the translatable part of the conversion mechanism is a nut and the rotatable part of the conversion mechanism is a screw, the differential device being actuatable to rotate the screw, upon translation of the inceptor connector.

12. The control mechanism as claimed in claim 1, further comprising a guiding mechanism, the guiding mechanism configured to maintain an orientation of the inceptor connector during translation of the inceptor connector.

13. The control mechanism as claimed in claim 1, further comprising: a stop configured to prevent movement of the control member when the inceptor connector reaches a maximum translation distance during the aircraft control process.

14. A bilateral control mechanism comprising: a first control mechanism; and a second control mechanism; wherein the first and second control mechanisms are each as claimed in claim 1.

15. A bilateral control mechanism as claimed in claim 14, wherein the differential device of the first control mechanism and the differential device of the second mechanism are synchronised such that: on translation of the inceptor connector of the first control mechanism during the aircraft control process the inceptor connector of the second control mechanism translates in an opposing direction to the inceptor connector of the first control mechanism; and on translation of the inceptor connector of the first control mechanism during the adjustment process the inceptor connector of the second control mechanism translates in the same direction as the inceptor connector of the first control mechanism.

16. A bilateral control mechanism as claimed in claim 15, wherein the control member of the first control mechanism and the control member of the second control mechanism are the same control member; and/or wherein the adjustment member of the first control mechanism and the adjustment member of the second control mechanism are the same adjustment member; and/or wherein the differential device of the first control mechanism and the differential device of the second control mechanism are the same differential device.
