

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405602
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Fujii; Norisuke

Information processing apparatus, information processing system, and information processing method

Abstract

Even if there is no similar record of plan generation for a manufacturing line, a logic of production scheduling is appropriately configured. An information processing apparatus stores a graph showing a manufacturing line configured to manufacture a plurality of items, task information indicating graphs showing basic modules and tasks of production scheduling, and a rule for selecting a logic of the production scheduling based on the tasks, identifies graphs showing basic modules included in the graph showing the manufacturing line by referring to the task information, extracts tasks corresponding to the identified graphs of the basic modules, selects a logic corresponding to the extracted tasks by referring to the rule, and outputs information indicating the selected logic.

Inventors:	Fujii; Norisuke (Tokyo, JP)
Applicant:	Hitachi, Ltd. (Tokyo, JP)
Family ID:	87161744
Assignee:	Hitachi, Ltd. (Tokyo, JP)
Appl. No.:	17/984567
Filed:	November 10, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230229147 A1	Jul. 20, 2023

Foreign Application Priority Data

JP	2022-006932	Jan. 20, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: G05B19/418 (20060101); G06T11/20 (20060101)

U.S. Cl.:

CPC G05B19/41865 (20130101); G06T11/206 (20130101); G05B2219/32281 (20130101)

Field of Classification Search

CPC: G05B (19/41865); G05B (2219/32281); G06T (11/206)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2017/0199518	12/2016	Stoeckel	N/A	G05B 19/41885
2019/0129387	12/2018	Mohanty	N/A	G06Q 10/063

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2021-68010	12/2020	JP	N/A

Primary Examiner: Collins; Gary

Attorney, Agent or Firm: Crowell & Moring LLP

Background/Summary

CLAIM OF PRIORITY

(1) The present application claims priority from Japanese patent application JP 2022-006932 filed on Jan. 20, 2022, the content of which is hereby incorporated by reference into this application.

BACKGROUND OF THE INVENTION

1. Field of the Invention

(2) The present invention relates to an information processing apparatus, an information processing system, and an information processing method.

2. Description of the Related Art

(3) Examples of the related art of the field of the invention include JP-A-2021-68010 (Patent Literature 1). This publication discloses that “a mathematical model representing a feature of a plan that has been generated and used before implementation of a plan generation system in a factory where the system is to be constructed from now on is compared with a mathematical model corresponding to processing of a source code that is created when the plan generation system is already constructed in another factory, and when it is determined that the mathematical models are the same, a past source code corresponding to the mathematical model is reused” (see the abstract).

(4) In the technique disclosed in Patent Literature 1, the number of man-hours for source code development is reduced by reusing the source code created in the past of the plan generation system, but it is not possible to cope with plan generation of a new case having no similar record in the past. In addition, since there are innumerable process flows in a manufacturing line in a factory

and there are innumerable logics for production scheduling corresponding to the process flows, there are many cases having no similar record in the past.

SUMMARY OF THE INVENTION

(5) Therefore, an aspect of the present invention appropriately configures a logic of production scheduling even if there is no similar record of plan generation for a manufacturing line.

(6) In order to solve the above problems, an aspect of the present invention adopts the following configuration. An information processing apparatus includes a processor and a memory. The memory stores a graph showing a manufacturing line configured to manufacture a plurality of items, task information indicating graphs showing basic modules and tasks of production scheduling, and a rule for selecting a logic of the production scheduling based on the tasks. The processor identifies graphs showing basic modules included in the graph showing the manufacturing line by referring to the task information, extracts tasks corresponding to the identified graphs of the basic modules by referring to the task information, selects a logic corresponding to the extracted tasks by referring to the rule, and outputs information indicating the selected logic.

Advantageous Effects

(7) According to an aspect of the present invention, a logic of production scheduling is appropriately configured even if there is no similar record of plan generation for a manufacturing line.

(8) Problems, configurations, and effects other than those described above will be clarified in the description of the following embodiment.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a block diagram illustrating a configuration example of a production scheduling system according to a first embodiment;

(2) FIG. 2 is a table illustrating an example of process flow information according to the first embodiment;

(3) FIG. 3 is a table illustrating an example of basic module information according to the first embodiment;

(4) FIG. 4 is a diagram illustrating an example of a logic selection rule according to the first embodiment;

(5) FIG. 5 is a table illustrating an example of implementation information according to the first embodiment;

(6) FIG. 6 is a table illustrating an example of scheduling logic configuration result information according to the first embodiment;

(7) FIG. 7 is a flowchart illustrating an example of logic configuration processing performed by a logic configuration apparatus according to the first embodiment;

(8) FIG. 8 is an explanatory diagram illustrating an outline of graphing of process flows and merging processing of graphs of the process flows according to the first embodiment;

(9) FIG. 9 is an explanatory diagram illustrating an outline of basic module identifying processing and task extraction processing according to the first embodiment;

(10) FIG. 10 is a diagram illustrating an example of a display screen displayed on a display device of the logic configuration apparatus according to the first embodiment; and

(11) FIG. 11 is a diagram illustrating an example of a detail display screen displayed on the display device of the logic configuration apparatus according to the first embodiment.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

(12) Hereinafter, an embodiment of the invention will be described in detail with reference to the

drawings. In the present embodiment, the same components are denoted by the same reference signs in principle, and a repeated description thereof will be omitted. Note that the present embodiment is merely an example for implementing the present invention and does not limit the technical scope of the present invention.

First Embodiment

(13) FIG. 1 is a block diagram illustrating a configuration example of a production scheduling system. A production scheduling system **500** includes, for example, a logic configuration apparatus **100**, a production scheduling apparatus **200**, and a process information management apparatus **300**, which are connected via a network **400** such as the Internet.

(14) The process information management apparatus **300** stores a process flow (a series of processes including one or more processes) for product production for each item, and transmits the process flow to the logic configuration apparatus **100**. The logic configuration apparatus **100** configures a logic for production scheduling for producing items, based on the process flow for each item received from the process information management apparatus **300**, and transmits implementation information for implementing the configured logic to the production scheduling apparatus **200**. The logic configuration apparatus **100** may receive an input of information indicating process flows of items from a user of the logic configuration apparatus **100**.

(15) The production scheduling apparatus **200** formulates a production schedule for items based on the logic indicated by the implementation information received from the logic configuration apparatus **100**. The production scheduling apparatus **200** stores delivery times of products of items and processing time required to produce the products of the items.

(16) The logic configuration apparatus **100** is implemented by, for example, a computer including a central processing unit (CPU) **110**, a memory **120**, an auxiliary storage device **130**, a display device **140**, an input device **150**, and a communication device **160**.

(17) The CPU **110** includes a processor and executes a program stored in the memory **120**. The memory **120** includes a read only memory (ROM), which is a nonvolatile storage element, and a random access memory (RAM), which is a volatile storage element. The ROM stores an invariable program (for example, a basic input/output system (BIOS)) and the like. The RAM is a high-speed and volatile storage element such as a dynamic random access memory (DRAM), and temporarily stores a program to be executed by the CPU **110** and data to be used when the program is executed.

(18) The auxiliary storage device **130** is, for example, a large-capacity and non-volatile storage device such as a magnetic storage device (hard disk drive (HDD)) or a flash memory (solid state drive (SSD)), and stores a program to be executed by the CPU **110** and data to be used when the program is executed. That is, the program is read from the auxiliary storage device **130**, loaded into the memory **120**, and executed by the CPU **110**.

(19) The display device **140** is a device such as a display or a printer that outputs an execution result of a program in a form that can be visually recognized by an operator. The input device **150** is a device such as a keyboard or a mouse that receives an input from the operator.

(20) The communication device **160** is a network interface device that controls communication with other devices according to a predetermined protocol. The communication device **160** may include a serial interface such as a universal serial bus (USB).

(21) A part or all of the programs executed by the CPU **110** may be provided to the logic configuration apparatus **100** via a removable medium (CD-ROM, flash memory, or the like) that is a non-transitory storage medium, or from an external computer including a non-transitory storage device via a network, and may be stored in the non-volatile auxiliary storage device **130** that is a non-transitory storage medium. Therefore, the logic configuration apparatus **100** may have an interface for reading data from a removable medium. The same applies to the production scheduling apparatus **200** and the process information management apparatus **300**.

(22) The logic configuration apparatus **100** is a computer system implemented on a physically single computer or implemented on a plurality of logically or physically constituted computers, and

may operate in separate threads on the same computer or may operate on a virtual computer constructed on a plurality of physical computer resources. The same applies to the production scheduling apparatus **200** and the process information management apparatus **300**. At least two of the logic configuration apparatus **100**, the production scheduling apparatus **200**, and the process information management apparatus **300** may be integrated.

(23) The CPU **110** includes, for example, a process flow analysis unit **111**, a basic module allocation unit **112**, a task extraction unit **113**, a logic configuration unit **114**, an implementation unit **115**, and a result display unit **116**. The process flow analysis unit **111** analyzes process flows of items and generates a graph showing a manufacturing line for manufacturing all items. The basic module allocation unit **112** identifies basic modules included in the graph showing the manufacturing line.

(24) The task extraction unit **113** extracts scheduling-related tasks corresponding to the identified basic modules. The logic configuration unit **114** selects a logic based on the extracted tasks. The implementation unit **115** generates data for implementing the selected logic on the production scheduling apparatus **200**. The result display unit **116** displays, on the display device **140**, execution results of programs executed by functional units.

(25) For example, the CPU **110** functions as the process flow analysis unit **111** by operating according to a process flow analysis program loaded into the memory **120**, and functions as the basic module allocation unit **112** by operating according to a basic module allocation program loaded into the memory **120**. The relationship between a program and a functional unit applies to the other functional units provided in the CPU **110**.

(26) A part or all of the functions of the functional units provided in the CPU **110** may be implemented using hardware such as an application specific integrated circuit (ASIC) or a field-programmable gate array (FPGA).

(27) The auxiliary storage device **130** stores, for example, process flow information **131**, basic module information **132**, a logic selection rule **133**, implementation information **134**, and scheduling logic configuration result information **135**.

(28) The process flow information **131** indicates a process flow for manufacturing products of items. The basic module information **132** indicates a graph of a basic module and a task corresponding to the basic module. The logic selection rule **133** is a rule for selecting a logic based on a task. The implementation information **134** includes information for implementing a logic on the production scheduling apparatus **200** (information indicating specifications of the production scheduling apparatus **200**). The scheduling logic configuration result information **135** indicates a selected logic.

(29) A part or all pieces of the information stored in the auxiliary storage device **130** may be stored in the memory **120**, may be stored in the production scheduling apparatus **200** or the process information management apparatus **300**, or may be stored in an external database connected to the production scheduling system **500**.

(30) In the present embodiment, information used by a data management system does not depend on a data structure and may be expressed in any data structure. For example, a data structure appropriately selected from a table, a list, a database, and a queue can store information.

(31) FIG. 2 is a table illustrating an example of the process flow information **131**. The process flow information **131** includes, for example, an item field **1311**, a process number field **1312**, a process field **1313**, and a use resource field **1314**. The item field **1311** holds information for identifying an item of a product. The process number field **1312** holds a process number indicating an order of processes for producing products. The process field **1313** holds information for identifying a process. The use resource field **1314** holds information indicating a use resource that is a resource used in the process.

(32) In the example in FIG. 2, in order to manufacture a product of an item B, it is necessary to perform a “cutting” process using a “processing machine” corresponding to a process number “1”,

a “bending” process using a “bending machine a” corresponding to a process number “2”, an “assembling” process by a “worker” corresponding to a process number “3”, and a “painting” process using a piece of “painting equipment” corresponding to a process number “4” in the order of the process numbers.

(33) In the process flow information **131**, a plurality of records having the same process number of the same item may be stored. In this case, any one of the processes indicated by the plurality of records having the same process number of the same item may be performed. In the example in FIG. 2, the “bending” process using any one of the “bending machine a”, a “bending machine b”, a “bending machine c”, and a “bending machine d” is performed, whereby a product of an item A can be manufactured.

(34) FIG. 3 is a table illustrating an example of the basic module information **132**. The basic module information **132** includes, for example, a basic module ID field **1321**, a graph field **1322**, and a task field **1323**. The basic module ID field **1321** holds an ID for identifying a basic module. The graph field **1322** holds information for identifying a directed graph that is a basic module. Specifically, for example, the graph field **1322** holds an adjacency matrix, a connection matrix, or a Laplacian matrix of a directed graph. The task field **1323** holds information indicating a task corresponding to a basic module.

(35) The “delivery time margin priority”, which is a task corresponding to a basic module having a basic module ID of “1”, is a task indicating that production of a product of an item having a large (or small) delivery time margin (the number of remaining days until the delivery time/processing time required to produce the product of the item) is preferentially started. The “processing time priority”, which is a task corresponding to a basic module having a basic module ID of “2”, is a task indicating that production of a product of an item requiring a short (or long) processing time for product production is preferentially started. The same task may correspond to different basic modules in the basic module information **132**.

(36) FIG. 4 is a diagram illustrating an example of the logic selection rule **133**. The logic selection rule **133** is a rule for selecting a logic based on a task, and is defined by, for example, an if statement having an obtained task as a condition. In the example in FIG. 4, “random” is selected as a logic when “delivery time margin priority” is not obtained as a task, “sorting in order of delivery time” is selected as a logic when “delivery time margin priority” is obtained as a task and “shortest processing time priority” is not obtained as a task, and “two-stage sorting” is selected as a logic when “delivery time margin priority” is obtained as a task and “shortest processing time priority” is obtained as a task.

(37) “Random” indicates that an introduction order of products of items (that is, an order in which production is started) is random. “Sorting in order of delivery time” indicates that an introduction order of the products of the items is an order from the nearest delivery time to the farthest delivery time (or a reverse order from the farthest delivery time to the nearest delivery time). The “two-stage sorting” indicates that an introduction order of the products of the items is an order in which the products of the items are sorted in an order from the nearest delivery time to the farthest delivery time (or a reverse order from the farthest delivery time to the nearest delivery time), and further products of items having the same delivery time are sorted in an ascending order (or in a descending order) of the processing time. Alternatively, the “two-stage sorting” indicates that an introduction order of the products of the items is an order in which the products of the items are sorted in an ascending order (or in a descending order) of the processing time, and further products of items having the same processing time are sorted in an order from the nearest delivery time to the farthest delivery time (or a reverse order from the farthest delivery time to the nearest delivery time).

(38) Although the logic selection rule **133** is defined by a simple if statement in the example in FIG. 4, the logic selection rule **133** may be defined by a predetermined probabilistic model that receives an obtained task and outputs a logic. In addition, for example, the model may be subjected

to learning by giving a correct logic for the obtained task by a user. In addition, the logic selection rule **133** may be programmed in a program that implements the logic configuration unit **114** without being stored in the auxiliary storage device **130**.

(39) FIG. 5 is a table illustrating an example of the implementation information **134**. The implementation information **134** includes, for example, a file field **1341**, a format field **1342**, and a writing position field **1343**. The file field **1341** holds information indicating a storage location and a file name of a file to which a logic is to be written. The information is held by the production scheduling apparatus **200**. The format field **1342** holds information indicating a format of the file indicated by the file field **1341**. The writing position field **1343** holds information indicating a position in the file indicated by the file field **1341** where the logic is to be written.

(40) FIG. 6 is a table illustrating an example of the scheduling logic configuration result information **135**. The scheduling logic configuration result information **135** includes, for example, a basic module ID field **1351**, a task field **1352**, and a logic field **1353**. The basic module ID field **1351** holds a basic module ID allocated by the basic module allocation unit **112**. The task field **1352** holds information indicating a task extracted by the task extraction unit **113**. The logic field **1353** holds information indicating a logic selected by the logic configuration unit **114**.

(41) FIG. 7 is a flowchart illustrating an example of logic configuration processing performed by the logic configuration apparatus **100**. It is assumed that the process flow information **131**, the basic module information **132**, the logic selection rule **133**, and the implementation information **134** are set before the logic configuration processing is started. The process flow analysis unit **111** refers to the process flow information **131** and graphs process flows of items (**S701**). Specifically, for example, for each item of the process flow information **131**, the process flow analysis unit **111** acquires a record, and generates a directed graph (by, for example, a graph representation method in the graph field **1322** of the basic module information **132**) in which each of use resources indicated by the record is set as a node, and in which connection of a use resource of a previous process indicated by a process number to a use resource of a subsequent process is set as an edge (an edge directed from the node indicating the use resource of the previous process to the node indicating the use resource of the subsequent process).

(42) The process flow analysis unit **111** merges directed graphs indicating the process flows of the items generated in step **S701** to generate a directed graph showing a manufacturing line for producing all the items (**S702**). In addition, the processing of step **S701** and step **S702** may be omitted, that is, the logic configuration apparatus **100** may receive the graph of the manufacturing line from the process information management apparatus **300** in advance.

(43) FIG. 8 is an explanatory diagram illustrating an outline of the graphing of the process flows in step **S701** and the merging processing of the graphs of the process flows in step **S702**. A graph **801** is a directed graph showing a process flow of the item A indicated by the process flow information **131** in FIG. 2, and a graph **802** is a directed graph showing a process flow of the item B indicated by the process flow information **131** in FIG. 2.

(44) In FIG. 8, a node “a” indicates a “bending machine a”, a node “b” indicates a “bending machine b”, a node “c” indicates a “bending machine c”, a node “d” indicates a “bending machine d”, a node “PM” indicates a “processing machine”, a node “WK” indicates a “worker”, and a node “PE” indicates a piece of “painting equipment”.

(45) The process flow analysis unit **111** assigns an edge (a start point is not defined), which has a resource of each process as an end point, to a process flow having only one process number such as the process flow in the graph **801** of the process flow of the item A.

(46) When the process flow analysis unit **111** determines that there are a plurality of process flows that include a common process by referring to the process flow information **131**, the process flow analysis unit **111** merges graphs of the plurality of process flows to generate a graph showing a manufacturing line including the graphs of the plurality of process flows.

(47) Specifically, for example, for a plurality of graphs including a common process, the process

flow analysis unit **111** generates a graph showing a manufacturing line by connecting, with an edge (the edge is directed from an earlier process to a later process), nodes corresponding to a use resource of the common process and nodes corresponding to a use resource of one process immediately before the common process and a use resource of one process immediately after the common process in a graph of another process flow.

(48) In the example in FIG. **8**, the process flow analysis unit **111** merges the graph **801** of the process flow of the item A and the graph **802** of the process flow of the item B to generate a graph **803** indicating a manufacturing line for manufacturing the item A and the item B. The graph **803** is a graph obtained by merging via “bending”, which is a process commonly included in the process flow indicated by the graph **801** and the process flow indicated by the graph **802**, and includes the graph **801** and the graph **801**. Note that both the graph **801** and the graph **802** include the node indicating the “bending machine a”, but in the graph **803** obtained by the merging, overlapping nodes are expressed as one node (that is, the graph **803** includes only one node of the “bending machine a”).

(49) Note that the process flow analysis unit **111** does not merge graphs of process flows that do not include a common process, and treats the graphs as separate manufacturing lines. That is, when there are a plurality of process flows that do not include a common process, the process flow analysis unit **111** generates a plurality of directed graphs indicating manufacturing lines.

(50) In the example described above, when it is determined that there are a plurality of process flows including a common process, the process flow analysis unit **111** generates a graph showing a manufacturing line and including graphs of the plurality of process flows. Alternatively, only when it is determined that there are a plurality of process flows including a common process and a common use resource, the process flow analysis unit **111** may generate a graph showing a manufacturing line and including graphs of the plurality of process flows. That is, in this case, the process flow analysis unit **111** does not merge graphs of process flows that do not include a common process and a common use resource, and treats the graph as separate manufacturing lines.

(51) Return to the description of FIG. **7**. Subsequently, the basic module allocation unit **112** identifies basic modules (graphs) included in the directed graph of the manufacturing line by referring to the basic module information **132** (**S703**). Specifically, for example, the basic module allocation unit **112** identifies the basic modules (graphs) included in the directed graph of the manufacturing line by solving a subset covering problem in which the basic modules are subgraphs. The basic module allocation unit **112** stores basic module IDs of the identified basic modules in the scheduling logic configuration result information **135**.

(52) The task extraction unit **113** extracts tasks corresponding to the basic module IDs identified in step **5703** from the basic module information **132**, and stores the extracted tasks in the scheduling logic configuration result information **135** (**S704**).

(53) FIG. **9** is an explanatory diagram illustrating an outline of the basic module identifying processing in step **5703** and the task extraction processing in step **5704**. In the example in FIG. **9**, a basic module **901** with a basic module ID “1” is a directed graph that includes a node **9011**, a node **9012**, and a node **9013** and that includes an edge directed from the node **9011** to the node **9012** and an edge directed from the node **9011** to the node **9013**.

(54) In the example in FIG. **9**, a basic module **902** with a basic module ID “2” is a directed graph that includes a node **9021**, a node **9022**, a node **9023**, and a node **9024** and that includes an edge directed from the node **9021** to the node **9023**, an edge directed from the node **9022** to the node **9023**, and an edge directed from the node **9023** to the node **9024**.

(55) In the example in FIG. **9**, since the graph **803** indicating the manufacturing line includes the basic module **901** and the basic module **902**, the basic module allocation unit **112** identifies the basic module **901** and the basic module **902**.

(56) The basic module allocation unit **112** may not necessarily extract all the basic modules included in the graph **803** indicating the manufacturing line. Specifically, for example, a priority

order of the basic modules may be determined in advance in the basic module information **132**, and the basic module allocation unit **112** may extract basic modules included in the graph **803** indicating the manufacturing line according to the priority order, for example, with a predetermined number as an upper limit.

(57) In the example in FIG. **9**, a node **8031** is connected to four nodes in the graph **803** indicating the manufacturing line, but since the basic module **901** is included as a part of (matches with a part of) the graph **803**, in such a case, the basic module allocation unit **112** determines that the basic module **901** is included in the graph **803**. The basic module allocation unit **112** may determine that the graph showing the manufacturing line includes a basic module only when it is determined that the graph showing the manufacturing line includes a portion completely matching the basic module.

(58) In the example in FIG. **9**, in the basic module information **132**, a task corresponding to the basic module **901** is “delivery time margin priority” and a task corresponding to the basic module **902** is “processing time priority”, and thus the task extraction unit **113** extracts “delivery time margin priority” and “processing time priority” as tasks.

(59) Return to the description of FIG. **7**. Subsequently, the logic configuration unit **114** selects a logic corresponding to the extracted task according to the logic selection rule **133**, and stores the selected logic in the scheduling logic configuration result information **135** (S705).

(60) The logic configuration unit **114** may display the extracted task and the selected logic on the display device **140**, and a user of the logic configuration apparatus **100** may input a correct logic via the input device **150**. When the logic configuration unit **114** determines that the selected logic and the correct logic are different from each other, the logic configuration unit **114** may learn the logic selection rule **133** based on the extracted task and the correct logic. Further, in this case, the logic configuration unit **114** stores the input correct logic in the logic field **1353** of the scheduling logic configuration result information **135**.

(61) The implementation unit **115** generates implementation-dedicated data (S706), transmits the generated implementation-dedicated data to the production scheduling apparatus **200**, and ends the logic configuration processing. Specifically, for example, the implementation unit **115** includes a record of the scheduling logic configuration result information **135** and a file name, a format, and a writing position indicated by the implementation information **134** in the implementation-dedicated data.

(62) The production scheduling apparatus **200** writes the logic indicated by a record of the scheduling logic configuration result information **135** into a file indicated by the received implementation-dedicated data (that is, implements the logic), and formulates a production schedule of the items based on the logic, delivery time of the products of the items (as necessary), and processing time required to produce the products of the items.

(63) The result display unit **116** may display a display screen and a detailed result display screen, which will be described later, on the display device **140** according to the execution of the processing in FIG. **7**.

(64) In the above example, an example has been described in which the basic module, the process flow, and the manufacturing line are represented by a directed graph. Alternatively, the basic module, the process flow, and the manufacturing line may be represented by an undirected graph (the edge of the graph in the above example may be an undirected edge).

(65) FIG. **10** is an example of a display screen displayed on the display device **140** of the logic configuration apparatus **100**. A display screen **1000** includes, for example, a process flow display area **1010** and a scheduling logic configuration result display area **1020**. The display screen **1000** may be displayed on a display device provided in the production scheduling apparatus **200**.

(66) The process flow display area **1010** includes, for example, a process flow information input area **1011**, a manufacturing line display area **1012**, a registration button **1013**, and an analysis button **1014**. The scheduling logic configuration result display area **1020** includes, for example, a

logic display area **1021** and a detail display button **1022**.

(67) The process flow information input area **1011** is an area for the user of the logic configuration apparatus **100** to input a process flow via the input device **150**. When the registration button **1013** is selected, the process flow input to the process flow information input area **1011** is stored into the process flow information **131**.

(68) When the analysis button **1014** is selected, the processing of steps **5701** to **5706** are executed, a graph showing a manufacturing line generated in step **5702** is displayed in the manufacturing line display area **1012**, and further a logic selected in step **5705** is displayed in the logic display area **1021**. Accordingly, the user can grasp the manufacturing line for manufacturing the products of all the items and the selected logic. When the detail display button **1022** is selected after the analysis button **1014** is selected, a detail display screen to be described later is displayed.

(69) FIG. **11** is a diagram illustrating an example of a detail display screen displayed on the display device **140** of the logic configuration apparatus **100**. A detail display screen **1100** includes, for example, a basic module display area **1110** and a scheduling logic configuration result detail display area **1120**. The detail display screen **1100** may be displayed on a display device provided in the production scheduling apparatus **200**.

(70) A basic module identified in step **S703** is displayed in the basic module display area **1110**. In the scheduling logic configuration result detail display area **1120**, information of the scheduling logic configuration result information **135** is displayed.

(71) As described above, the logic configuration apparatus **100** according to the present embodiment identifies a basic module included in a graph of a manufacturing line that is obtained by merging graphs indicating process flows of items, extracts a task corresponding to the identified basic module, and automatically selects a logic based on the extracted task.

(72) Accordingly, the logic configuration apparatus **100** can appropriately determine a task and a logic corresponding to a manufacturing line for manufacturing a product of an item, without defining in advance tasks and logics corresponding to process flows of innumerable items and innumerable manufacturing lines and without referring to operation records of production scheduling for similar manufacturing lines. In addition, with the logic configuration apparatus **100** according to the present embodiment, a task and a logic corresponding to a manufacturing line for manufacturing a product of an item can be appropriately determined, even if an operator is not a skilled person in logic design of the production scheduling. In addition, the logic configuration apparatus **100** according to the present embodiment can associate a process flow with a logic depending on a task, and thus can improve the reusability of the logic.

(73) The invention is not limited to the embodiment described above, and includes various modifications. For example, the embodiment described above has been described in detail for easy understanding of the invention, and the invention is not necessarily limited to those including all of the configurations described above. A part of a configuration according to one embodiment can be replaced with a configuration according to another embodiment, and a configuration according to one embodiment can be added to a configuration according to another embodiment. A part of a configuration according to one embodiment may be added, deleted, or replaced with another configuration.

(74) A part or all of the above configurations, functions, processing units, processing methods and the like may be implemented by hardware by, for example, designing using an integrated circuit. The above configurations, functions, and the like may be implemented by software by interpreting and executing programs for implementing functions by the processor. Information such as a program, a table, and a file for implementing the functions can be stored in a recording device such as a memory, a hard disk, or a solid state drive (SSD), or in a recording medium such as an IC card, an SD card, or a DVD.

(75) Control lines or information lines indicate what is considered necessary for description, and

not all the control lines or information lines are necessarily shown for a product. In practice, it may be considered that almost all configurations are connected to each other.

Claims

1. An information processing apparatus comprising: a processor; and a memory, wherein the memory stores a graph showing a manufacturing line configured to manufacture a plurality of items, task information indicating graphs showing basic modules and tasks of production scheduling, and a rule for selecting a logic of the production scheduling based on the tasks, and the processor identifies graphs showing basic modules included in the graph showing the manufacturing line by referring to the task information, extracts tasks corresponding to the identified graphs of the basic modules by referring to the task information, wherein the tasks include at least one of a delivery time margin priority and a processing time priority, selects a logic corresponding to the extracted tasks by referring to the rule, and outputs information indicating the selected logic.
2. The information processing apparatus according to claim 1, wherein the memory stores process flow information indicating process flows for manufacturing the plurality of items, and the processor generates graphs showing the process flows of the plurality of items by referring to the process flow information, and generates the graph showing the manufacturing line by merging the generated graphs showing the process flows of the plurality of items.
3. The information processing apparatus according to claim 1, wherein the information processing apparatus is connected to an input device and a display device, and the processor displays the extracted tasks and the selected logic on the display device, receives an input of a correct logic via the input device, and learns the rule based on the extracted tasks and the correct logic when it is determined that the selected logic and the correct logic are different from each other.
4. The information processing apparatus according to claim 1, wherein the processor generates data for outputting information indicating the graph showing the manufacturing line and the selected logic to a display device.
5. The information processing apparatus according to claim 1, wherein the processor generates data for outputting information indicating the identified graphs of the basic modules and the extracted tasks to a display device.
6. An information processing system comprising: a logic configuration apparatus; and a production scheduling apparatus, wherein the logic configuration apparatus stores a graph showing a manufacturing line configured to manufacture a plurality of items, task information indicating graphs showing basic modules and tasks of production scheduling, a rule for selecting a logic of the production scheduling based on the tasks, and implementation information indicating a specification of the production scheduling apparatus, identifies graphs showing basic modules included in the graph showing the manufacturing line by referring to the task information, extracts tasks corresponding to the identified graphs of the basic modules by referring to the task information, wherein the tasks include at least one of a delivery time margin priority and a processing time priority, selects a logic corresponding to the extracted tasks by referring to the rule, and generates, by referring to the specification indicated by the implementation information, implementation information for implementing information indicating the selected logic on the production scheduling apparatus, and outputs the generated implementation information to the production scheduling apparatus, and the production scheduling apparatus implements the logic based on the implementation information.
7. An information processing method to be executed by an information processing apparatus, the information processing apparatus including a processor and a memory, the memory being configured to store a graph showing a manufacturing line configured to manufacture a plurality of items, task information indicating graphs showing basic modules and tasks of production

scheduling, and a rule for selecting a logic of the production scheduling based on the tasks, the information processing method comprising: the processor identifying graphs showing basic modules included in the graph showing the manufacturing line by referring to the task information; the processor extracting tasks corresponding to the identified graphs of the basic modules by referring to the task information, wherein the tasks include at least one of a delivery time margin priority and a processing time priority; the processor selecting a logic corresponding to the extracted tasks by referring to the rule; and the processor outputting information indicating the selected logic.

8. The information processing method according to claim 7, the memory being configured to store process flow information indicating process flows for manufacturing the plurality of items, the information processing method further comprising: the processor generating graphs showing the process flows of the plurality of items by referring to the process flow information; and the processor generating the graph showing the manufacturing line by merging the generated graphs showing the process flows of the plurality of items.

9. The information processing method according to claim 7, the information processing apparatus being connected to an input device and a display device, the information processing method further comprising: the processor displaying the extracted tasks and the selected logic on the display device; the processor receiving an input of a correct logic via the input device; and the processor learning the rule based on the extracted tasks and the correct logic when it is determined that the selected logic and the correct logic are different from each other.

10. The information processing method according to claim 7, further comprising: the processor generating data for outputting information indicating the graph showing the manufacturing line and the selected logic to a display device.

11. The information processing method according to claim 7, further comprising: the processor generating data for outputting information indicating the identified graphs of the basic modules and the extracted tasks to a display device.
