

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405645
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Chung; Haein et al.

Hinge structure with air vent and electronic device having the same

Abstract

An electronic device includes first and second housings rotatable relative to each other, a fan inside the housing, and a hinge structure rotatably connecting the first and second housings to each other. The hinge structure includes a vent member rotating together with rotation of the first and second housings. The vent member includes first and second portions which guide first air flow between intake and exhaust openings together with operation of the fan. The first and second housings which face each other define a first angle therebetween, the first and second housings which are maximally rotated define a second angle therebetween, and the first and second housings forming a third angle between the first angle and the second angle, rotates the vent member to dispose the first and second vent portions together guiding air flow in different directions, relative to the front side of the electronic device.

Inventors: Chung; Haein (Suwon-si, KR), Kim; Hansang (Suwon-si, KR), Baek; Kunwoo (Suwon-si, KR), Ko; Giyeon (Suwon-si, KR), Lim; Jonghyun (Suwon-si, KR), Jeong; Chihwan (Suwon-si, KR), Jeong; Hui (Suwon-si, KR), Choi; Myoungjun (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 86999740

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Gyeonggi-Do, KR)

Appl. No.: 18/318003

Filed: May 16, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230280804 A1	Sep. 07, 2023

Foreign Application Priority Data

KR	10-2021-0189826	Dec. 28, 2021
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/021072 20221222 PENDING child-doc US 18318003

Publication Classification

Int. Cl.: **G06F1/20** (20060101); **G06F1/16** (20060101); **H05K7/20** (20060101)

U.S. Cl.:

CPC **G06F1/20** (20130101); **G06F1/1616** (20130101); **G06F1/1681** (20130101);
H05K7/20145 (20130101);

Field of Classification Search

CPC: G06F (1/20); G06F (1/1616); G06F (1/1681); G06F (1/203); G06F (2200/202); H05K
(7/20145)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6118655	12/1999	Mecredy, III	361/679.52	G06F 1/203
8926414	12/2014	Kirkpatrick	361/679.41	G06F 1/203
8982555	12/2014	Nishi	174/15.1	G06F 1/1616
9268377	12/2015	Macdonald et al.	N/A	N/A
9575524	12/2016	Prather et al.	N/A	N/A
10551881	12/2019	Ho	N/A	G06F 1/1681
11314297	12/2021	Degner	N/A	G06F 1/206
12021296	12/2023	Yoo	N/A	H01Q 9/42
2002/0075647	12/2001	DiFonzo	361/679.48	H05K 7/20172
2006/0114653	12/2005	Seto	361/679.48	G06F 1/203
2008/0128119	12/2007	Ali	165/122	G06F 1/203
2010/0165567	12/2009	Shih	361/679.48	G06F 1/1667
2013/0077241	12/2012	Senatori	361/694	G06F 1/203
2013/0327507	12/2012	Degner	361/695	H05K 7/2039
2015/0169014	12/2014	Rivera et al.	N/A	N/A
2017/0010637	12/2016	Garelli	N/A	G06F 1/203
2018/0284858	12/2017	Lee	N/A	G06F 1/1618
2020/0187381	12/2019	Degner et al.	N/A	N/A
2021/0018965	12/2020	Watanabe et al.	N/A	N/A
2021/0096618	12/2020	Radhakrishnan	N/A	G06F 1/206
2021/0356999	12/2020	Chao	N/A	H05K 7/20145

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103294107	12/2012	CN	N/A
2015049591	12/2014	JP	N/A
100746966	12/2006	KR	N/A
2011146064	12/2010	WO	N/A
2018183135	12/2017	WO	N/A

OTHER PUBLICATIONS

European Search Report for European Patent Application No. 22916610.3 dated Dec. 13, 2024.
cited by applicant

Primary Examiner: Rathod; Abhishek M

Attorney, Agent or Firm: CANTOR COLBURN LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation application of International Application No. PCT/KR2022/021072 designating the United States, filed on Dec. 22, 2022, at the Korean Intellectual Property Receiving Office and claiming priority to Korean Patent Application No. 10-2021-0189826, filed on Dec. 28, 2021, and Korean Patent Application No. 10-2022-0044982, filed on Apr. 12, 2022, at the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

1. Field

(1) The disclosure relates to a hinge structure having a vent and an electronic device including the same.

2. Description of Related Art

(2) An electronic device such as a laptop personal computer (PC) may include a heat dissipation structure for controlling a temperature of the electronic device, by dissipating heat generated within the electronic device during use thereof, to the outside of the electronic device and/or the heat-generating structure. For example, the electronic device may include an air vent structure for dissipating heat to the outside, via air circulation. To satisfy consumer tendency to value design aesthetics, a heat dissipation structure that is minimally exposed to the outside but still functions to dissipate heat from the electronic device is being developed.

SUMMARY

(3) Providing improved portability and aesthetics, electronic devices that are thinner and smaller are in demand. Various components are disposed inside the electronic device, and various technologies for removing heat generated from the components while the electronic device is being used, are being developed.

(4) In the case of an electronic device such as a laptop personal computer (PC), a fan component for performing a heat dissipation function, via air circulation, may be embedded within the electronic device. To effectively perform a heat dissipation function via air circulation, a vent structure for guiding the flow of air introduced into the electronic device, and air discharged from the electronic device, may be used. When an amount of space occupied inside the electronic device is reduced and exposure of the vent structure is minimized, miniaturization and external aesthetics of the electronic device may be improved.

(5) According to an embodiment of the disclosure, an electronic device including a hinge structure

in which a vent structure is formed may be provided.

(6) According to an embodiment of the disclosure, folding of the electronic device may be implemented via the hinge structure in which the vent structure is formed while a flow direction of air circulating in the electronic device is guided.

(7) According to an embodiment of the disclosure, by limiting a rotation angle of the hinge structure to an angle within a set range, a heat dissipation function may be effectively implemented even when the electronic device is positioned at any of various angles while being used.

(8) The technical goals to be achieved through embodiments of the present disclosure are not limited to those described above, and other technical goals not mentioned above will be clearly understood by one of ordinary skill in the art from the following description.

(9) According to embodiments of the disclosure, an electronic device includes a first housing including a first surface and a second surface opposite to the first surface, a second housing including a third surface and a fourth surface opposite to the third surface, a display visually exposed through the third surface, one or more fan component disposed in a first space inside the first housing, and a hinge structure rotatably connecting the first housing and the second housing about a rotation axis such that an angle between the first surface and the third surface changes between a first angle in a first state in which the first surface and the third surface face each other and a second angle in a second state in which the first surface and the third surface are maximally widened, where the first housing includes an opening formed at a position facing the hinge structure, and including an intake portion configured to suck air into the first space from the outside and an exhaust portion configured to discharge air from the first space to the outside, according to an operation of the fan component, and the hinge structure includes a vent member configured to rotate about the rotation axis, and in which a first vent portion for guiding air flow between the intake portion and the outside, and a second vent portion for guiding air flow between the exhaust portion and the outside are formed, and in a third state in which the angle between the first surface and the third surface forms a third angle between the first angle and the second angle, the first vent portion and the second vent portion guide the air flow in different directions from each other.

(10) According to embodiments of the disclosure, an electronic device includes a first housing including a first surface and a second surface opposite to the first surface, a second housing including a third surface and a fourth surface opposite to the third surface, and configured to rotate about a rotation axis relative to the first housing allowing change between a first state in which the third surface forms a first angle relative to the first surface and a second state in which the third surface forms a second angle relative to the first surface, a display disposed on the third surface, one or more fan component disposed in a first space inside the first housing, and a hinge structure disposed along the rotation axis and rotatably connecting the first housing and the second housing, where the first housing includes an opening formed at an end of the first housing facing the hinge structure, the opening being open in a direction parallel to the rotation axis, and including an intake portion configured to suck external air into the first space and an exhaust portion configured to discharge air from the first space to the outside, according to an operation of the fan component, and the hinge structure includes a vent member having a longitudinal direction parallel to the rotation axis and including a first vent portion formed in a portion overlapping the intake portion and a second vent portion formed in a portion overlapping the exhaust portion, in a state in which the opening is viewable, and in a state in which the third surface has an angle greater than or equal to a third angle between the first angle and the second angle relative to the first surface, the intake portion sucks air from a space between the first surface and the third surface through the first vent portion, and the exhaust portion exhausts air between the second surface and the fourth surface through the second vent portion.

(11) According to embodiments of the disclosure, an electronic device includes a first housing including a first surface and a second surface opposite to the first surface, a second housing including a third surface and a fourth surface opposite to the third surface, a display visually

exposed through the third surface, one or more fan component disposed in a first space inside the first housing, and a hinge structure rotatably connecting the first housing and the second housing allowing change between a first state in which the first surface and the third surface form a first angle facing each other and a second state in which the first surface and the third surface form a second angle, where the first housing includes an opening including an intake portion configured to suck air into the first space from the outside and an exhaust portion configured to discharge air from the first space to the outside, according to an operation of the fan component, and the hinge structure includes a rotating member connecting the first housing and the second housing and configured to rotate about the rotation axis according to the rotation of the second housing relative to the first housing, based on a third state in which the first surface and the third surface form a third angle between the first angle and the second angle, a vent member including a first vent portion through which the intake portion communicates with the outside, and a second vent portion through which the exhaust portion communicates with the outside, and a connecting member connecting the rotating member and the vent member, and the connecting member transmits a rotational force of the rotating member to the vent member during a change between the first state and the third state, and prevents transmission of the rotational force of the rotating member to the vent member during a change between the third state and the second state.

(12) According to embodiments of the disclosure, an electronic device includes a first housing comprising a first surface at a front side of the electronic device, a second surface which is opposite to the first surface and at a rear side of the electronic device, an inner space in communication with an outside of the first housing, an intake opening connected to the inner space and through which air flows to the inner space from the outside of the first housing, and an exhaust opening connected to the inner space and through which air flows from the inner space to the outside of the first housing, a second housing comprising a third surface at the front side of the electronic device and a fourth surface which is opposite to the third surface and at the rear side of the electronic device, a display visually exposed at the third surface, a fan which is in the inner space of the first housing, and a hinge structure rotatably connecting the first housing and the second housing to each other, about a rotation axis. The hinge structure includes a vent member which rotates about the rotation axis, together with rotation of the first housing relative to the second housing. The vent member includes a first vent portion which guides first air flow between the intake opening and an outside of the electronic device, together with operation of the fan, and a second vent portion which guides second air flow between the exhaust opening and the outside of the electronic device, together with the operation of the fan. The first surface and the third surface which face each other define a first angle between the first housing and the second housing, the first surface and the third surface which are disposed at a maximum rotational distance from each other define a second angle between the first housing and the second housing, and the first surface and the third surface which define a third angle between the first angle and the second angle, rotates the vent member to dispose the first vent portion guiding the first air flow in a direction relative to the front side of the electronic device, together with the second vent portion guiding the second air flow in a different direction from that of the first vent portion, relative to the front side of the electronic device.

(13) According to embodiments of the disclosure, an electronic device includes a first housing comprising a first surface at a front side of the electronic device, a second surface which is opposite to the first surface and at a rear side of the electronic device, an inner space in communication with an outside of the first housing, an intake opening connected to the inner space and through which air flows to the inner space from the outside of the first housing, and an exhaust opening connected to the inner space and through which air flows from the inner space to the outside of the first housing, a second housing rotatable relative to the first housing, about a rotation axis, the second housing comprising a third surface at the front side of the electronic device, and a fourth surface which is opposite to the third surface and at the rear side of the electronic device, a display visually exposed at the third surface, a fan which is in the inner space of the first housing, and a hinge

structure at the rotation axis and rotatably connecting the first housing and the second housing to each other. The hinge structure includes a vent member which is extended parallel to the rotation axis. The vent member comprising a first vent portion which faces the intake opening, and a second vent portion which faces the exhaust opening. the vent member rotates about the rotation axis, together with rotation of the first housing relative to the second housing, and guides air flow relative to the electronic device, together with operation of the fan. The first surface and the third surface which face each other define a first angle between the first housing and the second housing, the first surface and the third surface which are disposed at a maximum rotational distance from each other define a second angle between the first housing and the second housing, and the first surface and the third surface which define a third angle between the first angle and the second angle, rotates the vent member to dispose the first vent portion guiding a first air flow from the first surface and the third surface each at the front side of the electronic device, toward the intake opening of the first housing, together with defining a second air flow guided by the second vent portion, from the exhaust opening of the first housing, toward the second surface and the fourth surface each at the rear side of the electronic device.

(14) According to embodiments of the disclosure, an electronic device includes a first housing comprising a first surface at a front side of the electronic device, a second surface which is opposite to the first surface and at a rear side of the electronic device, an inner space in communication with an outside of the first housing, an intake opening connected to the inner space and through which air flows to the inner space from the outside of the first housing, and an exhaust opening connected to the inner space and through which air flows from the inner space to outside the first housing, a second housing comprising a third surface at the front side of the electronic device, and a fourth surface which is opposite to the third surface and at the rear side of the electronic device, a display visually exposed at the third surface, a fan which is in the inner space of the first housing, and a hinge structure rotatably connecting the first housing and the second housing to each other. The hinge structure includes a vent member which rotates about the rotation axis, together with rotation of the first housing relative to the second housing. The vent member includes a first vent portion which guides first air flow between the intake opening and outside of the electronic device, together with operation of the fan, and a second vent portion which guides second air flow between the exhaust opening and the outside of the electronic device, together with operation of the fan, and a rotational connecting member which is fixed to and rotatable together with the second housing, connects the second housing to the hinge structure, at the vent member, and transmits a rotational force from the rotation of the first housing relative to the second housing, to the vent member. The first surface and the third surface which face each other define a first angle between the first housing and the second housing, the first surface and the third surface which are disposed at a maximum rotational distance from each other define a second angle between the first housing and the second housing, the rotation of the first housing relative to the second housing, between the first angle and a third angle between the first angle and the second angle, rotates the rotational connecting member together with the vent member; and the rotation of the first housing relative to the second housing, between the third angle and the second angle, prevents transmission of the rotational force to the vent member, to stop rotation of the vent member.

(15) According to embodiments of the disclosure, by forming a vent structure through which air may pass in the hinge structure, a space occupied by the vent structure in the electronic device may be minimized while an internal space of the electronic device may be simplified.

(16) According to embodiments of the disclosure, by limiting a rotation angle of a vent member in which a vent portion is formed to a set range, intake of air to the electronic device and exhaust of air to the outside may be guided in a predetermined direction when the electronic device is in an unfolded state at a particular angle or more.

(17) According to embodiments of the disclosure, by separately forming each vent portion of the

vent member, mixing of air introduced into the electronic device and air discharged from the electronic device may be prevented.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other aspects, features, and advantages of certain embodiments of the present disclosure will be more apparent from the following detailed description, taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 is a block diagram illustrating an electronic device in a network environment according to an embodiment;
- (3) FIG. 2A is a perspective view illustrating an electronic device which is closed according to an embodiment;
- (4) FIG. 2B is a perspective view illustrating an electronic device which is open according to an embodiment;
- (5) FIG. 3A is a diagram illustrating an air flow according to an operation of a fan component in an electronic device according to an embodiment;
- (6) FIG. 3B is a perspective view of a first housing according to an embodiment;
- (7) FIG. 3C is a perspective view of a second housing according to an embodiment;
- (8) FIG. 4A is an exploded perspective view of a hinge structure according to an embodiment;
- (9) FIG. 4B is a front view, FIG. 4C is a rear view, FIG. 4D is a perspective view, and FIGS. 4E and 4F are enlarged perspective views, of a vent member according to an embodiment;
- (10) FIG. 4G is a perspective view illustrating a connection relationship between a vent member and a connecting member according to an embodiment;
- (11) FIG. 4H is a perspective view illustrating a connection relationship between a connecting member and a rotating member according to an embodiment;
- (12) FIG. 5A is a perspective view illustrating a first state of an electronic device according to one embodiment;
- (13) FIG. 5B is an enlarged perspective view illustrating a hinge structure in a first state of an electronic device;
- (14) FIG. 5C is an enlarged cross-sectional view of the electronic device taken along a Vc-Vc line of FIG. 5A;
- (15) FIG. 5D is an enlarged cross-sectional view of the electronic device taken along a Vd-Vd line of FIG. 5A;
- (16) FIG. 6A is a perspective view illustrating an electronic device which is open according to one embodiment;
- (17) FIG. 6B is an enlarged perspective view illustrating a hinge structure in an open electronic device;
- (18) FIG. 6C is a cross-sectional view of the electronic device taken along line VIc-VIc of FIG. 6A;
- (19) FIG. 6D is a cross-sectional view of the electronic device taken along line VIId-VIId of FIG. 6A;
- (20) FIG. 7A is a diagram illustrating an electronic device which is open according to one embodiment;
- (21) FIG. 7B is an enlarged perspective view illustrating a hinge structure in an open electronic device;
- (22) FIG. 7C is an enlarged cross-sectional view of the electronic device taken along line VIIc-VIIc line of FIG. 7A;
- (23) FIG. 7D is an enlarged cross-sectional view of the electronic device taken along line VIId-

VIII of FIG. 7A;

(24) FIG. 8A is a perspective view illustrating an air flow according to an operation of a fan component in an electronic device which is open according to an embodiment;

(25) FIG. 8B is a perspective view of a vent member according to an embodiment;

(26) FIG. 8C is a cross-sectional view of the electronic device taken along line VIIIC-VIIIC of FIG. 8A;

(27) FIG. 8D is a cross-sectional view of the electronic device taken along line VIIID-VIIID of FIG. 8A;

(28) FIG. 9A is a perspective view illustrating an air flow according to an operation of a fan component in an electronic device in a third state according to an embodiment;

(29) FIG. 9B is a perspective view of a vent member according to an embodiment;

(30) FIG. 9C is an enlarged cross-sectional view of the electronic device taken along line IXc-IXc of FIG. 9A; and

(31) FIG. 9D is an enlarged cross-sectional view of the electronic device taken along line IXd-IXd of FIG. 9A.

DETAILED DESCRIPTION

(32) Hereinafter, embodiments will be described in detail with reference to the accompanying drawings. When describing the embodiments with reference to the accompanying drawings, like reference numerals refer to like elements and a repeated description related thereto will be omitted.

(33) FIG. 1 is a block diagram illustrating an electronic device in a network environment according to one embodiment. Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or communicate with at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network).

According to one embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to one embodiment, the electronic device **101** may include a processor **120**, a memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, and a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one (e.g., the connecting terminal **178**) of the above components may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) of the components may be integrated as a single component (e.g., the display module **160**).

(34) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** connected to the processor **120**, and may perform various data processing or computation. According to one embodiment, as at least a portion of data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in a volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in a non-volatile memory **134**. According to one embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121** or to be predetermined to a specified function. The auxiliary processor **123** may be implemented separately from the main processor **121**

or as a part of the main processor **121**.

(35) The auxiliary processor **123** may control at least some of functions or states related to at least one (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) of the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state or along with the main processor **121** while the main processor **121** is an active state (e.g., executing an application). According to one embodiment, the auxiliary processor **123** (e.g., an ISP or a CP) may be implemented as a portion of another component (e.g., the camera module **180** or the communication module **190**) that is functionally related to the auxiliary processor **123**. According to one embodiment, the auxiliary processor **123** (e.g., an NPU) may include a hardware structure specified for artificial intelligence (AI) model processing. An AI model may be generated by machine learning. The machine learning may be performed by, for example, the electronic device **101**, in which artificial intelligence is performed, or performed via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, for example, supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning algorithms. The AI model may include a plurality of artificial neural network layers. An artificial neural network may include, for example, a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted Boltzmann machine (RBM), a deep belief network (DBN), and a bidirectional recurrent deep neural network (BRDNN), a deep Q-network, or a combination of two or more thereof, but is not limited thereto. The AI model may additionally or alternatively include a software structure other than the hardware structure.

(36) The memory **130** may store various pieces of data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various pieces of data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(37) The program **140** may be stored as software in the memory **130**, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(38) The input module **150** may receive, from outside (e.g., a user) the electronic device **101**, a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(39) The sound output module **155** may output a sound signal to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing a recording. The receiver may be used to receive an incoming call. According to one embodiment, the receiver may be implemented separately from the speaker or as a part of the speaker.

(40) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a control circuit for controlling a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, the hologram device, and the projector. According to one embodiment, the display module **160** may include a touch sensor adapted to sense a touch, or a pressure sensor adapted to measure an intensity of a force incurred by the touch.

(41) The audio module **170** may convert a sound into an electric signal or vice versa. According to one embodiment, the audio module **170** may obtain the sound via the input module **150** or output the sound via the sound output module **155** or an external electronic device (e.g., an electronic device **102** such as a speaker or a headphone) directly or wirelessly connected to the electronic device **101**.

(42) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic

device **101**, and generate an electric signal or data value corresponding to the detected state.

According to one embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(43) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to one embodiment, the interface **177** may include, for example, a high-definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(44) The connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected to an external electronic device (e.g., the electronic device **102**). According to one embodiment, the connecting terminal **178** may include, for example, an HDMI connector, a USB connector, an SD card connector, or an audio connector (e.g., a headphone connector).

(45) The haptic module **179** may convert an electric signal into a mechanical stimulus (e.g., a vibration or a movement) or an electrical stimulus which may be recognized by a user via his or her tactile sensation or kinesthetic sensation. According to one embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(46) The camera module **180** may capture a still image and moving images. According to one embodiment, the camera module **180** may include one or more lenses, image sensors, ISPs, or flashes.

(47) The power management module **188** may manage power supplied to the electronic device **101**. According to one embodiment, the power management module **188** may be implemented as, for example, at least a part of a power management integrated circuit (PMIC).

(48) The battery **189** may supply power to at least one component of the electronic device **101**. According to one embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(49) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently of the processor **120** (e.g., an AP) and that support a direct (e.g., wired) communication or a wireless communication. According to one embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local region network (LAN) communication module, or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device **104** via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., a LAN or a wide region network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multiple components (e.g., multiple chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the SIM **196**.

(50) The wireless communication module **192** may support a 5G network after a 4G network, and

next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., a mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (MIMO), full dimensional MIMO (FD-MIMO), an array antenna, analog beam-forming, or a large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to one embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(51) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to one embodiment, the antenna module **197** may include an antenna including a radiating element including a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to one embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in a communication network, such as the first network **198** or the second network **199**, may be selected by, for example, the communication module **190** from the plurality of antennas. The signal or power may be transmitted or received between the communication module **190** and the external electronic device via the at least one selected antenna. According to one embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as a part of the antenna module **197**.

(52) According to an example embodiments, the antenna module **197** may form a mmWave antenna module. According to one embodiment, the mmWave antenna module may include a PCB, an RFIC disposed on a first surface (e.g., a bottom surface) of the PCB or adjacent to the first surface and capable of supporting a designated a high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., a top or a side surface) of the PCB, or adjacent to the second surface and capable of transmitting or receiving signals in the designated high-frequency band.

(53) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(54) According to one embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the external electronic devices **102** or **104** may be a device of the same type as or a different type from the electronic device **101**. According to one embodiment, all or some of operations to be executed by the electronic device **101** may be executed at one or more external electronic devices (e.g., the external devices **102** and **104**, and the server **108**). For example, if the electronic device **101** needs to perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or service, or an additional function or an additional service related to the request, and may transfer a result of the performance to the electronic device **101**. The electronic device **101** may provide the result, with or

without further processing the result, as at least part of a response to the request. To that end, cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or MEC. In one embodiment, the external electronic device (e.g., the electronic device **104**) may include an Internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to one embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(55) The electronic device according to various embodiments may be one of various types of electronic devices. The electronic device may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance device. According to one embodiment of the disclosure, the electronic device is not limited to those described above.

(56) It should be appreciated that various embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. In connection with the description of the drawings, like reference numerals may be used for similar or related components. As used herein, a reference number may indicate a singular element or a plurality of the element. For example, a reference number labeling a singular form of an element within the drawing figures may be used to reference a plurality of the singular element within the text of specification.

(57) It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, “A or B”, “at least one of A and B”, “at least one of A or B”, “A, B or C”, “at least one of A, B and C”, and “A, B, or C,” each of which may include any one of the items listed together in the corresponding one of the phrases, or all possible combinations thereof. For example, “an element” has the same meaning as “at least one element,” unless the context clearly indicates otherwise. “At least one” is not to be construed as limiting “a” or “an.” “Or” means “and/or.” As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items. It will be further understood that the terms “comprises” and/or “comprising,” or “includes” and/or “including” when used in this specification, specify the presence of stated features, regions, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, regions, integers, steps, operations, elements, components, and/or groups thereof.

(58) Terms such as “first”, “second”, or “first” or “second” may simply be used to distinguish the component from other components in question, and do not limit the components in other aspects (e.g., importance or order).

(59) It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element. In contrast, when an element (e.g., a first element) is referred to, such as being “directly operatively” or “directly communicatively”, as “directly coupled with,” “directly coupled to,” “directly connected with,” or “directly connected to” another element (e.g., a second element), it means that no third element is between the elements.

(60) Furthermore, relative terms, such as “lower” or “bottom” and “upper” or “top,” may be used herein to describe one element's relationship to another element as illustrated in the Figures. It will be understood that relative terms are intended to encompass different orientations of the device in

addition to the orientation depicted in the Figures. For example, if the device in one of the figures is turned over, elements described as being on the “lower” side of other elements would then be oriented on “upper” sides of the other elements. The term “lower,” can therefore, encompasses both an orientation of “lower” and “upper,” depending on the particular orientation of the figure. Similarly, if the device in one of the figures is turned over, elements described as “below” or “beneath” other elements would then be oriented “above” the other elements. The terms “below” or “beneath” can, therefore, encompass both an orientation of above and below.

(61) Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and the present disclosure, and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

(62) Embodiments are described herein with reference to cross section illustrations that are schematic illustrations of idealized embodiments. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, embodiments described herein should not be construed as limited to the particular shapes of regions as illustrated herein but are to include deviations in shapes that result, for example, from manufacturing. For example, a region illustrated or described as flat may, typically, have rough and/or nonlinear features. Moreover, sharp angles that are illustrated may be rounded. Thus, the regions illustrated in the figures are schematic in nature and their shapes are not intended to illustrate the precise shape of a region and are not intended to limit the scope of the present claims.

(63) As used in connection with various example embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to one embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(64) Various embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., an internal memory **136** or an external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include code generated by a compiler or code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Here, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(65) According to an embodiment, a method according to one embodiment of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., a compact disc read-only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smartphones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of

the application store, or a relay server.

(66) According to embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to one embodiment, the integrated component may still perform one or more functions of each of the plurality of components in the same manner or in a similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to one embodiment, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(67) FIG. 2A is a perspective view illustrating an electronic device which is closed according to an embodiment, and FIG. 2B is a perspective view illustrating an electronic device according to an embodiment.

(68) Referring to FIGS. 2A and 2B, an electronic device **201** (e.g., the electronic device **101** of FIG. 1) according to one embodiment may include a first housing **210**, a second housing **220**, a display **230**, and a hinge assembly. The electronic device **201** may be, for example, a laptop computer, a tablet personal computer (PC), an e-book reader, a portable multimedia device, a portable medical device, a mobile terminal, or a home appliance.

(69) In one embodiment, the first housing **210** and the second housing **220** may form an exterior of the electronic device **201**. In one embodiment, the first housing **210** may include a first surface **210A**, a second surface **210B** facing a direction opposite to the first surface **210A**, and a first side surface **210C** surrounding a space between the first surface **210A** and the second surface **210B**. The second housing **220** may include a third surface **220A**, a fourth surface **220B** facing a direction opposite to the third surface **220A**, and a second side surface **220C** surrounding a space between the third surface **220A** and the fourth surface **220B**. In one embodiment, the third surface **220A** of the second housing **220** may be formed in a position facing the first surface **210A** of the first housing **210** of the electronic device **201** in the first state (e.g., a folded state of FIG. 2A).

(70) In one embodiment, the first housing **210** and the second housing **220** may be connected to be relatively rotatable about a rotation axis A. For example, the first housing **210** and the second housing **220** may be rotatably connected via a hinge structure **270**. In one embodiment, a state of the electronic device **201** may change via a relative rotation of the first housing **210** and the second housing **220** about the rotation axis A. For example, a state of the electronic device **201** may change between a first state in which the electronic device **201** is folded as shown in FIG. 2A and a second state in which the electronic device **201** is fully unfolded as shown in FIG. 2B, via a relative rotation of the first housing **210** and the second housing **220**. In one embodiment, the first housing **210** and the second housing **220** may be substantially symmetrically disposed relative to the rotation axis A. In one embodiment, an angle and a relative distance formed by the first housing **210** and the second housing **220** may change according to a state of the electronic device **201**. In one embodiment, the first housing **210** and the second housing **220** may be formed to be substantially symmetrical to each other in shape and size.

(71) In one embodiment, an angle formed by the first surface **210A** of the first housing **210** and the third surface **220A** of the second housing **220** may change according to a state of the electronic device **201**. In one embodiment, in the first state (e.g., the folded state) of the electronic device **201** in which the first surface **210A** and the third surface **220A** substantially face each other as shown in FIG. 2A, the first surface **210A** and the third surface **220A** may form a first angle substantially close to 0 degrees. For example, the first angle may range from 0 degrees to approximately 5 degrees. In one embodiment, in the second state (e.g., the unfolded state) in which the first surface

210A and the third surface **220A** are fully unfolded as shown in FIG. 2B, the first surface **210A** and the third surface **220A** may form a second angle corresponding to a set maximum angle. For example, the second angle may be a set angle in a range of approximately 120 degrees to 180 degrees. In one embodiment, the first surface **210A** and the third surface **220A** may form an angle between the first angle and the second angle according to a state of the electronic device **201**, for example, a relative rotation of the first housing **210** and the second housing **220**. For example, when the electronic device **201** forms a third state as shown in FIG. 6A, the first surface **210A** and the third surface **220A** may form a third angle positioned between the first angle and the second angle. The third angle may be, for example, a set angle in a range of approximately 90 degrees to 120 degrees. However, the third angle is an arbitrary angle set for an operation of the hinge structure **270** to be described later, and an angle to be formed between the first surface **210A** and the third surface **220A** by the electronic device **201** is not limited thereto. In other words, the angle formed by the first surface **210A** and the third surface **220A** may be adjusted to form an arbitrary angle between the first angle corresponding to a minimum angle and the second angle corresponding to a maximum angle, according to a use state of the electronic device **201**.

(72) In one embodiment, a keyboard **202**, a touchpad **204**, and a palm rest **206** may be disposed on the first surface **210A** of the first housing **210**. The keyboard **202** (e.g., the input module **150** of FIG. 1) may include a plurality of keys disposed on the first surface **210A** of the first housing **210**. The keyboard **202** may receive numeric or character information from a user. The keyboard **202** may include a plurality of input keys and function keys for setting various functions of the electronic device **201**. For example, the function keys may include an arrow key, a volume key, and/or a shortcut key set to perform a designated function. The keyboard **202** may include one of a query keypad, a 3*4 keypad, a 4*3 keypad, or a touch key. The touch pad **204** may receive user manipulation information. For example, the touchpad **204** may replace a function of a mouse. The touchpad **204** may receive a command to select or execute an application displayed on the display **230**. The palm rest **206** may be a pedestal for reducing wrist fatigue of a user of the electronic device **201** when the user is using the keyboard **202**.

(73) In one embodiment, the display **230** may display visual information to the outside. The display **230** may be visually exposed to the outside by being disposed on the third surface **220A** of the second housing **220**. For example, a concave portion **222** may be formed on the third surface **220A**, and the display **230** may be disposed to be seated on the concave portion **222**. In one embodiment, the display **230** may be covered so as not to be exposed to the outside by the first surface **210A** in the first state (e.g., the folded state of FIG. 2A) of the electronic device **201**. In one embodiment, the display **230** may be formed of at least one of a liquid crystal display (LCD), an organic light-emitting diode (OLED), an active-matrix organic light-emitting diode (AMOLED), a flexible display **230**, or a transparent display **230**. Although in the drawings, the display **230** is illustrated as being disposed on the third surface **220A** of the second housing **220**, this is only an example, and a position in which the display **230** is arranged relative to the electronic device **201** is not limited thereto. As an example, the display **230** may be disposed to extend from the third surface **220A** to the first surface **210A**, and as another example, the electronic device **201** may include an auxiliary display disposed on a surface (e.g., at least one of the first surface **210A**, the second surface **210B**, or the fourth surface **220B**) other than the third surface **220A**.

(74) In one embodiment, the hinge structure **270** may be disposed along the rotation axis A and may rotatably connect the first housing **210** and the second housing **220**. In one embodiment, the hinge structure **270** may allow the first housing **210** and the second housing **220** to relatively rotate such that the electronic device **201** may change in state between the first state (e.g., the folded state of FIG. 2A) in which an angle between the first surface **210A** and the third surface **220A** forms the first angle and the second state (e.g., a maximumly open state of FIG. 2B) in which an angle between the first surface **210A** and the third surface **220A** forms the second angle. Hereinafter, for ease of description, the relative rotation of the first housing **210** and the second housing **220** about

the rotation axis A is described based on the assumption that the second housing **220** is rotating relative to the first housing **210**.

(75) FIG. 3A is a diagram illustrating an air flow according to an operation of a fan component in an electronic device according to an embodiment, FIG. 3B is a perspective view of a first housing according to an embodiment, and FIG. 3C is a perspective view of a second housing according to an embodiment.

(76) Referring to FIGS. 3A to 3C, the electronic device **201** (e.g., the electronic device **101** of FIG. 1) according to one embodiment may include the first housing **210**, the second housing **220**, the display **230**, and heat dissipation structures **350** and **360**.

(77) In one embodiment, the first housing **210** may include the first surface **210A**, the second surface **210B** opposite to the first surface **210A**, and the first side surface **210C** surrounding a space between the first surface **210A** and the second surface **210B**. In one embodiment, when the electronic device **201** is being used, the first housing **210** may be disposed in a state in which the second surface **210B** faces a support surface of another structure, for example, a support surface of a structure such as a desk. In one embodiment, the second housing **220** may be rotatably connected to the first housing **210** at the rotation axis A. The second housing **220** may include the third surface **220A** formed to face the first surface **210A** in the first state (e.g., the folded state of FIG. 2A), the fourth surface **220B** opposite to the third surface **220A**, and the second side surface **220C** surrounding a space between the third surface **220A** and the fourth surface **220B**. In one embodiment, the display **230** may be disposed to be visually exposed on the third surface **220A** of the second housing **220**.

(78) In one embodiment, the first housing **210** may include a first space **2100** formed inside the first housing **210** (e.g., an inner space). Various components (e.g., a battery, a PCB, and the like) for performing a function of the electronic device **201** may be disposed in the first space **2100**. In one embodiment, the first housing **210** may include heat dissipation structures **350** and **360** for controlling a temperature of components disposed in the first space **2100**. For example, the first housing **210** may include an opening **360** through which the first space **2100** communicates with the outside, and one or more fan component **350** disposed in the first space **2100** and flowing air through the opening **360**.

(79) In one embodiment, the opening **360** may allow air to pass between the first space **2100** and the outside by opening at least a portion of the first housing **210**. In one embodiment, at least a portion of the opening **360** may be formed on a side surface of the first housing **210**. For example, the opening **360** may be formed in a side portion of the first housing **210** facing the hinge structure **370** as shown in FIG. 3A and FIG. 3B. In one embodiment, the opening **360** may include one or more intake portion **361** (e.g., an intake opening) through which air is sucked into the first space **2100** from the outside, and one or more of exhaust portions **362a** and **362b** (e.g., an exhaust opening) through which air is discharged from the first space **2100** to the outside. For example, the opening **360** may include one intake portion **361** (e.g., an intake opening) positioned at a central portion relative to a direction of the rotation axis A, a first exhaust portion **362a** (e.g., a first exhaust opening) disposed on a right side (e.g., a +X-axial direction) of the intake portion **361**, and a second exhaust portion **362b** (e.g., a second exhaust opening) disposed on a left side (e.g., a -X-axial direction) of the intake portion **361**, as shown in FIG. 3A and FIG. 3B. In one embodiment, the intake portion **361** and the exhaust portions **362a** and **362b** may be formed separately from each other as shown in FIG. 3A and FIG. 3B so that the air passing therethrough is not mixed in the air flow process. Meanwhile, the shape, number, and relative arrangement position of each of the intake portion **361** and the exhaust portions **362a** and **362b** of the opening **360** shown in the drawings are only examples, and are not limited to those of the embodiments illustrated in the drawings. For example, the opening **360** may include one of an intake portion and an exhaust portion, or may include a plurality of intake portions and exhaust portions.

(80) In one embodiment, one or more fan component **350** may be disposed in the first space **2100**

and may circulate air between the first space **2100** and the outside through the opening **360**. That is, the first space **2100** may be connected to (e.g., in fluid or air communication) with the outside of the electronic device **201**, such that air flow may be defined therebetween. In one embodiment, according to an operation of the fan component **350**, the fan component **350** may generate air pressure to circulate air between the first space **2100** and the outside, and adjust a temperature of the first space **2100** according to the circulation of the air. In one embodiment, according to an operation of the fan component **350**, external air may flow into the first space **2100** through the intake portion **361** and absorb heat generated in the first space **2100**, and then be discharged from the first space **2100** to the outside through the exhaust portions **362a** and **362b**. That is, the intake opening and the exhaust opening of the housing may be connected to (e.g., in fluid or air communication) with both the inner space of the housing and the outside of the housing). In one embodiment, the fan component **350** may be disposed in the first space **2100** to effectively radiate heat through the opening **360**. For example, when the opening **360** includes one intake portion **361** and a pair of exhaust portions **362a** and **362b** positioned on opposite sides of the intake portion **361** as shown in FIG. 3A, a pair of fan components **351** and **352** for discharging air through each of the exhaust portions **362a** and **362b** may be disposed in the first space **2100**. The fan component **350** may include a first fan component **351** disposed in the first space **2100** to be adjacent to the first exhaust portion **362a** relative to the direction of the rotation axis A, and a second fan component **352** disposed in a second space to be adjacent to the second exhaust portion **362b** relative to the direction of the rotation axis A. In this case, the first fan component **351** may circulate a part of the air F_i sucked into the first space **2100** through the intake part **361** in a left direction (e.g., a +X-axial direction) of the first housing **210** and discharge F_{o1} through the first exhaust portion **362a**, and the second fan component **352** may circulate a part of the air F_i sucked into the first space **2100** in a right direction (e.g., a -X-axial direction) of the first housing **210** and discharge F_{o2} through the second exhaust portions **362a** and **362b**. Meanwhile, the number and arrangement position of the fan component **350** shown in the drawings are only examples and are not limited thereto. For example, as shown in FIG. 8A, one fan component **850** may be disposed in a first space **8100** to circulate air, and as shown in FIG. 9A, a plurality of fan components **950** may be disposed in a first space **9100** to circulate air in different directions.

(81) In one embodiment, the hinge structure **370** may rotatably connect the first housing **210** and the second housing **220**. The hinge structure **370** may be disposed along the rotation axis A, and may rotate about the rotation axis A according to a rotation of the second housing **220** relative to the first housing **210**. In one embodiment, the hinge structure **370** may be disposed at a position facing the opening **360** formed in the first housing **210**. In one embodiment, at least a portion of the hinge structure **370** may be fixed to the second housing **220** and be rotatably connected to the first housing **210**. For example, the hinge structure **370** may be fixed to the third surface **220A** of the second housing **220** as shown in FIG. 3A, and an end of the hinge structure **370** may be rotatably connected to the first housing **210**. In this case, a seating space **314** that is concave inward may be formed in the side surface **210C** of the first housing **210** such that the hinge structure **370** may be rotatably inserted therein. The opening **360** may be formed on an inner circumferential surface of the seating space **314** in the direction of the rotation axis A.

(82) In one embodiment, the hinge structure **370** may include a vent member **371** for guiding a flow direction of air through the opening **360**. The vent member **371** may include a first vent portion **3711** (e.g., a first air flow guide portion) for guiding the air flow between the intake portion **361** and the outside, and a second vent portion **3712** (e.g., a second air flow guide portion) for guiding the air flow between the exhaust portions **362a** and **362b** and the outside. In one embodiment, the vent member **371** may be disposed at a position facing the opening **360**. In this case, the first vent portion **3711** may be formed in a portion of the vent member **371** facing the intake portion **361**, and the second vent portion **3712** may be formed in a portion of the vent member **371** facing the exhaust portions **362a** and **362b**. In one embodiment, the first vent portion

3711 and the second vent portion **3712** may be formed in positions and shapes corresponding to the intake portion **361** and the exhaust portions **362a** and **362b** of the opening **360**. For example, as shown in FIG. 3C, the intake portion **361** may be formed on a central portion of the opening **360** along the direction of the rotation axis A, and when a pair of exhaust portions **362a** and **362b** are formed on opposite sides of the intake portion **361**, the first vent portion **3711** may be formed on a central portion of the vent member **371** corresponding to the intake portion **361**, and a pair of second vent portions **3712a** and **3712b** may be formed on opposite side portions of the vent member **371** corresponding to the pair of exhaust portions **362a** and **362b**.

(83) In one embodiment, the first vent portion **371** and the second vent portion **372** may guide a flow of air in different directions. For example, in the third state as shown in FIG. 3A, the first vent portion **371** of the vent member **371** may guide air from the first surface **210A** and the third surface **220A** (e.g., at a front surface of the open electronic device) to the intake portion **361**, and the second vent portion **372** may guide air to be discharged between the second surface **210B** and the fourth surface **220B** (e.g., at a rear surface of the open electronic device) from the exhaust portions **362a** and **362b**. In this case, based on the direction of the rotation axis A, the first vent portion **371** may be formed longitudinally covering the intake portion **361**, and each of the second vent portions **3712a** and **3712b** may be formed longitudinally covering each of the corresponding exhaust portions **362a** and **362b** formed at a position of the opening **360**.

(84) FIG. 4A is an exploded perspective view of a hinge structure according to an embodiment, FIG. 4B is front view, FIG. 4C is a rear view, FIG. 4D is a perspective view, and FIGS. 4E and 4F are enlarged perspective views of a vent member according to an embodiment, FIG. 4G is a perspective view illustrating a connection relationship between a vent member and a connecting member according to one embodiment, and FIG. 4H is a perspective view illustrating a connection relationship between a connecting member and a rotating member according to an embodiment. FIGS. 4E and 4F are enlarged perspective views of region B and C in FIG. 4D, respectively.

(85) Referring to FIGS. 4A to 4H, a hinge structure **470** according to one embodiment may be connected to a second housing **420**. For example, the hinge structure **470** may be disposed on a third surface **420A** of the second housing **420** on which a display **430** is disposed.

(86) The hinge structure **470** according to one embodiment may include a vent member **471**, a rotating member **472**, and a connecting member **473**.

(87) In one embodiment, the vent member **471** may extend longitudinally in a direction of a rotation axis A (e.g., an X-axial direction). In one embodiment, the vent member **471** may include a first vent portion **4711** and a second vent portion **4712** formed to extend in the longitudinal direction. For example, the vent member **471** may include the first vent portion **4711** formed longitudinally on a central portion, and a pair of second vent portions **4712a** and **4712b** formed on opposite sides of the first vent portion **4711**, respectively. In one embodiment, based on the longitudinal direction of the vent member **471**, the first vent portion **4711** and the second vent portion **4712** may be formed in a position and length corresponding to the intake portion **361** and the exhaust portions **362a** and **362b** of the opening **360** formed in the first housing **210** as shown in FIG. 3C. In one embodiment, the vent member **471** may have a substantially circular cross-sectional shape when viewed in the direction of the rotation axis A. In one embodiment, based on a cross-section of the vent member **471** perpendicular to the rotation axis A, the first vent portion **4711** and the second vent portion **4712** may be formed such that at least a portion of an outer surface of the vent member **471** is concave to allow air to pass therethrough. In this case, based on the cross-section of the vent member **471** perpendicular to the rotation axis A as shown in FIG. 4B, a first vent portion **4711** and a second vent portion **4712** may be formed such that the outer surface of the vent member **471** is concave in different directions.

(88) In one embodiment, the vent member **471** may guide a flow direction of air passing through an opening (e.g., the opening **360** of FIG. 3B). For example, the vent member **471** may pass air through the first vent portion **4711** and the second vent portion **4712** having a concave outer

surface, and thereby guide the flow direction of air between a first space (e.g., the first space **2100** of FIG. 3A) inside the first housing and the outside. In one embodiment, the first vent portion **4711** may guide the flow direction of air introduced into a first space (e.g., the first space **2100** of FIG. 3B) from the outside through an intake portion (e.g., the intake portion **361** of FIG. 3B), and the second vent portion **4712** may guide the flow direction of air discharged from the first space (e.g., the first space **2100** of FIG. 3B) to the outside through an exhaust portion (e.g., the exhaust portions **362a** and **362b** of FIG. 3B). In one embodiment, since the first vent portion **4711** and the second vent portion **4712** are formed in different directions relative to the cross-section of the vent member **471** perpendicular to the rotation axis A, the flow directions of air passing through the first vent portion **4711** and the second vent portion **4712** may be different.

(89) In one embodiment, the vent member **471** may rotate about the rotation axis A according to an operation of the hinge structure **470**. In this case, the vent member **471** may rotate according to a rotation of the hinge structure **470** only in a set angle range. For example, when a state of an electronic device is changed between a first state (e.g., a first state of an electronic device **501** of FIG. 5A) and a second state (e.g., a second state of the electronic device **501** of FIG. 7A), the vent member **471** may only rotate between a first state (e.g., the first state of the electronic device **501** of FIG. 5A) in which a first housing (e.g., a first housing **510** of FIG. 5A) and the second housing **420** (e.g., a second housing **520** of FIG. 5A) form a first angle, and a third state (e.g., a third state of the electronic device **501** of FIG. 6A) in which a first housing and a second housing form a set third angle. In this case, when a state of the electronic device is changed from the third state and the second state, a rotation angle of the vent member **471** relative to the rotation axis A may be maintained in a stopped state. Accordingly, when an angle of the second housing relative to the first housing is changed between the set third angle and the second angle, the flow direction of air passing through the vent member **471** may be kept constant relative to the first housing. A further description thereof will be provided later.

(90) In one embodiment, the vent member **471** may include a stopper **4714**. The stopper **4714** may limit rotation of the vent member **471** about the rotation axis A so that the vent member **471** may rotate only in a set angle range. For example, when a state of the electronic device is being changed between the first state (e.g., the first state of the electronic device **501** of FIG. 5A) and the second state (e.g., the second state of the electronic device **501** of FIG. 7A), the stopper **4714** may allow the vent member **471** to rotate about the rotation axis A between the first state and the third state, and not allow the vent member **471** to rotate about the rotation axis A between the third state and the second state. In one embodiment, the stopper **4714** may be connected to an outer surface of the vent member **471**. For example, the stopper **4714** may be formed to protrude from the outer surface of the vent member **471**. In one embodiment, the stopper **4714** may restrict rotation of the vent member **471** in one direction (e.g., a direction of rotation from the third state to the second state according to an operation of the electronic device) by being in contact with another member, for example, an end of the first housing (e.g., the first housing **510** of FIG. 5A) in the third state of the electronic device. In one embodiment, the vent member **471** may include one or more stopper **4714**. For example, the vent member **471** may include a pair of stoppers **4714a** and **4714b** formed at opposite ends in a longitudinal direction.

(91) In one embodiment, the rotating member **472** may connect a first housing (e.g., the first housing **210** of FIG. 3A) and the second housing **420**. In one embodiment, at least a portion of the rotating member **472** may be fixed to the second housing **420** and be rotatably connected to the first housing along the rotation axis A. For example, the rotating member **472** may include a fixing portion **4723** having a surface connected to the second housing **420**. The fixing portion **4723** may be connected to the third surface **420A** of the second housing **420**. In one embodiment, the rotating member **472** may include a rotating portion **4722** rotatably connected to the first housing **410**. The rotating portion **4722** may be formed to protrude in the direction of the rotation axis A opposite to the vent member **471**. For example, a first rotating member **472a** may include a first rotating

portion **4722a** protruding in a +X-axial direction, and a second rotating member **472b** may include a second rotating portion **4722b** protruding in a -X-axial direction. In one embodiment, a fixing member **424** into which the rotating portion **4722** of the rotating member **472** is rotatably inserted may be formed in the first housing **420**. In one embodiment, a first fixing member **424a** into which the first rotating portion **4722a** of the first rotating member **472a** is inserted, and a second fixing member **424b** into which the second rotating portion **4722b** of the second rotating member **472b** is inserted may be formed in the first housing **420**. In one embodiment, the rotating member **472** may rotate about the rotation axis A according to a rotation of the second housing relative to the first housing. For example, when a state of the electronic device is changed between the first state and the second state, the rotating member **472** rotates about the rotation axis A and an angle between the first housing and the second housing changes between the first angle and the second angle.

(92) In one embodiment, the rotating member **472** may be connected to the vent member **471** along the direction of the rotation axis A. In one embodiment, the rotating member **472** may include the first rotating member **472a** connected to a first end **471a** (e.g., an end facing the +X-axial direction) of the vent member **471**, and the second rotating member **472b** connected to a second end **471b** (e.g., an end facing the -X-axial direction) of the vent member **471**, in the direction of the rotation axis A. In one embodiment, the rotating member **472** may include a connecting portion **4721** protruding in a direction of the vent member **471** along the direction of the rotation axis A, and the vent member **471** may include a connecting groove **4713** formed in the direction of the rotation axis A such that the connecting portion **4721** is inserted. For example, the vent member **471** may include a first connecting groove **4713a** formed at the first end **471a** in the direction of the rotation axis A, and a second connecting groove **4713b** formed at the second end **471b** in the direction of the rotation axis A. In this case, a first rotating member **472a** may include a first connecting portion **4721a** protruding in the direction of the rotation axis A so as to be insertable into the first connecting groove **4713a**, and a second rotating member **472b** may include a second connecting portion **4721b** protruding in the direction of the rotation axis A so as to be insertable into the second connecting groove **4713b**. The connecting portions **4721a** and **4721b** of each of the rotating members **472a** and **472b** may be respectively connected to opposite ends of the vent member **471** by being inserted into the connecting grooves **4713a** and **4713b**.

(93) In one embodiment, the connecting member **473** may connect the vent member **471** and the rotating member **472**. In one embodiment, the connecting member **473** may selectively transmit a rotational force of the rotating member **472** to the vent member **471** according to a state of the electronic device. For example, in the first and third states of the electronic device, the connecting member **473** may transmit a rotational force of the rotating member **472** to the vent member **471** so that the rotating member **472** and the vent member **471** may rotate integrally. During a change between the third state and the second state, the connecting member **473** may prevent transmission of the rotational force of the rotating member **472** to the vent member **471** so that the rotating member **472** may rotate independently of the vent member **471**.

(94) In one embodiment, the connecting member **473** may be disposed between the vent member **471** and the rotating member **472** in the direction of the rotation axis A. For example, the connecting member **473** may include a first connecting member **473a** disposed between the first rotating member **472a** and the vent member **471**, and a second connecting member **473b** disposed between the second rotating member **472b** and the vent member **471**. The connecting member **473** may include a first connecting surface **4730a** facing the vent member **471** and a second connecting surface **4730b** opposite to the first connecting surface **4730a** and facing the rotating member **472**.

(95) In one embodiment, the connecting member **473** may be fixed to the vent member **471**. For example, the connecting member **473** may have a first connecting surface **4730a** attached to an end surface of the vent member **471** facing the rotating member **472**. In one embodiment, a first connecting surface (e.g., a surface of the first connecting member **473a** facing a +X direction in FIG. 4A) (not shown) of the first connecting member **473a** may be attached to the first end **471a** of

the vent member **471**, and the first connecting surface **4730a** of the second connecting member **473b** may be attached to the second end **471b** of the vent member **471**.

(96) In one embodiment, the connecting member **473** may include a first fastening portion **4731** formed on the second connecting surface **4730b**, and the rotating member **472** may include a second fastening portion **4720** formed at an end of the rotating member **472** facing the vent member **471**, for example, an end of the rotating member **472** facing the second connecting surface **4730b**. In one embodiment, the first fastening portion **4731** of the connecting member **473** may be selectively fastened to the second fastening portion **4720** of the rotating member **472** according to a state of the electronic device, that is, depending on whether the vent member **471** is rotatable. For example, in a state (e.g., a state between a first state of FIG. 5A and a third state of FIG. 6A) between the first and third states of the electronic device in which rotation of the vent member **471** is not restricted, the first fastening portion **4731** and the second fastening portion **4720** may be interlocked and fastened to each other, and in a state (e.g., a state between a third state of FIG. 6A and a second state of FIG. 7A) between the third state and the second state in which rotation of the vent member **471** is restricted, the first fastening portion **4731** and the second fastening portion **4720** may be separated from each other. In one embodiment, the connecting member **473** may transmit a rotational force of the rotating member **472** to the vent member **471** according to a fastening state of the first fastening portion **4731** and the second fastening portion **4720**. For example, in a state in which the first fastening portion **4731** and the second fastening portion **4720** are fastened, the connecting member **473** may rotate according to the rotation of the rotating member **472** to rotate the vent member **471**. On the other hand, in a state in which the first fastening portion **4731** and the second fastening portion **4720** are separated, the connecting member **473** may prevent transmission of a rotational force between the rotating member **472** and the vent member **471**, and thereby allow the rotating member **472** to rotate independently in a state in which rotation of the vent member **471** is restricted.

(97) In one embodiment, the connecting member **473** may be formed of an elastic material that is deformable in shape. The connecting member **473** may be selectively fastened to the rotating member **472** while being deformed in shape according to a rotation of the hinge structure **470**. For example, the first fastening portion **4731** of the connecting member **473** may include a fastening protrusion protruding from the second connecting surface **4730b** in the direction of the rotation axis A, and the second fastening portion **4720** may include a fastening groove recessed at an end so that the fastening protrusion may be inserted. In this case, a concave portion **4710** that is concave in a direction opposite to the connecting member **473** along the direction of the rotation axis A may be formed on an end surface of the vent member **471** to which the connecting member **473** is attached. For example, a first concave portion **4710a** may be formed on the first end **471a** of the vent member **471**, and a second concave portion **4710b** may be formed on the second end **471b** of the vent member **471**. In one embodiment, the concave portion **4710** may at least partially overlap with the first fastening portion **4731** of the connecting member **473** when viewed in the direction of the rotation axis A.

(98) In one embodiment, when the state of the electronic device changes through operation from the first state to the second state (e.g., from the first state of FIG. 5A through the third state of FIG. 6A to the second state of FIG. 7A), from the first state to the third state (e.g., the first state of FIG. 5A to the third state of FIG. 6A), the first fastening portion **4731** of the connecting member **473** may be fastened to the second fastening portion **4720**. In this case, when the state of the electronic device changes through operation from the third state in which rotation of the vent member **471** is restricted to the second state (e.g., the third state of FIG. 6A to the second state of FIG. 7A), the first fastening portion **4731** may be deformed to be pressed in a direction of the concave portion **4710** by a rotation of the rotating member **472** to be separated from the second fastening portion **4720**. On the other hand, when the state of the electronic device changes through operation from the second state to the first state (e.g., when the electronic device **501** changes through operation

from the second state of FIG. 7A to the first state of FIG. 5A), the first fastening portion **4731** of the connecting member **473** may be pressed in a direction of the concave portion **4710** by an end surface of the rotating member **472** to maintain a stopped state from the second state to the third state, and when the third state is reached, may be inserted into the second fastening portion **4720** and held by resistance. In this case, when the electronic device changes through operation from the third state to the first state, the connecting member **473** may be rotated by the vent member **471** in a state in which the first fastening portion **4731** is fastened to the second fastening portion **4720**.

(99) In one embodiment, the hinge structure **470** may rotate according to an operation of the electronic device, for example, a rotation of the second housing **420** relative to the first housing. At the same time, the hinge structure **470** may limit rotation of the vent member **471** in a set state range, thereby guiding a flow of air in a predetermined direction in the set state. For example, the hinge structure **470**, by limiting the rotation of the vent member **471** between a third state (e.g., the third state of FIG. 6A) in which a third angle is formed by the first housing and the second housing **420** and a second state (e.g., the second state of FIG. 7A) in which a second angle is formed, may guide air from an intake to the first space and guide air exhausted from the first space at a predetermined angle relative to a surface (e.g., a surface on which a second surface of the first housing is supported) in a state where the first housing and the second housing **420** are separated by a third angle or more.

(100) Hereinafter, an operation of the hinge structure according to a state of the electronic device according to one embodiment is described with reference to FIGS. 5A to 7D.

(101) FIGS. 5A to 5D illustrate a first state of an electronic device **501**. FIG. 5A is a perspective view illustrating a first state of the electronic device **501** according to one embodiment, FIG. 5B is an enlarged perspective view illustrating a hinge structure **570** in a first state of the electronic device **501**, FIG. 5C is an enlarged cross-sectional view of the electronic device **501** taken along a Vc-Vc line of FIG. 5A, and FIG. 5D is an enlarged cross-sectional view of the electronic device **501** taken along a Vd-Vd line of FIG. 5A.

(102) Referring to FIGS. 5A to 5D, in the first state of the electronic device **501** (e.g., the electronic device **101** of FIG. 1 and the electronic device **201** of FIG. 2A) according to one embodiment, a first surface **510A** of the first housing **510** and a third surface **520A** of the second housing **520** may substantially face each other. In this case, the first surface **510A** and the third surface **520A** may form a first angle (e.g., about 0 degrees to 5 degrees).

(103) In one embodiment, the hinge structure **570** may be disposed along a rotation axis A and may rotatably connect the first housing **510** and the second housing **520**. In one embodiment, a vent member **571** may be disposed to face an opening **560** of the first housing **510**. A first vent portion **5711** of the vent member **571** may be disposed to correspond to an intake portion **561**, and a second vent portion **5712** may be disposed to correspond to an exhaust portion **562**. In one embodiment, a pair of second vent portions **5712a** and **5712b** may be formed on opposite sides of the first vent portion **5711**. In one embodiment, based on the first state, the vent member **571** may close the intake portion **561** via the first vent portion **5711** as shown in FIG. 5C, and close the exhaust portion **562** via the second vent portion **5712** as shown in FIG. 5D, to minimize exposure of the opening **560** to the outside. Accordingly, in the first state of the electronic device **501**, for example, in a closed state in which the electronic device **501** is not used, foreign material such as dust may be prevented from entering a first space **5100** inside the first housing **510** through the opening **560**.

(104) In one embodiment, in a first state as shown in FIG. 5B, a first fastening portion (e.g., the first fastening portion **4731** of FIG. 4H) of a connecting member **573** may be fastened to a second fastening portion (e.g., the second fastening portion **4720** of FIG. 4H) of a rotating member **572**. In this case, when the second housing **520** rotates relative to the first housing **510**, for example, when the electronic device **501** operates in a third state as shown in FIG. 6A, the connecting member **573** may transmit a rotational force of the rotating member **572** to the vent member **571** by rotating according to the rotation of the rotating member **572**.

(105) FIGS. 6A to 6D illustrate a third state of the electronic device **501**. FIG. 6A is a perspective view illustrating the electronic device **501** according to an embodiment, FIG. 6B is a diagram illustrating the hinge structure **570** in a third state of the electronic device **501**, FIG. 6C is a cross-sectional view of the electronic device **501** taken along line VIc-VIc of FIG. 6A, and FIG. 6D is a cross-sectional view of the electronic device **501** taken along line VIId-VIId of FIG. 6A.

(106) Referring to FIGS. 6A to 6D, in the third state of the electronic device **501** according to one embodiment, the first surface **510A** of the first housing **510** and the third surface **520A** of the second housing **520** may form a set third angle α_3 (e.g., an angle set in a range of about 90 degrees to 120 degrees). In one embodiment, a display **530** may be disposed on the third surface **520A**.

(107) In one embodiment, when the electronic device **501** operates from the first state of FIG. 5A to the third state of FIG. 6A, the vent member **571** may rotate according to the rotation of the rotating member **572**. In one embodiment, when the electronic device **501** reaches the third state, rotation of the vent member **571** may be restricted by a stopper **5714**. For example, when an angle of the third surface **520A** relative to the first surface **510A** reaches the set third angle α_3 , the stopper **5714** may be caught on an end of the second housing **520**, and may stop rotation of the vent member **571** when the angle of the third surface **520A** relative to the first surface **510A** is wider than the third angle α_3 . In one embodiment, based on the third state, the vent member **571** may guide a flow of air F_i flowing into the intake portion **561** from the outside through the first vent portion **5711** as shown in FIG. 6C. In this case, the first vent portion **5711** may guide the air F_i to be introduced into the first space **5100** from between the first surface **510A** and the third surface **520A**. In one embodiment, based on the third state, the vent member **571** may guide a flow of air F_o exhausted from the exhaust portion **562** to the outside through the second vent portion **5712** as shown in FIG. 6D. In this case, the first vent portion **5711** may guide the flow of the air F_o so that air is exhausted from the first space **5100** to between a second surface **510B** and a fourth surface **520B**.

(108) In one embodiment, in the third state, a first fastening portion **5731** of the connecting member **573** may remain fastened to a second fastening portion **5720** of the rotating member **572** as shown in FIG. 6B. In this case, when the second housing **520** rotates to have a narrow angle relative to the first housing **510**, for example, when the electronic device **501** operates to be in the first state as shown in FIG. 5A, the connecting member **573** may transmit a rotational force of the rotating member **572** to the vent member **571** by rotating according to the rotation of the rotating member **572**.

(109) FIGS. 7A to 7D illustrate a second state of the electronic device **501**. FIG. 7A is a perspective view illustrating the electronic device **501** which is open according to an embodiment, FIG. 7B is an enlarged perspective view illustrating the hinge structure **570** in an second state of the electronic device **501**, FIG. 7C is an enlarged cross-sectional view of the electronic device **501** taken along a line VIIc-VIIc of FIG. 7A, and FIG. 7D is an enlarged cross-sectional view of the electronic device **501** taken along a line VIId-VIId of FIG. 7A.

(110) Referring to FIGS. 7A to 7D, in the second state of the electronic device **501** according to one embodiment, the first surface **510A** of the first housing **510** and the third surface **520A** of the second housing **520** may form a second angle α_2 (e.g., a maximum angle set in a range of about 120 degrees to 180 degrees) that is a maximum angle.

(111) In one embodiment, when the state of the electronic device **501** changes from the third state of FIG. 6A to the second state of FIG. 7A, the vent member **571** may maintain a stopped state regardless of the operation of the electronic device **501** since rotation of the vent member **571** is restricted by the stopper **5714**. Based on an angle of rotation about the rotation axis A, a rotation angle of the vent member **571** may be kept constant between the third state of FIG. 6A and the second state of FIG. 7A. In this case, the first vent portion **5711** may guide the air F_i introduced into the first space **5100** from between the first surface **510A** and the third surface **520A** as shown in FIG. 7C, and the second vent portion **5712** may guide the air F_o exhausted from the first space

5100 to the second surface **510B** and the fourth surface **520B** as shown in FIG. 7D.

(112) In one embodiment, in the second state, the first fastening portion **5731** of the connecting member **573** may be separated from the second fastening portion **5720** of the rotating member **572** as shown in FIG. 7B. In one embodiment, when the state of the electronic device **501** changes from the third state of FIG. 6B to the second state of FIG. 7B, the rotating member **572** may rotate about the rotation axis A according to the operation of the electronic device **501**, and rotation of the connecting member **573** may be restricted by the vent member **571** such that the first fastening portion **5731** is separated from the second fastening portion **5720**. For example, a shape of the connecting member **573** may be deformed so that the first fastening portion **5731** is separated from the second fastening portion **5720** by a rotational force of the rotating member **572**. In this case, since the connecting member **573** does not interfere with the rotation of the rotating member **572** between the third state and the second state of the electronic device **501**, the rotating member **572** may rotate according to the operation of the electronic device **501** regardless of rotation being restricted by the vent member **571**. On the other hand, when a state of the electronic device **501** is changed from the second state of FIG. 7B to the third state of FIG. 6B, for example, when angles of the first housing **510** and the second housing **520** are decreased to become the set third angle α_3 , the first fastening portion **5731** of the connecting member **573** may be fastened to the second fastening portion **5720** of the rotating member **572** as shown in FIG. 6B.

(113) FIG. 8A is a perspective view illustrating an air flow according to an operation of a fan component in a third state of an electronic device according to an embodiment, FIG. 8B is a perspective view of a vent member according to an embodiment, FIG. 8C is a cross-sectional view of the electronic device taken along a line VIIIc-VIIIc of FIG. 8A, and FIG. 8D is a cross-sectional view of the electronic device taken along a line VIId-VIId of FIG. 8A.

(114) Referring to FIGS. 8A to 8D, an electronic device **801** according to one embodiment may include a first housing **810**, a second housing **820**, a display **830**, a fan component **850**, and a hinge structure **870**.

(115) In one embodiment, the first housing **810** and the second housing **820** may form an exterior of the electronic device **801**. The first housing **810** may include a first surface **810A** and a second surface **810B** opposite to the first surface **810A**, and the second housing **820** may include a third surface **820A** facing the first surface **810A** and a fourth surface **820B** opposite to the third surface **820A**. In one embodiment, the second surface **810B** of the first housing **810** may be supported on a support surface (e.g., a floor surface or a support surface of a structure such as a desk). In one embodiment, a first space **8100** in which components for performing a function of the electronic device **801** are disposed may be formed in the first housing **810**. In one embodiment, the first housing **810** may include an opening (e.g., the opening **360** of FIG. 3C) that is formed to face the hinge structure **870**, and through which the first space **8100** communicates with the outside. In one embodiment, the display **830** may be disposed to be visually exposed to the outside through the third surface **820A**.

(116) In one embodiment, the fan component **850** may be disposed in the first space **8100**, and may adjust a temperature inside the first space **8100** by circulating air between the first space **8100** and the outside. In one embodiment, one fan component **850** may be disposed in the first space **8100**. For example, the fan component **850** may be disposed in a central portion of the first space **8100** relative to a direction of a rotation axis A. In this case, the fan component **850** may suck and circulate air from the outside through a left portion (e.g., a +X-axial direction) of the first housing **810** in the direction of the rotation axis A, and discharge the air to a right side (e.g., a -X-axial direction) of the first housing **810**.

(117) In one embodiment, the hinge structure **870** may rotatably connect the first housing **810** and the second housing **820**. In one embodiment, the hinge structure **870** may include a vent member **871**, a rotating member **872**, and a connecting member **873**.

(118) In one embodiment, the hinge structure **870** may include the vent member **871** for guiding a

flow of air between the first space **8100** and the outside. In one embodiment, the vent member **871** may include a first vent portion **8711** for guiding a flow of air introduced into the first space **8100** from the outside, and a second vent portion **8712** for guiding a flow of air discharged from the first space **8100** to the outside. In one embodiment, based on the direction of the rotation axis A, the first vent portion **8711** may be formed on a left side (e.g., a +X-axial direction) of the vent member **871**, and the second vent portion **8712** may be formed on a right side (e.g., a -X-axial direction) of the vent member **871**. The first vent portion **8711** and the second vent portion **8712** may be formed in the vent member **871** to be separated from each other so that air passing through the first vent portion **8711** and the second vent portion are not mixed with each other. In one embodiment, the vent member **871** may be disposed to face an opening **860** formed in the first housing **810** allowing the first space **8100** to communicate with the outside. In this case, the first vent portion **8711** may be disposed to face an intake portion **861** of the opening **860**, and the second vent portion **8712** may be disposed to face an exhaust portion **862** of the opening **860**.

(119) In one embodiment, the vent member **871** may rotate about the rotation axis A according to a rotation of the second housing **820** relative to the first housing **810** between a first state (e.g., the first state of FIG. 2A) and a third state of the electronic device **801**, and rotation about the rotation axis A may be stopped between the third state and a second state (e.g., the second state of FIG. 2B). In one embodiment, in a state in which the third surface **820A** of the second housing **820** has a third angle α_3 set relative to the first surface **810A** as shown in FIG. 8A, the vent member **871** may guide air F_i introduced into the first space **8100** through the intake portion **861** of the opening **860** from a space between the first surface **810A** and the third surface **820A** through the first vent portion **8711** as shown in FIG. 8C, and guide air F_o exhausted from the first space **8100** through the second vent portion **8712** to between the second surface **810B** and the fourth surface **820B** through the exhaust portion **862** of the opening **860** as shown in FIG. 8D.

(120) FIG. 9A is a perspective view illustrating an air flow according to an operation of a fan component in a third state of an electronic device according to an embodiment, FIG. 9B is a perspective view of a vent member according to an embodiment, FIG. 9C is an enlarged cross-sectional view of the electronic device taken along a line IXc-IXc of FIG. 9A, and FIG. 9D is an enlarged cross-sectional view of the electronic device taken along a line IXd-IXd of FIG. 9A.

(121) Referring to FIGS. 9A to 9D, an electronic device according to one embodiment may include a first housing **910**, a second housing **920**, a display **930**, a fan component **950**, and a hinge structure **970**.

(122) In one embodiment, the first housing **910** and the second housing **920** may form an exterior of the electronic device. The first housing **910** may include a first surface **910A** and a second surface **910B** opposite to the first surface **910A**. The second surface **910B** of the first housing **910** may be supported on a support surface (e.g., a floor surface or a support surface of a structure such as a desk) via the second surface **910B**. The second housing **920** may include a third surface **920A** facing the first surface **910A** and a fourth surface **920B** opposite to the third surface **920A**. In one embodiment, the display **930** may be visually exposed on the third surface **920A**. In one embodiment, a first space **9100** in which a component (e.g., a battery, a PCB, and the like) for performing a function of an electronic device is disposed may be formed in the first housing **910**. In one embodiment, the first housing **910** may include an opening **960** (e.g., the opening **360** of FIG. 3C) that is formed to face the hinge structure **970**, and through which air passes between the first space **9100** and the outside.

(123) In one embodiment, a plurality of fan components **950** may be disposed in the first space **9100**. The plurality of fan components **950** may be disposed spaced apart from each other in the first space **9100** and may generate an air flow in the first space **9100** according to each operation. For example, as shown in FIG. 9A, the plurality of fan components **950** may be disposed in the first space **9100** in a direction parallel to a rotation axis A, and may introduce air F_i from the outside to the first space **9100** and exhaust air F_o from the first space **9100** to the outside through the opening

960 according to each operation.

(124) In one embodiment, the hinge structure **970** may rotatably connect the first housing **910** and the second housing **920**. The hinge structure **970** may include a vent member **971** for guiding a flow of air passing between the first space **9100** and the outside. In one embodiment, the vent member **971** may include a first vent portion **9711** for guiding a flow of intake air F_i introduced into the first space **9100** from the outside, and a second vent portion **9712** for guiding a flow of exhaust air F_o discharged from the first space **9100** to the outside. In one embodiment, a plurality of first vent portions **9711a**, **9711b**, and **9711c** and second vent portions **9712a** and **9712b** may be formed in the vent member **971** to correspond to an arrangement of a plurality of fan components **950** disposed in the first space **9100**. For example, as shown in FIG. 9A, when a plurality of fan components **950** are disposed inside the first space **9100** to suck and exhaust air according to each operation, the vent member **971** may include a plurality of first vent portions **9711a**, **9711b**, and **9711c** and a plurality of second vent portions **9712a** and **9712b** formed in positions corresponding to a plurality of air intake portions **961** and exhaust portions **962**. In one embodiment, based on a direction parallel to the rotation axis A, the plurality of first vent portions **9711a**, **9711b**, and **9711c** and the plurality of second vent portions **9712a** and **9712b** may be formed alternately in the vent member **971**. In this case, the first vent portions **9711a**, **9711b**, and **9711c** and the second vent portions **9712a** and **9712b** formed in the vent member **971** may be formed separately so that air passing through each other are not mixed with each other.

(125) In one embodiment, the vent member **971** may rotate about the rotation axis A according to a rotation of the second housing **920** relative to the first housing **910** between a first state (e.g., the first state of FIG. 2A) and a third state of the electronic device, and rotation about the rotation axis A may be stopped between the third state and a second state (e.g., the second state of FIG. 2B). In one embodiment, in a state in which the third surface **920A** of the second housing **920** has a third angle α_3 set relative to the first surface **910A** as shown in FIG. 9A, the vent member **971** may guide air F_i introduced into the first space **9100** through the first vent portions **9711a**, **9711b**, and **9711c** from a space between the first surface **910A** and the third surface **920A** as shown in FIG. 9C, and guide air F_o exhausted from the first space **9100** through the second vent portions **9712a** and **9712b** to between the second surface **910B** and the fourth surface **920B** as shown in FIG. 9D.

(126) According to embodiments, an electronic device **201** may include a first housing **210** including a first surface **210A** (e.g., a front surface) and a second surface **210B** (e.g., a rear surface) which is opposite to the first surface **210A**, a second housing **220** including a third surface **220A** (e.g., a front surface) and a fourth surface **220B** (e.g., a rear surface) opposite to the third surface **220A**, a display **230** which displays an image and visually exposed through the third surface **220A**, one or more fan component **350** disposed in a first space **2100** inside the first housing **210**, and a hinge structure **370** rotatably connecting the first housing **210** and the second housing **220** about a rotation axis A such that an angle between the first surface **210A** and the third surface **220A** changes between a first angle in a first state in which the first surface **210A** and the third surface **220A** face each other and a second angle in a second state in which the first surface **210A** and the third surface **220A** are maximally widened, where the first housing **210** may include an opening **360** formed at a position facing the hinge structure **370**, and including an intake portion **361** configured to suck air into the first space **2100** from the outside according to an operation of the fan component **350** and exhaust portions **362a** and **362b** configured to discharge air from the first space **2100** to the outside, and the hinge structure **370** may be configured to rotate about the rotation axis A, and may include a vent member **471** in which a first vent portion **4711** for guiding a flow of air between the intake portion **361** and the outside, and a second vent portion **4712** for guiding a flow of air between the exhaust portions **362a** and **362b** and the outside are formed, and where in a third state in which the angle between the first surface **210A** and the third surface **220A** forms a third angle between the first angle and the second angle, the first vent portion **4711** and the second vent portion **4712** may guide the flow of air in different directions from each other.

(127) The first surface **210A** and the third surface **220A** may together form a plurality of front surfaces and the second surface **210B** and the fourth surface **220B** may together form a plurality of rear surface.

(128) In an embodiment, an electronic device includes a first housing including a first surface at a front side of the electronic device, a second surface which is opposite to the first surface and at a rear side of the electronic device, an inner space in communication with an outside of the first housing, an intake opening connected to the inner space and through which air flows to the inner space from the outside of the first housing, and an exhaust opening connected to the inner space and through which air flows from the inner space to the outside of the first housing, a second housing including a third surface at the front side of the electronic device, and a fourth surface which is opposite to the third surface and at the rear side of the electronic device, a display visually exposed at the third surface, a fan which is in the inner space of the first housing, and a hinge structure rotatably connecting the first housing and the second housing to each other, about a rotation axis. The hinge structure including a vent member which rotates about the rotation axis, together with rotation of the first housing relative to the second housing. The vent member including a first vent portion which guides first air flow between the intake opening and an outside of the electronic device, together with operation of the fan, and a second vent portion which guides second air flow between the exhaust opening and the outside of the electronic device, together with the operation of the fan, where the first surface and the third surface which face each other define a first angle between the first housing and the second housing, the first surface and the third surface which are disposed at a maximum rotational distance from each other define a second angle between the first housing and the second housing, and the first surface and the third surface which define a third angle between the first angle and the second angle, rotates the vent member to dispose the first vent portion guiding the first air flow in a direction relative to the front side of the electronic device, together with the second vent portion guiding the second air flow in a different direction from that of the first vent portion, relative to the front side of the electronic device.

(129) According to embodiments, the vent member **471** may rotate between the first state and the third state and stop between the third state and the second state. That is, the rotation of the first housing relative to the second housing, between the first angle and the third angle, rotates the vent member, and the rotation of the first housing relative to the second housing, between the third angle and the second angle, stops rotation of the vent member.

(130) According to embodiments, the vent member **471** may include a stopper **4714** formed on an outer surface, and the stopper **4714** may limit rotation of the vent member **471** during a change between the third state and the second state by being in contact with an end of the first housing **210** in the third state. That is, the hinge structure further includes a stopper connected to the vent member, the first surface and the third surface which define the third angle therebetween, dispose the stopper in contact with an end of the first housing, and the stopper in contact with the end of the first housing, limits rotation of the vent member during the rotation of the first housing relative to the second housing, between the third angle and the second angle.

(131) According to embodiments, the hinge structure **370** may further include a rotating member **472** at least partially fixed to the second housing **220** and rotatably connected to the first housing **210**, and a connecting member **473** connecting the rotating member **472** and the vent member **471**, and configured to transmit a rotational force according to a rotation of the rotating member **472** to the vent member **471**. In an embodiment, for example, the electronic device may include a rotational connecting member (e.g., connecting member **473** with rotating member **472**) which is fixed to and rotatable together with the second housing, connects the second housing to the hinge structure, at the vent member, and transmits a rotational force from the rotation of the first housing relative to the second housing, to the vent member.

(132) According to embodiments, the connecting member **473** may transmit the rotational force of the rotating member **472** to the vent member **471** such that the rotating member **472** and the vent

member **471** rotate together during a change between the first state and the third state, and may prevent transmission of the rotational force of the rotating member **472** to the vent member **471** such that the rotating member **472** rotates independently relative to the vent member **471** during a change between the third state and the second state. That is, the rotation of the first housing relative to the second housing, between the first angle and the third angle, rotates the rotational connecting member together with the vent member, and the rotation of the first housing relative to the second housing, between the third angle and the second angle, prevents transmission of the rotational force to the vent member and rotates the rotational connecting member independently from the vent member.

(133) According to embodiments, in the connecting member **473**, a first connecting surface **4730a** may be attached to an end of the vent member **471** facing the rotating member **472** along a direction of the rotation axis A, and the connecting member **473** may include a first fastening portion **4731** formed on a second connecting surface **4730b** opposite to the first connecting surface **4730a**, and the rotating member **472** may include a second fastening portion **4720** formed at an end of the rotating member **472** facing the vent member **471** along the direction of the rotation axis A, where the first fastening portion **4731** and the second fastening portion **4720** may be engaged and fastened during a change between the first state and the third state, and separated during a change between the third state and the second state. That is, the rotational connecting member further includes a rotating member at which the rotational connecting member is fixed to the second housing, and a connecting member connecting the rotating member and the vent member to each other, the connecting member transmitting the rotational force to the vent member. The connecting member includes a first fastening portion engageable with the rotating member, the rotating member includes a second fastening portion at which the first fastening portion of the connecting member is engaged, the rotation of the first housing relative to the second housing, between the first angle and the third angle, engages the first and second fastening portions, and the rotation of the first housing relative to the second housing, between the third angle and the second angle, disposes the first and second fastening portions disengaged with each other.

(134) According to embodiments, a concave portion **4710** that is concave in the direction of the rotation axis A and overlaps with the first fastening portion may be formed at the end of the vent member **471**, and while the first state is changing to the second state through operation, the first fastening portion **4731** may be pressed in a direction of the concave portion **4710** to be separated from the second fastening portion **4720**. That is, the vent member further includes a concave portion defined at an end of the vent member, the first fastening portion overlaps the concave portion of the vent member, and the rotation of the first housing relative to the second housing, between the first angle and the second angle, presses the first fastening portion toward the concave portion to separate the first fastening portion from the second fastening portion.

(135) According to embodiments, the connecting member **473** may be formed of an elastic material, and while the third state is changing to the second state through operation, the first fastening portion **4731** may be separated from the second fastening portion **4720** while being deformed in the direction of the rotation axis A. That is, the rotation of the first housing relative to the second housing, between the third angle and the second angle, deforms the first fastening portion in the direction of the rotation axis, to separate the first fastening portion from the second fastening portion.

(136) According to embodiments, in the third state, the first vent portion **4711** may guide the air sucked into the intake portion **361** from between the first surface **210A** and the third surface **220A**, and the second vent portion **4712** may guide the air discharged from the exhaust portions **362a** and **362b** from between the second surface **210B** and the fourth surface **220B**. That is, the first surface and the third surface which define the third angle therebetween, define the first air flow guided by the first vent portion, from the first surface and the third surface each at the front side of the electronic device, and toward the intake opening of the first housing, together with defining the

second air flow guided by the second vent portion, from the exhaust opening of the first housing, toward the second surface and the fourth surface each at the rear side of the electronic device.

(137) According to embodiments, in a state in which an angle between the first surface **210A** and the third surface **220A** is greater than or equal to the third angle, a direction in which the air of the first vent portion **4711** and the second vent portion **4712** is guided relative to the first surface **210A** may be constant. That is, the vent member defines an air flow direction along the vent member, relative to the front side of the electronic device, and the first surface and the third surface which define the third angle therebetween, and the first surface and the third surface which define the second angle therebetween, rotate the vent member to define a same air flow direction along the vent member.

(138) According to embodiments, in the first state, the first vent portion **4711** may close the intake portion **361**, and the second vent portion **4712** may close the exhaust portions **362a** and **362b**. That is, the first surface and the third surface which define the first angle therebetween, dispose the first vent portion of the hinge structure rotated to close the intake opening of the first housing, together with disposing the second vent portion of the hinge structure rotated to close the exhaust opening of the first housing.

(139) According to embodiments, based on a cross-section perpendicular to the rotation axis A, the first vent portion **4711** may include an inwardly concave shape, and the second vent portion **4712** may include an inwardly concave shape in a different direction from the first vent portion **4711**. That is, within the hinge structure, the first vent portion includes an inwardly concave shape open in a direction, relative to the rotation axis, and the second vent portion includes an inwardly concave shape open in a different direction from the direction of the inwardly concave shape of the first vent portion, relative to the rotation axis.

(140) According to embodiments, based on a direction parallel to the rotation axis A, the vent member **471** may be formed such that the second vent portions **4712a** and **4712b** are positioned on opposite sides of the first vent portion **4711**, respectively. That is, within the vent member, the second vent portion is provided in plural to define second vent portions, and along the rotation axis, the second vent portions are on opposite sides of the first vent portion, respectively.

(141) According to embodiments, a plurality of the first vent portions **9711** and a plurality of the second vent portions **9712** may be alternately formed in the vent member **971** along the direction parallel to the rotation axis A. That is, within the vent member, the first vent portion and the second vent portion are each provided in plural to respectively define a plurality of first vent portions and a plurality of second vent portions, and the plurality of first vent portions alternate with the plurality of second vent portions, along the rotation axis.

(142) According to embodiments, the first vent portion **4711** and the second vent portion **4712** may be separately formed along a direction parallel to the rotation axis A so that the air guided through the first vent portion **4711** and the air guided through the second vent portion **4712** are not mixed with each other. That is, within the vent member, the first vent portion and the second vent portion are spaced apart from each other along the rotation axis.

(143) According to embodiments, an electronic device **201** may include a first housing **210** including a first surface **210A** and a second surface **210B** opposite to the first surface **210A**, a second housing **220** including a third surface **220A** and a fourth surface **220B** opposite to the third surface **220A**, and may be configured to rotate about a rotation axis A relative to the first housing **210** allowing change between a first state in which the third surface **220A** forms a first angle relative to the first surface **210A** and a second state in which the third surface **220A** forms a second angle relative to the first surface **210A**, a display **230** disposed on the third surface **220A**, one or more fan component **350** disposed in a first space **2100** inside the first housing **210**, and a hinge structure **370** disposed along the rotation axis A and rotatably connecting the first housing **210** and the second housing **220**, where the first housing **210** includes an opening **360** formed at an end of the first housing facing the hinge structure **370**, the opening **360** being open in a direction parallel

to the rotation axis A and including an intake portion **361** configured to suck external air into the first space **2100** and exhaust portions **362a** and **362b** configured to discharge air from the first space **2100** to the outside, according to an operation of the fan component **350**, and the hinge structure **370** may include a vent member **471** in a longitudinal direction parallel to the rotation axis A and including a first vent portion **4711** formed in a portion overlapping the intake portion **361** and a second vent portion **4712** formed in a portion overlapping the exhaust portions **362a** and **362b** in a state in which the opening **360** is viewed, and in a state in which the third surface **220A** has an angle greater than or equal to a third angle between the first angle and the second angle relative to the first surface **210A**, the intake portion **361** may suck air from a space between the first surface **210A** and the third surface **220A** through the first vent portion **4711**, and the exhaust portions **362a** and **362b** may exhaust air between the second surface **210B** and the fourth surface **220B** through the second vent portion **4712**. In an embodiment, the first surface and the third surface which define a third angle between the first angle and the second angle, rotates the vent member to dispose the first vent portion guiding a first air flow from the first surface and the third surface each at the front side of the electronic device, toward the intake opening of the first housing, together with defining a second air flow guided by the second vent portion, from the exhaust opening of the first housing, toward the second surface and the fourth surface each at the rear side of the electronic device.

(144) According to embodiments, the vent member **471** may rotate about a rotation axis A according to the rotation of the second housing **220** relative to the first housing **210**, during a change between the first state and the third state, and stop rotating during a change between the third state and the second state. That is, the rotation of the first housing relative to the second housing, between the first angle and the third angle, rotates the vent member, and the rotation of the first housing relative to the second housing, between the third angle and the second angle, stops rotation of the vent member.

(145) According to embodiments, the hinge structure **370** may further include a rotating member **472** connecting the first housing **210** and the second housing **220** and configured to rotate about the rotation axis A according to the rotation of the second housing **220** relative to the first housing **210**, and a connecting member **473** connecting the rotating member **472** and the vent member **471** in a direction of the rotation axis A, and the connecting member may transmit a rotational force of the rotating member **472** to the vent member **471** during a change between the first state and the third state, and prevent transmission of the rotational force of the rotating member **472** to the vent member **471** during a change between the third state and the second state. That is, a rotational connecting member which is fixed to and rotatable together with the second housing, connects the second housing to the hinge structure, at the vent member, and transmits a rotational force from the rotation of the first housing relative to the second housing, to the vent member, the rotation of the first housing relative to the second housing, between the first angle and the third angle, rotates the rotational connecting member together with the vent member, and the rotation of the first housing relative to the second housing, between the third angle and the second angle, prevents transmission of the rotational force to the vent member and rotates the rotational connecting member independently from the vent member.

(146) According to embodiments, the vent member **471** may further include a stopper **4714** formed on an outer surface, and while the first state is changing to the second state through operation, in response to the angle of the third surface **220A** relative to the first surface **210A** reaching the third angle, the stopper **4714** may limit rotation of the vent member **471** by being in contact with an end of the first housing **210**. That is, the hinge structure further includes a stopper connected to the vent member, the first surface and the third surface which define the third angle therebetween, dispose the stopper in contact with an end of the first housing, and the stopper in contact with the end of the first housing limits rotation of the vent member during the rotation of the first housing relative to the second housing, between the third angle and the second angle.

(147) According to embodiments, an electronic device **201** may include a first housing **210** including a first surface **210A** and a second surface **210B** opposite to the first surface **210A**, a second housing **220** including a third surface **220A** and a fourth surface **220B** opposite to the third surface **220A**, a display **230** visually exposed through the third surface **220A**, one or more fan component **350** disposed in a first space **2100** inside the first housing **210**, and a hinge structure **370** rotatably connecting the first housing **210** and the second housing **220** allowing change between a first state in which the first surface **210A** and the third surface **220A** form a first angle facing each other and a second state in which the first surface **210A** and the third surface **220A** form a second angle, where the first housing **210** may include an opening **360** including an intake portion **361** configured to suck air into the first space **2100** from the outside according to an operation of the fan component **350** and exhaust portions **362a** and **362b** configured to discharge air from the first space **2100** to the outside, and the hinge structure **370** may include a rotating member **472** connecting the first housing **210** and the second housing **220** and configured to rotate about the rotation axis A according to the rotation of the second housing **220** relative to the first housing **210**, based on a third state in which the first surface **210A** and the third surface **220A** form a third angle between the first angle and the second angle, a vent member **471** including a first vent portion **4711** through which the intake portion **361** communicates with the outside, and a second vent portion **4712** through which the exhaust portions **362a** and **362b** communicate with the outside, and a connecting member **473** connecting the rotating member **472** and the vent member **471**, and the connecting member **473** may transmit a rotational force of the rotating member **472** to the vent member **471** during a change between the first state and the third state, and prevent transmission of the rotational force of the rotating member **472** to the vent member **471** during a change between the third state and the second state. In an embodiment, the rotation of the first housing relative to the second housing, between the first angle and a third angle between the first angle and the second angle, rotates the rotational connecting member together with the vent member, and the rotation of the first housing relative to the second housing, between the third angle and the second angle, prevents transmission of the rotational force to the vent member, to stop rotation of the vent member.

Claims

1. An electronic device, comprising: a first housing comprising a first surface at a front side of the electronic device, a second surface which is opposite to the first surface and at a rear side of the electronic device, an inner space in communication with an outside of the first housing, an intake opening connected to the inner space and through which air flows to the inner space from the outside of the first housing, and an exhaust opening connected to the inner space and through which air flows from the inner space to the outside of the first housing; a second housing comprising a third surface at the front side of the electronic device, and a fourth surface which is opposite to the third surface and at the rear side of the electronic device; a display visually exposed at the third surface; a fan which is in the inner space of the first housing; and a hinge structure rotatably connecting the first housing and the second housing to each other, about a rotation axis, the hinge structure comprising: a vent member which rotates about the rotation axis, together with rotation of the first housing relative to the second housing, and the vent member comprising: a first vent portion which guides first air flow between the intake opening and an outside of the electronic device, together with operation of the fan, and a second vent portion which guides second air flow between the exhaust opening and the outside of the electronic device, together with the operation of the fan, wherein the first surface and the third surface which face each other define a first angle between the first housing and the second housing, the first surface and the third surface which are disposed at a maximum rotational distance from each other define a second angle between the first housing and the second housing, and the first surface and the third surface which define a third

angle between the first angle and the second angle, rotates the vent member to dispose the first vent portion guiding the first air flow in a direction relative to the front side of the electronic device, together with the second vent portion guiding the second air flow in a different direction from that of the first vent portion, relative to the front side of the electronic device.

2. The electronic device of claim 1, wherein the rotation of the first housing relative to the second housing, between the first angle and the third angle, rotates the vent member, and the rotation of the first housing relative to the second housing, between the third angle and the second angle, stops rotation of the vent member.

3. The electronic device of claim 2, wherein the hinge structure further comprises a stopper connected to the vent member, the first surface and the third surface which define the third angle therebetween, dispose the stopper in contact with an end of the first housing, and the stopper in contact with the end of the first housing, limits rotation of the vent member during the rotation of the first housing relative to the second housing, between the third angle and the second angle.

4. The electronic device of claim 2, wherein the hinge structure further comprises a rotational connecting member which is fixed to and rotatable together with the second housing, connects the second housing to the hinge structure, at the vent member, and transmits a rotational force from the rotation of the first housing relative to the second housing, to the vent member.

5. The electronic device of claim 4, wherein the rotation of the first housing relative to the second housing, between the first angle and the third angle, rotates the rotational connecting member together with the vent member; and the rotation of the first housing relative to the second housing, between the third angle and the second angle, prevents transmission of the rotational force to the vent member and rotates the rotational connecting member independently from the vent member.

6. The electronic device of claim 4, wherein the rotational connecting member further comprises: a rotating member at which the rotational connecting member is fixed to the second housing, and a connecting member connecting the rotating member and the vent member to each other, the connecting member transmitting the rotational force to the vent member, wherein the connecting member comprises a first fastening portion engageable with the rotating member, the rotating member comprises a second fastening portion at which the first fastening portion of the connecting member is engaged, the rotation of the first housing relative to the second housing, between the first angle and the third angle, engages the first and second fastening portions, and the rotation of the first housing relative to the second housing, between the third angle and the second angle, disposes the first and second fastening portions disengaged with each other.

7. The electronic device of claim 6, wherein the vent member further comprises a concave portion defined at an end of the vent member, the first fastening portion overlaps the concave portion of the vent member, and the rotation of the first housing relative to the second housing, between the third angle and the second angle, presses the first fastening portion toward the concave portion to separate the first fastening portion from the second fastening portion.

8. The electronic device of claim 6, wherein the connecting member comprises an elastic material, and the rotation of the first housing relative to the second housing, between the third angle and the second angle, deforms the first fastening portion in the direction of the rotation axis, to separate the first fastening portion from the second fastening portion.

9. The electronic device of claim 1, wherein the first surface and the third surface which define the third angle therebetween, define the first air flow guided by the first vent portion, from the first surface and the third surface each at the front side of the electronic device, and toward the intake opening of the first housing, together with defining the second air flow guided by the second vent portion, from the exhaust opening of the first housing, toward the second surface and the fourth surface each at the rear side of the electronic device.

10. The electronic device of claim 9, wherein the vent member defines an air flow direction along the vent member, relative to the front side of the electronic device, and the first surface and the third surface which define the third angle therebetween, and the first surface and the third surface

which define the second angle therebetween, rotate the vent member to define a same air flow direction along the vent member.

11. The electronic device of claim 1, wherein the first surface and the third surface which define the first angle therebetween, dispose the first vent portion of the hinge structure rotated to close the intake opening of the first housing, together with disposing the second vent portion of the hinge structure rotated to close the exhaust opening of the first housing.

12. The electronic device of claim 1, wherein within the hinge structure, the first vent portion comprises an inwardly concave shape open in a direction, relative to the rotation axis, and the second vent portion comprises an inwardly concave shape open in a different direction from the direction of the inwardly concave shape of the first vent portion, relative to the rotation axis.

13. The electronic device of claim 1, wherein within the vent member, the second vent portion is provided in plural to define second vent portions, and along the rotation axis, the second vent portions are on opposite sides of the first vent portion, respectively.

14. The electronic device of claim 1, wherein within the vent member, the first vent portion and the second vent portion are each provided in plural to respectively define a plurality of first vent portions and a plurality of second vent portions, and the plurality of first vent portions alternate with the plurality of second vent portions, along the rotation axis.

15. The electronic device of claim 1, wherein within the vent member, the first vent portion and the second vent portion are spaced apart from each other along the rotation axis.

16. An electronic device, comprising: a first housing comprising a first surface at a front side of the electronic device, a second surface which is opposite to the first surface and at a rear side of the electronic device, an inner space in communication with an outside of the first housing, an intake opening connected to the inner space and through which air flows to the inner space from the outside of the first housing, and an exhaust opening connected to the inner space and through which air flows from the inner space to the outside of the first housing; a second housing rotatable relative to the first housing, about a rotation axis, the second housing comprising a third surface at the front side of the electronic device, and a fourth surface which is opposite to the third surface and at the rear side of the electronic device; a display visually exposed at the third surface; a fan which is in the inner space of the first housing; and a hinge structure at the rotation axis and rotatably connecting the first housing and the second housing to each other, the hinge structure comprising: a vent member which is extended parallel to the rotation axis, the vent member comprising a first vent portion which faces the intake opening, and a second vent portion which faces the exhaust opening, wherein the vent member rotates about the rotation axis, together with rotation of the first housing relative to the second housing, and guides air flow relative to the electronic device, together with operation of the fan, wherein the first surface and the third surface which face each other define a first angle between the first housing and the second housing, the first surface and the third surface which are disposed at a maximum rotational distance from each other define a second angle between the first housing and the second housing, and the first surface and the third surface which define a third angle between the first angle and the second angle, rotates the vent member to dispose the first vent portion guiding a first air flow from the first surface and the third surface each at the front side of the electronic device, toward the intake opening of the first housing, together with defining a second air flow guided by the second vent portion, from the exhaust opening of the first housing, toward the second surface and the fourth surface each at the rear side of the electronic device.

17. The electronic device of claim 16, wherein the rotation of the first housing relative to the second housing, between the first angle and the third angle, rotates the vent member, and the rotation of the first housing relative to the second housing, between the third angle and the second angle, stops rotation of the vent member.

18. The electronic device of claim 16, wherein the hinge structure further comprises: a rotational connecting member which is fixed to and rotatable together with the second housing, connects the

second housing to the hinge structure, at the vent member, and transmits a rotational force from the rotation of the first housing relative to the second housing, to the vent member, the rotation of the first housing relative to the second housing, between the first angle and the third angle, rotates the rotational connecting member together with the vent member; and the rotation of the first housing relative to the second housing, between the third angle and the second angle, prevents transmission of the rotational force to the vent member and rotates the rotational connecting member independently from the vent member.

19. The electronic device of claim 18, wherein the hinge structure further comprises a stopper connected to the vent member, the first surface and the third surface which define the third angle therebetween, dispose the stopper in contact with an end of the first housing, and the stopper in contact with the end of the first housing limits rotation of the vent member during the rotation of the first housing relative to the second housing, between the third angle and the second angle.

20. An electronic device, comprising: a first housing comprising a first surface at a front side of the electronic device, a second surface which is opposite to the first surface and at a rear side of the electronic device, an inner space in communication with an outside of the first housing, an intake opening connected to the inner space and through which air flows to the inner space from the outside of the first housing, and an exhaust opening connected to the inner space and through which air flows from the inner space to outside the first housing; a second housing comprising a third surface at the front side of the electronic device, and a fourth surface which is opposite to the third surface and at the rear side of the electronic device; a display visually exposed at the third surface; a fan which is in the inner space of the first housing; and a hinge structure rotatably connecting the first housing and the second housing to each other, the hinge structure comprising: a vent member which rotates about the rotation axis, together with rotation of the first housing relative to the second housing, the vent member comprising: a first vent portion which guides first air flow between the intake opening and outside of the electronic device, together with operation of the fan, and a second vent portion which guides second air flow between the exhaust opening and the outside of the electronic device, together with operation of the fan, and a rotational connecting member which is fixed to and rotatable together with the second housing, connects the second housing to the hinge structure, at the vent member, and transmits a rotational force from the rotation of the first housing relative to the second housing, to the vent member, wherein the first surface and the third surface which face each other define a first angle between the first housing and the second housing, the first surface and the third surface which are disposed at a maximum rotational distance from each other define a second angle between the first housing and the second housing, the rotation of the first housing relative to the second housing, between the first angle and a third angle which is between the first angle and the second angle, rotates the rotational connecting member together with the vent member; and the rotation of the first housing relative to the second housing, between the third angle and the second angle, prevents transmission of the rotational force to the vent member, to stop rotation of the vent member.
