

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405661
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Nguyen; Shem et al.

Devices and methods for controlling electronic devices or systems with physical objects

Abstract

Some examples described in this disclosure are performed at a first electronic device (e.g., a computer system) that is in communication with a display and one or more input devices. In some examples, the first electronic device detects a change in a physical environment of the first electronic device due to movement of one or more physical objects in the physical environment indicative of a user input. In some examples, the first electronic device performs a first action at the first electronic device or at a second electronic device in communication with the first electronic device in accordance with the change in the physical environment due to movement of the one or more physical objects in the physical environment.

Inventors:	Nguyen; Shem (Oakland, CA), Prakkamakul; Soravis (Emeryville, CA)
Applicant:	Apple Inc. (Cupertino, CA)
Family ID:	87055525
Assignee:	Apple Inc. (Cupertino, CA)
Appl. No.:	18/151206
Filed:	January 06, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230221799 A1	Jul. 13, 2023

Related U.S. Application Data

us-provisional-application US 63266626 20220110

Publication Classification

Int. Cl.: G06F3/01 (20060101); G06F3/04842 (20220101); G10H1/00 (20060101)

U.S. Cl.:

CPC G06F3/013 (20130101); G06F3/017 (20130101); G10H1/0008 (20130101); G06F3/04842 (20130101); G10H2210/375 (20130101); G10H2220/455 (20130101)

Field of Classification Search

CPC: G06F (3/013); G06F (3/017); G06F (3/04842); G10H (1/0008); G10H (2220/355); G10H (2210/375)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10186086	12/2018	Giraldi	N/A	G06F 3/013
11635808	12/2022	Nagar	345/156	G06F 3/04815
2013/0257751	12/2012	Stafford	345/173	G06F 3/011
2013/0321271	12/2012	Bychkov	345/158	G06F 3/017
2014/0361988	12/2013	Katz	345/156	G06T 7/70
2015/0309629	12/2014	Amariutei	345/173	G06F 3/017
2017/0192493	12/2016	Ofek	N/A	G06F 3/04883
2019/0129607	12/2018	Saurabh	N/A	G06F 3/011
2020/0257371	12/2019	Sung	N/A	G06F 3/017
2020/0301513	12/2019	Mejia Cobo	N/A	G06F 3/011
2023/0251720	12/2022	Wren	715/702	G06F 3/04883

OTHER PUBLICATIONS

Polap et al., "Obstacle Detection as a Safety Alert in Augmented Reality Models by the Use of Deep Learning Techniques," Sensors, vol. 17, No. 2803, Dec. 4, 2017, 16 pages. cited by applicant
Qeshmy et al., "Managing Human Errors: Augmented Reality Systems as a Tool in the Quality Journey," Procedia Manufacturing, vol. 28, 2019, pp. 24-30. cited by applicant

Primary Examiner: Chow; Doon Y

Attorney, Agent or Firm: Kubota & Basol LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims the benefit of U.S. Provisional Application No. 63/266,626, filed Jan. 10, 2022, the content of which is incorporated herein by reference in its entirety for all purposes.

FIELD

(1) This relates generally to computer systems that detect a change in a physical environment and

perform an action at a respective computer system in accordance the detected change in the physical environment.

BACKGROUND

(2) A user may interact with a computer system using one or more input devices (e.g., a mouse, a touch sensor, a proximity sensor, and/or an image sensor). Sensors of the computer system can be used to capture images of the physical environment around the computer system (e.g., an operating environment of the computer system).

SUMMARY

(3) Some examples described in this disclosure are performed at a first electronic device (e.g., a computer system) that is in communication with a display and one or more input devices. In some examples, the first electronic device detects a change in a physical environment of the first electronic device due to movement of one or more physical objects in the physical environment indicative of a user input. In some examples, the first electronic device performs a first action at the first electronic device or at a second electronic device in communication with the first electronic device in accordance with the change in the physical environment due to movement of the one or more physical objects in the physical environment.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIGS. 1A-1B illustrate example block diagrams of architectures for a system or device in accordance with some examples of the disclosure.
- (2) FIGS. 2A-2E illustrate examples of an electronic device adjusting the volume of a television based on movement of one or more physical objects in accordance with some examples of the disclosure.
- (3) FIGS. 3A-3D illustrate examples of an electronic device detecting movement of one or more physical objects to toggle on/off a system function of the electronic device or at a second electronic device in accordance with some examples of the disclosure.
- (4) FIGS. 4A-4B illustrate examples of an electronic device performing an action at the electronic device or at a second electronic device in response to detecting a text-based input command.
- (5) FIGS. 5A-5C illustrate examples of an electronic device detecting one or more physical objects in the physical environment to construct a musical sequence (e.g., a sequence of musical notes) in accordance with some examples of the disclosure.
- (6) FIG. 6 illustrates process 600 for performing an action at a first electronic device or second electronic device in accordance with some examples of the disclosure.

DETAILED DESCRIPTION

- (7) In the following description, reference is made to the accompanying drawings which form a part hereof, and in which it is shown by way of illustration specific examples that are optionally practiced. It is to be understood that other examples of the disclosure are optionally used and structural changes are optionally made without departing from the scope of the disclosure.
- (8) The terminology used in the description of the various described examples herein is for the purpose of describing particular examples only and is not intended to be limiting. As used in the description of the various described examples and the appended claims, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other

features, integers, steps, operations, elements, components, and/or groups thereof.

(9) Further, although the following description uses terms “first,” “second,” etc. to describe various elements, these elements should not be limited by the terms. These terms are only used to distinguish one element from another. For example, a first device could be termed a second device, and, similarly, a second device could be termed a first device, without departing from the scope of the various described examples. The first device and the second device are both devices, but they are typically not the same device.

(10) As described herein, the term “if”, optionally, means “when” or “upon” or “in response to determining” or “in response to detecting,” depending on the context. Similarly, the phrase “if it is determined” or “if [a stated condition or event] is detected” is, optionally, construed to mean “upon determining” or “in response to determining” or “upon detecting [the stated condition or event]” or “in response to detecting [the stated condition or event],” depending on the context.

(11) A physical environment refers to a physical world that people can sense and/or interact with without aid of electronic devices. The physical environment may include physical features such as a physical surface or a physical object. For example, the physical environment corresponds to a physical park that includes physical trees, physical buildings, and physical people. People can directly sense and/or interact with the physical environment such as through sight, touch, hearing, taste, and smell. In contrast, an extended reality (XR) environment refers to a wholly or partially simulated environment that people sense and/or interact with via an electronic device. For example, the XR environment may include augmented reality (AR) content, mixed reality (MR) content, virtual reality (VR) content, and/or the like. An XR environment is often referred to herein as a computer-generated environment. With an XR system, a subset of a person's physical motions, or representations thereof, are tracked, and, in response, one or more characteristics of one or more virtual objects simulated in the XR environment are adjusted in a manner that comports with at least one law of physics. As one example, the XR system may detect head movement and, in response, adjust graphical content and an acoustic field presented to the person in a manner similar to how such views and sounds would change in a physical environment. As another example, the XR system may detect movement of the electronic device presenting the XR environment (e.g., a mobile phone, a tablet, a laptop, or the like) and, in response, adjust graphical content and an acoustic field presented to the person in a manner similar to how such views and sounds would change in a physical environment. In some situations (e.g., for accessibility reasons), the XR system may adjust characteristic(s) of graphical content in the XR environment in response to representations of physical motions (e.g., vocal commands).

(12) There are many different types of electronic systems that enable a person to sense and/or interact with various XR environments. Examples include head mountable systems, projection-based systems, heads-up displays (HUDs), vehicle windshields having integrated display capability, windows having integrated display capability, displays formed as lenses designed to be placed on a person's eyes (e.g., similar to contact lenses), headphones/earphones, speaker arrays, input systems (e.g., wearable or handheld controllers with or without haptic feedback), smartphones, tablets, and desktop/laptop computers. A head mountable system may have one or more speaker(s) and an integrated opaque display. Alternatively, a head mountable system may be configured to accept an external opaque display (e.g., a smartphone). The head mountable system may incorporate one or more imaging sensors to capture images or video of the physical environment, and/or one or more microphones to capture audio of the physical environment. Rather than an opaque display, a head mountable system may have a transparent or translucent display. The transparent or translucent display may have a medium through which light representative of images is directed to a person's eyes. The display may utilize digital light projection, OLEDs, LEDs, μ LEDs, liquid crystal on silicon, laser scanning light source, or any combination of these technologies. The medium may be an optical waveguide, a hologram medium, an optical combiner, an optical reflector, or any combination thereof. In some implementations, the transparent or

translucent display may be configured to become opaque selectively. Projection-based systems may employ retinal projection technology that projects graphical images onto a person's retina. Projection systems also may be configured to project virtual objects into the physical environment, for example, as a hologram or on a physical surface.

(13) FIGS. 1A-1B illustrate example block diagrams of architectures for a system or device in accordance with some examples of the disclosure. As illustrated in FIG. 1A, device **100** optionally includes various sensors (e.g., one or more hand tracking sensor(s) **102**, one or more location sensor(s) **104**, one or more image sensor(s) **106**, one or more touch-sensitive surface(s) **109**, one or more motion and/or orientation sensor(s) **110**, one or more eye tracking sensor(s) **112**, one or more microphone(s) **113** or other audio sensors, etc.), one or more display generation component(s) **114**, one or more speaker(s) **116**, one or more processor(s) **118**, one or more memories **120**, and/or communication circuitry **122**. One or more communication buses **108** are optionally used for communication between the above mentioned components of device **100**. In some examples, device **100** is a portable device, such as a mobile phone, smart phone, a tablet computer, a laptop computer, an auxiliary device in communication with another device, etc.

(14) Communication circuitry **122** optionally includes circuitry for communicating with electronic devices, networks, such as the Internet, intranets, a wired network and/or a wireless network, cellular networks and wireless local area networks (LANs). Communication circuitry **122** optionally includes circuitry for communicating using near-field communication (NFC) and/or short-range communication, such as Bluetooth®.

(15) Processor(s) **118** optionally include one or more general purpose processors, one or more graphics processors, and/or one or more digital signal processors (DSPs). In some examples, memory **120** is a non-transitory computer-readable storage medium (e.g., flash memory, random access memory, or other volatile or non-volatile memory or storage) that stores computer-readable instructions and/or programs configured to be executed by processor(s) **118** to perform the techniques, processes, and/or methods described below. In some examples, memories **120** include more than one non-transitory computer-readable storage medium. A non-transitory computer-readable storage medium can be any medium (e.g., excluding a signal) that can tangibly contain or store computer-executable instructions for use by or in connection with the instruction execution system, apparatus, or device. In some examples, the storage medium is a transitory computer-readable storage medium. In some examples, the storage medium is a non-transitory computer-readable storage medium. The non-transitory computer-readable storage medium can include, but is not limited to, magnetic, optical, and/or semiconductor storages. Examples of such storage include magnetic disks, optical discs based on CD, DVD, or Blu-ray technologies, as well as persistent solid-state memory such as flash, solid-state drives, and the like.

(16) Display generation component(s) **114** optionally include a single display (e.g., a liquid-crystal display (LCD), organic light-emitting diode (OLED), or other types of display). In some examples, display generation component(s) **114** include multiple displays. In some examples, display generation component(s) **114** includes a display with a touch-sensitive surface (e.g., a touch screen), a projector, a holographic projector, a retinal projector, etc.

(17) In some examples, device **100** includes touch-sensitive surface(s) **109** configured to receive user inputs (touch and/or proximity inputs), such as tap inputs and swipe inputs or other gestures. In some examples, display generation component(s) **114** and touch-sensitive surface(s) **109** together form touch-sensitive display(s) (e.g., a touch screen integrated with device **100** or external to device **100** that is in communication with device **100**).

(18) Image sensors(s) **106** optionally include one or more visible light image sensor, such as charged coupled device (CCD) sensors, and/or complementary metal-oxide-semiconductor (CMOS) sensors operable to obtain images of physical objects from the real-world environment. Image sensor(s) **106** optionally include one or more infrared (IR) or near infrared (NIR) sensors, such as a passive or an active IR or NIR sensor, for detecting infrared or near infrared light from

the real-world environment. For example, an active IR sensor includes an IR emitter for emitting infrared light into the real-world environment. Image sensor(s) **106** optionally include one or more cameras configured to capture movement of physical objects in the real-world environment. Image sensor(s) **106** optionally include one or more depth sensors configured to detect the distance of physical objects from device **100**. In some examples, information from one or more depth sensors can allow the device to identify and differentiate objects in the real-world environment from other objects in the real-world environment. In some examples, one or more depth sensors can allow the device to determine the texture and/or topography of objects in the real-world environment.

(19) In some examples, device **100** uses CCD sensors, event cameras, and depth sensors in combination to detect the physical environment around device **100**. In some examples, image sensor(s) **106** include a first image sensor and a second image sensor. The first image sensor and the second image sensor work together and are optionally configured to capture different information of physical objects in the real-world environment. In some examples, the first image sensor is a visible light image sensor and the second image sensor is a depth sensor. In some examples, device **100** uses image sensor(s) **106** to detect the position and orientation of device **100** and/or display generation component(s) **114** in the real-world environment. For example, device **100** uses image sensor(s) **106** to track the position and orientation of display generation component(s) **114** relative to one or more fixed objects in the real-world environment.

(20) In some examples, device **100** optionally includes hand tracking sensor(s) **102** and/or eye tracking sensor(s) **112**. Hand tracking sensor(s) **102** are configured to track the position/location of a user's hands and/or fingers, and/or motions of the user's hands and/or fingers with respect to the computer-generated environment, relative to the display generation component(s) **114**, and/or relative to another coordinate system. Eye tracking sensor(s) **112** are configured to track the position and movement of a user's gaze (eyes, face, and/or head, more generally) with respect to the real-world or computer-generated environment and/or relative to the display generation component(s) **114**. In some examples, hand tracking sensor(s) **102** and/or eye tracking sensor(s) **112** are implemented together with the display generation component(s) **114** (e.g., in the same device). In some examples, the hand tracking sensor(s) **102** and/or eye tracking sensor(s) **112** are implemented separate from the display generation component(s) **114** (e.g., in a different device).

(21) In some examples, the hand tracking sensor(s) **102** uses image sensor(s) **106** (e.g., one or more IR cameras, 3D cameras, depth cameras, etc.) that capture three-dimensional information from the real-world including one or more hands. In some examples, the hands can be resolved with sufficient resolution to distinguish fingers and their respective positions. In some examples, one or more image sensor(s) **106** are positioned relative to the user to define a field of view of the image sensor(s) and an interaction space in which finger/hand position, orientation and/or movement captured by the image sensors are used as inputs (e.g., to distinguish from a user's resting hand or other hands of other persons in the real-world environment). Tracking the fingers/hands for input (e.g., gestures) can be advantageous in that it provides an input means that does not require the user to touch or hold input device, and using image sensors allows for tracking without requiring the user to wear a beacon or sensor, etc. on the hands/fingers.

(22) In some examples, eye tracking sensor(s) **112** includes one or more eye tracking cameras (e.g., IR cameras) and/or illumination sources (e.g., IR light sources/LEDs) that emit light towards a user's eyes. Eye tracking cameras may be pointed towards a user's eyes to receive reflected light from the light sources directly or indirectly from the eyes. In some examples, both eyes are tracked separately by respective eye tracking cameras and illumination sources, and a gaze can be determined from tracking both eyes. In some examples, one eye (e.g., a dominant eye) is tracked by a respective eye tracking camera/illumination source(s).

(23) Device **100** optionally includes microphones(s) **113** or other audio sensors. Device **100** uses microphone(s) **113** to detect sound from the user and/or the real-world environment of the user. In some examples, microphone(s) **113** includes an array of microphones that optionally operate

together (e.g., to identify ambient noise or to locate the source of sound in space of the real-world environment).

(24) Device **100** optionally includes location sensor(s) **104** configured to detect a location of device **100** and/or of display generation component(s) **114**. For example, location sensor(s) **104** optionally includes a GPS receiver that receives data from one or more satellites and allows device **100** to determine the device's absolute position in the physical world.

(25) Device **100** optionally includes motion and/or orientation sensor(s) **110** configured to detect orientation and/or movement of device **100** and/or display generation component(s) **114**. For example, device **100** uses orientation sensor(s) **110** to track changes in the position and/or orientation of device **100** and/or display generation component(s) **114** (e.g., with respect to physical objects in the real-world environment). Orientation sensor(s) **110** optionally include one or more gyroscopes, one or more accelerometers, and/or one or more inertial measurement units (IMUs).

(26) It is understood that the architecture of FIG. **1A** is an example architecture, but that system/device **100** is not limited to the components and configuration of FIG. **1A**. For example, the device/system can include fewer, additional, or other components in the same or different configurations. In some examples, as illustrated in FIG. **1B**, system/device **150** can be divided between multiple devices. For example, a first device **160** optionally includes processor(s) **118A**, memory or memories **120A**, and communication circuitry **122A**, optionally communicating over communication bus(es) **108A**. A second device **170** (e.g., corresponding to device **100**) optionally includes various sensors (e.g., one or more hand tracking sensor(s) **102**, one or more location sensor(s) **104**, one or more image sensor(s) **106**, one or more touch-sensitive surface(s) **109**, one or more motion and/or orientation sensor(s) **110**, one or more eye tracking sensor(s) **112**, one or more microphone(s) **113** or other audio sensors, etc.), one or more display generation component(s) **114**, one or more speaker(s) **116**, one or more processor(s) **118B**, one or more memories **120B**, and/or communication circuitry **122B**. One or more communication buses **108B** are optionally used for communication between the above-mentioned components of device **170**. The details of the components for devices **160** and **170** are similar to the corresponding components discussed above with respect to device **100** and are not repeated here for brevity. First device **160** and second device **170** optionally communicate via a wired or wireless connection (e.g., via communication circuitry **122A-122B**) between the two devices.

(27) As described herein, in some examples, physical objects, even those without communication circuitry or electric circuitry, can be used to cause an electronic device to perform an action (e.g., control functionality of electronic device). For example, movement of a physical object or the results of movement of the physical object (or more generally a change in the physical environment device due to movement of one or more physical objects in the physical environment) can be indicative of a user input, which can be detected by sensors of an electronic device (e.g., image sensors, proximity sensors, etc.). In some examples, an electronic device performs a first action in accordance with the change in the physical environment due to movement of the one or more physical objects in the physical environment. In some examples, before the physical object can be used to cause an electronic device to perform an action, a configuration process (also referred to herein as an “enrollment process”) can be used to associate a physical object, one or more boundaries, and/or the associate action. Thus, the use of physical objects can be used to implement functionality for an electronic device, which may provide convenient or alternative ways of controlling a device using physical objects that are not otherwise communicatively coupled with the electronic device and/or without interactive directly with user interfaces displayed to the user of the electronic device.

(28) FIGS. **2A-2E** illustrate examples of an electronic device adjusting the volume of a television based on movement of one or more physical objects in accordance with some examples of the disclosure. FIG. **2A** illustrates an electronic device **201** that includes a display generation component (e.g., display generation component **114** in FIGS. **1A** and **1B**) and one or more image

sensors **214** (e.g., one or more sensors **102-112** described in FIGS. **1A** and **1B**). In some examples, the one or more image sensors **214** include one or more external sensors (e.g., sensors that face outwards from the user) to detect objects and movement of the user's hands in the physical environment **222** of the electronic device **101** and/or one or more internal sensors (e.g., sensors that face inwards towards the face of the user) to detect the attention (e.g., gaze) of the user. In some examples, the physical objects in the physical environment are presented by the electronic device **201** (e.g., displayed using display generation component **114**).

(29) In some examples, physical objects in the physical environment **222** of the electronic device **201** are presented by the electronic device **201** via a transparent or translucent display (e.g., the display of device **201** does not obscure the user's view of objects in the physical environment, thus allowing those objects to be visible). For example, as shown in FIG. **2A**, the electronic device **201** is presenting, via the transparent or translucent display generation component **114**, objects in the physical environment **222**, including a television **206** that is currently playing TV Show A at a first playback volume level **210**, a table **204**, and a physical object **202** (e.g., a pen, coffee mug, flashlight, comb, computer, phone, tablet or the like).

(30) In some examples, the electronic device **201** receives an input from a user corresponding to a request to control an electronic device (e.g., electronic device **201** or a second electronic device, such as television **206**) with a physical object in the physical environment **222** (as described in more detail below, in process **600**, and FIGS. **3A-3D**). The physical object that the user is requesting to use to control an electronic device optionally does not include electronic circuitry and/or communication circuitry with which to communicate with the electronic device **201** (or the second electronic device (e.g., television **206**)). In some examples, the input received by the electronic device **201** for controlling a respective electronic device with a physical object includes a predetermined gesture/movement input (as will be described in FIGS. **3A-3D**), voice input, and/or gaze input. For example, in FIG. **2A**, the electronic device **201** is receiving the voice input **224** stating "I want to control the volume of my TV with the object that I'm currently looking at," while the electronic device **201** is also detecting that the attention of the user is currently directed to Object A **202**. In some examples, the electronic device **201** detects that the attention of the user in FIG. **2A** is directed to Object A **202** in response to the electronic device **201** detecting, via the one or more image sensors **214**, that a gaze (e.g., represented by oval **208** with a plus sign) of the user is currently directed to Object A **202** (as illustrated in FIG. **2A**). Additionally or alternatively, the electronic device **201** optionally detects that the attention of the user was directed to Object A **202** in response to the electronic device **201** detecting, via the one or more image sensors **214** and/or an orientation sensor (e.g., orientation sensor **110**), that a head of the user is currently oriented towards Object A **202**. Additionally or alternatively, the electronic device **201** optionally receives a voice input stating "I want to control the volume of my TV with the Object A" such that Object A **202** can be identified by electronic device **201** without requiring the user to gaze at Object A **202**. It should be understood that while FIG. **2A** describes an example where the electronic device **201** is receiving input to control the television **206** (e.g., a second electronic device), the electronic device **201** can optionally receive input for controlling a system function of electronic device **201** with Object A **202**, such as controlling a brightness of the electronic device **201**, a playback position of a media item that is being played by electronic device **201**, etc. It should also be understood that the invention described herein is not limited to the example described in FIGS. **2A-2E**, but optionally applies to other devices/systems that are in communication with electronic device **201**, such as internet of things (IoT) devices/systems.

(31) In response to the electronic device **201** receiving the input in FIG. **2A** that included voice input **224** and gaze (e.g., represented by oval **208**), the electronic device **201** optionally initiates a process to control the volume of television **206** with Object A **202**, as illustrated in FIG. **2B**. In FIG. **2B**, the electronic device **201** is displaying a voice assistance user interface **216** (e.g., a system function of the electronic device **201** that enables hands-free operation of the electronic device **201**)

that includes an indication **212** of the voice input **224** provided in FIG. 2A and an indication **218** that indicates the next operation in configuring Object A **202** to control the volume of the television **206**. As shown, in some examples, the indication is a text based instruction prompting a user to provide/select the movement boundaries of Object A **202** for purposes of controlling the volume. It should be understood that while FIG. 2B illustrates the electronic device **201** displaying the voice assistance user interface **216** in response to the electronic device **201** receiving the input described in FIG. 2A, the electronic device **201** could also initiate the process to configure Object A **202** to control the volume of television **206** without displaying the voice assistance user interface **216** (e.g., communicate the remaining operations of the configuration process/instructions via a speaker of the electronic device **201** without displaying the voice assistance user interface **216**). Although a visual representation of the interaction with a voice assistance user interface is shown in FIG. 2B, it is understood that the interaction can use audio input only (e.g., using speaker and microphone), partially use audio input (optionally, with other input/output such as visual notifications, haptic feedback, etc.), and/or use not audio (e.g., using text driven or other user interface).

(32) In some examples, device **201** can initiate an enrollment process where the user can indicate the movement boundaries of Object A **202**. As shown in FIG. 2B, in some examples, configuring Object A **202** to control the volume of television **206** includes indicating the minimum and/or maximum movement boundaries of Object A **202** (optionally relative to another physical object in the physical environment **222** (e.g., table **204**), as will be described below). The minimum and maximum movement boundaries can represent end points of a slider-type control, where Object A **202** acts as the slider. In some examples, during and/or after successful enrollment, device **201** can provide a visual indicator (e.g., a virtual line between the minimum and maximum movement boundaries, a virtual indication of the maximum and minimum boundaries, a virtual representation of tick marks along the virtual line, and/or textual labels of “maximum” and “minimum” at maximum movement boundaries, etc.) to demonstrate the movement path of the slider-type control.

(33) In some examples, device **201** can prompt the user to select a minimum movement boundary and maximum movement boundary. For example, device **201** can display a first text prompt (and/or audio prompt) asking the user to move Object A **202** to a minimum movement boundary location. After completion, device **201** can display a second text prompt (and/or audio prompt) asking the user to move Object A **202** to a maximum movement boundary location.

(34) As will also be described in more detail below, after successfully configuring Object A **202** to control the volume of television **206** (e.g., after successful enrollment), the electronic device **201** optionally sets the volume of television **206** at 0% when the electronic device **201** is detecting that Object A **202** is located at the minimum movement boundary, and optionally sets the volume of television **206** at 100% when the electronic device **201** is detecting that Object A **202** is located at the maximum movement boundary. In some examples, the electronic device **201** detects gaze input from the user to indicate the minimum and maximum movement boundaries of Object A **202**. For example, in FIG. 2C, after the electronic device **201** displayed the indication **218** in FIG. 2B to indicate to the user that input indicating the minimum and maximum movement boundaries of Object A **202** is required, the electronic device **201** detected the user provided a first input that included the gaze represented by oval **208** directed to the front-left corner of table **204** to select the front-left corner of the table **204** as the minimum movement boundary of Object A **202** and a second input that included the gaze represented by oval **208** directed to the front-right corner of table **204** to select the front-right corner of the table **204** as the maximum movement boundary of Object A **202**.

(35) It should be understood that while the electronic device **201** detected gaze input from the user to select the minimum and maximum movement boundaries of Object A **202**, the electronic device **201** could have also additionally, or alternatively, detected other forms of input to indicate the minimum and maximum movement boundaries of Object A **202**, such as detecting, via the one or more image sensors **214**, that a hand of the user tapped on the front-left and front-right corners of

the table **204** to indicate the minimum and maximum movement boundaries of Object A **202**, respectively, or detecting that the user performed a predefined gesture (e.g., pinch or tap gesture that does not touch or contact the electronic device **201**) while the attention (e.g., gaze represented by oval **208**) of the user is directed to the front-left portion and front-right portion of the table **204** to indicate the minimum and maximum movement boundary of Object A **202**.

(36) In some examples, the electronic device **201** detects, via the one or more image sensors **214**, changes in the physical environment **222**. For example, in FIG. 2D, after receiving the one or more inputs selecting the minimum and maximum movement boundaries in FIG. 2C, the electronic device **201** is now detecting that the hand (e.g., represented by hexagon **226**) of the user has moved into the range of the one or more sensors **214** and is grabbing (e.g., holding) Object A **202** in the physical environment **222** (as compared to FIG. 2C where the hand (e.g., represented by hexagon **226**) was not in the range of the one or more image sensors **214** and was not grabbing Object A **202**). The electronic device **201** optionally detects that the hand (e.g., represented by hexagon **226**) of the user in FIG. 2D is grabbing Object A **202** as a result of (e.g., in response to) the one or more image sensors **214** capturing one or more images of a user (or part of a user, such the user's hand) while the user is interacting with the physical environment **222**. In FIG. 2E, while the hand (e.g., represented by hexagon **226**) of the user is continuing to grab/hold Object A **202**, the electronic device **201** is detecting that the hand (e.g., represented by hexagon **226**) of the user has moved Object A **202** from the location in the physical environment **222** illustrated in FIG. 2D (e.g., the front-middle portion of the table **204**) to the location in the physical environment **222** illustrated in FIG. 2E (e.g., slightly offset to the left of the front-right portion of the table **204**, which corresponds to the maximum movement boundary of Object A **202** (as described previously with respect to FIG. 2C)).

(37) In some examples, the volume level of the television **206** is (e.g., incrementally/gradually) adjusted as the location of Object A **202** relative to the selected minimum and maximum movement boundaries of Object A **202** changes. For example, as shown in FIG. 2E, the electronic device **201** has modified/updated the volume of television **206** from the volume level **210** (e.g., corresponding to a 50% volume level at the television **206**) illustrated in FIG. 2D to the volume level **220** illustrated in FIG. 2E (e.g., corresponding to a 95% volume level at the television **206**) in response to the electronic device **201** detecting movement of Object A **202** from a location in the physical environment **222** that is equidistance (e.g., a midpoint) between the minimum and maximum movement boundaries of Object A **202** as illustrated in FIG. 2D to a location in the physical environment **222** that is 5 units (e.g., inches, feet, yards, etc.) from the maximum movement boundary of Object A **202** (e.g., the front-right portion of the table **204**) and 95 units (e.g., inches, feet, yards, etc.) from the minimum movement boundary of Object A **202** (e.g., the front-left portion of the table **204**). As the electronic device **201** was detecting movement of the Object A **202** from the location in the physical environment **222** illustrated in FIG. 2D to the location in the physical environment **222** illustrated in FIG. 2E, the electronic device **201** optionally continuously updated the volume of the television **206** from the 50% volume level to the 95% volume level by 1%, 2%, 3%, 5%, or 10% (or any other suitable amount)—as opposed to only updating the volume of the television **206** after the electronic device **201** detects that Object A **202** is no longer moving in the physical environment **222**. While FIGS. 2D and 2E show the volume of the television **206** being adjusted in accordance with the horizontal movement of Object A **202**, it should be understood that the volume of television **206** could also be adjusted in accordance with vertical movement of Object A **202** in the physical environment **222** (e.g., if the minimum and maximum movement boundaries of Object A **202** are at different positions along a Y-axis (e.g., vertical location relative to the viewpoint of the user) vs. along an X-axis (e.g., horizontal location relative to the viewpoint of the user) as illustrated in FIGS. 2A-2E. Further, in some examples where the minimum and maximum movement boundaries of Object A **202** are at different positions along a Y-axis, the electronic device **201** optionally forgoes updating the volume of television **206** in

accordance with the movement of Object A **202** when Object A **202** is moved in an X and/or Z direction without the Y position of Object A **202** changing.

(38) After detecting the movement of Object A **202** to the location in the physical environment indicated in FIG. 2E, the electronic device **201** optionally updates/modifies the volume of the television **206** in response to detecting further movement of Object A **202** in the physical environment **222**. For example, after the electronic device **201** updated the volume of the television **206** to the volume level **220** (e.g., corresponding to a 95% volume level at the television **206**), the electronic device **201** optionally detects further movement of Object A **202** by the hand of the user. If the detected further movement of Object A **202** included movement of Object A **202** by 1, 2, 3, 4, or 5 units (e.g., inches, feet, yards) to the right of the physical location of Object A **202** illustrated in FIG. 2E, the electronic device **101** optionally increases the volume at the television **206** by 1%, 2%, 3%, 4%, or 5% to a 96%, 97%, 98%, 99%, or 100% volume level at the television **206**, respectively. Conversely, if the further movement of Object A **202** included movement of Object A **202** by 5, 10, 15, 20, or 25 units (e.g., inches, feet, yards) to the left of the physical location of Object A **202** illustrated in FIG. 2E, the electronic device **201** optionally decreases the volume at the television **206** by 5%, 10%, 15%, 20%, or 25% to a 90%, 80%, 75%, 70%, or 65% volume level at the television **206**, respectively.

(39) Although the example of FIGS. 2A-2E primarily describe a linear scale between the minimum and maximum movement boundaries and the corresponding volume adjustment, it is understood that in some examples, a non-linear correspondence between position and volume may be implemented. Additionally, although FIGS. 2A-2E primarily describe a slider-type functionality (e.g., volume adjustment, brightness adjustment, etc.) defined using maximum and minimum movement boundaries. As described herein, other types of functionality can be implemented (e.g., a knob using rotation of a mug, with the handle optionally representing the position of the knob, a toggle switch as described below with reference to FIGS. 3A-3D, etc.). Additionally, FIGS. 2A-2E primarily describe a configuration process initiated using audio and/or gaze inputs. As described herein, the configuration process can be initiated using other inputs.

(40) In some examples, the functionality can be a switch-type functionality (e.g., a toggle switch). In some examples, the electronic device detects movement of one or more physical objects to toggle on/off a system function at the electronic device (e.g., the device that is detecting the movement of the one or more physical objects) and/or toggle on/off a system function at a second electronic device (e.g., a device that is optionally not detecting the movement of the one or more physical objects), as will now be described with respect to FIGS. 3A-3D.

(41) FIG. 3A illustrates an electronic device **301** that includes a display generation component **114** and one or more image sensors **314**. The electronic device **301**, display generation component **114**, and the one or more image sensors **314** illustrated in FIG. 3A are optionally similar to or the same as the electronic device **201**, display generation component **114**, and the one or more image sensors **214** described and illustrated in FIGS. 2A-2E, respectively. As also shown in FIG. 3A, the electronic device **301** is presenting, via the transparent or translucent display generation component **114**, objects in the physical environment **322** of the electronic device **301**, including a television **306** that is currently powered off, a table **304**, and a physical object **302** (e.g., a pen, coffee mug, flashlight, comb, computer, phone, tablet, or the like).

(42) In some examples, the electronic device **301** initiates a process to control a system function of the electronic device **301** or another electronic device with a physical object in the physical environment **322** in response to audio and/or gaze input, as described with reference to FIGS. 2A-2E (e.g., initiating the configuration processes using gaze and/or audio inputs). In some examples, the electronic device **301** initiates a process to control a first system function of the electronic device **301** or a first system function of a second electronic device (e.g., television **306**) with a physical object in the physical environment **322** in response to the electronic device **301** detecting that the physical object moved in a pre-determined manner. For example, when the electronic

device **301** detects that a physical object has been moved in a left-to-right-to-left-to-right zigzag motion, the electronic device **301** optionally initiates a process to control the on/off state of television **306** with that physical object. Conversely, when the electronic device **301** detects that a physical object has been moved in a right-to-left-to-right-to-left zigzag motion the electronic device **301** optionally initiates a process to control the on/off state of a lighting system (e.g., a different function) in communication with the electronic device **301** (or optionally toggle on/off a 'Do Not Disturb' mode of the electronic device **301**) with that physical object. It should be understood that the above described motion and initiating a process to control an associated functionality are examples, and other functionalities can be controlled by different motions. For example, the electronic device **301** is optionally configured to detect a plurality of pre-determined motions, which optionally corresponds to requests to configure different system functions of the electronic device **301** or the second electronic device (e.g., a device/system in communication with the electronic device **301**). In some examples, a specific predetermined motion of any object can be detected to initiate a process to use that object for control and the associated functionality can be selected as part of the initiated process (e.g., using audio and/or gaze inputs to indicate the associated functionality) rather than being determined based one of a plurality of predetermined motions. In FIG. 3B, while the television **306** is currently powered off, the electronic device **301** detects that Object A **302** moved in a left-to-right-to-left-to-right zigzag motion, which in this example corresponds to the predetermined motion required for the electronic device **301** to initiate a process to control the on/off state of television **306** with Object A **302**. In response to the electronic device **301** detecting movement of Object A **302** in the left-to-right-to-left-to-right zigzag motion in the physical environment **322**, the electronic device **301** optionally initiates a process to configure to the on/off state of television **306** to be controlled with Object A **302**. In some examples, the process to configure the on/off state of television **306** with Object A **302** includes generating an audio output **308** that indicates to the user the next operation in the configuration process is to select a movement boundary for Object A **302**, as illustrated in FIG. 3B. The selected movement boundary is the location in the physical environment **322** that optionally causes the electronic device **301** to power on television **306** if the electronic device **301** detects movement of Object A **302** beyond the selected movement boundary and optionally causes the electronic device **301** to power off television **306** if the electronic device **301** does not detect movement of Object A **302** beyond the selected movement boundary (or remain powered off if television **306** is already powered off), as will be described in more detail below. It is understood that the audio output **308** can also be augmented or replaced by other types of information (e.g., haptic information, visual/textual notifications, etc.)

(43) In some examples, the electronic device **301** receives an input selecting the movement boundary in similar ways described previously in FIGS. 2A-2E. For example, in FIG. 3C, after the electronic device **301** generated the audio output **308** in FIG. 3B requiring the user to indicate the movement boundary of Object A **302**, the electronic device **301** detects an input that includes the gaze (e.g., represented by oval **310** with plus sign) of the user directed to the front-middle portion of the table **304** to select the front-middle portion of the table **304** as the movement boundary for Object A **302**. It should be understood that while the electronic device **301** detected gaze input from the user to select the movement boundary of Object A **301**, the electronic device **301** could have also additionally, or alternatively, detected other forms of input to select the movement boundary of Object A **302**, such as detecting, via the one or more image sensors **314**, that a hand of the user tapped on the front-middle portion of the table **304** to select the front-middle portion of the table **304** as the movement boundary for Object A **302**, or detecting that the user performed a predefined "air" gesture (e.g., pinch or tap gesture that does not touch or contact the electronic device **301**) while the attention (e.g., gaze represented by oval **310**) of the user is directed to the front-middle portion of the table **304** to select the front-middle portion of the table **304** as the movement boundary for Object A **302**.

(44) FIG. 3D illustrates a toggling of state (powering on television 306) using Object A 302 after the configuration process. In FIG. 3D, the electronic device 301 detects the hand (e.g., represented by hexagon 326) of the user has moved Object A 302 from the front-right portion of the table 304 to the front-left portion of the table 304, which is beyond the movement boundary selected in FIG. 3C (the front-middle portion of the table 304). In response to the electronic device 301 detecting that Object A 302 has moved beyond the movement boundary selected in FIG. 3C, the electronic device 301 transmits a signal to television 306 for turning on television 306, and in response to the television 306 receiving the transmitted signal from the electronic device 301, the television 306 is powered on (as illustrated in FIG. 3D). While, in FIG. 3D, the television 306 changed from being in a powered off state as illustrated in FIG. 3C to being in a powered on state as illustrated in FIG. 3D in response to the electronic device 301 detecting movement of Object A 302 beyond the movement boundary selected in FIG. 3C, it should be understood that if the electronic device 301 instead detected movement of Object A 302 that was not beyond the movement boundary selected in FIG. 3C, the television 306 would have optionally remained in the powered off state as illustrated in FIG. 3C (as opposed to changing to the powered on state). In some examples, the electronic device 301 detects further movement of Object A 302 after transmitting the signal to television 306 to power on television 306, and in response, the electronic device 301 modifies the on/off state of television 306 in analogous ways as previously described. In some examples, hysteresis can be applied to avoid toggling state when the object is places close to the movement boundary. In some examples, Object A 302 must move a threshold distance beyond the movement boundary in order to toggle the state.

(45) In some examples, the electronic device performs an action at the electronic device or at a second electronic device (e.g., a television, IoT system, or other system/device in communication with the electronic device) in response to detecting input commands written or drawn (e.g., a text-based and/or image-based input command), as will be described now with respect to FIGS. 4A and 4B.

(46) FIG. 4A illustrates an electronic device 401 that includes a display generation component 114 and one or more image sensors 414. The electronic device 401, display generation component 114, and the one or more image sensors 414 are optionally the same as or similar to the electronic device 201 and/or 301, display generation component 114, and/or the one or more image sensors 214 and/or 314 previously described in FIGS. 2A-3D. As shown in FIG. 4A, the physical environment 422 of the electronic device 401 includes an annotatable object 402 (e.g., a journal, piece of paper, notepad, or the like), a writing apparatus 404 (e.g., pen, pencil, marker, or any other type of object that is capable of annotating the annotatable object 402), and optionally a television 406 that is currently playing media content at a volume level 410. As described herein, in some examples, the writing apparatus can be used to physically ink the annotatable object (e.g., graphite of a pencil on paper, ink of a pen/marker on a notepad, or the like). In some examples, text-based or image-based input commands can enable the user to not only control an electronic device, but also to keep a physical “written record” of all the settings of user interface element (e.g., on the annotatable object) that can be retained and transported by the user for future reference or use.

(47) In FIG. 4A, the electronic device 401 has not yet detected/received a text-based or image-based input command because the writing apparatus 404 has not yet annotated the annotatable object 402 to include a text-based or image-based input command. In FIG. 4B, the writing apparatus 404 has annotated the annotatable object 402 to include a text-based or image-based input command corresponding to a request to adjust the volume level of television 406.

Specifically, the text-based or image-based input command includes a slider track (represented with a dashed line). A ‘-’ symbol and a ‘+’ symbol indicate minimum and maximum ends of the slider control (e.g., areas closer to the ‘-’ symbol corresponds to lower volume levels than areas closer to the ‘+’ symbol). The text-based or image-based input command further includes a slider bar represented by a ‘|’ symbol corresponds to the desired volume level of television 405 (e.g., a

representing a slider-type functionality), and its relative placement along the slider track can represent the volume level between the maximum and minimum ends. In some examples, the user can adjust the volume by erasing the ‘|’ symbol in a first location and redrawing the ‘|’ symbol in a second, different location along the slider track. The text-based or image-based input command also includes the characters/words “TV Volume” to indicate the text-based input command is associated with modifying the volume of television **406** (e.g., a device/system in communication with and visible to electronic device **401**). In some examples, before using the text-based or image-based input command to control device actions, the elements of the text-based or image-based input command (e.g., the recognition of a drawn slider, the maximum and minimum boundary locations, the corresponding functionality) can be confirmed as part of an enrollment process. In some examples, the user can be prompted with text and/or audio prompts to enter, clarify and/or confirm some or all of the information for enrollment prior to using the text-based or image-based input command for control. For example, a prompt can be issued for unentered aspects of the text-based or image-based command (e.g., instructing a user to add ‘+’ and ‘-’ symbols to indicate maximum and minimum points) or to clarify the semantic meaning of aspects of the text-based or image-based command (e.g., instructing the user to redraw the location of the ‘+’ symbol when the system cannot differentiate the user's drawings of the ‘+’ and ‘-’ symbols).

(48) After the writing apparatus **404** annotated the annotatable object **402** to include the text-based or image-based input command for controlling the volume of television **406** (e.g., in response to the annotation of the annotatable object), the electronic device **401** detects the text-based or image-based input command (e.g., via the one or more image sensors **414**), and transmits a signal to television **406** to control and/or modify the volume level of television **406** to correspond to the volume level indicated by the ‘|’ symbol in the text-based or image-based input command (as described previously). The television **406** receives the signal transmitted by the electronic device **401** and decreases the volume of television **406** from the volume level **420** illustrated in FIG. 4A to the volume level **432** illustrated in FIG. 4B (which corresponds to the volume level indicated by the ‘|’ symbol in the text-based or image-based input command). It should be understood that the above-described example is one possible example of a text-based or image-based input command that can be detected by electronic device **401**, but other text-based or image-based input commands may also be able to be detected by the electronic device **401** without departing from the scope of the disclosure. For example, the electronic device **401** is optionally configured to detect text-based or image-based input commands for modifying the lighting of a IoT-based lighting system that is in communication with the electronic device **401** or for modifying a function of the electronic device **401**, among other possibilities.

(49) Although FIGS. 4A-4B primarily describe a text-based or image-based input command having a slider-type functionality (e.g., volume adjustment) defined using maximum and minimum boundaries, as described herein, other types of functionality can be implemented (e.g., a knob using a change in the drawn position of the knob's pointer to indicate rotation, a toggle switch, a non-linear slider, etc.). Additionally, although FIGS. 4A-4B illustrate a slider-type functionality including a slider track and slider bar, that other user interface implementations of a slider control can be implemented. For example, the control can be a rectangle with minimum and maximum represented at opposite ends of the rectangle and shading within the rectangle relative to the minimum end of the rectangle can represent the volume level.

(50) Additionally, although FIGS. 4A-4B primarily describe a text-based or image-based input command in which the adjustment of the volume is achieved by the inked position of the ‘|’ symbol in the text-based or image-based input command, it is understood that in some examples, the adjustment of the volume can instead be achieved using a virtual slider control. For example, in response to detecting a slider control as part of a text-based or image-based input command (e.g., a slider track and slider bar annotated on the annotatable object), the system can cause a virtual slider control to be presented. In some examples, the virtual slider control can include a virtual slider

track and a virtual slider bar, which can occlude the inked slider control of the text-based or image-based input command. In some examples, while presenting the virtual slider control, the system can detect the use of writing apparatus **404** to manipulate the position of the virtual slider bar by touching the top of writing apparatus **404** to the virtual slider bar and dragging the virtual slider bar using the writing apparatus **404** (where the touching and movement are detected using the image sensors of device **401**, for example).

(51) In some examples, an electronic device detects one or more physical objects in the physical environment to construct a musical sequence (e.g., a sequence of musical notes), as will now be described with reference to FIGS. 5A-5C. In some examples, the physical objects can be used to implement a Musical Instrument Digital Interface (MIDI). In FIG. 5A, the electronic device **501** is detecting, via the one or more image sensors **515** (e.g., the same as or similar to the one or more image sensors **414** in FIGS. 4A and 4B), three physical objects in the physical environment **522** of the electronic device **501**: Object A **502**, Object B **504**, and Object C **506** (which are presented by the electronic device **501** via the transparent or translucent display generation component **114**). In some examples, the one or more physical objects in the physical environment **522** corresponds to one or more musical notes. Although not described in the context of FIGS. 5A-5C, the objects are optionally first configured to represent musical notes and the surface on which the objects are placed is optionally first configured to represent boundaries for the timing and frequency of a MIDI interface (e.g., assigning timing on a first axis (e.g., x-axis) and frequency on a second axis (e.g., y-axis)). For example, in FIG. 5A, in response to the electronic device **501** detecting Object A **502**, Object B **504**, and Object C **506**, the electronic device **501** constructs/generates a musical sequence **508**. As illustrated in FIG. 5A, the musical sequence **508** includes a first musical note **510** that corresponds to Object A **502**, a second musical note **512** that corresponds to Object B **504**, and a third musical note **514** that corresponds to Object C **506**.

(52) In some examples, the musical note that corresponds to a respective physical object in the physical environment **522** is based on one or more characteristics of that physical object. For example, the first musical note **510** is optionally different than the second musical note **512** and/or third musical note **514** because Object A **502**—the physical object corresponding to the first musical note **510** is different than the Object B **504** and/or Object C **506** (the physical objects corresponding to the second musical note **512** and third musical note **514**, respectively) (e.g., Object A **502** is a first type of physical object and Objects B **504** and/or C **506** are not of the first type).

(53) In some examples, the musical note that corresponds to a respective physical object in the physical environment **522** is based on the visual appearance of that respective physical object and/or the symbol included at the respective physical object (in addition to or as an alternative to using the x-y location to determine frequency and timing of each note). For example, Object A **502** optionally corresponds to the first musical note **510** because the electronic device **501** determined that a first symbol is located at Object A **502** (e.g., includes a drawing of a first musical instrument or musical note) and/or because the electronic device determined that Object A **502** is a first color (e.g., yellow, red, blue, etc.). Similarly, Objects B **504** and C **506** optionally corresponds to the second musical note **512** and third musical note **514**, respectively, for analogous reasons as described above. Thus, in some examples, the first musical note **510**, second musical note **512**, and third musical note **514** optionally correspond to different/distinct musical notes or the same musical note (e.g., depending on the position along the y-axis).

(54) In some examples, the timing of a musical note in the musical sequence **508** is based on the location of the corresponding physical object in the physical environment **522** of the electronic device **501**. For example, the musical note **510** optionally occurs before the musical note **512**, and the musical note **512** occurs before the musical note **514** in the musical sequence **508** because the electronic device **501** detected that Object A **502** is before Object B **504** and Object B **504** is before Object C **506** in a left to right manner. It should be understood that if the electronic device **501**

would have instead detected the physical objects in the physical environment in a right to left manner, the musical notes in the musical sequence **508** would have optionally been ordered with the third musical note **514** first, the second musical note **512** second, and the first musical note **510** third.

(55) In some examples, the distance in time between musical notes in the musical sequence **508** is based on (e.g., corresponds to) the distance between the corresponding physical objects in the physical environment **522**. For example, the musical note **512** optionally occurs 0.1, 0.5, 1, or 2 seconds after musical note **510** in the musical sequence **508** because the electronic device **501** has determined that Object B **504** is to the right of Object A **502** by 1, 2, 4, or 6 inches. Similarly, the time between musical note **512** and musical note **514** in the musical sequence **508** is optionally longer than the time between musical note **510** and **512** in the musical sequence **508** because the physical distance between Object A **502** and Object B **504** is less than the physical distance between Object B **504** and Object C **506** (as illustrated in FIG. 5A). In some examples, placing two (or more) objects at the same point along the time axis (e.g., the x-axis) can be used to implement a chord.

(56) In some examples, in response to the electronic device **501** constructing the musical sequence **508**, the electronic device **501** plays the musical sequence **508** or causes the musical sequence **508** to play at a second electronic device in communication with the electronic device **501** (e.g., a smart speaker, television, computer, or the like) plays the musical sequence **508**.

(57) In some examples, the electronic device **501** constructs a new musical sequence in response to detecting movement of physical objects in the physical environment **522** of the electronic device **501**. For example, in FIG. 5B, the electronic device is detecting that the hand (e.g., represented by hexagon **516**) of the user has grabbed/picked up Object B **504** in the physical environment **522**. After the electronic device detected that hand (e.g., represented by hexagon **516**) of the user grabbed/picked up Object B **504**, in FIG. 5C, the electronic device **501** detects movement of Object B **504** from the location in the physical environment **522** indicated in FIG. 5B to the location in the physical environment **522** indicated in FIG. 5C. In response to the electronic device **501** detecting movement of Object B **504** in the physical environment **522**, the electronic device **501** constructions a new musical sequence **518**, different from the musical sequence **508** illustrated in FIG. 5A in analogous ways as previously described.

(58) FIG. 6 illustrates an example process **600** for performing an action at a first electronic device or second electronic device in accordance with some examples of the disclosure. Process **600** is optionally performed at an electronic device such as device **100**, device **201**, **301**, **401**, and/or **501**. Some operations in process **600** are optionally combined and/or optionally omitted. The order of some operations in process **600** is optionally changed, in some examples.

(59) In some examples, process **600** is performed at a first electronic device in communication with a display and one or more input devices. In some examples, the first electronic device detects (**602**) a change in a physical environment of the first electronic device due to a movement of one or more physical objects in the physical environment indicative of a user input. In some examples, the first electronic device performs (**604**) a first action at the first electronic device or at a second electronic device in communication with the first electronic device in accordance with the change in the physical environment due to the movement of the one or more physical objects in the physical environment.

(60) In some examples, detecting the change in the physical environment of the first electronic device includes detecting movement of a first physical object of the one or more physical objects relative to a second physical object in the physical environment of the first electronic device, different from the one or more physical objects.

(61) In some examples, before the first electronic device detected the change in the physical environment, the first physical object was less than a threshold distance from the second physical object. In some examples, after detecting the change in the physical environment that includes

movement of the first object relative to the second object, in accordance with a determination that the first object is more than the threshold distance from the second object, the first electronic device performs the first action at the first electronic device or the second electronic device. In some examples, after detecting the change in the physical environment that includes movement of the first object relative to the second object, in accordance with a determination that the first object is not more than the threshold distance from the second object, the first electronic device forgoes performing the first action at the first electronic device or the second electronic device.

(62) In some examples, after performing the first action at the first or the second electronic device and while the first physical object is more than the threshold distance from the second physical object, the first electronic device detects movement of the first physical object relative to the second physical object. In some examples, in response to detecting movement of the first physical object relative to the second physical object, in accordance with a determination that the first physical object is less than a threshold distance from the second physical object, the first electronic device performs a second action at the first electronic device or the second electronic device, different from the first action. In some examples, in response to detecting movement of the first physical object relative to the second physical object, in accordance with a determination that the first physical object more than a threshold distance from the second physical object, the first electronic device forgoes performing the second action at the first electronic device or the second electronic device.

(63) In some examples, performing the first action includes toggling on a first function of the first or the second electronic device, and performing the second action includes toggling off the first function of the first or the second electronic device. In some examples, the one or more physical objects do not include electronic circuitry. In some examples, the change in the physical environment is captured via the one or more input devices of the first electronic device. In some examples, the one or more input devices include a camera that captures the movement of the one or more physical objects over a plurality of time periods.

(64) In some examples, performing the first action includes displaying a user interface object at the first electronic device. In some examples, in response to selecting the user interface object at the first electronic device, the first electronic device performs a second action, different from the first action, at the first or the second electronic device in accordance with the selection of the user interface object at the first electronic device.

(65) In some examples, before the first electronic device detected the change in the physical environment, the first physical object was a first distance from the second physical object. In some examples, after detecting the change in the physical environment that includes movement of the first object relative to the second object, in accordance with a determination that the first object is a second distance, different from the first distance, from the second physical object, the first electronic device performs the first action at the first or the second electronic device; and in accordance with a determination that the first object a third distance, different from the first distance, from the second physical object, the first electronic device performs a second action, different from the first action, at the first or the second electronic device.

(66) In some examples, after performing the first action at the first or the second electronic device and while the first physical object is the second distance from the second physical object, the first electronic device detects movement of the first physical object relative to the second physical object. In some examples, in response to detecting movement of the first physical object relative to the second physical object: in accordance with a determination that the first object is a fourth distance, different from the second distance, from the second physical object, the first electronic device performs a third action at the first or the second electronic device; and in accordance with a determination that the first object a fifth distance, different from the second distance, from the second physical object, the first electronic device performs a fourth action, different from the third action, at the first or the second electronic device.

(67) In some examples, performing the first action includes modifying a first function of the first or the second electronic device by a first amount, performing the second action includes modifying the first function of the first or the second electronic device by a second amount, different from the first amount, performing the third action includes modifying the first function of the first or the second electronic device by a third amount, different from the second amount, and performing the fourth action includes modifying the first function of the first or the second electronic device by a fourth amount, different from the third amount (e.g., adjusting volume or brightness level based on position of the first physical object acting as a slider).

(68) In some examples, before detecting movement of the first physical object relative to the second physical object (e.g., before performing the first action in accordance with the change in the physical environment due to the movement of the one or more physical objects in the physical environment), the first electronic device receives, via the one or more input devices, an input for configuring the first action to be performed based on the one or more physical objects. In some examples, in response to receiving the input, the first electronic device initiates a process to configure the first action to be performed based on movement of the one or more physical objects.

(69) In some examples, after detecting the change in the physical environment that includes movement of the one or more physical objects, in accordance with a determination that the first electronic device has not been configured to perform the first action responsive to movement of the one or more physical objects, the first electronic device forgoes performing the first action in response to detecting movement of the one or more physical objects.

(70) In some examples, the input for configuring the first action to be performed based on the one or more physical objects includes a gaze of the user of the first electronic device directed to the one or more physical objects for a threshold amount of time. In some examples, the input for configuring the first action to be performed based on the one or more physical objects includes a voice command (e.g., audio input) directed to the one or more physical objects. In some examples, the input for configuring the first action to be performed based on the first and the second physical object includes a pre-determined gesture directed to one of the one or more physical objects.

(71) In some examples, the one or more physical objects includes a plurality of physical objects and performing the first action includes constructing a sequence of musical notes in accordance a position of the plurality of physical objects, wherein a frequency of each of the musical notes is determined based on a corresponding position of one of the plurality of physical objects in the physical environment (e.g., in accordance with a determination that the first physical object is at a first position in the physical environment, constructing a first musical note; and in accordance with a determination that the first physical object is at a first position in the physical environment, constructing a second musical note, different from the first musical note).

(72) In some examples, after constructing the sequence of musical notes, the first electronic device detects movement of one or more of the plurality of physical objects. In some examples, in response to detecting movement of one or more of the plurality of physical objects, the first electronic device constructs a different sequence of musical notes (e.g., based on the updated position of the plurality of physical objects).

(73) In some examples, a timing of each of the musical notes is determined based on the corresponding position of one of the plurality of physical objects in the physical environment (e.g., based on the position of the plurality of objects along an axis representing time).

(74) In some examples, the one or more physical objects includes a writing apparatus and/or an annotatable object. In some examples, the first electronic device detects (602) a change in a physical environment of the first electronic device due to a movement of one or more physical objects in the physical environment indicative of a user input (e.g., detecting, in a physical environment, a user interface element inked on a physical surface with one or more physical objects and detecting, in the physical environment, a change in an appearance of the user interface element due to a movement of the one or more physical objects indicative of a user input). In some

examples, the first electronic device performs the first action at the first electronic device or at a second electronic device in communication with the first electronic device in accordance with the change in the physical environment due to the movement of the one or more physical objects in the physical environment (e.g., adjusting volume when the user draws a slider bar on the paper at a different location along the drawn slider user interface element).

(75) It should be understood that the particular order of the description of the operations in FIG. 6 is merely exemplary and is not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to reorder the operations described herein.

(76) The operations of process described above are, optionally, implemented by an electronic device comprising: one or more processors; memory; and one or more programs stored in the memory. The one or more programs stored in the memory and configured to be executed by the one or more processors, cause the processor to perform any of the above operations. The operations of process described above are, optionally, implemented by a storing one or more programs. The one or more programs stored in the non-transitory computer readable storage medium and configured to be executed by the one or more processors of an electronic device, cause the processor to perform any of the above operations.

(77) The operations of process described above are, optionally, implemented by running one or more functional modules in an information processing apparatus such as general-purpose processors (e.g., as described with respect to FIGS. 1A-1B) or application specific chips. Further, the operations described above with reference to FIG. 6 are, optionally, implemented by components depicted in FIGS. 1A-1B.

(78) The foregoing description, for purpose of explanation, has been described with reference to specific examples. However, the illustrative discussions above are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The examples were chosen and described in order to best explain the principles of the invention and its practical applications, to thereby enable others skilled in the art to best use the invention and various described examples with various modifications as are suited to the particular use contemplated.

Claims

1. A method comprising: at a first electronic device in communication with a display and one or more input devices: detecting a change in a physical environment of the first electronic device due to a movement of one or more physical objects, different from a hand of a user and different from a writing implement, in the physical environment indicative of a user input including detecting movement of a first physical object, of the one or more physical objects relative to a second physical object, from a first location in the physical environment of the first electronic device to a second location in the physical environment, wherein the first physical object is less than a threshold distance from the second physical object before detecting the change in the physical environment; after detecting the change in the physical environment, in accordance with a determination that the first physical object is more than the threshold distance from the second physical object, performing a first action at the first electronic device or at a second electronic device in communication with the first electronic device in accordance with the change in the physical environment due to the movement of the one or more physical objects in the physical environment; and in accordance with a determination that the first physical object is not more than the threshold distance from the second physical object, forgoing performing the first action at the first electronic device or the second electronic device.

2. The method of claim 1, further comprising: after performing the first action at the first electronic device or the second electronic device and while the first physical object is more than the threshold

distance from the second physical object, detecting movement of the first physical object relative to the second physical object; and in response to detecting movement of the first physical object relative to the second physical object: in accordance with a determination that the first physical object is less than the threshold distance from the second physical object, performing a second action at the first electronic device or the second electronic device, different from the first action; and in accordance with a determination that the first physical object more than the threshold distance from the second physical object, forgoing performing the second action at the first electronic device or the second electronic device.

3. The method of claim 2, wherein performing the first action includes toggling on a first function of the first electronic device or the second electronic device, and wherein performing the second action includes toggling off the first function of the first electronic device or the second electronic device.

4. A first electronic device, comprising: one or more input devices, including a first input device configured to detect a gaze of a user of the first electronic device; a display; and one or more processors configured to perform a method comprising: detecting a change in a physical environment of the first electronic device due to a movement of one or more physical objects, different from a hand of the user, in the physical environment indicative of a user input; performing a first action at the first electronic device or at a second electronic device in communication with the first electronic device in accordance with the change in the physical environment due to the movement of the one or more physical objects, in relation to a second physical object, different from the one or more physical objects, in the physical environment; and before performing the first action in accordance with the change in the physical environment due to the movement of the one or more physical objects in the physical environment, receiving, via the one or more input devices, an input for configuring the first action to be performed based on the one or more physical objects; and in response to receiving the input: initiating a process to configure the first action to be performed based on movement of the one or more physical objects, wherein the input for configuring the first action to be performed based on the one or more physical objects includes the gaze of a user of the first electronic device directed to the one or more physical objects for a threshold amount of time.

5. The first electronic device of claim 4, wherein the one or more physical objects do not include electronic circuitry.

6. The first electronic device of claim 4, wherein the change in the physical environment is captured via the one or more input devices of the first electronic device.

7. The first electronic device of claim 4, wherein the method comprises: after detecting the change in the physical environment that includes movement of the one or more physical objects: in accordance with a determination that the first electronic device has not been configured to perform the first action responsive to movement of the one or more physical objects, forgoing performing the first action in response to detecting movement of the one or more physical objects.

8. The first electronic device of claim 4, wherein the one or more physical objects includes a plurality of physical objects, and wherein performing the first action includes: constructing a sequence of musical notes in accordance a position of the plurality of physical objects, wherein a frequency of each of the musical notes is determined based on a corresponding position of one of the plurality of physical objects in the physical environment.

9. The first electronic device of claim 8, wherein the method comprises: after constructing the sequence of musical notes, detecting movement of one or more of the plurality of physical objects; and in response to detecting movement of the one or more of the plurality of physical objects, constructing a different sequence of musical notes.

10. The first electronic device of claim 8, wherein a timing of each of the musical notes is determined based on the corresponding position of one of the plurality of physical objects in the physical environment.

