

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406247
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Ben-Avi; David et al.

System, device and method for digital payment

Abstract

A system, apparatus, and method for performing payments using a web browser. The payment is made by activating a uniform resource locator (URL), which is linked to a website at a server, wherein the website comprises an embedded payment program that is loaded with a predetermined amount of payment and installs the embedded payment program in the mobile device. The payment program is configured to transfer the payment data through a near-field communication (NFC) radio to a payment terminal. The payment program is deleted after performing the payment.

Inventors:	Ben-Avi; David (Herzliya, IL), Rosenhoiz; Guy (Herzliya, IL)
Applicant:	NAYAX LTD. (Herzliya, IL)
Family ID:	87202469
Assignee:	NAYAX LTD. (Herzliya, IL)
Appl. No.:	18/719659
Filed (or PCT Filed):	January 25, 2023
PCT No.:	PCT/IL2023/050085
PCT Pub. No.:	WO2023/161919
PCT Pub. Date:	August 31, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240428224 A1	Dec. 26, 2024

Foreign Application Priority Data

IL	290829	Feb. 23, 2022
----	--------	---------------

Publication Classification

Int. Cl.: G06Q20/32 (20120101); G06Q20/36 (20120101)

U.S. Cl.:

CPC G06Q20/3278 (20130101); G06Q20/36 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2012/0330764	12/2011	Nahidipour	N/A	N/A
2016/0162882	12/2015	McClung, III	705/41	G06Q 20/352

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2019215687	12/2018	JP	N/A
20120128941	12/2011	KR	N/A
101836191	12/2017	KR	N/A

OTHER PUBLICATIONS

PCT International Search Report for International Application No. PCT/IL2023/050085, mailed Apr. 30, 2023, 3pp. cited by applicant
PCT Written Opinion for International Application No. PCT/IL2023/050085, mailed Apr. 30, 2023, 3pp. cited by applicant
Israel Patent Office, Search Report—ILPO for Israeli Patent Application No. 290829, dated May 23, 2022, 2pp. cited by applicant

Primary Examiner: Gart; Matthew S

Assistant Examiner: Nguyen; Liz P

Attorney, Agent or Firm: The Roy Gross Law Firm, LLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is a National Phase of PCT Patent Application No. PCT/IL2023/050085 having International filing date of Jan. 25, 2023, which claims the benefit of priority of Israeli Patent Application No. 290829, filed Feb. 23, 2022, the contents of which are all incorporated herein by reference in their entirety.

TECHNICAL FIELD

(2) Some embodiments described herein are generally relayed to a digital payment method and

system, specifically for transacting currency over a digital network.

BACKGROUND

(3) A digital payment system may use a digital wallet to perform payments over the Internet and/or metered networks and/or stores. The digital wallet may have and/or include credit card information and/or the bank account information and/or any other payment method and/or balance of a buyer. The digital wallet has access to such buyers' payments accounts and/or accounts to purchase merchandise on the Internet or physical stores. Thus, storing the credit card information in the digital wallet may be open to a range of security issues.

(4) There is a need to provide a solution to purchase goods and services using a computing device without using a permanent digital wallet application.

SUMMARY

(5) Embodiments of this disclosure may be related to a system, a method, and a server for managing payments configured to use a web browser to pay for goods and services are described hereinbelow by the ways of example only.

(6) One embodiment may include a system for performing payments by using a web browser for paying for goods and services, comprising a mobile device, wherein the mobile device is configured to: receive from a server a text message comprising a uniform resource locator (URL), which is linked to a website at the server; activate the URL, wherein the activation of the URL opens a web page comprising an embedded payment program which is loaded with a predetermined amount of payment and installs the embedded payment program in the mobile device, transfer the payment card data and the predetermined amount of payment through a near field communication (NFC) radio of the mobile device to a payment terminal by the embedded payment program, and delete the embedded payment program and the payment card data after performing the payment by closing the web page at the end of the transaction.

(7) For example, the payment terminal may include EuroPay, MasterCard, Visa (EMV) terminal.

(8) For example, the payment card data may comply with the EMV standard.

(9) For example, the embedded payment program may include a digital wallet program.

(10) For example, the web page may include a graphical representation of the embedded payment program and one or more information elements.

(11) For example, the embedded payment program is configured to control the NFC radio.

(12) For example, the payment card data comprises at least one of a bank account details, an account holder date of expiration of the payment card data, an available sum of money for payment.

(13) For example, the system may comprises a server for managing payments, wherein the server is configured to: generate the URL, which is linked to the website at the server, wherein the website comprises an embedded payment program that is configured to perform payment based on payment card data; and send the URL to the mobile device in a text message.

(14) For example, the payment terminal is configured to send a purchase status information to the server.

(15) For example, the predetermined amount of payment is selected from a national currency, a cryptographic currency, loyalty club points and a money-worth coupon.

(16) Another embodiment may include a method for performing payments by using a web browser for paying for goods and services operating in a mobile device, comprising: receiving from a server a text message comprising a uniform resource locator (URL), which is linked to a website at the server; activating the URL, wherein the activation of the URL may open a web page that may include an embedded payment program which is loaded with a predetermined amount of payment and installs the embedded payment program in the mobile device; performing a payment by the embedded payment program, which is configured to transfer the payment card data through a near field communication (NFC) radio of the mobile device to a payment terminal, and after performing the payment, delete the embedded payment program by closing the web page at the end of the

transaction.

(17) Another other embodiment may include a server for performing payments, wherein the server is configured to: generate a text message comprising a uniform resource locator (URL), which is linked to a website at the server, wherein the website comprises an embedded payment program loaded with a predetermined amount of payment and payment card data; send the URL to a mobile device to be activated; and perform payment by the embedded payment program, which is configured to transfer payment card data through a near field communication (NFC) radio to a payment terminal.

(18) For example, the embedded program and the payment card data are deleted after performing the payment by closing the web page at the end of the transaction.

(19) For example, the embedded payment program comprises a digital wallet program loaded with the predetermined amount of payment.

Description

BRIEF DESCRIPTION OF THE DRAWING

(1) FIG. 1 illustrates a block diagram of a system for purchasing goods and services using a web browser, according to some demonstrative embodiments.

(2) FIG. 2 illustrates a flow chart of a method for purchasing goods and services with a one-time use digital wallet application uploaded by a web page, according to some demonstrative embodiments.

(3) FIG. 3 illustrates a block diagram of a web page, according to some demonstrative embodiments.

(4) FIG. 4 illustrates a frame of paying card data, according to some demonstrative embodiments.

(5) FIG. 5 illustrates a product of manufacture, according to some demonstrative embodiments.

(6) FIG. 6 illustrates a block diagram of a system for purchasing goods and services using a web browser and a flow of a method for purchasing goods and services according to some demonstrative embodiments.

DETAILED DESCRIPTION

(7) In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of some embodiments. However, it will be understood by persons of ordinary skill in the art that some embodiments may be practiced without these specific details. In other instances, well-known methods, procedures, components, units, and/or circuits have not been described in detail so as not to obscure the discussion.

(8) Discussions made herein utilizing terms such as, for example, “processing,” “computing,” “calculating,” “determining,” “establishing,” “analyzing,” “checking,” or the like, may refer to operation(s) and/or process(es) of a computer, a computing platform, a computing system, or other electronic computing devices, that manipulate and/or transform data represented as physical (e.g., electronic) quantities within the computer's registers and/or memories into other data similarly represented as physical quantities within the computer's registers and/or memories or other information storage medium that may store instructions to perform operations and/or processes.

(9) The terms “plurality” and “a plurality,” as used herein, include, for example, “multiple” or “two or more.” For example, “a plurality of items” includes two or more items.

(10) References to “one embodiment,” “an embodiment,” “demonstrative embodiment,” “various embodiments,” etc., indicate that the embodiment(s) so described may include a particular feature, structure, or characteristic, but not every embodiment necessarily includes the particular feature, structure, or characteristic. Further, repeated use of the phrase “in one embodiment” does not necessarily refer to the same embodiment, although it may.

(11) As used herein, unless otherwise specified, the use of the ordinal adjectives “first,” “second,”

“third,” etc., to describe a common object merely indicate that different instances of like objects are being referred to and are not intended to imply that the objects so described must be in a given sequence, either temporally, spatially, in ranking, or any other manner.

(12) As used herein, the term “circuitry” may refer to, be part of, or include, an Application Specific Integrated Circuit (ASIC), an integrated circuit, an electronic circuit, a processor (shared, dedicated, or group), and/or memory (shared, dedicated, or group), that execute one or more software or firmware programs, a combinational logic circuit, and/or other suitable hardware components that provide the described functionality. In some demonstrative embodiments, the circuitry may be implemented in, or functions associated with the circuitry may be implemented by one or more software or firmware modules. In some demonstrative embodiments, the circuitry may include logic, at least partially operable in hardware.

(13) The term “logic” may refer, for example, to computing logic embedded in the circuitry of a computing apparatus and/or computing logic stored in a memory of a computing apparatus. For example, the logic may be accessible by a processor of the computing apparatus to execute the computing logic to perform computing functions and/or operations. In one example, logic may be embedded in various types of memory and/or firmware, e.g., silicon blocks of various chips and/or processors. Logic may be included in and/or implemented as part of various circuitry, e.g., radio circuitry, receiver circuitry, control circuitry, transmitter circuitry, transceiver circuitry, processor circuitry, and/or the like. In one example, logic may be embedded in volatile memory and/or non-volatile memory, including random access memory, read-only memory, programmable memory, magnetic memory, flash memory, persistent memory, and the like. Logic may be executed by one or more processors using memory, e.g., registers, stacks, buffers, and/or the like, coupled to one or more processors, e.g., as necessary to execute the logic.

(14) The term “module,” as used hereinbelow, is an object file that contains code to extend the running kernel environment.

(15) As used herein, the term “software engine” as used hereinbelow is an object file that contains code to extend the running kernel environment.

(16) The term “digital wallet,” as used hereinbelow, is both a software and information component. Digital wallets may be stored on a client-side. The digital wallets may use a Near Field Communication (NFC), e.g., of smartphones, to transfer payments by touching the smartphone to a payment terminal at a store.

(17) The term “EMV,” as used hereinbelow, is a payment method based upon a technical standard for smart payment cards and for payment terminals and automated teller machines. EMV originally stood for “EuroPay, Mastercard, and Visa,” the three companies which created the global payment standard.

(18) The term “EMV terminal,” as used hereinbelow, is a payment terminal also known as a Point of Sale (POS) terminal, credit card terminal, etc. The EMV terminal is a device that interfaces with payment cards, e.g., EuroPay, MasterCard, and Visa, to make electronic funds transfers. The terminal typically consists of a secure keypad for entering a PIN, a screen, a means of capturing information from payments cards, and a network connection to access the payment network for authorization.

(19) In some demonstrative embodiments, the payment terminal may allow a merchant to capture required credit and/or debit card information and transmit this data to the merchant services provider and/or bank for authorization and transfer funds to the merchant. The terminal may allow the merchant and/or their client to swipe, insert and/or hold a card near the device to capture the information.

(20) The term “Card(s),” as used hereinbelow, may include, for example, the prepaid card created and issued by an issuer, credit cards, debit cards, or the like.

(21) The term “Customer Credit Card Terminal,” as used hereinbelow, may include a transaction terminal, EMV, and/or non-EMV, which may be used by the Customer platform to generate

payment card data for each End-User credit card associated with the customer mobile application. For example, such terminals may reside with a payments gateway company or processor company (22) The term “customer mobile application,” as used hereinbelow, may include at least one application which is installed on the customer's computing device, for example, the loyalty club application, e-Wallet application, or the like. The customer mobile application may include the digital wallet SDK and may interact with the digital wallet platform and the customer platform. The customer mobile application may be configured to run on a computing device operating system, such as, for example, iOS and Android or React.

(23) The term “Payment Card Data,” as used hereinbelow, may include a unique placeholder called a payment card data and/or payment data and/or payment element, which is configured to include encrypted information of a payment ability of the user, for example, a credit card, a debit card, bank money transfer information, or the like. For example, the payment card data may be embedded into a payment card token. The payment card data may include the payment card number. For example, if the payment card number is 1234 5678 8765 4321, the payment card data identification may be, for example, E67TL8GC27X. In some demonstrative embodiment, the payment card data may be configured to access, retrieve, and maintain, for example, a customer's credit card information to ensure a higher level of security for both the customer and the business. The payment card data may be saved on the customer platform and/or on the customer's single-use mobile application. In some demonstrative embodiments, the payment card data may include a single-use payment card data.

(24) The term a Uniform Resource Locator (URL), as used hereinbelow, may be colloquially termed a web address, is a reference to a web resource that specifies its location on a computer network and a mechanism for retrieving it. A URL is a specific type of Uniform Resource Identifier (URI), although many people use the two terms interchangeably. URLs occur most commonly to reference web pages (HTTP) but are also used for file transfer (FTP), email (mailto), database access (JDBC), and many other applications. For example, web browsers may display the URL of a web page above the page in an address bar. A URL may have the form <http://www.example.com/index.html>, which indicates a protocol (HTTP), a hostname (www.example.com), and a file name ([index.html](http://www.example.com/index.html)).

(25) The term “Payment Card Data Service Provider (PCDSP),” as used hereinbelow, is an entity certified by, for example, MasterCard, Visa, or any other issuers, which are allowed to generate EMV data. The PCDSP may include an entity within the payments ecosystem that is configured to provide registered payment card data requestors. For example, the merchants holding the card credentials—with ‘surrogate’ Primary Account Number (PAN) values, otherwise known as payment card data. For example, the service may be provided by gateway services if desired.

(26) Reference is made first to FIG. 1, which is an illustration of a block diagram of a system **100** for purchasing goods and services using a web browser **130**, according to some demonstrative embodiments.

(27) In some demonstrative embodiments, system **100** may include a computing device **110**. For example, computing device **110** may include a smartphone, a tablet, a mobile computer, an electronic wallet, a dongle, a desktop computer, a computing device, or the like.

(28) In some demonstrative embodiments, computing device **110** may include processing circuitry **120**. For example, processing circuitry **120** may include one or more processors having one or more cores, a digital signal processor, a graphic processor, a communication processor, one or more memories, and the like.

(29) In some demonstrative embodiments, computing device **110** may include a near field communication (NFC) radio **125**. For example, NFC radio **125** may be configured to transfer payment card data by a payment program **134** to a payment terminal **140**. For example, the transfer of the payment card data may be done by attaching the computing device **110** to the payment terminal **140** at a point of sale (POS) (not shown), e.g., a store, a restaurant, a service provider, an

office, etc.

(30) In some demonstrative embodiments, the payment program **134** may be embedded in the web page **130** and include a temporary digital wallet software. For example, the temporary digital wallet software may load with the payment card data and may use the processing circuitry **120** to control the NFC radio **125**. The processing circuitry may operate the NFC radio **125** to transfer the payment card data and payment to the payment terminal **140**.

(31) In some demonstrative embodiments, system **100** may include a payment server **160**. The payment server **160** may include a downloadable payment program **162**, a URL generator **164**, and a payment card data generator module **166**.

(32) In some demonstrative embodiments, the payment card data generator **166** may be operably connected to a payment cards issuer server **170**. The payment cards issuer server **170** may issue one or more payment cards **172**, e.g., credit cards, debit cards, loadable cards, loyalty club cards, gift cards, and the like.

(33) The payment cards issuer server **170** may receive the payment card data from the payment terminal **140** and may transfer the payment to a merchant and/or service provider and/or the like.

(34) In some demonstrative embodiments, the payment card data generator module **166** may generate payment card data **134** based on the payment card, e.g., credit card **172**, at the issuer server **170**. For example, the payment card data may include a predetermined amount of payment to be used by the user and/or credit.

(35) For example, the predetermined amount of payment may be selected from a national currency, a cryptographic currency, loyalty club points and a money-worth coupon.

(36) In some demonstrative embodiments, the URL generator module **164** may be configured to generate a URL **150**. The URL **150** may include a link to a website that embeds the payment program **162** and/or payment card data, e.g., payment card data **134**.

(37) In some demonstrative embodiments, computing device **110** may receive the URL **150** as a text message, e.g., Short Message Service (SMS), and/or any other format used by one or more texting applications. For example, by clicking on the URL, the web browser **132** may download a web page that enables activation of the payment program **134** and the payment data **134** at the mobile device **110**.

(38) Advantageously, using a temporary digital wallet, including temporary payment card data, may increase the security of the user from being hacked and/or from stealing his payment card data. Furthermore, this is a new, easy and secure way to transfer money to the user. The user may use the payment card data on any device by clicking on the URL provided in a text message.

(39) In some demonstrative embodiments, the payment program may stay installed until the payment session is in progress and may be deleted with the payment card data when the payment session ends. Advantageously, this way of operation may apply the highest security level to the user from being hacked, and the payment card data does not remain stored at the computing device.

(40) In some demonstrative embodiments, system **100** for managing payments may be configured to use the web browser **130** to pay for goods and services. System **100** may include the computing device **110**, e.g., a mobile device. The computing device **110** may be configured to activate an URL **150**. The URL **150** may be linked to a website at a server the website may include a payment program **162** and/or payment card data **134**. The payment program **162** may be configured to perform payment based on payment card data **134**. For example, payment data **134** may be loaded into payment card data **168**. Computing device **110** may perform the payment by the payment program **132**.

(41) For example, the payment card data may include at least one of the bank account details, account holder details, an available amount of money, and/or any other data.

(42) In some demonstrative embodiments, the payment program **132** may be configured to transfer the payment data **134** through NFC radio **125** to the payment terminal **140**. The payment program **132** may be deleted after performing the payment. For example, deletion of the payment program

132 may be done by closing the web page and/or by closing the program and/or by closing the web browser **130**.

(43) In some demonstrative embodiments, payment terminal **140** may include EuroPay, MasterCard, Visa (EMV) terminal, and/or any other terminal.

(44) In some demonstrative embodiments, the activation of the URL **150** may cause the web browser **130** to open a web page and activate the payment program **132**, as well. For example, activation of the URL **150** may trigger the web browser **130** to download and install the payment program **132**. In some other demonstrative embodiments, the payment program **132** may be embedded on the web page, for example, as an instance. The web page may be programmed with ActiveX and/or JavaScript and/or HTML language and/or by any other programming language.

(45) In some demonstrative embodiments, the payment program **132** may be configured to enable the NFC radio **125** to transfer the payment card data **134** to the EMV terminal **140** and/or to any other terminal. For example, payment program **132** may include a digital wallet program and/or any other type of payment program. It should be understood that the digital wallet program may be a temporary digital wallet program that may be deleted when closing the web page and/or the web browser **130**.

(46) In some demonstrative embodiments, the web page may include a graphical representation of the URL **150** and one or more instructions on how to activate the URL and/or how to perform purchases using the payment program **132**.

(47) In some demonstrative embodiments, server **160** may include a server for managing payments, e.g., a payment server. Server **160** may be configured to generate the URL **150**, which may be linked to the resource, e.g., a website, at server **160**. For example, the website may include an embedded payment program **162** that may be configured to perform payment based on the payment card data **168**. The payment program **162** may be configured to perform payment based on the payment data uploaded to the payment card data **168**. For example, server **160** may send the URL **150** to the computing device **110**.

(48) In some demonstrative embodiments, the payment data may include a predetermined amount of payment. For example, the predetermined amount of payment may be selected from a national currency, a cryptographic currency, loyalty club points and money worth coupon or the like.

(49) In some demonstrative embodiments, server **160** may be configured to send the URL to the mobile device **110** in a text message **150**.

(50) Reference is now made to FIG. 2, which is a schematic illustration of a flow chart of a method **200** for purchasing goods and services with a one-time use digital wallet application uploaded by a web page, according to some demonstrative embodiments.

(51) In some demonstrative embodiments, method **200** may be configured to perform payments by using a web browser for paying for goods and services. Method **200** may be operated by a payment program, e.g., a digital wallet, installed on a mobile device, e.g., computing device **110** (FIG. 1).

(52) In some demonstrative embodiments, method **200** is configured to receive a URL, e.g., URL **150** (FIG. 1), from a server, e.g., payment server **160** (FIG. 1), at the computing device **110** (text box **210**). A user may activate the URL **150**, which may be linked to a resource at server **160**. For example, the resource may include the payment card data and the payment program. For example, the payment program, e.g., a digital wallet, may be configured to perform payment based on payment data uploaded to the payment card data.

(53) In some demonstrative embodiments, activating the URL may cause the opening of a web page at the web browser. The web page may include the payment program, e.g., payment program **162** (FIG. 1), and the payment card data, e.g., payment card data **134** (text box **220**).

(54) In some demonstrative embodiments, the payment program may perform payment by transferring the payment card data through an NFC radio, e.g., NFC radio **125** (FIG. 1), to a payment terminal, e.g., payment terminal **140** (FIG. 1) (text box **230**).

(55) In other demonstrative embodiments, the transfer of the payment data to the payment terminal

and/or directly to the merchant/seller account may be done with any type of data transfer technology.

(56) In some demonstrative embodiments, after transferring the payment to the merchant/seller account and/or completing the purchasing session, the payment program may be deleted from the computing device when closing the web page and/or the web browser (text box **240**).

(57) Reference is now made to FIG. **3**, which illustrates a block diagram of a web page **300**, according to some demonstrative embodiments. For example, web page **300** may include one or more visual and/or interacting and/or information elements **310**, such as for example, images, video, text, forms, a chat application, and any other information elements.

(58) In some demonstrative embodiments, web page **300** may include a payment program **320**. For example, the payment program **320** may include a digital wallet application with payment card data. For example, the payment card data may be loaded with a predetermined amount of payment and/or credit. The payment card data may be stored in the digital wallet program and/or application.

(59) In other demonstrative embodiments, the payment card data may be linked to the digital wallet program and/or application.

(60) Reference is now made to FIG. **4**, which illustrates a frame of a paying card data **400**, according to some demonstrative embodiments.

(61) In some demonstrative embodiments, payment card data **400** may include a header field **410**, a payment card data field **420**, a user data field **430**, a date of expiration field **440**, a sum of money field **450**, a credit field **460**, and a footer field.

(62) For example, the payment card data field **420** may include data of a user's credit card, for example, credit card number, expiration date, a bank account number of a user, and a CCV number. The user data field **430** may include, for example, a user first name, a user family name, a user identification number (ID), and the like. The date field **440** may include, for example, a date and/or an hour of expiration of the payment card data **400**. The sum field **450** may include, for example, the amount of money that the user can spend. The credit field **460** may include, for example, the credit limit of the payment card of the user, and the footer field **470** may include, for example, an authentication code of payment card data **400**. It should be understood that in other embodiments, the payment card data may include different fields.

(63) In some demonstrative embodiments, the payment card data **400** may be encrypted when it's stored at the payment program **132** (FIG. **1**) and may be decrypted when it's transferred to the payment terminal **140** (FIG. **1**.)

(64) Reference is now made to FIG. **5**, which is a schematic illustration of a product of manufacture **500**, according to some demonstrative embodiments. Product **500** may include one or more tangible computer-readable non-transitory storage media **510**, which may include computer-executable instructions **530**, implemented by processing device **520**, operable to, when executed by at least one computer processor, enable at least one processing circuitry **120** (FIG. **1**) to implement one or more program instructions for purchasing goods and services with a payment program that is downloaded and installed by clicking on a link of a web page. At least one processing circuitry **120** (FIG. **1**) may be configured to implement one or more program instructions and/or to perform, trigger and/or implement one or more operations, communications and/or functionalities as described above with reference to FIGS. **1**, **2**, **3**, **4** and **6**. The phrase “non-transitory machine-readable medium” is directed to include all computer-readable media, with the sole exception being a transitory propagating signal.

(65) In some demonstrative embodiments, product **500** and/or machine-readable storage medium **510** may include one or more types of computer-readable storage media capable of storing data, including volatile memory, non-volatile memory, removable or non-removable memory, erasable or non-erasable memory, writeable or re-writeable memory, and the like. For example, machine-readable storage medium **310** may include any type of memory, such as, for example, RAM,

DRAM, ROM, programmable ROM (PROM), erasable programmable ROM (EPROM), electrically erasable programmable ROM (EEPROM), Flash memory, a hard disk drive (HDD), a solid-state disk drive (SSD), fusion drive, and the like. The computer-readable storage media may include any suitable media involved with downloading or transferring a computer program from a remote computer to a requesting computer carried by data signals embodied in a carrier wave or other propagation medium through a communication link, e.g., a modem, radio, or network connection.

(66) In some demonstrative embodiments, processing device **520** may include logic. The logic may include instructions, data, and/or code, which, if executed by a machine, may cause the machine to perform a method, process and/or operations as described herein. The machine may include, for example, any suitable processing platform, computing platform, computing device, processing device, computing system, processing system, computer, processor, or the like, and may be implemented using any suitable combination of hardware, software, firmware, and the like.

(67) In some demonstrative embodiments, processing device **520** may include or may be implemented as software, firmware, a software module, an application, a program, a subroutine, instructions, an instruction set, computing code, words, values, symbols, and the like. Instructions **540** may include any suitable types of code, such as source code, compiled code, interpreted code, executable code, static code, dynamic code, and the like. Instructions may be implemented according to a predefined computer language, manner, or syntax for instructing a processor to perform a specific function. The instructions may be implemented using any suitable high-level, low-level, object-oriented, visual, compiled and/or interpreted programming languages, such as C, C++, C#, Java, Python, BASIC, Mat lab, assembly language, machine code, and the like.

(68) Turning to FIG. **6**, which illustrates a block diagram of a system **600** for purchasing goods and services using a web browser **690** and a flow of a method for purchasing goods and services according to some demonstrative embodiments.

(69) In some demonstrative embodiments, system **600** may include a server **675**, a mobile device **680**, and a payment terminal **685**.

(70) For example, the mobile device **680** may include the computing device **110** (FIG. **1**), a cellphone, a tablet, a laptop computer, and the like.

(71) In some demonstrative embodiments, server **675** may generate a payment URL (line **610**). Mobile device **680** may receive from server **675** a text message (not shown) (line **615**), with the URL **150** (FIG. **1**), which may be linked to a website at server **675**. Mobile device **680** may activate the URL **150** (FIG. **1**) (line **625**), wherein the activation of the URL **150** may open web page **690** (line **640**).

(72) For example, web page **690** may include an embedded payment program **132** (FIG. **1**), which may be loaded with a predetermined amount of payment and may install the embedded payment program in the mobile device (line **640**). Mobile device **680** may be configured to transfer the payment card data **168** (FIG. **1**) and the predetermined amount of payment through NFC radio **125** (FIG. **1**) of the mobile device **680** to payment terminal **685** by the embedded payment program (line **650**), and delete the embedded payment program and the payment card data after performing the payment by closing the web page at the end of the transaction (line **670**).

(73) For example, the predetermined amount of payment is selected from a national currency, a cryptographic currency, loyalty club points and a money-worth coupon and the like.

(74) In some demonstrative embodiments, the mobile device **680** may be configured to send purchase status information to server **675** (dotted line **660**).

(75) It is to be understood that the system and/or the method for performing payments by using a web browser for paying for goods and services is described hereinabove by way of example only. Other embodiments may be implemented based on the detailed description and the claims that followed.

(76) It is to be understood that like numerals in the drawings represent like elements through the

several figures and that not all components and/or steps described and illustrated with reference to the figures are required for all embodiments or arrangements.

(77) It should also be understood that the embodiments, implementations, and/or arrangements of the systems and methods disclosed herein can be incorporated as a software algorithm, application, program, module, or code residing in hardware, firmware, and/or on a computer useable medium (including software modules and browser plug-ins) that can be executed in a processor of a computer system or a computing device to configure the processor and/or other elements to perform the functions and/or operations described herein.

(78) It should be appreciated that according to at least one embodiment, one or more computer programs, modules, and/or applications that, when executed, perform methods of the present invention need not reside on a single computer or processor but can be distributed in a modular fashion amongst a number of different computers or processors to implement various aspects of the systems and methods disclosed herein.

(79) Thus, illustrative embodiments and arrangements of the present systems and methods provide a computer-implemented method, computer system, and computer program product for processing code(s). The flowchart and block diagrams in the figures illustrate the architecture, functionality, and operation of possible implementations of systems, methods, and computer program products according to various embodiments and arrangements. In this regard, each block in the flowchart or block diagrams can represent a module, segment, or portion of code, which comprises one or more executable instructions for implementing the specified logical function(s). It should also be noted that, in some alternative implementations, the functions noted in the block can occur out of order noted in the figures. For example, two blocks shown in succession may be executed substantially concurrently, or the blocks can sometimes be executed in the reverse order, depending upon the functionality involved. It will also be noted that each block of the block diagrams and/or flowchart illustration, and combinations of blocks in the block diagrams and/or flowchart illustration, can be implemented by particular purpose hardware-based systems that perform the specified functions or acts, or combinations of specialized purpose hardware and computer instructions.

(80) The terminology used herein is to describe particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms “a,” “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

(81) Also, the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting. The use of “including,” “comprising,” or “having,” “containing,” “involving,” and variations thereof herein is meant to encompass the items listed thereafter and equivalents thereof as well as additional items.

(82) The subject matter described above is provided by way of illustration only and should not be construed as limiting. Various modifications and changes can be made to the subject matter described herein without following the example embodiments and applications illustrated and described and without departing from the true spirit and scope of the present invention, which is set forth in the following claims.

Claims

1. A system for performing payments by using a web browser for paying for goods and services, comprising a mobile device comprising a processing circuitry and a server for managing payments, wherein the server is configured to: generate a uniform resource locator (URL), which is linked to a web page at the server, wherein the web page comprises an embedded payment program that is

configured to perform payment based on a payment card data; and send the URL to the mobile device in a text message; wherein the mobile device is configured to: receive from the server the text message comprising the URL; activate the URL, wherein the activation of the URL opens the web page comprising the embedded payment program which is loaded with a predetermined amount of payment and installs the embedded payment program in the mobile device and wherein the embedded payment program comprising a temporary digital wallet software configured to use the processing circuitry to control a near field communication (NFC) radio of the mobile device; transfer the payment card data and the predetermined amount of payment through the NFC radio to a payment terminal by the embedded payment program; and delete the embedded payment program and the payment card data from the mobile device after performing the payment by closing the web page at the end of the transaction.

2. The system of claim 1, wherein the payment terminal comprises EuroPay, MasterCard, Visa (EMV) terminal.

3. The system of claim 1, wherein the payment card data comply with the EMV standard.

4. The system of claim 1, wherein the web page comprises a graphical representation of the embedded payment program and one or more information elements.

5. The system of claim 1, wherein the embedded payment program is configured to control the NFC radio.

6. The system of claim 1, wherein the payment card data comprises at least one of a bank account details, an account holder date of expiration of the payment card data, an available sum of money for payment.

7. The system of claim 1, wherein the mobile device is configured to send a purchase status information to the server.

8. The system of claim 1, wherein the predetermined amount of payment is selected from a national currency, a cryptographic currency, loyalty club points and money worth coupon.

9. A method for performing payments by using a web browser for paying for goods and services operating in a mobile device, comprising: generating, by a server for managing payment, a uniform resource locator (URL), which is linked to a web page at the server, wherein the web page comprises an embedded payment program that is configured to perform payment based on a payment card data; and sending, by the server, the URL to a mobile device comprising a processing circuitry in a text message; receiving, by the mobile device from the server the text message comprising the URL, which is linked to a web page at the server; activating the URL, wherein the activation of the URL opens a web page comprising the embedded payment program which is loaded with a predetermined amount of payment and installs the embedded payment program in the mobile device and wherein the embedded payment program comprising a temporary digital wallet software configured to use the processing circuitry to control a near field communication (NFC) radio of the mobile device; performing a payment by the embedded payment program in the mobile device, which is configured to transfer the payment card data through the NFC radio of the mobile device to a payment terminal; and after performing the payment, delete the embedded payment program from the mobile device by closing the web page at the end of the transaction.

10. The method of claim 9, wherein the payment terminal comprises a EuroPay, MasterCard, Visa (EMV) terminal.

11. The method of claim 9, wherein the payment card data comply with an EMV standard.

12. The method of claim 9, wherein the web page comprises a graphical representation of the embedded payment program and information related to a payment using the web page.

13. The method of claim 9, wherein the payment card data comprises at least one of a bank account details, an account holder details, a date of expiration of the payment card data, and an available sum of money for payment.

14. The method of claim 9, wherein the mobile device is configured to send purchase status information to the server.

15. The method of claim 9, wherein the predetermined amount of payment is selected from a national currency, a cryptographic currency, loyalty club points, and money worth coupon.
 16. A server for performing payments, wherein the server is configured to: generate a text message comprising a uniform resource locator (URL), which is linked to a web page at the server, wherein the web page comprises an embedded payment program loaded with a predetermined amount of payment and payment card data to be installed in a mobile device; send the URL to a mobile device to be activated; and perform payment by the embedded payment program, which is configured to transfer payment card data through a near field communication (NFC) radio to a payment terminal; wherein the embedded program and the payment card data are deleted from the mobile device after performing the payment by closing the web page at the end of the transaction.
 17. The server of claim 16, wherein the payment terminal comprises an EuroPay, MasterCard, Visa (EMV) terminal.
 18. The server of claim 16, wherein the payment card data comply with an EMV standard.
 19. The server of claim 16, wherein the embedded software program comprises a digital wallet program loaded with the predetermined amount of payment.
 20. The server of claim 16, wherein the web page comprises a graphical representation of a link for downloading the software program and information related to the user payment card data.
 21. The server of claim 16, wherein the payment card data comprises at least one of bank account details, account holder details, date of expiration of the payment card data, an available sum of money for payment.
 22. The server of claim 16 is configured to receive a purchase status information from the mobile device is configured to send to the server.
 23. The server of claim 16, wherein the predetermined amount of payment is selected from a national currency, a cryptographic currency, loyalty club points and money worth coupon.
-