

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406484
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Hassani; Ali et al.

Biometric task network

Abstract

A selected biometric analysis task is performed in a deep neural network that includes a common feature extraction neural network, a plurality of task-specific neural networks, a segmentation neural network, a landmark mesh neural network, a plurality of soft target segmentation neural networks, and a plurality of expert pooling neural networks that perform the plurality of biometric analysis tasks by inputting the image to the common feature extraction network to determine latent variables. The latent variables can be input to the plurality of biometric task-specific neural networks to determine a plurality of first biometric analysis task outputs. The latent variables can be input to a landmark mesh neural network to determine a landmark mesh. The landmark mesh and the first biometric task outputs to a plurality of expert pooling neural networks to determine a plurality of second biometric task outputs.

Inventors:	Hassani; Ali (Ann Arbor, MI), El Shair; Zaid (Westland, MI)
Applicant:	Ford Global Technologies, LLC (Dearborn, MI)
Family ID:	87430798
Assignee:	Ford Global Technologies, LLC (Dearborn, MI)
Appl. No.:	17/730315
Filed:	April 27, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230260269 A1	Aug. 17, 2023

Related U.S. Application Data

us-provisional-application US 63310401 20220215

Publication Classification

Int. Cl.: G06V10/82 (20220101); G06V40/16 (20220101); G06V40/40 (20220101)

U.S. Cl.:

CPC G06V10/82 (20220101); G06V40/168 (20220101); G06V40/172 (20220101); G06V40/45 (20220101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7797803	12/2009	Falb et al.	N/A	N/A
10179563	12/2018	Ammons	N/A	N/A
10747989	12/2019	Zou et al.	N/A	N/A
10860837	12/2019	Ranjan et al.	N/A	N/A
2018/0060648	12/2017	Yoo et al.	N/A	N/A
2018/0365532	12/2017	Molchanov	N/A	G06V 40/162
2020/0210688	12/2019	Xu	N/A	N/A
2020/0394390	12/2019	Zhang et al.	N/A	N/A
2021/0117984	12/2020	Sharma et al.	N/A	N/A
2021/0150240	12/2020	Yu et al.	N/A	N/A
2022/0406090	12/2021	Liu	N/A	G06N 3/0455
2023/0063229	12/2022	Vemulapalli et al.	N/A	N/A
2023/0074706	12/2022	Xiao	N/A	G06V 30/1444
2023/0154090	12/2022	Bradley et al.	N/A	N/A
2023/0206700	12/2022	Khan	382/116	G06V 40/165
2023/0206925	12/2022	Havdan et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
106529402	12/2018	CN	N/A
110930982	12/2019	CN	N/A
111539480	12/2019	CN	N/A
11065977	12/2020	CN	N/A
110659744	12/2020	CN	N/A
4177822	12/2022	EP	N/A
101579288	12/2014	KR	N/A
2016026063	12/2015	WO	N/A
2022003107	12/2021	WO	N/A

OTHER PUBLICATIONS

T. Devries, K. Biswaranjan and G. W. Taylor, "Multi-task Learning of Facial Landmarks and Expression," 2014 Canadian Conference on Computer and Robot Vision, 2014, pp. 98-103, doi:

10.1109/CRV.2014.21. cited by applicant

Devries et al., "Multi-Task Learning of Facial Landmarks and Expression", 2014 Canadian Conference on Computer and Robot Vision, DOI: 10.1109/CRV.2014.21, Electronic ISBN:978-1-4799-4337-1, CD:978-1-4799-4338-8. cited by applicant

Notice of Allowance dated Aug. 23, 2023 re U.S. Appl. No. 17/730,324, filed Apr. 27, 2022. cited by applicant

Non-Final Office Action dated Oct. 8, 2024 re U.S. Appl. No. 17/730,294, filed Apr. 27, 2022. cited by applicant

Final Office Action dated Oct. 8, 2024 re U.S. Appl. No. 17/730,301, filed Apr. 27, 2022. cited by applicant

Notice of Allowance dated Feb. 14, 2025 re U.S. Appl. No. 17/730,301, filed Apr. 27, 2022. cited by applicant

Non-Final Office Action dated Jun. 2, 2025 re U.S. Appl. No. 17/730,294, filed Apr. 27, 2022. cited by applicant

Primary Examiner: Bali; Vikkram

Attorney, Agent or Firm: Brooks Kushman P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This patent application claims priority to U.S. Provisional Patent Application No. 63/310,401 filed on Feb. 15, 2022, which is hereby incorporated by reference in its entirety.

BACKGROUND

(1) Images can be acquired by sensors and processed using a computer to determine data regarding objects in an environment around a system. Operation of a sensing system can include acquiring accurate and timely data regarding objects in the system's environment. A computer can acquire images from one or more image sensors that can be processed to determine data regarding objects. Data extracted from images of objects can be used by a computer to operate systems including vehicles, robots, security, and object tracking systems.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram of an example traffic infrastructure system.
- (2) FIG. 2 is a diagram of an example biometric image.
- (3) FIG. 3 is a diagram of an example biometric system.
- (4) FIG. 4 is a diagram of an example multi-task biometric system.
- (5) FIG. 5 is a diagram of an example spoofed biometric image.
- (6) FIG. 6 is a diagram of an example segmented image.
- (7) FIG. 7 is a diagram of example multi-task biometric system including facial landmark processing.
- (8) FIG. 8 is a diagram of example multi-task biometric system including facial landmark processing and memory.
- (9) FIG. 9 is a flowchart diagram of an example process to train a deep neural network to perform biometric analysis tasks.

(10) FIG. 10 is a flowchart diagram of an example process to train a deep neural network including facial landmark guess processing and memory to perform biometric tasks.

(11) FIG. 11 is a flowchart diagram of an example process for performing biometric tasks in operation of a vehicle.

DETAILED DESCRIPTION

(12) Biometric analysis can be implemented in a computer to determine data regarding objects, for example potential users, in or around system or machine, such as a vehicle. Based on data determined from biometric analysis a vehicle, for example, can be operated. Biometric analysis herein means measuring, or making a determination based on measuring, data regarding a user based on physical characteristics of the user. For example, a computing device in a vehicle or traffic infrastructure system can be programmed to acquire one or more images from one or more sensors included in the vehicle or the traffic infrastructure system and grant permission for a user to operate the vehicle based on biometric data determined based on the images. This granting of permission is referred to herein as biometric identification. Biometric identification means determining the identity of a potential user based on analyzing biometric data. The determined identity of a user can be logged to keep track of which user is accessing a vehicle or compared to a list of authorized users to authenticate a user prior to granting permission to the user to operate a vehicle or system. In addition to biometric identification, biometric analysis can include determining one or more physical characteristics such as user drowsiness, gaze direction, user pose, user liveliness, etc. Biometric analysis tasks can be implemented in various other machines or systems, in addition to vehicles. For example, a computer system, a robot system, a manufacturing system, and a security system can require that a potential user be identified using an acquired image before granting access to the system or a secure area.

(13) Advantageously, techniques described herein can enhance the ability of a computing device in a traffic infrastructure system to perform biometric analysis based on a recognition that facial biometric algorithms such as facial feature identification include redundant tasks across different applications. Further, some facial biometric algorithms have sparse or limited training datasets. Techniques described herein include a multi-task network that includes a common feature identification neural network and a plurality of biometric analysis task neural networks. A deep neural network is configured to include a common feature extraction neural network as a “backbone” and a plurality of biometric analysis task neural networks that receive as input a common set of latent variables generated by the common feature extraction neural network. The deep neural network includes a plurality of expert pooling deep neural networks that training of the deep neural network by sharing results between the plurality of biometric analysis tasks.

(14) Performing biometric task analysis in a neural network can benefit from data regarding facial landmarks. Facial landmarks are key locations on an image of a user's face. Inside and outside corners of left and right eyes, left and right corners of lips, locations where the widest points of the nose joint the cheeks, and inside and outside corners of left and right eyebrows are all examples of facial landmarks. Polygons can be constructed based on the landmarks that indicate a soft target estimate of the locations of facial features. The soft target estimate of the locations of facial features can be input to segmentation neural networks and biometric task analysis neural networks as conditioning values. Inputting the soft target estimates can training of the segmentation neural networks and biometric task analysis neural networks by reducing the number of processing runs for output of the deep neural network to converge on correct results. Inputting the soft target estimates can operation of the segmentation neural networks and biometric task analysis neural networks at inference time by increasing the accuracy of the predictions output by the deep neural network while reducing a number of computer operations required to reach the predictions.

(15) Disclosed herein is a method, including providing output from a selected biometric analysis task that is one of a plurality of biometric analysis tasks, based on an image provided from an image sensor wherein the selected biometric analysis task is performed in a deep neural network

that includes a common feature extraction neural network, a plurality of biometric task-specific neural networks, a segmentation neural network, a landmark mesh neural network, a plurality of soft target segmentation neural networks, and a plurality of expert pooling neural networks that perform the plurality of biometric analysis tasks by inputting the image to the common feature extraction network to determine latent variables. The latent variables can be input to the plurality of biometric task-specific neural networks to determine a plurality of first biometric analysis task outputs. The latent variables can be input to a landmark mesh neural network to determine a landmark mesh and the landmark mesh and the first biometric task outputs can be input to a plurality of expert pooling neural networks to determine a plurality of second biometric task outputs. The plurality of biometric tasks can be performed by inputting the latent variables to the segmentation neural network to determine a first estimate segmentation map, inputting the landmark mesh to the plurality of soft target segmentation neural networks to determine a plurality of soft target estimates and inputting the first estimate segmentation map and the plurality of soft target estimates to an expert pooling neural network to determine a segmentation prediction.

(16) The output from the landmark mesh neural network can be stored in a memory and processed to determine temporal data regarding one or more image segments. A device can be operated based on the output from the deep neural network according to the selected biometric analysis task. The biometric analysis tasks can include biometric identification, liveness, and facial segmentation. The common feature extraction neural network can include a plurality of convolutional layers. The plurality of task-specific neural networks can include a plurality of fully connected layers. The segmentation neural network, the landmark mesh neural network, and the plurality of expert pooling neural networks can include a plurality of fully connected layers. The outputs from the plurality of task-specific neural networks can be input to a Softmax function before being combined with the outputs from the common feature extraction neural network. The outputs from the common feature extraction neural network can be combined with the soft target estimates using expert pooling. The deep neural network can be trained by determining one or more first loss functions based on the plurality of second biometric task outputs, combining the first loss functions to determine a joint loss function, and backpropagating the one or more first loss function and the joint loss function back through the deep neural network. Output from the expert pooling can be input to a Softmax function before being combined to determine the first loss functions. One or more outputs from the plurality of task-specific neural networks can be set to zero during training. The deep neural network can be trained based on a loss function determined based on sparse-categorical-cross-entropy statistics.

(17) Further disclosed is a computer readable medium, storing program instructions for executing some or all of the above method steps. Further disclosed is a computer programmed for executing some or all of the above method steps, including a computer apparatus, programmed to provide output from a selected biometric analysis task that is one of a plurality of biometric analysis tasks, based on an image provided from an image sensor wherein the selected biometric analysis task is performed in a deep neural network that includes a common feature extraction neural network, a plurality of biometric task-specific neural networks, a segmentation neural network, a landmark mesh neural network, a plurality of soft target segmentation neural networks, and a plurality of expert pooling neural networks that perform the plurality of biometric analysis tasks by inputting the image to the common feature extraction network to determine latent variables. The latent variables can be input to the plurality of biometric task-specific neural networks to determine a plurality of first biometric analysis task outputs. The latent variables can be input to a landmark mesh neural network to determine a landmark mesh and the landmark mesh and the first biometric task outputs can be input to a plurality of expert pooling neural networks to determine a plurality of second biometric task outputs. The plurality of biometric tasks can be performed by inputting the latent variables to the segmentation neural network to determine a first estimate segmentation map, inputting the landmark mesh to the plurality of soft target segmentation neural networks to

determine a plurality of soft target estimates and inputting the first estimate segmentation map and the plurality of soft target estimates to an expert pooling neural network to determine a segmentation prediction.

(18) The instructions can include further instructions to store the output from the landmark mesh neural network in a memory and process the output to determine temporal data regarding one or more image segments. A device can be operated based on the output from the deep neural network according to the selected biometric analysis task. The biometric analysis tasks can include biometric identification, liveliness, and facial segmentation. The common feature extraction neural network can include a plurality of convolutional layers. The plurality of task-specific neural networks can include a plurality of fully connected layers. The segmentation neural network, the landmark mesh neural network, and the plurality of expert pooling neural networks can include a plurality of fully connected layers. The outputs from the plurality of task-specific neural networks can be input to a Softmax function before being combined with the outputs from the common feature extraction neural network. The outputs from the common feature extraction neural network can be combined with the soft target estimates using expert pooling. The deep neural network can be trained by determining one or more first loss functions based on the plurality of second biometric task outputs, combining the first loss functions to determine a joint loss function, and backpropagating the one or more first loss function and the joint loss function back through the deep neural network. Output from the expert pooling can be input to a Softmax function before being combined to determine the first loss functions. One or more outputs from the plurality of task-specific neural networks can be set to zero during training. The deep neural network can be trained based on a loss function determined based on sparse-categorical-cross-entropy statistics.

(19) FIG. 1 is a diagram of a sensing system **100** that can include a traffic infrastructure node **105** that includes a server computer **120** and stationary sensors **122**. Sensing system **100** includes a vehicle **110**, operable in autonomous (“autonomous” by itself in this disclosure means “fully autonomous”), semi-autonomous, and occupant piloted (also referred to as non-autonomous) mode. One or more vehicle **110** computing devices **115** can receive data regarding the operation of the vehicle **110** from sensors **116**. The computing device **115** may operate the vehicle **110** in an autonomous mode, a semi-autonomous mode, or a non-autonomous mode.

(20) The computing device **115** includes a processor and a memory such as are known. Further, the memory includes one or more forms of computer-readable media, and stores instructions executable by the processor for performing various operations, including as disclosed herein. For example, the computing device **115** may include programming to operate one or more of vehicle brakes, propulsion (i.e., control of acceleration in the vehicle **110** by controlling one or more of an internal combustion engine, electric motor, hybrid engine, etc.), steering, climate control, interior and/or exterior lights, etc., as well as to determine whether and when the computing device **115**, as opposed to a human operator, is to control such operations.

(21) The computing device **115** may include or be communicatively coupled to, i.e., via a vehicle communications bus as described further below, more than one computing devices, i.e., controllers or the like included in the vehicle **110** for monitoring and/or controlling various vehicle components, i.e., a powertrain controller **112**, a brake controller **113**, a steering controller **114**, etc. The computing device **115** is generally arranged for communications on a vehicle communication network, i.e., including a bus in the vehicle **110** such as a controller area network (CAN) or the like; the vehicle **110** network can additionally or alternatively include wired or wireless communication mechanisms such as are known, i.e., Ethernet or other communication protocols.

(22) Via the vehicle network, the computing device **115** may transmit messages to various devices in the vehicle and/or receive messages from the various devices, i.e., controllers, actuators, sensors, etc., including sensors **116**. Alternatively, or additionally, in cases where the computing device **115** actually comprises multiple devices, the vehicle communication network may be used for communications between devices represented as the computing device **115** in this disclosure.

Further, as mentioned below, various controllers or sensing elements such as sensors **116** may provide data to the computing device **115** via the vehicle communication network.

(23) In addition, the computing device **115** may be configured for communicating through a vehicle-to-infrastructure (V-to-I) interface **111** with a remote server computer **120**, i.e., a cloud server, via a network **130**, which, as described below, includes hardware, firmware, and software that permits computing device **115** to communicate with a remote server computer **120** via a network **130** such as wireless Internet (WI-FI®) or cellular networks. V-to-I interface **111** may accordingly include processors, memory, transceivers, etc., configured to utilize various wired and/or wireless networking technologies, i.e., cellular, BLUETOOTH® and wired and/or wireless packet networks. Computing device **115** may be configured for communicating with other vehicles **110** through V-to-I interface **111** using vehicle-to-vehicle (V-to-V) networks, i.e., according to Dedicated Short Range Communications (DSRC) and/or the like, i.e., formed on an ad hoc basis among nearby vehicles **110** or formed through infrastructure-based networks. The computing device **115** also includes nonvolatile memory such as is known. Computing device **115** can log data by storing the data in nonvolatile memory for later retrieval and transmittal via the vehicle communication network and a vehicle to infrastructure (V-to-I) interface **111** to a server computer **120** or user mobile device **160**.

(24) As already mentioned, generally included in instructions stored in the memory and executable by the processor of the computing device **115** is programming for operating one or more vehicle **110** components, i.e., braking, steering, propulsion, etc., without intervention of a human operator. Using data received in the computing device **115**, i.e., the sensor data from the sensors **116**, the server computer **120**, etc., the computing device **115** may make various determinations and/or control various vehicle **110** components and/or operations without a driver to operate the vehicle **110**. For example, the computing device **115** may include programming to regulate vehicle **110** operational behaviors (i.e., physical manifestations of vehicle **110** operation) such as speed, acceleration, deceleration, steering, etc., as well as tactical behaviors (i.e., control of operational behaviors typically in a manner intended to achieve efficient traversal of a route) such as a distance between vehicles and/or amount of time between vehicles, lane-change, minimum gap between vehicles, left-turn-across-path minimum, time-to-arrival at a particular location and intersection (without signal) minimum time-to-arrival to cross the intersection.

(25) Controllers, as that term is used herein, include computing devices that typically are programmed to monitor and/or control a specific vehicle subsystem. Examples include a powertrain controller **112**, a brake controller **113**, and a steering controller **114**. A controller may be an electronic control unit (ECU) such as is known, possibly including additional programming as described herein. The controllers may communicatively be connected to and receive instructions from the computing device **115** to actuate the subsystem according to the instructions. For example, the brake controller **113** may receive instructions from the computing device **115** to operate the brakes of the vehicle **110**.

(26) The one or more controllers **112**, **113**, **114** for the vehicle **110** may include known electronic control units (ECUs) or the like including, as non-limiting examples, one or more powertrain controllers **112**, one or more brake controllers **113**, and one or more steering controllers **114**. Each of the controllers **112**, **113**, **114** may include respective processors and memories and one or more actuators. The controllers **112**, **113**, **114** may be programmed and connected to a vehicle **110** communications bus, such as a controller area network (CAN) bus or local interconnect network (LIN) bus, to receive instructions from the computing device **115** and control actuators based on the instructions.

(27) Sensors **116** may include a variety of devices known to provide data via the vehicle communications bus. For example, a radar fixed to a front bumper (not shown) of the vehicle **110** may provide a distance from the vehicle **110** to a next vehicle in front of the vehicle **110**, or a global positioning system (GPS) sensor disposed in the vehicle **110** may provide geographical

coordinates of the vehicle **110**. The distance(s) provided by the radar and/or other sensors **116** and/or the geographical coordinates provided by the GPS sensor may be used by the computing device **115** to operate the vehicle **110** autonomously or semi-autonomously, for example.

(28) The vehicle **110** is generally a land-based vehicle **110** capable of autonomous and/or semi-autonomous operation and having three or more wheels, i.e., a passenger car, light truck, etc. The vehicle **110** includes one or more sensors **116**, the V-to-I interface **111**, the computing device **115** and one or more controllers **112**, **113**, **114**. The sensors **116** may collect data related to the vehicle **110** and the environment in which the vehicle **110** is operating. By way of example, and not limitation, sensors **116** may include, i.e., altimeters, cameras, LIDAR, radar, ultrasonic sensors, infrared sensors, pressure sensors, accelerometers, gyroscopes, temperature sensors, pressure sensors, hall sensors, optical sensors, voltage sensors, current sensors, mechanical sensors such as switches, etc. The sensors **116** may be used to sense the environment in which the vehicle **110** is operating, i.e., sensors **116** can detect phenomena such as weather conditions (precipitation, external ambient temperature, etc.), the grade of a road, the location of a road (i.e., using road edges, lane markings, etc.), or locations of target objects such as neighboring vehicles **110**. The sensors **116** may further be used to collect data including dynamic vehicle **110** data related to operations of the vehicle **110** such as velocity, yaw rate, steering angle, engine speed, brake pressure, oil pressure, the power level applied to controllers **112**, **113**, **114** in the vehicle **110**, connectivity between components, and accurate and timely performance of components of the vehicle **110**.

(29) Vehicles can be equipped to operate in both autonomous and occupant piloted mode. By a semi- or fully-autonomous mode, we mean a mode of operation wherein a vehicle can be piloted partly or entirely by a computing device as part of a system having sensors and controllers. The vehicle can be occupied or unoccupied, but in either case the vehicle can be partly or completely piloted without assistance of an occupant. For purposes of this disclosure, an autonomous mode is defined as one in which each of vehicle propulsion (i.e., via a powertrain including an internal combustion engine and/or electric motor), braking, and steering are controlled by one or more vehicle computers; in a semi-autonomous mode the vehicle computer(s) control(s) one or more of vehicle propulsion, braking, and steering. In a non-autonomous mode, none of these are controlled by a computer.

(30) A traffic infrastructure node **105** can include a physical structure such as a tower or other support structure (i.e., a pole, a box mountable to a bridge support, cell phone tower, road sign support, etc.) on which infrastructure sensors **122**, as well as server computer **120** can be mounted, stored, and/or contained, and powered, etc. One traffic infrastructure node **105** is shown in FIG. 1 for ease of illustration, but the system **100** could and likely would include tens, hundreds, or thousands of traffic infrastructure nodes **105**. The traffic infrastructure node **105** is typically stationary, i.e., fixed to and not able to move from a specific geographic location. The infrastructure sensors **122** may include one or more sensors such as described above for the vehicle **110** sensors **116**, i.e., lidar, radar, cameras, ultrasonic sensors, etc. The infrastructure sensors **122** are fixed or stationary. That is, each sensor **122** is mounted to the infrastructure node so as to have a substantially unmoving and unchanging field of view.

(31) Server computer **120** typically has features in common with the vehicle **110** V-to-I interface **111** and computing device **115**, and therefore will not be described further to avoid redundancy. Although not shown for ease of illustration, the traffic infrastructure node **105** also includes a power source such as a battery, solar power cells, and/or a connection to a power grid. A traffic infrastructure node **105** server computer **120** and/or vehicle **110** computer **115** can receive sensor **116**, **122** data to monitor one or more objects. An "object," in the context of this disclosure, is a physical, i.e., material, structure detected by a vehicle sensor **116** and/or infrastructure sensor **122**. An object may be a biological object such as a human. A server computer **120** and/or computing device **115** can perform biometric analysis on object data acquired by a sensor **116/122**.

(32) FIG. 2 is a diagram of an image acquisition system **200** included in a vehicle **110** or traffic infrastructure node **105**. Image **202** can be acquired by a camera **204**, which can be a sensor **116**, **122**, having a field of view **206**. The image **202** can be acquired when a user approaches a vehicle **110**, for example. A computing device **115** in the vehicle **110** or a server computer **120** can execute a biometric analysis task that authenticates the user and grants permission to the user to operate the vehicle **110**, i.e., unlocks a door to permit the user to enter the vehicle **110**. In addition to biometric identification, spoof detection biometric analysis tasks such as liveness detection can be used to determine whether the image data presented for user identification is a real image of a real user, i.e., not a photograph of a user or not a mask of a user.

(33) Other biometric analysis tasks based on images of a user as are known in the art include drowsiness detection, head pose detection, gaze detection, and emotion detection. Drowsiness detection can determine a user's state of alertness typically by analyzing eyelid position and blink rates. Head pose detection can also determine a user's state of alertness and attention to vehicle operation, typically by analyzing location and orientation of a user's face to detect nodding and slumping postures. Gaze detection can determine the direction in which a user's eyes are looking to determine whether the user is paying attention to vehicle operation. Emotion detection can determine an emotional state of a user, i.e., is a user agitated or frightened, to detect possible distractions from vehicle operation.

(34) FIG. 3 is a diagram of a biometric analysis task system **300**. A biometric analysis task system **300** can be implemented on a server computer **120** or computing device **115**. Biometric analysis tasks including user identification, spoof detection, drowsiness detection, head pose detection, and gaze detection share common computational tasks **304**, such as determining a location and orientation of a user's face in an image **302**. Other common computational tasks include determining location and size of facial features such as eyes, mouth, and nose. FIG. 3 illustrates an image **302** being input to common computational tasks **304** to determine common facial feature data such as location, orientation, and features, for example. The common facial feature data can be input to biometric analysis tasks **306**, **308**, **310** to determine biometric tasks outputs **312**, **314**, **316**. The biometric task outputs can be **312**, **314**, **316** one or more of user identification, spoof detection, drowsiness detection, head pose detection, gaze detection, and emotion detection etc.

(35) FIG. 4 is a diagram of a biometric analysis task system implemented as a deep neural network (DNN) **400** configured to input an image **402** into a plurality of convolutional layers **404**, **406**, **408** that are included in a common feature extraction convolutional neural network (CNN) **410**. A biometric analysis task system implemented as a DNN **400** can be executed on a server computer **120** or computing device **115**. The common feature extraction or “backbone” CNN **410** extracts common facial features from image data and outputs latent variables. Latent variables are common facial features output by CNN **410** in response to an input image **402** that includes a human face. CNN **410** is trained as described herein to process an image **402** to determine the location of a human face and determine facial features indicating the location, orientation, and size of human facial features such as eyes, nose, and mouth. CNN **410** can also determine facial features such as skin tone, texture and presence/absence of facial hair, and presence/absence of objects such as glasses and body piercings. The facial features are referred to as common facial features because they are output as latent variables in common to a plurality of biometric analysis task neural networks **412**, **414**, **416**, **418**, **420** and a segmentation neural network **422**. Biometric analysis task neural networks **412**, **414**, **416**, **418**, **420** include a plurality of fully connected layers that can perform tasks such as biometric identification, spoof detection including liveness, drowsiness detection, head pose detection, gaze detection, and emotion detection. Segmentation neural network **422** can perform facial feature segmentation by determining regions in an image of a user's face that can include features such as eyes, teeth, lips, nose, and facial skin, for example.

(36) Biometric analysis task neural networks **412**, **414**, **416**, **418**, **420** and segmentation neural network **422** are trained to output predictions regarding the biometric analysis tasks or

segmentation task based on latent variables output from the common feature extraction CNN **410**. Predictions output from the biometric analysis tasks include biometric identification of a user. A biometric identification prediction is a probability that an input image includes a human face that matches a human face that the DNN **400** was previously trained to recognize. A liveliness prediction is a probability that the image **402** includes a live user, as opposed to a photograph or mask of a user. A drowsiness prediction is a probability that the image **402** includes a user experiencing drowsiness. A head pose prediction are estimates of the roll, pitch, and yaw of a user's head. An emotion prediction is a probability that the user is experiencing a strong emotion such as anger or fear. A facial segmentation prediction is an image with regions which indicate the locations of facial features.

(37) DNN **400** can include SoftMax functions **424, 426, 428, 430, 432** on the output of the biometric analysis task neural networks **412, 414, 416, 418, 420**, respectively. The SoftMax functions **424, 426, 428, 430, 432** are functions that turn a vector of K real values into a vector of K real values between 0 and 1 that sum to 1. Output from the SoftMax functions **424, 426, 428, 430, 432** can be output as results of the biometric analysis tasks or used to calculate loss functions. Processing the outputs of the biometric analysis task neural networks **412, 414, 416, 418, 420** with SoftMax functions **424, 426, 428, 430, 432** permits the outputs to be combined into a joint loss function for training the DNN **400**. A loss function compares the output from a SoftMax function **424, 426, 428, 430, 432** connected to a biometric analysis task neural network **412, 414, 416, 418, 420** with a ground truth value to determine how closely the biometric analysis task neural network has come to determining a correct result. A SoftMax function **424, 426, 428, 430, 432**, by limiting the output from each biometric analysis task neural network **412, 414, 416, 418, 420** to values between 0 and 1 prevents one or more of the outputs from dominating the calculation of a joint loss function due to numerical differences in the outputs. A joint loss function is determined by combining the individual loss functions for each biometric analysis task neural network **412, 414, 416, 418, 420**, typically by adding the individual loss functions together.

(38) Training a DNN **400** can include determining a training dataset of images **402** and ground truth for each image **402**. Determining ground truth can include inspecting the images **402** in the training dataset and estimating the correct result to be expected from a SoftMax function **424, 426, 428, 430, 432** connected to a biometric analysis task neural network **412, 414, 416, 418, 420**. During training an image **402** can be input to the DNN **400** a plurality of times. Each time the image **402** is input, weights or parameters that control the operation of the convolutional layers **404, 406, 408**, of the CNN **410** and the fully connected layers of the biometric analysis task neural networks **412, 414, 416, 418, 420** can be altered and a joint loss function based on the outputs and the ground truth values for each output can be determined. The joint loss function can be backpropagated through the DNN **400** to select the weights for each layer that result in the lowest joint loss, i.e., the most correct results. Backpropagation is a process for applying the joint loss function to the weights of the DNN **400** layers starting at the layers closest to the output and progressing back to the layers closest to the input. By processing a plurality of input images **402** including ground truth in the training dataset a plurality of times, a set of weights for the layers of the DNN **400** can be selected that converge on correct results for the entire training dataset the DNN **400** can be determined. Selecting an optimum set of weights in this fashion is referred to as training the DNN **400**.

(39) Segmentation determines regions in an image indicating the different facial features. Segmentation labels the regions according to segment classes, where each segment class indicates a different facial feature. Example segment classes include left eye, right eye, teeth, upper lip, lower lip, nose, facial skin, left eyebrow, right eyebrow, etc. The number of facial segmentation classes can be equal to 14 or more for a typical segmentation neural network **422**. Each segment is further specified by its location, shape, and number of pixels included in the segment. In determining a loss function, the segments in a predicted segmented image output by segmentation neural network

422 can be compared to the segments in a ground truth segmented image. Comparing segments includes determining that the pixels of a predicted segment overlap with the pixels of a ground truth segment having the same class designation. The comparison can be qualitative, based on sparse-categorical-cross-entropy statistics, which requires that a percentage, for example 50%, of the ground truth segment pixels are overlapped with a predicted segment with the same class designation. In other examples the comparison can be quantitative, based on mean-square-error statistics which count the number of non-overlapped pixels in the ground truth segments and take the square of the number of non-overlapped pixels.

(40) Training the DNN **400** using a joint loss function can advantageously compensate for differences in training datasets for each biometric analysis task. The quality of training for a biometric task can be dependent upon the number of images available with appropriate ground truth for each biometric analysis task. For example, biometric identification tasks can benefit from the existence of large commercially available datasets that include ground truth. Other biometric analysis tasks, such as drowsiness determination or gaze determination can require that a user acquire image data and estimate ground truth manually. Advantageously, training DNN **400** using a joint loss function determined as discussed herein can permit sharing training datasets between biometric analysis tasks having large training datasets with biometric analysis tasks having smaller training datasets. For example, the individual loss functions can be weighted as they are combined to form a joint loss function to give more weight to loss functions that include larger training datasets.

(41) In examples where one or more of the biometric analysis tasks can have small amounts of ground truth data to include in a training dataset, training the DNN **400** can be done by branch training isolation. Branch training isolation sets the output from a biometric analysis task neural network having no ground truth data for a particular image in a training dataset to a null value. Setting the output from a biometric analysis task neural network to a null value also sets the loss function determined for the biometric analysis task neural network to zero. Branch training isolation also freezes the weights included in the biometric analysis task neural network for that image. This permits the biometric analysis task neural network to be available for joint training along with the rest of the DNN **400** without penalizing biometric analysis tasks with sparse training datasets. For example, drowsiness detection typically has fewer images with ground truth than identification tasks.

(42) FIG. 5 is a diagram of an image acquisition system **500** included in a vehicle **110** or traffic infrastructure node **105**. Spoofed image **502** can be acquired by a camera **504**, which can be a sensor **116**, **122**, having a field of view **508**. The image **502** has been acquired of a user wearing a spandex mask to appear as an authorized user (i.e., to spoof the user) of a vehicle. A computing device **115** in the vehicle **110** or a server computer **120** can execute a biometric analysis task that authenticates the user and grants permission to the user to operate the vehicle **110**, i.e., unlocks a door to permit the user to enter the vehicle **110**. In addition to biometric identification, spoof detection biometric analysis tasks such as liveness detection can be used to determine whether the image data presented for user identification is a real image of a real user, i.e., not a photograph of a user or not a mask of a user. Without liveness detection a biometric identification system can be spoofed into granting access to an unauthorized user.

(43) Other techniques for anti-spoofing detection exist. For example, a 3D or depth scanner such as a lidar scanner can be employed in addition to a camera to acquire data of a potential user. The 3D scanner can detect the difference between a flat photograph and a human face. A thermal or far-infrared camera can detect characteristic thermal emissions from facial skin to distinguish a mask from a human face. Techniques discussed herein for incorporating output from image segmentation tasks with biometric identification tasks and skin tone biometric analysis tasks enhances accuracy of both biometric identification and liveness detection while eliminating a need for additional 3D or infrared sensors. By configuring the biometric analysis task neural network for multiple

biometric tasks as described herein, training datasets can be used that include relatively fewer examples for tasks such as liveness detection to produce good training results with fewer resources expended than if more training images and ground truth were required.

(44) FIG. 6 is a diagram of an image **600** of a human face **602**. Image **600** includes landmark locations, indicated by open circles, indicating inside **606** and outside **608** corners of the right eye, inside **610** and outside **612** corners of the left eye, and right **614** and left **616** corners of the mouth. Landmark locations can be determined by DNN **700**, **800**, discussed in relation to FIGS. 7 and 8, below. Based on the landmark locations, polygons can be constructed indicating the mouth **618**, right eye **620**, and left eye **622**. Polygons based on landmark locations can also be determined by DNN **700**, **800**, discussed in relation to FIGS. 7 and 8, below. Image **604** includes a segmented **624** version of a human face **602**. Segmented **624** version of the human face **602** can also be determined by DNN **700**, **800** based on the landmark locations output by common feature extraction CNN **704** of DNN **700**, **800**.

(45) Segmented **624** version of human face **602** includes image segments indicating the mouth **626**, right eye **628**, left eye **630**. The image segments indicating the mouth **626**, right eye **628**, left eye **630** indicate the corresponding areas of the human face **602** with higher accuracy than the polygons, i.e., the pixels of the image segments conform more closely to the areas of the facial features in image **600**, however segmented **624** version of the human face **602** requires more time and computing resources to determine. Polygons based on landmark locations is a soft target estimate for expected locations of facial features in human face **602**. A soft target estimate is a coarse estimate for expected locations of facial features that can be determined quickly using limited computing resources. The soft target estimate can be input to biometric analysis tasks to enhance the computation of the biometric analysis tasks by indicating regions of the image in which to perform processing.

(46) For example, gaze detection, emotion detection, and drowsiness detection can be enhanced by concentrating processing on polygons indicating the eyes **620**, **622** and mouth **618** regions of an image **600**. Landmark locations which indicate other regions of the human face **602** can be determined such as eyebrows, nose, chin, etc. and polygons based on these additional landmark locations can be input to biometric analysis tasks to enhance processing using limited additional time and processing resources.

(47) FIG. 7 is a diagram of a DNN **700** configured to enhance training and inference over the DNN **400** illustrated in FIG. 4 by combining data from a landmark mesh neural network **710** with output from biometric analysis task neural networks for emotion detection **706** and head pose **708** using expert pooling neural networks **722**, **724**. DNN **700** inputs an image **702** to a common feature extraction CNN **704**. CNN **704** includes a plurality of convolutional layers to determine latent variables indicating facial features determined based on input image **702**. Latent variables output from the common feature extraction CNN **704**, i.e., facial features, is output to emotion detection **706** and head pose **708** biometric analysis neural networks, first estimate segmentation neural network **716**, and landmark mesh neural network **710**. Emotion detection **706** and head pose **708** biometric analysis neural networks, first estimate segmentation neural network **716**, and landmark mesh neural network **710** include fully connected layers. Landmark mesh neural network **710** determines a landmark mesh based on an input image **702** that includes a human face as discussed in relation to FIG. 6, above. Output landmark mesh is input to a SoftMax function **712** that conditions the landmark mesh output to range from 0 to 1. Output from SoftMax function **712** is input to soft target estimate neural networks **718**, **720** which determine polygons for combining with outputs from emotion detection **706** and head pose **708** biometric analysis task neural networks.

(48) The polygons output from soft target estimate neural networks **718**, **720** can be selected to conform to polygons expected to the emotion detection **706** and head pose **708** biometric analysis task neural networks. As discussed above, eye polygon, mouth polygons and eyebrow polygons

might be expected to emotion detection. Chin polygons, nose polygons, eye polygons and mouth polygons might be expected to emotion detection, for example. Output from emotion detection **706** and head pose **708** biometric analysis neural networks are combined with polygons output from soft target estimate neural networks **718**, **720** at expert pooling neural networks **722**, **724**. Expert pooling neural networks the emotion detection **706** and head pose **708** predictions based on data included in the determined polygons. Predictions output from the expert pooling neural networks **722**, **724** can be output at inference time to a computing device **115** in a vehicle **110** to operate the vehicle. At training time, predictions output from expert pooling neural networks **722**, **724** are input to SoftMax functions **726**, **728** to condition the output to the range between 0 and 1. At training time, output from the SoftMax functions **726**, **728** can be input to loss functions to be combined with ground truth data included in the input image **702**. The loss functions for the predictions can be combined in a joint loss function to be backpropagated through DNN **700**.

(49) Landmark mesh output from SoftMax function **712** can be input to soft target map neural network **714** where the landmark mesh is processed to form an output landmark mesh image that can be input to expert pooling neural network **730** along with latent variables output by common feature extraction CNN **704**. In addition, first estimate segmentation neural network **716** receives as input latent variables and outputs a first estimate segmentation map for input image **702**. First estimate segmentation map includes a plurality of regions of pixels indicating facial segment classes. Expert pooling neural network **730** combines soft target map, latent variables and first estimate segmentation map to determine a segmentation task prediction **732**. At inference time the segmentation task prediction can be used by biometric identification tasks, for example. At training time, segmentation task prediction can be compared to a ground truth segmentation mask to determine a loss function that can be combined with biometric analysis task loss functions to determine a joint loss function to be backpropagated through DNN **700**. Training DNN **700** typically takes place on a server computer **120**. Following training, DNN **700** can be transmitted to a computing device **115** in a vehicle **110** to perform biometric identification tasks on image data acquired by sensors **116** included the vehicle **110**.

(50) Determining a joint loss function can be a function of loss method, task complexity and fusion approach. Loss method is the mathematical technique for determining loss. For example, using mean-squared-error, which calculates differences in pixel counts for facial mask segment outputs vs. ground truth, will generate loss proportional to the number of facial mask segment classes square (i.e., **5002**) whereas determining loss using sparse-categorical-cross-entropy, which determines probabilities of presence/absence for facial mask segment outputs vs. ground truth will be proportional to the number of classes (i.e., **14** facial structures). Determining loss values using the wrong technique can result in destructive training interference, where one loss value dominates the joint loss function.

(51) Loss values can be normalized to reflect the task complexity, i.e., more complex tasks can result in greater loss function values. In addition, it can be beneficial to bias the loss towards tasks that behave as inputs to others. A dynamic loss scheme can be used to address this. In a dynamic loss scheme, losses can be normalized to be a 0:1 range based upon loss function complexity, where the loss functions are further weighted by training importance. Early in the training input functions (i.e., semantic segmentation and ID here) can be prioritized by increasing a weight value applied to the loss function. Once their validation accuracy enhances the joint loss function can be weighted towards hard tasks (i.e., anti-spoofing) and then easy tasks such as skin tone based upon further enhancements in validation accuracy. Determining a joint loss function as a function of loss method, task complexity and fusion approach can enhance training of a DNN **700** by increasing the rate at which the training converges on a set of DNN **700** weights that provide minimal joint loss functions over the training dataset. Fusion approach means the manner in which outputs from one task are used as inputs to another task. Increasing the rate at which the training converges decreases the time and computing resources required to train a DNN **700**.

(52) In an example of a DNN **700** that performs biometric task analysis, the DNN **700** can be simplified to enhance training and inference by removing soft target map neural network **714** and first estimate segmentation neural network **716**. Output from landmark mesh neural network **710** can be input to SoftMax function **712** and output directly to expert pooling neural network **730** (dotted line). Landmark mesh neural network **710** can provide facial feature data for segmentation task prediction **732** without requiring soft target map neural network **714** and first estimate segmentation neural network **716**. Configuring DNN **700** to add a connection from landmark mesh Softmax function **712** to expert pooling neural network **730** can reduce computing resources required to train and operate DNN **700**. DNN **700** can be trained and operated with and without soft target map neural network **714** and first estimate segmentation neural network **716** to determine whether segmentation task prediction **732** accuracy is maintained. In examples where segmentation task prediction **732** accuracy is maintained, DNN **700** can be enhanced by reducing computational resources required at inference time.

(53) FIG. **8** is a diagram of a DNN **800** for performing biometric analysis similarly to DNN **700** in FIG. **7**. DNN **800** includes the same components as DNN **700** in FIG. **7** configured in the same fashion except for memory **802** included between output from landmark mesh neural network **710**, SoftMax function **712**, and inputs to soft target estimate neural networks **718**, **720**. Memory **802** permits queuing of data from multiple frames of input image **702** data. A DNN **800** can input a sequence of frames of video data that includes a plurality of images **702** of a user's face acquired over a short time period, for example one second or less and determine temporal landmark mesh outputs. For example, the sequence of video frames can include motion of the user's eyes and/or mouth such as eye blinking or lip motions during speech.

(54) Storing temporal image data regarding motion of a user's eyes and mouth can permit DNN **800** to determine biometric analysis tasks such as emotion or head pose with greater accuracy and higher confidence than determining emotion or head pose based on a single static image. DNN **800** can process the temporal data by determining derivatives or calculating optical flow data on the landmark mesh images, for example. Expert pooling neural networks **722**, **724** can be configured to determine 3D convolutions by stacking the temporal image data in 3D stacks and using 3D convolution kernels to determine motion in the temporal image data. Memory **802** can be applied to facial features that can be expected to move during the short time sequence input to DNN **800**. For example, hair features and skin tones are typically not expected to change over a short time period and therefore would typically not benefit from temporal processing.

(55) A DNN **800** including memory **802** can be trained by video sequences of images **702** including facial feature motion and ground truth data describing the facial feature motion present in the video sequences. For example, video sequences of users blinking and/or speaking can be included in a training database. At training time, the images **702** of the video sequence can be input to DNN **800**. Memory **802** can store outputs from the landmark mesh neural network until the video segment ends or a limit on the number of frames of memory is reached. While the memory **802** is being filled, the loss functions based on the emotion detection **706** and head pose **708** biometric analysis neural networks can be set to zero and the weights for emotion detection **706** and head pose **708** biometric analysis neural networks can be frozen. When the video segment ends or the limit on frame storage is reached, the stored temporal data in the memories can be output to soft target estimate neural networks **718**, **720** for processing and subsequent output to expert pooling neural networks **722**, **724** to determine predictions to be used to output to computing device **115** at inference time and to determine loss functions at training time.

(56) FIG. **9** is a flowchart, described in relation to FIGS. **1-4** of a process **900** for training a DNN **400** including a common feature extraction CNN **410**, a plurality of biometric analysis task neural networks **412**, **414**, **416**, **418**, **420** and a segmentation neural network **422**. Process **900** can be implemented by a processor of a computing device **115** or server computer **120**, taking as input image data from sensors **116**, **122**, executing commands, and outputting biometric analysis task

predictions. A DNN **400** is typically executed on a server computer **120** on a traffic infrastructure node **105** at training time and transmitted to a computing device **115** in a vehicle **110** for operation at inference time. Process **900** includes multiple blocks that can be executed in the illustrated order. Process **900** could alternatively or additionally include fewer blocks or can include the blocks executed in different orders.

(57) Process **900** begins at block **902**, where an image **402** is acquired from a training dataset. Image **402** includes ground truth for one or more biometric analysis tasks as discussed above in relation to FIG. **3**. In examples where ground truth is not available for one or more biometric analysis tasks, the output from the one or more biometric analysis task neural networks **412**, **414**, **416**, **418**, **420** or the segmentation neural network **422** can be set to a null value and the weights for the one or more biometric analysis task neural networks **412**, **414**, **416**, **418**, **420** or the segmentation neural network **422** can be frozen. Freezing a neural network prevents the weights that program the neural network from being updated based on backpropagating a joint loss function as described below with respect to a block **912**, the loss function being determined at block **910** as also described below.

(58) At block **904** the image **402** is input to a common feature extraction CNN **410** to determine facial features to be output as latent variables as discussed in relation to FIG. **4**, above.

(59) At block **906** the latent variables are input to a plurality of biometric analysis task neural networks **412**, **414**, **416**, **418**, **420** or the segmentation neural network **422** which process the latent variables to determine predictions regarding the input image **402** as discussed above in relation to FIG. **4**. At inference time the predictions can be output to a computing device **115** to be used to operate a vehicle **110**.

(60) At block **908**, the predictions output from biometric analysis task neural networks **412**, **414**, **416**, **418**, **420** are input to SoftMax functions **424**, **426**, **428**, **430**, **432** to condition the output predictions to be between 0 and 1. Conditioning the output predictions permits the output predictions to be combined at block **910** into a joint loss function without one or more of the output predictions numerically dominating the calculations.

(61) At block **910** the output from the SoftMax functions **424**, **426**, **428**, **430**, **432** and the segmentation neural network **422** are combined with ground truth to determine a joint loss function for the DNN **400** in response to an input image **402**.

(62) At block **912** the joint loss function can be backpropagated through the layers of the DNN **400** to determine optimal weights for the layers of the DNN **400**. Optimal weights are the weights that result in outputs that most closely match the ground truth included in the training dataset. As discussed above in relation to FIG. **4**, training DNN **400** includes inputting an input image **402** a plurality of times while varying the weights that program the layers of the DNN **400**. Training the DNN **400** includes selecting weights for the layers of DNN **400** that provide the lowest joint loss function for the greatest number of input images **402** in the training dataset. The selected weights are the output resulting from a successful training process **900**. Following block **912** process **900** ends.

(63) FIG. **10** is a flowchart, described in relation to FIGS. **1-9**, of a process **1000** for training a DNN **700**, **800** including a common feature extraction CNN **704**, emotion detection **706** and head pose **708** biometric analysis task neural networks, a first estimate segmentation neural network **716** and a landmark mesh neural network **710**. Process **1000** can be implemented by a processor of a computing device **115** or server computer **120**, taking as input image data from sensors **116**, **122**, executing commands, and outputting biometric analysis task predictions. A DNN **700**, **800** is typically executed on a server computer **120** on a traffic infrastructure node **105** at training time and transmitted to a computing device **115** in a vehicle **110** for operation at inference time. Process **1000** could alternatively or additionally include fewer blocks or can include the blocks executed in different orders.

(64) Process **1000** begins at block **1002**, where an image **702** is acquired from a training dataset.

Image **702** includes ground truth for one or more biometric analysis tasks as discussed above in relation to FIGS. **7** and **8**. In examples where ground truth is not available for one or more biometric analysis tasks, the output from the one or more biometric analysis tasks can be set to a null value and the weights for the one or more biometric analysis tasks can be frozen to prevent them from being updated based on a joint loss function determined based on the outputs from the biometric analysis tasks.

(65) At block **1004** the image **702** is input to a common feature extraction CNN **704** to determine facial features to be output as latent variables as discussed in relation to FIGS. **7** and **8**, above.

(66) At block **1006** the latent variables are input to emotion detection **706** and head pose **708** biometric analysis task neural networks and a first estimate segmentation neural network **716** which process the latent variables to determine first predictions regarding the biometric analysis tasks and facial feature segmentation tasks. Latent variables are also input to landmark mesh neural network **710** which determines facial feature landmarks. Landmark mesh output is input to a SoftMax function **712**. In DNN **800**, output from landmark mesh SoftMax function **712** is input to a memory **802**, where output from a plurality of input images **702** can be stored and output as a stack of landmark mesh outputs.

(67) At block **1008** the output from the landmark mesh SoftMax function **712** is combined with latent variables from common feature extraction CNN **704** determine a soft target map neural network **714** where the landmark mesh is processed to form an output landmark mesh image. Output from the landmark mesh SoftMax function **712** is also input to soft target estimate neural networks **718**, **720** to determine facial feature polygons. In DNN **800** a stack of landmark mesh outputs is input to soft target estimate neural networks to form a stack of soft target estimate polygons.

(68) At block **1010** the soft target estimate polygons output from soft target estimate neural networks **718**, **720** are combined with output from emotion detection and head pose expert pooling neural networks **722**, **724**, respectively to determine predictions regarding emotion detection and head pose,

(69) At block **1012** the outputs from soft target map neural network **714**, latent variables output from common feature extraction CNN **704** and first estimate segmentation neural network **716** are input to expert pooling neural network **730** to determine a segmentation task prediction **732**. At inference time segmentation task prediction **732** can be output to computing device **115** to be combined with other outputs to perform biometric identification, for example.

(70) At block **1014**, at training time, predictions output from expert pooling neural networks **722**, **724** are input to SoftMax functions **726**, **728**, respectively. Softmax functions condition the output predictions to be between 0 and 1.

(71) At block **1016** the outputs from the SoftMax functions **726**, **728** and segmentation task prediction **732** are combined with ground truth to determine loss functions which are then combined with to yield a joint loss function. The individual loss functions can be summed to form a joint loss function, for example.

(72) At block **1018** the joint loss function can be backpropagated through the layers of the DNN **700**, **800** to determine optimal weights for the layers of the DNN **700**. Optimal weights are the selected weights that result in outputs that most closely match the ground truth included in the training dataset. The selected weights are the output resulting from a successful training process **1000**. Following block **1018** process **1000** ends.

(73) FIG. **11** is a flowchart, described in relation to FIGS. **1-7**, of a process **1100** for operating a vehicle based at least in part on biometric tasks. The process **1100** includes performing emotion detection and head pose biometric analysis tasks and image segmentation with a DNN **700** including a common feature extraction CNN **410**, a head pose **708** biometric analysis task neural network for determining a head pose prediction, an emotion detection **706** biometric analysis neural network and segmentation task prediction **732** for an image segmentation prediction. Process **1100**

can be implemented by a processor of a computing device **115** or server computer **120**, taking as input image data from sensors **116**, **122**, executing commands, and outputting biometric analysis task predictions. Process **1100** could alternatively or additionally include fewer blocks or can include the blocks executed in different orders.

(74) Following training a DNN **700** as discussed above in relation to FIG. 7, the trained DNN **700** can be transmitted to a computing device **115** in a device such as a vehicle **110** for inference. As discussed above in relation to FIG. 7, DNN **700** can be trained with emotion detection **706** and head pose **708** biometric analysis task neural networks landmark mesh neural network **710**. At inference time, the DNN **700** can be reduced to only include biometric analysis task neural networks that pertain to a specific task or tasks. In this example, the DNN **700** will be used for head pose detection and will include head pose **708** biometric analysis task neural network and landmark mesh neural network **710**. Reconfiguring the DNN **700** in this fashion permits training the DNN **700** with a large and varied training dataset that includes training images and ground truth for a plurality of biometric analysis tasks, while providing a lightweight DNN **700** that saves computer resources including memory space and execution time at inference time.

(75) Process **1100** begins at block **1102** where the vehicle **110** acquires an image **702** using a sensor **116** included in the vehicle **110**. Process **1100** could also be implemented in a security system, a robot guidance system, or a handheld device such as a cell phone that seeks to determine the identity of a potential user before granting access to a device.

(76) At block **1104** the computing device **115** inputs the image **702** to the common feature extraction CNN **410** to determine facial features to output as latent variables.

(77) At block **1106** the latent variables are input to head pose **708** neural network and landmark mesh neural network **710** to determine predictions regarding the head pose of the user imaged in input image **702**.

(78) At block **1108** the prediction regarding head pose is output from DNN **700** to the computing device **115** in the vehicle **110**.

(79) At block **1110** the computing device **115** determines a head pose score for the user in the image **702**. Computing device **115** can determine a probability that the head pose prediction output by DNN **700** is within tolerance for operation of the vehicle **110**, i.e., is the user asleep or otherwise not paying attention to the task.

(80) At block **1112** the computing device **115** tests the head pose score from block **1110**. If the head pose score is greater than a user-specified threshold, the user is authenticated and process **1100** passes to block **1114**. The threshold can be determined by processing a plurality of input images **702** that include head poses that are determined by users to be acceptable and head poses that are determined by users to be unacceptable. Distributions of head pose scores for acceptable and unacceptable head poses can be determined and a threshold that separates the two distributions can be determined. If the head pose score is lower than the user-specified threshold the user fails authentication and process **1100** branches to block **1116**.

(81) At block **1114** the user has passed head pose and the user is granted permission to operate the vehicle **110**. This can include unlocking doors to permit entry to the vehicle **110** and turning on the vehicle **110** controls to permit the user to operate the vehicle **110**, granting the user permission to operate various vehicle components, such as climate control, infotainment, etc., to name a few examples. Following block **1114** process **1100** ends.

(82) At block **1116** the user has failed head pose authentication and permission to operate the vehicle can be revoked. This can result in an alert being sounded or the vehicle stopping, for example. Following block **1116** the process **1100** ends.

(83) Computing devices such as those discussed herein generally each includes commands executable by one or more computing devices such as those identified above, and for carrying out blocks or steps of processes described above. For example, process blocks discussed above may be embodied as computer-executable commands.

(84) Computer-executable commands may be compiled or interpreted from computer programs created using a variety of programming languages and/or technologies, including, without limitation, and either alone or in combination, Java™, C, C++, Python, *Julia*, SCALA, Visual Basic, Java Script, Perl, HTML, etc. In general, a processor (i.e., a microprocessor) receives commands, i.e., from a memory, a computer-readable medium, etc., and executes these commands, thereby performing one or more processes, including one or more of the processes described herein. Such commands and other data may be stored in files and transmitted using a variety of computer-readable media. A file in a computing device is generally a collection of data stored on a computer readable medium, such as a storage medium, a random access memory, etc.

(85) A computer-readable medium (also referred to as a processor-readable medium) includes any non-transitory (i.e., tangible) medium that participates in providing data (i.e., instructions) that may be read by a computer (i.e., by a processor of a computer). Such a medium may take many forms, including, but not limited to, non-volatile media and volatile media. Instructions may be transmitted by one or more transmission media, including fiber optics, wires, wireless communication, including the internals that comprise a system bus coupled to a processor of a computer. Common forms of computer-readable media include, for example, RAM, a PROM, an EPROM, a FLASH-EEPROM, any other memory chip or cartridge, or any other medium from which a computer can read.

(86) All terms used in the claims are intended to be given their plain and ordinary meanings as understood by those skilled in the art unless an explicit indication to the contrary is made herein. In particular, use of the singular articles such as “a,” “the,” “said,” etc. should be read to recite one or more of the indicated elements unless a claim recites an explicit limitation to the contrary.

(87) The term “exemplary” is used herein in the sense of signifying an example, i.e., a reference to an “exemplary widget” should be read as simply referring to an example of a widget.

(88) The adverb “approximately” modifying a value or result means that a shape, structure, measurement, value, determination, calculation, etc. may deviate from an exactly described geometry, distance, measurement, value, determination, calculation, etc., because of imperfections in materials, machining, manufacturing, sensor measurements, computations, processing time, communications time, etc.

(89) In the drawings, the same reference numbers indicate the same elements. Further, some or all of these elements could be changed. With regard to the media, processes, systems, methods, etc. described herein, it should be understood that, although the steps or blocks of such processes, etc. have been described as occurring according to a certain ordered sequence, such processes could be practiced with the described steps performed in an order other than the order described herein. It further should be understood that certain steps could be performed simultaneously, that other steps could be added, or that certain steps described herein could be omitted. In other words, the descriptions of processes herein are provided for the purpose of illustrating certain embodiments, and should in no way be construed so as to limit the claimed invention.

Claims

1. A system, comprising: a computer that includes a processor and a memory, the memory including instructions executable by the processor to provide output from a selected biometric analysis task that is one of a plurality of biometric analysis tasks, based on an image provided from an image sensor; wherein the selected biometric analysis task is performed in a deep neural network that includes a common feature extraction neural network, a plurality of biometric task-specific neural networks, a segmentation neural network, a landmark mesh neural network, a plurality of soft target segmentation neural networks, and a plurality of expert pooling neural networks that perform the plurality of biometric analysis tasks by: inputting the image to the common feature extraction network to determine latent variables; inputting the latent variables to

the plurality of biometric task-specific neural networks including emotion detection and head pose to determine a plurality of first biometric analysis task outputs; inputting the latent variables to a landmark mesh neural network to determine a landmark mesh that includes polygons based on landmark locations that indicate features of a human face; inputting the landmark mesh and the first biometric task outputs to a plurality of expert pooling neural networks to determine a plurality of second biometric task outputs; and training the deep neural network by: determining one or more first loss functions based on the plurality of second biometric task outputs; combining the first loss functions to determine a joint loss function that gives more weight to loss functions for biometric tasks that include larger training datasets than biometric tasks that include smaller training datasets; and backpropagating the one or more first loss function and the joint loss function back through the deep neural network.

2. The system of claim 1, the instructions including further instructions to perform the plurality of biometric tasks by: inputting the latent variables to the segmentation neural network to determine a first estimate segmentation map; inputting the landmark mesh to the plurality of soft target segmentation neural networks to determine a plurality of soft target estimates; and inputting the first estimate segmentation map and the plurality of soft target estimates to an expert pooling neural network to determine a segmentation prediction.

3. The system of claim 1, wherein the output from the landmark mesh neural network is stored in a memory and processed to determine temporal data regarding one or more image segments.

4. The system of claim 1, further comprising a device, wherein the instructions include instructions to operate the device based on the output from the deep neural network according to the selected biometric analysis task.

5. The system of claim 1, wherein the biometric analysis tasks include biometric identification, liveness, and facial segmentation.

6. The system of claim 1, wherein the common feature extraction neural network includes a plurality of convolutional layers.

7. The system of claim 1, wherein the plurality of task-specific neural networks includes a plurality of fully connected layers.

8. The system of claim 1, wherein the segmentation neural network, the landmark mesh neural network, and the plurality of expert pooling neural networks include a plurality of fully connected layers.

9. The system of claim 1, wherein the outputs from the plurality of task-specific neural networks are input to a Softmax function before being combined with the outputs from the common feature extraction neural network.

10. The system of claim 1, wherein the outputs from the common feature extraction neural network are combined with the soft target estimates using expert pooling.

11. The system of claim 1, wherein output from the expert pooling are input to a Softmax function before being combined to determine the first loss functions.

12. The system of claim 1, wherein one or more outputs from the plurality of task-specific neural networks are set to zero during training.

13. A method, comprising: providing output from a selected biometric analysis task that is one of a plurality of biometric analysis tasks, based on an image provided from an image sensor; wherein the selected biometric analysis task is performed in a deep neural network that includes a common feature extraction neural network, a plurality of biometric task-specific neural networks, a segmentation neural network, a landmark mesh neural network, a plurality of soft target segmentation neural networks, and a plurality of expert pooling neural networks that perform the plurality of biometric analysis tasks by: inputting the image to the common feature extraction network to determine latent variables; inputting the latent variables to the plurality of biometric task-specific neural networks including emotion detection and head pose to determine a plurality of first biometric analysis task outputs; inputting the latent variables to a landmark mesh neural

network to determine a landmark mesh that includes polygons based on landmark locations that indicate features of a human face; inputting the landmark mesh and the first biometric task outputs to a plurality of expert pooling neural networks to determine a plurality of second biometric task outputs; training the deep neural network by: determining one or more first loss functions based on the plurality of second biometric task outputs; combining the first loss functions to determine a joint loss function that gives more weight to loss functions for biometric tasks that include larger training datasets than biometric tasks that include smaller training datasets; and backpropagating the one or more first loss function and the joint loss function back through the deep neural network.

14. The method of claim 13, further comprising: inputting the latent variables to the segmentation neural network to determine a first estimate segmentation map; inputting the landmark mesh to the plurality of soft target segmentation neural networks to determine a plurality of soft target estimates; and inputting the first estimate segmentation map and the plurality of soft target estimates to an expert pooling neural network to determine a segmentation prediction.

15. The method of claim 13, wherein the output from the landmark mesh neural network is stored in a memory and processed to determine temporal data regarding one or more image segments.

16. The method of claim 13, further comprising a device, wherein the device is operated based on the output from the deep neural network according to the selected biometric analysis task.

17. The method of claim 13, wherein the biometric analysis tasks include biometric identification, liveliness, and facial segmentation.

18. The method of claim 13, wherein the common feature extraction neural network includes a plurality of convolutional layers.

19. The method of claim 13, wherein the plurality of task-specific neural networks includes a plurality of fully connected layers.

20. The method of claim 13, wherein the segmentation neural network, the landmark mesh neural network, and the plurality of expert pooling neural networks include a plurality of fully connected layers.
