

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407768
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Dong; Shaohong et al.

Foldable mechanism and foldable terminal

Abstract

A foldable mechanism and a foldable terminal are provided. The foldable mechanism includes a base, a pressing plate assembly, and a flexible support plate, where the pressing plate assembly is mounted on the base, and the flexible support plate is mounted on the pressing plate assembly. The pressing plate assembly includes a first pressing plate swing arm, and a rotating portion of the first pressing plate swing arm is rotatably connected to the base, to implement a rotatable connection between the first pressing plate swing arm and the base. The flexible support plate is mounted on the first pressing plate swing arm and may bend under driving of the first pressing plate swing arm, and a bending direction of the flexible support plate is parallel to a rotation center of the first pressing plate swing arm relative to the base.

Inventors:	Dong; Shaohong (Shenzhen, CN), Chen; Guimin (Shenzhen, CN), Chen; Ruihao (Shenzhen, CN), Jin; Kaifang (Shenzhen, CN), Dong; Changfu (Shenzhen, CN)
Applicant:	Honor Device Co., Ltd. (Shenzhen, CN)
Family ID:	87748056
Assignee:	HONOR DEVICE CO., LTD. (Shenzhen, CN)
Appl. No.:	18/029474
Filed (or PCT Filed):	December 29, 2022
PCT No.:	PCT/CN2022/143394
PCT Pub. No.:	WO2023/185167
PCT Pub. Date:	October 05, 2023

Prior Publication Data

Document Identifier	Publication Date
----------------------------	-------------------------

Foreign Application Priority Data

CN

202210334431.6

Mar. 31, 2022

Publication Classification**Int. Cl.:** G06F1/16 (20060101); H04M1/02 (20060101)**U.S. Cl.:**

CPC H04M1/022 (20130101); G06F1/1616 (20130101); G06F1/1681 (20130101);

Field of Classification Search**USPC:** None

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11336759	12/2021	Liao et al.	N/A	N/A
11917780	12/2023	Caplow-Munro	N/A	H05K 5/0226
11953949	12/2023	An	N/A	H05K 5/0226
12007808	12/2023	Park	N/A	G06F 1/1618
12133344	12/2023	Chang	N/A	F16C 11/04
2019/0278338	12/2018	Siddiqui	N/A	G06F 1/1656
2021/0368032	12/2020	Liao et al.	N/A	N/A
2022/0104370	12/2021	Wu	N/A	H05K 5/0017
2022/0303371	12/2021	Liao	N/A	H04M 1/0268
2023/0164253	12/2022	Xu et al.	N/A	N/A
2023/0403347	12/2022	Liu	N/A	H04M 1/022
2024/0004430	12/2023	Zhao et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
111698355	12/2019	CN	N/A
112449036	12/2020	CN	N/A
113067923	12/2020	CN	N/A
113067924	12/2020	CN	N/A
113194183	12/2020	CN	N/A
113315860	12/2020	CN	N/A
113763814	12/2020	CN	N/A
113833741	12/2020	CN	N/A
113795683	12/2021	CN	N/A
2021129882	12/2020	WO	N/A

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is a national stage of International Application No. PCT/CN2022/143394 filed on Dec. 29, 2022, which claims priority to Chinese Patent Application No. 202210334431.6 filed on Mar. 31, 2022. The disclosures of both of the aforementioned applications are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

(2) This application relates to the field of foldable terminals, and in particular, to a foldable mechanism and a foldable terminal.

BACKGROUND

(3) With the development of science and technology, the era of a large-screen intelligent terminal is approaching, and a foldable terminal is favored by a user because of advantages such as a large screen and easy-to-carry. Currently, a foldable terminal usually implements folding and unfolding by using a foldable mechanism. However, an existing foldable mechanism usually requires a large amount of components to implement folding and unfolding, leading to a complex structure of the foldable mechanism, which is not conducive to a lightweight design of the foldable terminal.

SUMMARY

(4) This application provides a foldable mechanism and a foldable terminal, which can simplify a structure of the foldable mechanism, thereby implementing a lightweight design of the foldable terminal.

(5) According to a first aspect, this application provides a foldable mechanism, including a base, a pressing plate assembly, and a flexible support plate, where the pressing plate assembly is mounted on the base, and the flexible support plate is mounted on the pressing plate assembly. The pressing plate assembly includes a first pressing plate swing arm, and a rotating portion of the first pressing plate swing arm is rotatably connected to the base, to implement a rotatable connection between the first pressing plate swing arm and the base. The flexible support plate is mounted on the first pressing plate swing arm and may bend under driving of the first pressing plate swing arm, and a bending direction of the flexible support plate is parallel to a rotation center of the first pressing plate swing arm relative to the base.

(6) In the foldable mechanism shown in this application, the flexible support plate is directly mounted on the first pressing plate swing arm without requiring a spring to mount the flexible support plate on the base, so that a quantity of components of the foldable mechanism is simplified. In this way, an assembly process of the foldable mechanism is simplified, which is conducive to improve the assembly precision of the foldable mechanism, and a structure of the foldable mechanism is simplified, so that the structure of the foldable mechanism is simple. In a case that the foldable mechanism is applied to a foldable terminal, a lightweight design of the foldable terminal can be implemented. In addition, a partial thickness of the flexible support plate can be very thin, which is further conducive to implement a light and thin design of the foldable mechanism.

(7) In an implementation, there are four first pressing plate swing arms, and the four first pressing plate swing arms are arranged at intervals, to ensure the assembly stability between the pressing plate assembly and the base.

(8) In an implementation, the rotating portion of the first pressing plate swing arm is slidably and

rotatably connected to the base, to implement a slidable and rotatable connection between the first pressing plate swing arm and the base. In a case that the first pressing plate swing arm rotates relative to the base, the first pressing plate swing arm generates a relative displacement with the base, and the displacement generated by the first pressing plate swing arm matches a size change generated due to bending of the flexible support plate, thereby ensuring a flat flexible support plate and preventing the flexible support plate from generating wrinkles.

(9) In an implementation, the pressing plate assembly of the foldable mechanism further includes a second pressing plate swing arm, and a rotating portion of the second pressing plate swing arm is rotatably connected to the base, to implement a rotatable connection between the second pressing plate swing arm and the base. The flexible support plate is further mounted on the second pressing plate swing arm and bends under driving of the second pressing plate swing arm, so that the bending direction of the flexible support plate is further parallel to a rotation center of the second pressing plate swing arm relative to the base.

(10) In the foldable mechanism shown in this application, the flexible support plate is directly mounted on the first pressing plate swing arm and the second pressing plate swing arm without requiring a spring to mount the flexible support plate on the base, so that a quantity of components of the foldable mechanism is simplified. In this way, an assembly process of the foldable mechanism is simplified, which is conducive to improve the assembly precision of the foldable mechanism, and a structure of the foldable mechanism is simplified, so that the structure of the foldable mechanism is simple. In a case that the foldable mechanism is applied to a foldable terminal, a lightweight design of the foldable terminal can be implemented.

(11) In an implementation, there are four second pressing plate swing arms, and the four second pressing plate swing arms are arranged at intervals, to ensure the assembly stability between the pressing plate assembly and the base.

(12) In an implementation, the rotating portion of the second pressing plate swing arm is slidably and rotatably connected to the base, to implement a slidable and rotatable connection between the second pressing plate swing arm and the base. In a case that the second pressing plate swing arm rotates relative to the base, the second pressing plate swing arm generates a displacement with the base, and the displacement generated by the second pressing plate swing arm matches a size change generated due to bending of the flexible support plate, thereby ensuring a flat flexible support plate and preventing the flexible support plate from generating wrinkles.

(13) In an implementation, a connection portion of the first pressing plate swing arm is provided with an assembly hole. A connection portion of the second pressing plate swing arm is provided with an assembly hole. The flexible support plate includes a flexible support portion, a first fixing portion, and a second fixing portion. The flexible support portion is provided with a plurality of strip-shaped grooves, and the plurality of strip-shaped grooves are parallel to each other and arranged at intervals. An extending direction of each of the strip-shaped grooves is parallel to the bending direction of the flexible support plate, to ensure the flexibility of the flexible support plate. The first fixing portion and the second fixing portion are both fixedly connected to a bottom surface of the flexible support portion, the first fixing portion is mounted in the assembly hole of the first pressing plate swing arm, and the second fixing portion is mounted in the assembly hole of the second pressing plate swing arm, to implement assembly between the flexible support plate and the pressing plate assembly.

(14) In an implementation, openings of the plurality of strip-shaped grooves are all located on a bottom surface of the flexible support plate, to ensure the integrity of a top surface of the flexible support plate. Each of the strip-shaped groove is recessed from the bottom surface of the flexible support plate in a direction away from the top surface, and runs through a front end surface and a rear end surface of the flexible support plate. The strip-shaped grooves are disposed at intervals with both the first fixing portion and the second fixing portion.

(15) In an implementation, the pressing plate assembly of the foldable mechanism further includes

a first pressing plate and a second pressing plate. The first pressing plate is slidably connected to a sliding portion of the first pressing plate swing arm, to implement a slidable connection between the first pressing plate and the first pressing plate swing arm. The second pressing plate is slidably connected to a sliding portion of the second pressing plate swing arm, to implement a slidable connection between the second pressing plate and the second pressing plate swing arm.

(16) In a case that the foldable mechanism is in a flattened state, the first pressing plate and the second pressing plate are respectively located on two opposite sides of the base, and a top surface of the first pressing plate and a top surface of the second pressing plate are flush with a top surface of the flexible support plate and jointly form a support surface.

(17) In a case that the foldable mechanism is applied to a foldable terminal, the support surface can support a foldable part of a display screen. Therefore, a good display effect of the display screen can be ensured, and in a case that the foldable part is touched, the foldable part is not easily damaged or recessed due to touching of an external force, thereby improving the use reliability of the display screen. In addition, the flexible support plate is not provided with an opening. Therefore, the top surface of the flexible support plate is a complete flat surface, and an area of the support surface is relatively large, so that the foldable part can be better supported, thereby improving a support effect of the flexible support plate to the foldable part.

(18) In an implementation, the foldable mechanism further includes a connection assembly, and the connection assembly is mounted on the base. The connection assembly includes a first fixing frame and a second fixing frame. The first fixing frame is slidably and rotatably connected to the first pressing plate. The second fixing frame is slidably and rotatably connected to the second pressing plate.

(19) In a case that the foldable mechanism is in a folded state, the first fixing frame, the second fixing frame, the first pressing plate, the second pressing plate, and the flexible support plate enclose to form an avoidance space, and the avoidance space is in a droplet shape.

(20) In a case that the foldable mechanism is applied to a foldable terminal, the avoidance space may avoid an R angle formed when the foldable part bends, so that the foldable part does not bend at a relatively large angle, thereby avoiding a poor phenomenon such as a crease in the display screen, and helping prolong a service life of the display screen.

(21) In an implementation, the base is provided with an avoidance groove. In a case that the foldable mechanism is in a folded state, the avoidance groove is configured to avoid a bottom portion of the flexible support plate, thereby preventing interference generated between the base and the flexible support plate and helping form the avoidance space in the droplet shape.

(22) In an implementation, the connection assembly further includes a first primary swing arm and a second primary swing arm. A rotating portion of the first primary swing arm is rotatably connected to the first fixing frame, to implement a rotatable connection between the first primary swing arm and the first fixing frame. A sliding portion of the first primary swing arm is slidably and rotatably connected to the base, to implement a slidable and rotatable connection between the first primary swing arm and the base. A rotating portion of the second primary swing arm is rotatably connected to the second fixing frame, to implement a rotatable connection between the second primary swing arm and the second fixing frame. A sliding portion of the second primary swing arm is slidably and rotatably connected to the base, to implement a slidable and rotatable connection between the second primary swing arm and the base.

(23) In an implementation, the flexible support portion is further provided with a first avoidance groove and a second avoidance groove, and openings of the first avoidance groove and the second avoidance groove are both located on the bottom surface of the flexible support portion.

(24) In a case that the foldable mechanism is in a flattened state, the first avoidance groove is configured to avoid the sliding portion of the first primary swing arm, and the second avoidance groove is configured to avoid the sliding portion of the second primary swing arm, to prevent interference generated between the first primary swing arm and the second primary swing arm with

the flexible support plate. Therefore, the flexible support portion may not be abutted against by the first primary swing arm and the second primary swing arm and protrude out relative to the top surface of the first pressing plate and the top surface of the second pressing plate, thereby ensuring that the top surface of the flexible support plate is flush with the top surface of the first pressing plate and the top surface of the second pressing plate.

(25) The first avoidance groove and the second avoidance groove are both in communication with one or more strip-shaped grooves.

(26) In an implementation, the connection assembly of the foldable mechanism further includes a first secondary swing arm and a second secondary swing arm. A sliding portion of the first secondary swing arm is slidably connected to the first fixing frame, to implement a slidable connection between the first secondary swing arm and the first fixing frame. A rotating portion of the first secondary swing arm is rotatably connected to the base, to implement a rotatable connection between the first secondary swing arm and the base. A sliding portion of the second secondary swing arm is slidably connected to the second fixing frame, to implement a slidable connection between the second secondary swing arm and the second fixing frame. A rotating portion of the second secondary swing arm is rotatably connected to the base, to implement a rotatable connection between the second secondary swing arm and the base.

(27) In an implementation, the flexible support portion is further provided with a third avoidance groove and a fourth avoidance groove, and openings of the third avoidance groove and the fourth avoidance groove are both located on the bottom surface of the flexible support portion. In a case that the foldable mechanism is in a flattened state, the third avoidance groove is configured to avoid the rotating portion of the first secondary swing arm, and the fourth avoidance groove is configured to avoid the rotating portion of the second secondary swing arm, to prevent interference generated between the first secondary swing arm and the second secondary swing arm with the flexible support plate. Therefore, the flexible support portion may not be abutted against by the first secondary swing arm and the second secondary swing arm and protrude out relative to the top surface of the first pressing plate and the top surface of the second pressing plate, thereby ensuring that the top surface of the flexible support plate is flush with the top surface of the first pressing plate and the top surface of the second pressing plate.

(28) The third avoidance groove and the fourth avoidance groove are both in communication with one or more strip-shaped grooves.

(29) In an implementation, the foldable mechanism further includes a damping assembly, and the damping assembly is mounted on the connection assembly. In a process that the connection assembly is folded or unfolded relative to the base, the damping assembly may provide a damping force.

(30) The damping assembly includes a first damping member and a second damping member. The first damping member is mounted on the first fixing frame, is fixedly connected to the first secondary swing arm, and may slide relative to the first fixing frame under driving of the first secondary swing arm. The second damping member is mounted on the second fixing frame, is fixedly connected to the second secondary swing arm, and may slide relative to the second fixing frame under driving of the second secondary swing arm.

(31) In a case that the foldable mechanism is applied to a foldable terminal, in a process that a user uses the foldable terminal, for example, when the foldable terminal is in a folded state or a flattened state and when the foldable terminal is switched between the folded state and the unfolded state, the user can apparently feel the damping force provided by the damping assembly, so that the user can experience a good hand feeling, and the use experience of the user is improved.

(32) In an implementation, the foldable mechanism further includes a synchronization assembly, and the synchronization assembly is mounted on the base and slidably connected to the connection assembly. The synchronization assembly is slidably connected to the first secondary swing arm and the second secondary swing arm, so that the first secondary swing arm and the second secondary

swing arm rotate synchronously relative to the base.

(33) In an implementation, the rotating portion of the first secondary swing arm is provided with a first spiral groove, and the rotating portion of the second secondary swing arm is provided with a second spiral groove.

(34) The synchronization assembly of the foldable mechanism includes a fixing column and a synchronization slider, the fixing column is mounted on the base, and the synchronization slider is slidably connected to the fixing column. A first cam of the synchronization slider is mounted in the first spiral groove, and may slide relative to the rotating portion of the first secondary swing arm in the first spiral groove. A second cam of the synchronization slider is mounted in the second spiral groove, and may slide relative to the rotating portion of the second secondary swing arm in the second spiral groove.

(35) When the first secondary swing arm rotates relative to the base, the first cam slides relative to the rotating portion of the first secondary swing arm in the first spiral groove, to drive the synchronization slider to slide relative to the fixing column, drive the second cam to slide relative to the rotating portion of the second secondary swing arm in the second spiral groove, and further drive the second secondary swing arm to rotate relative to the base, thereby implementing synchronous rotation between the first secondary swing arm and the second secondary swing arm.

(36) Similarly, when the second secondary swing arm rotates relative to the base, the synchronization assembly may drive the first secondary swing arm to rotate relative to the base, thereby implementing the synchronous rotation between the first secondary swing arm and the second secondary swing arm.

(37) In an implementation, the base is an integrally formed structural member, so that the overall strength of the base can be improved, and the structure stability of the base can be ensured.

Compared with an existing base structure, the base shown in this application does not need a fixing member such as a screw or a screw nail to implement assembly between a holder and a shaft cover. This is conducive to assembly of the foldable mechanism, the assembly precision of the base can be improved, and a quantity of components of the foldable mechanism is also simplified, which is conducive to implement a lightweight design of the foldable terminal.

(38) In an implementation, the base is provided with a first engagement groove, and the first engagement groove is an arc-shaped groove. The rotating portion of the first pressing plate swing arm is in a shape of an arc-shaped plate, and the rotating portion of the first pressing plate swing arm is mounted in the first engagement groove and slides and rotates relative to the base in the first sliding groove.

(39) Since the base is an integrally formed structural member, the first engagement groove does not need to be formed through engagement of the shaft cover and the holder. In the foldable mechanism, a sum of a thickness of the first engagement groove and a thickness of the rotating portion of the first pressing plate swing arm is relatively small, so that space occupied by the foldable mechanism can be reduced, which is conducive to implement a light and thin design of the foldable mechanism.

(40) In an implementation, the base is provided with a second engagement groove, the rotating portion of the second pressing plate swing arm is in a shape of an arc-shaped plate, and the rotating portion of the second pressing plate swing arm is mounted in the second engagement groove and slides and rotates in the second engagement groove.

(41) According to a second aspect, this application provides a foldable terminal, including a first housing, a second housing, and the foldable mechanism according to any one of the foregoing, where the foldable mechanism is connected between the first housing and the second housing.

(42) In the foldable mechanism used by the foldable terminal shown in this application, the flexible support plate is directly mounted on the first pressing plate swing arm without requiring a spring to mount the flexible support plate on the base, so that a quantity of components of the foldable mechanism is simplified. In this way, an assembly process of the foldable mechanism is simplified,

which is conducive to improve the assembly precision of the foldable mechanism, and a structure of the foldable mechanism is simplified, so that the structure of the foldable mechanism is simple, which is conducive to implement a lightweight design of the foldable terminal. In addition, a partial thickness of the flexible support plate can be very thin, which is further conducive to implement a light and thin design of the foldable terminal.

(43) In an implementation, the foldable terminal further includes a display screen, and the display screen includes a first display part, a second display part, and a foldable part, where the foldable part is connected between the first display part and the second display part. The first display part is mounted in the first housing, the second display part is mounted in the second housing, and the foldable part is disposed opposite to the foldable mechanism.

(44) In a case that the foldable terminal is in an unfolded state, the top surface of the flexible support plate supports the foldable part.

(45) The first pressing plate and the second pressing plate are respectively located on two opposite sides of the base, and the top surface of the first pressing plate and the top surface of the second pressing plate are flush with the top surface of the flexible support plate and jointly form a support surface to support the foldable part.

(46) The support surface can support the foldable part of the display screen. Therefore, a good display effect of the display screen can be ensured, and in a case that the foldable part is touched, the foldable part is not easily damaged or recessed due to touching of an external force, thereby improving the use reliability of the display screen. In addition, the flexible support plate is not provided with an opening. Therefore, the top surface of the flexible support plate is a complete flat surface, and an area of the support surface is relatively large, so that the foldable part can be better supported, thereby improving a support effect of the flexible support plate to the foldable part.

(47) In an implementation, in a case that the foldable terminal is in a folded state, the foldable part is received in the avoidance space of the foldable mechanism.

(48) The first fixing frame, the second fixing frame, the first pressing plate, the second pressing plate, and the flexible support plate enclose to form an avoidance space, and the avoidance space is in a droplet shape. The droplet-shaped avoidance space may avoid an R angle formed when the foldable part bends, so that the foldable part does not bend at a relatively large angle, thereby avoiding a poor phenomenon such as a crease in the display screen, and helping prolong a service life of the display screen.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) To describe the technical solutions in the embodiments of this application more clearly, the following describes the accompanying drawings required in the embodiments of this application.

(2) FIG. 1 is a schematic structural diagram of a foldable terminal in a state according to an embodiment of this application;

(3) FIG. 2 is a schematic structural diagram of the foldable terminal shown in FIG. 1 in a second state;

(4) FIG. 3 is a schematic exploded structural view of the foldable terminal shown in FIG. 2;

(5) FIG. 4 is a schematic exploded structural view of a foldable apparatus in the foldable terminal shown in FIG. 3;

(6) FIG. 5 is a schematic structural diagram of a foldable mechanism in the foldable apparatus shown in FIG. 4;

(7) FIG. 6 is a schematic exploded structural view of the foldable mechanism shown in FIG. 5;

(8) FIG. 7 is a schematic structural diagram of a base in the foldable mechanism shown in FIG. 6;

(9) FIG. 8 is a schematic structural diagram of a first part in the base shown in FIG. 7;

- (10) FIG. **9** is a schematic structural diagram of a second part in the base shown in FIG. **7**;
- (11) FIG. **10** is a schematic structural diagram of a third part in the base shown in FIG. **7**;
- (12) FIG. **11** is a schematic structural diagram of a first connection assembly, a first damping assembly, and a first synchronization assembly in the foldable mechanism shown in FIG. **6**;
- (13) FIG. **12** is a schematic structural diagram of the first connection assembly, the first damping assembly, and the first synchronization assembly shown in FIG. **11** from another perspective;
- (14) FIG. **13** is a schematic structural diagram of a second connection assembly, a second damping assembly, and a second synchronization assembly in the foldable mechanism shown in FIG. **6**;
- (15) FIG. **14** is a schematic structural diagram of the second connection assembly, the second damping assembly, and the second synchronization assembly shown in FIG. **13** from another perspective;
- (16) FIG. **15** is a schematic structural diagram of a third connection assembly in the foldable mechanism shown in FIG. **6**;
- (17) FIG. **16** is a schematic structural diagram of the third connection assembly shown in FIG. **15** from another perspective;
- (18) FIG. **17** is a schematic structural diagram of a pressing plate assembly in the foldable mechanism shown in FIG. **6**;
- (19) FIG. **18** is a schematic structural diagram of the pressing plate assembly shown in FIG. **17** from another perspective;
- (20) FIG. **19** is a schematic structural diagram of a support plate in the foldable mechanism shown in FIG. **6**;
- (21) FIG. **20** is a schematic structural diagram of the support plate shown in FIG. **19** from another perspective;
- (22) FIG. **21** is a schematic cross-sectional structural view of the foldable mechanism shown in FIG. **5** cut along I-I;
- (23) FIG. **22** is a schematic structural diagram of the foldable mechanism shown in FIG. **21** in a folded state;
- (24) FIG. **23** is a schematic partial cross-sectional structural diagram of the foldable terminal shown in FIG. **2**; and
- (25) FIG. **24** is a schematic structural diagram of the foldable terminal shown in FIG. **23** in a folded state.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

- (26) The following clearly and completely describes the technical solutions in the embodiments of this application with reference to the accompanying drawings in the embodiments of this application.
- (27) Refer to FIG. **1** and FIG. **2**, FIG. **1** is a schematic structural diagram of a foldable terminal **1000** in a state according to an embodiment of this application, and FIG. **2** is a schematic structural diagram of the foldable terminal **1000** shown in FIG. **1** in a second state.
- (28) The foldable terminal **1000** may be a foldable electronic product such as a mobile phone, a tablet computer, a personal computer, a multimedia player, an e-book reader, a notebook computer, a vehicle-mounted device, or a wearable device. In this embodiment, the foldable terminal **1000** is a foldable mobile phone. That is, the foldable terminal **1000** is a mobile phone that can be switched between a folded state and an unfolded state.
- (29) For ease of description, a length direction of the shown foldable terminal **1000** is defined as an X-axis direction, a length direction of the foldable terminal **1000** is defined as a Y-axis direction, and a thickness direction of the foldable terminal **1000** is defined as a Z-axis direction, where the X-axis direction, the Y-axis direction, and the Z-axis direction are perpendicular to each other.
- (30) It should be noted that, limitation words such as parallel and perpendicular that are about a relatively position relationship mentioned in the embodiments of this application are all said for a current processing level rather than absolute and strict definitions in mathematics, so that existence

of a slight deviation is also permitted, and approximately parallel and approximately perpendicular are also included. For example, A being parallel to B refers to that A is parallel to or approximately parallel to B, provided that an angle between A and B ranges from 0 degree to 10 degrees. For example, A being perpendicular to B refers to that A is perpendicular to or approximately perpendicular to B, provided that an angle between A and B ranges from 80 degrees to 100 degrees.

(31) In this embodiment, an extending direction of a rotation axis of the foldable terminal **1000** is the Y-axis direction. That is, the foldable terminal **1000** can be relatively unfolded or relatively folded around the Y-axis direction. The foldable terminal **1000** shown in FIG. 1 is in a folded state, a size of the foldable terminal **1000** in the X-axis direction is relatively small, and the foldable terminal **1000** is easy to carry. The foldable terminal **1000** shown in FIG. 2 is in an unfolded state, a size of the foldable terminal **1000** in the X-axis direction is relatively large, and the foldable terminal **1000** has a relatively large display area. For example, an unfolding angle α of the foldable terminal **1000** shown in FIG. 2 is 180 degrees. That is, the foldable terminal **1000** shown in FIG. 2 is in a flattened state.

(32) It should be noted that, a slight deviation is allowed for all angles described as examples in the embodiments of this application. For example, the unfolding angle α of the foldable terminal **1000** shown in FIG. 2 being 180 degrees refers to that α may be 180 degrees, or may be approximately 180 degrees, for example, 170 degrees, 175 degrees, 185 degrees, and 190 degrees. An angle for example described in the following may be used for same understanding.

(33) It should be understood that the foldable terminal **1000** shown in the embodiments of this application is a terminal that may be folded for one time. In some other embodiments, the foldable terminal **1000** may also be a terminal that may be folded for a plurality of times (more than twice). In this case, the foldable terminal **1000** may include a plurality of parts, two adjacent parts may be folded relatively close to each other to cause the foldable terminal **1000** to be in a folded state, and two adjacent parts may be also unfolded relatively far from each other to cause the foldable terminal **1000** to be in an unfolded state.

(34) Refer to FIG. 3, FIG. 3 is a schematic exploded structural view of the foldable terminal **1000** shown in FIG. 2.

(35) The foldable terminal **1000** includes a foldable apparatus **100** and a display screen **200**, and the display screen **200** is mounted in the foldable apparatus **100**. The display screen **200** includes a display surface (not marked in the figure) away from the foldable apparatus **100**, and the display surface is configured to display information such as text, an image, or a video. In this embodiment, the display screen **200** includes a first display part **210**, a second display part **220**, and a foldable part **230**, where the foldable part **230** is connected between the first display part **210** and the second display part **220**. The foldable part **230** may bend around the Y-axis direction.

(36) As shown in FIG. 1, when the foldable terminal **1000** is in a folded state, the first display part **210** and the second display part **220** are disposed opposite to each other, and the foldable part **230** bends. In this case, the display screen **200** is in a folded state, and an exposed area of the display screen **200** is relatively small, thereby greatly reducing a probability that the display screen **200** is damaged, and effectively protecting the display screen **200**. As shown in FIG. 2, when the foldable terminal **1000** is in an unfolded state, the first display part **210** and the second display part **220** are unfolded opposite to each other, and the foldable part **230** does not bend and is flattened. In this case, angles between the first display part **210**, the second display part **220**, and the foldable part **230** are all α , and the display screen **200** has a large display area, so as to implement large-screen display of the foldable terminal **1000** and improve the use experience of the user.

(37) It should be understood that, the foldable terminal **1000** shown in this embodiment of this application is folded inward, and the display screen **200** of the foldable terminal **1000** in the folded state is located on an inner side of the foldable apparatus **100**. In some other embodiments, the foldable terminal **1000** may also be folded outward. In this case, the display screen **200** of the foldable terminal **1000** in the folded state is located on an outer side of the foldable apparatus **100**.

(38) Refer to FIG. 4, FIG. 4 is a schematic exploded structural view of the foldable apparatus **100** in the foldable terminal **1000** shown in FIG. 3.

(39) In this embodiment, the foldable apparatus **100** includes a first housing **110**, a second housing **120**, and a foldable mechanism **130**. The foldable mechanism **130** is connected between the first housing **110** and the second housing **120**, so as to implement a rotatable connection between the first housing **110** and the second housing **120**. Specifically, the first housing **110** carries the first display part **210**, and the second housing **120** carries the second display part **220**. In other words, the first display part **210** is mounted in the first housing **110**, and the second display part **220** is mounted in the second housing **120**. The foldable mechanism **130** is disposed opposite to the foldable part **230**.

(40) The first housing **110** and the second housing **120** may rotate relative to each other through the foldable mechanism **130**, so that the foldable apparatus **100** is switched between a folded state and an unfolded state. Specifically, the first housing **110** and the second housing **120** may rotate relative to each other to be disposed opposite to each other, so that the foldable apparatus **100** is in a folded state, as shown in FIG. 1. In this case, the foldable mechanism **130** is in a folded state. The first housing **110** and the second housing **120** may also rotate relative to each other to be unfolded to each other, so that the foldable apparatus **100** is in an unfolded state, as shown in FIG. 2. In this case, the foldable mechanism **130** is in an unfolded state. For example, the foldable terminal **1000** shown in FIG. 2 is in a flattened state, and an angle between the first housing **110** and the second housing **120** is α . In this case, the foldable mechanism **130** is in a flattened state.

(41) The first housing **110** is provided with a first receiving groove **1101**, and the first receiving groove **1101** is located on a side of the first housing **110** facing the second housing **120**. An opening of the first receiving groove **1101** is located on a top surface of the first housing **110**. The first receiving groove **1101** is recessed in a direction from the top surface to a bottom surface of the first housing **110**, and runs through a right side surface of the first housing **110**.

(42) The second housing **120** and the first housing **110** have a same structure and are mirror-symmetrical with respect to the foldable mechanism **130**. The second housing **120** is provided with a second receiving groove **1201**, and the second receiving groove **1201** is located on a side of the second housing **120** facing the first housing **110**. An opening of the second receiving groove **1201** is located on a top surface of the second housing **120**. The second receiving groove **1201** is recessed in a direction from the top surface to a bottom surface of the second housing **120**, and runs through a side surface of the second housing **120** facing the first housing **110**.

(43) When the foldable apparatus **100** is in a flattened state, that is, when an angle between the first housing **110** and the second housing **120** is α , the first receiving groove **1101** and the second receiving groove **1201** enclose to form a receiving space **1301**. The foldable mechanism **130** is mounted in the receiving space **1301**. A part of the foldable mechanism **130** is mounted in the first receiving groove **1101** of the first housing **110**, and a part of the foldable mechanism **130** is mounted in the second receiving groove **1201** of the second housing **120**.

(44) It should be noted that, in this embodiment of this application, orientation words such as “top”, “bottom”, “left”, “right”, “front”, and “rear” that are used when the foldable terminal **1000** is described are mainly described according to a display orientation of the foldable terminal **1000** in FIG. 2, where a direction facing a Z-axis positive direction is “top”, a direction facing a Z-axis negative direction is “bottom”, a direction facing an X-axis positive direction is “right”, a direction facing an X-axis negative direction is “left”, a direction facing a Y-axis positive direction is “rear”, and a direction facing a Y-axis negative direction is “front”, which do not form a limitation on orientations of the foldable terminal **1000** in an actual application scenario.

(45) In an existing foldable mechanism, a screen is usually supported by using a floating plate, and the floating plate is usually mounted on the base by using springs. The floating plate goes down relative to the base under action of the springs and goes up relative to the base under action of swing arms, and a large amount of components are required in the foldable mechanism to drive the

floating plate to move relative to the base. As a result, assembly of the foldable mechanism is complex, and a problem of a poor assembly precision easily occurs, leading to a complex structure of the foldable mechanism, which is not conducive to a lightweight design of the foldable terminal. In addition, openings need to be provided on the floating plate to avoid the swing arms, to prevent interference generated between the floating plate and the swing arms. As a result, the screen cannot be completely supported, and dents may easily occur on the screen, affect the use experience of the user. The following describes a structure of the foldable mechanism **130** in the foldable terminal **1000** shown in this embodiment of this application.

(46) Refer to FIG. 5 and FIG. 6, FIG. 5 is a schematic structural diagram of a foldable mechanism **130** in the foldable apparatus **100** shown in FIG. 4, and FIG. 6 is a schematic exploded structural view of the foldable mechanism **130** shown in FIG. 5.

(47) The foldable mechanism **130** includes a base **10**, a connection assembly **20**, a damping assembly **30**, a pressing plate assembly **40**, and a flexible support plate **50**. The connection assembly **20** and the pressing plate assembly **40** are both mounted on the base **10**, and may be both folded or unfolded relative to the base **10**, so as to switch between a folded state and an unfolded state. The damping assembly **30** is mounted on the connection assembly **20** and may be folded or unfolded relative to the base **10** under driving of the connection assembly **20**, so as to switch between a folded state and an unfolded state. The flexible support plate **50** is mounted on the pressing plate assembly **40** and may be folded or unfolded under driving of the pressing plate assembly **40**, so as to switch between a folded state and an unfolded state. For example, the base **10** extends in the Y-axis direction.

(48) In this embodiment, there are three connection assemblies **20**, and the three connection assemblies **20** are arranged at intervals in the Y-axis direction. The three connection assemblies **20** are respectively a first connection assembly **20a**, a second connection assembly **20b**, and a third connection assembly **20c**, where the third connection assembly **20c** is located between the first connection assembly **20a** and the second connection assembly **20b**. The first connection assembly **20a** is located on a front side of the foldable mechanism **130**, the second connection assembly **20b** is located on a rear side of the foldable mechanism **130**, and the third connection assembly **20c** is located on a middle portion of the foldable mechanism **130**. In some other embodiments, there may be one, two, or at least four connection assemblies **20**, and a quantity of the connection assemblies **20** is not specifically limited in this application.

(49) The first connection assembly **20a** includes a first fixing frame **21a**, a second fixing frame **22a**, a first primary swing arm **23a**, a second primary swing arm **24a**, a first secondary swing arm **25a**, and a second secondary swing arm **26a**. The first primary swing arm **23a** is rotatably connected to the first fixing frame **21a** and is slidably and rotatably connected to the base **10**. The second primary swing arm **24a** is rotatably connected to the second fixing frame **22a** and is slidably and rotatably connected to the base **10a**. The first secondary swing arm **25a** is rotatably connected to the first fixing frame **21a** and is rotatably connected to the base **10**. The second secondary swing arm **26a** is slidably connected to the second fixing frame **22a** and is rotatably connected to the base **10**.

(50) When the first connection assembly **20a** is switched between the folded state and the unfolded state, a direction in which the first fixing frame **21a**, the first primary swing arm **23a**, and the first secondary swing arm **25a** rotate relative to the base **10** is a first direction, and a direction in which the second fixing frame **22a**, the second primary swing arm **24a**, and the second secondary swing arm **26a** rotate relative to the base **10** is a second direction, where the second direction is opposite to the first direction.

(51) For example, when the first connection assembly **20a** is switched from the folded state to the unfolded state, the first fixing frame **21a**, the first primary swing arm **23a**, and the first secondary swing arm **25a** rotate relative to the base **10** in an anticlockwise direction, and the second fixing frame **22a**, the second primary swing arm **24a**, and the second secondary swing arm **26a** rotate

relative to the base **10** in a clockwise direction. When the first connection assembly **20a** is switched from the unfolded state to the folded state, the first primary swing arm **23a** and the first secondary swing arm **25a** rotate relative to the base **10** in a clockwise direction, and the second primary swing arm **24a** and the second secondary swing arm **26a** rotate relative to the base **10** in an anticlockwise direction.

(52) It should be noted that, the second connection assembly **20b** and the first connection assembly **20a** may be same or similar assemblies, structures that are symmetrical or partially symmetrical, or different structures. The second connection assembly **20b** may be centrally symmetrical with the first connection assembly **20a**. For basic structures of components, a connection relationship between the components, and a connection relationship between the components and other components outside the components in the second connection assembly **20b**, refer to a related design of the first connection assembly **20a**, and a detailed structure or position arrangement of the components of the second connection assembly **20b** may be different from that of the first connection assembly **20a**.

(53) In this embodiment, the second connection assembly **20b** includes a first fixing frame **21b**, a second fixing frame **22b**, a first primary swing arm **23b**, a second primary swing arm **24a**, a first secondary swing arm **25b**, and a second secondary swing arm **26b**. For structures of components, and connection relationships between the components and the base **10**, the pressing plate assembly **40**, and the damping assembly **30** of the second connection assembly **20b**, refer to related description of the first connection assembly **20a**.

(54) The third connection assembly **20c** includes a first fixing frame **21c**, a second fixing frame **22c**, a first primary swing arm **23c**, and a second primary swing arm **24c**. For structures of components, and connection relationships between the components and the base **10**, the pressing plate assembly **40**, and the damping assembly **30** of the third connection assembly **20c**, refer to related description of the first connection assembly **20a**. In some other embodiments, the third connection assembly **20c** may also include a first secondary swing arm and a second secondary swing arm (not shown in the figure), which is not specifically limited in this application.

(55) It should be noted that, the first fixing frame **21a** of the first connection assembly **20a**, the first fixing frame **21b** of the second connection assembly **20b**, and the first fixing frame **21c** of the third connection assembly **20c** may be structural members that are independent of each other, or may be a plurality of parts of an integral structural member; and/or the second fixing frame **22a** of the first connection assembly **20a**, the second fixing frame **22b** of the second connection assembly **20b**, and the second fixing frame **22c** of the third connection assembly **20c** may be structural members that are independent of each other, or may be a plurality of parts of an integral structural member.

(56) It should be understood that, “and/or” mentioned in this embodiment of this application refers to both “and” and “or”. For example, A and/or B includes three cases: Only A exists, only B exists, and both A and B exist, and description of “and/or” in the following may be understood as the same meaning.

(57) In addition, the foldable mechanism **130** further includes a synchronization assembly **60**, and the synchronization assembly **60** is mounted on the base **10** and slidably connected to the connection assembly **20**. In this embodiment, there are two synchronization assemblies **60**, and the two synchronization assemblies **60** are arranged at intervals in the Y-axis direction. The two synchronization assemblies **60** are respectively a first synchronization assembly **60a** and a second synchronization assembly **60b**. The first synchronization assembly **60a** is mounted on a front side of the base **10**, and is slidably connected to the first secondary swing arm **25a** and the second secondary swing arm **26a**, so that the first secondary swing arm **25a** and the second secondary swing arm **26a** rotate synchronously relative to the base **10**. The second synchronization assembly **60b** is mounted on a rear side of the base **10**, and is slidably connected to the first secondary swing arm **25a** and the second secondary swing arm **26a**, so that the first secondary swing arm **25b** and the second secondary swing arm **26b** rotate synchronously relative to the base **10**.

(58) It should be noted that, the second synchronization assembly **60b** and the first synchronization assembly **60a** may be same or similar assemblies, structures that are symmetrical or partially symmetrical, or different structures. The second synchronization assembly **60b** may be mirror-symmetrical with the first synchronization assembly **60a**. For basic structures of components, a connection relationship between the components, and a connection relationship between the components and other components outside the components in the second synchronization assembly **60b**, refer to a related design of the first synchronization assembly **60a**, and a detailed structure or position arrangement of the components of the second synchronization assembly **60b** may be different from that of the first synchronization assembly **60a**.

(59) In this embodiment, there are two damping assemblies **30**, and the two damping assemblies **30** are arranged at intervals in the Y-axis direction. The two damping assemblies **30** are respectively a first damping assembly **30a** and a second damping assembly **30b**, and the first damping assembly **30a** is mounted on the first connection assembly **20a**. In a process that the first connection assembly **20a** is folded or unfolded relative to the base **10**, the first damping assembly **30a** may provide a damping force. The second damping assembly **30b** is mounted on the second connection assembly **20b**. In a process that the second connection assembly **20b** is folded or unfolded relative to the base **10**, the second damping assembly **30b** may provide a damping force. In a process that a user uses the foldable terminal **1000**, for example, when the foldable terminal **1000** is in a folded state or a flattened state and when the foldable terminal **1000** is switched between the folded state and the unfolded state, the user can apparently feel the damping force provided by the first damping assembly **30a** and the second damping assembly **30b**, so that the user can experience a good hand feeling, and the use experience of the user is improved.

(60) In some other embodiments, there may also be three damping assemblies **30**, and the three damping assemblies **30** are respectively a first damping assembly **30a**, a second damping assembly **30b**, and a third damping assembly (not shown in the figure), where the third damping assembly is mounted on the third connection assembly **20c**. In a process that the third connection assembly **20c** is folded or unfolded relative to the base **10**, the third damping assembly may provide a damping force. Alternatively, there may be one or at least four damping assemblies **30**, and a quantity of the damping assemblies **30** is not specifically limited in this application.

(61) In this embodiment, the first damping assembly **30a** includes a first damping member **31a** and a second damping member **32a**. The first damping member **31a** is mounted on the first fixing frame **21a**, is fixedly connected to the first secondary swing arm **25a**, and may slide relative to the first fixing frame **21a** under driving of the first secondary swing arm **25a**. The second damping member **32a** is mounted on the second fixing frame **22a**, is fixedly connected to the second secondary swing arm **26a**, and may slide relative to the second fixing frame **22a** under driving of the second secondary swing arm **26a**.

(62) It should be noted that, the second damping assembly **30b** and the first damping assembly **30a** may be same or similar assemblies, structures that are symmetrical or partially symmetrical, or different structures. The second damping assembly **30b** may be mirror-symmetrical with the first damping assembly **30a**. For basic structures of components, a connection relationship between the components, and a connection relationship between the components and other components outside the components in the second damping assembly **30b**, refer to a related design of the first damping assembly **30a**, and a detailed structure or position arrangement of the components of the second damping assembly **30b** may be different from that of the first damping assembly **30a**.

(63) In this embodiment, the second damping assembly **30b** includes a first damping member **31b** and a second damping member **32b**. The first damping member **31b** is mounted on the first fixing frame **21b**, is fixedly connected to the first secondary swing arm **25b**, and may slide relative to the first fixing frame **21b** under driving of the first secondary swing arm **25b**. The second damping member **32b** is mounted on the second fixing frame **22b**, is fixedly connected to the second secondary swing arm **26b**, and may slide relative to the second fixing frame **22b** under driving of

the second secondary swing arm **26b**. For structures of components, and connection relationships between the components and the base **10**, the second connection assembly **20b**, and the pressing plate assembly **40** of the second damping assembly **30b**, refer to related description of the first damping assembly **30a**.

(64) The pressing plate assembly **40** is slidably and rotatably connected to the connection assembly **20**. In this embodiment, the pressing plate assembly **40** includes a first pressing plate **41**, a second pressing plate **42**, a first pressing plate swing arm **43**, and a second pressing plate swing arm **44**. A front side of the first pressing plate **41** is slidably and rotatably connected to the first fixing frame **21a**, a rear side of the first pressing plate **41** is slidably and rotatably connected to the first fixing frame **21b**, and a middle portion of the first pressing plate **41** is slidably and rotatably connected to the first fixing frame **21c**. A front side of the second pressing plate **42** is slidably and rotatably connected to the second fixing frame **22a**, a rear side of the second pressing plate **42** is slidably and rotatably connected to the second fixing frame **22b**, and a middle portion of the second pressing plate **42** is slidably and rotatably connected to the second fixing frame **22c**. There are four first pressing plate swing arms **43** and four second pressing plate swing arms **44**. In the Y-axis direction, the four first pressing plate swing arms **43** are arranged at intervals, and the four second pressing plate swing arms **44** are arranged at intervals. In some other embodiments, there may also be one, two, or at least four first pressing plate swing arms **43**, and/or there may also be one, two, or at least four second pressing plate swing arms **44**. A quantity of the first pressing plate swing arms **43** and a quantity of the second pressing plate swing arms **44** are not specifically limited in this application.

(65) Each first pressing plate swing arm **43** is slidably connected to the first pressing plate **41** and is slidably and rotatably connected to the base **10**. Each second pressing plate swing arm **44** is slidably connected to the second pressing plate **42** and is slidably and rotatably connected to the base **10**. Rotation centers of the first pressing plate swing arm **43** and the second pressing plate swing arm **44** relative to the base **10** are both parallel to the Y-axis direction. In some other embodiments, each first pressing plate swing arm **43** may also be rotatably connected to the base **10**, and/or each second pressing plate swing arm **44** may also be rotatably connected to the base **10**.

(66) The flexible support plate **50** is mounted on the first pressing plate swing arm **43** and the second pressing plate swing arm **44**, and may bend under driving of the first pressing plate swing arm **43** and the second pressing plate swing arm **44** to be folded or unfolded, to implement mutual switching between the folded state and the unfolded state. A bending direction of the flexible support plate **50** is the Y-axis direction, and is parallel to the rotation centers of the first pressing plate swing arm **43** and the second pressing plate swing arm **44** relative to the base **10**. It should be noted that, the bending direction of the flexible support plate **50** being the Y-axis direction refers to that the flexible support plate **50** may bend around the Y-axis direction.

(67) Refer to FIG. 7, FIG. 7 is a schematic structural diagram of the base **10** in the foldable mechanism **130** shown in FIG. 6.

(68) The base **10** is provided with an avoidance groove **101**, and an opening of the avoidance groove **101** is located on a top surface of the base **10**. Specifically, the opening of the avoidance groove **101** is located in a middle region of the top surface of the base **10**. The avoidance groove **101** is recessed in a direction from the top surface to a bottom surface of the base **10** (the Z-axis negative direction shown in the figure). The avoidance groove **101** extends in the Y-axis direction. The avoidance groove **101** is an arc-shaped groove. That is, a groove bottom wall of the avoidance groove **101** is an arc-shaped surface.

(69) In this embodiment, the base **10** includes a first part **10a**, a second part **10b**, and a third part **10c**, where the first part **10a**, the second part **10b**, and the third part **10c** are sequentially arranged in the Y-axis direction, and the third part **10c** is connected between the first part **10a** and the second part **10b**. The first part **10a** is located on the front side of the base **10** and may be mated with the first connection assembly **20a** and the first synchronization assembly **60a** (as shown in FIG. 6). The

second part **10b** is located on the rear side of the base **10** and may be mated with the second connection assembly **20b** and the second synchronization assembly **60b** (as shown in FIG. 6). The third part **10c** is located on a middle portion of the base **10** and may be mated with the third connection assembly **20c** (as shown in FIG. 6).

(70) It should be noted that, the first part **10a** and the second part **10b** may be same or similar assemblies, structures that are symmetrical or partially symmetrical, or different structures. For example, the first part **10a** and the second part **10b** may be centrally symmetrical, to improve the symmetry of the base **10**, simplify the whole structure of the base **10**, improve the structure stability of the base **10**, and reduce manufacturing costs of the base **10**. For basic structures of components, a connection relationship between the components, and a connection relationship between the components and other components outside the components in the second part **10b**, refer to a related design of the first part **10a**, and a detailed structure or position arrangement of the components of the second part **10b** may be different from that of the first part **10a**.

(71) In this embodiment, the base **10** is an integrally formed structural member, so that the overall strength of the base **10** can be improved, and the structure stability of the base **10** can be ensured. Compared with an existing base structure, the base shown in this embodiment of this application does not need a fixing member such as a screw or a screw nail to implement assembly between a holder and a shaft cover. In this way, a quantity of components of the foldable mechanism **130** is simplified, which is conducive to assembly of the foldable mechanism **130** and may also improve the assembly precision of the base **10**.

(72) The base **10** may be made of a high-strength and wear-resistant material, so that the base **10** has a relatively high strength and good wear resistance, thereby preventing the base **10** from being worn and affecting the use reliability of the foldable mechanism **130**, and ensuring the use experience of the foldable mechanism **130**. For example, the base is integrally formed by a high-strength and wear-resistant metal material such as stainless steel or titanium alloy, or the base **10** may be integrally formed by a stainless steel material and a high-strength plastic material through injection molding, or the base **10** may be integrally formed by titanium alloy and a high-strength plastic material through injection molding, or the base **10** may be integrally formed by aluminum alloy and a high-strength plastic material through injection molding.

(73) Refer to FIG. 7 and FIG. 8, FIG. 8 is a schematic structural diagram of the first part **10a** in the base **10** shown in FIG. 7.

(74) The first part **10a** of the base **10** is provided with a first sliding groove **101a**, a second sliding groove **102a**, a first rotating groove **103a**, a second rotating groove **104a**, a first engagement groove **105a**, and a second engagement groove **106a**. The first sliding groove **101a**, the first rotating groove **103a**, and the first engagement groove **105a** are all located on a left side of the first part **10a**, and all run through a left side surface of the first part **10a** and the groove bottom wall of the avoidance groove **101**. In the Y-axis negative direction, the first engagement groove **105a**, the first sliding groove **101a**, and the first rotating groove **103a** are sequentially arranged at intervals. The second sliding groove **102a**, the second rotating groove **104a**, and the second engagement groove **106a** are all located on a right side of the first part **10a**, and all run through a right side surface of the first part **10a** and the groove bottom wall of the avoidance groove **101**. In the Y-axis negative direction, the second engagement groove **106a**, the second sliding groove **102a**, and the second rotating groove **104a** are sequentially arranged at intervals.

(75) In the Y-axis direction, the first sliding groove **101a** and the second sliding groove **102a** are disposed at intervals. In the X-axis direction, the first rotating groove **103a** and the second rotating groove **104a** are disposed at intervals and opposite to each other, and the first engagement groove **105a** and the second engagement groove **106a** are disposed at intervals and opposite to each other. The first sliding groove **101a**, the second sliding groove **102a**, the first engagement groove **105a** and the second engagement groove **106a** are all arc-shaped grooves. That is, groove bottom walls of the first sliding groove **101a**, the second sliding groove **102a**, the first engagement groove **105a**,

and the second engagement groove **106a** are all arc-shaped surfaces.

(76) The first rotating groove **103a** includes two first groove side walls (not marked in the figure), and in the Y-axis direction, the two first groove side walls are disposed at intervals and opposite to each other. Each first groove side wall is provided with a first mounting hole (not marked in the figure), and the first mounting hole extends in the Y-axis direction. Both the two first mounting holes are circular holes and are disposed coaxially.

(77) It should be noted that, the “coaxially” mentioned in this embodiment of this application refers to that extended lines of axes overlap with each other. For example, A being coaxial with B refers to that an extended line of an axis of A overlaps with an extended line of an axis of B, and description of “coaxially” in the following may be understood as the same meaning.

(78) The second rotating groove **104a** includes two second groove side walls (not marked in the figure), and in the Y-axis direction, the two second groove side walls are disposed at intervals and opposite to each other. Each second groove side wall is provided with a second mounting hole (not marked in the figure), and the second mounting hole extends in the Y-axis direction. Both the two second mounting holes are circular holes and are disposed coaxially. In the X-axis direction, each second mounting hole is disposed at intervals with one first mounting hole.

(79) In addition, the first part **10a** of the base **10** is further provided with a communication groove **107a**, and an opening of the communication groove **107a** is located on the groove bottom wall of the avoidance groove **101**. The communication groove **107a** extends in a direction from the groove bottom wall of the avoidance groove **101** to a bottom surface of the first part **10a** (the Z-axis negative direction shown in the figure). Specifically, the communication groove **107a** is located between the first rotating groove **103a** and the second rotating groove **104a**, and is in communication with the first rotating groove **103a** and the second rotating groove **104a**.

(80) The communication groove **107a** includes a third groove side wall and a fourth groove side wall (not marked in the figure), and in the Y-axis direction, the third groove side wall and the fourth groove side wall are disposed at intervals and opposite to each other. The third groove side wall is provided with a third mounting hole (not marked in the figure), and the third mounting hole extends in the Y-axis positive direction. The fourth groove side wall is provided with a bump (not marked in the figure), and the bump extends in the Y-axis positive direction. The bump is provided with a fourth mounting hole (not shown in the figure), and an opening of the fourth mounting hole is located on a surface of the bump away from the fourth groove side wall. The fourth mounting hole extends in the Y-axis negative direction. The third mounting hole and the fourth mounting hole are both square holes, and the third mounting hole and the fourth mounting hole are disposed opposite to each other.

(81) Refer to FIG. 8 and FIG. 9, FIG. 9 is a schematic structural diagram of the second part **10b** in the base **10** shown in FIG. 7.

(82) The second part **10b** of the base **10** is provided with a first sliding groove **101b**, a second sliding groove **102b**, a first rotating groove **103b**, a second rotating groove **104a**, a first engagement groove **105b**, a second engagement groove **106b**, and a communication groove **107b**. In this embodiment, for structures of the first sliding groove **101a**, the second sliding groove **102b**, the first rotating groove **103b**, the second rotating groove **104b**, the first engagement groove **105b**, the second engagement groove **106b**, and the communication groove **107b**, respectively refer to related description of the first sliding groove **101a**, the second sliding groove **102a**, the first rotating groove **103a**, the second rotating groove **104a**, the first engagement groove **105a**, the second engagement groove **106a**, and the communication groove **107a** in the first part **10a** in the above, and details are not described herein again. In the Y-axis positive direction, the first engagement groove **105b**, the first sliding groove **101b**, and the first rotating groove **103b** are sequentially arranged at intervals, and the second engagement groove **106b**, the second sliding groove **102b**, and the second rotating groove **104a** are sequentially arranged at intervals.

(83) Refer to FIG. 8 and FIG. 10, FIG. 10 is a schematic structural diagram of the third part **10c** in

the base **10** shown in FIG. 7.

(84) The third part **10c** of the base **10** is provided with a first sliding groove **101c**, a second sliding groove **102c**, a first engagement groove **103c**, and a second engagement groove **104c**. In this embodiment, for structures of the first sliding groove **101c**, the second sliding groove **102c**, the first engagement groove **103c**, and the second engagement groove **104c**, respectively refer to related description of the first sliding groove **101a**, the second sliding groove **102a**, the first engagement groove **105a**, and the second engagement groove **106a** in the first part **10a** in the above, and details are not described herein again.

(85) There are two first engagement grooves **103c** and two second engagement grooves **104c**. In the Y-axis direction, the two first engagement grooves **103c** are respectively located on two opposite sides of the first sliding groove **101c**, and the two second engagement grooves **104c** are respectively located on two opposite sides of the second sliding groove **102c**. In the X-axis direction, one first engagement groove **103c** and one second engagement groove **104c** are disposed at intervals and opposite to each other.

(86) Refer to FIG. 8, FIG. 11, and FIG. 12, FIG. 11 is a schematic structural diagram of the first connection assembly **20a**, the first damping assembly **30a**, and the first synchronization assembly **60a** in the foldable mechanism **130** shown in FIG. 6, and FIG. 12 is a schematic structural diagram of the first connection assembly **20a**, the first damping assembly **30a**, and the first synchronization assembly **60a** shown in FIG. 11 from another perspective.

(87) The first fixing frame **21a** is provided with a receiving notch **211a**, a mounting notch **212a**, a chute **213a**, a first mounting groove **214a**, a second mounting groove **215a**, an avoidance groove **216a**, and a guiding groove **217a**. An opening of the receiving notch **211a** is located on a top surface of the first fixing frame **21a**. The receiving notch **211a** is recessed in a direction from the top surface to a bottom surface of the first fixing frame **21a** (that is, the Z-axis negative direction shown in the figure), and runs through a front end surface, a rear end surface, and a right side surface of the first fixing frame **21a**. In some other embodiments, the receiving notch **211a** may not run through the front end surface of the first fixing frame **21a**, and/or the receiving notch **211a** may not run through the rear end surface of the first fixing frame **21a**, and/or the receiving notch **211a** may not run through the right side surface of the first fixing frame **21a**.

(88) An opening of the mounting notch **212a** is located on the right side surface of the first fixing frame **21a**. The mounting notch **212a** is recessed in a direction from the right side surface to a left side surface of the first fixing frame **21a** (the X-axis negative direction shown in the figure), and runs through the bottom surface of the first fixing frame **21a** and a groove bottom wall of the receiving notch **211a**. In some other embodiments, the mounting notch **212a** may not run through the bottom surface of the first fixing frame **21a**.

(89) The mounting notch **212a** includes two groove side walls disposed opposite to each other and a groove bottom wall (not marked in the figure) connected between the two groove side walls. The two groove side walls of the mounting notch **212a** are both provided with a mounting hole (not marked in the figure), and the mounting hole is recessed in the Y-axis direction. The two mounting holes are circular holes, and the two mounting holes are coaxial. For example, axes of the two mounting holes are parallel to the Y-axis direction.

(90) The groove bottom wall of the mounting notch **212a** is convexly provided with a mounting boss (not marked in the figure), and the mounting boss is disposed at intervals with the two groove side walls of the mounting notch **212a**. The mounting boss is provided with a through hole (not marked in the figure), and in the Y-axis direction, the through hole runs through the mounting boss. The through hole is a circular hole, and the through hole is coaxial with the two mounting holes. For example, an axis of the through hole is parallel to the Y-axis direction. In some other embodiments, the groove bottom wall of the mounting notch **212a** may not be convexly provided with the mounting boss.

(91) The chute **213a** is located on one side of the mounting notch **212a** facing the Y-axis negative

direction, and is disposed at intervals with the mounting notch **212a**. An opening of the chute **213a** is located on the right side surface of the first fixing frame **21a**. The chute **213a** is recessed in a direction from the right side surface to the left side surface of the first fixing frame **21a**, and runs through the left side surface of the first fixing frame **21a** and the bottom surface of the first fixing frame **21a**. For example, a cross section of the chute **213a** is in a square shape. In some other embodiments, the cross section of the chute **213a** may alternatively be a circular hole or a special-shaped hole.

(92) In the Y-axis direction, the first mounting groove **214a** and the second mounting groove **215a** are located on two opposite sides of the chute **213a**, and are in communication with the chute **213a**. The first mounting groove **214a** is located on one side of the chute **213a** facing the Y-axis positive direction. An opening of the first mounting groove **214a** is located on the bottom surface of the first fixing frame **21a**. The first mounting groove **214a** is recessed in a direction from the bottom surface to the top surface of the first fixing frame **21a**, and runs through a groove side wall of the chute **213a**. A groove side wall of the first mounting groove **214a** is convexly provided with a first fixing block **218a**, and the first fixing block **218a** extends from the groove bottom wall of the first mounting groove **214a** in the Z-axis negative direction. For example, the first fixing block **218a** is in a shape of a square block.

(93) The second mounting groove **215a** is located on one side of the chute **213a** facing the Y-axis negative direction. A structure of the second mounting groove **215a** is approximately the same as the structure of the first mounting groove **214a**, and is not described herein again. A groove bottom wall of the second mounting groove **215a** is convexly provided with a second fixing block **219a**. For example, the second fixing block **219a** is in a shape of a square block.

(94) The avoidance groove **216a** is located on one side of the mounting notch **212a** away from the chute **213a**, and is disposed at intervals with the mounting notch **212a**. An opening of the avoidance groove **216a** is located on the right side surface of the first fixing frame **21a**. The avoidance groove **216a** is recessed in a direction from the right side surface to the left side surface of the first fixing frame **21a**, and runs through the bottom surface of the first fixing frame **21a** and the groove bottom wall of the receiving notch **211a**. In addition, a groove bottom wall of the avoidance groove **216a** is provided with a sliding hole **2161a**, and the sliding hole **2161a** extends in the X-axis negative direction and runs through the left side surface of the first fixing frame **21a**. For example, the sliding hole **2161a** is a square hole.

(95) In some other embodiments, the avoidance groove **216a** may not run through the bottom surface of the first fixing frame **21a**, and/or the avoidance groove **216a** may not run through the groove bottom wall of the receiving notch **211a**, and/or the groove bottom wall of the avoidance groove **216a** may not be provided with the sliding hole **2161a**, or the sliding hole **2161a** may not run through the left side surface of the first fixing frame **21a**.

(96) An opening of the guiding groove **217a** is located on the groove bottom wall of the receiving notch **211a**. The guiding groove **217a** is recessed in a direction from the groove bottom wall of the receiving notch **211a** to the bottom surface of the first fixing frame **21a** (the Z-axis negative direction shown in the figure), and runs through the left side surface of the first fixing frame **21a**. The guiding groove **217a** is an arc-shaped groove. That is, a groove bottom wall of the guiding groove **217a** is an arc-shaped surface. In some other embodiments, the guiding groove **217a** may not run through the left side surface of the first fixing frame **21a**.

(97) In this embodiment, there are two guiding grooves **217a**. One guiding groove **217a** is located on one side of the avoidance groove **216a** away from the mounting notch **212a**, is disposed at intervals with the avoidance groove **216a**, and runs through the top surface of the first fixing frame **21a** and the front end surface of the first fixing frame **21a**. The other guiding groove **217a** is located on one side of the chute **213a** away from the mounting notch **212a**, is disposed at intervals with the chute **213a**, and runs through the top surface of the first fixing frame **21a** and the rear end surface of the first fixing frame **21a**. In some other embodiments, the guiding groove **217a** may not

run through the top surface of the first fixing frame **21a**, and/or the guiding groove **217a** may not run through the front end surface of the first fixing frame **21a**, and/or the guiding groove **217a** may not run through the rear end surface of the first fixing frame **21a**.

(98) In this embodiment, the first primary swing arm **23a** includes a rotating portion **231a**, a connection portion **232a**, and a sliding portion **233a**, where the connection portion **232a** is connected between the rotating portion **231a** and the sliding portion **233a**. The rotating portion **231a** includes two sub-rotating portions **234a**, and the two sub-rotating portions **234a** are arranged at intervals in the Y-axis direction. Each sub-rotating portion **234a** is provided with a through hole (not marked in the figure), and in the Y-axis direction, the through hole runs through the sub-rotating portion **234a**.

(99) A structure of the rotating portion **231a** is adapted to a structure of the mounting notch **212a**. In addition, the first connection assembly **20a** further includes a first pin shaft **271a**, and the first pin shaft **271a** may run through the through holes of the two sub-rotating portions **234a**. Specifically, the first pin shaft **271a** may be mounted in the mounting notch **212a**. The first pin shaft **271a** may run through the through hole of the mounting boss in the mounting notch **212a**. Two ends of the first pin shaft **271a** are respectively mounted in the mounting holes of the two groove side walls of the mounting notch **212a**, and are respectively fixedly connected to hole walls of the two mounting holes. In this embodiment, the first pin shaft **271a** is a circular shaft, and an axis of the first pin shaft **271a** is parallel to the Y-axis direction. The two sub-rotating portions **234a** may rotate relative to the first pin shaft **271a**, to implement a rotatable connection between the rotating portion **231a** and the first pin shaft **271a**, and further implement a rotatable connection between the first primary swing arm **23a** and the first fixing frame **21a**.

(100) The connection portion **232a** is in a shape of a flat plate. A structure of the sliding portion **233a** is adapted to a structure of the first sliding groove **101a**. The sliding portion **233a** is in a shape of an arc-shaped plate, and an axis of the sliding portion **233a** is parallel to the Y-axis direction. The sliding portion **233a** is mounted in the first sliding groove **101a**, and may slide and rotate in the first sliding groove **101a**, to implement a slidable and rotatable connection between the sliding portion **233a** and the base **10**, and further implement a slidable and rotatable connection between the first primary swing arm **23a** and the base **10**. In this case, the sliding portion **233a** and the first sliding groove **101a** are coaxial.

(101) It may be understood that, since the base **10** is an integrally formed structural member, the first sliding groove **101a** does not need to be formed through cooperation of a shaft cover and a holder. In the foldable mechanism **130**, a sum of a thickness of the first sliding groove **101a** and a thickness of the sliding portion **233a** is relatively small, so that space occupied by the foldable mechanism **130** can be reduced, which is conducive to implement a light and thin design of the foldable mechanism **130**.

(102) In this embodiment, the first secondary swing arm **25a** includes a rotating portion **251a**, a connection portion **252a**, and a sliding portion **253a**, where the connection portion **252a** is connected between the rotating portion **251a** and the sliding portion **253a**. The sliding portion **253a** is in a shape of a flat plate. A bottom surface of the sliding portion **253a** is convexly provided with a third fixing block **254a**, and the third fixing block **254a** extends in the Z-axis negative direction. The third fixing block **254a** is disposed in a middle region of the bottom surface of the sliding portion **253a**. For example, the third fixing block **254a** is in a shape of a square block.

(103) A structure of the sliding portion **253a** is adapted to a structure of the chute **213a**. The sliding portion **253a** may be mounted in the chute **213a**, and may slide relative to the first fixing frame **21a** in the chute **213a**, to implement a slidable connection between the first secondary swing arm **25a** and the first fixing frame **21a**.

(104) In this embodiment, the rotating portion **251a** is in a shape of a cylinder. The rotating portion **251a** is provided with a through hole (not marked in the figure) and a first spiral groove **255a**. In the Y-axis direction, the through hole runs through the rotating portion **251a**. The first spiral groove

255a is located on one side of the rotating portion **251a** away from the connection portion **252a**. The first spiral groove **255a** extends along an axis of the rotating portion **251a** in a winding manner.

(105) A structure of the rotating portion **251a** is adapted to a structure of the first rotating groove **103a**. In addition, the first connection assembly **20a** further includes a first rotating shaft **281a**, and the first rotating shaft **281a** runs through the through hole of the rotating portion **251a**. Specifically, the first rotating shaft **281a** may be mounted in the first rotating groove **103a**. Two ends of the first rotating shaft **281a** are respectively mounted in the first mounting holes of the two first groove side walls in the first rotating groove **103a**, and are respectively fixedly connected to hole walls of the two first mounting holes. The rotating portion **251a** may rotate relative to the first rotating shaft **281a**, to implement a rotatable connection between the rotating portion **251a** and the base **10**, and further implement a rotatable connection between the first secondary swing arm **25a** and the base **10**.

(106) In this embodiment, the first rotating shaft **281a** is a circular shaft, an axis of the first rotating shaft **281a** is parallel to the Y-axis direction, and the first rotating shaft is coaxial with the rotating portion **251a**. In this case, the rotation center of the rotating portion **251a** of the first secondary swing arm **25a** relative to the base **10** is the axis of the first rotating shaft **281a**. That is, the rotation center of the first secondary swing arm **25a** relative to the base **10** is the axis of the first rotating shaft **281a**.

(107) The second fixing frame **22a** is provided with a receiving notch **221a**, a mounting notch **222a**, a chute **223a**, a first mounting groove **224a**, a second mounting groove **225a**, an avoidance groove **226a**, and a guiding groove **227a**. For structures of the receiving notch **221a**, the mounting notch **222a**, the chute **223a**, the first mounting groove **224a**, the second mounting groove **225a**, the avoidance groove **226a**, and the guiding groove **227a**, respectively refer to related description of the receiving notch **211a**, the mounting notch **212a**, the chute **213a**, the first mounting groove **214a**, the second mounting groove **215a**, the avoidance groove **216a**, and the guiding groove **217a** in the first fixing frame **21a**, and details are not described herein again.

(108) The receiving notch **221a** further runs through a left side surface of the second fixing frame **22a**. Openings of the mounting notch **222a** and the chute **223a** are located on the left side surface of the second fixing frame **22a**. A groove bottom wall of the first mounting groove **224a** is convexly provided with a first fixing block **228a**, and a groove bottom wall of the second mounting groove **225a** is convexly provided with a second fixing block **229a**. An opening of the avoidance groove **226a** is located on the left side surface of the second fixing frame **22a**, a groove bottom wall of the avoidance groove **226a** is provided with a sliding hole **2261a**, and the sliding hole **2261a** extends in the X-axis positive direction and runs through a right side surface of the second fixing frame **22a**.

(109) The second primary swing arm **24a** includes a rotating portion **241a**, a connection portion **242a**, and a sliding portion **243a**, where the connection portion **242a** is connected between the rotating portion **241a** and the sliding portion **243a**. For a structure of the second primary swing arm **24a**, refer to related description of the first primary swing arm **23a** in the above, and details are not described herein again.

(110) The rotating portion **241a** includes two sub-rotating portions **244a**. A structure of the rotating portion **241a** is adapted to a structure of the mounting notch **222a**. In addition, the first connection assembly **20a** further includes a second pin shaft **272a**, and the second pin shaft **272a** may run through through holes (not shown in the figure) of the two sub-rotating portions **244a**. Specifically, the second pin shaft **272a** may be mounted in the mounting notch **222a**. The second pin shaft **272a** is a circular shaft, and an axis of the second pin shaft **272a** is parallel to the Y-axis direction. The two sub-rotating portions **244a** may rotate relative to the second pin shaft **272a**, to implement a rotatable connection between the rotating portion **241a** and the second pin shaft **272a**, and further implement a rotatable connection between the second primary swing arm **24a** and the second fixing

frame **22a**.

(111) A structure of the sliding portion **243a** is adapted to a structure of the second sliding groove **102a**. The sliding portion **243a** is in a shape of an arc-shaped plate, and an axis of the sliding portion **243a** is parallel to the Y-axis direction. The sliding portion **243a** is mounted in the second sliding groove **102a**, and may slide and rotate in the second sliding groove **102a**, to implement a slidable and rotatable connection between the sliding portion **243a** and the base **10**, and further implement a slidable and rotatable connection between the second primary swing arm **24a** and the base **10**. The sliding portion **243a** and the second sliding groove **102a** are coaxial.

(112) It may be understood that, since the base **10** is an integrally formed structural member, the second sliding groove **102a** does not need to be formed through cooperation of a shaft cover and a holder. A sum of a thickness of the second sliding groove **102a** and a thickness of the sliding portion **243a** is relatively small, so that space occupied by the foldable mechanism **130** can be reduced, which is conducive to implement a light and thin design of the foldable mechanism **130**.

(113) The second secondary swing arm **26a** includes a rotating portion **261a**, a connection portion **262a**, and a sliding portion **263a**, where the connection portion **262a** is connected between the rotating portion **261a** and the sliding portion **263a**. For a structure of the second secondary swing arm **26a**, refer to related description of the first secondary swing arm **25a** in the above, and details are not described herein again.

(114) A bottom surface of the sliding portion **263a** is convexly provided with a third fixing block **264a**. A structure of the sliding portion **263a** is adapted to a structure of the chute **223a**. The sliding portion **263a** may be mounted in the chute **223a**, and may slide relative to the second fixing frame **22a** in the first chute **223a**, to implement a slidable connection between the sliding portion **263a** and the second fixing frame **22a**, and further implement a slidable connection between the second secondary swing arm **26a** and the second fixing frame **22a**.

(115) The rotating portion **261a** is provided with a through hole (not marked in the figure) and a second spiral groove **265a**. A structure of the rotating portion **261a** is adapted to a structure of the second rotating groove **104a**. In addition, the first connection assembly **20a** further includes a second rotating shaft **282a**, and the second rotating shaft **282a** runs through the through hole of the rotating portion **261a**. Specifically, the second rotating shaft **282a** may be mounted in the second rotating groove **104a**. The rotating portion **261a** may rotate relative to the second rotating shaft **282a**, to implement a rotatable connection between the rotating portion **261a** and the base **10**, and further implement a rotatable connection between the second secondary swing arm **26a** and the base **10**.

(116) The second rotating shaft **282a** is a circular shaft, and an axis of the second rotating shaft **282a** is parallel to the Y-axis direction. In this case, the rotation center of the rotating portion **261a** of the second secondary swing arm **26a** relative to the base **10** is the axis of the second rotating shaft **282a**. That is, the rotation center of the second secondary swing arm **26a** relative to the base **10** is the axis of the second rotating shaft **282a**.

(117) In a process that the first connection assembly **20a** is switched between the folded state and the unfolded state, when the first fixing frame **21a** rotates relative to the base **10**, the first fixing frame **21a** drives the first primary swing arm **23a** to rotate relative to the first fixing frame **21a**, drives the first primary swing arm **23a** to slide and rotate relative to the base **10**, further drives the first secondary swing arm **25a** to slide relative to the first fixing frame **21a**, and further drives the first secondary swing arm **25a** to rotate relative to the base **10**. Similarly, when the second fixing frame **22a** rotates relative to the base **10**, the second fixing frame **22a** drives the second primary swing arm **24a** to rotate relative to the second fixing frame **22a**, drives the second primary swing arm **24a** to slide and rotate relative to the base **10**, further drives the second secondary swing arm **26a** to slide relative to the second fixing frame **22a**, and further drives the second secondary swing arm **26a** to rotate relative to the base **10**.

(118) The first damping member **31a** includes a first fixing portion **311a**, a second fixing portion

312a, a third fixing portion **313a**, a first connecting portion **314a**, and a second connecting portion **315a**. The third fixing portion **313a** is located between the first fixing portion **311a** and the second fixing portion **312a**, and is disposed at intervals with the first fixing portion **311a** and the second fixing portion **312a**. The first connecting portion **314a** is fixedly connected between the first fixing portion **311a** and the third fixing portion **313a**. The second connecting portion **315a** is fixedly connected between the second fixing portion **312a** and the third fixing portion **313a**. The first damping member **31a** is an integrally formed structural member.

(119) The first fixing portion **311a** is provided with a first fixing hole **316a**, and the first fixing hole **316a** runs through the first fixing portion **311a** in a thickness direction of the first fixing portion **311a**. The second fixing portion **312a** is provided with a second fixing hole **317a**, and the second fixing hole **317a** runs through the second fixing portion **312a** in a thickness direction of the second fixing portion **312a**. The third fixing portion **313a** is provided with a third fixing hole **318a**, and the third fixing hole **318a** runs through the third fixing portion **313a** in a thickness direction of the third fixing portion **313a**.

(120) Specifically, the first fixing portion **311a** is mounted in the first mounting groove **214a**, and the second fixing portion **312a** is mounted in the second mounting groove **215a**, to implement assembly between the first damping member **31a** and the first fixing frame **21a**. The third fixing portion **313a** is fixedly connected to the sliding portion **253a** of the first secondary swing arm **25a**, to implement a fixed connection between the first damping member **31a** and the first secondary swing arm **25a**. The first fixing block **218a** is mounted in the first fixing hole **316a**, the second fixing block **219a** is mounted in the second fixing hole **317a**, and the third fixing block **254a** is mounted in the third fixing hole **318a**.

(121) When the first secondary swing arm **25a** slides relative to the first fixing frame **21a**, the sliding portion **253a** drives the third fixing portion **313a** to move relative to the first fixing portion **311a** and the second fixing portion **312a**, and the first connecting portion **314a** and the second connecting portion **315a** are deformed to generate a damping force. In a process that the user folds or unfolds the foldable terminal **1000**, the user can feel the damping force generated by the first connecting portion **314a** and the second connecting portion **315a** due to deformation, so that the user can feel a good hand feeling, thereby improving the use experience of the user.

(122) The second damping member **32a** includes a first fixing portion **321a**, a second fixing portion **322a**, a third fixing portion **323a**, a first connecting portion **324a**, and a second connecting portion **325a**. For the first fixing portion **321a**, the second fixing portion **322a**, the third fixing portion **323a**, the first connecting portion **324a**, and the second connecting portion **325a**, respectively refer to related description of the first fixing portion **311a**, the second fixing portion **312a**, the third fixing portion **313a**, the first connecting portion **314a**, and the second connecting portion **315a** in the first damping member **31a** in the above, and details are not described herein again.

(123) Specifically, the first fixing portion **321a** is mounted in the first mounting groove **224a**, and the second fixing portion **322a** is mounted in the second mounting groove **225a**, to implement assembly between the second damping member **32a** and the second fixing frame **22a**. The third fixing portion **323a** is fixedly connected to the sliding portion **263a** of the second secondary swing arm **26a**, to implement a fixed connection between the second damping member **32a** and the second secondary swing arm **26a**. The first fixing block **228a** is mounted in the first fixing hole **326a**, the second fixing block **229a** is mounted in the second fixing hole **327a**, and the third fixing block **264a** is mounted in the third fixing hole **328a**.

(124) When the second secondary swing arm **26a** slides relative to the second fixing frame **22a**, the sliding portion **253a** drives the third fixing portion **323a** to move relative to the first fixing portion **321a** and the second fixing portion **322a**, and the first connecting portion **324a** and the second connecting portion **325a** are deformed to generate a damping force. In a process that the user folds or unfolds the foldable terminal **1000**, the user can feel the damping force generated by the first connecting portion **324a** and the second connecting portion **325a** due to deformation, so that the

user can feel a good hand feeling, thereby improving the use experience of the user.

(125) When the first connection assembly **20a** is switched between the folded state and the unfolded state, the first fixing frame **21a**, the second fixing frame **22a**, the first secondary swing arm **25a**, and the second secondary swing arm **26a** all rotate relative to the base **10**, and further drives the first damping member **31a** and the second damping member **32a** to rotate relative to the base **10**, so that the first damping assembly **30a** is switched between the folded state and the unfolded state.

(126) In the foldable mechanism **130** shown in this embodiment, the first damping assembly **30a** mounted on the first connection assembly **20a** is used to provide a damping force for a folding process and an unfolding process. Compared with a common damping mechanism that provides damping by using springs and cams, the first damping assembly **30a** shown in this embodiment has fewer components and is easy to assemble, so that costs of the foldable mechanism **130** can be reduced, and the structure of the foldable mechanism **130** can be simplified. In addition, the first damping assembly **30a** may be further directly mounted on the first connection assembly **20a** without being mounted on the base **10**. Therefore, the first damping assembly **30a** does not need to occupy space of the base **10**, which is conducive to implement a light and thin design of the foldable mechanism **130**.

(127) In some other embodiments, the first damping assembly **30a** may alternatively provide the damping force in the folding process and the unfolding process of the foldable mechanism **130** by using springs and cams, which is not specifically limited in this application.

(128) The first synchronization assembly **60** includes a fixing column **61a** and a synchronization slider **62a**, where the synchronization slider **62a** is sleeved on the fixing column **61a** and may slide relative to the fixing column **61a**. The synchronization slider **62a** is provided with a first cam **63a** and a second cam **64a**, and the first cam **63a** and the second cam **64a** are respectively located on two opposite sides of the synchronization slider **62a**. A structure of the first cam **63a** is adapted to a structure of the first spiral groove **255a**, and a structure of the second cam **64a** is adapted to a structure of the second spiral groove **265a**.

(129) The first synchronization assembly **60a** is mounted in the communication groove **107a**. Specifically, the fixing column **61a** and the synchronization slider **62a** are both mounted in the communication groove **107a**, and the first cam **63a** is mounted in the first spiral groove **255a** and may slide relative to the rotating portion **251a** in the first spiral groove **255a**. The second cam **64a** is mounted in the second spiral groove **265a** and may slide relative to the rotating portion **261a** in the second spiral groove **265a**. One end of the fixing column **61a** is mounted in the third mounting hole of the third groove side wall, and the other end is mounted in the fourth mounting hole of the bump and is fixedly connected to a hole wall of the fourth mounting hole.

(130) When the first secondary swing arm **25a** rotates relative to the base **10**, the rotating portion **251a** drives the first cam **63a** to slide in the first spiral groove **255a**, to drive the synchronization slider **62a** to slide relative to the fixing column **61a**, drive the second cam **64a** to slide relative to the rotating portion **261a** in the second spiral groove **265a**, and further drive the second secondary swing arm **26a** to rotate relative to the base **10**, so as to implement synchronous rotation between the first secondary swing arm **25a** and the second secondary swing arm **26a**. Similarly, when the second secondary swing arm **26a** rotates relative to the base **10**, the first synchronization assembly **60a** may drive the first secondary swing arm **25a** to rotate relative to the base **10**, thereby implementing the synchronous rotation between the first secondary swing arm **25a** and the second secondary swing arm **26a**.

(131) In the foldable mechanism **130** shown in this embodiment, synchronous rotation is implemented through cooperation of spiral grooves and cams. Compared with a common manner in which synchronous rotation is implemented through gears, a quantity of components of the foldable mechanism **130** is reduced, so that an assembly error between the components is avoided, and costs of the foldable mechanism **130** are reduced. In addition, a thickness size (a size in the Z-

axis direction) of the first synchronization assembly **60a** is relatively small, which is conducive to reduce a thickness size of the foldable mechanism **130**, thereby implementing a light and thin design of the foldable mechanism **130**.

(132) In some other embodiments, synchronous rotation may alternatively be implemented by using a synchronization assembly including gears, which is not specifically limited in this application.

(133) Refer to FIG. **9**, FIG. **13**, and FIG. **14**, FIG. **13** is a schematic structural diagram of the second connection assembly **20b**, the second damping assembly **30b**, and the second synchronization assembly **60b** in the foldable mechanism **130** shown in FIG. **6**, and FIG. **14** is a schematic structural diagram of the second connection assembly **20b**, the second damping assembly **30b**, and the second synchronization assembly **60b** shown in FIG. **13** from another perspective.

(134) The first fixing frame **21b** is provided with a receiving notch **211b**, a mounting notch **212b**, a chute **213b**, a first mounting groove **214b**, a second mounting groove **215b**, an avoidance groove **216b**, and a guiding groove **217b**. For structures of the receiving notch **211b**, the mounting notch **212b**, the chute **213b**, the first mounting groove **214b**, the second mounting groove **215b**, the avoidance groove **216b**, and the guiding groove **217b**, respectively refer to related description of the receiving notch **211a**, the mounting notch **212a**, the chute **213a**, the first mounting groove **214a**, the second mounting groove **215a**, the avoidance groove **216a**, and the guiding groove **217a** (as shown in FIG. **11** and FIG. **12**) in the first fixing frame **21a** in the above, and details are not described herein again.

(135) The chute **213b** is located on one side of the mounting notch **212b** facing the Y-axis positive direction. A groove bottom wall of the first mounting groove **214b** is convexly provided with a first fixing block **218b**, and a groove bottom wall of the second mounting groove **215b** is convexly provided with a second fixing block **219b**. The avoidance groove **216b** is located on one side of the mounting notch **212b** facing the Y-axis negative direction. A groove bottom wall of the avoidance groove **216b** is provided with a sliding hole **2161b**.

(136) The first primary swing arm **23b** includes a rotating portion **231b**, a connection portion **232b**, and a sliding portion **233b**, where the connection portion **232b** is connected between the rotating portion **231b** and the sliding portion **233b**. For a structure of the first primary swing arm **23b**, refer to related description of the first primary swing arm **23a** (as shown in FIG. **11** and FIG. **12**) in the above, and details are not described herein again.

(137) The rotating portion **231b** includes two sub-rotating portions **234b**. A structure of the rotating portion **231b** is adapted to a structure of the mounting notch **212b**. In addition, the second connection assembly **20b** further includes a first pin shaft **271b**, and the first pin shaft **271b** may run through through holes (not shown in the figure) of the two sub-rotating portions **234b**. Specifically, the first pin shaft **271b** may be mounted in the mounting notch **212b**. The first pin shaft **271b** is a circular shaft, an axis of the first pin shaft **271b** is parallel to the Y-axis direction, and the first pin shaft **271b** is coaxial with the first pin shaft **271a** (as shown in FIG. **11** and FIG. **12**). The two sub-rotating portions **234b** may rotate relative to the first pin shaft **271b**, to implement a rotatable connection between the rotating portion **231b** and the first pin shaft **271b**, and further implement a rotatable connection between the first primary swing arm **23b** and the first fixing frame **21b**.

(138) A structure of the sliding portion **233b** is adapted to a structure of the first sliding groove **101b**. The sliding portion **233b** is mounted in the first sliding groove **101b**, and may slide and rotate in the first sliding groove **101b**, to implement a slidable and rotatable connection between the sliding portion **233b** and the base **10**, and further implement a slidable and rotatable connection between the first primary swing arm **23b** and the base **10**. In this case, the sliding portion **233b** and the first sliding groove **101b** are coaxial.

(139) It may be understood that, since the base **10** is an integrally formed structural member, the

first sliding groove **101b** does not need to be formed through cooperation of a shaft cover and a holder. A sum of a thickness of the first sliding groove **101b** and a thickness of the sliding portion **233b** is relatively small, so that space occupied by the foldable mechanism **130** can be reduced, which is conducive to implement a light and thin design of the foldable mechanism **130**.

(140) The first secondary swing arm **25b** includes a rotating portion **251b**, a connection portion **252b**, and a sliding portion **253b**, where the connection portion **252b** is connected between the rotating portion **251b** and the sliding portion **253b**. For a structure of the first secondary swing arm **25b**, refer to related description of the first secondary swing arm **25b** (as shown in FIG. **11** and FIG. **12**) in the first connection assembly **20a**, and details are not described herein again.

(141) A bottom surface of the sliding portion **253b** is convexly provided with a third fixing block **254b**. A structure of the sliding portion **253b** is adapted to a structure of the chute **213b**. The sliding portion **253b** may be mounted in the chute **213b**, and may slide relative to the first fixing frame **21b** in the first chute **213b**, to implement a slidable connection between the sliding portion **253b** and the first fixing frame **21b**, and further implement a slidable connection between the first secondary swing arm **25b** and the first fixing frame **21b**.

(142) The rotating portion **251b** is provided with a through hole (not marked in the figure) and a first spiral groove **255b**. A structure of the rotating portion **251b** is adapted to a structure of the first rotating groove **103b**. In addition, the second connection assembly **20b** further includes a first rotating shaft **281b**, and the first rotating shaft **281b** may run through the through hole of the rotating portion **251b**. Specifically, the first rotating shaft **281b** may be mounted in the first rotating groove **103b**. The rotating portion **251b** may rotate relative to the first rotating shaft **281b**, to implement a rotatable connection between the rotating portion **251b** and the base **10**, and further implement a rotatable connection between the first secondary swing arm **25b** and the base **10**.

(143) The first rotating shaft **281b** is a circular shaft, an axis of the first rotating shaft **281b** is parallel to the Y-axis direction, and the first rotating shaft **281b** is coaxial with the first rotating shaft **281a** (as shown in FIG. **11** and FIG. **12**). In this case, the rotation center of the rotating portion **251b** of the first secondary swing arm **25b** relative to the base **10** is the axis of the first rotating shaft **281b**. That is, the rotation center of the first secondary swing arm **25b** relative to the base **10** is the axis of the first rotating shaft **281b**.

(144) The second fixing frame **22b** is provided with a receiving notch **221b**, a mounting notch **222b**, a chute **223b**, a first mounting groove **224b**, a second mounting groove **225b**, an avoidance groove **226b**, and a guiding groove **227b**. For structures of the receiving notch **221b**, the mounting notch **222b**, the chute **223b**, the first mounting groove **224b**, the second mounting groove **225b**, the avoidance groove **226b**, and the guiding groove **227b**, respectively refer to related description of the receiving notch **211b**, the mounting notch **212b**, the chute **213b**, the first mounting groove **214b**, the second mounting groove **215b**, the avoidance groove **216b**, and the guiding groove **217b** in the first fixing frame **21b**, and details are not described herein again.

(145) The receiving notch **221b** further runs through a left side surface of the second fixing frame **22b**. Openings of the mounting notch **222b** and the chute **223b** are located on the left side surface of the second fixing frame **22b**. A groove bottom wall of the first mounting groove **224b** is convexly provided with a first fixing block **228b**, and a groove bottom wall of the second mounting groove **225b** is convexly provided with a second fixing block **229b**. An opening of the avoidance groove **226b** is located on the left side surface of the second fixing frame **22**, a groove bottom wall of the avoidance groove **226b** is provided with a sliding hole **2261b**, and the sliding hole **2261b** extends in the X-axis positive direction and runs through a right side surface of the second fixing frame **22b**.

(146) The second primary swing arm **24b** includes a rotating portion **241b**, a connection portion **242b**, and a sliding portion **243b**, where the connection portion **242b** is connected between the rotating portion **241b** and the sliding portion **243b**. For a structure of the second primary swing arm **24b**, refer to related description of the first primary swing arm **23b** in the above, and details are not

described herein again.

(147) The rotating portion **241b** includes two sub-rotating portions **244b**. A structure of the rotating portion **241b** is adapted to a structure of the mounting notch **222b**. In addition, the second connection assembly **20b** further includes a second pin shaft **272b**, and the second pin shaft **272b** may run through through holes (not shown in the figure) of the two sub-rotating portions **244b**. Specifically, the second pin shaft **272b** may be mounted in the mounting notch **222b**. The second pin shaft **272b** is a circular shaft, an axis of the second pin shaft **272b** is parallel to the Y-axis direction, and the second pin shaft **272b** is coaxial with the second pin shaft **272a** (as shown in FIG. **11** and FIG. **12**). The two sub-rotating portions **244b** may rotate relative to the second pin shaft **272b**, to implement a rotatable connection between the rotating portion **241b** and the second pin shaft **272b**, and further implement a rotatable connection between the second primary swing arm **24b** and the second fixing frame **22b**.

(148) A structure of the sliding portion **243b** is adapted to a structure of the second sliding groove **102b**. The sliding portion **243b** is mounted in the second sliding groove **102b**, and may slide and rotate in the second sliding groove **102b**, to implement a slidable and rotatable connection between the sliding portion **243b** and the base **10**, and further implement a slidable and rotatable connection between the second primary swing arm **24b** and the base **10**. The sliding portion **243b** and the second sliding groove **102b** are coaxial.

(149) It may be understood that, since the base **10** is an integrally formed structural member, the second sliding groove **102b** does not need to be formed through cooperation of a shaft cover and a holder. A sum of a thickness of the second sliding groove **102b** and a thickness of the sliding portion **243b** is relatively small, so that space occupied by the foldable mechanism **130** can be reduced, which is conducive to implement a light and thin design of the foldable mechanism **130**.

(150) The second secondary swing arm **26b** includes a rotating portion **261b**, a connection portion **262b**, and a sliding portion **263b**, where the connection portion **262b** is connected between the rotating portion **261b** and the sliding portion **263b**. For a structure of the second secondary swing arm **26b**, refer to related description of the first secondary swing arm **25b** in the above, and details are not described herein again.

(151) A bottom surface of the sliding portion **263b** is convexly provided with a third fixing block **264b**. A structure of the sliding portion **263b** is adapted to a structure of the chute **223b**. The sliding portion **263b** may be mounted in the chute **223b**, and may slide relative to the second fixing frame **22b** in the first chute **223b**, to implement a slidable connection between the sliding portion **263b** and the second fixing frame **22b**, and further implement a slidable connection between the second secondary swing arm **26b** and the second fixing frame **22b**.

(152) The rotating portion **261b** is provided with a through hole (not marked in the figure) and a second spiral groove **265b**. A structure of the rotating portion **261b** is adapted to a structure of the second rotating groove **104b**. In addition, the second connection assembly **20b** further includes a second rotating shaft **282b**, and the second rotating shaft **282b** runs through the through hole of the rotating portion **261b**. Specifically, the second rotating shaft **282b** may be mounted in the second rotating groove **104b**. The rotating portion **261b** may rotate relative to the second rotating shaft **282b**, to implement a rotatable connection between the rotating portion **261b** and the base **10**, and further implement a rotatable connection between the second secondary swing arm **26b** and the base **10**.

(153) The second rotating shaft **282b** is a circular shaft, an axis of the second rotating shaft **282b** is parallel to the Y-axis direction, and the second rotating shaft **282b** is coaxial with the second rotating shaft **282a** (as shown in FIG. **11** and FIG. **12**). In this case, the rotation center of the rotating portion **261b** of the second secondary swing arm **26b** relative to the base **10** is the axis of the second rotating shaft **282b**. That is, the rotation center of the second secondary swing arm **26b** relative to the base **10** is the axis of the second rotating shaft **282b**.

(154) When the first fixing frame **21b** and the second fixing frame **22b** rotate relative to the base

10, the first fixing frame **21b** drives the first primary swing arm **23b** to rotate relative to the first fixing frame **21b**, drives the first primary swing arm **23b** to slide and rotate relative to the base **10**, further drives the first secondary swing arm **25b** to slide relative to the first fixing frame **21b**, and further drives the first secondary swing arm **25b** to rotate relative to the base **10**; and the second fixing frame **22b** drives the second primary swing arm **24b** to rotate relative to the second fixing frame **22b**, drives the second primary swing arm **24b** to slide and rotate relative to the base **10**, further drives the second secondary swing arm **26a** to slide relative to the second fixing frame **22b**, and further drives the second secondary swing arm **26a** to rotate relative to the base **10**, to implement mutual switching of the second connection assembly **20b** between the folded state and the flattened state.

(155) In this embodiment, the second damping assembly **30b** and the first damping assembly **30a** (as shown in FIG. **11** and FIG. **12**) have a same structure. The first damping member **31b** includes a first fixing portion **311b**, a second fixing portion **312b**, a third fixing portion **313b**, a first connecting portion **314b**, and a second connecting portion **315b**. For the first fixing portion **311b**, the second fixing portion **312b**, the third fixing portion **313b**, the first connecting portion **314b**, and the second connecting portion **315b**, respectively refer to related description of the first fixing portion **311a**, the second fixing portion **312a**, the third fixing portion **313a**, the first connecting portion **314a**, and the second connecting portion **315a** (as shown in FIG. **11** and FIG. **12**) in the first damping member **31a** in the above, and details are not described herein again.

(156) Specifically, the first fixing portion **311b** is mounted in the first mounting groove **214b**, and the second fixing portion **312b** is mounted in the second mounting groove **215b**, to implement assembly between the first damping member **31b** and the first fixing frame **21b**. The third fixing portion **313b** is fixedly connected to the sliding portion **253b** of the first secondary swing arm **25b**, to implement a fixed connection between the first damping member **31b** and the first secondary swing arm **25b**. The first fixing block **218b** is mounted in the first fixing hole **316b**, the second fixing block **219b** is mounted in the second fixing hole **317b**, and the third fixing block **254b** is mounted in the third fixing hole **318b**.

(157) The second damping member **32b** includes a first fixing portion **321b**, a second fixing portion **322b**, a third fixing portion **323b**, a first connecting portion **324b**, and a second connecting portion **325b**. For the first fixing portion **321b**, the second fixing portion **322b**, the third fixing portion **323b**, the first connecting portion **324b**, and the second connecting portion **325b**, respectively refer to related description of the first fixing portion **311b**, the second fixing portion **312b**, the third fixing portion **313b**, the first connecting portion **314b**, and the second connecting portion **315b** (as shown in FIG. **11** and FIG. **12**) in the first damping member **31b** in the above, and details are not described herein again.

(158) The first fixing portion **321b** is mounted in the first mounting groove **224b**, and the second fixing portion **322b** is mounted in the second mounting groove **225b**, to implement assembly between the second damping member **32b** and the second fixing frame **22b**. The third fixing portion **323b** is fixedly connected to the sliding portion **263b** of the second secondary swing arm **26b**, to implement a fixed connection between the second damping member **32b** and the second secondary swing arm **26b**. The first fixing block **228b** is mounted in the first fixing hole **326b**, the second fixing block **229b** is mounted in the second fixing hole **327b**, and the third fixing block **264b** is mounted in the third fixing hole **328b**.

(159) In this embodiment, the second synchronization assembly **60b** and the first synchronization assembly **60a** have a same structure. The second synchronization assembly **60b** includes a fixing column **61b** and a synchronization slider **62b**. Specifically, the second synchronization assembly **60b** is mounted in the communication groove **107b**. The fixing column **61b** and the synchronization slider **62b** are both mounted in the communication groove **107b**, and a first cam **63b** is mounted in the first spiral groove **255b** and may slide relative to the rotating portion **251b** in the first spiral groove **255b**. A second cam **64b** is mounted in the second spiral groove **265b** and may slide relative

to the rotating portion **261b** in the second spiral groove **265b**. For structures of components of the second synchronization assembly **60b**, and connection relationships between the components and the second connection assembly **20b**, refer to related description of the first synchronization assembly **60a**.

(160) Refer to FIG. **10**, FIG. **15**, and FIG. **16**, FIG. **15** is a schematic structural diagram of the third connection assembly **20c** in the foldable mechanism **130** shown in FIG. **6**, and FIG. **16** is a schematic structural diagram of the third connection assembly **20c** shown in FIG. **15** from another perspective.

(161) The first fixing frame **21c** is provided with a receiving notch **211c**, a mounting notch **212c**, and a guiding groove **213c**. For structures of the receiving notch **211c**, the mounting notch **212c**, and the guiding groove **213c**, respectively refer to related description of the receiving notch **211a**, the mounting notch **212a**, and the guiding groove **217a** (as shown in FIG. **11** and FIG. **12**) in the first fixing frame **21a** in the above, and details are not described herein again. The mounting notch **212c** is located in a middle portion of the first fixing frame **21c**.

(162) The first primary swing arm **23c** includes a rotating portion **231c**, a connection portion **232c**, and a sliding portion **233c**, where the connection portion **232c** is connected between the rotating portion **231c** and the sliding portion **233c**. For a structure of the first primary swing arm **23c**, refer to related description of the first primary swing arm **23a** (as shown in FIG. **11** and FIG. **12**) in the above, and details are not described herein again.

(163) The rotating portion **231c** includes two sub-rotating portions **234c**. A structure of the rotating portion **231c** is adapted to a structure of the mounting notch **212c**. In addition, the third connection assembly **20c** further includes a first pin shaft **251c**, and the first pin shaft **251c** may run through holes (not shown in the figure) of the two sub-rotating portions **234c**. Specifically, the first pin shaft **251c** may be mounted in the mounting notch **212c**. The first pin shaft **251c** is a circular shaft, an axis of the first pin shaft **251c** is parallel to the Y-axis direction, and the first pin shaft **251c** is coaxial with the first pin shaft **271a** (as shown in FIG. **11** and FIG. **12**). The two sub-rotating portions **234c** may rotate relative to the first pin shaft **251c**, to implement a rotatable connection between the rotating portion **231c** and the first pin shaft **251c**, and further implement a rotatable connection between the first primary swing arm **23c** and the first fixing frame **21c**.

(164) A structure of the sliding portion **233c** is adapted to a structure of the first sliding groove **101c**. The sliding portion **233c** is mounted in the first sliding groove **101c**, and may slide and rotate in the first sliding groove **101c**, to implement a slidable and rotatable connection between the sliding portion **233c** and the base **10**, and further implement a slidable and rotatable connection between the first primary swing arm **23c** and the base **10**. In this case, the sliding portion **233c** and the first sliding groove **101c** are coaxial.

(165) The second fixing frame **22c** is provided with a receiving notch **221c**, a mounting notch **222c**, and a guiding groove **223c**. In this embodiment, for structures of the receiving notch **221c**, the mounting notch **222c**, and the guiding groove **223c**, refer to related description of the receiving notch **211c**, the mounting notch **212c**, and the guiding groove **213c** of the first fixing frame **21c** in the above, and details are not described herein again. The receiving notch **221c** further runs through a left side surface of the second fixing frame **22c**. An opening of the mounting notch **222c** is located on the left side surface of the second fixing frame **22c**.

(166) The second primary swing arm **24c** includes a rotating portion **241c**, a connection portion **242c**, and a sliding portion **243c**, where the connection portion **242c** is connected between the rotating portion **241c** and the sliding portion **243c**. For a structure of the second primary swing arm **24c**, refer to related description of the first primary swing arm **23c** in the above, and details are not described herein again.

(167) The rotating portion **241c** includes two sub-rotating portions **244c**. A structure of the rotating portion **241c** is adapted to a structure of the mounting notch **222c**. In addition, the third connection assembly **20c** further includes a second pin shaft **252c**, and the second pin shaft **252c** may run

through through holes (not shown in the figure) of the two sub-rotating portions **244c**. Specifically, the second pin shaft **252C** may be mounted in the mounting notch **222c**. The second pin shaft **252C** is a circular shaft, an axis of the second pin shaft **252C** is parallel to the Y-axis direction, and the second pin shaft **252C** is coaxial with the second pin shaft **272a** (as shown in FIG. **11** and FIG. **12**). The two sub-rotating portions **244c** may rotate relative to the second pin shaft **252c**, to implement a rotatable connection between the rotating portion **241C** and the second pin shaft **252c**, and further implement a rotatable connection between the second primary swing arm **24c** and the second fixing frame **22c**.

(168) A structure of the sliding portion **243c** is adapted to a structure of the second sliding groove **102c**. The sliding portion **243c** is mounted in the second sliding groove **102c**, and may slide and rotate in the second sliding groove **102c**, to implement a slidable and rotatable connection between the sliding portion **243c** and the base **10**, and further implement a slidable and rotatable connection between the second primary swing arm **24c** and the base **10**. In this case, the sliding portion **243c** and the second sliding groove **102c** are coaxial.

(169) When the first fixing frame **21c** and the second fixing frame **22C** rotate relative to the base **10**, the first fixing frame **21c** drives the first primary swing arm **23c** to rotate relative to the first fixing frame **21c**, and drives the first primary swing arm **23c** to slide and rotate relative to the base **10**; and the second fixing frame **22c** drives the second primary swing arm **24c** to rotate relative to the second fixing frame **22c**, and drives the second primary swing arm **24c** to slide and rotate relative to the base **10**, to implement mutual switching of the third connection assembly **20c** between the folded state and the flattened state.

(170) Refer to FIG. **17** and FIG. **18**, FIG. **17** is a schematic structural diagram of the pressing plate assembly **40** in the foldable mechanism **130** shown in FIG. **6**, and FIG. **18** is a schematic structural diagram of the pressing plate assembly **40** shown in FIG. **17** from another perspective.

(171) The first pressing plate **41** includes a support portion **411**, an assistance portion **412**, and a guiding slider **413**, where the assistance portion **412** and the guiding slider **413** are both fixedly connected to the support portion **411**. The first pressing plate **41** is an integrally formed structural member, to improve the structural strength of the first pressing plate **41** and ensure the structure stability of the first pressing plate **41**.

(172) The integrally formed first pressing plate **41** can reduce structural members of the foldable mechanism **130**, facilitates assembly of the foldable mechanism **130**, and reduces costs of the foldable mechanism **130**, which is conducive to a small-scale design of the foldable mechanism **130**. In addition, a weight of the integrally formed first pressing plate **41** is relatively small, which is conducive to implement a lightweight design of the foldable mechanism **130**.

(173) In some other embodiments, the first pressing plate **41** may alternatively be an integral structural member formed in an assembling manner. For example, the assistance portion **412** and the guiding slider **413** may be fixedly connected to the support portion **411** through soldering or adhesion.

(174) The support portion **411** is approximately in a shape of a strip-shaped plate. In this embodiment, the support portion **411** extends in the Y-axis direction. The assistance portion **412** is fixedly connected to a bottom surface of the support portion **411**. The assistance portion **412** is provided with a sliding hole **414**, and an opening of the sliding hole **414** is located on a right side surface of the assistance portion **412**. The sliding hole **414** is recessed in a direction from the right side surface to a left side surface of the assistance portion **412** (the X-axis negative direction shown in the figure), and runs through the left side surface of the assistance portion **412**. That is, the sliding hole **414** runs through the assistance portion **412** in the X-axis direction. For example, the sliding hole **414** is a square hole.

(175) In some other embodiments, the sliding hole **414** may alternatively not run through the left side surface of the first pressing plate **41**, or the assistance portion **412** may alternatively enclose with the support portion **411** to form the sliding hole **414**. A specific formation manner of the

sliding hole **414** is not limited in this application.

(176) In this embodiment, there are four assistance portions **412**, and the four assistance portions **412** are sequentially arranged at intervals in the Y-axis direction. The four assistance portions **412** are respectively a front assistance portion **412a**, a rear assistance portion **412b**, and middle assistance portions **412c**, where there are two middle assistance portions **412c**. The front assistance portion **412a** is fixedly connected to a front side of the support portion **411**, the rear assistance portion **412b** is fixedly connected to a rear side of the support portion **411**, and the two middle assistance portions **412c** are fixedly connected to a middle portion of the support portion **411**. In some other embodiments, there may alternatively be one, two, three, or at least five assistance portions **412**, and a quantity of the assistance portions **412** is not specifically limited in this application.

(177) The guiding slider **413** is fixedly connected to the bottom surface of the support portion **411**, and is disposed at intervals with the assistance portion **412**. The guiding slider **413** extends in a direction from the bottom surface to be away from a top surface of the support portion **411**. A structure of the guiding slider **413** is adapted to a structure of a guiding groove (for example, the guiding groove **217a** shown in FIG. 11, the guiding groove **217b** shown in FIG. 13, and the guiding groove **213c** shown in FIG. 15). A bottom surface of the guiding slider **413** is an arc-shaped surface.

(178) In this embodiment, there are six guiding sliders **413**, and the six guiding sliders **413** are sequentially arranged at intervals in the Y-axis direction. The six guiding sliders **413** are respectively two front guiding sliders **413a**, two rear guiding sliders **413b**, and two middle guiding sliders **413c**. The two front guiding sliders **413a** are fixedly connected to the front side of the support portion **411**, and are located on two opposite sides of the front assistance portion **412a**. The two rear guiding sliders **413b** are fixedly connected to the rear side of the support portion **411**, and are located on two opposite sides of the rear assistance portion **412b**. The two middle guiding sliders **413c** are fixedly connected to the middle portion of the support portion **411**, are located between the two assistance portions **412c**, and are disposed at intervals with the middle assistance portions **412c**. In some other embodiments, there may alternatively be less than five or at least seven guiding sliders **413**, and a quantity of the guiding sliders **413** is not specifically limited in this application.

(179) In this embodiment, the four first pressing plate swing arms **43** are respectively a first front pressing plate swing arm **43a**, a first rear pressing plate swing arm **43b**, and first middle pressing plate swing arms **43c**, where there are two first middle pressing plate swing arms **43c**. In some other embodiments, there may alternatively be less than three or at least five first pressing plate swing arms **43**, and a quantity of the first pressing plate swing arms **43** is not specifically limited in this application.

(180) The first front pressing plate swing arm **43a** includes a rotating portion **431a**, a connection portion **432a**, and a sliding portion **433a**, where the connection portion **432a** is connected between the rotating portion **431a** and the sliding portion **433a**. The sliding portion **433a** is in a shape of a flat plate. A structure of the sliding portion **433a** is adapted to a structure of the sliding hole **414** of the front assistance portion **412a**. The sliding portion **433a** may run through the sliding hole **414** of the front assistance portion **412a**, and may slide relative to the first pressing plate **41** in the sliding hole **414** of the front assistance portion **412a**, to implement a slidable connection between the first front pressing plate swing arm **43a** and the first pressing plate **41**.

(181) The connection portion **432a** is provided with an assembly hole **434a**, and an opening of the assembly hole **434a** is located on a top surface of the connection portion **432a**. The assembly hole **434a** is recessed in a direction from the top surface to a bottom surface of the connection portion **432a** (the Z-axis negative direction shown in the figure), and runs through the bottom surface of the connection portion **432a**. That is, the assembly hole **434a** runs through the connection portion **432a** in a thickness direction of the connection portion **432a** (the Z-axis direction shown in the figure).

For example, the assembly hole **434a** is a circular hole. In some other embodiments, the assembly hole **434a** may alternatively not run through the bottom surface of the connection portion **432a**, and/or the assembly hole **434a** may alternatively be a square hole or a special-shaped hole.

(182) A structure of the rotating portion **431a** is adapted to a structure of the first engagement groove **105a** (as shown in FIG. 8). In this embodiment, the rotating portion **431a** is in a shape of an arc-shaped plate, and an axis of the rotating portion **431a** is parallel to the Y-axis direction. The rotating portion **431a** is mounted in the first engagement groove **105a**, and may slide and rotate in the first engagement groove **101a**, to implement a slidable and rotatable connection between the first front pressing plate swing arm **43a** and the base **10**. In this case, the rotating portion **431a** and the first engagement groove **105a** are coaxial. A rotation center of the first front pressing plate swing arm **43a** relative to the base **10** is parallel to the Y-axis direction.

(183) It may be understood that, since the base **10** is an integrally formed structural member, the first engagement groove **105a** does not need to be formed through cooperation of a shaft cover and a holder. In the foldable mechanism **130**, a sum of a thickness of the first engagement groove **105a** and a thickness of the rotating portion **431a** is relatively small, so that space occupied by the foldable mechanism **130** can be reduced, which is conducive to implement a light and thin design of the foldable mechanism **130**.

(184) The first rear pressing plate swing arm **43b** and the first front pressing plate swing arm **43a** have a same structure. A connection portion **432b** of the first rear pressing plate swing arm **43b** is provided with an assembly hole **434b**. A structure of a sliding portion **433b** in the first rear pressing plate swing arm **43b** is adapted to a structure of the sliding hole **414** of the rear assistance portion **412b**. The sliding portion **433b** may run through the sliding hole **414** of the rear assistance portion **412b**, and may slide relative to the first pressing plate **41** in the sliding hole **414** of the rear assistance portion **412b**, to implement a slidable connection between the first rear pressing plate swing arm **43b** and the first pressing plate **41**. A structure of a rotating portion **431b** in the first rear pressing plate swing arm **43b** is adapted to a structure of the first engagement groove **105b** (as shown in FIG. 9). The rotating portion **431b** is mounted in the first engagement groove **105b**, and may slide and rotate in the first engagement groove **105b**, to implement a slidable and rotatable connection between the first rear pressing plate swing arm **43b** and the base **10**. In this case, the rotating portion **431b** and the first engagement groove **105b** are coaxial. A rotation center of the first rear pressing plate swing arm **43b** relative to the base **10** is parallel to the Y-axis direction, and is coaxial with the rotation center of the first front pressing plate swing arm **43a** relative to the base **10**.

(185) The first middle pressing plate swing arm **43c** and the first front pressing plate swing arm **43a** have a same structure. A connection portion **432c** of the first middle pressing plate swing arm **43c** is provided with an assembly hole **434c**. A structure of a sliding portion **433c** in the first middle pressing plate swing arm **43c** is adapted to a structure of the sliding hole **414** of the middle assistance portion **412c**. The sliding portions **433c** of the two first middle pressing plate swing arms **43c** may respectively run through the sliding holes **414** of the two middle assistance portions **412c**, and may slide relative to the first pressing plate **41** in the sliding holes **414**, to implement a slidable connection between the two first middle pressing plate swing arms **43c** and the first pressing plate **41**. A structure of a rotating portion **431c** in the first middle pressing plate swing arm **43c** is adapted to a structure of the first engagement groove **105c** (as shown in FIG. 1). The rotating portions **431c** of the two first middle pressing plate swing arms **43c** may be respectively mounted in two first engagement grooves **105c**, and may slide and rotate in the first engagement grooves **105c**, to implement a rotatable connection between the two first middle pressing plate swing arms **43c** and the base **10**. In this case, the rotating portion **431c** and the first engagement groove **105c** are coaxial. A rotation center of the first middle pressing plate swing arm **43c** relative to the base **10** is parallel to the Y-axis direction, and is coaxial with the rotation center of the first front pressing plate swing arm **43a** relative to the base **10**.

(186) Refer to FIG. 11, FIG. 13, and FIG. 15 together, the front side of the support portion **411** may be received in the receiving notch **211a** of the first fixing frame **21a**, the rear side of the support portion **411** may be received in the receiving notch **211b** of the first fixing frame **21b**, and the middle portion of the support portion **411** may be received in the receiving notch **211c** of the first fixing frame **21c**.

(187) The front assistance portion **412a** may be received in the avoidance groove **216a** of the first fixing frame **21a**. The sliding hole **414** of the front assistance portion **412a** is in communication with the sliding hole **2161a** of the first fixing frame **21a**, and the sliding portion **433a** of the first front pressing plate swing arm **43a** may also run through the sliding hole **2161a** of the first fixing frame **21a** and may slide relative to the first fixing frame **21a** in the sliding hole **2161a**.

(188) The rear assistance portion **412b** may be received in the avoidance groove **216b** of the first fixing frame **21b**. The sliding hole **414** of the rear assistance portion **412b** is in communication with the sliding hole **2161b** of the first fixing frame **21b**, and the sliding portion **433b** of the first rear pressing plate swing arm **43b** may also run through the sliding hole **2161b** of the first fixing frame **21b** and may slide relative to the first fixing frame **21b** in the sliding hole **2161b**.

(189) The two front guiding sliders **413a** may be respectively mounted in the two guiding grooves **217a** of the first fixing frame **21a**, and may slide and rotate in the guiding grooves **217a**, to implement a slidable and rotatable connection between the first pressing plate **41** and the first fixing frame **21a**. The two rear guiding sliders **413b** may be respectively mounted in the two guiding grooves **217b** of the first fixing frame **21b**, and may slide and rotate in the guiding grooves **217b**, to implement a slidable and rotatable connection between the first pressing plate **41** and the first fixing frame **21b**. The two middle guiding sliders **413c** may be respectively mounted in the two guiding grooves **213c** of the first fixing frame **21c**, and may slide and rotate in the guiding grooves **213c**, to implement a slidable and rotatable connection between the first pressing plate **41** and the first fixing frame **21c**.

(190) The second pressing plate **42** and the first pressing plate **41** have a same structure. The second pressing plate **42** includes a support portion **421**, an assistance portion **422**, and a guiding slider **423**, where the assistance portion **422** and the guiding slider **423** are both fixedly connected to the support portion **421**. For structures of the support portion **421**, the assistance portion **422**, and the guiding slider **423**, refer to related description of the support portion **411**, the assistance portion **412**, and the guiding slider **413** in the first pressing plate **41** in the above, and details are not described herein again. The assistance portion **422** is provided with a sliding hole **424**.

(191) The second pressing plate swing arm **44** and the first pressing plate swing arm **43** have a same structure. In this embodiment, there are four second pressing plate swing arms **44**, and the four second pressing plate swing arms **44** are respectively a second front pressing plate swing arm **44a**, a second rear pressing plate swing arm **44b**, and second middle pressing plate swing arms **44c**, where there are two second middle pressing plate swing arms **44c**.

(192) A connection portion **442a** of the second front pressing plate swing arm **44a** is provided with an assembly hole **444a**. A structure of a sliding portion **443a** in the second front pressing plate swing arm **44a** is adapted to a structure of the sliding hole **424** of a front assistance portion **422a**. The sliding portion **443a** may run through the sliding hole **424** of the front assistance portion **422a**, and may slide relative to the second pressing plate **42** in the sliding hole **424** of the front assistance portion **422a**, to implement a slidable connection between the second front pressing plate swing arm **44a** and the second pressing plate **42**. A structure of a rotating portion **441a** of the second front pressing plate swing arm **44a** is adapted to a structure of the second engagement groove **106a**. The rotating portion **441a** may be mounted in the second engagement groove **106a** (as shown in FIG. 8), and may slide and rotate in the second engagement groove **106a**, to implement a rotatable connection between the second front pressing plate swing arm **44a** and the base **10**. In this case, the rotating portion **441a** and the second engagement groove **106a** are coaxial. A rotation center of the second front pressing plate swing arm **44a** relative to the base **10** is parallel to the Y-axis direction,

and is disposed at intervals with the rotation center of the first front pressing plate swing arm **43a** relative to the base **10**.

(193) It may be understood that, since the base **10** is an integrally formed structural member, the second engagement groove **106a** does not need to be formed through cooperation of a shaft cover and a holder. In the foldable mechanism **130**, a sum of a thickness of the second engagement groove **106a** and a thickness of the rotating portion **441a** is relatively small, so that space occupied by the foldable mechanism **130** can be reduced, which is conducive to implement a light and thin design of the foldable mechanism **130**.

(194) The second rear pressing plate swing arm **44b** and the second front pressing plate swing arm **44a** have a same structure. A connection portion **442b** of the second rear pressing plate swing arm **44b** is provided with an assembly hole **444b**. A structure of a sliding portion **443b** of the second rear pressing plate swing arm **44b** is adapted to a structure of the sliding hole **424** of a rear assistance portion **422b**. The sliding portion **443b** may run through the sliding hole **424** of the rear assistance portion **422b**, and may slide relative to the second pressing plate **42** in the sliding hole **424** of the rear assistance portion **422b**, to implement a slidable connection between the second rear pressing plate swing arm **44b** and the second pressing plate **42**. A structure of a rotating portion **441b** of the second rear pressing plate swing arm **44b** is adapted to a structure of the second engagement groove **106b** (as shown in FIG. 9). The rotating portion **441b** is mounted in the second engagement groove **106b**, and may slide and rotate in the second engagement groove **106b**, to implement a slidable and rotatable connection between the second rear pressing plate swing arm **44b** and the base **10**. In this case, the rotating portion **441b** and the second engagement groove **106b** are coaxial. A rotation center of the second rear pressing plate swing arm **44b** relative to the base **10** is parallel to the Y-axis direction, and is coaxial with the rotation center of the second front pressing plate swing arm **44a** relative to the base **10**.

(195) The second middle pressing plate swing arm **44c** and the second front pressing plate swing arm **44a** have a same structure. A connection portion **442c** of the second middle pressing plate swing arm **44c** is provided with an assembly hole **444c**. A structure of a sliding portion **443c** in the second middle pressing plate swing arm **44c** is adapted to a structure of the sliding hole **424** of a middle assistance portion **422c**. The sliding portions **443c** of the two second middle pressing plate swing arms **44c** may respectively run through the sliding holes **424** of the two middle assistance portions **422c**, and may slide relative to the second pressing plate **42** in the sliding holes **424**, to implement a slidable connection between each of the two second middle pressing plate swing arms **44c** and the second pressing plate **42**. A structure of a rotating portion **441c** of the second middle pressing plate swing arm **44c** is adapted to a structure of the second engagement groove **106c** (as shown in FIG. 10). The rotating portions **441c** of the two second middle pressing plate swing arms **44c** may be respectively mounted in one second engagement groove **106c**, and may slide and rotate in the second engagement grooves **106c**, to implement a rotatable connection between the two second middle pressing plate swing arms **44c** and the base **10**. In this case, the rotating portion **441c** and the second engagement groove **106c** are coaxial. A rotation center of the second middle pressing plate swing arm **44c** relative to the base **10** is parallel to the Y-axis direction, and is coaxial with the rotation center of the second front pressing plate swing arm **44a** relative to the base **10**.

(196) Refer to FIG. 11, FIG. 13, and FIG. 15 together, in this embodiment, the front side of the support portion **421** may be received in the receiving notch **221a** of the second fixing frame **22a**, the rear side of the support portion **421** may be received in the receiving notch **221b** of the second fixing frame **22b**, and the middle portion of the support portion **421** may be received in the receiving notch **221c** of the second fixing frame **22c**.

(197) The front assistance portion **422a** may be received in the avoidance groove **226a** of the second fixing frame **22a**. The sliding hole **424** of the front assistance portion **422a** is in communication with the sliding hole **2261a** of the second fixing frame **22a**, and the sliding portion **443a** of the second front pressing plate swing arm **44a** may also run through the sliding hole **2261a**

of the second fixing frame **22a** and may slide relative to the second fixing frame **22a** in the sliding hole **2261a**.

(198) The rear assistance portion **422b** may be received in the avoidance groove **226b** of the second fixing frame **22b**. The sliding hole **424** of the rear assistance portion **422b** is in communication with the sliding hole **2261b** of the second fixing frame **22b**, and the sliding portion **443b** of the second rear pressing plate swing arm **44b** may also run through the sliding hole **2261a** of the second fixing frame **22b** and may slide relative to the second fixing frame **22b** in the sliding hole **2261a**.

(199) The two front guiding sliders **423a** may be respectively mounted in the two guiding grooves **227a** of the second fixing frame **22a**, and may slide and rotate in the guiding grooves **227a**, to implement a slidable and rotatable connection between the second pressing plate **42** and the second fixing frame **22a**. The two rear guiding sliders **423b** may be respectively mounted in the two guiding grooves **227b** of the second fixing frame **22b**, and may slide and rotate in the guiding grooves **227b**, to implement a slidable and rotatable connection between the second pressing plate **42** and the second fixing frame **22b**. The two middle guiding sliders **423c** may be respectively mounted in the two guiding grooves **223c** of the second fixing frame **22c**, and may slide and rotate in the guiding grooves **223c**, to implement a slidable and rotatable connection between the second pressing plate **42** and the second fixing frame **22c**.

(200) It should be noted that, engagement relationships between the pressing plate assembly **40** and the first connection assembly **20a**, the second connection assembly **20b**, and the third connection assembly **20c** are approximately the same. To avoid repetition, description is provided below by using the engagement relationship between the pressing plate **40** and the first connection assembly **20a** as an example.

(201) When the first fixing frame **21a** and the second fixing frame **22a** rotate relative to the base **10** (as shown in FIG. 7), the first fixing frame **21a** drives the first pressing plate **41** to slide and rotate relative to the first fixing frame **21a**, and further drives the first pressing plate **41** to slide relative to the first pressing plate swing arm **43**, to drive the first pressing plate **41** and the first pressing plate swing arm **43** to rotate relative to the base **10**; and the second fixing frame **22a** drives the second pressing plate **42** to slide and rotate relative to the second fixing frame **22a**, and further drives the second pressing plate **42** to slide relative to the second pressing plate swing arm **44**, to drive the second pressing plate **42** and the second pressing plate swing arm **44** to rotate relative to the base **10**, thereby implementing mutual switching of the pressing plate assembly **40** between the folded state and the flattened state.

(202) Refer to FIG. 19 and FIG. 20, FIG. 19 is a schematic structural diagram of the flexible support plate **50** in the foldable mechanism **130** shown in FIG. 6, and FIG. 20 is a schematic structural diagram of the flexible support plate **50** shown in FIG. 19 from another perspective.

(203) The flexible support plate **50** includes a flexible support portion **51**, a first fixing portion **52**, and a second fixing portion **53**, where the first fixing portion **52** and the second fixing portion **53** are both fixedly connected to the flexible support portion **51**. The flexible support plate **50** may be an integrally formed structural member, to reduce a quantity of components of the flexible support plate **50**. In this way, assembly of the flexible support plate **50** is facilitated, and manufacturing costs of the flexible support plate **50** may also be reduced. It may be understood that, a partial thickness of the flexible support plate **50** may be very thin, to reduce a thickness of the flexible support plate **50**, which is conducive to reduce a thickness of the foldable mechanism **130**, and implements a light and thin design of the foldable mechanism **130**.

(204) The flexible support portion **51** is in a shape of a strip-shaped plate. The flexible support portion **51** extends in the Y-axis direction and may bend around the Y-axis direction. The flexible support portion **51** is provided with a plurality of strip-shaped grooves **511**, and an opening of each strip-shaped groove **511** is located on a bottom surface of the flexible support portion **51**, to ensure the integrity of a top surface of the flexible support portion **51**. Specifically, the opening of each strip-shaped groove **511** is located in a middle region of the bottom surface of the flexible support

portion **51**. The strip-shaped groove **511** is recessed in a direction from the bottom surface to the top surface of the flexible support portion **51** (the Z-axis negative direction shown in the figure), and runs through a front side surface and a rear side surface of the flexible support portion **51**. In the X-axis direction, the plurality of strip-shaped grooves **511** are parallel to each other and are arranged at intervals. An extending direction of the strip-shaped groove **511** is parallel to the Y-axis direction, to improve the flexibility of the flexible support portion **51**, which is conducive to bending of the flexible support portion **51** in the Y-axis direction. In some other embodiments, openings of the plurality of strip-shaped grooves **511** may alternatively be located on the top surface of the flexible support portion **51**.

(205) In addition, the flexible support portion **51** is further provided with a first avoidance groove **512**, a second avoidance groove **513**, a third avoidance groove **514**, and a fourth avoidance groove **515**. Openings of the first avoidance groove **512**, the second avoidance groove **513**, the third avoidance groove **514**, and the fourth avoidance groove **515** are all located on the bottom surface of the flexible support portion **51**, and are all in communication with one or more strip-shaped grooves **511**.

(206) In this embodiment, there are three first avoidance grooves **512**, and the first avoidance grooves **512** are all located on a left side of the flexible support portion **51**. In the Y-axis direction, the three first avoidance grooves **512** are arranged at intervals. The three first avoidance grooves **512** are respectively a first front avoidance groove **512a**, a first rear avoidance groove **512b**, and a first middle avoidance groove **512c**. The first front avoidance groove **512a** is located on a front side of the flexible support portion **51**, the first rear avoidance groove **512b** is located on a rear side of the flexible support portion **51**, and the first middle avoidance groove **512c** is located on a middle portion of the flexible support portion **51**.

(207) There are three second avoidance grooves **513**, and the three second avoidance grooves **513** are all located on a right side of the flexible support portion **51**. In the Y-axis direction, the three second avoidance grooves **513** are arranged at intervals. The three second avoidance grooves **513** are respectively a second front avoidance groove **513a**, a second rear avoidance groove **513b**, and a second middle avoidance groove **513c**. The second front avoidance groove **513a** is located on the front side of the flexible support portion **51**, is located on one side of the first front avoidance groove **512a** facing the Y-axis negative direction, and is disposed at intervals with the first front avoidance groove **512a**. The second rear avoidance groove **513b** is located on the rear side of the flexible support portion **51**, is located on one side of the first rear avoidance groove **512b** facing the Y-axis negative direction, and is disposed at intervals with the first rear avoidance groove **512b**. The second middle avoidance groove **513c** is located on the middle portion of the flexible support portion **51**, is located on one side of the first middle avoidance groove **512c** facing the Y-axis negative direction, and is disposed at intervals with the first middle avoidance groove **512c**.

(208) There are two third avoidance grooves **514** and two fourth avoidance grooves **515**. The two third avoidance grooves **514** are respectively a third front avoidance groove **514a** and a third rear avoidance groove **514b**, and the two fourth avoidance grooves **515** are respectively a fourth front avoidance groove **515a** and a fourth rear avoidance groove **515b**. The third front avoidance groove **514a** and the fourth front avoidance groove **515a** are both located on the front side of the flexible support portion **51**, are both located on one side of the second front avoidance groove **513a** away from the first front avoidance groove **512a**, and are both disposed at intervals with the second front avoidance groove **513a**. The third rear avoidance groove **514b** and the fourth rear avoidance groove **515b** are both located on the rear side of the flexible support portion **51**, are both located on one side of the second rear avoidance groove **513b** away from the first rear avoidance groove **512b**, and are both disposed at intervals with the second rear avoidance groove **513b**. In the X-axis direction, the third front avoidance groove **514a** and the fourth front avoidance groove **515a** are disposed at intervals and opposite to each other, and the third rear avoidance groove **514b** and the fourth rear avoidance groove **515b** are disposed at intervals and opposite to each other.

(209) The first fixing portion **52** is fixedly connected to the bottom surface of the flexible support portion **51**, and is disposed at intervals with the strip-shaped groove **511**. Specifically, the first fixing portion **52** is fixedly connected to an edge region of a bottom portion of the flexible support portion **51**. The first fixing portion **52** extends in a direction from the bottom surface to be away from the top surface of the flexible support portion **51** (the Z-axis positive direction shown in the figure). For example, the first fixing portion **52** is in a shape of a cylinder.

(210) In this embodiment, there are four first fixing portions **52**, the four first fixing portions **52** are all fixedly connected to the left side of the flexible support portion **51**, and in the Y-axis direction, the four first fixing portions **52** are arranged at intervals. The four first fixing portions **52** are respectively a first front fixing portion **52a**, a first rear fixing portion **52b**, and first middle fixing portions **52c**, where there are two first middle fixing portions **52c**. The first front fixing portion **52a** is fixedly connected to the front side of the flexible support portion **51**, is located on one side of the first front avoidance groove **512a** away from the third front avoidance groove **514a**, and is disposed at intervals with the first front avoidance groove **512a**. The first rear fixing portion **52b** is fixedly connected to the rear side of the flexible support portion **51**, is located on one side of the first rear avoidance groove **512b** away from the third rear avoidance groove **514b**, and is disposed at intervals with the second rear avoidance groove **513b**. The two first middle fixing portions **52c** are both fixedly connected to the middle portion of the flexible support portion **51**, are respectively located on two opposite sides of the first middle avoidance groove **512c**, and are both disposed at intervals with the first middle avoidance groove **512c**.

(211) The second fixing portion **53** is fixedly connected to the bottom surface of the flexible support portion **51**, and is disposed at intervals with both the strip-shaped groove **511** and the first fixing portion **52**. In this embodiment, for a structure of the second fixing portion **53** and a relationship between the second fixing portion **53** and the flexible support portion **51**, refer to related description of the first fixing portion **52**, and details are not described herein again. There are four second fixing portions **53**, and the four second fixing portions **53** are all fixedly connected to the right side of the flexible support portion **51**. In the Y-axis direction, the four second fixing portions **53** are arranged at intervals. The four second fixing portions **53** are respectively a second front fixing portion **53a**, a second rear fixing portion **53b**, and second middle fixing portions **53c**, where there are two second middle fixing portions **53c**.

(212) Refer to FIG. 17 and FIG. 18 together, the first front fixing portion **52a** is mounted in the assembly hole **434a** of the first front pressing plate swing arm **43a**, the first rear fixing portion **52b** is mounted in the assembly hole **434b** of the first rear pressing plate swing arm **43b**, the two first middle fixing portions **52c** are respectively mounted in the assembly holes **434c** of the two first middle pressing plate swing arms **43c**, the second front fixing portion **53a** is mounted in the assembly hole **444a** of the second front pressing plate swing arm **44a**, the second rear fixing portion **53b** is mounted in the assembly hole **444b** of the second rear pressing plate swing arm **44b**, and the two second middle fixing portions **53c** are respectively mounted in the assembly holes **444c** of the two second middle pressing plate swing arms **44c**, to implement assembly between the flexible support plate **50** and the pressing plate assembly **40**.

(213) When the pressing plate assembly **40** is switched between the folded state and the unfolded state, the first pressing plate swing arm **43** and the second pressing plate swing arm **44** both rotate relative to the base **10** (as shown in FIG. 7), to drive the first fixing portion **52** and the second fixing portion **53** to rotate relative to the base **10**, and further drive the flexible support portion **51** to be relatively folded or unfolded. In other words, the flexible support plate **50** may be relatively folded or unfolded under driving of the pressing plate assembly **40**. That is, the flexible support plate **50** may be switched between the folded state and the unfolded state under driving of the pressing plate assembly **40**.

(214) It may be understood that, when the first pressing plate swing arm **43** and the second pressing plate swing arm **44** rotate relative to the base **10**, both the first pressing plate swing arm **43** and the

second pressing plate swing arm **44** may generate a relative displacement with the base **10**. In this case, the displacements generated by the first pressing plate swing arm **43** and the second pressing plate swing arm **44** may match a size change generated due to bending of the flexible support plate **50**, thereby ensuring that the flexible support plate **50** is maintained in a flat state, preventing the flexible support plate **50** from generating wrinkles, and improving the use reliability of the foldable mechanism **130**.

(215) Refer to FIG. **21** and FIG. **22** together, FIG. **21** is a schematic cross-sectional structural view of the foldable mechanism **130** shown in FIG. **5** cut along I-I, and FIG. **22** is a schematic structural diagram of the foldable mechanism **130** shown in FIG. **21** in a folded state. Being cut along I-I refers to being cut along a place in which the line I-I is located, and similar description in this application may be understood as the same meaning.

(216) When the foldable mechanism **130** is in a flattened state, the pressing plate assembly **40** is in a flattened state, the first pressing plate **41** and the second pressing plate **42** are respectively located on two sides of the base **10**, the flexible support plate **50** is relatively flattened, the top surface of the first pressing plate **41** (namely, the top surface of the support portion **411**), the top surface of the second pressing plate **42** (namely, the top surface of the support portion **421**), and the top surface of the flexible support plate **50** (namely, the top surface of the flexible support portion **51**) are flush with each other, and the top surface of the first pressing plate **41**, the top surface of the second pressing plate **42**, and the top surface of the flexible support plate **50** form a support surface **1302**.

(217) The first front avoidance groove **512a** avoids the sliding portion **232a** of the first primary swing arm **23a** (as shown in FIG. **11**), the first rear avoidance groove **512b** avoids the sliding portion **232b** of the first primary swing arm **23b** (as shown in FIG. **13**), and the first middle avoidance groove **512c** avoids the sliding portion **232c** of the first primary swing arm **23c** (as shown in FIG. **15**). The second front avoidance groove **513a** avoids the sliding portion **242a** of the second primary swing arm **24a** (as shown in FIG. **11**), the second rear avoidance groove **513b** avoids the sliding portion **242b** of the second primary swing arm **24b** (as shown in FIG. **13**), and the second middle avoidance groove **513c** avoids the sliding portion **242c** of the second primary swing arm **24c** (as shown in FIG. **15**).

(218) The third front avoidance groove **514a** avoids the rotating portion **251a** of the first secondary swing arm **25a** (as shown in FIG. **11**), and the third rear avoidance groove **514b** avoids the rotating portion **251b** of the first secondary swing arm **25b** (as shown in FIG. **13**). The fourth front avoidance groove **515a** avoids the rotating portion **261a** of the second secondary swing arm **26a** (as shown in FIG. **11**), and the fourth rear avoidance groove **515b** avoids the rotating portion **261b** of the second secondary swing arm **26b** (as shown in FIG. **13**).

(219) It may be understood that, when the flexible support plate **50** is in the flattened state, arrangement of the avoidance grooves in the flexible support plate **50** may avoid interference generated between the flexible support plate **50** and the swing arms in the connection assembly **20**, so that the flexible support portion **51** may not be abutted against by the swing arms and protrude out relative to the top surface of the first pressing plate **41** and the top surface of the second pressing plate **42**, thereby ensuring that the top surface of the flexible support plate **50** is flush with the top surface of the first pressing plate **41** and the top surface of the second pressing plate **42**.

(220) When the foldable mechanism **130** is in the folded state, the pressing plate assembly **40** is in the folded state, the first pressing plate **41** and the second pressing plate **42** are disposed opposite to each other, the flexible support plate **50** bends and are folded, and the first fixing frame (for example, the first fixing frame **21a** shown in FIG. **11**, the first fixing frame **21b** shown in FIG. **13**, and the first fixing frame **21c** shown in FIG. **15**), the second fixing frame (for example, the second fixing frame **22a** shown in FIG. **11**, the second fixing frame **22b** shown in FIG. **13**, and the second fixing frame **22c** shown in FIG. **15**), the first pressing plate **41**, the second pressing plate **42**, and the flexible support plate **50** enclose to form an avoidance space **1303**. A cross section of the avoidance space **1303** is in a “droplet” shape. It should be noted that, the cross section of the

avoidance space **1303** refers to a section after the avoidance space is cut along a plane X-Z.

(221) The bottom portion of the flexible support plate **50** is received in the avoidance groove **101** of the base **10** (as shown in FIG. 7). It may be understood, the design of the avoidance groove **101** in the base **10** can avoid the bottom portion of the flexible support plate **50**, and avoid interference generated between the base **10** and the flexible support plate **50**, helping forming the “droplet”-shaped avoidance space **1303**.

(222) Refer to FIG. 3, FIG. 23, and FIG. 24, FIG. 23 is a schematic partial cross-sectional structural view of the foldable terminal **1000** shown in FIG. 2, and FIG. 24 is a schematic structural diagram of the foldable terminal **1000** shown in FIG. 3 in a folded state. In the foldable terminal **1000** shown in FIG. 23 and FIG. 24, only the foldable mechanism **130** and the foldable part **230** of the display screen **200** are shown.

(223) Specifically, the first fixing frame **21a** (as shown in FIG. 11), the first fixing frame **21b** (as shown in FIG. 13), and the first fixing frame **21c** (as shown in FIG. 15) are fixedly connected to the first housing **110**, and the second fixing frame **22a** (as shown in FIG. 11), the second fixing frame **22b** (as shown in FIG. 13), and the second fixing frame **22c** (as shown in FIG. 15) are fixedly connected to the second housing **120**. For example, the first fixing frame **21a**, the first fixing frame **21b**, and the first fixing frame **21c** may be fixedly connected to the first housing **110** through a fastener such as a screw or a bolt, and the second fixing frame **22a**, the second fixing frame **22b**, and the second fixing frame **22c** may be fixedly connected to the second housing **120** through a fastener such as a screw or a bolt.

(224) In this case, the support surface **1302** formed by the first pressing plate **41**, the second pressing plate **42**, and the flexible support plate **50** can support the foldable part **230** of the display screen **200**. Therefore, a good display effect of the display screen **200** can be ensured, and in a case that the foldable part **230** is touched, the foldable part **230** is not easily damaged or recessed due to touching of an external force, thereby improving the use reliability of the display screen **200**. The support surface **1302** may be flush with the top surface of the first housing **110** and the top surface of the second housing **120**, so that the first pressing plate **41**, the second pressing plate **42**, and the flexible support plate **50** may jointly support the display screen **200** with the first housing **110** and the second housing **120**, thereby implementing effective support of the flattened foldable apparatus **100** to the display screen **200**.

(225) It may be understood that, the flexible support plate **50** is not provided with an opening. Therefore, the top surface of the flexible support plate **50** is a complete flat surface, and an area of the support surface **1302** is relatively large, so that the foldable part **230** can be well supported, thereby improving a support effect of the flexible support plate **50** to the foldable part **230**.

(226) When the foldable terminal **1000** is in the folded state, the foldable part **230** of the display screen **200** is located on an inner side of the foldable mechanism **130**. Specifically, the foldable part **230** is located in the avoidance space **1303**. In this case, the foldable mechanism **130** may avoid an R angle formed when the foldable part **230** bends, so that the foldable part **230** does not bend at a relatively large angle, thereby avoiding a poor phenomenon such as a crease in the display screen **200**, and helping to prolong a service life of the display screen **200**.

(227) In the foldable mechanism **130** used by the foldable terminal **1000** shown in this embodiment, the display screen **200** is supported by using the flexible support plate **50**, and the flexible support plate **50** is directly mounted on the first pressing plate swing arm **43** and the second pressing plate swing arm **44**, so that assembly of the flexible support plate **50** can be implemented without springs. Therefore, a quantity of components of the foldable mechanism **130** is reduced, an assembly process of the foldable mechanism **130** is simplified, a problem of a relatively poor assembly precision is resolved, and the structure of the foldable mechanism **130** is further simplified, so that the structure of the foldable mechanism **130** is simple, which is conducive to a lightweight design of the foldable terminal **1000**.

(228) The foregoing descriptions are merely specific implementations of this application, but are

not intended to limit the protection scope of this application. Any variation or replacement readily figured out by a person skilled in the art within the technical scope disclosed in this application shall fall within the protection scope of this application. The embodiments in this application and features in the embodiments may be combined with each other in a case that no conflict occurs. Therefore, the protection scope of this application shall be subject to the protection scope of the claims.

Claims

1. A foldable mechanism, comprising: a base; a first pressing plate swing arm; a second pressing plate swing arm; and a flexible support plate, wherein a first rotating portion of the first pressing plate swing arm is rotatably connected to the base, the flexible support plate is mounted on the first pressing plate swing arm and bends under driving of the first pressing plate swing arm, wherein a bending direction of the flexible support plate is parallel to a first rotation axis of the first pressing plate swing arm relative to the base, wherein a second rotating portion of the second pressing plate swing arm is rotatably connected to the base, the flexible support plate is further mounted on the second pressing plate swing arm and bends under driving of the second pressing plate swing arm, and the bending direction of the flexible support plate is further parallel to a second rotation axis of the second pressing plate swing arm relative to the base, wherein a first connection portion of the first pressing plate swing arm is provided with a first assembly hole, a second connection portion of the second pressing plate swing arm is provided with a second assembly hole, and the flexible support plate comprises a flexible support portion, a first fixing portion, and a second fixing portion, and wherein the flexible support portion is provided with a plurality of strip-shaped grooves, the plurality of strip-shaped grooves are parallel to each other and arranged at intervals, a corresponding extending direction of each of the strip-shaped grooves is parallel to the bending direction of the flexible support plate, the first fixing portion and the second fixing portion are fixedly connected to a bottom surface of the flexible support portion, the first fixing portion is mounted in the first assembly hole of the first pressing plate swing arm, and the second fixing portion is mounted in the second assembly hole of the second pressing plate swing arm.
2. The foldable mechanism according to claim 1, wherein the first pressing plate swing arm is slidably and rotatably connected to the base.
3. The foldable mechanism according to claim 1, wherein the second rotating portion of the second pressing plate swing arm is slidably and rotatably connected to the base.
4. The foldable mechanism according to claim 1, wherein openings of the plurality of strip-shaped grooves are located on the bottom surface of the flexible support portion.
5. The foldable mechanism according to claim 1, wherein the foldable mechanism further comprises a first pressing plate and a second pressing plate, the first pressing plate is slidably connected to a first sliding portion of the first pressing plate swing arm, and the second pressing plate is slidably connected to a second sliding portion of the second pressing plate swing arm, and wherein the foldable mechanism is in a flattened state, and the first pressing plate and the second pressing plate are respectively located on two opposite sides of the base, and a first top surface of the first pressing plate and a second top surface of the second pressing plate are flush with a top surface of the flexible support plate.
6. The foldable mechanism according to claim 5, wherein the foldable mechanism further comprises a first fixing frame and a second fixing frame, the first fixing frame is slidably and rotatably connected to the first pressing plate, and the second fixing frame is slidably and rotatably connected to the second pressing plate, and wherein the foldable mechanism is in a folded state, and the first pressing plate and the second pressing plate are disposed opposite to each other, the first fixing frame, the second fixing frame, the first pressing plate, the second pressing plate, and the flexible support plate encloses to form an avoidance space, and the avoidance space is in a

droplet shape.

7. The foldable mechanism according to claim 6, wherein the base is provided with an avoidance groove, the foldable mechanism is in the folded state, and the avoidance groove is configured to avoid a bottom portion of the flexible support plate.

8. The foldable mechanism according to claim 6, further comprising a first primary swing arm and a second primary swing arm, wherein a third rotating portion of the first primary swing arm is rotatably connected to the first fixing frame, a third sliding portion of the first primary swing arm is slidably and rotatably connected to the base, a fourth rotating portion of the second primary swing arm is rotatably connected to the second fixing frame, and a fourth sliding portion of the second primary swing arm is slidably and rotatably connected to the base.

9. The foldable mechanism according to claim 8, wherein the flexible support portion is further provided with a first avoidance groove and a second avoidance groove, and openings of the first avoidance groove and the second avoidance groove are both located on the bottom surface of the flexible support portion, and wherein the foldable mechanism is in the flattened state, the first avoidance groove is configured to avoid the third sliding portion of the first primary swing arm, and the second avoidance groove is configured to avoid the fourth sliding portion of the second primary swing arm.

10. The foldable mechanism according to claim 6, further comprising a first secondary swing arm and a second secondary swing arm, wherein a fifth sliding portion of the first secondary swing arm is slidably connected to the first fixing frame, a fifth rotating portion of the first secondary swing arm is rotatably connected to the base, a sixth sliding portion of the second secondary swing arm is slidably connected to the second fixing frame, and a sixth rotating portion of the second secondary swing arm is rotatably connected to the base.

11. The foldable mechanism according to claim 10, wherein the flexible support portion is further provided with a third avoidance groove and a fourth avoidance groove, and openings of the third avoidance groove and the fourth avoidance groove are both located on the bottom surface of the flexible support portion, and wherein in a case that the foldable mechanism is in the flattened state, the third avoidance groove is configured to avoid the fifth rotating portion of the first secondary swing arm, and the fourth avoidance groove is configured to avoid the sixth rotating portion of the second secondary swing arm.

12. The foldable mechanism according to claim 1, wherein the base is an integrally formed structural member.

13. The foldable mechanism according to claim 12, wherein the base is provided with a first engagement groove, the first engagement groove is an arc-shaped groove, the first rotating portion of the first pressing plate swing arm is in a shape of an arc-shaped plate, and the first rotating portion of the first pressing plate swing arm is mounted in the first engagement groove and slides and rotates relative to the base in the first engagement groove.

14. A foldable terminal, comprising: a first housing; a second housing; and a foldable mechanism, wherein the foldable mechanism is connected between the first housing and the second housing, the foldable mechanism including: a base; a first pressing plate swing arm; a second pressing plate swing arm; and a flexible support plate, wherein a first rotating portion of the first pressing plate swing arm is rotatably connected to the base, the flexible support plate is mounted on the first pressing plate swing arm and bends under driving of the first pressing plate swing arm, and wherein a bending direction of the flexible support plate is parallel to a first rotation axis of the first pressing plate swing arm relative to the base, wherein a second rotating portion of the second pressing plate swing arm is rotatably connected to the base, the flexible support plate is further mounted on the second pressing plate swing arm and bends under driving of the second pressing plate swing arm, and the bending direction of the flexible support plate is further parallel to a second rotation axis of the second pressing plate swing arm relative to the base, wherein a first connection portion of the first pressing plate swing arm is provided with a first assembly hole, a

second connection portion of the second pressing plate swing arm is provided with a second assembly hole, and the flexible support plate comprises a flexible support portion, a first fixing portion, and a second fixing portion, and wherein the flexible support portion is provided with a plurality of strip-shaped grooves, the plurality of strip-shaped grooves are parallel to each other and arranged at intervals, a corresponding extending direction of each of the strip-shaped grooves is parallel to the bending direction of the flexible support plate, the first fixing portion and the second fixing portion are fixedly connected to a bottom surface of the flexible support portion, the first fixing portion is mounted in the first assembly hole of the first pressing plate swing arm, and the second fixing portion is mounted in the second assembly hole of the second pressing plate swing arm.

15. The foldable terminal according to claim 14, further comprising a display screen, wherein the display screen comprises a first display part, a second display part, and a foldable part, the foldable part is connected between the first display part and the second display part, the first display part is mounted in the first housing, the second display part is mounted in the second housing, and the foldable part and the foldable mechanism are disposed opposite to each other, and wherein the foldable terminal is in an unfolded state, and a top surface of the flexible support plate supports the foldable part.

16. The foldable terminal according to claim 15, wherein the foldable terminal is in a folded state, and the foldable part is received in an avoidance space of the foldable mechanism.

17. The foldable terminal according to claim 14, wherein the first pressing plate swing arm is slidably and rotatably connected to the base.

18. A foldable mechanism, comprising: a base; a first pressing plate swing arm; a second pressing plate swing arm; and a flexible support plate, wherein a first rotating portion of the first pressing plate swing arm is rotatably connected to the base, the flexible support plate is mounted on the first pressing plate swing arm and bends under driving of the first pressing plate swing arm, wherein a bending direction of the flexible support plate is parallel to a first rotation axis of the first pressing plate swing arm relative to the base, wherein a second rotating portion of the second pressing plate swing arm is rotatably connected to the base, the flexible support plate is further mounted on the second pressing plate swing arm and bends under driving of the second pressing plate swing arm, and the bending direction of the flexible support plate is further parallel to a second rotation axis of the second pressing plate swing arm relative to the base, wherein the foldable mechanism further comprises a first pressing plate and a second pressing plate, the first pressing plate is slidably connected to a first sliding portion of the first pressing plate swing arm, and the second pressing plate is slidably connected to a second sliding portion of the second pressing plate swing arm, and wherein the foldable mechanism is in a flattened state, and the first pressing plate and the second pressing plate are respectively located on two opposite sides of the base, and a first top surface of the first pressing plate and a second top surface of the second pressing plate are flush with a top surface of the flexible support plate.

19. The foldable mechanism according to claim 18, wherein the foldable mechanism further comprises a first fixing frame and a second fixing frame, the first fixing frame is slidably and rotatably connected to the first pressing plate, and the second fixing frame is slidably and rotatably connected to the second pressing plate, and wherein the foldable mechanism is in a folded state, and the first pressing plate and the second pressing plate are disposed opposite to each other, the first fixing frame, the second fixing frame, the first pressing plate, the second pressing plate, and the flexible support plate encloses to form an avoidance space, and the avoidance space is in a droplet shape.

20. The foldable mechanism according to claim 19, wherein the base is provided with an avoidance groove, the foldable mechanism is in the folded state, and the avoidance groove is configured to avoid a bottom portion of the flexible support plate.
