

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385954
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Van Itallie; Bryan P. et al.

Compact combination electrical panel safety monitor and test point

Abstract

An electrical safety monitor is provided. The electrical safety monitor may include a housing having a face. The electrical safety monitor further includes a plurality of line inputs for hardwiring a plurality of electrical connections, The electrical safety monitor further includes a plurality of test points with each of the test points corresponding to one of the line inputs, each of the plurality of test points accessible at the face of the housing. The electrical safety monitor further includes a line monitoring circuit having a plurality of light indicators and configured to produce light if voltage exists between any two of the line inputs to thereby indicate presence of voltage to a user. The electrical safety monitor further includes illumination areas associated with each of the test points, wherein each of the illumination areas is provided light by one or more of the plurality of light indicators.

Inventors: Van Itallie; Bryan P. (Davenport, IA), Tuttle; Aaron (McCausland, IA), Meehan; Connor B. (Ann Arbor, MI), Clarke; Roger S. (Santa Claus, IN)

Applicant: Grace Technologies, Inc. (Davenport, IA)

Family ID: 86695339

Assignee: GRACE TECHNOLOGIES, INC. (Davenport, IA)

Appl. No.: 18/422758

Filed: January 25, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240159803 A1	May. 16, 2024

Related U.S. Application Data

continuation parent-doc US 17551993 20211215 US 11913979 child-doc US 18422758

Publication Classification

Int. Cl.: G01R19/155 (20060101)

U.S. Cl.:

CPC G01R19/155 (20130101);

Field of Classification Search

CPC: G01R (19/155); G01R (31/008); G01R (31/00); G01R (31/005); G01R (15/08); G01R (15/00); G01R (17/00); G01R (29/00); G01R (33/00); G01R (33/26); G01R (35/00); G01R (15/09); G01R (1/206); G05B (23/0256); G08B (25/14); H01R (13/7135); H01R (13/713); H01R (13/00); H01R (12/70); H01R (24/00); H01R (33/00); H01R (13/66); H01R (13/70); H01R (13/7175); H01H (9/182); H01H (83/04)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6703938	12/2003	Clarke	N/A	N/A
9013296	12/2014	Clarke	340/514	G01R 19/155
2002/0074370	12/2001	Quintana	N/A	N/A
2007/0132458	12/2006	Allen	324/523	G01R 19/155
2007/0170949	12/2006	Pak	324/760.01	G09G 3/006
2009/0118604	12/2008	Phan	600/345	A61B 5/1486
2022/0148392	12/2021	Adkins et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201503480	12/2009	CN	N/A
216083069	12/2021	CN	N/A
0085772	12/1982	EP	G01R 31/31914
2576369	12/2019	GB	H02M 7/42

OTHER PUBLICATIONS

Adkins et al., U.S. Appl. No. 17/451,000, Oct. 15, 2021, Compact Test Point Device. cited by applicant

Adkins et al., U.S. Appl. No. 17/529,579, Nov. 18, 2021, Wireless Voltage Measurement, Testing and Analytics System. cited by applicant

Breitsprecher et al., U.S. Appl. No. 29/780,030, Apr. 22, 2021, Voltage Indicator With Test Points. cited by applicant

Primary Examiner: Zimmerman; Brian A

Assistant Examiner: Afrifa-Kyei; Anthony D

Attorney, Agent or Firm: Goodhue, Coleman & Owens, P.C.

Background/Summary

RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/551,993, filed Dec. 15, 2021, hereby incorporated by reference in its entirety.

FIELD OF THE INVENTION

(1) The present invention relates to electrical safety. More particularly, but not exclusively, the present invention relates to electrical panel safety monitoring and test points.

BACKGROUND

(2) The present invention relates to electrical safety, and more particularly to monitoring of circuits such as 1000 VAC or 1500 VDC voltages using voltage indicators. A voltage indicator is generally a low cost device that pre-verifies electrical isolation before maintenance personnel open a control panel and risk exposure to hazardous voltages. Typically mounted to the panel exterior and hardwired into the load side of the main disconnect, this device provides electrical maintenance with an additional safety value. Easy to apply, low cost, quick installation, and inherent reliability makes a voltage indicator a very effective electrical safety device.

(3) Creating and insuring an electrically safe work condition is critical for electricians performing maintenance on de-energized systems. The presence of voltage is the only determining factor if an electrical accident or an arc flash can possibly occur—No voltage, No accident, No arc flash. “Voltage or no voltage” is also the basis of the NFPA 70E's (National Fire Protection Association Standard's for Electrical Safety Requirements for Employee Workplaces) two primary themes: a) establishing an electrically safe work condition, and b) achieving safety while working on energized systems. A voltage warning indicator is like a ‘hard wired voltmeter’ with the advantage that it needs no power supply or batteries because it is powered from the same ‘voltage’ that it indicates. A voltage indicator is an additional safety measure between maintenance personnel and hazardous voltage.

(4) U.S. Pat. No. 6,703,938 to Clarke, herein incorporated by reference in its entirety, illustrates one type of electrical safety monitor. Despite the advances of Clarke and other prior art devices, problems remain. In particular, it would be useful to not only provide a voltage warning indicator but also the ability to conduct a full absence of voltage test required as part of a lock-out/tag-out process without exposing the electrician to unsafe risk of electrical shock or arc flash. Moreover, it would be advantageous to do so in a compact combination while still maintaining UL spacing requirements associated with circuits carrying up to 1000 VAC or 1500 VDC. Therefore problems remain.

SUMMARY

(5) Therefore, it is a primary object, feature, or advantage of the present invention to improve over the state of the art.

(6) It is a further object, feature, or advantage of the present invention to provide an electrical panel safety monitor which includes test points.

(7) It is a still further object, feature, or advantage of the present invention to provide an electrical panel safety monitor which includes test points and is compact.

(8) Another object, feature, or advantage is to provide an electrical panel safety monitor which may be used to indicate presence of voltage on three-phase connections and also allow for probing test

points to determine voltage between different test points.

(9) Yet another object, feature, or advantage is to provide an electrical panel safety monitor.

(10) Yet another object, feature, or advantage is to provide separate voltage test and test point circuits within a single compact housing.

(11) Another object, feature, or advantage is to provide a housing with a face on which both test points and illuminated areas indicative of presence of voltage may be positioned.

(12) Yet another object, feature, or advantage is to use modern miniature and flexible circuit elements, light pipes, and electrical potting compound to allow a voltage indicator circuit and a test point circuit to be placed in close proximity while maintaining UL spacing requirements associated with circuits carrying up to 1000 VAC or 1500 VDC.

(13) A further object, feature, or advantage is to improve electrical safety by enabling an electrician to have both visual indication of the presence of voltage at a panel and to conduct the full absence of voltage test required as part of the lock-out/tag-out process without exposing the electrician to unsafe risk of electrical shock or arc flash.

(14) A still further object, feature, or advantage is to use light pipes enable the voltage indicator LEDs to flash in rings around the test points for clear indication of which circuit has voltage associated with it.

(15) Another object, feature, or advantage is to provide a clear, yet waterproof, lockable cover provides environmental ratings as appropriate for use in most industrial applications (UL Type 4, 4X, 12, 13).

(16) One or more of these and/or other objects, features, or advantages of the present invention will become apparent from the specification and claims that follow. No single embodiment need provide each and every object, feature, or advantage. Different embodiments may have different objects, features, or advantages. Therefore, the present invention is not to be limited to or by any objects, features, or advantages stated herein.

(17) According to one aspect an electrical safety monitor is provided. The electrical safety monitor may include a housing having a face. The electrical safety monitor further includes a plurality of line inputs for hardwiring a plurality of electrical connections, The electrical safety monitor further includes a plurality of test points with each of the test points corresponding to one of the line inputs, each of the plurality of test points accessible at the face of the housing. The electrical safety monitor further includes a line monitoring circuit having a plurality of light indicators and configured to produce light if voltage exists between any two of the line inputs to thereby indicate presence of voltage to a user. The electrical safety monitor further includes illumination areas associated with each of the test points, wherein each of the illumination areas is provided light by one or more of the plurality of light indicators. Each of the illumination areas may be positioned around a corresponding one of the test points. The electrical safety monitor may further include light pipes for conveying light from the plurality of light indicators to the illumination areas. Each of the test points may comprise a conductive well for insertion of a test probe. The plurality of line inputs may include an L1, an L2, an L3, and a GND three-phase connection. The electrical safety monitor may include a voltage test circuit electrically connected to the plurality of test points. The voltage test circuit may be associated with a voltage test circuit board. The voltage test circuit board may be a flexible circuit board. The line monitoring circuit may be associated with a line monitoring circuit board. The line monitoring circuit board may be a flexible circuit board. The electrical safety monitor may further include an electrical potting compound wherein at least a portion of electrical compound separates one or more components of the line monitoring circuit board from the voltage test circuit board. The electrical safety monitor may further include a transparent cover operatively connected to the housing for covering the face of the housing when the transparent cover is in a closed position.

(18) According to another aspect, an electrical safety monitor includes a housing having a face, a plurality of input lines, and a line monitoring circuit board disposed within the housing and having

a voltage indicator circuit associated therewith, the voltage indicator circuit comprising a plurality of visual indicators such that there is at least one of the plurality of visual indicators corresponding with each of the plurality of input lines. The electrical safety monitor may further include a voltage test circuit board disposed within the housing and having a voltage test circuit associated therewith. The electrical safety monitor may further include a plurality of test points positioned at the face and electrically connected to the voltage test circuit such that each of the plurality of the test points corresponds with one of the plurality of input lines. The electrical safety monitor may further include a plurality of illumination areas positioned at the face, wherein each of the plurality of illumination areas is positioned around a corresponding one of the test points. Each of the illumination areas may fully encircle a corresponding one of the test points. The electrical safety monitor may further include light pipes for conveying light from the plurality of visual indicators to the illumination areas. Each of the test points may further include a conductive well for insertion of a test probe. The plurality of line inputs may include an L1, an L2, an L3, and a GND three-phase connection. The voltage test circuit board may be a flexible circuit board. The line monitoring circuit board may be a flexible circuit board. The electrical safety monitor may further include an electrical potting compound wherein at least a portion of electrical compound separates one or more components of the line monitoring circuit board from the voltage test circuit board.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Illustrated embodiments of the disclosure are described in detail below with reference to the attached drawing figures, which are incorporated by reference herein.
- (2) FIG. 1 is a view of a cabinet or enclosure to which an electrical safety monitor with test points is mounted.
- (3) FIG. 2 is a perspective view of the electrical safety monitor with test points.
- (4) FIG. 3 is a block diagram of the electrical safety monitor with test points.
- (5) FIG. 4 is a block diagram showing a voltage indicator circuit and a test circuit.
- (6) FIG. 5 further illustrates a voltage indicator or line monitoring circuit board and a voltage test circuit board.
- (7) FIG. 6 is a cross sectional view of the device with the cross-section taken through the test points.
- (8) FIG. 7 is a cross sectional view of the device with the cross-section taken perpendicular to the circuit boards so that both circuit boards may be more clearly shown.
- (9) FIG. 8 illustrates one example of a circuit to provide a device with a combined voltage indicator and test points.
- (10) FIG. 9 is a front view of a cover for the device.
- (11) FIG. 10 is a perspective view of the transparent cover when mounted to the device.
- (12) FIG. 11 and FIG. 12 illustrate an alternative example of a transparent cover.

DETAILED DESCRIPTION

(13) This invention combines a voltage indicator or line monitoring circuit such as that disclosed in U.S. Pat. No. 6,703,938, hereby incorporated by reference in its entirety, with a voltage test circuit such as a parallel impedance-protected circuit that terminates in standard meter probe test points into a small form factor to easily mount on an industrial electrical panel. Use of modern miniature and flexible circuit elements, light pipes, and electrical potting compound enables these two circuits to be placed in close proximity while maintaining UL spacing requirements associated with circuits carrying up to 1000 VAC or 1500 VDC. By providing both circuits in the same package, this enables an electrician to have both visual indication of the presence of voltage at the panel and to conduct the full absence of voltage test required as part of the lock-out/tag-out process without

exposing the electrician to unsafe risk of electrical shock or arc flash. Light pipes enable the voltage indicator LEDs to flash in rings around the test points for clear indication of which line input has voltage associated with it. The form factor of this invention may be as shown described in Design Patent Application 29/780,030, hereby incorporated by reference in its entirety. A clear, yet waterproof, lockable cover may be used to provide environmental ratings as appropriate for use in most industrial applications (e.g. UL Type 4, 4X, 12, 13).

(14) FIG. 1 is a view of one embodiment of the present invention. A control cabinet **2** is shown. A device **10** is shown which is mounted to the control panel cabinet **12**. The device **10** may be a permanent electrical safety device (PESD) that allows qualified individuals to perform an absence of voltage test (AVT) from outside of the electrical cabinet. The device **10** may be mounted directly on any enclosure with the option to test either the line side or the load side.

(15) FIG. 2 illustrates the device **10**. The device **10** has a housing **12** with a threaded portion **14**. A face **20** is shown. The device **10** provides for voltage indication and for providing test points. On the face **20** includes test points **24, 28, 32, 36**. Each of the test points **24, 28, 32, 36** is associated with a different input line or phase and may be in the form of a conductive well for receiving a test probe. Thus, an operator could access a L1 voltage through test point **24**, a L2 voltage through test point **28**, a L3 voltage through test point **32**, and GND through test point **36**. Each of the test points may be hardwired directly to energy sources and allows for measurement of AC/DC voltages by inserting insulated meter probes into any two test points to take a voltage reading of either phase to phase or phase to ground. The test points may be protected by impedance to limit the maximum current possible in the event of a short circuit and single component failure to less than 4 milliamps while providing an accurate voltage reading within 3.3% of true voltage. This provides accurate voltage readings without the risk of shock or arc.

(16) Also as shown in FIG. 2, there are illumination areas **26, 30, 34, 38** associated with each of the test points **24, 28, 32, 36**. The illumination areas **26, 30, 34, 38** may be in the form of rings which extend around the corresponding test points. Each of the illumination areas **26, 30, 34, 38** may be illuminated to show the presence of voltage by illuminating the area. The illumination areas **26, 30, 34, 38** may receive light from visual indicators such as LEDs or other light sources disposed within the housing. The light may be piped to the corresponding illumination areas **26, 30, 34, 38**. Thus, an individual may readily identify which of the line inputs have voltage present prior to making any measurements. In some embodiments, each of the visual indicators may flash at a rate associated with the voltage present such that a higher flash rate may generally indicate a higher voltage. Thus, an individual may be alerted as to the presence of voltage as well as an indication of magnitude of the voltage present.

(17) Although a three-phase power connection is shown as is typically used for AC power lines, the circuit may be modified to accommodate other types of power connectors. For example, instead of a three-phase power connection, a single-phase power connection may be monitored in which case there would need only be two power line inputs. Similarly, a five-wire power connection may be used which include a first line input, a second line input, a third line input, a ground, and a neutral connection. It is also to be understood that the circuit may also be used for DC voltage lines as well as AC voltage lines and thus the same device may be used in a wide range of applications and environments.

(18) FIG. 3 is a block diagram illustrating the device **10**. The device **10** has a housing **12**. Disposed within the housing **12** is both a voltage indicator or line monitoring printed circuit board (PCB) **50** and a voltage test printed circuit board (PCB) **60**. Each of the line monitoring PCB **50** and the voltage test PCB **60** may be flexible circuit boards. In addition, an electrical potting compound **70** may be used to further separate and isolate components from the line monitoring PCB **50** and the voltage test PCB **60**. Thus, these two parallel circuits may be disposed within a housing **12** with a compact form factor while maintaining Underwriter Laboratories (UL) required spacing between components associated with 1000 VAC/1500 VDC circuits. Thus, the housing **12** with its compact

form factor allows, for example, the device to be installed using a standard 30 mm electrical panel knockout. There are a number of light pipes **52, 54, 56, 58** associated with the line monitoring printed circuit board **50**. Each of the light pipes **52, 54, 56, 58** may provide for piping or conveying light from one or more light sources associated with the line monitoring PCB **50** which may be in the form of LEDs to the face of the device, such as to the rings located on the face such as those best shown in FIG. 2.

(19) The line monitoring printed circuit board **50** may comprise a circuit such as that shown and described in U.S. Pat. No. 6,703,938, hereby incorporated by reference in its entirety. The line monitoring circuit may be enhanced to reduce the overall power draw while allowing a wider range of detectable voltage inputs.

(20) The light pipes **52, 54, 56, 58** may be used to route the flashes from voltage indicator LEDs to rings or other illumination areas associated with each of the test points, thus clearly identifying which circuit has voltage on it. This makes it intuitive for the electrician performing the test to know which circuit lines have voltage and which ones are being measured at any time. The use of these light pipes also enables the placement of the visual indicator immediately adjacent to the higher voltage test point components without violating UL spacing requirements.

(21) The use of flexible circuit boards **50, 60** enables the line monitoring circuit to be on a completely separate circuit board **50** from the voltage test circuit on the voltage test circuit board **60** while bringing both the LED indicators and the voltage test points to a common face location. It also allows for both circuits to be powered from a common set of wires, reducing the chance of errors during installation into the electrical panel.

(22) FIG. 4 is a block diagram of circuitry for the device. A voltage indicator circuit **80** is shown such as may be mounted on or otherwise associated with the voltage indicator PCB. A voltage test circuit **82** is shown such as may be mounted on or otherwise associated with the voltage test PCB. The voltage indicator circuit may include a plurality of light sources or light indicators **84, 86, 88, 90** which may be LEDs. Light pipes **52, 54, 56, 58** may be used to convey light from the light indicators **84, 86, 88, 90** to the face **20**. A plurality of line inputs **92** are shown which are electrically connected to both the voltage indicator circuit **80** and the test circuit **82**. A plurality of electrical connections **94, 96, 98, 100** are shown which connect test points on the face **20** with the test circuit **82**.

(23) The device may be designed to have different configurations for use in 3-phase AC, 50/60/400 Hz (Delta or Wye configurations), single-phase AC, or DC applications up to 1000 VAC/1500 VDC with indications and test points for each phase, neutral, and ground. A transparent, waterproof, tool-access cover (not shown) enables the voltage indication to be clearly seen while protecting the circuit from environmental hazards and meeting UL Type ratings of 4, 4X, 12, and 13 or other applicable ratings or standards.

(24) FIG. 5 further illustrates a voltage indicator circuit board **50** and a voltage test circuit board **60** and further shows test points **24, 28, 32, 36**. Electrical potting compound (not shown) may be used to separate components of the two circuit boards **50, 60** to provide for electrical isolation while allowing for the small package size.

(25) FIG. 6 is a cross sectional view of the device **10** through the test points. In FIG. 6, there are a plurality of light sources in the form of LEDs **84, 86, 88, 90**. Light pipes **52, 54, 56, 58** correspond with the LEDs **84, 86, 88, 90** to convey light to the face of the device **10**. Electrical potting compound **70** may fill an internal cavity and allows for tight component spacing within the limited size of the device. FIG. 7 is a cross sectional view of the device **10** perpendicular to the circuit boards so that both circuit boards may be more clearly shown.

(26) FIG. 8 illustrates one example of a circuit to provide a device with a combined voltage indicator and test points. In the embodiment shown, monitored voltage lines include L1, L2, L3, N, and GND. Voltage dividers are used to connect each of the line inputs to test points. Thus, **R16, R17** are positioned between the L1 input and the L1 test point TP-L1. Similarly **R18, R19** are

positioned between the L2 input and the L2 test point TP-L2. R20, R21 are positioned between the L3 input and the L3 test point TP-L3. R22, R23 are positioned between the neutral line input N and the N test point TP-N. R24, R25 are positioned between the GND line input GND and the GND test point TP-GND.

(27) The voltage indicator circuit is similar to that described in U.S. Pat. No. 6,703,938 to Clarke. Current-limiting resistors R1, R2, R3, R4, R5 are electrically connected to the corresponding line inputs L1, L2, L3, N, GND. Each of the inputs L1a, L2a, L3a, Na, GNDa, are then connected to two set of diodes. Thus L1a is electrically connected to D16A, D16B and D21A, D21B. L2a is electrically connected to D15A, D15B and D20A, D20B. (D12A, D21A). L3a is electrically connected to D14A, D14B and D19A, D19B. Na is electrically connected to D13A, D13B and D17A, D17B. GNDa is electrically connected to D12A, D12B and D17A, D17B. There is a first set of LEDs D1, D2, D3, D4, D5 associated with positive voltages with each LED having a resistor associated with it, namely R6, R7, R8, R9, R10. There is a second set of LEDs D6, D7, D8, D9, D10 associated with negative voltages with each LED having a resistor associated with it namely R11, R12, R13, R14, R15. There is a set of capacitors C1, C2, C3, C4, C5 associated with the positive portion of the circuit and a second set of capacitors C6, C7, C8, C9, C10 associated with the negative portion of the circuit. There is a Zener diode D22 and flasher circuit F1 associated with the positive portion of the circuit and a Zener diode D23 and flasher circuit F2 associated with the negative portion of the circuit.

(28) FIG. 9 is a front view of a cover 120 for the device. FIG. 10 is a perspective view of the transparent cover 120 when mounted to the device. The transparent cover 120 serves several functions. First, the transparent cover 120 provides for protection for the test points. Thus, while the cover 120 is in a closed position, the test points are not accessible. The protection provided may be UL Type 12, 13, 4, 4X protection.

(29) However, while the cover 120 is in the closed position, because the cover 120 is transparent, LEDs or other visual indicators on the face of the device are visible. When the transparent cover 120 is in an open position, the test points are accessible and the LEDs or other visual indicators remain visible.

(30) FIG. 11 and FIG. 12 illustrate an alternative example of a transparent cover 130 which may be used. It is to be understood that the cover may take on any number of other alternative shapes and configurations as may be desired in a particular application or configuration or as may be required to obtain a relevant UL rating or other meeting a relevant standard.

(31) Another feature provided by the electrical safety monitor is that in the event of a loss of a phase, the corresponding visual indicator turns off and the visual indicator for GND is illuminated. However, when an external voltage test meter is used and the probes placed in the test points for the failed phase and a powered phase, current will travel through the voltage meter and cause the visual indicators for the failed phase to illuminate (although at a much lower intensity). This provides confirmation that the visual indicators (e.g. LEDs) and test circuit for the phase are still working.

(32) Therefore, an electrical safety monitor with test points has been shown and described. The invention is not to be limited to the particular embodiments described herein. In particular, the invention contemplates numerous variations in the number of line puts, the position and shape of illumination area, the voltage indicator circuit, the test point circuit, the housing, and the circuit boards. The foregoing description has been presented for purposes of illustration and description. It is not intended to be an exhaustive list or limit any of the invention to the precise forms disclosed. It is contemplated that other alternatives or exemplary aspects are considered included in the invention. The description is merely examples of embodiments, processes, or methods of the invention. It is understood that any other modifications, substitutions, and/or additions can be made, which are within the intended spirit and scope of the invention.

Claims

1. An electrical safety monitor, comprising: a housing having a face; a plurality of line inputs for hardwiring a plurality of electrical connections; a plurality of meter probe test points with each of the meter probe test points corresponding to one of the line inputs and operatively connected thereto, each of the plurality of meter probe test points accessible at the face of the housing; a line monitoring circuit electrically connected to the plurality of line inputs and a plurality of light indicators, the line monitoring circuit configured to produce light using the light indicators to thereby indicate presence of voltage at each of the plurality of line inputs to a user; and wherein the plurality of light indicators are positioned at the face of the electrical safety monitor, with each of the plurality of light indicators corresponding with one of the plurality of meter probe test points.
2. The electrical safety monitor of claim 1 wherein the plurality of light indicators provide light at a corresponding one of the meter probe test points.
3. The electrical safety monitor of claim 2 further comprising light pipes for conveying light from the plurality of light indicators to illumination areas associated with the meter probe test points.
4. The electrical safety monitor of claim 1 wherein each of the meter probe test points comprises a conductive well for insertion of a test probe of a voltmeter.
5. The electrical safety monitor of claim 1 wherein the plurality of line inputs includes an L1, an L2, an L3, and a GND three-phase connection.
6. The electrical safety monitor of claim 1 wherein the plurality of line inputs include an L1, an L2, an L3, a Neutral, and a GND connection.
7. The electrical safety monitor of claim 1 further comprising a voltage test circuit electrically connected to the plurality of meter probe test points.
8. The electrical safety monitor of claim 7 wherein the voltage test circuit is associated with a voltage test circuit board.
9. The electrical safety monitor of claim 8 wherein the voltage test circuit board is a flexible circuit board.
10. The electrical safety monitor of claim 8 wherein the line monitoring circuit is associated with a line monitoring circuit board.
11. The electrical safety monitor of claim 10 wherein the line monitoring circuit board is a flexible circuit board.
12. The electrical safety monitor of claim 9 further comprising an electrical potting compound wherein at least a portion of electrical compound separates one or more components of the line monitoring circuit board from the voltage test circuit board.
13. The electrical safety monitor of claim 10 further comprising a transparent cover operatively connected to the housing for covering the face of the housing when the transparent cover is in a closed position.
14. The electrical safety monitor of claim 1 wherein the line monitoring circuitry is configured to accommodate DC voltages at the plurality of line inputs.
15. The electrical safety monitor of claim 1 wherein the line monitoring circuitry is configured to accommodate 1500 VDC voltages at the plurality of line inputs.
16. The electrical safety monitor of claim 1 wherein the line monitoring circuitry is configured to accommodate 1000 VAC at the plurality of line inputs.
17. The electrical safety monitor of claim 1 wherein each of the plurality of meter probe test points is impedance protected.
18. An electrical safety monitor, comprising: a housing for mounting to a door of an electrical cabinet such that the electrical safety monitor is accessible without opening the door of the electrical cabinet; a plurality of input lines; a line monitoring circuit board disposed within the housing and having a line monitoring circuit associated therewith, the line monitoring circuit being

electrically connected to a plurality of visual indicators such that there is at least one of the plurality of visual indicators corresponding with each of the plurality of input lines; a voltage test circuit board disposed within the housing and having a voltage test circuit associated therewith; a plurality of meter probe test points positioned at the face and electrically connected to the voltage test circuit such that each of the plurality of the meter probe test points corresponds with one of the plurality of input lines; a plurality of visual indicators to indicate presence of voltage at the plurality of input lines without opening the door of the electrical cabinet; wherein each of the plurality of meter probe test points is impedance protected.

19. The electrical safety monitor of claim 18 further comprising light pipes for conveying light from the plurality of visual indicators to illumination areas.

20. The electrical safety monitor of claim 18 wherein the line monitoring circuitry is configured to accommodate DC voltages at the plurality of line inputs.

21. The electrical safety monitor of claim 18 wherein the line monitoring circuitry is configured to accommodate 1500 VDC voltages at the plurality of line inputs.

22. The electrical safety monitor of claim 18 wherein the line monitoring circuitry is configured to accommodate 1000 VAC and 1500 VDC voltages at the plurality of line inputs.

23. The electrical safety monitor of claim 18 further comprising a transparent cover operatively connected to the housing for covering the face of the housing when the transparent cover is in a closed position thereby protecting the plurality of meter probe test point while allowing the plurality of visual indicators to be seen.

24. An electrical safety monitor, comprising: a housing for mounting to a door of an electrical cabinet such that the electrical safety monitor is accessible without opening the door of the electrical cabinet; a plurality of line inputs for hardwiring a plurality of electrical connections; a line monitoring circuit electrically connected to a plurality of light indicators and configured to produce light if voltage exists between any two of the plurality of line inputs to thereby indicate presence of voltage to a user; a plurality of meter probe test points with each of the meter probe test points corresponding to one of the line inputs and operatively connected thereto through at least one resistor to provide high input impedance, each of the plurality of meter probe test points accessible at a face of the housing; and a transparent cover operatively connected to the housing for covering the face of the housing when the transparent cover is in a closed position thereby protecting the plurality of meter probe test points while allowing the plurality of light indicators to be seen; and wherein each of the meter probe test points comprises a conductive area for insertion of a test probe of a voltmeter.

25. The electrical safety monitor of claim 24 wherein the electrical safety monitor is further configured with circuitry to allow the user to perform an absence of voltage test (AVT) from outside of the electrical cabinet.

26. The electrical safety monitor of claim 24 wherein the plurality of line inputs includes an L1, an L2, an L3, and a GND three-phase connection.

27. The electrical safety monitor of claim 24 wherein the plurality of line inputs include an L1, an L2, an L3, a Neutral, and a GND connection.

28. The electrical safety monitor of claim 24 further comprising a voltage test circuit.

29. An electrical safety monitor, comprising: a housing having a face, the housing configured for mounting to an electrical cabinet; a plurality of line inputs for hardwiring a plurality of electrical connections; a plurality of meter probe test points with each of the meter probe test points corresponding to one of the line inputs and operatively connected thereto through at least one resistor to provide impedance protection, each of the plurality of meter probe test points accessible at the face of the housing; a line monitoring circuit electrically connected to a plurality of light indicators and configured to produce light if voltage exists between any two of the line inputs to thereby indicate presence of voltage to a user; wherein the electrical safety monitor comprises circuitry configured to allow a user to perform an absence of voltage test (AVT) from outside of the

electrical cabinet.

30. An electrical safety monitor, comprising: a housing for mounting to a door of an electrical cabinet such that the electrical safety monitor is accessible without opening the door of the electrical cabinet; a plurality of line inputs for hardwiring a plurality of electrical connections; a line monitoring circuit electrically connected to a plurality of light indicators and configured to produce light if voltage exists between any two of the plurality of line inputs to thereby indicate presence of voltage to a user; a plurality of meter probe test points with each of the meter probe test points corresponding to one of the line inputs and operatively connected thereto with circuitry configured to provide high input impedance at each of the plurality of meter probe test points, each of the plurality of meter probe test points accessible at a face of the housing; and a transparent cover operatively connected to the housing for covering the face of the housing when the transparent cover is in a closed position thereby protecting the plurality of meter probe test points while allowing the plurality of light indicators to be seen; wherein each of the meter probe test points comprises a conductive area for insertion of a test probe of a voltmeter; wherein the electrical safety monitor is configured to allow the user to perform an absence of voltage test (AVT) from outside of the electrical cabinet.

31. An electrical safety monitor, comprising: a housing for mounting to a door of an electrical cabinet such that the electrical safety monitor is accessible without opening the door of the electrical cabinet; a plurality of line inputs for hardwiring a plurality of electrical connections; a plurality of meter probe test points with each of the meter probe test points corresponding to one of the line inputs and operatively connected thereto, each of the plurality of meter probe test points accessible at a face of the housing; a line monitoring circuit electrically connected to the plurality of line inputs and a plurality of light indicators, the line monitoring circuit configured to produce light using the light indicators to thereby indicate presence of voltage at each of the plurality of line inputs to a user; and wherein the plurality of light indicators are positioned at the face of the electrical safety monitor, with each of the plurality of light indicators corresponding with one of the plurality of meter probe test points; wherein each of the plurality of meter probe test points is impedance protected.

32. An electrical safety monitor, comprising: a housing having a face; a plurality of line inputs for hardwiring a plurality of electrical connections; a plurality of meter probe test points with each of the meter probe test points corresponding to one of the line inputs and operatively connected thereto; a line monitoring circuit electrically connected to the plurality of line inputs and a plurality of light indicators, the line monitoring circuit configured to produce light using the light indicators to thereby indicate presence of voltage at each of the plurality of line inputs to a user; a voltage testing circuit configured for verifying absence of voltage at the plurality of line inputs; wherein each of the plurality of meter probe test points is impedance protected.

33. An electrical safety monitor, comprising: a housing having a face; a plurality of line inputs for hardwiring a plurality of electrical connections; a plurality of meter probe test points with each of the meter probe test points corresponding to one of the line inputs and operatively connected thereto, each of the plurality of meter probe test points accessible at the face of the housing; a line monitoring circuit electrically connected to the plurality of line inputs and a plurality of light indicators, the line monitoring circuit configured to produce light using one or more of the plurality of light indicators to thereby indicate presence of voltage at each of the plurality of line inputs to a user; and illumination areas associated with each of the meter probe test points, wherein each of the illumination areas is provided light by one or more of the plurality of light indicators; wherein each of the illumination areas is positioned around a corresponding one of the meter probe test points.

34. An electrical safety monitor, comprising: a housing for mounting to a door of an electrical cabinet such that the electrical safety monitor is accessible without opening the door of the electrical cabinet; a plurality of input lines; a line monitoring circuit board disposed within the housing and having a line monitoring circuit associated therewith, the line monitoring circuit being

electrically connected to a plurality of visual indicators such that there is at least one of the plurality of visual indicators corresponding with each of the plurality of input lines; a voltage test circuit board disposed within the housing and having a voltage test circuit associated therewith; a plurality of meter probe test points positioned at the face and electrically connected to the voltage test circuit such that each of the plurality of the meter probe test points corresponds with one of the plurality of input lines; a plurality of illumination areas positioned at the face, wherein each of the plurality of illumination areas is positioned around a corresponding one of the meter probe test points.

35. The electrical safety monitor of claim 34 further comprising light pipes for conveying light from the plurality of visual indicators to the illumination areas.

36. The electrical safety monitor of claim 34 wherein the line monitoring circuitry is configured to accommodate DC voltages at the plurality of line inputs.

37. The electrical safety monitor of claim 34 wherein the line monitoring circuitry is configured to accommodate 1500 VDC voltages at the plurality of line inputs.

38. The electrical safety monitor of claim 34 wherein the line monitoring circuitry is configured to accommodate 1000 VAC and 1500 VDC voltages at the plurality of line inputs.

39. The electrical safety monitor of claim 34 further comprising a transparent cover operatively connected to the housing for covering the face of the housing when the transparent cover is in a closed position thereby protecting the plurality of meter probe test point while allowing the illumination areas to be seen.
