

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12386580
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Song; Sungyoon et al.

Cloud server supporting co-editing between electronic devices and operating method thereof

Abstract

A server, one or more electronic devices and method thereof are disclosed. The server provides cloud-based services and includes a communication module, a memory and a processor. The electronic devices further include a display. Both are operable to implement the method, including the server receiving input data including coordinate information from the device(s), the server determining whether the coordinates include a set of adjacent coordinates disposed within a threshold distance of each other, the server generating setting information if so, and transmitting the setting information and coordination information to the devices. The devices display a screen based on data received from the server, generate coordinate information based on user inputs, transmit input data including the coordinate information to the server, and display an object.

Inventors: Song; Sungyoon (Gyeonggi-do, KR), Park; Gun (Gyeonggi-do, KR)

Applicant: Samsung Electronics Co., Ltd. (Gyeonggi-do, KR)

Family ID: 86730624

Assignee: Samsung Electronics Co., Ltd (Suwon-si, KR)

Appl. No.: 18/108927

Filed: February 13, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230195404 A1	Jun. 22, 2023

Foreign Application Priority Data

KR	10-2021-0172778	Dec. 06, 2021
KR	10-2021-0189965	Dec. 28, 2021

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/015709 20221017 PENDING child-doc US 18108927

Publication Classification

Int. Cl.: G06F3/14 (20060101); G06F3/041 (20060101)

U.S. Cl.:

CPC G06F3/1462 (20130101); G06F3/041 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9098230	12/2014	Masuda et al.	N/A	N/A
9513765	12/2015	Miyazaki	N/A	G06F 3/03547
10657219	12/2019	Bowman et al.	N/A	N/A
11004272	12/2020	Wei	N/A	G06T 7/70
2002/0046887	12/2001	Yanagisawa	345/156	G06F 3/0317
2012/0249415	12/2011	Nakajima	345/1.3	G06F 3/04883
2014/0340352	12/2013	Nakajima	345/174	G06F 3/04166
2018/0064024	12/2017	Choi	N/A	G05D 1/0227
2020/0042128	12/2019	Yang	N/A	G06F 3/04886
2021/0349625	12/2020	Li	N/A	G06T 11/60
2021/0349628	12/2020	Lin	N/A	G06F 3/03547
2022/0011888	12/2021	Kim	N/A	G06F 3/0338
2023/0139193	12/2022	Lin	342/442	G01S 5/12

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2012-247861	12/2011	JP	N/A
6431336	12/2017	JP	N/A
10-2017-0070555	12/2016	KR	N/A
10-1826625	12/2017	KR	N/A
10-1876134	12/2017	KR	N/A
10-2019-0039767	12/2018	KR	N/A
10-2019-0138798	12/2018	KR	N/A

Primary Examiner: Vu; Toan H

Attorney, Agent or Firm: Cha & Reiter, LLC.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a Bypass continuation application of International Application No. PCT/KR2022/015709 designating the United States, filed on Oct. 17, 2022, in the Korean Intellectual Property Receiving Office and claiming the benefit under 35 USC § 119(a) of Korean Patent Application No. 10-2021-0172778 filed on Dec. 6, 2021, and Korean Patent Application No. 10-2021-0189965 filed on Dec. 28, 2021, in the Korean Intellectual Property Office, the entire disclosures of which are incorporated herein by reference for all purposes.

BACKGROUND

1. Technical Field

(1) The disclosure relates to cloud computing, and more particularly, to time-shifting user inputs in a collaborative, cloud-based multi-user workspace.

2. Description of Related Art

(2) Recently, electronic devices have advanced so as to provide a diversity of applications and functions, in addition to the ability to communicate with external electronic devices over networks. As electronic devices continue to advance, a demand has arisen for cloud computing capabilities. Cloud computing enables users to store information in a remote server on the Internet, and to access the server for the stored information for usage anytime and anywhere. The increase in cloud computing demand has accelerated the development of various applications that leverage cloud computing in their operations. The development of electronic devices with cloud computing functionality thus enables users to access servers and other such services, such that a same set of applications of information can be accessed over multiple electronic devices.

SUMMARY

(3) A cloud server may enable a plurality of users to perform together co-editing such as drawing or handwriting through electronic devices, thereby enabling cloud-based multi-user collaborative workspaces. As all of the users may perform editing in the multi-user workspace, the electronic devices will generally display results of the edits according to the order in which the user inputs are transmitted to the cloud server, which then provides rendering instructions to each of the electronic devices.

(4) However, when the users perform editing at positions near to each other, readability of objects in the workspace may be degraded due to overlapping coordinates, line segments, drawings, and the like.

(5) According to an embodiment, a server is disclosed, providing cloud-based services for one or more electronic devices, including: a communication module configured to communicate with the one or more electronic devices; a memory storing computer-executable instructions; and a processor operatively coupled to the communication module and the memory, wherein the instructions are executable by the processor to cause the server to: receive input data including at least coordinate information, from at least one of the one or more electronic devices; determine whether adjacent coordinates are included in the coordinate information within a threshold distance of one another by analyzing the coordinate information; based on detecting the adjacent coordinates, generate setting information corresponding to the coordinate information; and transmit output data including the coordinate information and the setting information to the one or more electronic devices.

(6) According to an embodiment, an electronic device is disclosed, including: a communication module configured to communicate with a server providing cloud-based services for one or more electronic devices including the electronic device; a memory storing computer-executable instructions; and a processor operatively coupled to the communication module, the display module

and the memory, wherein the instructions are executable by the processor to cause the electronic device to: display, on the display module, a screen based on output data received from the server, wherein the output data includes coordinate information that is input to at least one of the one or more electronic devices, and setting information corresponding to the coordination information; generate coordinate information based on a user input; transmit, to the server, input data including at least the coordinate information; and display an object corresponding to the coordinate information based on the setting information.

(7) According to an embodiment, an operating method is disclosed, of a server providing cloud-based services for one or more electronic devices, including: receiving input data including at least coordinate information from at least one of the one or more electronic devices, determining whether adjacent coordinates are included in the coordinate information within a threshold distance by analyzing the coordinate information, based on detecting the adjacent coordinates, generating setting information corresponding to the coordinate information, and transmitting output data including the coordinate information and the setting information to the one or more electronic devices.

(8) According to certain embodiments of the present disclosure, there is provided an electronic device that may transmit together time information corresponding to coordinate information to a cloud server and may display an object corresponding to the coordinate information based on setting information generated in the cloud server.

(9) According to certain embodiments of the present disclosure, there is provided a cloud server that may receive coordinate information and time information corresponding to the coordinate information from an electronic device and may generate setting information through correction of an output speed or through time-shifting when there are adjacent coordinates.

(10) Other features and aspects will be apparent from the following detailed description, the drawings, and the claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features, and advantages of certain embodiments of the present disclosure will be more apparent from the following detailed description, taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a block diagram illustrating an electronic device in a network environment according to an embodiment;

(3) FIG. 2 is a block diagram illustrating a display module according to an embodiment;

(4) FIG. 3 is a block diagram illustrating a configuration of an electronic device and a configuration of a cloud server according to an embodiment;

(5) FIG. 4 is a diagram illustrating an example of correcting an output speed of an object corresponding to adjacent coordinates according to an embodiment;

(6) FIG. 5 is a diagram illustrating an example of correcting an output time through time-shifting for adjacent coordinates according to an embodiment;

(7) FIG. 6 is a diagram illustrating an operation of a cloud server to determine adjacent coordinates based on a type of a user input according to an embodiment;

(8) FIG. 7 is a diagram illustrating an operation of a cloud server to generate setting information for adjacent coordinates according to an embodiment;

(9) FIGS. 8A through 8D are diagrams illustrating an example of outputting a screen according to setting information in an electronic device according to an embodiment;

(10) FIG. 9 is a flowchart illustrating an operating method of a cloud server according to an embodiment; and

(11) FIG. 10 is a flowchart illustrating an operating method of an electronic device according to an embodiment.

DETAILED DESCRIPTION

(12) Hereinafter, certain example embodiments will be described in greater detail with reference to the accompanying drawings. When describing the example embodiments with reference to the accompanying drawings, like reference numerals refer to like elements and a repeated description related thereto will be omitted.

(13) <Electronic Device and Cloud Server>

(14) FIG. 1 is a block diagram illustrating an example electronic device in a network environment according to an embodiment.

(15) FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100** according to an embodiment. Referring to FIG. 1, an electronic device **101** in a network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or communicate with at least one of an electronic device **104** and a server **108** via a second network **199** (e.g., a long-range wireless communication network). The electronic device **101** may communicate with the electronic device **104** via the server **108**. The electronic device **101** may include a processor **120**, a memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, and a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one (e.g., the connecting terminal **178**) of the above components may be omitted from the electronic device **101**, or one or more other components may be added to the electronic device **101**. In some embodiments, some (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) of the components may be integrated as a single component (e.g., the display module **160**).

(16) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** connected to the processor **120** and may perform various data processing or computation.

According to an embodiment, as at least a part of data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in a volatile memory **132**, process the command or data stored in the volatile memory **132**, and store resulting data in a non-volatile memory **134**. The processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)) or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121** or to be specific to a specified function. The auxiliary processor **123** may be implemented separately from the main processor **121** or as a part of the main processor **121**.

(17) The auxiliary processor **123** may control at least some of functions or states related to at least one (e.g., the display device **160**, the sensor module **176**, or the communication module **190**) of the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state or along with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). The auxiliary processor **123** (e.g., an ISP or a CP) may be implemented as a portion of another component (e.g., the camera module **180** or the communication module **190**) that is functionally related to the auxiliary processor **123**. The auxiliary processor **123** (e.g., an NPU) may include a hardware structure specifically for artificial intelligence (AI) model processing. An AI model may be generated by

machine learning. The learning may be performed by, for example, the electronic device **101**, in which the AI model is performed, or performed via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, for example, supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The AI model may include a plurality of artificial neural network layers. An artificial neural network may include, for example, a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted Boltzmann machine (RBM), a deep belief network (DBN), and a bidirectional recurrent deep neural network (BRDNN), a deep Q-network, or a combination of two or more thereof, but is not limited thereto. The AI model may alternatively or additionally include a software structure other than the hardware structure.

(18) The memory **130** may store various pieces of data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various pieces of data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**. The non-volatile memory **134** may include an internal memory **136** and an external memory **138**.

(19) The program **140** may be stored as software in the memory **130** and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(20) The input module **150** may receive, from outside (e.g., a user) the electronic device **101**, a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(21) The sound output module **155** may output a sound signal to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing a recording. The receiver may be used to receive an incoming call. The receiver may be implemented separately from the speaker or as a part of the speaker.

(22) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector, and a control circuitry to control its corresponding one of the display, the hologram device, and the projector. The display module **160** may include a touch sensor adapted to sense a touch, or a pressure sensor adapted to measure an intensity of a force of the touch.

(23) The audio module **170** may convert sound into an electric signal or vice versa. The audio module **170** may obtain the sound via the input module **150** or output the sound via the sound output module **155** or an external electronic device (e.g., the electronic device **102**, such as a speaker or headphones) directly or wirelessly connected to the electronic device **101**.

(24) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101** and generate an electric signal or data value corresponding to the detected state. The sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(25) The interface **177** may support one or more specified protocols to be used by the electronic device **101** to couple with an external electronic device (e.g., the electronic device **102**) directly (e.g., by wire) or wirelessly. The interface **177** may include, for example, a high-definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(26) The connecting terminal **178** may include a connector via which the electronic device **101** may physically connect to an external electronic device (e.g., the electronic device **102**). The connecting

terminal **178** may include, for example, an HDMI connector, a USB connector, an SD card connector, or an audio connector (e.g., a headphones connector).

(27) The haptic module **179** may convert an electric signal into a mechanical stimulus (e.g., a vibration or a movement) or an electrical stimulus, which may be recognized by a user via their tactile sensation or kinesthetic sensation. The haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(28) The camera module **180** may capture a still image and moving images. The camera module **180** may include one or more lenses, image sensors, ISPs, and flashes.

(29) The power management module **188** may manage power supplied to the electronic device **101**. The power management module **188** may be implemented as, for example, at least a part of a power management integrated circuit (PMIC).

(30) The battery **189** may supply power to at least one component of the electronic device **101**. The battery **189** may include, for example, a primary cell, which is not rechargeable, a secondary cell, which is rechargeable, or a fuel cell.

(31) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and an external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more CPs that are operable independently from the processor **120** (e.g., an AP) and that support direct (e.g., wired) communication or wireless communication. The communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device, for example, the electronic device **104**, via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., a LAN or a wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multiple components (e.g., multiple chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the SIM **196**.

(32) The wireless communication module **192** may support a 5G network after a 4G network, and a next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., a mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (MIMO), full dimensional MIMO (FD-MIMO), an array antenna, analog beamforming, or a large-scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). The wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a

round trip of 1 ms or less) for implementing URLLC.

(33) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., an external electronic device) of the electronic device **101**. The antenna module **197** may include an antenna including a radiating element including a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). The antenna module **197** may include a plurality of antennas (e.g., an antenna array). In such a case, at least one antenna appropriate for a communication scheme used in a communication network, such as the first network **198** or the second network **199**, may be selected by, for example, the communication module **190** from the plurality of antennas. The signal or power may be transmitted or received between the communication module **190** and the external electronic device via the at least one selected antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as a part of the antenna module **197**.

(34) The antenna module **197** may form a mmWave antenna module. The mmWave antenna module may include a PCB, an RFIC on a first surface (e.g., a bottom surface) of the PCB or adjacent to the first surface of the PCB and capable of supporting a designated high-frequency band (e.g., a mmWave band), and a plurality of antennas (e.g., an antenna array) disposed on a second surface (e.g., a top or a side surface) of the PCB, or adjacent to the second surface of the PCB and capable of transmitting or receiving signals in the designated high-frequency band.

(35) At least some of the above-described components may be coupled mutually and exchange signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general-purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(36) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device (e.g., the electronic device **104**) via the server **108** coupled with the second network **199**. Each of the external electronic devices (e.g., the electronic device **102** or **104**) may be a device of the same type as or a different type from the electronic device **101**. All or some of operations to be executed by the electronic device **101** may be executed by one or more of the external electronic devices (e.g., the electronic devices **102** and **104** and the server **108**). For example, if the electronic device **101** needs to perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or service, may request one or more external electronic devices to perform at least a part of the function or service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request and may transfer a result of the performance to the electronic device **101**. The electronic device **101** may provide the result, with or without further processing of the result, as at least part of a response to the request. To that end, cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra-low latency services using, e.g., distributed computing or MEC. In an embodiment, the external electronic device (e.g., the electronic device **104**) may include an Internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. The external electronic device (e.g., the electronic device **104**) or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., a smart home, a smart city, a smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(37) FIG. 2 is a block diagram **200** illustrating the display module **160** according to an example embodiment. Referring to FIG. 2, the display module **160** may include a display **210** and a display driver integrated circuit (IC) (DDI) **230** for controlling the display **210**. The DDI **230** may include an interface module **231**, a memory **233** (e.g., a buffer memory), an image processing module **235**,

or a mapping module **237**. The DDI **230** may receive, for example, image data or image information including an image control signal corresponding to a command for controlling the image data from another component of the electronic device **101** through the interface module **231**. For example, the image information may be received from the processor **120** (e.g., the main processor **121** (e.g., an application processor)) or the auxiliary processor **123** (e.g., a graphics processing unit (GPU)) operating independently of a function of the main processor **121**. The DDI **230** may communicate with a touch circuit **250** or the sensor module **176** through the interface module **231**. In addition, the DDI **230** may store, in the memory **233**, at least a portion of the received image information in units of frames, for example. The image processing module **235** may perform pre-processing or post-processing (e.g., adjusting resolution, brightness, or size) on the portion of the image data based at least on a characteristic of the image data or a characteristic of the display **210**. The mapping module **237** may generate a voltage value or a current value corresponding to the image data obtained through the pre-processing or the post-processing by the image processing module **235**. The generation of the voltage value or the current value may be performed based at least on attributes (e.g., an arrangement of pixels (RGB stripe or pentile structure), or size of each sub-pixel) of pixels of the display **210**. As at least some pixels of the display **210** may operate based at least on the voltage value or the current value, visual information (e.g., text, images, or icons) corresponding to the image data may be displayed on the display **210**.

(38) According to an embodiment, the display module **160** may further include the touch circuit **250**. The touch circuit **250** may include a touch sensor **251** and a touch sensor integrated circuit (IC) **253** for controlling the touch sensor **251**. For example, the touch sensor IC **253** may control the touch sensor **251** to sense a touch input or a hovering input made at a specific position on the display **210**. In this example, the touch sensor IC **253** may sense the touch input or the hovering input by measuring a change (e.g., a voltage, a light amount, a resistance, or an electric charge amount) in a signal for the specific position on the display **210**. The touch sensor IC **253** may provide the processor **120** with information (e.g., a position, an area, a pressure, or a time) associated with the sensed touch input or hovering input. At least a portion (e.g., the touch sensor IC **253**) of the touch circuit **250** may be included as a portion of the DDI **230**, the display **210**, or another component (e.g., the auxiliary processor **123**) provided outside the display module **160**.

(39) According to an embodiment, the display module **160** may further include at least one sensor (e.g., a fingerprint sensor, an iris sensor, a pressure sensor, or an illuminance sensor) of the sensor module **176**, or a control circuit for controlling the sensor. In this case, the sensor or the control circuit may be embedded in a portion (e.g., the display **210** or the DDI **230**) of the display module **160** or a portion of the touch circuit **250**. For example, when the sensor module **176** embedded in the display module **160** includes a biosensor (e.g., a fingerprint sensor), the biosensor may obtain biometric information (e.g., a fingerprint image) associated with a touch input to a partial area of the display **210**. For another example, when the sensor module **176** embedded in the display module **160** includes a pressure sensor, the pressure sensor may obtain pressure information associated with a touch input through a partial area or an entire area of the display **210**. The touch sensor **251** or the sensor module **176** may be arranged between pixels of a pixel layer of the display **210**, or above or below the pixel layer.

(40) According to certain embodiments of the present disclosure, an electronic device may be a device of one of various types. The electronic device may include, as non-limiting examples, a portable communication device (e.g., a smartphone, etc.), a computing device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. However, the electronic device is not limited to the foregoing examples.

(41) It is to be understood that various example embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. In connection with the description of the drawings, like reference numerals may be

used for similar or related components. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things unless the relevant context clearly indicates otherwise. As used herein, “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” each of which may include any one of the items listed together in the corresponding one of the phrases, or all possible combinations thereof. Terms such as “first,” “second,” or “first” or “second” may simply be used to distinguish the component from other components in question, and do not limit the components in other aspects (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively,” as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., by wire), wirelessly, or via a third element.

(42) As used in connection with certain embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry.” A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in the form of an application-specific integrated circuit (ASIC).

(43) Certain embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., the internal memory **136** or the external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium and execute it. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include code generated by a compiler or code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Here, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(44) According to certain embodiments, a method described herein may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., a compact disc read-only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smartphones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as a memory of the manufacturer's server, a server of the application store, or a relay server.

(45) According to certain embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to certain embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to certain embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration.

(46) According to certain embodiments, operations performed by the module, the program, or

another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(47) FIG. 3 is a block diagram illustrating an example configuration of an electronic device (e.g., the electronic devices **101**, **102**, and **104**) and a configuration of a cloud server **300** according to an embodiment.

(48) Referring to FIG. 3, illustrated are a plurality of electronic devices **101**, **102**, and **104** and a cloud server **300** supporting a joint work between the electronic devices **101**, **102**, and **104**.

(49) The electronic device **101** may include the communication module **190** that communicates with the cloud server **300**, the display module **160** that displays a screen based on output data received from the server **300**, the memory **130** that stores therein computer-executable commands, and the processor **120** that executes the instructions by accessing the memory **130**. The electronic device **101** may include the input module **150** that receives a user input and the sensor module **176** that obtains information associated with a touch input. For a more detailed description of the electronic device **101**, the memory **130**, the processor **120**, the input module **150**, the communication module **190**, the display module **160**, and the sensor module **176**, reference may be made to what has been described above with reference to FIGS. 1 and 2 and a repeated description thereof will be omitted here.

(50) According to an embodiment, the instructions stored in the memory **130** of the electronic device **101** may be configured to cause the electronic device **101** to generate coordinate information based on a user input; transmit input data including the coordinate information and time information corresponding to the coordinate information to the cloud server **300**; and display an object corresponding to the coordinate information based on setting information included in output data received from the cloud server **300**. The output data may include the coordinate information input to at least one (e.g., the electronic devices **101** and **102**) of one or more electronic devices (e.g., the electronic devices **101**, **102**, and **104**) and the setting information corresponding to the coordinate information.

(51) The electronic device **102** and the electronic device **104** may include the same or corresponding components as the electronic device **101**, and the electronic devices **101**, **102**, and **104** may perform a joint work through the cloud server **300**. For example, any one of drawing and handwriting may be performed in each of the electronic devices **101**, **102**, and **104**, and a result of the performing may be output from all the electronic devices **101**, **102**, and **104**.

(52) The cloud server **300** may include a communication module **390** that communicates with the electronic devices **101**, **102**, and **104**, a memory **330** that stores therein computer-executable instructions, and a processor **320**. The communication module **390**, the memory **330**, and the processor **320** may be the same or similar components, for example, the communication module **190**, the memory **130**, and the processor **120** described above with reference to FIG. 1. The memory **330** may include, for example, a volatile memory or a non-volatile memory.

(53) According to an embodiment, the instructions stored in the memory **330** of the cloud server **300** may be configured to cause the cloud server **300** to receive, from at least one (e.g., the electronic device **102**) of one or more electronic devices (e.g., the electronic devices **101**, **102**, and **104**), input data including coordinate information and time information corresponding to the coordinate information; determine whether there are adjacent coordinates within a threshold distance by analyzing the coordinate information; when there are the adjacent coordinates, generate setting information corresponding to the coordinate information; and transmit output data including the coordinate information and the setting information to the one or more electronic devices **101**, **102**, and **104**.

(54) According to an embodiment, the processor **320** of the cloud server **300** may determine whether there are adjacent coordinates based on coordinate information received from the same electronic device **101**, and generate the setting information including output speed information of

an object corresponding to the coordinate information. An example of determining whether there are adjacent coordinates based on coordinate information received from the same electronic device (e.g., the electronic device **101**) will be described in detail with reference to FIG. 4.

(55) According to an embodiment, the processor **320** of the cloud server **300** may determine whether there are adjacent coordinates based on coordinate information received from different electronic devices (e.g., the electronic devices **101** and **102**), and generate the setting information including output time information of an object corresponding to the coordinate information. An example of determining whether there are adjacent coordinates based on coordinate information received from different electronic devices (e.g., the electronic devices **101** and **102**) will be described in detail with reference to FIG. 5. In addition, an example of determining whether there are adjacent coordinates based on the coordinate information received from the different electronic devices (e.g., the electronic devices **101** and **102**), and displaying an object on the electronic devices **101**, **102**, and **104** will be described in detail with reference to FIGS. 7, and 8A through 8D.

(56) According to an embodiment, the setting information corresponding to the coordinate information may be generated according to user settings. For example, when the coordinate information received from the same electronic device **101** indicates adjacent coordinates according to the user settings, the setting information may include the output time information instead of output speed information of the object. For another example, when the coordinate information received from different electronic devices, for example, the electronic devices **101** and **102**, indicates adjacent coordinates, the setting information may include the output speed information instead of the output time information of the object. Alternatively, the setting information may not be generated according to the user settings.

(57) According to an embodiment, the time information may not be included in the input data, and the processor **320** may transmit the coordinate information to the one or more electronic devices **101**, **102**, and **104** without generating the setting information corresponding to the coordinate information.

(58) According to an embodiment, the coordinate information may be generated according to a user input to each of the one or more electronic devices **101**, **102**, and **104**, and the user input may include, for example, any one of drawing and handwriting. Whether there are adjacent coordinates may be determined in various ways depending on a type of the user input. An operation of the processor **320** of the cloud server **300** to determine adjacent coordinates according to a type of a user input will be described in detail below with reference to FIG. 6.

(59) According to an embodiment, the processor **320** of the cloud server **300** may use an algorithm for maintaining consistency between pieces of coordinate information received from the one or more electronic devices **101**, **102**, and **104**. For example, the processor **320** may use an operational transformation (OT) algorithm to prevent a collision between pieces of coordinate information received from different electronic devices.

(60) According to an embodiment, a processor (e.g., the processor **120** of the electronic device **101**) of the one or more electronic devices **101**, **102**, and **104** may display an object corresponding to coordinate information, based on the coordinate information and setting information corresponding to the coordinate information received from the cloud server **300**. For example, objects may be displayed on the electronic device **101** as to be described below with reference to FIGS. 4 through 8D. Although examples will be described based mainly on the electronic device **101** with reference to FIGS. 4 through 8D, examples are not limited thereto and the same screen may also be displayed on each of the one or more electronic devices **101**, **102**, and **104**.

(61) Hereinafter, operations of the electronic device **101** and the cloud server **300** will be described in detail with reference to FIGS. 4 through 10.

(62) FIG. 4 is a diagram illustrating an example of correcting an output speed of an object corresponding to adjacent coordinates according to an embodiment.

(63) Although FIGS. 4 through 8D illustrate example screens displayed on the electronic device

101, this is provided merely as an example, and it should be understood the same screen may be displayed on each of one or more electronic devices (e.g., the electronic devices **101**, **102**, and **104**) communicating with the cloud server **300**.

(64) According to an embodiment, for a joint work (e.g., interoperation) performed between the one or more electronic devices **101**, **102**, and **104** through the cloud server **300**, the processor **320** of the cloud server **300** may determine whether adjacent coordinates are extant based on coordinate information received from the same electronic device **101**. For example, a user may draw, with a digital pen, a line **410** including coordinates **411**, **413**, **415**, and **417** on the electronic device **101**. In this example described with reference to FIG. 4, the user may input, to the electronic device **101**, the coordinates in sequential order, starting from the coordinate **411** to the coordinate **413**, the coordinate **415**, and the coordinate **417**. The processor **120** of the electronic device **101** may receive the user input through the input module **150**, and generate the coordinate information based on the user input.

(65) According to an embodiment, the processor **120** of the electronic device **101** may transmit input data including the coordinate information and time information corresponding to the coordinate information to the cloud server **300**. For example, the processor **120** of the electronic device **101** may transmit, as the input data, information (1, 4), (2, 3), (2.5, 2.5), and (4, 1) about the coordinates **411**, **413**, **415**, and **417** and the time information about time at which the coordinates **411**, **413**, **415**, and **417** are input, respectively.

(66) According to an embodiment, the processor **320** of the cloud server **300** may determine whether there are adjacent coordinates disposed within a threshold distance of one another, by analyzing the coordinate information. For example, as illustrated in FIG. 4, a distance between the coordinate **413** and the coordinate **415** is less than or equal to the threshold distance (e.g., a unit of 1 distance), the processor **320** of the cloud server **300** may determine that adjacent coordinates are extant within the coordinate information.

(67) According to an embodiment, when there are adjacent coordinates, the processor **320** of the cloud server **300** may generate setting information corresponding to the coordinate information, and transmit output data including the coordinate information and the setting information to the one or more electronic devices **101**, **102**, and **104**. According to an embodiment, when determining that there are adjacent coordinates based on the coordinate information received from the same electronic device **101**, the processor **320** may generate the setting information including output speed information of an object corresponding to the coordinate information.

(68) For example, when the coordinates **413** and **415**, as received from the same electronic device **101**, are adjacent to each other, the processor **320** may set an output speed for the adjacent coordinates **413** and **415** to be a first speed, which may be comparatively low or slow. In contrast, the processor **320** may set an output speed to be a second speed, that is comparatively high or fast, being greater than the first speed, for the other coordinates **411** and **417** that are not adjacent to each other.

(69) According to an embodiment, the one or more electronic devices **101**, **102**, and **104** may display the object corresponding to the coordinate information based on the setting information in the received output data. For example, referring to FIG. 4, after the coordinate **411** is displayed on the electronic device **101**, the coordinate **413** and a line segment between the coordinates **411** and **413** may be output “fast” (e.g., at the second speed). Thereafter, the coordinate **415** and a line segment between the coordinates **413** and **415** may be output “slow” (e.g., at the first speed), and the coordinate **417** and a line segment between the coordinates **415** and **417** may be output fast again. Because the one or more electronic devices **101**, **102**, and **104** are performing a joint work together, the screen of the electronic device **101** is illustrated in FIG. 4. However, the same objects may be also displayed on the displays of the other electronic devices **102** and **104**. An example of how an object is displayed according to setting information will be described in detail below with reference to FIGS. 8A through 8D.

(70) According to the embodiment described above with reference to FIG. 4, the correction of an output speed may improve the visibility of the adjacent coordinates **413** and **415** and may allow joint users (e.g., respective users of the one or more electronic devices **101**, **102**, and **104**) to identify a sequence of the work more clearly.

(71) FIG. 5 is a diagram illustrating an example of correcting an output time through time-shifting for adjacent coordinates according to an embodiment.

(72) Referring to FIG. 5, illustrated is an example screen displayed on the electronic device **101** in which the one or more electronic devices **101**, **102**, and **104** perform a joint work through the cloud server **300**. Although FIG. 5 illustrates a screen displayed on the electronic device **101** for convenience of description, a user of the electronic device **101** may perform a work with the electronic device **101** and a user of the electronic device **102** may perform a work with the electronic device **102**, and objects in setting information generated by the cloud server **300** may be displayed on respective screens of all electronic devices (e.g., the one or more electronic devices **101**, **102**, and **104**) performing the joint work.

(73) For example, the user of the electronic device **101** may draw a line **510** including coordinates **511**, **513**, and **515** on the electronic device **101** with a digital pen, and the user of the electronic device **102** may draw a line **550** including coordinates **551**, **553**, and **555** with a digital pen. In this example described with reference to FIG. 5, the coordinates **511**, **513**, and **515** may be sequentially input to the electronic device **101**, and the coordinates **551**, **553**, and **555** may be sequentially input to the electronic device **102**. The processors of the electronic devices **101** and **102** may each receive the respective user inputs through input modules and generate the coordinate information based on the user inputs.

(74) According to an embodiment, the processors of the electronic device **101** and **102** may each transmit input data including the coordinate information and time information corresponding to the coordinate information to the cloud server **300**. For example, the processor **120** of the electronic device **101** may transmit, as the input data, the coordinates (1, 1), (2, 2), and (4, 4) as the coordinates **511**, **513**, and **515**, and the time information which indicates times at which each of the coordinates **511**, **513**, and **515** are input respectively. In addition, the processor of the electronic device **102** may transmit, as the input data, coordinates (1, 4), (2, 3), and (4, 1) as the coordinates **551**, **553**, and **555**, and the time information which indicates times at which each of the coordinates **551**, **553**, and **555** were input respectively.

(75) According to an embodiment, the processor **320** of the cloud server **300** may analyze the coordinate information received from the electronic devices **101** and **102**, which are different electronic devices, and may determine whether there are any adjacent coordinates within a threshold distance found within the coordinate information. For example, since a distance between the coordinate **553** input from the electronic device **102** and the coordinate **513** input from the electronic device **101** is less than or equal to the threshold distance (e.g., a distance unit of “1”), the processor **320** of the cloud server **300** may determine that there are adjacent coordinates extant in the coordinate information.

(76) According to an embodiment, when determining that there are adjacent coordinates, the processor **320** of the cloud server **300** may generate setting information corresponding to the coordinate information, and transmit output data including the coordinate information and the setting information to the one or more electronic devices **101**, **102**, and **104**. When determining that there are adjacent coordinates in the coordinate information received from the different electronic devices **101** and **102**, the processor **320** may generate the setting information including output time information of an object corresponding to the coordinate information.

(77) For example, the processor **320** may generate the setting information by correcting an output time via time-shifting for the adjacent coordinates **513** and **553**. The processor **320** may perform time-shifting on the output time based on a coordinate (e.g., the coordinate **513**) that is input first between the two adjacent coordinates **513** and **553**. An example of how the processor **320** of the

cloud server **300** generates setting information by performing time-shifting on adjacent coordinates input from different electronic devices will be described in detail below with reference to FIG. 7.

(78) According to an embodiment, the one or more electronic devices **101**, **102**, and **104** may display the object corresponding to the coordinate information based on the setting information in the received output data. For example, referring to FIG. 5, after the coordinate **511** is displayed on the electronic device **101**, the output of coordinates **513**, **515**, **551**, **553**, and **555** may be time-shifted. Although the screen of the electronic device **101** is illustrated in FIG. 5, objects may also be displayed in corresponding manner on the electronic device **102** and the electronic device **104**, because the one or more electronic devices **101**, **102**, and **104** are performing an interoperative joint work together.

(79) An example of how objects time-shifted based on setting information are output to each electronic device (e.g., the electronic devices **101**, **102**, and **104**) will be described in detail below with reference to FIGS. 8A through 8D.

(80) According to the embodiment described above with reference to FIG. 5, the correction of an output time through time-shifting may improve the visibility of the adjacent coordinates **513** and **553**, and may allow joint users (e.g., the respective users of the one or more electronic devices **101**, **102**, and **104**) to identify the sequence and subject of the work more clearly.

(81) FIG. 6 is a diagram illustrating an example operation of a cloud server to determine adjacent coordinates based on a type of a user input according to an embodiment.

(82) Referring to FIG. 6, illustrated is an example screen displayed on the electronic device **101** when one or more electronic devices **101**, **102**, and **104** perform a joint work through the cloud server **300**. Although examples of a user input have been described as coordinates and lines above with reference to FIGS. 4 and 5, the user input is not limited thereto, and various types of user inputs such as figures and characters may also be used during a joint work.

(83) For example, referring to FIG. 6, a rectangular object **610** formed with coordinates **611**, **613**, **615**, and **617** may be generated according to a user input to the electronic device **101**, and a line **650** with coordinates **651** and **653** may be generated according to another user input to the electronic device **102**.

(84) As described above with reference to FIGS. 4 and 5, the processor **320** of the cloud server **300** may receive, from each client terminal (e.g., the electronic device **101** and the electronic device **102**), input data including coordinate information based on a user input and time information, and may determine whether there are adjacent coordinates in the coordinate information.

(85) Referring to FIG. 6, the processor **320** may calculate a shortest distance between the rectangular object **610** and the line **650**. For example, the processor **320** may determine, as the shortest distance, a distance between the coordinate **613** of the rectangular object **610** and a coordinate (4, 4) **651** of the line **650**. In this example, when the shortest distance is within a threshold distance, the processor **320** may determine the coordinate **613** and the coordinate **651** to be adjacent coordinates.

(86) According to an embodiment, when adjacent coordinates are detected, the processor **320** may generate setting information corresponding to the coordinate information and transmit output data including the setting information and the coordinate information to the electronic devices **101**, **102**, and **104**. As described above with reference to FIGS. 3 through 5, the setting information may include output speed information for an object corresponding to the coordinate information, or output time information corresponding to the coordinate information. The electronic devices **101**, **102**, and **104** may display the object corresponding to the coordinate information based on the setting information.

(87) FIG. 7 is a diagram illustrating an example operation of a cloud server to generate setting information for adjacent coordinates according to an embodiment.

(88) Referring to FIG. 7, an example is illustrated of how one or more electronic devices **101**, **102**, and **104** perform a joint work through the cloud server **300**. According to an embodiment, input

data including coordinate information and time information may be transmitted to the cloud server **300** according to a user input to the electronic device **101** as indicated by an arrow **701**, and may be transmitted to the cloud server **300** according to a user input to the electronic device **102** as indicated by an arrow **702**.

(89) The processor **320** of the cloud server **300** may obtain, from the input data received from the electronic device **101**, information about a line **710** including coordinates **711**, **713**, and **715** and the time information about time at which the coordinates are input, and may obtain, from the input data received from the electronic device **102**, information about a line **750** including coordinates **751**, **753**, and **755** and the time information about time at which the coordinates are input.

(90) According to an embodiment, the processor **320** of the cloud server **300** may determine that there are adjacent coordinates because a distance between the coordinate **713** and the coordinate **753** is within a threshold distance (e.g., a distance unit of “1”), and generate setting information corresponding to the coordinate information.

(91) For example, the processor **320** may generate the setting information, including output speed information, as associated with the coordinates **711**, **713**, and **715** that are included in the line **710**, and which are input to the electronic device **101**. For example, the processor **320** may delay an output time of the coordinate **713** to 300 by 100, and delay an output time of the coordinate **715** to 500 by 100, without changing an output time of the coordinate **711**.

(92) For another example, the processor **320** may time-shift an output time of the coordinates **751**, **753**, and **755** included in the line **750** input to the electronic device **102**. For example, the processor **320** may shift the output time by 500 for each of all the coordinates **751**, **753**, and **755**.

(93) However, example embodiments are not limited to the above-described examples, and the processor **320** may generate the setting information in various ways. For example, the processor **320** may further change attribute values such as boldness, transparency, and color while correcting the output time or the output speed. For example, the processor **320** may apply boldness, increase transparency, increase thickness, and increase saturation for the coordinates **715**, **753**, and **755** that are input after the coordinate **713** which is input first between the adjacent coordinates **713** and **753**, and may then exclude boldness, lower transparency, reduce thickness, and lower saturation for a corresponding coordinate or the coordinates **711** and **713** that are previously input.

(94) According to an embodiment, the processor **320** of the cloud server **300** may transmit output data including the coordinate information and the setting information to the electronic devices **101**, **102**, and **104** that are performing the joint work together. For example, the output data corresponding to the work performed in the electronic device **101** may be transmitted to the electronic devices **101**, **102**, and **104** as indicated by arrows **703**, **706**, and **707**, and the output data corresponding to the work performed in the electronic device **102** may be transmitted to the electronic devices **101**, **102**, and **104** as indicated by arrows **704**, **705**, and **708**.

(95) The electronic devices **101**, **102**, and **104** may display an object corresponding to the coordinate information based on the setting information in the received output data. An example of how objects are displayed on electronic devices will be described in detail below with reference to FIGS. **8A** through **8D**.

(96) FIGS. **8A** through **8D** are diagrams illustrating an example of outputting a screen according to setting information in an electronic device according to an embodiment.

(97) Referring to FIGS. **8A** through **8D**, after output data is transmitted to an electronic device as described above with reference to FIG. **7**, an object corresponding to coordinate information may be displayed on the electronic device **101** according to setting information. Although the example to be described hereinafter with reference to FIGS. **8A** through **8D** is based mainly on the electronic device **101**, example screens illustrated in FIGS. **8A** through **8D** may be displayed on all the electronic devices **101**, **102**, and **104** performing a joint work as described above with reference to FIG. **7**.

(98) For example, coordinates **811**, **813**, **815**, **851**, **853**, and **855** and lines **810** and **850** that are

illustrated in FIGS. 8A through 8D may correspond to the coordinates **711**, **713**, **715**, **751**, **753**, and **755** and the lines **710** and **750** that are illustrated in FIG. 7. As described above with reference to FIG. 7, an output speed may be set to be a first speed (e.g., “slow”) by being delayed by 100, starting from the coordinate **813** which is an adjacent coordinate among the line **810** and the coordinates **811**, **813**, and **815** corresponding to input data generated by the electronic device **101**. In addition, as described above with reference to FIG. 7, an output time may be changed as the line **850** and the coordinates **851**, **853**, and **855** corresponding to input data generated by the electronic device **102** are all time-shifted by 500.

(99) For example, referring to FIG. 8A, the coordinate **811** may be output at time **100** in the electronic device **101**, and the coordinate **813** may be output at time **300**, corresponding to a delay of 100 time units from time **200**, that is the input time information described above with reference to FIG. 7. Referring to FIG. 8B, the coordinate **815** may be output at time **500** that is delayed by 100 time units from time **400** that is the input time information described above with reference to FIG. 7.

(100) Referring to FIGS. 8C and 8D, the line **850** and the coordinates **851**, **853**, and **855** corresponding to the input data generated by the electronic device **102** may all be time-shifted by 500 to be output. The time information included in the input data of the coordinates **751**, **753**, and **755** described above with reference to FIG. 7 may include time **200**, time **250**, and time **600**, respectively. However, referring to FIGS. 8C and 8D, they may be time-shifted by 500 each, and be output at time **700**, time **750**, and time **1100**, respectively.

(101) According to an embodiment, the time-shifting or the output speed correction for adjacent coordinates described above with reference to FIGS. 8A through 8D may be applied when synchronization is performed between coordinate information for respective users when joint users are performing work in real time.

(102) According to embodiment, the time-shifting or the output speed correction described above with reference to FIGS. 8A through 8D may also be applied in the same way even when a user cancels (or rolls back) the execution. For example, in a situation of FIG. 8D, the user of the electronic device **101** may cancel the execution of an immediate portion of work performed by a joint user, and the example screens illustrated in FIGS. 8C, 8B, and 8A may be sequentially displayed on the electronic device **101**.

(103) While the screens illustrated in FIGS. 8C, 8B, and 8A, starting from the screen illustrated in FIG. 8D, are being displayed, the time-shifting or the output speed correction described above may be applied once again. For example, as the user of the electronic device **101** presses a button indicating “cancel execution” (or “undo,” “roll back,” etc.) in the situation of FIG. 8D, time at which the screen illustrated in FIG. 8C is output again may be time **1450** that is delayed from time **1100** of FIG. 8D by 350 that is a difference between time **750** of FIG. 8C and time **1100** of FIG. 8D. For another example, a time at which the screen illustrated in FIG. 8B is re-output after the execution is re-canceled in the situation of FIG. 8C, may be a time **1500** corresponding to a delay from time **1450** of FIG. 8C by 50 that is a difference between time **700** of FIG. 8B and time **750** of FIG. 8C.

(104) According to an embodiment, as described above with reference to FIGS. 8A through 8D, an operation of displaying an object on the electronic device **101** may be activated or deactivated according to user settings. For example, when displaying a result of performing a joint work, the user of the electronic device **101** may configure a setting that controls adjustment of output based on the presence or absence of adjacent coordinates, while the user of the electronic device **102** and the user of the electronic device **104** may configure their own instances of the application to use the output adjustment function. In this example, the electronic device **101** may display an output based on the time information included in the input data generated by the electronic devices **101** and **102** as described above with reference to FIG. 7. For example, the coordinate **811** may be output at time **100**, the coordinate **813** at time **200**, the coordinate **815** at time **400**, the coordinate **751** at time **200**,

the coordinate **753** at time **250**, and the coordinate **755** at time **600**.

(105) <Operating Method of Electronic Device>

(106) FIG. **9** is a flowchart illustrating an example operating method of a cloud server according to an embodiment.

(107) Operations **910** through **940** to be described hereinafter with reference to FIG. **9** may be performed by the processor **320** of the cloud server **300** described above with reference to FIG. **3**, and what has been described above with reference to FIGS. **1** through **8D** will not be repeated for conciseness.

(108) In operation **910**, the processor **320** may receive input data including coordinate information and time information corresponding to the coordinate information from at least one device (e.g., the electronic device **101** and the electronic device **102**) of one or more electronic devices (e.g., the electronic devices **101**, **102**, and **104**).

(109) In operation **920**, the processor **320** may determine whether the coordinate information includes within it adjacent coordinates within a threshold distance of each other, by analyzing the coordinate information. In the absence of the adjacent coordinates, an object may be displayed on each electronic device without correction of the input data.

(110) In operation **930**, in the presence of the adjacent coordinates, the processor **320** may generate setting information corresponding to the coordinate information. As described above with reference to FIGS. **4** through **8D**, the processor **320** may generate the setting information including output speed information of an object corresponding to the coordinate information or the setting information including output time information of the object corresponding to the coordinate information.

(111) In operation **940**, the processor **320** may transmit output data including the coordinate information and the setting information to the one or more electronic devices **101**, **102**, and **104**.

(112) FIG. **10** is a flowchart illustrating an operating method of an electronic device according to an embodiment.

(113) Operations **1010** through **1040** to be described hereinafter with reference to FIG. **10** may be performed by the processor **120** of the electronic device **101** described above with reference to FIG. **3**, and what has been described above with reference to FIGS. **1** through **8D** will not be repeated for conciseness.

(114) In operation **1010**, the processor **120** may generate coordinate information based on a user input. For example, as a user performs handwriting or drawing with the electronic device **101**, the coordinate information may be generated.

(115) In operation **1020**, the processor **120** may transmit input data including the coordinate information and time information corresponding to the coordinate information to the cloud server **300**. As described above with reference to FIGS. **4** through **8D**, the processor **120** may transmit, to the cloud server **300**, each coordinate and time information indicative of respective times at which each coordinate information is input. In addition, as described above with reference to FIG. **9**, the processor **320** of the cloud server **300** may generate setting information corresponding to the coordinate information when there are adjacent coordinates based on the received input data.

(116) In operation **1030**, the processor **120** may receive output data from the cloud server **300**. The output data may include coordinate information input to at least one (e.g., the electronic device **101** and the electronic device **102**) of one or more electronic devices (e.g., the electronic devices **101**, **102**, and **104**) and setting information corresponding to each coordinate information.

(117) In operation **1040**, the processor **120** may display an object corresponding to the coordinate information based on the setting information. As described above with reference to FIGS. **8A** through **8D**, the processor **120** may display the object according to the setting information in which an output time or an output speed is corrected.

(118) According to an embodiment, a cloud server (e.g., the cloud server **300**) for a joint work among one or more electronic devices (e.g., the electronic devices **101**, **102**, and **104**) may include

a communication module (e.g., the communication module **390**) that communicates with the electronic devices **101**, **102**, and **104**; a memory (e.g., the memory **330**) that stores therein computer-executable instructions; and a processor (e.g., the processor **320**) that executes the instructions by accessing the memory **330**. The instructions may be configured to cause the cloud server **300** to receive input data including coordinate information and time information corresponding to the coordinate information from at least one (e.g., the electronic devices **101** and **102**) of the electronic devices **101**, **102**, and **104**; determine whether there are adjacent coordinates within a threshold distance by analyzing the coordinate information; when there are adjacent coordinates, generate setting information corresponding to the coordinate information; and transmit output data including the coordinate information and the setting information to the electronic devices **101**, **102**, and **104**.

(119) The coordinate information may be generated based on a user input to each of the electronic devices **101**, **102**, and **104**, and the user input may include one of drawing and handwriting.

(120) The adjacent coordinates may be determined based on coordinate information received from the same electronic device (e.g., the electronic device **101**), and the setting information may include output speed information of an object corresponding to the coordinate information.

(121) The adjacent coordinates may be determined based on coordinate information received from different electronic devices (e.g., the electronic devices **101** and **102**), and the setting information may include output time information of an object corresponding to the coordinate information.

(122) The instructions may be configured to cause the cloud server **300** to transmit the coordinate information to the one or more electronic devices **101**, **102**, and **104** without generating the setting information, when the time information is not present in the input data.

(123) The instructions may be further configured to cause the cloud server **300** to use an algorithm for maintaining consistency in the coordinate information received from the one or more electronic devices **101**, **102**, and **104**.

(124) The setting information may be settable by a user.

(125) The one or more electronic devices **101**, **102**, and **104** may display the object corresponding to the coordinate information based on the setting information.

(126) According to an embodiment, an electronic device (e.g., the electronic device **101**) may include a communication module (e.g., the communication module **190**) that communicates with a server (e.g., the cloud server **300**) for a joint work among one or more electronic devices (e.g., electronic devices **101**, **102**, and **104**); a display module (e.g., the display module **160**) that displays a screen based on output data received from the server **300**; a memory (e.g., the memory **130**) that stores therein computer-executable instructions; and a processor (e.g., the processor **120**) that executes the instructions by accessing the memory **130**. The output data may include coordinate information input to at least one (e.g., the electronic devices **101** and **102**) of the one or more electronic devices **101**, **102**, and **104**, and setting information corresponding to the coordinate information. The instructions may be configured to cause the electronic device **101** to generate the coordinate information based on a user input; transmit the input data including the coordinate information and time information corresponding to the coordinate information to the server **300**; and display an object corresponding to the coordinate information based on the setting information.

(127) The user input may include one of drawing and handwriting.

(128) The server **300** may receive the input data including the coordinate information and the time information corresponding to the coordinate information from the at least one electronic device (e.g., the electronic devices **101** and **102**) of the one or more electronic devices **101**, **102**, and **104**; determine whether there are adjacent coordinates within a threshold distance by analyzing the coordinate information; when there are adjacent coordinates, generate the setting information corresponding to the coordinate information; and transmit the output data including the coordinate information and the setting information to the one or more electronic devices **101**, **102**, and **104**.

(129) The adjacent coordinates may be determined based on coordinate information received from

the same electronic device (e.g., the electronic device **101**), and the setting information may include output speed information of an object corresponding to the coordinate information.

(130) The adjacent coordinates may be determined based on coordinate information received from different electronic devices, and the setting information may include output time information of an object corresponding to the coordinate information.

(131) When the time information is not present in the input data, the server **300** may transmit the coordinate information to the one or more electronic devices **101**, **102**, and **104** without generating the setting information.

(132) According to an embodiment, an operating method of the server **300** for a joint work among one or more electronic devices (e.g., the electronic devices **101**, **102**, and **104**) may include: receiving input data including coordinate information and time information corresponding to the coordinate information from at least one (e.g., the electronic devices **101** and **102**) of the one or more electronic devices **101**, **102**, and **104**; determining whether there are adjacent coordinates within a threshold distance by analyzing the coordinate information; when there are adjacent coordinates, generating setting information corresponding to the coordinate information; and transmitting output data including the coordinate information and the setting information to one or more electronic devices **101**, **102**, and **104**.

(133) The coordinate information may be generated based on a user input to each of the one or more electronic devices **101**, **102**, and **104**, and the user input may include one of drawing and handwriting.

(134) The adjacent coordinates may be determined based on coordinate information received from the same electronic device (e.g., the electronic device **101**), and the setting information may include output speed information of an object corresponding to the coordinate information.

(135) The adjacent coordinates may be determined based on coordinate information received from different electronic devices (e.g., the electronic devices **101** and **102**), and the setting information may include output time information of an object corresponding to the coordinate information.

(136) The one or more electronic devices **101**, **102**, and **104** may display the object corresponding to the coordinate information based on the setting information.

(137) While the present disclosure has been shown and described with reference to certain embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the present disclosure as defined by the appended claims and their equivalents.

Claims

1. A server providing cloud-based services for one or more electronic devices, comprising: a communication module configured to communicate with the one or more electronic devices; a memory storing computer-executable instructions; and a processor operatively coupled to the communication module and the memory, wherein the instructions are executable by the processor to cause the server to: receive input data including at least coordinate information; from at least one of the one or more electronic devices; determine whether adjacent coordinates are included in the coordinate information within a threshold distance of one another by analyzing the coordinate information; based on detecting the adjacent coordinates, generate setting information corresponding to the coordinate information; and transmit output data including the coordinate information and the setting information to the one or more electronic devices.
2. The server of claim 1, wherein the coordinate information is generated based on user inputs received by each of the one or more electronic devices, wherein the user inputs include any one of a drawing input and a handwriting input.
3. The server of claim 1, wherein the adjacent coordinates are determined based on coordinate information received from the same electronic device, and wherein the setting information includes

output speed information for an object corresponding to the coordinate information.

4. The server of claim 1, wherein the adjacent coordinates are determined based on coordinate information received from different electronic devices, and wherein the setting information includes output time information for an object corresponding to the coordinate information.

5. The server of claim 1, wherein the instructions are further executable to cause the server to: when time information is omitted from the input data, transmit the coordinate information to the one or more electronic devices in absence of generating the setting information.

6. The server of claim 1, wherein the instructions are further executable to cause the server to: using an algorithm, maintain consistency between different pieces of coordinate information received from the one or more electronic devices.

7. The server of claim 1, wherein the setting information is configurable by a user.

8. The server of claim 1, wherein the one or more electronic devices are configured to display an object corresponding to the coordinate information based on the setting information.

9. An operating method of a server providing cloud-based services for one or more electronic devices, comprising: receiving input data including at least coordinate information from at least one of the one or more electronic devices; determining whether adjacent coordinates are included in the coordinate information within a threshold distance by analyzing the coordinate information; based on detecting the adjacent coordinates, generating setting information corresponding to the coordinate information; and transmitting output data including the coordinate information and the setting information to the one or more electronic devices.

10. The operating method of claim 9, wherein the coordinate information is generated based on user inputs received by each of the one or more electronic devices, wherein the user inputs include any one of a drawing input and a handwriting input.

11. The operating method of claim 9, wherein the adjacent coordinates received from the same electronic device, and wherein the setting information includes output speed information for an object corresponding to the coordinate information.

12. The operating method of claim 9, wherein the adjacent coordinates are determined based on coordinate information received from different electronic devices, and wherein the setting information includes output time information for an object corresponding to the coordinate information.

13. The operating method of claim 9, wherein the one or more electronic devices are configured to display an object corresponding to the coordinate information based on the setting information.

14. A non-transitory computer-readable storage medium storing instructions that, when executed by a processor, cause the processor to perform the operating method of claim 9.
