

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12388674
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Heo; Junyeon et al.

Electronic device and method of operating the same

Abstract

An electronic device includes a communication module, and processor and a memory. The communication module connects with an Internet of Things server and plural smart devices. The processor is operatively connected to the communication module. The memory is operatively connected to the processor and includes instructions which, when executed by the processor, cause the processor to configure a control interface for controlling operations of the smart devices according to a user schedule type of a user schedule, and control the operations of the smart devices through the control interface.

Inventors: Heo; Junyeon (Suwon-si, KR), Kim; Changwon (Suwon-si, KR), Jung; Joohee (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 86694030

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 18/092024

Filed: December 30, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230188378 A1	Jun. 15, 2023

Foreign Application Priority Data

KR	10-2021-0178717	Dec. 14, 2021
KR	10-2021-0192671	Dec. 30, 2021

Related U.S. Application Data

Publication Classification

Int. Cl.: H04L12/28 (20060101); H04L67/125 (20220101)

U.S. Cl.:

CPC H04L12/282 (20130101); H04L67/125 (20130101);

Field of Classification Search

CPC: H04L (12/282); H04L (67/125)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7124087	12/2005	Rodriguez et al.	N/A	N/A
8620841	12/2012	Filson	706/12	H04L 12/1895
10051068	12/2017	Sharma et al.	N/A	N/A
10855833	12/2019	Santamaria et al.	N/A	N/A
11727085	12/2022	Samal et al.	N/A	N/A
2004/0203644	12/2003	Anders et al.	N/A	N/A
2013/0090767	12/2012	Bruck	700/276	G05D 23/1902
2016/0179075	12/2015	Shin	700/275	G06F 3/016
2019/0199549	12/2018	Park	N/A	H04L 12/2816
2020/0065123	12/2019	Yang	N/A	G06F 9/455
2020/0294503	12/2019	Ryu	N/A	G06F 3/167
2020/0383033	12/2019	Foti	N/A	H04W 76/16
2021/0193333	12/2020	Nishimura	N/A	H04Q 9/00
2022/0151450	12/2021	Case	N/A	B25J 13/003
2023/0199878	12/2022	Kwon	370/329	H04L 12/12
2023/0205157	12/2022	Myung	700/28	H04Q 9/00
2023/0291826	12/2022	Xu	N/A	G06F 1/1626
2024/0064413	12/2023	Saragih	N/A	H04N 23/74
2024/0249556	12/2023	Tusch	N/A	G06V 20/52

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
4251902	12/2008	JP	N/A
2011-158186	12/2010	JP	N/A
6218852	12/2016	JP	N/A
6433563	12/2017	JP	N/A
10-0619955	12/2005	KR	N/A
10-1684423	12/2015	KR	N/A
10-2050425	12/2019	KR	N/A
10-2247518	12/2020	KR	N/A

OTHER PUBLICATIONS

Primary Examiner: Patel; Dhairya A

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application is a continuation Application of International Application No. PCT/KR2022/020228 filed on Dec. 13, 2022 with the World Intellectual Property Organization (WIPO), and is based on and claims priority under 35 U.S.C. § 119 to Korean Patent Application No. 10-2021-0178717, filed on Dec. 14, 2021 and Korean Application No. 10-2021-0192671, filed on Dec. 30, 2021, in the Korean Intellectual Property Office, the disclosures of each of which being incorporated by reference herein in their entireties.

BACKGROUND

1. Field

(1) The disclosure relates to an electronic device capable of controlling smart devices according to user schedules and a method of operating the same.

2. Description of Related Art

(2) Smart devices (for example, table PCs, smart watches, smart audio devices, smart video devices, home appliances, lights, smart door locks, and a plurality of detection sensors) operating through the connection with an electronic device (for example, a smartphone) within the home (or office) are increasing. A technology for controlling the operation of each smart device through the electronic device (for example, the smartphone) has been proposed, but the operation is controlled according to operation states of the smart devices. In order to prepare operations of the plurality of smart devices and change states of the plurality of smart devices according to user schedules, a control interface capable of controlling the plurality of devices according to the user schedules should be generated and provided.

(3) The above information is provided as only background information to help for understanding of the disclosure. A determination indicating which content can be applied as prior arts in connection with the disclosure has not been made and nothing has been claimed.

SUMMARY

(4) In accordance with an aspect of the disclosure, an electronic device may comprise a communication module configured to connect with an Internet of Things server and a plurality of smart devices; a processor operatively connected to the communication module; and a memory operatively connected to the processor, the memory comprising instructions which, when executed by the processor, cause the processor to configure a control interface for controlling operations of the plurality of smart devices according to a user schedule type of a user schedule; and control the operations of the plurality of smart devices through the control interface.

(5) In accordance with another aspect of the disclosure, a method of operating an electronic device may comprise connecting with an Internet of Things server and a plurality of smart devices, registering a user schedule, configuring a control interface for controlling operations of the plurality of smart devices according to a user schedule type of the user schedule, and controlling the operations of the plurality of smart devices through the control interface.

(6) Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features, and advantages of certain embodiments of the present disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a block diagram illustrating an electronic device within a network environment according to various embodiments;

(3) FIG. 2 is a block diagram illustrating a display module according to various embodiments;

(4) FIG. 3 illustrates the control of a plurality of smart devices through the electronic device in a smart control system according to various embodiments;

(5) FIG. 4 illustrates that user schedules are identified using the electronic device and the control interface for controlling the operations of the plurality of smart devices according to the user schedules is provided, according to some embodiments;

(6) FIG. 5 illustrates a method of configuring smart devices according to registration of user schedules, according to some embodiments;

(7) FIG. 6 illustrates an example of the configuration of a control interface for controlling operations of smart devices according to user schedules, according to some embodiments;

(8) FIG. 7 illustrates an example of the configuration of a time point at which a control interface is provided for each characteristic of devices (for example, smart devices), according to some embodiments;

(9) FIG. 8 illustrates an example of the configuration of an option interface of devices (for example, smart devices) for each time point of the user schedule, according to some embodiments;

(10) FIG. 9 illustrates an example of provision of a control interface for controlling operations of smart devices according to user schedules, according to some embodiments;

(11) FIGS. 10 and 11 illustrate examples of a control interface provision method when a state of a device (for example, a smart device) registered in a user schedule (for example, home working) does not match a device at the current time point (for example, a smart device), according to some embodiments;

(12) FIGS. 12 and 13 illustrate examples of a control interface provision method when a location registered in a user schedule (for example, home working) does not match a current user location, according to some embodiments;

(13) FIGS. 14 and 15 illustrate examples of a control interface provision method when a state of a device (for example, a smart device) registered in a user schedule (for example, home training) does not match a state of a device at the current time point (for example, a smart device), according to some embodiments;

(14) FIGS. 16 and 17 illustrate examples of a control interface provision method when the location registered in the user schedule (for example, home training) does not match the current user location, according to some embodiments;

(15) FIG. 18 illustrates an example of a user configuration option for a control interface for controlling operations of smart devices, according to some embodiments;

(16) FIG. 19 illustrates an example of a user configuration option of a control interface for each device (for example, smart device) according to a user schedule (for example, home working), according to some embodiments;

(17) FIG. 20 illustrates an example of a user configuration option of a control interface for each time point of a user schedule according to the user schedule (for example, home working),

according to some embodiments;

(18) FIGS. **21** and **22** illustrate examples of a control interface provision method according to a user schedule (for example, travel), according to some embodiments;

(19) FIG. **23** illustrates an example of a user configuration option of a control interface for each device (for example, smart device) according to a user schedule (for example, travel), according to some embodiments;

(20) FIG. **24** illustrates an example of a user configuration option of a control interface for each time point of a user schedule according to the user schedule (for example, travel), according to some embodiments;

(21) FIGS. **25** and **26** illustrate examples of a control interface provision method according to a user schedule (for example, watching content), according to some embodiments;

(22) FIG. **27** illustrates an example of a user configuration option of a control interface for each device (for example, smart device) according to a user schedule (for example, watching content), according to some embodiments;

(23) FIG. **28** illustrates an example of a user configuration option of a control interface for each time point of a user schedule according to the user schedule (for example, watching content), according to some embodiments;

(24) FIG. **29** illustrates an example of a user configuration option of a control interface for each device (for example, smart device) according to a user schedule (for example, home training), according to some embodiments; and

(25) FIG. **30** illustrates an example of a user configuration option of a control interface for each time point of a user schedule according to the user schedule (for example, home training), according to some embodiment.

DETAILED DESCRIPTION

(26) The description made with reference to the accompanying drawings is provided to help for inclusive understanding of various embodiments as defined by the claims and equivalent thereto. Throughout the drawings, it may be understood that similar reference numbers refer to similar elements, components, and structures. Various detailed matters to help for understanding are included herein, but should be considered as only examples. Accordingly, those skilled in the art recognize that various changes and modifications of various embodiments in the specification can be made without departing from the scope and idea of the disclosure. Further, the description of well known functions and configurations may be omitted for clearness and brevity.

(27) Terms and words used in the following description and claims are not limited to bibliographical meanings, and are merely used by inventors for clear and consistent understanding of the disclosure. Accordingly, it should be apparent to those skilled in the art that the following description of various embodiments is not to limit the disclosure defined by the accompanying drawings and equivalent thereto and is merely provided for the purpose of examples.

(28) Unless otherwise noted in the context, singular expressions should be understood as including a plurality of targets. Therefore, for example, an expression of “element surfaces” may include an expression of one or more of the surfaces.

(29) Once a user schedule stored in an electronic device starts, many steps are needed and it takes a time to configure a function of each of a plurality of smart devices associated with the user schedule. Further, even though the user schedule starts, a user may be absent in a configured location or time, or at least one smart device cannot operate, but there is no clear solution to these issues. In addition, a notification is provided on the basis of states of the smart devices rather than the user, and thus it is not possible to control operations of the smart devices according to the user schedule. Smart devices (for example, tablet PCs, smart watches, smart audio devices, smart video devices, home appliances, lights, smart door locks, and a plurality of detection sensors) operating through a link with an electronic device (for example, a smart phone) within home (or office) have increased, but there is no method of controlling the plurality of smart devices according to the user

schedule.

(30) Various embodiments may provide an electronic device and a method of operating the same capable of generating and providing a control interface for controlling smart devices according to a user schedule.

(31) The technical subjects pursued in this document are not limited to the above mentioned technical subjects, and other technical subjects which are not mentioned may be clearly understood through the following descriptions by those skilled in the art of this document.

(32) Additional aspects are partially described in the following description, and parts thereof may become clear from the description or understood by the presented embodiments.

(33) An electronic device according to various embodiments may include a communication module configured to make a connection with a plurality of smart devices and an Internet of Things (TOT) server, a processor operatively connected to the communication module, and a memory operatively connected to the processor. The memory may include instructions causing the processor to configure a control interface for controlling operations of the plurality of smart devices according to a user schedule type, based on an input user schedule and control the operations of the plurality of smart devices through the control interface.

(34) A method of operating an electronic device according to embodiments may include making a connection with a plurality of smart devices and an Internet of Things (TOT) server, registering a user schedule, configuring a control interface for controlling operations of the plurality of smart devices according to a user schedule type, and controlling the operation of the plurality of smart devices through the control interface.

(35) The electronic device and the method of operating the same according to various embodiments may provide a customized control interface for controlling operations of smart devices having high usage correlation with user schedules on the basis of calendar schedules.

(36) The electronic device and the method of operating the same according to various embodiments may provide a customized control interface for pre-emptively controlling operations of smart devices according to each time point (for example, before the schedule, at which the schedule starts, during the schedule, or after the schedule) of the user schedule.

(37) The electronic device and the method of operating the same according to various embodiments may provide a customized control interface for controlling operations of smart devices in further consideration of a user condition at a time point at which the control interface is provided.

(38) The electronic device and the method of operating the same according to various embodiments may provide a user experience capable of easily controlling operations of a plurality of smart devices by reducing steps of identifying the user schedule, reducing cumbersome steps of finding functions of the plurality of smart devices and controlling the same, and providing a control interface according to the user schedule.

(39) The electronic device and the method of operating the same according to various embodiments may provide a control interface capable of controlling a plurality of smart devices according to a user schedule and control operations of the plurality of smart devices according to a user schedule through the control interface.

(40) The electronic device and the method of operating the same according to various embodiments may provide a control interface capable of controlling operations of a plurality of smart devices when a state of a device (for example, smart device) registered in a user schedule (for example, home working, home training, travel, or watching content) does not match a state of a device at the current time point (for example, smart device).

(41) The electronic device and the method of operating the same according to various embodiments may provide a control interface capable of controlling operations of a plurality of smart devices when a location registered in a user schedule (for example, home working, home training, travel, or watching content) does not match a current user location.

(42) The electronic device and the method of operating the same according to various embodiments

may provide a control interface capable of controlling operations of a plurality of smart devices according to a user schedule (for example, home working, home training, travel, or watching content).

(43) The electronic device and the method of operating the same according to various embodiments may provide a control interface capable of controlling operations of a plurality of smart devices for each time point of the user schedule according to the user schedule (for example, home working, home training, travel, or watching content).

(44) In addition, various effects directly or indirectly detected through the disclosure can be provided.

(45) FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100** according to various embodiments.

(46) Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).

(47) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. According to one embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(48) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may

include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(49) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(50) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(51) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(52) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(53) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(54) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(55) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(56) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(57) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**).

According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(58) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(59) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(60) The power management module **188** may manage power supplied to the electronic device **101**. According to one embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(61) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(62) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(63) The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may

support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(64) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(65) According to various embodiments, the antenna module **197** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(66) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(67) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(68) The electronic device according to various embodiments may be one of various types of

electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(69) It should be appreciated that various embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(70) As used in connection with various embodiments, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(71) Various embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(72) According to an embodiment, a method according to various embodiments may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(73) According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the

multiple entities may be separately disposed in different components. According to various embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(74) According to an embodiment, a display module **160** may include a flexible display configured to be folded or unfolded.

(75) According to an embodiment, the display module **160** may include a flexible display arranged to be slidable and configured to provide a screen (for example, a display screen).

(76) According to an embodiment, the display module **160** may be referred to as a variable display (for example, a stretchable display), an expandable display, or a slide-out display.

(77) According to an embodiment, the display module **160** may include a bar-type or a plate-type display.

(78) FIG. **2** is a block diagram illustrating the display module according to various embodiments.

(79) Referring to FIG. **2**, the display module **160** may include a display **200** and a display driver IC **230** (hereinafter, referred to as a 'DDI **230**') configured to control the display **200**.

(80) The DDI **230** may include an interface module **231**, a memory **233** (for example, a buffer memory), an image processing module **235**, and/or a mapping module **237**.

(81) According to an embodiment, the DDI **230** may receive image data or image information including an image control signal corresponding to a command for controlling the image data from another element of the electronic device **101** through the interface module **231**.

(82) According to an embodiment, the image information may be received from a processor (for example, the processor **120** of FIG. **1**) (for example, the main processor **121** of FIG. **1**) (for example, an application processor) or an auxiliary processor (for example, the auxiliary processor **123** of FIG. **1**) (for example, a graphics processing unit) operating independently from the function of the main processor **121**.

(83) According to an embodiment, the DDI **230** may communicate with a touch circuit **250** or the sensor module **176** through the interface module **231**. Further, the DDI **230** may store at least some of the received image information in the memory **233**. In an example, the DDI **230** may store at least some of the received image information in the memory **233** in units of frames.

(84) According to an embodiment, the image processing module **235** may preprocess or postprocess at least some of the image data (for example, control a resolution, a brightness, or a size) on the basis of at least characteristics of the image data or characteristics of the display **200**.

(85) According to an embodiment, the mapping module **237** may generate a voltage value or a current value corresponding to the preprocessed or postprocessed image data through the image processing module **235**. In an embodiment, the generation of the voltage value or the current value may be performed on the basis of, for example, at least some of the attributes of pixels of the display **200** (for example, arrangement of the pixels (RGB stripe or pentile structure)).

(86) In an embodiment, at least some pixels of the display **200** may be operated on the basis of at least some of the voltage value or the current value, and thus visual information (for example, text, images, and/or icons) corresponding to the image data may be displayed through the display **200**.

(87) According to an embodiment, the display module **160** may further include a touch circuit **250**. The touch circuit **250** may include a touch sensor **251** and a touch sensor IC **253** configured to control the same.

(88) In an embodiment, the touch sensor IC **253** may control the touch sensor **251** to detect a touch

input or a hovering input for a specific location of the display **200**. For example, the touch sensor IC **253** may detect the touch input or the hovering input by measuring a change in a signal (for example, voltage, an amount of light, resistance, or an amount of charge) for the specific location of the display **200**. The touch sensor IC **253** may provide the processor (for example, the processor **120** of FIG. **1**) with information on the detected touch input or hovering input (for example, location, area, pressure, or time).

(89) According to an embodiment, at least some of the touch circuit **250** (for example, the touch sensor IC **253**) may be included as a part of the display driver IC **230** or the display **200**.

(90) According to an embodiment, at least some of the touch circuit **250** (for example, the touch sensor IC **253**) may be included as a part of another element (for example, the auxiliary processor **123**) arranged outside the display module **160**.

(91) According to an embodiment, the display module **160** may further include at least one sensor (for example, an expansion detection sensor, a fingerprint sensor, an iris sensor, a pressure sensor, or an illumination sensor) of the sensor module **176** or a control circuit therefor. In this case, the at least one sensor or the control circuit therefor may be embedded into a part of the display module **160** (for example, the display **200** or the DDI **230**) or a part of the touch circuit **250**. For example, when the sensor module **176** embedded into the display module **160** includes a biometric sensor (for example, a fingerprint sensor), the biometric sensor may acquire biometric information (for example, a fingerprint image) associated with a touch input through some areas of the display **200**. In another example, when the sensor module **176** embedded into the display module **160** includes a pressure sensor, the pressure sensor may acquire pressure information associated with a touch input through some or all areas of the display **200**. In another example, when the sensor module **176** embedded into the display module **160** includes an expansion detection sensor, the expansion detection sensor may sense a change in the area (for example, the screen size) of the display (for example, a variable display). According to an embodiment, the touch sensor **251** or the sensor module **176** may be arranged between pixels of a pixel layer of the display **200** or above or below the pixel layer.

(92) According to an embodiment, the display **200** may include a digitizer **260** configured to detect an input (for example, a touch input or a hovering input) of an input device (for example, a stylus pen). The digitizer **260** may convert analog coordinates of the input device (for example, the stylus pen) into digital data and transfer the digital data to the processor (for example, the processor **120** of FIG. **1**). The processor (for example, the processor **120** of FIG. **1**) may detect an input (for example, a touch input or a hovering input) through the input device (for example, the stylus pen) on the basis of digital data input from the digitizer **260**.

(93) FIG. **3** illustrates the control of a plurality of smart devices through the electronic device in a smart control system according to various embodiments.

(94) Referring to FIG. **3**, a smart control system according to various embodiments may include at least one electronic device **300** (for example, smartphones) (for example, the electronic device **101** of FIG. **1**, an Internet of Things (IOT) server **310**, an Internet network **320** (for example, an IOT communication network), a plurality of smart devices **330** (for example, mobile devices, wearable devices, display devices, audio devices, household appliances, light devices, smart home devices, and smart sensors), and a communication module **340** (for example, a short-range communication network module, a Wi-Fi module, or a Bluetooth module). In some embodiments, the communication module **340** may be, for example, an access point in a home or office.

(95) According to an embodiment, the electronic device **300** may be connected to the Internet network **320** (for example, a long-range communication network) through a wireless or a wired communication scheme. The electronic device **300** may be connected to the IOT server **310** through the Internet network **320**.

(96) According to an embodiment, the electronic device **300** may be connected to the communication module **340** through a wireless or a wired communication scheme. The electronic

device **300** may be connected to the plurality of smart devices **330** through the communication module **340**. The electronic device **300** may be connected to the IOT server **310** through the communication module **340**.

(97) According to an embodiment, the IOT server **310** may be connected to the Internet network **320** through a wired or a wireless communication scheme. The IOT server **310** may be connected to the electronic device **300** and the plurality of smart devices **330** through the Internet network **320**.

(98) According to an embodiment, at least some of the plurality of smart devices **330** may be connected to the Internet network **320**. At least some of the plurality of smart devices **330** may be connected to the electronic device **300** and the IOT server **310** through the Internet network **320**.

(99) According to an embodiment, at least some of the plurality of smart devices **330** may be connected to the communication module **340**. At least some of the plurality of smart devices **330** may be connected to the electronic device **300** and the IOT server **310** through the communication module **340**.

(100) According to an embodiment, the electronic device **300** may recognize user schedules through the processor and register the user schedules (for example, store the user schedules in the memory). The electronic device **300** may provide the pre-registered user schedules to the IOT server **310**. The electronic device **300** may generate a control interface configured to control the operations of the plurality of smart devices **330** according to the user schedules through the processor. In an embodiment, the electronic device **300** may provide the generated control interface to the IOT server **310**. In an embodiment, the IOT server **310** may store the control interface provided from the electronic device **300** in the memory. The IOT server **310** may provide the control interface to the electronic device **300** or another electronic device according to the user schedules through the processor.

(101) In an embodiment, the IOT server **310** may include a processor configured to recognize user schedules and generate a control interface for controlling the operations of the plurality of smart devices **330** according to the user schedules. In an embodiment, the IOT server **310** may include a memory configured to store user schedules, the control information, and instructions for generating the control interface.

(102) According to an embodiment, the electronic device **300** may register the user schedules and provide the pre-registered user schedules to the IOT server **310**. The IOT server **310** may generate a control interface for controlling the operations of the plurality of smart devices **330** according to the registered user schedules. In an embodiment, the IOT server **310** may store the generated control interface and provide the control interface to the electronic device **300** or another electronic device according to the user schedules.

(103) According to an embodiment, the electronic device **300** may generate a control interface for controlling the operations of the plurality of smart devices **330** according to the user schedules. The electronic device **300** may control the operations of the plurality of smart devices **330** through the control interface. In an embodiment, the electronic device **300** may include a processor configured to recognize the user schedules and generate a control interface for controlling the operations of the plurality of smart devices **330** according to the user schedules. In an embodiment, the electronic device **300** may include a memory configured to store the user schedules, the control interface, and instructions for generating the control interface.

(104) According to an embodiment, the IOT server **310** may generate a control interface for controlling the operations of the plurality of smart devices **330** according to the user schedules and provide the control interface to the electronic device **300**. The electronic device **300** may control the operations of the plurality of smart devices **330** through the control interface provided from the IOT server **310**.

(105) FIG. 3 illustrates that one electronic device **300** is provided. However, the disclosure is not limited thereto, and in some embodiments, a plurality of electronic devices **300** may be provided.

In FIG. 3, at least some of the electronic device **300**, the communication module **340**, and the plurality of smart devices **330** may be located within a predetermined space (for example, home or office). However, the disclosure is not limited thereto, and in some embodiments, a plurality of electronic devices **300** may be located within a predetermined space (for example, home or office). In some embodiments, the electronic device **300**, the communication module **340**, the plurality of smart devices **330**, the Internet network **320** and the IOT server **310** may be located in a predetermined space (for example, a home or office).

(106) According to an embodiment, at least one electronic device **300** may be connected to the IOT server **310**, the communication module **340**, and/or the plurality of smart devices **330** through a communication scheme in which wired and wireless types are combined as well as a wired communication scheme or a wireless communication scheme.

(107) According to an embodiment, at least one electronic device **300** and the plurality of smart devices **330** may be connected through a device-to-device (D2D) scheme.

(108) According to an embodiment, at least one electronic device **300** may control the operations of the plurality of smart devices **330** on the basis of a user selection input through the touch sensor. In an embodiment, at least one electronic device **300** may activate the control interface according to the user selection input through the touch sensor and control the operations of the plurality of smart devices **330** through the control interface.

(109) According to an embodiment, at least one electronic device **300** may control the operations of the plurality of smart devices **330** on the basis of user selection input through an electronic pen (for example, a stylus pen). In an embodiment, at least one electronic device **300** may activate the control interface according to the user selection input through the electronic pen (for example, the stylus pen) and control the operations of the plurality of smart devices **330** through the control interface.

(110) According to an embodiment, at least one electronic device **300** may control the operations of the plurality of smart devices **330** by recognizing a user utterance. In an embodiment, at least one electronic device **300** may activate the control interface by recognizing the user utterance and control the operations of the plurality of smart devices **330** through the control interface.

(111) FIG. 4 illustrates that user schedules are identified using the electronic device and the control interface for controlling the operations of the plurality of smart devices according to the user schedules is provided.

(112) Referring to FIG. 4, according to an embodiment, an electronic device **400** (for example, the electronic device **101** of FIG. 1 or the electronic device **300** of FIG. 3) may display content of one or more pre-registered user schedules through a calendar schedule function **410**. In an embodiment, the electronic device **400** may display the content of the one or more user schedules on the display and output the same through a sound in order to allow the user to visually and acoustically identify the one or more user schedules.

(113) According to an embodiment, the electronic device **400** may activate a control interface **420** for controlling the operations of the plurality of smart devices linked to the one or more user schedules according to the user schedules. The electronic device **400** may make the operation of each of the plurality of smart devices controlled through the control interface **420**.

(114) In an embodiment, when a task force (TF) video meeting is registered as a user schedule, the electronic device **400** may determine whether the start time of the video meeting (for example, a target time point) has come (or has entered the target time point). When the start time of the video meeting occurs, the electronic device **400** displays a message indicating the start of the TF video meeting and determines a plurality of smart devices to operate through a link to the TF video meeting.

(115) The electronic device **400** may activate the control interface **420** for controlling the operations of the plurality of smart devices to operate through the link to the TF video meeting and control the operations of the plurality of smart devices linked to the TF video meeting through the

control interface **420**. For example, the operation of an air conditioner is changed to a windless mode, the operation of a robot cleaner is stopped, and the operation of an IOT speaker is changed to a turn-on state.

(116) The electronic device **400** according to various embodiments may provide a customized control interface for controlling the operations of smart devices having a high usage correlation with the one or more user schedules on the basis of calendar schedules. The electronic device **400** may provide the customized control interface for preemptively controlling the operations of the smart devices according to each time point related to the one or more user schedules (for example, before the start of the user schedule, at the start of the user schedule, during the user schedule, or after the end of the user schedule).

(117) FIG. 5 is a diagram **500** illustrating a method of configuring smart devices according to registration of user schedules.

(118) Referring to FIG. 5, according to an embodiment, the electronic device (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) according to various embodiments may configure devices (for example, the plurality of smart devices **330** of FIG. 3) having a high correlation according to registration of user schedules.

(119) In operation **510**, the electronic device (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) according to various embodiments may initiate addition of a user schedule.

(120) In operation **520**, the electronic device (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) according to various embodiments may input user schedule information. For example, the user schedule information may include information on a title of the schedule, content of the schedule, and a location at which the schedule is conducted, etc.

(121) In operation **530**, the electronic device (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) according to various embodiments may classify a type of the user schedule on the basis of the input user schedule information.

(122) In an embodiment, the electronic device (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) may classify the type of the user schedule as shown in [Table 1].

(123) TABLE-US-00001 TABLE 1 Identification #video #home #travel #watching keyword based meeting training #holiday movie on schedule #online #home #summer #watching information meeting workout vacation soap opera (identification #home #home pilates #winter #watching keyword is meeting #home health vacation soccer game predefined, #WIFI #LAN #home #day travel #watching and can be cable meeting stretching #healing travel baseball game individually #home #Jeju travel #watching added by user working #Gangneung Olympic game or travel #watching automatically World Cup added by AI) game #watching premiere Schedule type Home working Home training Travel Watching content Identification #study #nap #catnap #home keyword based #examination #sleeping hours #put sb down cooking on schedule period for nap #preparing information #preparing for #take nap #nap dinner (identification mid-term #catnap #slumber #preparing keyword is exam lunch predefined, #preparing for #preparing and can be final exam breakfast individually #preparing for #preparing added by user quiz party food or #homework automatically added by AI) Schedule type Home study sleep cooking

(124) In an embodiment, the electronic device (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) may classify the plurality of smart devices according to each user schedule type on the basis of an identification keyword based on the user schedule. For example, the identification keyword may be predefined and may be individually added according to a user selection. For example, the identification keyword may be automatically added by artificial intelligence (AI).

(125) In an embodiment, the electronic device (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) may classify the plurality of smart devices according to each

user schedule type on the basis of the user schedule such as home working, home training, travel, watching content, home study, sleep, or cooking. In some embodiments, each of the plurality of smart devices may be associated with one or more user schedule types that are relevant to the smart device. For example, home working may be associated with an air conditioner, a stereo, and/or lighting; travel may be associated with a security system and/or robot cleaner; cooking may be associated with an oven and/or a refrigerator, etc.

(126) In operation **540**, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) according to various embodiments may configure a combination of usage devices (for example, the plurality of smart devices **330** of FIG. **3**) suitable for the user schedule type.

(127) In an embodiment, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may combine and configure smart devices suitable for the user schedule type as shown in [Table 2].

(128) TABLE-US-00002 TABLE 2 Device/schedule Home Home Watching Home type working training travel content study sleep cooking mobile Turned on Turned on Turned on Turned on Turned on — — (optimized for app) Tablet Turned on — — — Turned on — — Watch — Exercise mode — — — — — Buds Connected — Connected — Connected — — Speaker Mute Turned on Mute Mute — Turned off Turned on Washing Laundry Sports wear Laundry — — — — machine reserved reserved Drying Laundry — Laundry — — — — machine reserved reserved Steam — Sports wear — — — — — closet Shoes — Sports wear — — — — — cleaner Robot Pause — — — Pause Stop — cleaner Oven — — — — — preheating Air Windless Air Turned off Air Windless Windless — conditioner conditioning (reservation conditioning canceled) Air Windless Turned on Turned off — Windless Windless Turned off purifier (reservation canceled) TV Turned off Turned on — Sports mode Turned off Turned off — Sound bar (audio) — — — Sports mode — — — Light — Brightening — — — Turned off — Home CCTV — — Turned on — — — — Open/close — — Turned on — — — — sensor Human body — — Turned on — — — — detection sensor Smoke — — Turned on — — — — detector Leakage — — Turned on — — — — detection sensor

(129) In an embodiment, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may combine and configure smart devices suitable for the user schedule type according to the user schedule such as home working, home training, travel, watching content, home study, sleep, or cooking. For example, a security system and robot cleaner may be configured to turn on when the user schedule is a traveling user type; an air conditioner may be configured to a certain temperature, a stereo may be configured to change to a given station, and/or lighting may be configured to turn on when home working, etc.

(130) In operation **550**, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) according to various embodiments may select smart devices to operate through the link to the user schedule as target devices and configure the option of the smart devices selected as the target devices.

(131) In operation **560**, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) according to various embodiments may store the user schedules in the memory.

(132) In an embodiment, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) according to various embodiments may store the user schedules in an internal memory of the electronic device and provide the user schedules to the IOT server (for example, the IOT server **310** of FIG. **1**).

(133) For example, the IOT server (for example, the IOT server **310** of FIG. **3**) may store the user schedules provided from the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) in an internal memory of the IOT server (for example, the IOT server **310** of FIG. **3**).

(134) At least some of the operations illustrated in FIG. 5 may be omitted. Before or after at least some of the operations illustrated in FIG. 5, at least some operations mentioned with reference to other drawings of the disclosure may be added and/or inserted. The operations illustrated in FIG. 5 may be performed by the processor (for example, the processor **120** of FIG. **1**) of the electronic device (for example, the electronic device **101** of FIG. **1**, the electronic device **300** of FIG. **3**, or the electronic device **400** of FIG. **4**) or the processor of the IOT server (for example, the IOT server **310** of FIG. **3**). For example, the memory of the electronic device (for example, the electronic device **101** of FIG. **1**, the electronic device **300** of FIG. **3**, or the electronic device **400** of FIG. **4**) or the IOT server (for example, the IOT server **310** of FIG. **3**) may store instructions causing the processor to, when executed, perform at least some operations illustrated in FIG. 5.

(135) FIG. 6 illustrates an example of the configuration of a control interface for controlling operations of smart devices according to user schedules.

(136) Referring to FIG. 6, according to an embodiment, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) according to various embodiments may configure a control interface according to a user schedule. In another embodiment, the IOT server (for example, the IOT server **310** of FIG. **3**) may configure a control interface according to a user schedule.

(137) In operation **610**, in an embodiment, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) according to various embodiments may read information (for example, notification storage information) for a notification of the user schedule from the memory. In another embodiment, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may receive the information for the notification of the user schedule from the IOT server (for example, the IOT server **310** of FIG. **3**).

(138) In operation **620**, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) according to various embodiments may distinguish characteristics of devices (for example, the plurality of smart devices **330** of FIG. **3**) for configuring the control interface. In another embodiment, the IOT server (for example, the IOT server **310** of FIG. **3**) may distinguish characteristics of devices (for example, the plurality of smart devices **330** of FIG. **3**) for configuring the control interface.

(139) In an embodiment, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may distinguish characteristics of devices (for example, the plurality of smart devices **330** of FIG. **3**) for configuring the control interface as shown in [Table 3].

(140) TABLE-US-00003 TABLE 3 Device characteristic (wired/wireless) Public device or Device mobility charging required not Mobile ◦ (wireless) ◦ Personal Tablet ◦ (wireless) ◦ Personal Watch ◦ (wireless) ◦ Personal Buds ◦ (wireless) ◦ Personal Speaker fixed (wired/wireless) Public x/◦ Washing machine fixed (wired) x Public Drying machine fixed (wired) x Public Steam closet fixed (wired) x Public Shoes cleaner fixed (wired) x Public Robot cleaner fixed (wireless) ◦ Public Oven fixed (wired) x Public Air conditioner fixed (wired) x Public Air purifier fixed (wired) x Public TV fixed (wired) x Public Sound bar (audio) fixed (wired) x Public Light fixed (wired) x Public

(141) As another example, operation **620** may be performed by the IOT server (for example, the IOT server **310** of FIG. **3**).

(142) At least some of the operations illustrated in FIG. 6 may be omitted. Before or after at least some of the operations illustrated in FIG. 6, at least some operations mentioned with reference to other drawings of the disclosure may be added and/or inserted. The operations illustrated in FIG. 6 may be performed by the processor (for example, the processor **120** of FIG. **1**) of the electronic device (for example, the electronic device **101** of FIG. **1**, the electronic device **300** of FIG. **3**, or the electronic device **400** of FIG. **4**) or the processor of the IOT server (for example, the IOT server **310** of FIG. **3**). For example, the memory of the electronic device (for example, the electronic

device **101** of FIG. **1**, the electronic device **300** of FIG. **3**, or the electronic device **400** of FIG. **4**) or the IOT server (for example, the IOT server **310** of FIG. **3**) may store instructions causing the processor to, when executed, perform at least some operations illustrated in FIG. **6**.

(143) FIG. **7** illustrates an example of the configuration of a time point at which a control interface is provided for each characteristic of devices (for example, smart devices).

(144) Referring to FIGS. **6** and **7**, in operation **631**, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may determine whether a plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) have mobility as shown in [Table 4].

(145) When there are smart devices having mobility among the plurality of smart devices **330** on the basis of the determination result of operation **631**, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may add a provision time point before the user schedule time to the smart devices having mobility among the plurality of smart devices **330** in operation **633**. Operation **633** may be performed after operation **632**.

(146) TABLE-US-00004 TABLE 4 Characteristic of each device/schedule Before Start of During time point schedule schedule schedule After schedule Mobility In same In same — — space? space? Wireless Is charging — Is battery Is charging (charging) required? sufficient? required? Public — — Is state — changed (by another user)

(147) When there is no smart device having mobility among the plurality of smart devices **330** on the basis of the determination result of operation **631**, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may determine whether the smart devices **330** are wireless devices as shown in [Table 4] in operation **633**.

(148) When the smart devices **330** are wireless devices on the basis of the determination result of operation **633**, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may add provision time points before, during, and after the user schedule in operation **634**. Operation **635** may be performed after operation **634**.

(149) When the smart devices **330** are not wireless devices on the basis of the determination result of operation **633**, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may determine whether the smart devices **330** are public devices as shown in [Table 4] in operation **635**.

(150) When the smart devices **330** are public devices on the basis of the determination result of operation **635**, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may add the provision time during the user schedule time in operation **636**.

(151) When the smart devices **330** are not public devices on the basis of the determination result of operation **635**, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may perform operation **640**.

(152) In another embodiment, operation **631** to operation **635** may be performed by the IOT server (for example, the IOT server **310** of FIG. **3**).

(153) At least some of the operations illustrated in FIG. **7** may be omitted. Before or after at least some of the operations illustrated in FIG. **7**, at least some operations mentioned with reference to other drawings of the disclosure may be added and/or inserted. The operations illustrated in FIG. **7** may be performed by the processor (for example, the processor **120** of FIG. **1**) of the electronic device (for example, the electronic device **101** of FIG. **1**, the electronic device **300** of FIG. **3**, or the electronic device **400** of FIG. **4**) or the processor of the IOT server (for example, the IOT server **310** of FIG. **3**). For example, the memory of the electronic device (for example, the electronic device **101** of FIG. **1**, the electronic device **300** of FIG. **3**, or the electronic device **400** of FIG. **4**) or the IOT server (for example, the IOT server **310** of FIG. **3**) may store instructions causing the processor to, when executed, perform at least some operations illustrated in FIG. **7**.

(154) FIG. **8** illustrates an example of the configuration of an option interface of devices (for

example, smart devices) for each time point of the user schedule.

(155) Referring to FIGS. 6 and 8, in operation 640, the electronic device (for example, the electronic device 300 of FIG. 3 or the electronic device 400 of FIG. 4) may configure an option interface of devices (for example, the plurality of smart devices 330 of FIG. 3) for each user schedule time point.

(156) In an embodiment, the electronic device (for example, the electronic device 300 of FIG. 3 or the electronic device 400 of FIG. 4) may configure the option interface of the plurality of smart devices 330 depending on whether it is before the user schedule starts, a start time point of the user schedule, it is during the user schedule, or it is after the user schedule.

(157) As another example, operation 640 may be performed by the IOT server (for example, the IOT server 310 of FIG. 3).

(158) In operation 650, the electronic device (for example, the electronic device 300 of FIG. 3 or the electronic device 400 of FIG. 4) may complete the automatic configuration of a control interface (for example, the control interface 420 of FIG. 4) for controlling the operations of the plurality of smart devices 330 according to the user schedule.

(159) As another example, operation 650 may be performed by the IOT server (for example, the IOT server 310 of FIG. 3).

(160) In operation 660, the electronic device (for example, the electronic device 300 of FIG. 3 or the electronic device 400 of FIG. 4) may store content of the control interface (for example, the control interface 420 of FIG. 4) in the user schedule.

(161) As another example, operation 660 may be performed by the IOT server (for example, the IOT server 310 of FIG. 3).

(162) FIG. 9 illustrates an example of provision of a control interface for controlling operations of smart devices according to user schedules.

(163) Referring to FIGS. 6 and 9, according to an embodiment, the electronic device (for example, the electronic device 300 of FIG. 3 or the electronic device 400 of FIG. 4) according to various embodiments may provide a control interface (for example, the control interface 420 of FIG. 4). In another embodiment, the IOT server (for example, the IOT server 310 of FIG. 3) may provide the control interface (for example, the control interface 420 of FIG. 4).

(164) In operation 910, the electronic device (for example, the electronic device 300 of FIG. 3 or the electronic device 400 of FIG. 4) may enter a notification time of the user schedule and the user schedule time point shown in [Table 4] (for example, before the user schedule, the start time point of the user schedule, during the user schedule, or after the user schedule).

(165) As another example, operation 910 may be performed by the IOT server (for example, the IOT server 310 of FIG. 3).

(166) In operation 920, the electronic device (for example, the electronic device 300 of FIG. 3 or the electronic device 400 of FIG. 4) may identify attributes of the location at which the user schedule is conducted and the user location.

(167) In an embodiment, the electronic device (for example, the electronic device 300 of FIG. 3 or the electronic device 400 of FIG. 4) may identify the attributes of the location at which the user schedule is conducted and the user location as shown in [Table 5].

(168) TABLE-US-00005

TABLE 5	Whether schedule	Schedule location	User location (based on attributes match user attributes mobile phone)	location	Schedule	Within home	Match within
Outside home	Non-match	home	Unidentified	Non-match	Schedule	Within home	Non-match
outside	Outside home	Match	home	Unidentified	Non-match	none	Within home/outside
home/unidentified							none

(169) As another example, operation 920 may be performed by the IOT server (for example, the IOT server 310 of FIG. 3).

(170) In operation 930, the electronic device (for example, the electronic device 300 of FIG. 3 or the electronic device 400 of FIG. 4) may identify states of target devices (for example, the plurality

of smart devices **330** of FIG. **3**).

(171) In an embodiment, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) or the IOT server (for example, the IOT server **310** of FIG. **3**) may identify states of the plurality of smart devices **330** according to each time point of the user schedules (for example, before the schedule, the start of the schedule, during the schedule, or after the schedule) as shown in [Table 6]. For example, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) or the IOT server (for example, the IOT server **310** of FIG. **3**) may configure a device option interface according to each schedule time point and determine whether current states of the target devices (for example, the plurality of smart devices **330** of FIG. **3**) at each time point are different from preset states. For example, when the current states of the target devices (for example, the plurality of smart devices **330** of FIG. **3**) at each time point are different from the preset states, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) or the IOT server (for example, the IOT server **310** of FIG. **3**) may provide a device option interface according to each schedule time point. For example, when the current states of the target devices (for example, the plurality of smart devices **330** of FIG. **3**) at each time point are not different from the preset states, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) or the IOT server (for example, the IOT server **310** of FIG. **3**) may not provide the option interface according to each schedule time point.

(172) TABLE-US-00006 TABLE 6 Whether to provide control interface according to device state at each schedule time point

	Before	Start of	During	After
Match	provide	provide	provide	provide
Non-match	omit	omit	omit	omit

TABLE 6 Whether to provide control interface according to device state at each schedule time point

Match/none Is configuration of device option interface according to each schedule time point different from target device state at each time point .fwdarw. provide if different .fwdarw. omit if same Non-match provide omit omit

(173) As another example, operation **930** may be performed by the IOT server (for example, the IOT server **310** of FIG. **3**).

(174) In operation **940**, the IOT server (for example, the IOT server **310** of FIG. **3**) may determine whether provision of a control interface for controlling operations of the plurality of smart devices **330** is needed on the basis of a user schedule time point (for example, before the start of the user schedule, at the time point at the user schedule starts, during the user schedule, or after the user schedule).

(175) As another example, operation **940** may be performed by the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**).

(176) When provision of the control interface for controlling the operations of the plurality of smart devices **330** is needed on the basis of the determination result of operation **940**, the IOT server (for example, the IOT server **310** of FIG. **3**) may provide the control interface for controlling the operations of the plurality of smart devices **330** to the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) in operation **950**.

(177) When provision of the control interface for controlling the operations of the plurality of smart devices **330** is not needed on the basis of the determination result of operation **940**, the IOT server (for example, the IOT server **310** of FIG. **3**) may not provide the control interface for controlling the operations of the plurality of smart devices **330** in operation **960**.

(178) In another embodiment, operation **940** may be performed by the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**).

(179) In another embodiment, when provision of the control interface for controlling the operations of the plurality of smart devices **330** is needed, the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may read the control interface stored in the internal memory of the electronic device (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) and control the operations of the plurality of smart devices **330**.

(180) At least some of the operations illustrated in FIG. 9 may be omitted. Before or after at least some of the operations illustrated in FIG. 9, at least some operations mentioned with reference to other drawings of the disclosure may be added and/or inserted. The operations illustrated in FIG. 9 may be performed by the processor (for example, the processor **120** of FIG. 1) of the electronic device (for example, the electronic device **101** of FIG. 1, the electronic device **300** of FIG. 3, or the electronic device **400** of FIG. 4) or the processor of the IOT server (for example, the IOT server **310** of FIG. 3). For example, the memory of the electronic device (for example, the electronic device **101** of FIG. 1, the electronic device **300** of FIG. 3, or the electronic device **400** of FIG. 4) or the IOT server (for example, the IOT server **310** of FIG. 3) may store instructions causing the processor to, when executed, perform at least some operations illustrated in FIG. 9.

(181) FIGS. 10 and 11 illustrate examples of a control interface provision method when a state of a device (for example, a smart device) registered in a user schedule (for example, home working) does not match a device at the current time point (for example, a smart device).

(182) Referring to FIGS. 10 and 11, in an embodiment, when states of devices (for example, the plurality of smart devices **330** of FIG. 3) of the user schedule (for example, home working) do not match states of devices at the current time point (for example, the plurality of smart devices **330** of FIG. 3), a control interface **1030** may be provided to an electronic device **1000**. The electronic device **1000** may control the operations of the plurality of smart devices **330** through the control interface **1030**.

(183) In an embodiment, the IOT server (for example, the IOT server **310** of FIG. 3) may provide the control interface **1030** to the electronic device **1000** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4).

(184) In another embodiment, the control interface **1030** may be provided after the control interface **1030** stored in the internal memory of the electronic device **1000** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) is read.

(185) In an embodiment, the electronic device **1000** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) or the IOT server **310** may configure devices (for example, the plurality of smart devices **330**) related to a user schedule **1020** (for example, a video meeting) as indicated by reference numeral **1010**.

(186) In an embodiment, the electronic device **1000** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) may receive the control interface **1030** for controlling the operations of the devices (for example, the plurality of smart devices **330**) related to the user schedule **1020** (for example, the video meeting during home working) from the IOT server **310**.

(187) In another embodiment, the electronic device **1000** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) may read the control interface **1030** for controlling the operations of the devices (for example, the plurality of smart devices **330**) related to the user schedule **1020** (for example, the video meeting during home working) stored in the internal memory.

(188) In an embodiment, the electronic device **1000** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) may control the operations of the smart devices **330** through the control interface **1030** of the devices (for example, the plurality of smart devices **330**) related to the user schedule **1020** (for example, the video meeting during home working).

(189) For example, the electronic device **1000** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) may separate the time point into before the schedule **1041**, the start of the schedule **1042**, during the schedule **1043**, and after the schedule **1044** with respect to the user schedule **1020** (for example, the video meeting during home working).

(190) In an embodiment, the electronic device **1000** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) may identify states of the plurality of smart devices **330** according to each time point of the user schedule **1020** (for example, the video meeting during home working). In an embodiment, the electronic device **1000** (for example, the electronic device

300 of FIG. **3** or the electronic device **400** of FIG. **4**) may identify the states of the plurality of smart devices **330** before the schedule **1041**, at the start of the schedule **1042**, during the schedule **1043**, and after the schedule **1044** and the state of each of the plurality of smart devices **330** at the current time point.

(191) In an embodiment, when the states of the smart device before the schedule **1041**, at the start of the schedule **1042**, during the schedule **1043**, and after the schedule **1044** do not match the state of the smart device at the current time point as indicated by reference numeral **1051**, the electronic device **1000** (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) or the IOT server (for example, the IOT server **310** of FIG. **3**) may provide a control interface **1052** for controlling the operation of the smart device for the non-matching time point to the electronic device **1000**. The control interface **1052** may be provided from the IOT server (for example, the IOT server **310** of FIG. **3**) to the electronic device **1000**, or the control interface **1052** stored in the internal memory of the electronic device **1000** may be read.

(192) In an embodiment, the electronic device **1000** may control the operations of the plurality of smart devices **330** through the control interfaces **1030** and **1052**.

(193) At least some of the operations illustrated in FIGS. **10** and **11** may be omitted. Before or after at least some of the operations illustrated in FIGS. **10** and **11**, at least some operations mentioned with reference to other drawings in the disclosure may be added and/or inserted. The operations illustrated in FIGS. **10** and **11** may be performed by the processor (for example, the processor **120** of FIG. **1**) of the electronic device **1000** or the processor of the IOT server (for example, the IOT server **310** of FIG. **3**). For example, the memory of the electronic device **1000** or the IOT server (for example, the IOT server **310** of FIG. **3**) may store instructions causing the processor to, when executed, perform at least some operations illustrated in FIGS. **10** and **11**.

(194) FIGS. **12** and **13** illustrate examples of a control interface provision method when a location registered in a user schedule (for example, home working) does not match a current user location.

(195) Referring to FIGS. **12** and **13**, as an embodiment, when the location of the user schedule (for example, home working) does not match the user location, a control interface **1230** may be provided to the electronic device **1200**. The electronic device **1200** may control operations of a plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) through the control interface **1230**.

(196) In an embodiment, the IOT server (for example, the IOT server **310** of FIG. **3**) may provide the control interface **1230** to the electronic device **1200** (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**).

(197) In another embodiment, the control interface **1230** may be provided after the control interface **1230** stored in the internal memory of the electronic device **1200** (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) is read.

(198) In an embodiment, the electronic device **1200** (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) or the IOT server (for example, the IOT server **310** of FIG. **3**) may configure devices (for example, the plurality of smart devices **330**) related to a user schedule **1220** (for example, a video meeting) as indicated by reference numeral **1210**.

(199) In an embodiment, the electronic device **1200** (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may receive the control interface **1230** for controlling the operations of the devices (for example, the plurality of smart devices **330**) related to the user schedule **1220** (for example, the video meeting during home working) from the IOT server **310**.

(200) In another embodiment, the electronic device **1200** (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may read the control interface **1230** for controlling the operations of the devices (for example, the plurality of smart devices **330**) related to the user schedule **1220** (for example, the video meeting during home working) stored in the internal memory.

(201) In an embodiment, the electronic device **1200** (for example, the electronic device **300** of FIG.

3 or the electronic device **400** of FIG. 4) may control the operations of the smart devices **330** through the control interface **1230** of the devices (for example, the plurality of smart devices **330**) related to the user schedule **1220** (for example, the video meeting during home working).

(202) For example, the electronic device **1200** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) may separate the time point into before the schedule **1241**, the start of the schedule **1242**, during the schedule **1243**, and after the schedule **1244** with respect to the user schedule **1220** (for example, the video meeting during home working).

(203) In an embodiment, the electronic device **1200** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) or the IOT server (for example, the IOT server **310** of FIG. 3) may identify the location of the user schedule according to each time point of the user schedule **1220** (for example, the video meeting during home working) and the user location at the current time point. For example, the electronic device **1200** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) may identify the locations of the user schedule before the schedule **1241**, at the start of the schedule **1242**, during the schedule **1243**, and after the schedule **1244** and the user location at the current time point.

(204) In an embodiment, when the locations of the user schedule before the schedule **1241**, at the start of the schedule **1242**, during the schedule **1243**, and after the schedule **1244** do not match the user location at the current time point as indicated by reference numeral **1251**, the electronic device **1200** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) or the IOT server (for example, the IOT server **310** of FIG. 3) may provide a control interface **1252** for controlling the operation of the smart device for the time point at which the user location does not match. The control interface **1252** may be provided from the IOT server (for example, the IOT server **310** of FIG. 3) to the electronic device **1200**, or the control interface **1252** stored in the internal memory of the electronic device **1200** may be read.

(205) In an embodiment, the electronic device **1200** may control operations of the plurality of smart devices **330** through the control interfaces **1230** and **1252**.

(206) At least some of the operations illustrated in FIGS. 12 and 13 may be omitted. Before or after at least some of the operations illustrated in FIGS. 12 and 13, at least some operations mentioned with reference to other drawings in the disclosure may be added and/or inserted. The operations illustrated in FIGS. 12 and 13 may be performed the processor (for example, the processor **120** of FIG. 1) of the electronic device **1200** or the processor of the IOT server (for example, the IOT server **310** of FIG. 3). For example, the memory of the electronic device **1200** or the IOT server (for example, the IOT server **310** of FIG. 3) may store instructions causing the processor to, when executed, perform at least some operations illustrated in FIGS. 12 and 13.

(207) FIGS. 14 and 15 illustrate examples of a control interface provision method when a state of a device (for example, a smart device) registered in a user schedule (for example, home training) does not match a state of a device at the current time point (for example, a smart device).

(208) Referring to FIGS. 14 and 15, in an embodiment, when states of the devices (for example, the plurality of smart devices **330** of FIG. 3) of the user schedule (for example, home training) do not match the states of the devices (for example, the plurality of smart devices **330** of FIG. 3) at the current time point, a control interface **1430** may be provided to an electronic device **1400**. The electronic device **1400** may control the operations of the plurality of smart devices **330** through the control interface **1430**.

(209) In an embodiment, the IOT server (for example, the IOT server **310** of FIG. 3) may provide the control interface **1430** to the electronic device **1400** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4).

(210) In another embodiment, the control interface **1430** may be provided after the control interface **1430** stored in the internal memory of the electronic device **1400** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) is read.

(211) In an embodiment, the electronic device **1400** (for example, the electronic device **300** of FIG.

3 or the electronic device **400** of FIG. 4) or the IOT server **310** may configure devices (for example, the plurality of smart devices **330**) related to the user schedule **1420** (for example, home training) as indicated by reference numeral **1410**.

(212) In an embodiment, the electronic device **1400** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) or the IOT server **310** may receive the control interface **1430** for controlling operations of the devices (for example, the plurality of smart devices **330**) related to the user schedule **1420** (for example, home training) from the IOT server **310**.

(213) In another embodiment, the electronic device **1200** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) may read the control interface **1430** for controlling operations of the devices (for example, the plurality of smart devices **330**) related to the user schedule **1420** (for example, home training) stored in the internal memory.

(214) In an embodiment, the electronic device **1400** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) or the IOT server **310** may control the operations the plurality of smart devices **330** through the control interface **1430** of the devices (for example, the plurality of smart devices **330**) related to the user schedule **1420** (for example, home training).

(215) For example, the electronic device **1400** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) or the IOT server **310** may separate the time point into before the schedule **1441**, the start of the schedule **1442**, during the schedule **1443**, and after the schedule **1444** with respect to the user schedule **1420** (for example, home training).

(216) In an embodiment, the electronic device **1400** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) may identify states of the plurality of smart devices **330** according to each time point of the user schedule **1420** (for example, home training). In an embodiment, the electronic device **1400** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) may identify the states of the plurality of smart devices **330** before the schedule **1441**, at the start of the schedule **1442**, during the schedule **1443**, and after the schedule **1444** and the state of each of the plurality of smart devices **330** at the current time point.

(217) In an embodiment, when the states of the smart device before the schedule **1441**, at the start of the schedule **1442**, during the schedule **1443**, and after the schedule **1444** do not match the state of the smart device at the current state, the electronic device **1400** (for example, the electronic device **300** of FIG. 3 or the electronic device **400** of FIG. 4) or the IOT server (for example, the IOT server **310** of FIG. 3) may provide the control interface **1452** or **1454** for controlling the operation of the smart device for the non-matching time point **1451** or **1453** to the electronic device **1000**. The control interface **1452** or **1454** may be provided from the IOT server (for example, the IOT server **310** of FIG. 3) to the electronic device **1400**, or the control interface **1452** or **1454** stored in the internal memory of the electronic device **1400** may be read.

(218) In an embodiment, the electronic device **1400** may control the operations of the plurality of smart devices **330** through the control interface **1430**, **1452**, or **1454**.

(219) At least some of the operations illustrated in FIGS. 14 and 15 may be omitted. Before or after at least some of the operations illustrated in FIGS. 14 and 15, at least some operations mentioned with reference to other drawings in the disclosure may be added and/or inserted. The operations illustrated in FIGS. 14 and 15 may be performed the processor (for example, the processor **120** of FIG. 1) of the electronic device **1400** or the processor of the IOT server (for example, the IOT server **310** of FIG. 3). For example, the memory of the electronic device **1400** or the IOT server (for example, the IOT server **310** of FIG. 3) may store instructions causing the processor to, when executed, perform at least some operations illustrated in FIGS. 14 and 15.

(220) FIGS. 16 and 17 illustrate examples of a control interface provision method when the location registered in the user schedule (for example, home training) does not match the current user location.

(221) Referring to FIGS. 16 and 17, in an embodiment, when the location of the user schedule (for example, home training) does not match the user location, a control interface **1630** may be

provided to an electronic device **1600**. The electronic device **1600** may control operations of a plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) through the control interface **1630**.

(222) In an embodiment, the IOT server (for example, the IOT server **310** of FIG. **3**) may provide the control interface **1630** to the electronic device **1600** (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**).

(223) In another embodiment, the control interface **1630** may be provided after the control interface **1630** stored in the internal memory of the electronic device **1600** (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) is read.

(224) In an embodiment, the electronic device **1600** (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) or the IOT server (for example, the IOT server **310** of FIG. **3**) may configure devices (for example, the plurality of smart devices **330**) related to a user schedule **1620** (for example, home training) as indicated by reference numeral **1610**.

(225) In an embodiment, the electronic device **1600** (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may receive the control interface **1630** for controlling operations of the devices for example, the plurality of smart devices **330**) related to the user schedule **1620** (for example, home training) from the IOT server **310**.

(226) In another embodiment, the electronic device **1600** (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may read the control interface **1630** for controlling operations of the devices (for example, the plurality of smart devices **330**) related to the user schedule **1620** (for example, home training) stored in the internal memory.

(227) In an embodiment, the electronic device **1400** (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may control the operations of the plurality of smart devices **330** through the control interface **1630** of the devices (for example, the plurality of smart devices **330**) related to the user schedule **1620** (for example, home training).

(228) For example, the electronic device **1600** (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may separate the time point into before the schedule **1641**, the start of the schedule **1642**, during the schedule **1643**, and after the schedule **1644** with respect to the user schedule **1620** (for example, home training).

(229) In an embodiment, the electronic device **1600** (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) or the IOT server **310** may identify the location of the user schedule according to each time point of the user schedule **1620** (for example, home training) and the user location at the current time point. For example, the electronic device **1600** (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) may identify the location of the user schedule before the schedule **1641**, at the start of the schedule **1642**, during the schedule **1643**, and after the schedule **1644** and the user location at the current time point.

(230) In an embodiment, when the location of the user schedule before the schedule **1641**, at the start of the schedule **1642**, during the schedule **1643**, and after the schedule **1644** does not match the user location at the current time point as indicated by reference numeral **1651** or **1653**, the electronic device **1600** (for example, the electronic device **300** of FIG. **3** or the electronic device **400** of FIG. **4**) or the IOT server (for example, the IOT server **310** of FIG. **3**) may provide the control interface **1652** or **1654** for controlling the operation of the smart device for the time point at which the user location does not match to the electronic device **1600**. The control interface **1652** or **1654** may be provided from the IOT server (for example, the IOT server **310** of FIG. **3**) to the electronic device **1600**, or the control interface **1652** or **1654** stored in the internal memory of the electronic device **1600** may be read.

(231) In an embodiment, the electronic device **1600** may control the operations of the plurality of smart devices **330** through the control interface **1630**, **1652**, or **1654**.

(232) At least some of the operations illustrated in FIGS. **16** and **17** may be omitted. Before or after at least some of the operations illustrated in FIGS. **16** and **17**, at least some operations mentioned

with reference to other drawings in the disclosure may be added and/or inserted. The operations illustrated in FIGS. **16** and **17** may be performed the processor (for example, the processor **120** of FIG. **1**) of the electronic device **1600** or the processor of the IOT server (for example, the IOT server **310** of FIG. **3**). For example, the memory of the electronic device **1600** or the IOT server (for example, the IOT server **310** of FIG. **3**) may store instructions causing the processor to, when executed, perform at least some operations illustrated in FIGS. **16** and **17**.

(233) FIG. **18** illustrates an example of a user configuration option for a control interface for controlling operations of smart devices.

(234) Referring to FIG. **18**, an electronic device **1800** (for example, the electronic device **300** of FIG. **3**, the electronic device **400** of FIG. **4**, the electronic device **1000** of FIG. **10**, the electronic device **1200** of FIG. **12**, the electronic device **1400** of FIG. **14**, or the electronic device **1600** of FIG. **16**) or an IOT server (for example, the IOT server **310** of FIG. **3**) according to various embodiments may configure a user option for a control interface of devices (for example, the plurality of smart devices **330** of FIG. **3**) according to each user schedule time point.

(235) In an embodiment, the electronic device **1800** or the IOT server **310** may separate the time point into before the user schedule, the start of the user schedule, during the user schedule **1810**, and after the user schedule **1830** and provide the user option for the control interface.

(236) In an embodiment, the electronic device **1800** or the IOT server **310** may provide a user option **1820** of the control interface for controlling operations of a plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) before the user schedule, at the start of the user schedule, or during the user schedule **1810**. For example, when a first offer is made before the start of the user schedule, at the time point at which the user schedule starts, and during the user schedule **1810**, the electronic device **1800** or the IOT server **310** may provide the user option **1820** of the control interface. For example, when a configuration of ‘continuously receiving an offer to control the device with respect to this schedule’ is turned off in the user option **1820** of the control interface, the electronic device **1800** or the IOT server **310** may not provide the control interface for this schedule thereafter.

(237) In an embodiment, the electronic device **1800** or the IOT server **310** may provide the user option **1840** of the control interface for controlling operations of the smart devices (for example, the plurality of smart devices **330** of FIG. **3**) after the user schedule **1830**. For example, the electronic device **1800** or the IOT server **310** may provide the user option **1840** of the control interface to extend the operations of the plurality of smart devices **330** by extending the user schedule after the schedule **1830**.

(238) FIG. **19** is a diagram **1900** illustrating an example of a user configuration option for a control interface for each device (for example, smart device) according to a user schedule (for example, home working).

(239) Referring to FIG. **19**, an electronic device (for example, the electronic device **300** of FIG. **3**, the electronic device **400** of FIG. **4**, the electronic device **1000** of FIG. **10**, the electronic device **1200** of FIG. **12**, the electronic device **1400** of FIG. **14**, the electronic device **1600** of FIG. **16**, or the electronic device **1800** of FIG. **18**) or an IOT server (for example, the IOT server **310** of FIG. **3**) according to various embodiments may provide a user configuration option for a control interface for each of a plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to a user schedule (for example, home working).

(240) In an embodiment, the smart devices **330** may include mobile devices, tablet devices, smart watches, Bluetooth earphones (for example, buds), speakers, washing machines, drying machines, steam closets, shoes cleaners, robot cleaners, ovens, air conditions, air purifiers, TVs, sound bars (audio), and lights.

(241) In an embodiment, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to a device characteristic and configure operation options of the plurality of smart devices **330**.

- (242) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** into devices which can move and devices which cannot move on the basis of mobility. The electronic device or the IOT server **310** according to various embodiments may configure an operation option according to the device which can move and the device which cannot move.
- (243) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** into devices which are required to be charged and devices which are not required to be charged on the basis of whether the devices are required to be charged. The electronic device or the IOT server **310** according to various embodiments may configure an operation option according to the device which is required to be charged and the device which is not required to be charged.
- (244) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** into public devices and non-public devices on the basis of whether the devices are public devices. The electronic device or the IOT server **310** according to various embodiments may configure an operation option according to the public device and the non-public device.
- (245) FIG. **20** is a diagram **2000** illustrating an example of a user configuration option for a control interface at each time point of a user schedule according to the user schedule.
- (246) Referring to FIG. **20**, an electronic device (for example, the electronic device **300** of FIG. **3**, the electronic device **400** of FIG. **4**, the electronic device **1000** of FIG. **10**, the electronic device **1200** of FIG. **12**, the electronic device **1400** of FIG. **14**, the electronic device **1600** of FIG. **16**, or the electronic device **1800** of FIG. **18**) or an IOT server (for example, the IOT server **310** of FIG. **3**) according to various embodiments provide a user configuration option of a control interface for each of a plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to a time point (for example, before the schedule, at the start of the schedule, during the schedule, or after the schedule) of the user schedule (for example, home working).
- (247) In an embodiment, the smart devices **330** may include mobile devices, tablet devices, smart watches, Bluetooth earphones (for example, buds), speakers, washing machines, drying machines, steam closets, shoes cleaners, robot cleaners, ovens, air conditions, air purifiers, TVs, sound bars (audio), and/or lights, etc.
- (248) In an embodiment, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the time point (for example, before the schedule, at the start of the schedule, during the schedule, or after the schedule) of the user schedule (for example, home working) and configure operation options of the plurality of smart devices **330**.
- (249) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the time point before the user schedule (for example, home working) and configure operation options of the plurality of smart devices **330** (for example, power on, power off, communication connection, communication disconnection, and operation mode).
- (250) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the start of the user schedule (for example, home working) and configure operation options of the plurality of smart devices **330** (for example, power on, power off, communication connection, communication disconnection, and operation mode).
- (251) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the time point during the user schedule (for example, home working) and configure operation options of the plurality of smart devices **330** (for example, power on, power off, communication connection, communication disconnection, and operation mode).

(252) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the time point after the user schedule (for example, home working) and configure operation options of the plurality of smart devices **330** (for example, power on, power off, communication connection, communication disconnection, and operation mode).

(253) FIGS. **21** and **22** illustrate examples of a control interface provision method according to a user schedule (for example, travel).

(254) Referring to FIGS. **21** and **22**, an electronic device **2100** (for example, the electronic device **300** of FIG. **3**, the electronic device **400** of FIG. **4**, the electronic device **1000** of FIG. **10**, the electronic device **1200** of FIG. **12**, the electronic device **1400** of FIG. **14**, the electronic device **1600** of FIG. **16**, or the electronic device **1800** of FIG. **18**) or an IOT server (for example, the IOT server **310** of FIG. **3**) according to various embodiments may provide a control interface for each of a plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to a time point (for example, before the schedule **2110**, at the start of the schedule **2130**, during the schedule **2150**, or after the schedule **2170**) of the user schedule (for example, travel).

(255) In an embodiment, the time points of the user schedule (for example, travel) may include time points before the schedule **2110**, at the schedule starts **2130**, during the schedule **2150**, and after the schedule **2170**.

(256) For example, the electronic device **2100** or the IOT server **310** according to various embodiments may provide a first control interface **2120** for controlling operations of the plurality of smart devices **330** according to the time point before the schedule **2110** of the user schedule (for example, travel).

(257) For example, the electronic device **2100** or the IOT server **310** according to various embodiments may provide a second control interface **2140** (for example, informing of home monitoring security (go out) execution before the start of the travel) for controlling the operations of the plurality of smart devices **330** according to the start of the schedule **2130** of the user schedule (for example, travel).

(258) For example, the electronic device **2100** or the IOT server **310** according to various embodiments may provide a third control interface **2160** for controlling the operations of the plurality of smart devices **330** according to the time point during the schedule **2150** of the user schedule (for example, travel).

(259) For example, the electronic device **2100** or the IOT server **310** according to various embodiments may provide a fourth control interface **2180** for controlling the operations of the plurality of smart devices **330** according to the time point after the schedule **2170** of the user schedule (for example, travel).

(260) FIG. **23** is a diagram **2300** illustrating an example of a user configuration option of a control interface for each device (for example, smart device) according to a user schedule (for example, travel).

(261) Referring to FIG. **23**, an electronic device **2100** (for example, the electronic device **300** of FIG. **3**, the electronic device **400** of FIG. **4**, the electronic device **1000** of FIG. **10**, the electronic device **1200** of FIG. **12**, the electronic device **1400** of FIG. **14**, the electronic device **1600** of FIG. **16**, the electronic device **1800** of FIG. **18**, or the electronic device **2100** of FIG. **21**) or an IOT server (for example, the IOT server **310** of FIG. **3**) according to various embodiments may provide a user configuration option of a control interface for each of a plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to a user schedule (for example, travel).

(262) In an embodiment, the smart devices **330** may include mobile devices, air conditioners, air purifiers, home CCTVs, open/close sensors, human body sensors, smoke detectors, and leakage detection sensors.

(263) In an embodiment, the electronic device or the IOT server **310** according to various

embodiments may classify the plurality of smart devices **330** according to a device characteristic and configure operation options of the plurality of smart devices **330**.

(264) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** into public devices and non-public devices on the basis of whether the devices are public devices. The electronic device or the IOT server **310** according to various embodiments may configure an operation option according to the public device and the non-public device.

(265) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** into device which can move and devices which cannot move on the basis of mobility. The electronic device or the IOT server **310** according to various embodiments may configure an operation option according to the device which can move and the device which cannot move.

(266) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** into devices which are required to be charged and devices which are not required to be charged on the basis of whether the devices are required to be charged. The electronic device or the IOT server **310** according to various embodiments may configure an operation option according to the device which is required to be charged and the device which is not required to be charged.

(267) FIG. **24** is a diagram **2400** illustrating an example of a user configuration option of a control interface for each time point of a user schedule according to the user schedule (for example, travel).

(268) Referring to FIG. **24**, an electronic device (for example, the electronic device **300** of FIG. **3**, the electronic device **400** of FIG. **4**, the electronic device **1000** of FIG. **10**, the electronic device **1200** of FIG. **12**, the electronic device **1400** of FIG. **14**, the electronic device **1600** of FIG. **16**, the electronic device **1800** of FIG. **18**, or the electronic device **2100** of FIG. **21**) or an IOT server (for example, the IOT server **310** of FIG. **3**) according to various embodiments may provide a user configuration option of a control interface for each of a plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to a time point (for example, before the schedule, at the start of the schedule, during the schedule, or after the schedule) of a user schedule (for example, travel).

(269) In an embodiment, the smart devices **330** may include mobile devices, air conditioners, air purifiers, home CCTVs, open/close sensors, human body sensors, smoke detectors, and leakage detection sensors.

(270) In an embodiment, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the time point (before the schedule, at which the schedule starts, during the schedule, or after the schedule) of the user schedule (for example, travel) and configure operation options of the plurality of smart devices **330**.

(271) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the time point before the schedule of the user schedule (for example, travel) and configure operation options of the plurality of smart devices **330** (for example, power on, power off, communication connection, communication disconnection, security start, security release, reservation, reservation cancel, and operation mode).

(272) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the start of the schedule of the user schedule (for example, travel) and configure operation options of the plurality of smart devices **330** (for example, power on, power off, communication connection, communication disconnection, security start, security release, reservation, reservation cancel, and operation mode).

(273) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the time point during the schedule of the user schedule (for example, travel) and configure operation options of the plurality of smart

devices **330** (for example, power on, power off, communication connection, communication disconnection, security start, security release, reservation, reservation cancel, and operation mode). (274) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the time point after the schedule of the user schedule (for example, travel) and configure operation options of the plurality of smart devices **330** (for example, power on, power off, communication connection, communication disconnection, security start, security release, reservation, reservation cancel, and operation mode).

(275) FIGS. **25** and **26** illustrate examples of a control interface provision method according to a user schedule (for example, watching content).

(276) Referring to FIGS. **25** and **26**, an electronic device **2500** (for example, the electronic device **300** of FIG. **3**, the electronic device **400** of FIG. **4**, the electronic device **1000** of FIG. **10**, the electronic device **1200** of FIG. **12**, the electronic device **1400** of FIG. **14**, the electronic device **1600** of FIG. **16**, the electronic device **1800** of FIG. **18**, or the electronic device **2100** of FIG. **21**) or an IOT server (for example, the IOT server **310** of FIG. **3**) according to various embodiments may provide a control interface for each of a plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to a time point (for example, before the schedule **2510**, at which the schedule starts **2530**, during the schedule **2550**, or after the schedule **2570**) of the user schedule (for example, watching content).

(277) In an embodiment, the time points of the user schedule (for example, watching content) may include time points before the schedule **2510**, at which the schedule starts **2530**, during the schedule **2550**, and after the schedule **2570**.

(278) For example, the electronic device **2500** or the IOT server **310** according to various embodiments may provide a first control interface **2520** (for example, informing of check of sound bar network disconnection) for controlling operations of the plurality of smart devices **330** according to the time point before the schedule **2510** of the user schedule (for example, watching content).

(279) For example, the electronic device **2500** or the IOT server **310** according to various embodiments may provide a second control interface **2540** for controlling the operations of the plurality of smart devices **330** according to the start of the schedule **2530** of the user schedule (for example, watching content).

(280) For example, the electronic device **2500** or the IOT server **310** according to various embodiments may provide a third control interface **2560** (for example, a re-execution button) for controlling the operations of the plurality of smart devices **330** according to the time point during the schedule **2550** of the user schedule (for example, watching content).

(281) For example, the electronic device **2500** or the IOT server **310** according to various embodiments may provide a fourth control interface **2580** (for example, a sports mode end button) for controlling the operations of the plurality of smart devices **330** according to the time point after the schedule **2570** of the user schedule (for example, watching content).

(282) FIG. **27** illustrates an example of a user configuration option of a control interface for each device (for example, smart device) according to a user schedule (for example, watching content).

(283) Referring to FIG. **27**, an electronic device (for example, the electronic device **300** of FIG. **3**, the electronic device **400** of FIG. **4**, the electronic device **1000** of FIG. **10**, the electronic device **1200** of FIG. **12**, the electronic device **1400** of FIG. **14**, the electronic device **1600** of FIG. **16**, the electronic device **1800** of FIG. **18**, the electronic device **2100** of FIG. **21**, or the electronic device **2500** of FIG. **25**) or an IOT server (for example, the IOT server **310** of FIG. **3**) according to various embodiments may provide a user configuration option of a control interface for each of a plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to a user schedule (for example, watching content).

(284) In an embodiment, the smart devices **330** may include mobile devices, speakers, air

conditioners, TVs, and sound bars (audio).

(285) In an embodiment, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to a device characteristic and configure operation options of the plurality of smart devices **330**.

(286) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** into device which can move and devices which cannot move on the basis of mobility. The electronic device or the IOT server **310** according to various embodiments may configure an operation option according to the device which can move and the device which cannot move.

(287) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** into devices which are required to be charged and devices which are not required to be charged on the basis of whether the devices are required to be charged. The electronic device or the IOT server **310** according to various embodiments may configure an operation option according to the device which is required to be charged and the device which is not required to be charged.

(288) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** into public devices and non-public devices on the basis of whether the devices are public devices. The electronic device or the IOT server **310** according to various embodiments may configure an operation option according to the public device and the non-public device.

(289) FIG. **28** illustrates an example of a user configuration option of a control interface for each time point of a user schedule according to the user schedule (for example, watching content).

(290) Referring to FIG. **28**, an electronic device (for example, the electronic device **300** of FIG. **3**, the electronic device **400** of FIG. **4**, the electronic device **1000** of FIG. **10**, the electronic device **1200** of FIG. **12**, the electronic device **1400** of FIG. **14**, the electronic device **1600** of FIG. **16**, the electronic device **1800** of FIG. **18**, the electronic device **2100** of FIG. **21**, or the electronic device **2500** of FIG. **25**) or an IOT server (for example, the IOT server **310** of FIG. **3**) according to various embodiments may provide a user configuration option of a control interface for each of a plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to a time point (for example, before the schedule, at which the schedule starts, during the schedule, or after the schedule) of a user schedule (for example, watching content).

(291) In an embodiment, the smart devices **330** may include mobile devices, speakers, TVs, sound bars (audio), and air conditioners.

(292) In an embodiment, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the time point (for example, before the schedule, at which the schedule starts, during the schedule, or after the schedule) of the user schedule (for example, watching content) and configure operation options of the plurality of smart devices **330**.

(293) In an embodiment, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the time point before the schedule of the user schedule (for example, watching content) and configure operation options of the plurality of smart devices **330** (for example, power on, power off, communication connection, communication disconnection, mute, air conditioning, and operation mode).

(294) In an embodiment, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the start of the schedule of the user schedule (for example, watching content) and configure operation options of the plurality of smart devices **330** (for example, power on, power off, communication connection, communication disconnection, mute, air conditioning, and operation mode).

(295) In an embodiment, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the time point during the

schedule of the user schedule (for example, watching content) and configure operation options of the plurality of smart devices **330** (for example, power on, power off, communication connection, communication disconnection, mute, air conditioning, and operation mode).

(296) In an embodiment, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the time point after the schedule of the user schedule (for example, watching content) and configure operation options of the plurality of smart devices **330** (for example, power on, power off, communication connection, communication disconnection, mute, air conditioning, and operation mode).

(297) FIG. **29** illustrates an example of a user configuration option of a control interface for each device (for example, smart device) according to a user schedule (for example, home training).

(298) Referring to FIG. **29**, an electronic device (for example, the electronic device **300** of FIG. **3**, the electronic device **400** of FIG. **4**, the electronic device **1000** of FIG. **10**, the electronic device **1200** of FIG. **12**, the electronic device **1400** of FIG. **14**, the electronic device **1600** of FIG. **16**, the electronic device **1800** of FIG. **18**, the electronic device **2100** of FIG. **21**, or the electronic device **2500** of FIG. **25**) or an IOT server (for example, the IOT server **310** of FIG. **3**) according to various embodiments may provide a user configuration option of a control interface for each of a plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to a user schedule (for example, home training).

(299) In an embodiment, the smart devices **330** may include mobile devices, smart watches, speakers, washing machines, steam closets, air conditioners, TVs, and lights.

(300) In an embodiment, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to a device characteristic and configure operation options of the plurality of smart devices **330**.

(301) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** into device which can move and devices which cannot move on the basis of mobility. The electronic device or the IOT server **310** according to various embodiments may configure an operation option according to the device which can move and the device which cannot move.

(302) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** into devices which are required to be charged and devices which are not required to be charged on the basis of whether the devices are required to be charged. The electronic device or the IOT server **310** according to various embodiments may configure an operation option according to the device which is required to be charged and the device which is not required to be charged.

(303) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** into public devices and non-public devices on the basis of whether the devices are public devices. The electronic device or the IOT server **310** according to various embodiments may configure an operation option according to the public device and the non-public device.

(304) FIG. **30** illustrates an example of a user configuration option of a control interface for each time point of a user schedule according to the user schedule (for example, home training).

(305) Referring to FIG. **30**, an electronic device (for example, the electronic device **300** of FIG. **3**, the electronic device **400** of FIG. **4**, the electronic device **1000** of FIG. **10**, the electronic device **1200** of FIG. **12**, the electronic device **1400** of FIG. **14**, the electronic device **1600** of FIG. **16**, the electronic device **1800** of FIG. **18**, the electronic device **2100** of FIG. **21**, or the electronic device **2500** of FIG. **25**) or an IOT server (for example, the IOT server **310** of FIG. **3**) according to various embodiments may provide a user configuration option of a control interface for each of a plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to a time point (for example, before the schedule, at which the schedule starts, during the schedule, or after the schedule) of a user schedule (for example, home training).

(306) In an embodiment, the smart devices **330** may include mobile devices, smart watches, speakers, washing machines, steam closets, air conditioners, TVs, and lights.

(307) In an embodiment, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to a time point (for example, before the schedule, at which the schedule starts, during the schedule, or after the schedule) of the user schedule (for example, home training) and configure operation options of the plurality of smart devices **330**.

(308) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the time point before the schedule of the user schedule (for example, home training) and configure operation options of the plurality of smart devices **330** (for example, power on, power off, communication connection, communication disconnection, mute, air conditioning, clean mode, sports mode, sound volume, and operation mode).

(309) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the start of the schedule of the user schedule (for example, home training) and configure operation options of the plurality of smart devices **330** (for example, power on, power off, communication connection, communication disconnection, mute, air conditioning, clean mode, sports mode, sound volume, and operation mode).

(310) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the time point during the schedule of the user schedule (for example, home training) and configure operation options of the plurality of smart devices **330** (for example, power on, power off, communication connection, communication disconnection, mute, air conditioning, clean mode, sports mode, sound volume, and operation mode).

(311) For example, the electronic device or the IOT server **310** according to various embodiments may classify the plurality of smart devices **330** according to the time point after the schedule of the user schedule (for example, home training) and configure operation options of the plurality of smart devices **330** (for example, power on, power off, communication connection, communication disconnection, mute, air conditioning, clean mode, sports mode, sound volume, and operation mode).

(312) The electronic device and the method of operating the same according to various embodiments may provide a customized control interface for controlling operations of smart devices having high usage correlation with user schedules on the basis of calendar schedules.

(313) The electronic device and the method of operating the same according to various embodiments may provide a customized control interface for pre-emptively controlling operations of smart devices according to each time point (for example, before the schedule, at which the schedule starts, during the schedule, or after the schedule) of the user schedule.

(314) The electronic device and the method of operating the same according to various embodiments may provide a customized control interface for controlling operations of smart devices in further consideration of a user condition at a time point at which the control interface is provided.

(315) The electronic device and the method of operating the same according to various embodiments may provide a user experience capable of easily controlling operations of a plurality of smart devices by reducing steps of identifying the user schedule, reducing cumbersome steps of finding functions of the plurality of smart devices and controlling the same, and providing a control interface according to the user schedule.

(316) The electronic device and the method of operating the same according to various embodiments may provide the electronic device (for example, smartphone) with a control interface capable of controlling a plurality of smart devices according to a user schedule and control

operations of the plurality of smart devices according to a user schedule through the control interface.

(317) The electronic device and the method of operating the same according to various embodiments may provide a control interface capable of controlling operations of a plurality of smart devices when a state of a device (for example, smart device) registered in a user schedule (for example, home working, home training, travel, or watching content) does not match a state of a device at the current time point (for example, smart device).

(318) The electronic device and the method of operating the same according to various embodiments may provide a control interface capable of controlling operations of a plurality of smart devices when a location registered in a user schedule (for example, home working, home training, travel, or watching content) does not match a current user location.

(319) The electronic device and the method of operating the same according to various embodiments may provide a control interface capable of controlling operations of a plurality of smart devices according to a user schedule (for example, home working, home training, travel, or watching content).

(320) The electronic device and the method of operating the same according to various embodiments may provide a control interface capable of controlling operations of a plurality of smart devices for each time point of the user schedule according to the user schedule (for example, home working, home training, travel, or watching content).

(321) An electronic device (the electronic device **101** of FIG. **1**, the electronic device **300** of FIG. **3**, the electronic device **400** of FIG. **4**, the electronic device **1000** of FIG. **10**, the electronic device **1200** of FIG. **12**, the electronic device **1400** of FIG. **14**, the electronic device **1600** of FIG. **16**, the electronic device **1800** of FIG. **18**, the electronic device **2100** of FIG. **21**, or the electronic device **2500** of FIG. **25**) according to various embodiments may include a communication module (for example, the communication module **190** of FIG. **1**) for making a connection with a plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) and an Internet of Things (JOT) server, a processor (for example, the processor **120** of FIG. **1**) operatively connected to the communication module (for example, the communication module **190** of FIG. **1**), and a memory (for example, the memory **130** of FIG. **1**) operatively connected to the processor (for example, the processor **120** of FIG. **1**). The memory (for example, the memory **130** of FIG. **1**) may include instructions causing the processor (for example, the processor **120** of FIG. **1**) to configure a control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**) for controlling operations of the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to a user schedule type, based on an input user schedule and control the operations of the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) through the control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**).

(322) According to an embodiment, the processor (for example, the processor **120** of FIG. **1**) may configure the control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**) for controlling the operations of the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to a time point of the user schedule.

(323) According to an embodiment, the processor (for example, the processor **120** of FIG. **1**) may classify the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to a device characteristic and provide the control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**) according to the

device characteristic of the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**).

(324) According to an embodiment, the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) may be classified based on whether the plurality of smart devices have mobility, need wired or wireless charging, or are public devices.

(325) According to an embodiment, the control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**) may be provided according to the device characteristic of the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to the time point before the schedule of the user schedule (for example, before the schedule **1041** of FIG. **11**, before the schedule **1241** of FIG. **13**, before the schedule **1441** of FIG. **15**, or before the schedule **1641** of FIG. **17**).

(326) According to an embodiment, the control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**) may be provided according to the device characteristic of the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to start of the schedule of the user schedule (for example, the start of the schedule **1042** of FIG. **11**, the start of the schedule **1241** of FIG. **13**, the start of the schedule **1442** of FIG. **15**, or the start of the schedule **1642** of FIG. **17**).

(327) According to an embodiment, the control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**) may be provided according to the device characteristic of the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to the time point during the schedule of the user schedule (for example, during the schedule **1043** of FIG. **11**, during the schedule **1243** of FIG. **13**, during the schedule **1443** of FIG. **15**, or during the schedule **1643** of FIG. **17**).

(328) According to an embodiment, the control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**) may be provided according to the device characteristic of the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to the time point after the user schedule (for example, after the schedule **1044** of FIG. **11**, after the schedule **1244** of FIG. **13**, after the schedule **1444** of FIG. **15**, or after the schedule **1644** of FIG. **17**).

(329) According to an embodiment, a target time point at which the control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**) is activated may be configured according to the time point of the user schedule. A user location may be identified when entering the target time point, and the control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**) may be provided according to the user location.

(330) According to an embodiment, a target time point at which the control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**) is activated may be configured according to the time point of the user schedule. States of the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) may be identified when entering the target time point, and the control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**) may be provided according to the states of the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**).

3).

(331) A method of operating an electronic device (for example, the electronic device **101** of FIG. **1**, the electronic device **300** of FIG. **3**, the electronic device **400** of FIG. **4**, the electronic device **1000** of FIG. **10**, the electronic device **1200** of FIG. **12**, the electronic device **1400** of FIG. **14**, the electronic device **1600** of FIG. **16**, the electronic device **1800** of FIG. **18**, the electronic device **2100** of FIG. **21**, or the electronic device **2500** of FIG. **25**) according to various embodiments may include making a connection with a plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) and an Internet of Things (JOT) server, registering a user schedule, configuring a control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**) for controlling operations of the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to a user schedule type, and controlling the operation of the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) through the control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**).

(332) According to an embodiment, the control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**) for controlling the operations of the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) may be configured according to a time point of the user schedule.

(333) According to an embodiment, the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) may be classified according to a device characteristic, and the control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**) may be provided according to the device characteristic of the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**).

(334) According to an embodiment, the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) may be classified based on whether the plurality of smart devices have mobility, need wired or wireless charging, or are public devices.

(335) According to an embodiment, the control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**) may be provided according to the device characteristic of the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to the time point before the schedule of the user schedule (for example, before the schedule **1041** of FIG. **11**, before the schedule **1241** of FIG. **13**, before the schedule **1441** of FIG. **15**, or before the schedule **1641** of FIG. **17**).

(336) According to an embodiment, the control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**) may be provided according to the device characteristic of the plurality of smart devices (for example, the plurality of smart devices **330** of FIG. **3**) according to start of the schedule of the user schedule (for example, the start of the schedule **1042** of FIG. **11**, the start of the schedule **1241** of FIG. **13**, the start of the schedule **1442** of FIG. **15**, or the start of the schedule **1642** of FIG. **17**).

(337) According to an embodiment, the control interface (for example, the control interface **420** of FIG. **4**, the control interface **1030** of FIG. **10**, the control interface **1230** of FIG. **12**, the control interface **1430** of FIG. **14**, or the control interface **1630** of FIG. **16**) may be provided according to the device characteristic of the plurality of smart devices for example, the plurality of smart devices **330** of FIG. **3**) according to the time point during the schedule of the user schedule (for example, during the schedule **1043** of FIG. **11**, during the schedule **1243** of FIG. **13**, during the schedule

1443 of FIG. 15, or during the schedule 1643 of FIG. 17).

(338) According to an embodiment, the control interface (for example, the control interface 420 of FIG. 4, the control interface 1030 of FIG. 10, the control interface 1230 of FIG. 12, the control interface 1430 of FIG. 14, or the control interface 1630 of FIG. 16) may be provided according to the device characteristic of the plurality of smart devices (for example, the plurality of smart devices 330 of FIG. 3) according to the time point after the user schedule (for example, after the schedule 1044 of FIG. 11, after the schedule 1244 of FIG. 13, after the schedule 1444 of FIG. 15, or after the schedule 1644 of FIG. 17).

(339) According to an embodiment, a target time point at which the control interface (for example, the control interface 420 of FIG. 4, the control interface 1030 of FIG. 10, the control interface 1230 of FIG. 12, the control interface 1430 of FIG. 14, or the control interface 1630 of FIG. 16) is activated may be configured according to the time point of the user schedule. A user location may be identified when entering the target time point, and the control interface (for example, the control interface 420 of FIG. 4, the control interface 1030 of FIG. 10, the control interface 1230 of FIG. 12, the control interface 1430 of FIG. 14, or the control interface 1630 of FIG. 16) may be provided according to the user location.

(340) According to an embodiment, a target time point at which the control interface (for example, the control interface 420 of FIG. 4, the control interface 1030 of FIG. 10, the control interface 1230 of FIG. 12, the control interface 1430 of FIG. 14, or the control interface 1630 of FIG. 16) is activated may be configured according to the time point of the user schedule. States of the plurality of smart devices (for example, the plurality of smart devices 330 of FIG. 3) may be identified when entering the target time point, and the control interface (for example, the control interface 420 of FIG. 4, the control interface 1030 of FIG. 10, the control interface 1230 of FIG. 12, the control interface 1430 of FIG. 14, or the control interface 1630 of FIG. 16) may be provided according to the states of the plurality of smart devices (for example, the plurality of smart devices 330 of FIG. 3).

(341) The electronic device and the method of operating the same according to various embodiments may provide a customized control interface for controlling operations of smart devices having high usage correlation with user schedules on the basis of calendar schedules.

(342) The electronic device and the method of operating the same according to various embodiments may provide a customized control interface for pre-emptively controlling operations of smart devices according to each time point (for example, before the schedule, at which the schedule starts, during the schedule, or after the schedule) of the user schedule.

(343) The electronic device and the method of operating the same according to various embodiments may provide a customized control interface for controlling operations of smart devices in further consideration of a user condition at a time point at which the control interface is provided.

(344) The electronic device and the method of operating the same according to various embodiments may provide a user experience capable of easily controlling operations of a plurality of smart devices by reducing steps of identifying the user schedule, reducing cumbersome steps of finding functions of the plurality of smart devices and controlling the same, and providing a control interface according to the user schedule.

(345) The electronic device and the method of operating the same according to various embodiments may provide the electronic device (for example, smartphone) with a control interface capable of controlling a plurality of smart devices according to a user schedule and control operations of the plurality of smart devices according to a user schedule through the control interface.

(346) The electronic device and the method of operating the same according to various embodiments may provide a control interface capable of controlling operations of a plurality of smart devices when a state of a device (for example, smart device) registered in a user schedule (for

example, home working, home training, travel, or watching content) does not match a state of a device at the current time point (for example, smart device).

(347) The electronic device and the method of operating the same according to various embodiments may provide a control interface capable of controlling operations of a plurality of smart devices when a location registered in a user schedule (for example, home working, home training, travel, or watching content) does not match a current user location.

(348) The electronic device and the method of operating the same according to various embodiments may provide a control interface capable of controlling operations of a plurality of smart devices according to a user schedule (for example, home working, home training, travel, or watching content).

(349) The electronic device and the method of operating the same according to various embodiments may provide a control interface capable of controlling operations of a plurality of smart devices for each time point of the user schedule according to the user schedule (for example, home working, home training, travel, or watching content).

(350) The disclosure has been illustrated and described with reference to various implementations thereof, but it is understood by those skilled in the art that various changes in forms and details can be made without departing the idea and scope of the disclosure. The disclosure is defined by the accompanying claims and equivalent thereto.

Claims

1. An electronic device comprising: a communication circuit configured to connect with an Internet of Things server and a plurality of smart devices, the plurality of smart devices including a plurality of different types of smart devices; a processor operatively connected to the communication circuit; and memory for storing instructions that, when executed by the processor, cause the electronic device to: identify target smart devices that have a usage correlation with a user schedule type of a user schedule, the target smart devices including at least two different types of smart devices; configure a control interface for controlling, through a single interface, a plurality of operations that correspond respectively to the target smart devices, according to the user schedule type of the user schedule; check a location registered in a user schedule and a current user location; activate the control interface to display the control interface at a target time point associated with the user schedule, and display the control interface to control the target smart devices when there is a mismatch between the location registered in the user schedule and the current user location, the displayed control interface including individual controls for each of the target smart devices; and control the plurality of operations of the target smart devices based a user input to the individual controls that is received through the displayed control interface.

2. The electronic device of claim 1, wherein the instructions further cause the electronic device to classify the plurality of smart devices according to a device characteristic, and provide the control interface according to the device characteristic.

3. The electronic device of claim 2, wherein the device characteristic comprises whether a smart device has mobility, needs wired or wireless charging, or is a public device.

4. The electronic device of claim 2, wherein the time point is before the user schedule, and the control interface is provided before the user schedule.

5. The electronic device of claim 2, wherein the time point is a start of the user schedule, and the control interface is provided at the start of the user schedule.

6. The electronic device of claim 2, wherein the time point is during the user schedule, and the control interface is provided during the user schedule.

7. The electronic device of claim 2, wherein the time point is after the user schedule, and the control interface is provided after the user schedule.

8. The electronic device of claim 2, wherein the instructions further cause the electronic device to:

determine a user location when the target time point occurs, and provide the control interface according to the user location that is determined.

9. The electronic device of claim 2, wherein the instructions further cause the electronic device to: determine states of the plurality of smart devices when the target time point occurs, and provide the control interface according to the states of the plurality of smart devices.

10. A method of operating an electronic device, the method comprising: connecting with an Internet of Things server and a plurality of smart devices, the plurality of smart devices including a plurality of different types of smart devices; registering a user schedule; identifying target smart devices that have a usage correlation with a user schedule type of a user schedule, the target smart devices including at least two different types of smart devices; configuring a control interface for controlling, through a single interface, a plurality of operations that correspond respectively to the target smart devices, according to the user schedule type of the user schedule; checking a location registered in a user schedule and a current user location; activating the control interface to display the control interface at a target time point associated with the user schedule, and displaying the control interface to control the target smart devices when there is a mismatch between the location registered in the user schedule and the current user location, the displayed control interface including individual controls for each of the target smart devices; and controlling the plurality of operations of the target smart devices based on a user input to the individual controls that is received through the displayed control interface.

11. The method of claim 10, wherein the plurality of smart devices are classified according to a device characteristic, and the control interface is provided according to the device characteristic.

12. The method of claim 11, wherein the device characteristic comprises whether a smart device has mobility, needs wired or wireless charging, or is a public device.

13. The method of claim 11, wherein the time point is before the user schedule, and the control interface is provided before the user schedule.

14. The method of claim 11, wherein the time point is a start of the user schedule, and the control interface is provided at the start of the user schedule.

15. The method of claim 11, wherein the time point is during the user schedule, and the control interface is provided during the user schedule.

16. The method of claim 11, wherein the time point is after the user schedule, and the control interface is provided after the user schedule.

17. The method of claim 11, wherein the method further comprises: determining a user location when the target time point occurs, and providing the control interface according to the user location that is determined.

18. The method of claim 11, wherein the method further comprises: determining states of the plurality of smart devices when the target time point occurs, and providing the control interface according to the states of the plurality of smart devices.
