

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12389091
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Cheng; Sung-Pao et al.

Photo detector

Abstract

A photo detector including a photo sensor part and a power source module is provided. The power source module is fixed on the photo sensor part and electrically connected to the photo sensor part. The power source module is detachable and includes a handle.

Inventors:	Cheng; Sung-Pao (Tainan, TW), Lo; Hsin-Lin (Tainan, TW)
Applicant:	InnoCare Optoelectronics Corporation (Tainan, TW)
Family ID:	86689744
Assignee:	InnoCare Optoelectronics Corporation (Tainan, TW)
Appl. No.:	18/366703
Filed:	August 08, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240080537 A1	Mar. 07, 2024

Foreign Application Priority Data

TW	111209748	Sep. 07, 2022
----	-----------	---------------

Publication Classification

Int. Cl.: H04N23/30 (20230101); H04N23/54 (20230101)

U.S. Cl.:

CPC H04N23/30 (20230101); H04N23/54 (20230101);

Field of Classification Search

USPC: 348/162

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6832729	12/2003	Perry	235/491	G06K 7/12
2005/0072935	12/2004	Lussier	250/458.1	G01N 21/6486
2006/0169907	12/2005	Shinden	250/370.09	H04N 23/651
2010/0207024	12/2009	Thiele	250/330	G03B 17/00
2010/0284521	12/2009	McBroom	378/204	A61B 6/4233
2015/0192286	12/2014	Hansen	362/373	F21L 4/027
2015/0373482	12/2014	Barnard	370/338	H04W 4/40
2017/0168496	12/2016	Yamamoto	N/A	G05D 1/0212
2019/0041271	12/2018	Preston	N/A	G01K 1/026
2020/0003628	12/2019	Preston	N/A	G01K 13/00
2020/0081369	12/2019	Kojima	N/A	G03G 15/065
2020/0330321	12/2019	Wersland	N/A	A61H 23/00
2022/0143463	12/2021	Campanaro	N/A	A63B 22/0087
2023/0049899	12/2022	Yeh	N/A	G02B 27/0093
2023/0370573	12/2022	Maddox	N/A	H04N 7/183

Primary Examiner: Dhillon; Peet

Attorney, Agent or Firm: JCIPRNET

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims the priority benefit of Taiwan application serial no. 111209748, filed on Sep. 7, 2022. The entirety of the above-mentioned patent application is hereby incorporated by reference herein and made a part of this specification.

BACKGROUND

Technical Field

(2) The disclosure relates to an electronic device, and particularly relates to a photo detector.

Description of Related Art

(3) Portable design allows an electronic device to provide more convenient operations. However, the portable design also makes it impossible for the electronic device to be continuously connected to a power source, and thus a usage time is limited.

SUMMARY

(4) The disclosure is directed to a photo detector including a photo sensor part and a power source module. The power source module is fixed on the photo sensor part and is electrically connected to the photo sensor part. The power source module is detachable, and the power source module includes a handle.

(5) According to an embodiment of the disclosure, the power source module includes a battery and

a first interface. The first interface is electrically connected to the battery, and the first interface is used for transmitting an external power source to charge the battery.

(6) According to an embodiment of the disclosure, the power source module further includes a second interface. The second interface is electrically connected to the battery, and the second interface is used for transmitting a power source provided by the battery.

(7) According to an embodiment of the disclosure, at least one of the first interface and the second interface is a USB interface.

(8) According to an embodiment of the disclosure, the photo detector further includes a connector. The photo sensor part is electrically connected to the power source module through the connector.

(9) According to an embodiment of the disclosure, the power source module includes a protruding structure, and the photo sensor part includes a concave structure. The protruding structure is disposed in the concave structure, so that the power source module is fixed on the photo sensor part.

(10) According to an embodiment of the disclosure, the power source module includes a battery and a display unit. The display unit is electrically connected to the battery, and the display unit is used for displaying a power level of the battery.

(11) According to an embodiment of the disclosure, the power source module further includes a controller electrically connected between the battery and the display unit.

(12) According to an embodiment of the disclosure, the power source module includes an analog-to-digital signal converter electrically connected between the battery and the controller.

(13) According to an embodiment of the disclosure, the photo sensor part includes an electrical storage unit, and the electrical storage unit is electrically connected to the power source module to receive a power source.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a diagram of a power source module for a photo detector according to some embodiments of the disclosure.
- (2) FIG. 2 is a schematic diagram of a photo detector according to an embodiment of the disclosure.
- (3) FIG. 3A and FIG. 3B are schematic diagrams of a detachable connection structure according to an embodiment of the disclosure.
- (4) FIG. 4 is a schematic diagram of a photo detector according to an embodiment of the disclosure.
- (5) FIG. 5 is a schematic block diagram of some components of a power source module according to an embodiment of the disclosure.
- (6) FIG. 6 is a schematic block diagram of some components of a power source module according to an embodiment of the disclosure.

DESCRIPTION OF THE EMBODIMENTS

- (7) The disclosure may be understood by referring to the following detailed description in conjunction with the accompanying drawings. It should be noted that, in order to achieve easy understanding of the readers and concise of the drawings, the drawings in the disclosure only depict a part of an electronic device, and specific elements in the drawings are not drawn to actual scales. In addition, the number and size of each element in the figures are for illustration only, and are not intended to limit the scope of the disclosure.
- (8) Certain terms are used throughout the specification of the disclosure and the appended claims to refer to specific components. Those skilled in the art should understand that electronic device manufacturers may probably use different names to refer to the same components. This

specification is not intended to distinguish between components that have the same function but different names. In the following specification and claims, the terms “including”, “containing”, “having”, etc., are open terms, so that they should be interpreted as meaning of “including but not limited to . . .”. Therefore, when the terms “including”, “containing”, and/or “having” are used in the description of the disclosure, they specify existence of corresponding features, regions, steps, operations, and/or components, but do not exclude existence of one or more corresponding features, regions, steps, operations, and/or components.

(9) Directional terminology mentioned in the specification, such as “top”, “bottom”, “front”, “back”, “left”, and “right” merely refer to the directions in the accompanying drawings. Therefore, the used directional terminology is only illustrative, and is not intended to limit the disclosure. In the drawings, the drawings illustrate general characteristics of methods, structures, and/or materials used in specific embodiments. However, these drawings should not be construed as defining or limiting of a scope or nature of the embodiments. For example, for clarity's sake, a relative size, thickness, and location of each film layer, area and/or structure may be reduced or enlarged.

(10) When a corresponding component (for example, a film layer or an area) is described as being “disposed on another component”, the component may be directly disposed or formed on another component, or other components probably exist therebetween. On the other hand, when a component is described as being “directly disposed on another component”, none other component exists therebetween. Moreover, when a component is described as being “disposed on another component”, the two components have a vertical relationship in a top view direction, and this component may be above or below the another component, and the vertical relationship depends on an orientation of the device.

(11) It should be understood that when a component or a film layer is described as being “connected to” another component or film layer, it may be directly connected to the another component or film layer, or there is an intervening component or film layer therebetween. When a component is described as being “directly connected” to another component or film layer, there is no intervening component or film layer therebetween. Moreover, when a component is described as being “coupled to another component (or a variant thereof)”, the component may be directly connected to the another component, or indirectly connected (for example, electrically connected) to the another component through one or more components.

(12) The terms “about”, “equal to”, “equivalent” or “identical”, “substantially” or “approximately” are generally interpreted as being within a range of 20% of a given value or range, or as being within a range of 10%, 5%, 3%, 2%, 1%, or 0.5% of the given value or range.

(13) The ordinal numbers used in the specification and claims, such as “first” and “second” are used to modify components, and do not imply and represent the component or these components have any previous ordinal numbers, and do not represent a sequence of one component with another, or a sequence in a manufacturing method. The use of these ordinal numbers is only to make a clear distinction between a component with a certain name and another component with the same name. The same terms may not be used in the claims and the specification, and accordingly, a first component in the specification may be a second component in the claims.

(14) In the disclosure, any two values or directions used for comparison may have certain errors. If the first value is equal to the second value, it implies that there may be an error of about 10% between the first value and the second value; if the first direction is perpendicular to the second direction, an angle between the first direction and the second direction may be between 80 degrees and 100 degrees; and if the first direction is parallel to the second direction, the angle between the first direction and the second direction may be between 0 degree and 10 degrees.

(15) It should be noted that, in the following embodiments, the features of several different embodiments may be replaced, reorganized, and mixed to complete other embodiments without departing from the spirit of the disclosure. As long as the features of the various embodiments do not violate the spirit of the disclosure or conflict with each other, they may be mixed and matched

arbitrarily.

(16) FIG. 1 is a diagram of a power source module for a photo detector according to some embodiments of the disclosure. In FIG. 1, a power source module **100** has a casing **110**. In some embodiments, a material of the casing **110** may include plastic, ceramic, metal, alloy, other suitable materials, or a combination thereof. The casing **110** may have at least one opening **112**, and the opening **112** and a part of the casing **110** surrounding the opening **112** may be regarded as a handle **114**, so that the power source module **100** includes the handle **114**. In some embodiments, a shape of the handle **114** may be designed according to different requirements. For example, the opening **112** may have a wavy shape, a circular shape, a rectangular shape, a polygonal shape or other suitable shapes for a user to grasp. In some embodiments, one side of the casing **110** of the power source module **100** has an arc-shaped edge, and the side is adjacent to the opening **112**, but the disclosure is not limited thereto. In the embodiment, the power source module **100** includes a battery **120**. The battery **120** may be disposed inside the casing **110** and covered by the casing **110**. The battery **120** may be used to provide sufficient electrical storage capacity. Referring to FIG. 1, an installation area of the battery **120** is shown by dotted lines. The larger a volume of the battery **120** is, the higher the battery capacity is, but the disclosure is not limited thereto. The battery **120** may be a battery of various forms, including, for example, a wet battery, a dry battery, a fuel battery, a solar battery, or a combination thereof. In some embodiments, the battery **120** may include a rechargeable battery or a secondary battery, such as, a lead battery, a nickel cadmium (Ni Cd) battery, a nickel iron battery, a nickel-metal hydride battery (Ni MH), a lithium ion battery (Li Ion), a rechargeable alkaline battery, a silver zinc battery, a solid-state battery, etc., but the disclosure is not limited thereto. In some embodiments, the battery **120** may be formed by a plurality of battery cells connected in parallel or in series, but the disclosure is not limited thereto.

(17) In the embodiment, the power source module **100** includes the battery **120** and a first interface **130**. The first interface **130** may be electrically connected to the battery **120**, and the first interface **130** is configured to transmit an external power source (not shown) to charge the battery **120**. In other embodiments (not shown), the power source module **100** may include a plurality of first interfaces **130** adjacent to or separated from each other. In some embodiments, as shown in a right half of FIG. 1, a side surface **110S** of the casing **110** is shown, the first interface **130** may be disposed on the side surface **110S** of the casing **110** for a corresponding connection structure to connect, but the disclosure is not limited thereto. In other embodiments, the first interface **130** may be provided on other surfaces of the casing **110**. In some embodiments, the first interface **130** is, for example, a universal serial bus (USB) interface, for which a USB connector may be inserted into the first interface **130**, but the disclosure is not limited thereto. A type of the USB interface may include type-A USB interface, type-B USB interface, type-C USB interface, mini-A USB interface, mini-B USB interface, micro-A USB interface, micro-B USB interface, lightning interface, USB 3.0 interface, etc., but the disclosure is not limited thereto. In some embodiments, a transmission line may be provided to connect between the first interface **130** and the external power source (such as an external battery, an external power supply socket, etc.), so as to provide power to the battery **120** of the power source module **100** through the transmission line to realize charging, but the disclosure is not limited thereto.

(18) In the embodiment, the power source module **100** further includes a second interface **140**. The second interface **140** may be electrically connected to the battery **120**, and the second interface **140** is configured to transmit a power source provided by the battery **120**. The second interface **140** may be disposed on the side surface **110S** of the casing **110**. In other embodiments, the second interface **140** may be disposed on other surfaces of the casing **110**. In FIG. 1, the first interface **130** and the second interface **140** may be disposed on two opposite side surfaces of the power source module **100**, but the disclosure is not limited thereto. In some embodiments, the first interface **130** and the second interface **140** may be disposed adjacent to each other. In other embodiments (not shown), the power source module **100** may include a plurality of second interfaces **140** adjacent to

or separated from each other. In some embodiments, the second interface **140** is, for example, a USB interface, for which a USB connector may be inserted into the second interface **140**, but the disclosure is not limited thereto. In some embodiments, at least one of the first interface **130** and the second interface **140** is a USB interface. In some embodiments, the first interface **130** and the second interface **140** may be different types of USB interfaces. For example, a transmission line may be inserted between the second interface **140** and an external device (not shown) to transmit the power source of the battery **120** to the external device, but the disclosure is not limited thereto. The first interface **130** and the second interface **140** may be used for charging and discharging the battery **120**, respectively.

(19) In the embodiment, the power source module **100** further includes a first connecting member **150** disposed in the casing **110** and adjacent to a connecting edge **E100** of the casing **110**. The first connecting member **150** may have an electrical transmission property, and may be electrically connected to the battery **120** to provide the power source of the battery **120** to devices outside the power source module **100**. The first connecting member **150** may have a magnetic attraction property so as to be attached to a corresponding device. In the embodiment, the power source module **100** further includes a display unit **160**. The display unit **160** is electrically connected to the battery **120**, and the display unit **160** may be used to display a power level of the battery **120**. The display unit **160** may include a display panel, or may be a light-emitting unit, but the disclosure is not limited thereto. In some embodiments, the power source module **100** may further include a controller **170**. The controller **170** is electrically connected between the battery **120** and the display unit **160**, and the controller **170** may read the power level of the battery **120** and display the power level of the battery **120** on the display unit **160**. In some embodiments, the controller **170** may include a micro control unit (MCU), but the disclosure is not limited thereto. The controller **170** in FIG. **1** is only schematically indicated, and a dashed box labeled with **170** is not used to represent an actual outline and position of the controller. In some embodiments, the controller **170** may be a control circuit integrated with the display unit **160**, a control circuit integrated with the battery **120**, or may be an independent circuit element. In some embodiments, the power source module **100** may further include an analog-to-digital signal converter (ADC) not shown in FIG. **1**, and the ADC may be electrically connected between the battery **120** and the controller **170** for implementing signal conversion.

(20) In the embodiment, the power source module **100** may have a connecting edge **E100**, and a shape of the connecting edge **E100** may be designed according to the connected photo sensor part. In FIG. **1**, the connecting edge **E100** is, for example, a straight edge, but the disclosure is not limited thereto. In some embodiments, the first interface **130** and/or the second interface **140** may not be on the connecting edge **E100**. In some embodiments, the first connecting member **150** may be disposed on the connecting edge **E100**.

(21) FIG. **2** is a schematic diagram of a photo detector according to an embodiment of the disclosure. In FIG. **2**, a photo detector **10** includes a power source module **100** and a photo sensor part **200**. The power source module **100** is fixed on the photo sensor part **200** to constitute the photo detector **10** of the embodiment. The power source module **100** may be electrically connected to the photo sensor part **200**. Specifically, the power source module **100** may be used to provide a power source to the photo sensor part **200**. In addition, the power source module **100** fixed on the photo sensor part **200** may be detachable, i.e., the power source module **100** may be fixed on the photo sensor part **200** or removed from the photo sensor part **200** according to requirements. In some embodiments, the photo sensor part **200** may be combined with other devices, such as a light source module, to realize photo detection, but the disclosure not limited thereto.

(22) In the embodiment, the power source module **100** includes a casing **110** provided with a handle **114**, a battery **120**, a first interface **130**, a second interface **140**, a first connecting member **150** and/or a display unit **160**, but the disclosure is not limited thereto. Here, a specific structure and composition of the power source module **100** may be substantially inferred by referring to the

related description of FIG. 1. In the embodiment, the power source module **100** fixed to the photo sensor part **200** includes the handle **114**. The user may move the photo detector **10** by holding the handle **114**. Therefore, the photo detector **10** has a design that is easy to carry and move, thereby improving the convenience of use.

(23) In some embodiments, the power source module **100** may be fixed to the photo sensor part **200** in such a way that the connecting edge **E100** of the power source module **100** is adjacent to one of a plurality of edges of the photo sensor part **200**, such as a connecting edge **E200**, but the disclosure is not limited thereto. In some embodiments, a length of the connecting edge **E100** may be approximately equal to, but not limited to, the connecting edge **E200**. In some embodiments, the length of the connecting edge **E100** may be different from that of the connecting edge **E200**. In some embodiments, the connecting edge **E100** may be substantially parallel to the connecting edge **E200**, but the disclosure is not limited thereto. In other embodiments (not shown), the connecting edge **E100** and the connecting edge **E200** may have curved edges or other shaped edges. In other embodiments (not shown), the shapes of the connecting edge **E100** and the connecting edge **E200** may be substantially complementary in design. The connection edge **E100** of the power source module **100** and the connection edge **E200** of the photo sensor part **200** may be closely adjacent to each other.

(24) The photo sensor part **200** includes a plurality of photo sensor units **210**. The plurality of photo sensor units **210** may be arranged in an array or in other manners. The photo sensor units **210** may be used to receive electromagnetic waves of a specific wavelength, and the photo sensor part **200** may obtain a corresponding sensing image according to an intensity and a distribution of the received electromagnetic waves. In some embodiments, the photo sensor units **210** may be used for receiving X-rays, and the photo detector **10** may be used in a field of X-ray image sensing, but the disclosure is not limited thereto. In some embodiments, the photo sensor part **200** may be used together with an X-ray light source to realize X-ray image sensing.

(25) The photo sensor part **200** further includes an electrical storage unit **220**, and the electrical storage unit **220** is electrically connected to the power source module **100** to receive a power source. The power stored in the electrical storage unit **220** may be supplied to the photo sensor unit **210** to perform sensing. Therefore, the photo sensor part **200** may perform photo detection without being directly connected to an external power source. In other words, the photo sensor part **200** is a portable photo sensor part. In some embodiments, the photo sensor part **200** may be applied in a medical imaging field to provide instant and convenient image sensing operations, but the disclosure is not limited thereto. For example, in an outdoor environment without an external power supply, the photo sensor part **200** may still capture required medical images to provide real-time detection.

(26) In some embodiments, the photo sensor part **200** further includes a second connecting member **230**. The second connecting member **230** is suitable for docking with the first connecting member **150** on the power source module **100** to form a connector **300**. Specifically, the photo detector **10** further includes the connector **300**, and the photo sensor part **200** may be electrically connected to the power source module **100** through the connector **300**. In some embodiments, the second connecting member **230** may be electrically connected to the electrical storage unit **220**, and the photo sensor part **200** may receive the power source provided by the battery **120** in the power source module **100** via the connector **300**. In some embodiments, the connector **300** may be used to transmit a power level signal of the electrical storage unit **220** of the photo sensor part **200** to the power source module **100**, and the power level of the photo sensor part **200** may be displayed on the display unit **160** of the power source module **100**, but the disclosure is not limited thereto.

(27) In some embodiments, the second connecting member **230** may be disposed adjacent to the connecting edge **E200** of the photo sensor part **200**, and the second connecting member **230** may have a design corresponding to the first connecting member **150**. In some embodiments, the method for fixing the power source module **100** to the photo sensor part **200** is, for example, to

connect the first connecting member **150** with the second connecting member **230**. The second connecting member **230** may have a magnetic attraction property to attract the first connecting member **150**. For example, the second connecting member **230** may have a magnetic attraction material, and the magnetic attraction material may be exposed at the connecting edge **E200** to attract the magnetic attraction material of the first connecting member **150** to each other.

(28) In some embodiments, the second connecting member **230** may have electrical transmission properties and may be electrically connected to the electrical storage unit **220**. In some embodiments, when the power source module **100** is fixed on the light detection component **200**, the second connecting member **230** may receive the power source provided by the power source module **100** through the first connecting member **150** and transmit the received power source to the electrical storage unit **220**. In this way, the power source module **100** may charge the photo sensor part **200** through the connector **300**. The power source module **100** may provide power source to the photo sensor part **200** so that the photo detector **10** may have a longer operating time.

(29) In FIG. 2, when the power source module **100** is fixed to the photo sensor part **200**, the first interface **130** and the second interface **140** may still be connected to other external devices to realize functions of charging the battery **120** and charging other devices.

(30) The photo detector **10** may include a detachable connection structure **400**. The detachable connection structure **400** may be disposed between the connecting edge **E100** of the power source module **100** and the connection edge **E200** of the photo sensor part **200**. In some embodiments, the detachable connection structure **400** may be formed by corresponding structures disposed on the power source module **100** and the photo sensor part **200**. The detachable connection structure **400** may stably fix the power source module **100** to the photo sensor part **200**, and may separate the power source module **100** from the photo sensor part **200** when necessary. In some embodiments, the detachable connecting structure **400** may include two parts, and the two parts may be structures mutually engaged with each other, but the disclosure is not limited thereto.

(31) FIG. 3A and FIG. 3B are schematic diagrams of a detachable connection structure according to an embodiment of the disclosure. In FIG. 3A and FIG. 3B, the power source module **100** includes a protruding structure **402**, the photo sensor part **200** includes a recessed structure **404** (for example, a card slot), and the protruding structure **402** is set in the recessed structure **404** to fix the power source module **100** on the photo sensor part **200**. In detail, a part of the protruding structure **402** may be disposed in or embedded in the recessed structure **404** to fix the power source module **100** on the photo sensor part **200**. For example, the protruding structure **402** may be moved toward an assembling direction **D** to be disposed in the recessed structure **404**, so that the power source module **100** is fixed to the photo sensor part **200**. The connecting edge **E100** of the power source module **100** and the connecting edge **E200** of the photo sensor part **200** may be close to each other or even contact each other. In addition, a movable sliding block **406** may be selectively disposed in the recessed structure **404**, so that the protruding structure **402**, the recessed structure **404** and the sliding block **406** may serve as an implementation of the detachable connection structure **400**, but the disclosure is not limited thereto.

(32) As shown in FIG. 3A, the protruding structure **402** may be protruded from the connecting edge **E100** of the power source module **100**. In some embodiments, the protruding structure **402** may be formed by a protruding portion of the casing of the power source module **100** and has the same material as the casing, but the disclosure is not limited thereto. In some embodiments, the material of the protruding structure **402** may be different from the material of the casing **110**. In some embodiments, the protruding structure **402** may be attached to the casing **110** of the power source module **100** by adhering, locking or other bonding manners. In some embodiments, the casing **110** of the power source module **100** may be provided with an accommodating groove, and the protruding structure **402** may be disposed in the accommodating groove or removed from the accommodating groove according to requirements. When the protruding structure **402** is disposed in the accommodating groove, the protruding structure **402**, for example, does not protrude from

the connecting edge E100, but the disclosure is not limited thereto. As shown in FIG. 3A, when required, the protruding structure 402 may remove out of the accommodating groove to protrude from the connecting edge E100, but the disclosure is not limited thereto. In some embodiments, the protruding structure 402 may be pivoted on the casing of the power source module 100, but the disclosure is not limited thereto. The protruding structure 402 may have an extension portion 402A close to the power source module 100 and/or a hook portion 402B away from the power source module 100. An extending direction of the extension portion 402A may substantially conform to the assembling direction D, and the hook portion 402B is, for example, located at an end of the extension portion 402A. In some embodiments, the protruding structure 402, for example, protrudes out of the connecting edge E100 along the assembling direction D. In some embodiments, in a direction perpendicular to the assembling direction D, a width WA of the extension portion 402A may be, for example, smaller than a width WB of the hook portion 402B to form an L-shaped appearance, but the disclosure is not limited thereto. In other embodiments (not shown), the protruding structure 402, for example, has other shapes, such as T-shape, J-shape or other suitable shapes.

(33) The recessed structure 404 disposed in the photo sensor part 200 may include a first portion 404A (for example, an entrance portion) and a second portion 404B (for example, an accommodating portion). In some embodiments, in the direction perpendicular to the assembling direction D, a width WC of the first portion 404A is, for example, less than or equal to a width WD of the second portion 404B, but the disclosure is not limited thereto. In some embodiments, the width WC of the first portion 404A may be greater than or equal to the width WB of the hook portion 402B of the protruding structure 402, but the disclosure is not limited thereto. Therefore, when the protruding structure 402 moves toward the assembling direction D, the recessed structure 404 may have a sufficient width to accommodate the protruding structure 402. In addition, the width WD of the second portion 404B of the recessed structure 404 may, for example, accommodate the hook portion 402B and/or the sliding block 406 of the protruding structure 402.

(34) In some embodiments, the sliding block 406 accommodated in the recessed structure 404 may have a protruding portion 406A and a base portion 406B. A width WE of the protruding portion 406A may be greater than a width WF of the base portion 406B, so that the sliding block 406 has a substantially complementary contour relative to that of the hook portion 402B of the protruding structure 402, but the disclosure is not limited thereto. The sliding block 406 may be moved in a direction S to change a position. In FIG. 3A, the protruding structure 402 has not been disposed in the groove structure 404, and the sliding block 406 is now, for example, at a position away from the first portion 404A, but the disclosure is not limited thereto. In FIG. 3B, the protrusion structure 402 may be disposed in the groove structure 404. At this time, the sliding block 406 may be moved to a position closer to the first portion 404A, and the protruding portion 406A of the sliding block 406 may, for example, abut against the hook portion 402B of the protruding structure 402, thereby fixing the power source module 100 to the photo sensor part 200, but the disclosure is not limited thereto. In some embodiments, the sliding block 406 may be slid from the position shown in FIG. 3B to the position shown in FIG. 3A, and the protruding structure 402 may be removed from the groove structure 404 to remove the power source module 100, so that the power source module 100 is separated from the photo sensor part 200.

(35) FIG. 4 is a schematic diagram of a photo detector according to an embodiment of the disclosure. In FIG. 4, the photo detector 20 includes the power source module 100 and a photo sensor part 200', where the power source module 100 is detachably fixed to the photo sensor part 200'. The power source module 100 includes the handle 114, the battery 120, the first interface 130, the second interface 140, the first connecting member 150 and/or the display unit 160. Here, the power source module 100 is substantially the same as the power source module 100 in the aforementioned embodiment, so that the description of the power source module 100 in the aforementioned embodiment may be applied and integrated in the embodiment. In some

embodiments, the photo sensor part **200'** may include a photo sensor panel **202** and a fixing frame **204**. The photo sensor panel **202** may include a plurality of photo sensor units **210** and/or an electrical storage unit **220**, and description of these components may refer to the corresponding components of the photo sensor part **200** in the aforementioned embodiment. In other words, a difference between the embodiment and the previous embodiment is that the photo sensor part **200'** additionally includes the fixing frame **204**, and the second connecting member **230** may be disposed on the fixing frame **204**, but the disclosure is not limited thereto. Therefore, the same reference numerals in the embodiment as in the previous embodiment denote the same construction, and the two embodiments may refer to each other's descriptions to understand the characteristics of the individual components.

(36) In the embodiment, the fixing frame **204** may be, for example, disposed on at least one side of the photo sensor panel **202**. For example, as shown in FIG. 4, the fixing frame **204** may be disposed on all sides of the photo sensor panel **202**, the fixing frame **204**, for example, surrounds the photo sensor panel **202** to package or protect the photo sensor panel **202**. One of a plurality of edges of the fixing frame **204** may be used as a connecting edge **E200'** of the photo sensor part **200'**. The second connecting member **230** may be disposed on the fixing frame **204** and disposed adjacent to the connecting edge **E200'**. In some embodiments, after the power source module **100** is fixed to the photo sensor part **200**, the connecting edge **E100** of the power source module **100** may be, for example, close to the connecting edge **E200'** of the photo sensor part **200'**, so that the first connecting member **150** is connected to the second connecting member **230** to constitute the connector **300** that is electrically connected between the photo sensor part **200'** and the power source module **100**.

(37) In some embodiments, the second connecting member **230** may be electrically connected to the electrical storage unit **220** of the photo sensor panel **202**. In this way, the photo sensor part **200'** may receive the power source provided by the battery **120** in the power source module **100** through the connector **300**. In addition, the connector **300** may be selectively used to transmit a power level signal of the photo sensor part **200'** to the power source module **100**, and the power level of the photo sensor part **200'** may be displayed on the display unit **160** of the battery module **100**. In some embodiments, the photo sensor part **200'** may have an arc edge.

(38) FIG. 5 is a schematic block diagram of some components of a power source module according to an embodiment of the disclosure. In FIG. 5, a power source module **500** may include a display unit **502**, a microcontroller (MCU) **504**, an analog-to-digital converter (ADC) **506** and/or a battery **508**, but the disclosure is not limited thereto. In some embodiments, the display unit **502** is electrically connected to the battery **508**, and the display unit **502** is used to display a power level of the battery **508**. In some embodiments, the display unit **502** may be electrically connected to the MCU **504**. The MCU **504** may be connected to the ADC **506**, and the ADC **506** may be connected to the battery **508**. In other words, the ADC **506** is electrically connected between the battery **508** and the MCU **504**. In some embodiments, a power level signal of the battery **508** may be converted by the ADC **506** and then transmitted to the MCU **504**, and the MCU **504** may transmit instructions to the display unit **502**, so that the display unit **502** displays the power level signal received by the MCU **504**, but the disclosure is not limited thereto. In this way, the power source module **500** may not only store electric energy, but may also display an amount of electric power, so that the user may learn a state of the power source module **500** to determine a timing of charging.

(39) In some embodiments, the power source module **500** may be applied to the aforementioned power source module **100**. For example, the display unit **502** may be implemented by the display unit **160** in the aforementioned embodiment. In addition, the battery **508** in the power source module **500** may be the battery **120** in the aforementioned embodiments. In other embodiments, since the power source module **100** of the aforementioned embodiment may be fixed to and electrically connected to the photo sensor part **200** or **200'**, the design of applying the power source module **500** may be also to read the power level of the electrical storage unit **220** in the photo

sensor part **200** or **200'** for displaying in the display unit **502**. For example, the ADC **506** may be electrically connected to the electrical storage unit **220** through the connector **300** of the aforementioned embodiment, so as to receive the power level signal of the electrical storage unit **220**, and convert the power level signal of the electrical storage unit **220** and transmit it to the MCU **504**, but the disclosure is not limited thereto. The MCU **504** may provide power level information of the electrical storage unit **220** to the display unit **502**, and the display unit **502** displays the power level information. In some embodiments, the display unit **502** may have different display areas, where one display area may be used to display the power level of the battery **120** of the power source module **100**, and another display area may be used to display a power level of the electrical storage unit **220** of the photo sensor part **200** or the photo sensor part **200'**, but the disclosure is not limited thereto. Therefore, when the design of the power source module **500** is applied to the power source module **100** of the photo detector **10** or the photo detector **20**, the power level of the battery **120** of the power source module **100** and/or the power level of the power storage unit **220** of the photo sensor part **200** or **200'** may be directly read on the display unit **160** of the power source module **100**.

(40) FIG. **6** is a schematic block diagram of some components of a power source module according to an embodiment of the disclosure. In FIG. **6**, a power source module **600** may include a display unit **602**, a controller **604** (for example, an MCU), and a battery **606**, but the disclosure is not limited thereto. The display unit **602** may be electrically connected to the MCU **604**. The MCU **604** may be connected between the battery **606** and the display unit **602**. In some embodiments, the MCU **604** may be connected to the battery **606** through an Inter-Integrated Circuit (PC) **608**. In some embodiments, the MCU **604** may transmit an instruction to the display unit **602** to display a power level signal received by the MCU **604** via the display unit **602**. In this way, the power source module **600** may not only store electric energy, but may further display the amount of electric power, so that the user may learn the state of the power source module **600** to determine a timing of charging.

(41) Similar to the power source module **500**, the power source module **600** may be applied to the aforementioned power source module **100**. For example, the display unit **602** may be implemented by the display unit **160** in the aforementioned embodiment. In addition, the battery **606** in the power source module **600** may be the battery **120** in the aforementioned embodiment. In other embodiments, since the power source module **100** of the aforementioned embodiment may be fixed to and electrically connected to the photo sensor part **200** or the photo sensor part **200'**, the design of the power source module **600** may also read the power level of the electrical storage unit **220** in the photo sensor part **200** or the photo sensor part **200'**, and display the same via the display unit **602**. For example, the MCU **604** may be electrically connected to the electrical storage unit **220** through the PC **608** and the connector **300** of the aforementioned embodiment, so as to receive the power level signal of the electrical storage unit **220** and provide the power level signal of the electrical storage unit **220** to the display unit **602**, and the display unit **602** displays the power level signal of the electrical storage unit **220**. In some embodiments, the display unit **602** may have different display areas, where one display area may be used to display the power level of the battery **120** of the power source module **100**, and another display area may be used to display a power level of the electrical storage unit **220** of the photo sensor part **200** or the photo sensor part **200'**, but the disclosure is not limited thereto. Therefore, when the design of the power source module **600** is applied to the power source module **100** of the photo detector **10** or the photo detector **20**, the power level of the battery **120** of the power source module **100** and/or the power level of the power storage unit **220** of the photo sensor part **200** or **200'** may be directly read on the display unit **160** of the power source module **100**.

(42) In summary, the photo detector of the disclosure includes the power source module and the photo sensor part. The photo sensor part is a portable device, so that the power source module may be used to charge the photo sensor part to prolong an operating time of the photo sensor part. In

some embodiments, the power source module fixed on the photo sensor part may be detached without limiting the use of the photo sensor part. In addition, the power source module may charge other external devices besides the photo sensor part to provide multiple charging functions. In some embodiments, the display unit disposed on the power source module may display the power level of the power source module itself as well as the power level of the photo sensor part, so that the user may conveniently observe the power level of the photo detector. In some embodiments, the battery module has the handle, so that the photo detector is easy to carry and move.

Claims

1. A photo detector, comprising: a photo sensor part; and a power source part, fixed on the photo sensor part, and electrically connected to the photo sensor part, wherein the power source part comprises a casing detachably fixed to the photo sensor part, the casing has at least one opening, and a part of the casing surrounding the opening forms a handle.
2. The photo detector according to claim 1, wherein the power source part comprises a battery and one or more interface, the one or more interface is electrically connected to the battery.
3. The photo detector according to claim 2, wherein at least one of the one or more interface is a USB interface.
4. The photo detector according to claim 1, further comprising a connector, wherein the photo sensor part is electrically connected to the power source part through the connector.
5. The photo detector according to claim 1, wherein the power source part comprises a protruding structure, the photo sensor part comprises a concave structure, and the protruding structure is disposed in the concave structure so that the power source part is fixed on the photo sensor part.
6. The photo detector according to claim 1, wherein the power source part comprises a battery and a display unit, the display unit is electrically connected to the battery, and the display unit is used for displaying a power level of the battery.
7. The photo detector according to claim 6, wherein the power source part further comprises a controller electrically connected between the battery and the display unit.
8. The photo detector according to claim 7, wherein the power source part comprises an analog-to-digital signal converter electrically connected between the battery and the controller.
9. The photo detector according to claim 1, wherein the photo sensor part comprises an electrical storage unit, and the electrical storage unit is electrically connected to the power source part to receive a power source.
10. The photo detector according to claim 1, wherein the power source part comprises a battery and a first interface, the first interface is electrically connected to the battery, and the first interface is disposed on a side surface of the casing.
11. The photo detector according to claim 10, wherein the power source part further comprises a second interface, and the first interface and the second interface are disposed on two opposite side surfaces of the casing.
12. The photo detector according to claim 1, wherein the casing has a connecting edge, and the connecting edge is adjacent to one of edges of the photo sensor part.
13. The photo detector according to claim 1, wherein a battery is covered by the casing.
14. The photo detector according to claim 1, wherein the photo sensor part comprises a plurality of photo sensor units arranged in an array.
15. The photo detector according to claim 14, wherein the photo sensor units are used for receiving X-rays.
16. The photo detector according to claim 1, wherein the power source part further comprises a first connecting member, the photo sensor part comprises a second connecting member, and the second connecting member is suitable for docking with the first connecting member.
17. The photo detector according to claim 16, wherein the second connecting member has a

magnetic attraction material.

18. The photo detector according to claim 16, wherein the photo sensor part comprises a photo sensor panel and a fixing frame, the fixing frame surrounds the photo sensor panel, and the second connecting member is disposed on the fixing frame.
