

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403778
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Nakamura; Nobuo et al.

Tractor and vehicle equipped with tractor

Abstract

A tractor that includes: a driver equipped with a left and right pair of driving wheels; a vehicle main body provided between the left and right pair of driving wheels; a periphery information detection sensor provided at the vehicle main body and detecting periphery information; a controller provided in the vehicle main body and controlling autonomous traveling by the driver in accordance with the periphery information detected by the periphery information detection sensor; and a first coupler provided at the vehicle main body and configured to be coupled to a trailer.

Inventors:	Nakamura; Nobuo (Nagoya, JP), Kobayashi; Hiroyuki (Mitaka, JP)
Applicant:	TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)
Family ID:	85797698
Assignee:	TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)
Appl. No.:	17/897653
Filed:	August 29, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230112240 A1	Apr. 13, 2023

Foreign Application Priority Data

JP	2021-166467	Oct. 08, 2021
----	-------------	---------------

Publication Classification

Int. Cl.: B60L50/70 (20190101); B60W60/00 (20200101); B62D53/02 (20060101)

U.S. Cl.:

CPC **B60L50/70** (20190201); **B60W60/001** (20200201); **B62D53/02** (20130101);

Field of Classification Search

CPC: B62D (53/02); B62D (53/04); B60L (50/70); B60L (50/71); B60L (50/72); B60L (50/75);
 B60K (2015/03315)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6722460	12/2003	Yang	180/65.245	B62M 7/12
7252166	12/2006	Kubusch	180/65.1	B60K 15/03
9829882	12/2016	MacGregor	N/A	B62D 61/00
10538190	12/2019	Metellus	N/A	B60F 5/02
11597454	12/2022	Kaneko	N/A	B60P 3/40
11707955	12/2022	Smith	701/28	B60D 1/62
2012/0193154	12/2011	Wellborn	180/14.2	B60W 10/20
2015/0367885	12/2014	Bruns	280/408	B62D 5/0421
2019/0033856	12/2018	Ferguson	N/A	G06K 19/0723
2019/0210479	12/2018	Bachmann	N/A	B60L 15/38
2019/0232849	12/2018	Kaneko	N/A	B60P 1/003
2019/0315236	12/2018	Mere	N/A	H02J 7/342
2019/0318306	12/2018	Mere	N/A	G06V 20/56
2022/0118977	12/2021	Shimbo et al.	N/A	N/A
2022/0402354	12/2021	Wang	N/A	H01M 50/249
2022/0410701	12/2021	Mei	N/A	B60K 15/07
2023/0115169	12/2022	Mei	280/830	B60K 15/063
2024/0149961	12/2023	Stout	N/A	B60R 1/26
2024/0278607	12/2023	Rayner	N/A	B60D 1/665
2024/0286647	12/2023	Nakamura	N/A	B60L 50/60
2024/0359554	12/2023	Hornback	N/A	B60K 15/067
2024/0408977	12/2023	Yhr	N/A	B60L 53/57

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
113246751	12/2020	CN	B60K 15/07
2020-125090	12/2019	JP	N/A

OTHER PUBLICATIONS

Translation of CN-113246751-A (Year: 2021). cited by examiner

Primary Examiner: Ebner; Katy M

Attorney, Agent or Firm: Dinsmore & Shohl LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application is based on and claims priority under 35 USC 119 from Japanese Patent Application No. 2021-166467 filed on Oct. 8, 2021, the disclosure of which is incorporated by reference herein.

BACKGROUND

Technical Field

(2) The present disclosure relates to a tractor and to a vehicle equipped with a tractor.

Related Art

(3) Japanese Patent Application Laid-Open (JP-A) No. 2020-125090 discloses a towing vehicle (a tractor) that is equipped with autonomous driving functions.

(4) The related technology mentioned above has scope for improvement in regard to a tractor that tows a trailer by autonomous running becoming more compact.

SUMMARY

(5) An aspect of the present disclosure is a tractor that includes: a driver equipped with a left and right pair of driving wheels; a vehicle main body provided between the left and right pair of driving wheels; a periphery information detection sensor provided at the vehicle main body and detecting periphery information; a controller provided in the vehicle main body and controlling autonomous traveling by the driver in accordance with the periphery information detected by the periphery information detection sensor; and a first coupler provided at the vehicle main body and configured to be coupled to a trailer.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a perspective view, seen from a diagonal forward side, showing an exemplary tractor according to a first exemplary embodiment of the present disclosure and a trailer to be towed by the tractor, in a state in which the tractor and trailer are uncoupled.

(2) FIG. 2 is a perspective view, seen from a diagonal rearward side, showing the exemplary tractor in FIG. 1.

(3) FIG. 3A is a block diagram showing some of exemplary hardware structures of the tractor in FIG. 1.

(4) FIG. 3B is a block diagram showing an example of functional structures of a control device in FIG. 3A.

(5) FIG. 4 is a perspective view, seen from the diagonal forward side, showing a vehicle in which the exemplary tractor and trailer in FIG. 1 are coupled.

(6) FIG. 5 is a side view, seen from sideward from the left side, showing the exemplary vehicle in FIG. 4.

(7) FIG. 6 is a simplified side sectional diagram showing a state in which a protrusion portion at a lower front face side of the exemplary trailer shown in FIG. 1 is inserted into a recess portion at a rear face side of a vehicle main body of the exemplary tractor shown in FIG. 2.

(8) FIG. 7 is a perspective view, seen from the diagonal forward side, showing an exemplary tractor according to a second exemplary embodiment of the present disclosure and a trailer to be towed by the tractor, in a state in which the tractor and trailer are uncoupled.

DETAILED DESCRIPTION

First Exemplary Embodiment

(9) A tractor according to a first exemplary embodiment of the present disclosure and a vehicle that is equipped with the tractor are described using FIG. 1 to FIG. 6. An arrow FR that is shown as appropriate in these drawings indicates a vehicle front side, an arrow UP indicates a vehicle upper side, and an arrow W indicates a vehicle width direction.

(10) FIG. 1 is a perspective view, seen from a diagonal forward side, showing a tractor 20 according to the first exemplary embodiment and a trailer 50 to be towed by the tractor 20, in a state in which the tractor 20 and trailer 50 are uncoupled. FIG. 2 is a perspective view, seen from a diagonal rearward side, showing the tractor 20. The tractor 20 according to the present exemplary embodiment may be given predetermined operation commands from, for example, a portable device 100 of a user P shown in FIG. 1 or the like. The portable device 100, includes, for example, a liquid crystal display equipped with a touch panel that enables touch operations by the user P. The tractor 20 is capable of, for example wireless communications with a server via a network.

(11) As shown in FIG. 1 and FIG. 2, the tractor 20 is equipped with a left and right pair of driving wheels 26. The left and right pair of driving wheels 26 constitute portions of a driver 22 for causing autonomous running of the tractor 20. A vehicle main body 28 is provided between the left and right pair of driving wheels 26. Fender portions 27 that cover peripheries of the driving wheels 26 are formed continuously from both vehicle width direction sides of the vehicle main body 28. As shown in FIG. 1, vicinity information detection sensors 32 that detect vicinity information are provided at the vehicle main body 28.

(12) FIG. 3A shows some of hardware structures of the tractor 20 in a block diagram. The tractor 20 includes a battery. As shown in FIG. 3A, the tractor 20 includes the driver 22, a control device 30, the vicinity information detection sensors 32, a global positioning system (GPS) device 34, vehicle state sensors 36 and a coupler 40.

(13) The control device 30 is provided in the vehicle main body 28 (see FIG. 1) and includes a central processing unit (CPU, or processor) 30A, which is an example of a hardware processor, read-only memory (ROM) 30B, which is an example of memory, random access memory (RAM) 30C, storage 30D, a communications interface 30E (“communications I/F” in FIG. 3A) and an input/output interface 30F (“input/output I/F” in FIG. 3A). The CPU 30A, ROM 30B, RAM 30C, storage 30D, communications interface 30E and input/output interface 30F are connected with one another to be capable of communications via a bus 30Z.

(14) The CPU 30A is a central arithmetic processing unit that executes various programs and controls respective parts. That is, the CPU 30A reads a program from the ROM 30B or storage 30D and executes the program, using the RAM 30C as a work area. The CPU 30A performs control of the structures described above and various kinds of computational processing in accordance with programs recorded in the ROM 30B or storage 30D.

(15) The ROM 30B stores various programs and various kinds of data. The RAM 30C serves as a work area and temporarily memorizes programs and data. The storage 30D is constituted with a memory device such as a hard disk drive (HDD), a solid state drive (SSD) or the like. The storage 30D stores various programs and various kinds of data. In the present exemplary embodiment, an autonomous driving control program for controlling autonomous running of the driver 22 in accordance with vicinity information detected by the vicinity information detection sensors 32 is stored in the ROM 30B or storage 30D. Map information and the like is memorized in the storage 30D. The communications interface 30E is an interface for the control device 30 to communicate with other equipment.

(16) The input/output interface 30F is an interface for communicating with various devices mounted at the tractor 20. Via the input/output interface 30F, the control device 30 according to the present exemplary embodiment is connected with, for example, a control unit 23 of the driver 22, the vicinity information detection sensors 32, the GPS device 34, the vehicle state sensors 36, and a release actuator 42 of the coupler 40.

(17) The driver 22 includes the control unit 23, a motor 24, a steering device 25 and the driving wheels 26 (see FIG. 1 and the like). The control unit 23 is a device that controls the motor 24 and the steering device 25 in response to command signals from the control device 30. The motor 24 transmits driving force to the driving wheels 26. The steering device 25 changes a steering angle of the driving wheels 26.

(18) The tractor **20** according to the present exemplary embodiment runs by operation of the driver **22**, and autonomous running of the tractor **20** is controlled by the control device **30**. That is, as a functional structure, the control device **30** includes a controller **301** shown in FIG. 3B. The controller **301** controls autonomous running of the driver **22** in accordance with vicinity information detected by the vicinity information detection sensors **32**. This functional structure is realized by the CPU **30A** shown in FIG. 3A loading and executing the autonomous driving control program memorized at the ROM **30B** or storage **30D**.

(19) The vicinity information detection sensors **32** are a sensor group for gathering information about the surroundings of the tractor **20**. The vicinity information detection sensors **32** include, for example, a camera that images vicinity information of the tractor **20**. The vicinity information detection sensors **32** may also include at least one of, for example, a millimeter wave radar that transmits scanning waves in a predetermined range and receives reflected waves and a lidar (laser imaging detection and ranging) that scans a predetermined range.

(20) The GPS device **34** is a device that measures a current position of the tractor **20**. The GPS device **34** includes an antenna that receives signals from GPS satellites. The vehicle state sensors **36** acquire information representing running states and operation states of the tractor **20**. The vehicle state sensors **36** include, for example, a steering sensor that detects steering angles of the tractor **20** and a speed sensor that detects running speeds of the tractor **20**.

(21) As shown in FIG. 2, the coupler **40** is provided at a rear portion of the vehicle main body **28** of the tractor **20**. The coupler **40** serves as a first coupler that can be coupled with the trailer **50**. The coupler **40** is provided with a coupler main body **40A**, a knuckle **40B** and a locking pin **40C**. In plan view, the coupler main body **40A** is formed in a substantial “U” shape that opens to a vehicle outer side. The knuckle **40B** is provided at a protruding side of the coupler **40** at one of left or right. The knuckle **40B** is attached to be turnable about a knuckle pin **40P** that is in the vehicle vertical direction. The locking pin **40C** is connected to a lock that locks the knuckle **40B** in a closed state. The basic structure of the coupler **40** is similar to widely known railway couplers in, for example, Japanese Patent No. 5,837,668 and the like. Accordingly, the basic structure of the coupler **40** is not described in detail here.

(22) A coupler **52** with a similar structure to the coupler **40** (see FIG. 2) is provided at a lower front face side of the trailer **50** shown in FIG. 1. That is, the coupler **52** is equipped with a coupler main body **52A**, a knuckle **52B** and a locking pin **52C** (which are shown simplified in the drawings). The coupler **52** constitutes a second coupler that can be coupled to the coupler **40** (see FIG. 2). When the tractor **20** and the trailer **50** are to be coupled, the couplers **40** and **52** are aligned with one another and pushed together in a state in which the knuckle **52B** and the knuckle **40B** shown in FIG. 2 are in respective open states. Accordingly, the knuckles **40B** and **52B** turn in closing directions thereof and the couplers **40** and **52** are automatically coupled with one another.

(23) As an example, the coupler **40** is in a condition in which most of the coupler main body **40A** is accommodated in a recess portion **28A** formed in the vehicle main body **28**. Similarly, the coupler **52** shown in FIG. 1 is in a condition in which most of the coupler main body **52A** is accommodated in a recess portion **54A** formed in the trailer **50**.

(24) The lock of the locking pin **40C** shown in FIG. 2 may be displaced to a lock release position by the release actuator **42** illustrated in FIG. 3A. To add to this description, when a command to open the knuckle **40B** of the coupler **40** is transmitted from the portable device **100** of the user P shown in FIG. 1 and the communications interface **30E** shown in FIG. 3A receives this command, the control device **30** is configured to give an operation command to the release actuator **42**, and the release actuator **42** operates.

(25) The lock of the locking pin **52C** shown in FIG. 1 may be displaced to a lock release position by a release actuator provided at the trailer **50**. The release actuator provided at the trailer **50** is configured to be operated by, for example, a command inputted from a user interface provided at the trailer **50**.

- (26) As shown in FIG. 1, the trailer **50** is equipped with a power supply connector **62**. A power supplier **60** (see FIG. 5) that includes the power supply connector **62** is described below. The trailer **50** is equipped with a protrusion portion **54B** that protrudes to the vehicle front side, at the upper side of the coupler **52** at the lower front face side. The power supply connector **62** is provided at a front end portion of the protrusion portion **54B**.
- (27) As shown in FIG. 2, a recess portion **28B** that is recessed to the vehicle front side is formed at the upper side of the coupler **40**, at an upper portion of the rear face side of the vehicle main body **28** of the tractor **20**. A power receiving connector **44** is provided at a recess floor side of the recess portion **28B**. In a state shown in FIG. 4 and FIG. 5 in which the tractor **20** is coupled to the trailer **50**, the protrusion portion **54B** of the trailer **50** (see FIG. 1) is inserted into the recess portion **28B** of the tractor **20** (see FIG. 2). FIG. 6 shows the state in which the protrusion portion **54B** of the trailer **50** is inserted into the recess portion **28B** of the tractor **20**, in a simplified side sectional diagram.
- (28) As shown in FIG. 6, in the state in which the tractor **20** is coupled to the trailer **50**, the power receiving connector **44** is connected with the power supply connector **62**. Thus, the driver **22** is capable of using electric power supplied from the power supplier **60** via the power receiving connector **44** for running.
- (29) As shown in FIG. 4 and FIG. 5, the trailer **50** includes an accommodation space former **50R** that forms an accommodation space at the rear side of a vehicle front portion **50F**. An outer profile portion **50F1** that forms an outer profile of the vehicle front portion **50F** extends in the vehicle vertical direction. As shown in FIG. 1, both of vehicle width direction end portions of a front side lower portion of the outer profile portion **50F1** of the vehicle front portion **50F** are angled to the vehicle rear side towards the vehicle lower side, and the front face side of the front side lower portion is recessed toward the vehicle rear side relative to the two vehicle width direction end portions.
- (30) As shown in FIG. 4 and FIG. 5, the accommodation space former **50R** is provided continuously to the rear side of the vehicle front portion **50F** and, together with the outer profile portion **50F1** of the vehicle front portion **50F**, forms a frame shape in side view and forms an accommodation space therein. To add to this description, the accommodation space former **50R** is provided with a roof portion **50R1**, a floor portion **50R2** and a rear wall portion **50R3**. The roof portion **50R1** extends to the vehicle rear side from an upper end portion of the outer profile portion **50F1** of the vehicle front portion **50F**. The floor portion **50R2** extends to the vehicle rear side from a lower end portion of the outer profile portion **50F1** of the vehicle front portion **50F**. The rear wall portion **50R3** links a rear end portion of the roof portion **50R1** with a rear end portion of the floor portion **50R2** in the vehicle vertical direction. A load **110** may be placed in the accommodation space former **50R**, on the floor portion **50R2**. A left and right pair of wheels **50W** are provided at the lower side of a rear portion of the floor portion **50R2**.
- (31) As shown in FIG. 5, tank storage portions **56** are formed in the vehicle front portion **50F** at the upper side of the coupler **52**. The tank storage portions **56** are capable of storing a plural number (for example, three) of hydrogen tanks **70** in a vertical array. Each tank storage portion **56** extends in the vehicle front-and-rear direction, and an insertion aperture **56A** is provided at the front end of the tank storage portion **56** (see FIG. 4). Each hydrogen tank **70** is provided with a tank main body **70A** in a cylindrical container shape. A handle **70B**, shown in FIG. 4, is formed at one end portion of a length direction of the tank main body **70A**. The handle **70B** is held by a user when the user is inserting the hydrogen tank **70** through the insertion aperture **56A** into the tank storage portion **56** and the like.
- (32) In the present exemplary embodiment, the hydrogen tank **70** is structured to be lockable. For example, the handle **70B** of the hydrogen tank **70** is gripped by a user and, in a state in which a spanning direction of the handle **70B** is in a vertical direction, the hydrogen tank **70** is inserted deep into the tank storage portion **56**. Then, when the hydrogen tank **70** is turned 90° about the axis

thereof in the vehicle front-and-rear direction such that the spanning direction of the handle **70B** becomes a horizontal direction (the direction shown in FIG. **4**), the hydrogen tank **70** is locked.

(33) As shown in FIG. **5**, a fuel cell **58** is provided in the vehicle front portion **50F** at the vehicle rear side of the tank storage portions **56**. The fuel cell **58** is connected with the hydrogen tanks **70** and an air compressor. The fuel cell **58** receives a supply of hydrogen from the hydrogen tanks **70** stored in the tank storage portions **56**, receives a supply of compressed air containing oxygen from the air compressor, and generates electricity.

(34) The power supplier **60** (depicted as a block in the drawings) is mounted in the vehicle front portion **50F** at the lower side of the fuel cell **58**. The power supplier **60** supplies electric power from the fuel cell **58** through the power supply connector **62** shown in FIG. **6** to the tractor **20** via the power receiving connector **44**.

Operation and Effects

(35) Now, operation and effects of the above exemplary embodiment are described.

(36) As shown in FIG. **1** and FIG. **2**, the driver **22** of the tractor **20** according to the present exemplary embodiment is equipped with the left and right pair of driving wheels **26**, and the vehicle main body **28** is provided between the left and right pair of driving wheels **26**. The vicinity information detection sensors **32** provided at the vehicle main body **28** (see FIG. **1**) detect vicinity information. The controller **301** provided in the vehicle main body **28** (see FIG. **3B**) controls autonomous running of the driver **22** in accordance with vicinity information detected by the vicinity information detection sensors **32**. The coupler **40** provided at the vehicle main body **28** shown in FIG. **2** is coupled to the coupler **52** of the trailer **50** shown in FIG. **1**. Accordingly, the tractor **20** that tows the trailer **50** by autonomous running may be compact.

(37) The tractor **20** according to the present exemplary embodiment is employed when the trailer **50** that is to be towed is equipped with the power supplier **60** including the power supply connector **62** (see FIG. **5**). The power receiving connector **44** shown in FIG. **2** is provided at the vehicle main body **28** and is connected with the power supply connector **62**. The driver **22** is capable of using electric power supplied from the power supplier **60** (see FIG. **5**) via the power receiving connector **44** for running. Therefore, the tractor may be more compact than a structure in which an electric power source for running the driver is mounted at the tractor.

(38) As described above, according to the tractor **20** according to the present exemplary embodiment, while employing a compact structure, the tractor **20** may tow the trailer **50** by autonomous running.

(39) As described above, a vehicle **10** according to the present exemplary embodiment that is shown in FIG. **5** and the like is provided with the tractor **20** and the trailer **50**. The trailer **50** includes the coupler **52**, the tank storage portions **56**, the fuel cell **58** and the power supplier **60** at the vehicle front portion **50F**, and the trailer **50** includes the accommodation space former **50R** at the rear side of the vehicle front portion **50F**. According to this structure, electric power is generated in the vehicle front portion **50F** of the trailer **50** that is disposed closer to the tractor **20** and may be supplied to the tractor **20**, and the load **110** may be placed at the rear side of the vehicle front portion **50F** of the trailer **50**. As necessary, the tractor **20** may be uncoupled from the trailer **50** and another trailer may be towed by the tractor **20**.

Second Exemplary Embodiment

(40) Now, a second exemplary embodiment of the present disclosure is described using FIG. **7**. FIG. **7** is a perspective view, seen from the diagonal forward side, showing a tractor **80** according to the second exemplary embodiment and the trailer **50**, which is to be towed by the tractor **80**, in a state in which the tractor **80** and trailer **50** are uncoupled. As shown in FIG. **7**, the tractor **80** according to the present exemplary embodiment differs from the tractor **20** according to the first exemplary embodiment (see FIG. **1**) in that a wheel **82**, which is smaller than the driving wheels **26**, is provided at the front side in the vehicle front-and-rear direction of the vehicle main body **28**. Other structures are the same as in the first exemplary embodiment except in the respects described

below. Structural portions that are the same as in the first exemplary embodiment are assigned the same reference symbols and are not described here.

(41) As shown in FIG. 7, the wheel **82** is disposed at a vehicle width direction central portion of the front side in the vehicle front-and-rear direction of the vehicle main body **28**. The wheel **82** is turnably supported by a bracket **84**. A support portion **86** protrudes from the vehicle width direction central portion at the front side in the vehicle front-and-rear direction of the vehicle main body **28**. The bracket **84** is turnable relative to the support portion **86** about an axis in the vehicle vertical direction.

(42) According to the present exemplary embodiment, the same operation and effects as in the first exemplary embodiment described above may be provided, in addition to which running of the tractor **80** may be made more stable.

Supplementary Descriptions of the Exemplary Embodiments

(43) In the first and second exemplary embodiments described above, structures are described in which the trailer **50** shown in FIG. 1 and FIG. 7 is equipped with the power supplier **60** including the power supply connector **62** (see FIG. 5). However, structures are possible in which a trailer is not equipped with a power supplier and a tractor may be run by electric power from a power source mounted at the tractor.

(44) In the first and second exemplary embodiments described above, the coupler **40** (see FIG. 2) is employed as the first coupler and the coupler **52** is employed as the second coupler. However, alternative coupling structures including fittings and the like may be employed for the first coupler and the second coupler.

(45) In the second exemplary embodiment described above, the wheel **82** that is smaller than the driving wheels **26** is provided at the front side in the vehicle front-and-rear direction of the vehicle main body **28**. As a variant example, instead of the wheel **82**, a wheel that is smaller than the driving wheels (**26**) may be provided at the rear side in the vehicle front-and-rear direction of the vehicle main body (**28**).

(46) The exemplary embodiments described above and variant examples mentioned above may be embodied in suitable combinations.

(47) Above, illustrative examples of the present disclosure are described, but the present disclosure is not limited by these descriptions; numerous modifications beyond these descriptions may be embodied within a technical scope not departing from the gist of the disclosure.

(48) The present disclosure provides a tractor that, while employing a compact structure, may tow a trailer by autonomous running, and provides a vehicle equipped with the tractor.

(49) A first aspect of the present disclosure is a tractor that includes: a driver equipped with a left and right pair of driving wheels; a vehicle main body provided between the left and right pair of driving wheels; a periphery information detection sensor provided at the vehicle main body and detecting periphery information; a controller provided in the vehicle main body and controlling autonomous traveling by the driver in accordance with the periphery information detected by the periphery information detection sensor; and a first coupler provided at the vehicle main body and configured to be coupled to a trailer.

(50) According to the first aspect, the driver is equipped with the left and right pair of driving wheels, and the vehicle main body is provided between the left and right pair of driving wheels. The vicinity information detection sensor provided at the vehicle main body detects vicinity information. The controller provided in the vehicle main body controls autonomous driving of the driver in accordance with the vicinity information detected by the vicinity information detection sensor. The first coupler provided at the vehicle main body can be coupled to a trailer. Accordingly, a tractor that tows a trailer by autonomous running may become more compact.

(51) A second aspect of the present disclosure is the tractor of the first aspect, that further includes a power supplier including a power supply connector, wherein the vehicle main body has a power receiving connector coupled to the power supply connector, and the driver is configured to be

capable of driving by the driver using electric power supplied from the power supplier via the power receiving connector.

(52) According to the second aspect, if a trailer is equipped with the power supplier including the power supply connector, the power receiving connector that can be connected with the power supply connector is provided at the vehicle main body, and the driver is configured to be capable of using electric power supplied from the power supplier via the power receiving connector for running of the driver. Therefore, the tractor may be more compact than a structure in which an electric power source for running the driver is mounted at the tractor.

(53) A third aspect of the present disclosure is the tractor of the first aspect or the second aspect that further includes, at one of a front side or a rear side in a vehicle front-and-rear direction of the vehicle main body, a wheel that is smaller than the driving wheels.

(54) According to the third aspect, running of the tractor may be made more stable by the wheel provided at the front side or rear side in the vehicle front-and-rear direction of the vehicle main body.

(55) A fourth aspect of the present disclosure is a vehicle that includes: the tractor of the second aspect; and the trailer, the trailer including, at a vehicle front portion: a second coupler configured to be coupled to the first coupler, a plurality of tank storages at an upper side of the second coupler, the plurality of tank storages being capable of storing a plurality of hydrogen tanks in a vertical array, a fuel cell receiving a supply of hydrogen from the hydrogen tanks stored in the tank storages and generating electric power, and the power supplier, the power supplier supplying electric power from the fuel cell through the power supply connector to the tractor via the power receiving connector, wherein the trailer further includes an accommodation space former forming an accommodation space at a rear side of the vehicle front portion.

(56) According to the fourth aspect, the tractor may be compact, electric power may be generated in the vehicle front portion of the trailer, which is disposed closer to the tractor, and the electric power may be supplied to the tractor. Moreover, a load may be placed at the rear side of the vehicle front portion of the trailer. As necessary, the tractor may be uncoupled from the trailer and another trailer may be towed by the tractor.

(57) According to the present disclosure, while employing a compact structure, a tractor may tow a trailer by autonomous running.

Claims

1. A tractor comprising: a driver equipped with a left and right pair of driving wheels; a vehicle main body provided between the left and right pair of driving wheels, the vehicle main body including a recess portion providing a power receiving connector configured to be coupled to a power supply connector of a power supplier, and the driver is configured to be capable of driving by the driver using electric power supplied from the power supplier via the power receiving connector; a periphery information detection sensor provided at the vehicle main body and detecting periphery information; a controller provided in the vehicle main body and controlling autonomous traveling by the driver in accordance with the periphery information detected by the periphery information detection sensor; and a first coupler provided at the vehicle main body and configured to be coupled to a trailer, the first coupler comprising a coupler main body and a knuckle rotatably connected to the coupler main body between an open state and a closed state.
2. The tractor according to claim 1, further comprising, at one of a front side or a rear side in a vehicle front-and-rear direction of the vehicle main body, a wheel that is smaller than the driving wheels.
3. The tractor according to claim 1, wherein the tractor is a substantially circular cylinder, both end faces of which respectively correspond to each of the driving wheels.
4. A vehicle comprising: the tractor according to claim 1; and the trailer, the trailer including, at a

vehicle front portion: a second coupler configured to be coupled to the first coupler, a plurality of tank storages at an upper side of the second coupler, the plurality of tank storages being capable of storing a plurality of hydrogen tanks in a vertical array, a fuel cell receiving a supply of hydrogen from the hydrogen tanks stored in the tank storages and generating electric power, and the power supplier, the power supplier supplying electric power from the fuel cell through the power supply connector to the tractor via the power receiving connector, wherein the trailer further includes an accommodation space former forming an accommodation space at a rear side of the vehicle front portion.

5. The vehicle according to claim 4, wherein the plurality of tank storages extend in a vehicle front-and-rear direction and include insertion apertures at front ends thereof.

6. The tractor according to claim 1, wherein the coupler main body has a U-shape configuration.

7. The tractor according to claim 1, wherein the first coupler further comprises a lock pin that retains the knuckle in the closed state.

8. The vehicle according to claim 4, wherein the trailer includes a protrusion portion providing the power supply connector, the protrusion disposed within the recess portion and connecting the power supply connector with the power receiving connector.
